COUNCIL REGULATION (EEC) No 2746/77

of 5 December 1977

temporarily suspending the autonomous Common Customs Tariff duties on certain industrial products

THE COUNCIL OF THE EUROPEAN COMMUNITIES,

Having regard to the Treaty establishing the European Economic Community, and in particular Article 28 thereof,

Having regard to the draft Regulation submitted by the Commission,

Whereas production of the products referred to in this Regulation is at present inadequate or non-existent within the Community and producers are thus unable to meet the needs of user industries in the Community ;

Whereas it is in the Community's interest in certain cases to suspend the autonomous Common Customs Tariff duties only partially, particularly because of the existence of Community production, and in other cases to suspend them completely ;

Whereas, taking account of the difficulties involved in accurately assessing the development of the economic situation in the sectors concerned in the near future, these suspension measures should be taken only temporarily, by fixing their term of validity to coincide with the interests of Community production,

HAS ADOPTED THIS REGULATION :

Article 1

The autonomous Common Customs Tariff duties on the products listed in the tables annexed to this Regulation shall be suspended at the level indicated in respect of each of them.

These suspensions shall be valid :

— from 1 January to 31 March 1978 for the product listed in Table I ;

— from 1 January to 30 June 1978 for the products listed in Table II.

Article 2

This Regulation shall enter into force on 1 January 1978.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 5 December 1977.

For the Council

The President

A. HUMBLET

ANNEX

TABLE I

CCT heading No	Description	Rate of autonomous duty (%)
ex 25.19 A	Magnesium oxide, dead-burned but not fused, of a purity not less than 95 %, which may not contain : (a) more than 0·05 % by weight of boron compounds evaluated as B_2O_3 (b) more than 3·5 % by weight of calcium compounds evaluated as CaO (c) more than 1·1 % by weight of silicon compounds evaluated as SiO_2 (d) a total of more than 0·7 % by weight of aluminium compounds and iron compounds evaluated as Al_2O_3 and Fe_2O_3	0

TABLE II

CCT heading No	Description	Rate of autonomous duty (%)
ex 28.04 C III	Tellurium, in ingots	0
28.42 A VI	Lithium carbonates	3
28.46 A I b)	Sodium borates, anhydrous	0
ex 28.48 B III	Dialuminium hexamagnesium carbonate decahydroxide tetrahydrate	0
ex 29.02 B	1, 6, 7, 8, 9, 14, 15, 16, 17, 17, 18, 18-Dodecachloropentacyclo[12. 2. 1. $1^{6,9}.0^{2,13}.0^{5,10}$]octadeca-7,15-diene	0
ex 29.03 B II	2-Nitropropane	8
ex 29.08 D	*tert*-Butyl hydroperoxide, aqueous solution	0
ex 29.11 E I	4-Hydroxy-3-methoxybenzaldehyde (vanillin)	0
ex 29.15 A IV a)	Sebacic acid	0
ex 29.15 C III	Benzyl 3-hydroxy-2,2,4-trimethylpentyl phthalate	0
ex 29.16 B VI	3,5-Di-iodosalicylic acid	6
ex 29.22 D I	3,5-Dichloroaniline	0
ex 29.23 A II	Dinoprost (INN), Trometamol salt (INN)	0
ex 29.23 B II	3-Chloro-4-(4-chlorophenoxy)aniline	6
ex 29.23 D V	3,5-Diaminobenzoic acid	0
ex 29.25 B III b)	2'-Benzoyl-4'-chloro-*N*-(2-hydroxypropyl)glycinanilide	0
ex 29.30	Methyl isocyanate	5
ex 29.30	*O,O*-Bis(4-*tert*-butylphenyl)-*N*-cyclohexylphosphoramidothioate	0
ex 29.31 B	2-Methyl-2-(methylthio)propionaldehyde oxine	0
ex 29.31 B	Cyclohexanethiol	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 29.35 Q	2,3-Dihydro-2,2-dimethylbenzofuran-7-ol	0
ex 29.35 Q	Dexchlorpheniramine (INN) hydrogen maleate	0
ex 29.35 Q	Carpipramine (INN) dihydrochloride	0
ex 29.35 Q	Clotiazepam (INN)	0
ex 29.35 Q and ex 30.03 A II b)	Butorphanol (INN) and its salts	0
ex 29.35 Q	1,3,5-Triacryloylperhydro-1,3,5-triazine	0
ex 29.35 Q	*L*-Tryptophan	0
ex 29.45	Potassium *tert*-butoxide	0
ex 30.01 B	Mixture of oestrogens of equine origin	0
ex 30.01 B	Human serum	0
ex 32.08 D	Glass in the form of flakes of a length not less than 0·1 and not more than 3·5 mm and of a thickness not less than two and not more than five micrometers	0
ex 34.02	(Alkyl, C_{12}-C_{16})benzylbis(2-hydroxypropyl)ammonium chloride	0
ex 38.19 G	Catalysts consisting of copper chloride supported on aluminium oxide for the preparation of dichloroethane from ethylene, hydrochloric acid and oxygen. (a)	0
ex 38.19 G	Catalysts, in the form of granules having a diameter of not less than three and not more than 10 mm, consisting of silver supported on aluminium oxide, the silver content being not less than 16 % and not more than 19 % by weight	0
ex 38.19 U	Mixture of x-butyl-4,4'-isopropylidenediphenol and x,x'-dibutyl-4,4'-isopropylidenediphenol	0
ex 38.19 U	Mixture of 4-octyldiphenylamine and 4,4'-dioctyldiphenylamine intended for the production of polybutadiene-acrylonitrile (a)	0
ex 39.02 C VII b)	Polyvinylchloride sheeting less than 1 mm thick of a width not less than 23 and not more than 28 cm, containing not less than 30 % and not more than 40 % by weight of a plasticizer, in rolls	10
ex 39.06 B	*O*-(2-Hydroxyethyl)amylopectin hydrolysate	0
ex 48.01 F	Japanese tissue (special long-fibre paper) for the manufacture of artificial sausage casings or for wrapping man-made textile fibres (continuous) in the course of industrial processing (a)	0
ex 51.02 A II	Polyimide strip, whether or not in rolls	0
ex 81.04 G I	Electrolytic manganese of a purity of at least 99·7 %, intended for the chemical industry (a)	0
ex 81.04 K I	Titanium sponge	0
ex 84.63	Forged and roughly shaped generator and turbine shafts of a weight exceeding 150 tonnes	0
ex 85.21 A V	Digital displays consisting of a glass tube mounted on a board up to 220 mm long and 45 mm wide excluding leads. The tube contains a straight line of digits not less than four in number, each digit consisting of a number of segments containing an inert gas such as helium or argon with a metallic base coated with phosphorus salts which give off light when bombarded with electrons	0

(a) The application of this suspension will be subject to the conditions determined by the competent authorities.

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	Digital displays consisting of a printed circuit board of a size not exceeding 35 mm by 90 mm with a single line of digits, not less than three in number, comprising light-emitting diodes manufactured from gallium-based semiconductor compounds mounted thereon. Each digit comprises seven segments plus a decimal point and the line of digits has a protective cover of translucent plastic	0
ex 88.05 B	Visual display system generating images by computer intended for equipping flight simulators for civil aircraft (a)	0

(a) The application of this suspension will be subject to the conditions determined by the competent authorities.