I

(Acts whose publication is obligatory)

COUNCIL REGULATION (EEC) No 3393/89

of 16 October 1989

temporarily suspending the autonomous Common Customs Tariff duty on certain industrial products (in the microelectronics and related sectors)

THE COUNCIL OF THE EUROPEAN COMMUNITIES,

Having regard to the Treaty establishing the European Economic Community, and in particular Article 28 thereof,

Having regard to the proposal from the Commission,

Whereas production of the products referred to in this Regulation is at present inadequate or non-existent within the Community and producers are thus unable to meet the needs of user-industries in the Community;

Whereas it is in the Community's interest in certain cases to suspend the autonomous Common Customs Tariff duties only partially, particularly because of the existence of Community production, and in other cases to suspend them completely;

Whereas, taking account of the difficulties involved in accurately assessing the development of the economic situation in the sectors concerned in the near future, these suspension measures should be taken only temporarily, by fixing their period of validity by reference to the interests of Community production,

HAS ADOPTED THIS REGULATION:

Article 1

The autonomous Common Customs Tariff duties for the products listed in the Annexes shall be suspended at the level indicated in respect of each of them.

These suspensions shall apply from:

— 1 January to 31 March 1990 for the product referred to in Annex I,

— 1 January to 30 June 1990 for the products referred to in Annex II.

Article 2

This Regulation shall enter into force on 1 January 1990.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg, 16 October 1989.

For the Council

The President

M. DELEBARRE

ANNEX I

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 30	Electrically erasable, programmable read-only memories (so-called E^2PROMs), in the form of an unmounted monolithic integrated circuit (chip) with a storage capacity of 16 Kbits, used in the manufacture of microwave systems for the identification of persons and objects (a)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

ANNEX II

CN code	Description	Rate of autonomous duty (%)
ex 8471 93 50	Floppy-disk storage units for the manufacture of products falling within headings 8469 or 8471 (a)	0
ex 8471 93 60	Digital audio tape storage unit for the manufacture of products falling within headings 8469 or 8471 (a)	0
ex 8471 99 90	Optical reader for reading alphanumerical dot-matrix printing characters and converting them into electrical signals, comprising a read head containing an optical detector, an amplifier, a focusing lens and two lamps, linked by one or two flat cables to a central module of which the dimensions do not exceed 200 × 220 mm, comprising a printed circuit board on which are mounted a microprocessor, an image recognition circuit and an analog-to-digital converter	0
ex 8473 10 00	Integrated memory unit for electronic typewriters, comprising a printed circuit with two or four static read/write random-access memories each with 8 K × 8 bit capacity, electronic control components and memory back-up-batteries, contained in a cartridge fitted with connectors, of external dimensions not exceeding 11 × 40 × 90 mm, and bearing: — an identification marking consisting of or including the following combination of letters: MEMOCART or — other identification markings relating to devices complying with the abovementioned description	0
ex 8473 30 00	Ferrite magnetic heads of Winchester technology for disk file peripherals, as well as carrying arms equipped with such magnetic heads, capable of recording to a density of not less than 10 tracks per millimetre	0
ex 8473 30 00	Magnetic bubble memories with a storage capacity of not more than four megabits contained in a housing the exterior dimensions of which do not exceed 43 × 44 mm, with not more than 42 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: BDL 0133 MBM 2011 FBM 64 DA BDL 0134 MBM 2256 7110 BDN 0151 FBM 54 DB 7114-1 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8473 30 00	Component forming the arithmetic/logic element of a central processing unit, comprising not more than nine printed circuit boards, the dimensions of which do not exceed 290 × 310 mm on each of which are mounted not more than 121 ECL gate arrays or ECL random access memories (ECL-RAMs) and combinations thereof contained in a framework the dimensions of which do not exceed 611 × 501 × 596 mm which serves as a housing and interconnector for the printed circuit boards, which bear: — an identification marking consisting of or including one of the following combinations of figures and letters: CO1B 2675 E 500 CO1B 2675 H 500 CO1B 2675 H 501 CO1B 2675 H 502 CO1B 2675 H 503 CO1B 2675 H 504 or — other identification markings relating to devices complying with the abovementioned description	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8473 40 00	Thermal printer heads of thick or thin film technology consisting of a printed circuit with at least one tantalum capacitor and an electrolytic capacitor contained in a metal support with connector, printer element and heat sink, supplied with the appropriate support and transport roll	0
ex 8483 10 90	Integrally forged and roughly shaped generator and turbine shafts of a weight exceeding 215 tonnes	0
ex 8501 10 99	DC electric motor, brushless, with a torque of not more than 0,018 Nm, with coupling flange of a diameter of 35 mm and precision-made chuck of a diameter of 25 mm with internal motor, three-phase winding, rated speed of 3 600 rpm, supply voltage of 12 V ± 10 %	0
ex 8501 10 99	DC electric motor, brushless, with a torque of not more than 0,20 Nm, with coupling flange of a diameter of 74 mm, a spindle of a diameter of 40 mm, rated speed of 3 600 rpm, supply voltage of 12 V ± 10 %, with cables and connectors	0
ex 8501 10 99	DC electric motor, brushless, with a torque of not more than 0,20 Nm, with outside rotor of a maximum diameter of 55 mm, coupling flange of a diameter of 77 mm and precision-made chuck of a diameter of 44 mm, four-phase winding, rated speed of 3 600 rpm, supply voltage of 12 V ± 10 % and fitted with wires and connectors	0
ex 8501 10 99	Hybrid stepping motor with an angle of step of 1,8°, 200 steps per revolution, a four-phase rotation cycle with single-pole windings, comprising a rotor and a laminated stator enclosed between two square section flanges with sides not exceeding 42 mm and fitted with biterminate shaft and wires and connectors	0
ex 8501 10 99	Hybrid stepping motor with an angle of step of 0,9°, 400 steps per revolution, two- or four-phase rotation sequence and bipolar windings, comprising a rotor and a laminated stator enclosed between two square section flanges with sides not more than 40 mm wide and fitted with biterminate shaft, wires and connectors	0
ex 8501 10 99	Hybrid stepping motor with an angle of step of 0,9°, 400 steps per revolution, two-phase rotation sequence and bipolar windings, comprising a rotor and a stator encapsulated in a cylindrical housing with a maximum diameter of 47 mm and maximum thickness of 14 mm, fitted with a single shaft output and cables with connectors	0
ex 8501 10 99	Hybrid stepping motor with an angle of step of 0,9°, 400 steps per revolution and two-phase rotation sequence, and bipolar windings, comprising a rotor, a laminated stator enclosed between two square section flanges with sides not exceeding 40 mm, an integral 2- or 3-phase tachometer enclosed in a cap with a maximum diameter of 35 mm, and separate cables and connectors for the motor and tachometer outputs, with maximum dimensions of 40 × 40 × 62 mm, including the shaft	0
ex 8501 10 99	Hybrid stepping motor with an angle of step of 0,9°, 400 steps per revolution and two-phase rotation sequence with bipolar winding, comprising a rotor, a laminated stator enclosed between two flanges, one of square section with a side of 40 mm maximum, the other front face having a shaped profile with two projections with fixing slots, an integral two- or three-phase tachometer enclosed in a cover of diameter of 35 mm maximum, separate cables and connectors for the motor and tachometer outputs, with overall dimensions not exceeding 40 × 40 × 62 mm, including the shaft but excluding the projections of the front flange	0
ex 8501 10 99	Direct-current bipolar stepping motor with a single stator, an output of not more than 37,5 W, a rotary angle/step of 180°, two steps per rotation, a two-phase rotation cycle with single-pole winding, an output torque of not less than $0,1 \times 10^{-6}$ Nm and not more than $0,1 \times 10^{-4}$ Nm and a supply voltage of not more than 3 V	0
ex 8504 40 99	Static converter consisting of a combination of seven diodes in cascade, for output voltages of not less than 40 kV DC with a load current of not less than 3 mA	0
ex 8506 19 10	Lithium iodine single cell battery with dimensions not exceeding 45 × 9 × 23 mm and a voltage not exceeding 2,8 V	0

CN code	Description	Rate of autonomous duty (%)
ex 8506 19 10	Unit consisting of not more than two lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 28 connecting pins and incorporating a control circuit	0
ex 8506 19 90	Dry zinc/carbon batteries of a voltage of not less than 5,5 V and not more than 6,5 V and of a size not exceeding 110 × 90 × 5 mm, for incorporation in film cassettes for instant pictures (a)	0
ex 8517 90 91	Assembly for telephonic apparatus consisting of a microphone, protecting circuit and four-way connecting socket, mounted on a printed circuit, with dimensions not exceeding 22 × 40 mm	0
ex 8523 20 10	Rigid magnetic disks, prelubricated, oxide type, with a coercivity of 300 Oe or more	0
ex 8523 20 10	Rigid magnetic disk with a thin-film metallic coating, having a coercivity of more than 600 Oe, an external diameter of 88 mm or more but not exceeding 231 mm	0
ex 8529 10 70	Ceramic filters for frequencies not less than 4,5 and not exceeding 6,6 MHz contained in a housing, the dimensions of which do not exceed 9 × 24 mm	0
ex 8529 10 70	Ceramic filter package comprising two ceramic filters with three connecting pins and one ceramic resonator with two connecting pins, each having a frequency of 10,7 MHz ± 30 kHz, contained in a housing the exterior dimensions of which do not exceed 10 × 10 mm	0
ex 8529 90 99	Interline charge-coupled image sensor with filter, the dimensions of which do not exceed 43 × 89 mm	0
ex 8531 20 90	Liquid crystal display (LCD), the exterior dimensions of which do not exceed 11 × 28 × 88 mm, apart from cables and plugs, consisting of a layer of liquid crystals between two glass plates, with 121 display dots (arranged in 16 × 7 dots and nine symbols), mounted on a printed circuit board comprising electronic components providing drive and control functions with not more than nine connecting pins	0
ex 8531 20 90	Dot-matrix LCD display with symbols, the exterior dimensions of which do not exceed 18 × 35 × 117 mm, apart from cables and plugs, consisting of a layer of liquid crystal between two glass plates with 423 display dots (arranged in 60 columns and 7 rows with three symbols), mounted on a printed circuit board with interface electronics of C-MOS technology, plus a backlight function and not more than 16 connecting wires with contact areas	0
ex 8531 20 90	Dot-matrix displays, whose external dimensions do not exceed 15 × 62 × 276 mm excluding cables and connectors, consisting of a layer of liquid crystals between two glass sheets or plates with 32 768 dots (arranged in 64 lines and 512 columns), mounted on a printed-circuit board comprising electronic components providing drive and control functions, with or without cable and connector	0
ex 8532 29 00	Gold capacitor with a rated capacitance of 100 mF, an operating voltage of 5,5 V and a leakage current of not more than 100 μA, contained in a cylindrical housing of a height of less than 8 mm and a diameter of not more than 14 mm	0
ex 8532 30 10	Variable plate capacitor with plastic dielectric, with a capacitance of not more than 2 × 355 pF for the AM section and not more than 2 × 20 pF for the FM section, contained in a housing the exterior dimensions of which do not exceed 21 × 24 mm	0
ex 8532 30 90	Adjustable capacitor, in the form of a circular plate with a diameter of not more than 2,5 mm, fitted with a screw head in its centre and two connecting tags, of a thickness not exceeding 3 mm and a capacity of from 5 to 30 pF, for the manufacture of products falling within Chapter 91 (a)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8533 29 00	Device consisting of fixed resistors with a positive temperature coefficient having a nominal resistance in DC of 19,6 Ω at 20 °C, an insulation resistance of more than 1 MΩ, for the protection of telephone exchanges against prolonged increases in voltage of not more than 1 000 V, contained in a housing the exterior dimensions of which do not exceed 48 × 19 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 20793 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8533 40 10	Slide potentiometer with one or two resistor tracks and a slide distance of 20 mm, contained in a housing with not more than eight connecting pins	0
ex 8534 00 11 ex 8534 00 19	Single-face printed circuit, of dimensions not exceeding 30 × 30 mm, for the manufacture of products falling within Chapter 91 (a)	0
ex 8535 90 00 ex 8540 91 00	Socket for cathode-ray tubes	0
ex 8536 41 10 ex 8536 41 90 ex 8536 49 00	Thermal relays contained in a hermetically sealed glass cartridge not exceeding 35 mm in length excluding wires, with a maximum leakage rate of 10^{-6} cm^3 He/sec at one bar in the temperature range 0 to 160 °C, to be incorporated into compressors for refrigerating equipment (a)	0
ex 8536 50 00	Telephone line switch assembly consisting of one moveable and one stationary bifurcated spring with contact area of diffused gold on palladium silver inlay, mounted in polycarbonate material, and of dimensions not exceeding 40 × 20 × 13 mm	0
ex 8536 50 00	Reed switches in the form of a glass capsule containing not more than three electrical contacts on metal arms and a small quantity of mercury	0
ex 8540 11 10	Colour cathode-ray tubes with a slit mask, equipped with electron guns placed side by side (in-line technology) with a distance between stripes of the same colour not exceeding 0,47 mm and having the following characteristics: — a diagonal screen measurement not less than 12 and not more than 16 cm — a diagonal angle of deflection not exceeding 55°	8
ex 8540 11 10	Colour cathode-ray tubes with a slit mask, equipped with electron guns placed side by side (in-line technology) with a distance between stripes of the same colour of not more than 0,47 mm and having the following characteristics: — a diagonal screen measurement not less than 22 and not more than 26 cm — a diagonal angle of deflection of not more than 76° — a phosphor layer calibrated with the following nominal coordinates for the colour dots: *red* *green* *blue* X 0,610 0,298 0,151 Y 0,342 0,588 0,064	0
ex 8540 20 90	Photomultiplier consisting of a photocathode tube with nine dynodes, for light of wavelength of 160 nm or more but not exceeding 930 nm, of a diameter not exceeding 14 mm and a height not exceeding 94 mm	0
ex 8540 30 10	Colour cathode-ray rubes with a dot mask, equipped with electron guns placed side by side (in-line technology), with a distance of less than 0,45 mm between colour dots and with at least one of the following characteristics: — a diagonal screen measurement of not less than 42 cm, a diagonal angle of deflection of not more than 90° and convergence errors exceeding 0,8 mm at the corners — a built-in system, inseparably linked to the tube, for the absorption of vibration (so called potting system) — without internal magnetic screen — a phosphor layer calibrated with the following nominal coordinates for the colour dots:	

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8540 30 10 *(cont'd)*		
	red *green* *blue*	
	X 0,64 0,29 0,15	
	Y 0,33 0,60 0,06	
	or	
	X 0,64 0,31 0,155	
	Y 0,34 0,595 0,07	
	or	
	X 0,62 0,21 0,15	
	Y 0,33 0,615 0,06	
	or	
	X 0,610 0,307 0,150	
	Y 0,350 0,595 0,065	
	or	
	X 0,61 0,205 0,15	
	Y 0,35 0,680 0,065	
	or	
	X 0,62 0,29 0,15	
	Y 0,35 0,60 0,065	0
ex 8540 30 10	Colour cathode-ray tubes with a dot mask equipped with electron guns in a triangular fashion (delta technology) with a distance of less than 0,65 mm between colour dots and with at least one of the following characteristics: — a diagonal screen measurement of at least 66 cm — equipped with a phosphor layer calibrated with the following nominal coordinates for the colour dots:	
	red *green* *blue*	
	X 0,64 0,29 0,15	
	Y 0,33 0,60 0,06	
	or	
	X 0,64 0,31 0,155	
	Y 0,34 0,595 0,07	
	or	
	X 0,610 0,307 0,150	
	Y 0,350 0,595 0,065	
	or	
	X 0,61 0,205 0,15	
	Y 0,35 0,680 0,065	
	or	
	X 0,62 0,29 0,15	
	Y 0,35 0,60 0,065	0
ex 8540 30 10 ex 8540 30 90	Cathode-ray tubes with a memory (direct view storage tubes) for the reproduction of alphanumeric and analog data, equipped with a scanning device, for reading the images	0
ex 8540 30 90	Flat screen monochrome cathode-ray tubes having a diagonal screen measurement of not less than 142 mm and not more than 145 mm, a luminescence of between 300 and 400 lumen, a resolution of between 0,06 and 0,1 mm, phosphor types P 1 or P 55 or P 56, an anode voltage of more than 34 kV, a focus voltage of more than 7 kV and a cathode current of not less than 3 mA	0
ex 8540 89 11	Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 350 × 300 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallized base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0
ex 8540 91 00	Tungsten elements coated with insulating material, grids and cathodes for use in the manufacture of electron guns for monochrome cathode-ray tubes (a)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8540 91 00	Electron gun for the production of monochrome cathode-ray tubes with diagonal screen measurement of not less than 7,6 and not more than 30,5 cm (a)	0
ex 8540 91 00	Deflector yoke for cathode-ray tubes with an operating frequency of between 31 250 Hz and 64 000 Hz incorporating a quadripolar magnet	0
ex 8541 10 91	Silicon power rectifier diodes of planar technology, with a recovery time of less than 100 ns, a maximum recurring reverse voltage of 200 V, and average conducting-state current of 2,5 A, or more, contained in a flat housing the exterior dimensions of which exceed 9 × 9 × 5 mm, but do not exceed 17 × 11 × 5 mm	0
ex 8541 10 99	Germanium-gold diodes with forward voltage not exceeding 1 V at 5 mA	0
ex 8541 29 90	Transistor with a power of not less than 150 W at a voltage of not less than 160 V and with a cut-off frequency of not less than 20 MHz, contained in a housing the exterior dimensions of which do not exceed 37 × 22 mm, with not more than three connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 2 SA 1170 2 SC 2774 2 SA 1215 2 SC 2921 2 SA 1494 2 SC 3858 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8541 40 10	Light-emitting diode (LED) made from a gallium-based semiconductor compound, mounted in a rectangular housing the exterior dimensions of which do not exceed 4 × 20 × 21 mm, with two connecting pins, and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: LT 9305 SLF 209 LT 9306 SLF 909 or — other identification markings relating to devices complying with the abovementioned description, for use in the manufacture of radio broadcast receivers and sound recorders or reproducers (a)	0
ex 8541 40 10	Assembly consisting of not more than 10 light-emitting diodes (LEDs) made from a gallium-based semiconductor compound, mounted in a rectangular housing the exterior dimensions of which do not exceed 68 × 25 × 4 mm, with not more than 20 connecting pins, and bearing: — an identification marking consisting of or including the following combination of figures and letters: LT 9355 or — other identification markings relating to devices complying with the abovementioned description, for use in the manufacture of radio broadcast receivers and sound recorders or reproducers (a)	0
ex 8541 40 10 ex 8541 40 93	Laser diode with one photodiode, emitting light of a nominal wavelength of 780 nm, contained in a housing having a diameter of not more than 10 mm and a height of not more than 9 mm, with not more than 10 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: LT 022 LDGU or — other identification markings relating to devices complying with the abovementioned description	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8541 40 10 ex 8542 20 90	Digital display of a size not exceeding 25 × 35 mm, consisting of a printed circuit board on which are mounted, under a plastic cover, up to 22 light-emitting diodes manufactured from gallium-based semiconductor compounds. Each display consists of a single character with or without a plus or minus sign and/or one or two dots	7
ex 8541 40 10 ex 8542 20 90	Digital displays, consisting of a printed circuit board of a size not exceeding 35 × 90 mm with a single line of characters, not less than three in number, comprising light-emitting diodes made from gallium-based semiconductor compounds mounted thereon. Each character is composed of up to eight segments with or without a decimal point and the line of characters has a protective cover of plastic	0
ex 8541 40 91	Module of not more than five solar cells of thin-film technology, on a substrate the exterior dimensions of which do not exceed 70 × 18 mm	0
ex 8541 40 93	Opto-electronic circuit consisting of one or more light-emitting diodes and one or more photodiodes with amplifier circuit, contained in a plastic housing with not more than 16 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HC PL 2400 HC PL 5700 HC PL 5730 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8541 60 00	Quartz crystal oscillating at a frequency of 32 768 Hz, contained in a cylindrical housing of a length not exceeding 8,2 mm and a diameter not exceeding 3,2 mm, for the manufacture of products falling within Chapter 91 (a)	0
ex 8541 60 00	Polarized ceramic piezo-electric crystals oscillating in a frequency range of not less than 500 and not more than 12 500 kHz, contained in a housing the exterior dimensions of which do not exceed 14 × 15 mm, with not more than three connecting pins	0
ex 8542 11 30	Control and driver circuit for dot-matrix liquid crystal displays, of C-MOS technology, with a character generator, and having a drive voltage of more than 10 V, in the form of a monolithic integrated circuit without a housing (microchip) for the manufacture of liquid crystal display modules (a)	0
ex 8542 11 30	Driver circuit for liquid crystal displays, of C-MOS technology, with 40 or more output channels, and having a drive voltage of more than 10 V, in the form of a monolithic integrated circuit without a housing (chips), for the manufacture of liquid crystal display modules (a)	0
ex 8542 11 41	Dynamic read/write random-access memory of N-MOS (including H-MOS) technology (N/H-MOS D-RAM) with a storage capacity of 64 Kbit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 22 × 7 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: KM 4164 MN 4264 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 41	Dynamic random-access memories of C-MOS technology (C-MOS D-RAMs), with a storage capacity of 256 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing:	

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 41 *(cont'd)*	— an identification marking consisting of or including one of the following combinations of figures and letters: 51 C 256 53 C 256 53 C 464 MB 81 C 258 TC 51832 51 C 259 53 C 258 53 C 466 MB 81 C 446 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 41	Dynamic random-access memories (D-RAMs) of N-MOS (including H-MOS) technology, with a storage capacity of 256 Kbits and an access time not exceeding 150 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 34 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HB 50562 HM 50256 PD 41254 M5M 4256 HM 50464 PD 41256 M5M 4464 PD 41464 MB 81256 MB 81464 TMM 41256 TMM 41464 MSM 4256 TMS 4256 MSM 4464 TMS 4464 or — other identification markings relating to devices complying with the abovementioned description	8
ex 8542 11 41	Dual port dynamic random-access memory (D-RAM) of MOS technology, with data registers and a serial read output control, with a storage capacity of 256 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 13 × 39 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: MB 81461 M5M 4 C 264 PD 41264 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 41 ex 8542 11 43	Dynamic read/write random-access memories manufactured in N-MOS (including H-MOS) technology (D-RAMs), consisting of a substrate layer with not less than two and not more than eight chips having a storage capacity of 128, 192 or 256 Kbits and a storage capacity of not less than 256 Kbits and not more than two megabits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 57 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 6025841 6031587 6870392 7379172 6025843 6031591 6870393 7379174 6025856 6870395 7379176 6025858 7379181 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 43	Random-access memory with a storage capacity of 1 Mbit, with separate in- and outputs and serial shift registers (so-called field memories), of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 54 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TC 521 000 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 43	Dual port dynamic random-access memory (D-RAM) of MOS technology, with data registers and a serial read output control, with a storage capacity of 1 Mbit in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 13 × 37 mm, with not more than 32 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: TC 524256 MB 81 C 4251 TMS 44 C 251 TC 524257 MSM 442256 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Static random-access memories of C-MOS technology (C-MOS S-RAMs), in the form of a monolithic integrated circuit with a storage capacity of 16 × 4 bits, an access time not exceeding 35 ns, contained in a housing the exterior dimensions of which do not exceed 9 × 21 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY7C189 CY7C190 CY74S189 CY54S189 CY27S03 CY27S07 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Static random-access memories of bipolar technology (bipolar S-RAMs), with a storage capacity of 64 × 9 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 40 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82 S 09 MBM 93419 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Static random-access memory (S-RAM) with a storage capacity of 256 bits superimposed bit-for-bit on an electrically erasable, programmable, read-only-memory (E^2PROM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 24 mm, with not more than 18 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 51 *(cont'd)*	— an identification marking consisting of or including one of the following combinations of figures and letters: X 2210 X 2443 X 2444 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Static random-access memories of C-MOS technology (C-MOS S-RAMs), with a storage capacity of 256 × 4 bits and an access time not exceeding 60 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 12 × 29 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY7C122 CY 93422 CY93L422 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Static random-access memories of N-MOS (including H-MOS) technology (N-MOS S-RAMs), with a storage capacity of 256 × 4 bits with an access time not exceeding 25 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 9122 — 25 91 L 22 — 25 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Random-access memories of ECL technology (ECL-RAMs) with a storage capacity of 256 × 4 bits, and the access time not exceeding 8 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 11 × 32 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 10422 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Static random-access memories of TTL technology (TTL S-RAMs), with a storage capacity of 1 Kbit and an access time not exceeding 45 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 30 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 93422 93425 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 51	Static random-access memory (S-RAM) with a storage capacity of 1 Kbit, superimposed bit-for-bit on an electrically erasable, programmable, read-only memory (E^2PROM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: X 2001 X 2201 A X 2212 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Static random-access memory (S-RAM) with a storage capacity of 2 Kbits, superimposed bit-for-bit on an electrically erasable, programmable, read-only memory (E^2PROM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of the following combination of figures and letters: X 2002 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Static random-access memories (S-RAMs) of MOS technology, with a storage capacity of 1 K × 4 bits and access time not exceeding 25 ns, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 8 × 32 mm, with not less than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 9150-20 CY 7 C 150-15 AM 9150-25 CY 7 C 150-25 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Random-access memories of ECL technology (ECL-RAMs) with a storage capacity of 4 Kbits and an access time not exceeding 50 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 11 × 32 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 10470 10474 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Static random-access memory (S-RAM) with a storage capacity of 4 Kbits, superimposed bit-for-bit on an electrically erasable, programmable, read-only memory (E^2PROM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 51 *(cont'd)*	— an identification marking consisting of the following combination of figures and letters: X 2004 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Static random-access memories of N-MOS (including H-MOS) technology (N-MOS S-RAMs), with a storage capacity of 8 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 4008 8112 4118 8114 4801 8185 8104 PD 421 8108 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Static random-access memory of C-MOS technology (C-MOS S-RAM), with a storage capacity of 2 K × 8 bits and with a nominal standby power of not more than 0,005 mW at 25 °C, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: TC5516APL-2 TC5517CPL-15 TC5517BPL-20 TC5516AFL-2 TC5517CPL-20 TC5517BPL-25 TC5516APL TC5517CFL-15 TC5517BFL-20 TC65516AFL TC5517CFL-20 TC5517BFL-25 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 51	Non-volatile memory consisting of a C-MOS S-RAM, with a capacity of 16 Kbits and internal power supply, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 19 × 40 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DS 1220 Y MK 48 Z 02 (B) or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 51	Random-access memories of ECL technology (ECL-RAMs) with a storage capacity of 16 Kbits and an access time not exceeding 15 ns in the form of a monolithic integrated circuit, contained in a housing the dimensions of which do not exceed 18 × 37 mm, with not more than 28 connecting pins or contact areas and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 51 *(cont'd)*	— an identification marking consisting of or including one of the following combinations of figures: 10480 10484 100484 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Static random-access memory of C-MOS technology (C-MOS S-RAM), with a storage capacity of 32 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TC 5532 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Non-volatile memory consisting of a static read/write random access memory of C-MOS technology (C-MOS S-RAM), with a storage capacity of 64 Kbits and an internal energy source, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 20 × 42 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: DS 1225 Y or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 51	Random-access memories of ECL technology (ECL-RAMs) with a storage capacity of 64 Kbits in the form of a monolithic integrated circuit, contained in a housing the dimensions of which do not exceed 10 × 29 mm, with not more than 22 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 10490 or — other identification markings relating to devices, complying with the abovementioned description	0
ex 8542 11 52	Static read/write random-access memories of N-MOS (including H-MOS) technology (N-MOS S-RAMs), with a storage capacity of 72 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TMM 2089 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 52	Static random access memories (S-RAMs) of C-MOS technology, with a storage capacity of 32K × 8 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 39 × 17 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HM 62256, PD 43256, TC 55257, MB 84256 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 52	Non-volatile memory consisting of a static C-MOS random-access memory, with a storage capacity of 256 Kbits and built-in energy source, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 19 × 40 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DS 1230 DS 1235 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 61	Read-only memory in C-MOS technology (C-MOS ROM) with a storage capacity of 256 Kbits and a standby current of not more than 0,03 mA, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 17 × 50 mm, with not more than 54 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HN 61256 HN 613256 MB 83256 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 61	Read-only memory in C-MOS technology (C-MOS ROM) with a storage capacity of 1 Mbit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HN 62301 P MB 83 1000 MB 83 1124 TC 53 1000 P or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 63	UV-erasable, programmable, read-only memories (EPROMs) with a storage capacity of 2 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with a quartz window on the upper surface and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82140 PP AMI 702 ADC or — other identification markings relating to EPROMs complying with the abovementioned description	4

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 63	UV-erasable, programmable, read-only memory (EPROM) equipped with a programmable input/output system, with a storage capacity of 2 K × 8 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 52 mm, with a quartz window on the upper face and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: D 8755 A TMP 8755 AC or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 63	UV-erasable programmable read-only memory (EPROM) having a storage capacity of 16 Kbits and an access time of not more than 65 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with a quartz window on its upper surface, and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY 245 W CY 7C 291 W or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 63	UV-erasable programmable read-only memory (EPROM) having a storage capacity of 64 Kbits and an access time of not more than 65 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with a quartz window on its upper surface, and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY 7C 261 W CY 7C 263 W CY 7C 268 W CY 7C 269 W or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 63 ex 8542 11 76	Programmable read-only memories, erasable (EPROMs) or non-erasable (PROMs), in the form of a monolithic integrated circuit having a storage capacity of 128 Kbits and an access time of not more than 100 ns, contained in a housing whose external dimensions do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas, with or without a quartz window on the upper surface and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY 7C 251 CY 7C 254 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 63 ex 8542 11 76	Programmable read-only memories, erasable (EPROMs) or non-erasable (PROMs), in the form of a monolithic integrated circuit having a storage capacity of 256 Kbits and an access time of not more than 100 ns, contained in a housing whose external dimensions do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas, with or without a quartz window on the upper surface and bearing: — an identification marking consisting of or including the following combination of figures and letters: CY 7C 271 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 72	Electrically erasable, programmable, read-only memories (E^2PROMs) with a storage capacity of 16 Kbits, in the form of a monolithic circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 42 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 2817 24 C 16 X 2816 28 C 16 28 C 17 38 C 16 52 B 13 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 72	Electrically erasable, programmable, read-only memories (E^2PROMs) with a storage capacity of 64 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 28 C 64 52 B 33 52 B 33 H MBM 28 C 65 MCM 2864 X 2864 A or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 72	Electrically erasable, programmable, read-only memories (E^2PROMs) with a storage capacity of 128 Kbits, in the form of a monolithic circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: X 28128 A or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 72	Electrically erasable, programmable, read-only memories (E^2PROMs) with a storage capacity of 256 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 42 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 28256 28 C 256 48 C 256 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 72	Electrically erasable, programmable, read-only memories (E^2PROMs) with a storage capacity of 512 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 42 mm, with not more than 32 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 48 F 512 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 72	Electrically erasable, programmable, read-only memories (E^2PROMs) with a storage capacity of 1 Mbit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 42 mm, with not more than 32 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 48 F 010 or — an identification markings relating to devices covered by the abovementioned description	0
ex 8542 11 76	Write buffer memory, of C-MOS technology, with an organization of 4 × 16 bits comprising eight bits of address and eight bits of data, and four-bit parity in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 68 connecting pins, and bearing: — an identification marking consisting of or including the following combination of figures and letters: R 2020/16 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 76	Double row buffer memory, with shift registers and random-access read/write memories, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: CRT 9212 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 76	Dynamic FIFO (first-in, first-out) read/write memory of TTL technology with a storage capacity of 256 bits in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 7 × 20 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 67 L 401 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 76	Dynamic FIFO (first in, first out) read/write memory, of MOS technology, with a storage capacity of 7 280 or 9 080 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 12 × 36 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: PD 41101 PD 42 101 PD 41102 PD 42 102 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 76	Programmable, non-erasable, read-only memories (PROMs) of Schottky TTL technology, with a storage capacity of 2 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 24 connecting pins or contact areas, and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 76 *(cont'd)*	— an identification marking consisting of or including one of the following combinations of figures or figures and letters: 27 S 12 — 5305 — 6305 — 76 LS 03 27 S 13 — 5306 — 6306 — 7620 — 5308 — 6308 — 7621 28 L 22 — 5309 — 6309 28 LA 22 — 53 S 240 — 63 S 240 — 82 S 114 28 L 2 XMFC — 53 S 241 — 63 S 241 — 82 S 130 — — 6335 — 82 S 131 29613 — 54 S 570 — 6336 29770 — 54 S 571 — — 93436 29771 — — 7053 — 93446 — 5604 — 7058 38510 — 5624 — — MB 7115 — — 74 S 570 — MB 7116 — — 74 S 571 — MB 7117 — — — MB 7118 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 76	Programmable non-erasable read-only memories (PROMs) of MOS technology, with a storage capacity of 16 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 39 × 17 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 7 C 245 7 C 291 7 C 292 HM 6616 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 76	Programmable non-erasable read-only memories (PROMs) of bipolar technology with a storage capacity of 16 Kbits and a standby current equal to, or of more than, 50 mA and less than, or equal to, 80 mA in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 33 × 14 mm, with not more than 24 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: 27 PS 191 A or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 76	Programmable non-erasable read-only memories (PROMs) with a storage capacity of 32 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 63 S 3281 AM 27 S 43 MB 7141 MB 7142 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 76	Programmable non-erasable read-only memory (PROM) having a storage capacity of 64 Kbits and an access time of not more than 65 ns, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 44 mm, with not more than 32 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CY 7C 261 MB 7143 CY 7C 263 MB 7144 CY 7C 264 MB 71 C 44 CY 7C 268 CY 7C 269 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81	4-bit single-chip microcomputers of C-MOS technology, having driver-functions for liquid crystal displays (LCD), consisting of a read-only memory (ROM) with a capacity of 12 Kbits and a random-access memory (RAM) with a capacity of 160 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 14 × 18 mm, with not more than 60 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: MBM 58421 or — other identifications marking relating to devices complying with the abovementioned description	0
ex 8542 11 81	Single-chip microcomputer of C-MOS technology, consisting of an arithmetical logic unit (ALU) with an organization of four bits, a read-only memory (ROM) with a storage capacity of 2 K × 8 bits, a dual-tone, multi-frequency (DTMF) generator, a random access memory (RAM) with a storage capacity of 1 Kbit, whether or not with another random access memory (RAM) with a storage capacity of 512 bits, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 16 × 54 mm, with not more than 42 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: T 6978 TCM 8301 TCM 8302 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81	4-bit single-chip microcomputers of C-MOS technology, consisting of a read-only memory (ROM) with a capacity of not less than 10 Kbits and not more than 16 Kbits and a random-access memory (RAM) with a capacity of not more than 1 536 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 54 mm, with not more than 67 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: TMP 47 C 200 HD 44750 TMP 47 C 220 TMP 47 C 221 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 81	4-bit single-chip microcomputers of C-MOS technology, consisting of a read-only memory (ROM) with a capacity of 4 K × 8 bits, random-access memories (RAM) with a total capacity of 3 Kbits, a DMTF-generator, in the form of a monolithic integrated circuit contianed in a housing the exterior dimensions of which do not exceed 16 × 54 mm, with not more than 42 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TMP 47 C 452 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81	4-bit single-chip microcomputers consisting of a read-only memory (ROM) with a capacity of not less than 18 Kbits and not more than 104 Kbits and a random-access memory (RAM) with a capacity of not less than 512 bits and not more than 4 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 20 × 60 mm, with not more than 100 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CD 3200-3299 TMC 0270-0279 TMC 0500-0599 TMC 0980-0989 TMC 1500-1599 TMC 1980-1999 TMP 47 C 670 TP 0310-03299 TP 0450-04599 TP 0480-04899 TP 0500-05999 T 7767 BS TSS 200 TSS 400 HD 38800 HD 38820 HD 44796 HD 44800 HD 44801 HD 44820 HD 44840 HD 44860 HD 614042 HD 404 189 HD 614 080 SMC 6214 SMC 6215 SMC 6234 SMC 6266 SMC 62 L 34 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81	4-bit single-chip microcomputer of C-MOS technology, in the form of a monolithic integrated circuit, comprising a read-only memory (ROM) or a programmable non-erasable read-only memory (PROM) with a storage capacity of 160 Kbits or more and a read/write random access memory (RAM) with a storage capacity not exceeding 4 Kbits, contained in a housing the exterior dimensions of which do not exceed 20 × 60 mm, with not more than 64 connecting pins and bearing: — an identification code consisting of or including one of the following alphanumeric combinations: HD 404019 HD 404919 HD 40 74019 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81	8-bit single-chip microcomputer of MOS technology, having universal peripheral interface functions, consisting of a central processing unit, a random access read-write memory (RAM) with a storage capacity of 1 Kbit, UV-erasable, programmable read-only memory (EPROM) with a storage capacity of 2 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 53 mm, having a quartz window on the upper face, with not more than 44 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: D 8742 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 81	8-bit single-chip microcomputer, consisting of an electronic, programmable, read-only memory (EPROM) UV-erasable with a capacity of 32 Kbits and a random access memory (RAM) with a capacity of 1 Kbit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 53 mm, with a quartz window and not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 7742 8751 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81	8-bit single-chip microcomputer of C-MOS technology in the form of a monolithic integrated circuit consisting of a read-only memory (ROM) with a capacity of 16 Kbits, a random access memory (RAM) with a capacity of not more than 2 Kbits, an electrically erasable programmable read-only memory (E^2PROM) with a capacity of 640 bits, 8-bit two-way converters (ADC/DAC), an analog multiplexer, and programmable amplifiers for analog signal control, contained in a housing the exterior dimensions of which do not exceed 26 × 20 mm, with not more than 100 connecting pins and bearing: — an identification marking either consisting of or including the following combination of letters: DAPC or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81	8-bit single-chip microcomputer of N-MOS (including H-MOS) technology, having universal peripheral interface functions, consisting of a random access read-write memory (RAM) with a storage capacity of 2 Kbits, a non-erasable, programmable read-only memory (PROM) or a UV-erasable, programmable read-only memory (EPROM) with a storage capacity of 16 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 53 mm, with not more than 44 connecting pins or 44 contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures: 8042 8742 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81	8-bit single-chip microcomputer of C-MOS technology consisting of a random access memory (RAM) with a storage capacity of 2 Kbits, a programmable read-only memory (PROM) or a UV-erasable programmable read-only memory (EPROM) with a storage capacity of 64 Kbits and a multi-protocol serial communication port, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 63 × 52 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: 80 C 152 77 C 82 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81	8-bit microprocessor of N-MOS (including H-MOS) technology, for the encoding/decoding of data in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 53 × 15 mm, with not more than 40 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 81 *(cont'd)*	— an identification marking consisting of or including one of the following combinations of figures and letters: Z 8068 8294 Z 9518 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81	8-bit microprocessor of C-MOS technology, consisting of a central processing unit (CPU), a memory controller, a two-channel DMA controller, two-channel programmable 16-bit counter/timer, a wait-state generator, a two-channel asynchronous serial communication interface (ASCI) and a bus controller, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 62 × 26 mm, with not more than 80 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 64180 HD 64 A 180 HD 64 B 180 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81 ex 8542 11 83	8-bit single chip microcomputer of C-MOS technology with a 16-bit internal structure, consisting of a random-access memory (RAM) with a storage capacity of 2 Kbits, 20 input-output ports, a comparator input port, two asynchronous channels with programmable transfer rates, an interrupt controller, two direct-access memory channels, and two 16-bit counters, in the form of a monolithic integrated circuit contained in a housing the external dimensions of which do not exceed 31 × 31 mm, containing no more than 84 connecting pins or contact pads and bearing: — an identification mark consisting of/or including the following alphanumeric combination: PD 70320 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81 ex 8542 11 83	8-bit microprocessor of N-MOS (including H-MOS) technology with 16-bit internal architecture, in the form of a monolithic integrated circuit consisting of a central processing unit (CPU), a timing generator, two independent DMA channels, a programmable interrupt controller, three programmable 16-bit timers, programmable memory and peripheral chip select, a programmable wait state generator and a local bus controller, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 80188 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 81 ex 8542 11 83 ex 8542 11 85	Central processing unit of N-MOS (including H-MOS) technology (N-MOS CPU), consisting of one 16 × 16-bit service memory, one 16 × 20-bit service memory, one 32 × 32-bit service memory, one 8 × 8-bit service memory, one 16-bit register, two 20-bit registers, one 8-bit register, one 12-bit register, one 5-bit counter and timing network, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 25 mm, with not more than 68 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 81 ex 8542 11 83 ex 8542 11 85 *(cont'd)*	— an identification marking consisting of or including the following combination of figures and letters: LSI-604041855 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81 ex 8542 11 83 ex 8542 11 85 ex 8542 11 87	Numeric processor extension unit of N-MOS (including H-MOS) technology (N-MOS NPX) containing not more than 14 registers, in the form of a monolithic intergrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 53 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 80287 8087 NS 32081 TX 32081 W or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81 ex 8542 11 83 ex 8542 11 85 ex 8542 11 87	Floating-point arithmetic co-processor of MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 46 × 53 mm, with not more than 208 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 80387 R 2010/16 74 APC 8847 MC 68881 NCR 32020 WTL 3167 MC 68882 NS 32381 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 81 ex 8542 11 83 ex 8542 11 85 ex 8542 11 87	Text co-processor, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 25 mm, with not more than 68 connecting pins, and bearing: — an identification marking consisting of or including the following combination of figures and letters: C 82730 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 83	16-bit single-chip microcomputer using N-MOS technology (including H-MOS), comprising at least one read-only memory (ROM) in the form of a monolithic integrated circuit with a 510 × 13-bit storage capacity or a programmable UV-erasable read-only memory (EPROM) in the form of a monolithic integrated circuit with a 512 × 13-bit storage capacity, a read/write random access (RAM) in the form of a monolithic integrated circuit with a 2 Kbit storage capacity in the form of a monolithic integrated circuit in a housing containing no more than 28 connecting pins and with dimensions not exceeding 16 × 37 mm, and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: PD 7720 PD 77 P 20 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 83	16-bit single-chip microcomputer, comprising a read-only memory (ROM) with a capacity of 64 Kbits, a random access memory (RAM) with a capacity of 2 Kbits, a digital/analog converter with sample/hold, contained in a housing the exterior dimensions of which do not exceed 40 × 40 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 8397 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 83	16-bit microprocessor of bipolar technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 82 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 29116 SBP 9989 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 83	16-bit microprocessor of C-MOS technology, consisting of a central processing unit (CPU) and an 8-bit or 16-bit external data bus in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 54 × 30 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 70108 80 C 188 Z 70116 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 83	16-bit microprocessor of C-MOS technology, consisting of a central processing unit (CPU), a memory controller, a 2 Kbit cache memory, three programmable 16-bit counter/timers, a full duplex universal asynchronous receiver/transmitter (UART) and four DMA channels, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 26 × 26 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: Z 280 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 83	16-bit microprocessor in N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, consisting of a central processing unit (CPU), a timing generator, two independent DMA channels, a programmable interrupt controller, three programmable 16-bit timers, programmable memory and external chip selection logic, a programmable wait state generator with bus control unit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 68 connecting pins or contact areas and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 83 *(cont'd)*	— an identification marking consisting of or including the following combination of figures: 80186 or — other identification markings relating to devices complying with the abovementioned description	 0
ex 8542 11 83	16-bit microprocessor of N-MOS technology (including H-MOS) consisting of a central processing unit (CPU), a memory management and protection unit (MMU) and a real address and virtual address operating mode system (OSO), in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 30 × 30 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 80286 or — other identification markings relating to devices complying with the abovementioned description	 10
ex 8542 11 83	16-bit communication processor of C-MOS technology, containing a coder/decoder for the conversion of data into serial/parallel signals in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 28 × 28 mm, with not more than 132 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: TMS 380 C 16 or — other identification markings relating to devices complying with the abovementioned description	 0
ex 8542 11 83	16-bit communications processor of N-MOS (including H-MOS) technology, consisting of a random access memory (RAM) with a storage capacity of 22 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15 × 60 mm, with not more than 48 connecting pins of contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: TMS 38010 or — other identification markings relating to devices complying with the abovementioned description	 0
ex 8542 11 83 ex 8542 11 85	16-bit single-chip microcomputer of MOS technology, with an arithmetic-logic unit (ALU) of 32 bits, consisting of a random-access memory (RAM) with a storage capacity of not more than 9 Kbits, a read-only memory (ROM) or a UV-erasable, programmable read-only memory (EPROM) with a storage capacity of not more than 64 Kbits, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 54 × 29 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 32010 320 C 10 320 C 17 320 E 15 32011 320 C 15 320 C 25 320 E 17 or — other identification markings relating to devices complying with the abovementioned description	 0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 83 ex 8542 11 85	16-bit microprocessor with an arithmetic-logic unit (ALU) of 32 bits, of MOS-technology, comprising a random-access memory (RAM) with a storage capacity of 8,5 Kbits, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 29 × 29 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: TMS 32020 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 85	32-bit single-chip microcomputers of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit consisting of 24 registers of 32 bits and a RAM with a capacity of 2 Kbits, contained in a housing the exterior dimensions of which do not exceed 24 × 24 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HGC 6127 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 85	32-bit single-chip microcomputer in C-MOS-technology, in the form of a monolithic integrated circuit consisting of a ROM with a capacity of 24 Kbits and RAMs with a total capacitiy of 4 Kbits, contained in a housing the exterior dimensions of which are not less than 30 × 30 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: MB 8764 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 85	32-bit single-chip microcomputer, consisting of a read-only memory (ROM) having a storage capacity of 16 Kbits, random-access memories (RAM) having a total storage capacity of 32 Kbits a floating decimal point arithmetical unit with a capacity of 32 bits in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 30 × 53 mm, with not more than 100 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: DSP 32 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 85	32-bit single-chip microcomputer of C-MOS technology, consisting of two random-access read-write memories (RAM) with a total storage capacity of 64 Kbits and a read-only memory (ROM) with a capacity of 128 Kbits, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 28 × 28 mm, with not more than 100 connecting pins or contact areas and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 85 *(cont'd)*	— an identification marking consisting of or including the following combination of figures and letters: 320 C 30 or — other identification markings relating to circuits complying with the abovementioned description	0
ex 8542 11 85	32-bit microprocessor of C-MOS technology, with a 16-bit external data bus and a 24-bit external address bus, with a virtual storage address capacity of 64 terabytes, in the form of a monolithic integrated circuit, contained in a housing whose dimensions do not exceed 31 × 31 mm, with not more than 100 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combinations of figures and letters: 80386 SX or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 85	32-bit microprocessor of C-MOS technology, with an external data bus of 32 bits and an external address bus of 32 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 46 × 46 mm, with not more than 208 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 80386 80 486 MC 68020 NS 32532 CYC 601 MC 68030 NS 32 C 032 L 64801 MC 68032 R 2000/16 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 85	32-bit microprocessor of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 38 × 38 mm, with not more than 132 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: NCR 32000 NS 32032 NS 32332 CPU 0404 1871 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Arithmetic-logic unit of N-MOS (including H-MOS) technology, consisting of one 32-bit register, one 24-bit register, one 4-bit register, 12 1-bit registers, two 16 × 24-bit service memories, one logic network performing arithmetic and logic operations, decodifying logic, and error detection and management logic, one 8-bit counter and a timing network, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 23 × 82 mm, with not more than 64 connecting pins and bearing: — the identification marking: ALU 0486 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Arithmetic-logic unit (ALU) of C-MOS technology, with a capacity of 32-bits, for image processors in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 50 × 50 mm, with not more than 145 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: XL 8237 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Logic circuit of N-MOS (including H-MOS) technology (N-MOS LC) serving as a clock generator for central processing unit, main memory and input/output interfaces, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 25 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: H 108982 (MCC) or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Clock generator and controller for microprocessors, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 24 × 9 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82 C 84 82 C 284 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Clock generator for a graphics controller in the form of a monolithic integrated circuit of C-MOS technology contained in a housing the exterior dimensions of which do not exceed 20 × 7 mm with 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figure and letters: PCLK 1 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Logic circuit of bipolar technology, with not more than six logic functions, a supply voltage of not less than 11 V and not more than 18 V, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 23 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: FZH 101 A FZH 111 A FZH 191 FZH 201 FZJ 121 FZK 101 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Logic control circuits of N-MOS (including H-MOS) technology, consisting of one 7-bit register, three timers, one multiplexer, sequential and combining networks intended to perform control operations, decodifying logic, error detection and management logic and a timing network, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 23 x 82 mm, with not more than 64 connecting pins and bearing: — the identification marking: MIC 0482 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Semi-custom logic array (gate array) of C-MOS technology, with metal gates, with an operating voltage of 12 volts, with not less than 637 two-input functions, having within the array a digital code produced by an electron beam, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 29 x 11 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: FB 215 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 91	Field programmable array logics (PALs) of C-MOS technology, with a programmable AND array, fixed OR array, not more than 32 inputs and not more than 12 outputs, whether or not with registers, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 19 x 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 16 P 8 16 RP 4 C 16 L 8 C 16 R 4 C 16 R 6 C 16 R 8 C 20 G 10 C 22 V 10 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Programmable, non-erasable, logic circuits (field programmable logic array) of TTL Schottky technology, with not more than 48 AND functions, not more than eight OR functions, and not more than 16 inputs, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 x 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: FP 54 AS 839 FP 74 AS 839 82 S 100 FP 54 AS 840 FP 74 AS 840 82 S 101 SN 54 LS 333 SN 74 LS 333 SN 54 LS 334 SN 74 LS 334 93458 SN 54 LS 335 SN 74 LS 335 93459 SN 54 LS 336 SN 74 LS 336 or — other identification markings relating to devices complying with the abovementioned description	5

CN code	Description	Rate of autonomous duty (%)
ex 8582 11 91	Logic call array (LCA) with not more than 1 200 gates, programmable, electrically erasable, of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 62 × 31 mm, with not more than 84 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: XC 2064 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Non-erasable, programmable logic device of C-MOS technology, with not less than 1 800 logic gates, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 28 × 28 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: EP 1800 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Non-erasable user-programmable logic sequencer of bipolar technology, having not more than 48 AND functions, a 6-bit state register, an 8-bit output register, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 82 S 105 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	UV-erasable programmable logic device (EPLD) of C-MOS technology containing not less than 600 logic gates, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 29 × 124 mm, with a quartz window on the upper surface, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: EP 600 CY 7C 330 16 L 8-W CY 7C 331 16 R 4-W CY 7C 332 16 R 6-W 16 R 8-W 22 V 10-W or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Error detection and correction circuit of N-MOS (including H-MOS) technology capable of detecting and correcting single bit errors and detecting all double bit errors, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 68 contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 8206 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Burst error processor (BEP) of N-MOS (including H-MOS) technology for detecting and correcting multiple errors derived from a line of magnetic disks, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 54 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 8065 AM 9520 AM 9521 or — any other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Error correction and detection unit (ECDU) of bipolar technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 62 mm, with not more than 48 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 2960 74 F 630 74 F 631 74 LS 630 74 LS 631 DP 8400 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	CPU controller, of C-MOS technology comprising a control unit for the refreshment of memories, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 100 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: FE 3010 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit of C-MOS technology, operating at 12 MHz consisting of a programmable interval timer, a clockgenerator, two direct memory access controllers and a memory mapper, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combinations of figures: 82 231 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit of C-MOS technology, for the management of asynchronous cycles of a 32-bit central processing unit, of a direct memory access circuit and of a multimaster bus, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 100 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91 *(cont'd)*	— an identification marking consisting of or including the following combination of figures and letters: 82 C 321 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control and interface circuit for 16-bit peripherals, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 132 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 82 303 82 304 82 306 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Hard-disk controller of MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 53 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 1454-001 HDC 9224 PD 7261 PD 7262 WD 1010 WD 2010 WD 42 C 22 WD 5010 WD 5011 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Floppy-disk controller of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 26 × 62 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of letters and figures: FE 2100 82077 G 70360-33 L 1 A 0519 MB 89311 WD 16 C 92 WD 37 C 65 WD 57 C 65 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Four-channel read/write monolithic integrated circuit of bipolar technology for controlling magnetic heads in hard-disk units, contained in a housing whose exterior dimensions do not exceed 12 × 19 mm, with not more than 28 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91 *(cont'd)*	— an identification marking consisting of or including the following combination of figures and letters: SSI 510 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus controller of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 41 × 41 mm, with not more than 145 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 82 C 301 82 C 88 82355 82 C 211 82358 82 C 288 MSM 6307 82 308 VIC 068 82 309 VL 86 C 410 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Seven-channel programmable controller for direct memory access, comprising two eight-channel programmable interrupt controllers and five programmable 16-bit timers/counters, of C-MOS technology in the form of a monolithic integrated circuit, containing in a housing the exterior dimensions of which do not exceed 32 × 32 mm, with not more than 132 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combinations of figures: 82 357 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Direct memory access controller comprising the detection and the control of the refreshment of dynamic random-access memories (D-RAM), of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 32 × 32 mm, with not more than 84 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: VC 2730-000 1 C or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Buffer manager and controller of C-MOS technology in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 36 × 36 mm, with not more than 144 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: WD 11 C 00-22 WD 83 C 580 WD 83 C 583 WD 12 C 00-22 82 C 325 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Buffer manager and controller of N-MOS (including H-MOS) technology in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 54 × 17 mm, with not more than 40 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91 *(cont'd)*	— an identification marking consisting of or including the following combination of figures and letters: WD 1015 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Cache memory manager and controller of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing whose external dimensions do not exceed 38 × 38 mm, with not more than 132 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 82385 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit of C-MOS technology for the control of S/RAMs, capable of multiplexing addresses and generating pulses, and for the sequential control of data for the peripheral magnetic unit/rigid disk interface, and memory control, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of letters and figures: OMTI 5055 (OMTI 20513) or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit for static memory control (S-RAM), of MOS technology, with address multiplexing and pulse generation facility, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 28 × 54 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AIC 300 OMTI 506 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Dynamic random access memory controller of MOS technology (MOS D-RAM controller) capable of multiplexing addresses and generating timing, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 17 × 62 mm, with not more than 48 connecting pins or 52 contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82 C 08 THCT 4502 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit of bipolar technology for the control of dynamic random-access memories (D-RAMs), capable of multiplexing addresses and generating timing, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 26 × 67 mm, with not more than 68 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91 *(cont'd)*	— an identification marking consisting of or including one of the following combinations of figures and letters: DP 8408 DP 8428 MB 1422 DP 8409 DP 8429 SN 74 S 409 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Memory management unit of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the dimension of which do not exceed 36 × 36 mm, with not more than 132 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: MC 68851 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Memory management unit of N-MOS (including H-MOS) technology (N-MOS MMU) with a maximum addressing capacity of 4 Gbytes, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 36 × 82 mm, with not more than 132 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 68451 TX 32082 W NS 32082 NS 32382 0404 1872 or — other identification markings relating devices complying with the abovementioned description	0
ex 8542 11 91	Input-output circuit of N-MOS (including H-MOS) technology for data control equipped with a timing control with a static random-access memory (S-RAM) with a capacity of 128 × 8 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 54 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 6532 CO 10750 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Sequence control circuit of N-MOS (including H-MOS) technology, consisting of one 32-bit register, three 16-bit registers, one 16 × 16-bit service memory, one 7 × 17-bit last-in-first-out (LIFO) memory, one adder circuit, decodifying logic, priority logic, error detection and management logic, one 16-bit multiplexer, one 8-bit counter and a timing network, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 23 × 82 mm, with not more than 64 connecting pins and bearing: — the identification marking: CSS 0484 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Sequential data control circuit of MOS technology for interface between a hard-disk memory unit and the memory control unit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 28 × 54 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AIC 010 AIC 100 OMTI 505 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Sequence control circuit for image processors of C-MOS technology in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 50 × 50 mm, with not more than 145 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: XL 8236 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Status and shift control unit of bipolar technology in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 57 mm with not more than 42 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AM 2904 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Circuit of advanced low-power Schottky (ALPS) technology for the asynchronous control of signal lines (bus) and the conversion of a local bus into a multiplexed bus (BAM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 37 × 13 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 68452 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Contention resolving a local area network (LAN) controller, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 63 × 63 mm, with not more than 84 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 8001 MCM 68590 82590 8003 WD 2840 82592 82586 WD 80 C 24 82588 WD 83 C 503 AM 7990 WD 83 C 510 COM 9026 WD 83 C 603 DP 8390 WD 83 C 690 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Multiprotocol control circuit for the serial transmission of data, in the form of a monolithic integrated circuit of N-MOS (including H-MOS) technology, contained in a housing the exterior dimensions of which do not exceed 18 × 54 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: SCN 2652 MC 2652 SCN 68652 MC 68652 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit for data block transfer between dynamic memory and peripherals (DMA transfer controller or 'DTC'), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 63 × 38 mm, with not more than 133 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: Z 8516 82 C 223 HD 68450 Z 9516 82307 WE 32104 82380 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit for the universal asynchronous transmission and the separation of data and interface for peripherals, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 27 × 27 mm, with not more than 80 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures or figures and letters: 82 C 607 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Serial communication controllers of MOS technology, with two independent duplex channels with a capacity of 1,6 Mbits/sec or more but not exceeding 4 Mbits/sec, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 62 × 21 mm, with not more than 52 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: Z 80 C 30 PD 72001 Z 85 C 30 SNC 68562 Z 85 C 35 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit, of N-MOS (including H-MOS) technology, for data/address flows from the CPU, inputs/outputs and the main memory, in the form of a monolithic integrated circuit, contained in a housing whose dimensions do not exceed 36 × 36 mm, with not more than 132 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: CIM 1456 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Data-synchronizer for tape-reading units of bipolar technology in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 39 × 15 mm with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: VT 210 or — other identification markings relating to the abovementioned description	0
ex 8542 11 91	Display controller and character generator (DCCG), of C-MOS technology, for liquid-crystal dot-matrix display system in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 24 × 26 mm, with not more than 80 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: HD 61830 LH 5821 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Interpolation pulse generator, of C-MOS technology, for controlling geometrical functions, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: KM 3701 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Graphics controller of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 100 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: PEGA 82 C 431 82 C 435 82 C 441 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Graphic display controller (GDC) of N-MOS technology (including H-MOS), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 52 × 18 mm, with not more than 44 connecting pins and bearing: — an identification marking consisting of or including the following combinations of figures and letters: Z 7220 A 82720 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Video controller, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15 × 52 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 38301-A L 1A 2099 PVC-2 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Cathode-ray tube video controller of MOS-technology, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 32 × 62 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CRT 9007 VL 86 C 310 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Monochrome display controller (MDC) of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 25 × 25 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 01-01.00 551 A or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Cathode-ray tube controller (CRTC) of C-MOS technology in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 32 × 62 mm, with not more than 100 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82 C 434 V 6363 MB 89321 MB 89322 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Cathode-ray tube controller (CRTC) of N-MOS (including H-MOS) technology for the control of more than 80 signs per line, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 62 × 25 mm, with not more than 68 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: AM 8052 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Cathode-ray tube controller (CRTC) of bipolar technology, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 15 × 55 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: SCB 2675 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit for cathode-ray tubes or liquid-crystal displays (CRT and LCD controller) of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 84 connecting pins or contact areas, and bearing: — an identification marking consisting of or including the following combination of figures and letters: V 6355-DJ or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Driver circuit for liquid crystal displays (LCD-driver) of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 14 × 14 mm, comprising not more than 64 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: LC 7582 or — other identification codes relating to devices which comply with this description	0
ex 8542 11 91	Programmable advanced video display controller (AVDC) of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, contained in a housing whose external dimensions do not exceed 15 × 55 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: SCN 2674 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 91	Video gate arrays programmed to control graphics and memory, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 35 × 35 mm, with not more than 144 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combination of figures and letters: PVGA 82 C 451 82 C 452 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Colour selection controller of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 19 × 52 mm, with not more than 44 connecting pins or contact areas and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91 *(cont'd)*	— an identification marking consisting of or including the following combination of figures and letters: 82 C 433 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Monolithic integrated circuit with at least 16 analog switching elements, of C-MOS technology, for controlling signals in the range of 20 to 20 000 Hz, capable of dealing with signals up to 3 V with a distortion of not more than 0,05 % over the whole frequency range at a voltage of 1 V, contained in a housing the exterior dimensions of which do not exceed 16 × 40 mm, with not more than 42 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: TC 9164 N TC 9177 P TC 9184 P or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Analog-digital monolithic circuit, capable of controlling brushless motors and keeping their speed constant, contained in a housing the exterior dimensions of which do not exceed 9 × 25 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: MGA 3015 A SSI 590 UC 1633 UC 1634 UC 3633 UC 3634 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Analog-digital monolithic integrated circuit of bipolar technology, for damping the oscillations of stepping motors during the positioning phase, contained in a housing the exterior dimensions of which do not exceed 18 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of letters: STEDA or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Controller for servo-devices of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 54 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: KM 3702 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Four-channel control circuit of C-MOS technology, for maintaining a constant electromagnetic traction force with incorporated diodes and a storage capacity of 4 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 7 × 22 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: UCN 5813 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Eight-channel control circuit of C-MOS technology, for maintaining a constant electromagnetic traction force with incorporated diodes and a storage capacity of 8 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 9 × 28 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: UCN 5801 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit of TTL technology for the firing of magnetic print hammers, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 23 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 801379-002 810751-001 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	8-bit (octal) dynamic memory bipolar driver, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 33 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 2965 AM 2966 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Timing control unit (TCU) with two-phase cycle for central processing unit (CPU) and memory management unit (MMU), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: NS 32201 NS 32 C 201 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Driver circuit for writer signals for magnetic tape storage units, of bipolar technology in the form of a monolithic integrated circuit obtained in a housing the exterior dimensions of which do not exceed 29 × 11 mm with not more than 22 connecting pins and bearing: — an identification marking consisting of or including the following combination if figures and letters: VT 211 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control and interface circuit between a 32-bit microprocessor and a floating point coprocessor of CMOs technology in the form of a monolithic integrated circuit contained in a housing, the exterior dimensions of which do not exceed 54 × 54 mm, with not more than 299 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: CY 7 C 608 L 64802 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control and interface operating at 12 MHz circuit of C-MOS technology, consisting of a clock generator, a bus controller for a microprocessor, a timer, two programmable interrupt controllers and an interface for numeric coprocessor, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 × 30 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combinations of figures: 82230 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Control circuit for bus interface of MOS technology functioning as an adaptor between the central unit and the external control units, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 63 × 26 mm, with not more than 68 connecting pins on contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: WD 33 C 92 WD 33 C 93 NCR 5380 NCR 5381 NCR 53 C 80 NCR 53 C 90 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Interface and control circuit for Manchester-coded data, of Schottky technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 14 mm, with not more than 20 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: TMS 38052 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Bus interface circuit with a programmable data transfer rate, of N-MOS (including H-MOS) technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 27 x 27 mm, with not more than 100 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: TMS 38030 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Serial and parallel interface bus circuit for communication between the central processing unit and a peripheral, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 26 x 26 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 1820-5022 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Subscriber line interface circuit (SLIC) with a high voltage rating of not less than 200 V, with direct internal relay drive, in the form of a monolothic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 x 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HC 5504 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Enhanced programmable communications interface (EPCI), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 x 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 2661 68661 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Interface circuit between 32-bit microprocessors and 16-bit peripheral units and D-RAM controller, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 30 x 30 mm, with no more than 132 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures: 82335 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Interface circuit for the synchronization of data flow from a hard-disk drive, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 35 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: DP 8462 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Analog-digital monolithic integrated circuit of bipolar technology for interface signals between the peripheral hard-disk, memory unit and the central unit, contained in a housing the exterior dimensions of which do not exceed 15 × 50 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 581 C or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Interface circuit of C-MOS technology for signals between peripheral hard-disk memory units and central units, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 28 × 53 mm, with not more than 80 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: OMTI 5080 (OMTI 20508) OMTI 5090 (OMTI 20509) WD 11 C 00-17 WD 14 C 00-17 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Encoder/decoder serial interface circuit for hard-disk drives, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 37 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AIC 250 AIC 270 DP 8463 B OMTI 5027 (OMTI 20527) OMTI 5070 (OMTI 20507) or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Serial interface, capable of implementing the data stream encoding, decoding and associated control functions for a local area network, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91 *(cont'd)*	8002 8023 82501 82 C 501 AM 7991 COM 9032 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Station digital interface circuit for parallel-to-serial or serial-to-parallel conversion of digital signals in telephone sets, of C-MOS technology (C-MOS STID), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins, and bearing: — an identification marking consisting of or including the following combination of figures and letters: WCC 295 G or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit in C-MOS technology, for the control of communication lines comprising a numerical bus, two independent receivers and a transmitter consisting of a first-in first-out (FIFO) memory, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 20 × 52 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: HS 3282 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface for graphic controllers, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 84 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of letters: PBI or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit of bipolar technology with 8-, 9- or 10-bit registers, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 9 × 34 mm, with not more than 24 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 29821 AM 29822 AM 29823 AM 29824 AM 29825 AM 29826 AM 29843 AM 29844 AM 29845 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91	Multiple bus interface circuit (multiple bus buffer) of low-power Schottky technolgy for interfacing the error correction and detection unit system data bus and dynamic random-access memory (D-RAM), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 20 × 33 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AM 2961 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit of AS or ALPS technology, for the management of address signals, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 26 × 26 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82 A 203 82 A 204 82 A 303 82 A 304 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit of AS or ALPS technology, for the management of data flow in the signal lines of the CPU, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 26 × 26 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: 82 A 205 82 A 305 82 A 436 82 A 442 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit of C-MOS technology, for the management of address signals, comprising a circuit with 4 × 2-input AND gates, two buffer circuits, two latch circuits, four independent transceivers, a 256 × 4-bit PROM, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 31 × 31 mm, with not more than 84 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: FE 3020 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 91	Bus interface circuit of C-MOS technology, for the management of I/0 data flow in signal lines, with four independent transceivers, a circuit with 4 × 2-input AND gates, a circuit with 4 × 2-input NAND gates, a separator circuit, a flip-flop circuit, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 31 × 31 mm, with not more than 84 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 91 *(cont'd)*	— an identification marking consisting of or including the following combination of figures and letters: FE 3030 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Computing unit without an internal programme sequencer for the multiplication or processing of fixed and floating point numbers, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 42 × 42 mm, with not more than 144 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: ADSP 3210 ADSP 3220 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	8 × 8-bit multiplier accumulator (MAC) of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 62 × 16 mm, with not more than 48 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: ADSP-1008 A or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Hard-disk data separator (HDDS), in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 37 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DP 8460-2 DP 8460-3 DP 8460-4 DP 8465 HDC 9226 WD 10 C 20 WD 10 C 21 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Address comparator consisting of one or more static random-access memories (S-RAM), a parity generator, a parity checker and one or more comparators, af C-MOS technology, in the form of a monolithic integrated circuit contained in a housing the exterior dimensions of which do not exceed 20 × 65 mm, with not more than 48 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: SN 74 ACT 2152 SN 74 ACT 2154 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99	Six- or eight-channel read/write signal generator for hard-disk drives, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 13 × 13 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: SSI 117 SSI 501 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Receiver/transmitter of Schottky technology, for Manchester-coded data, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 28 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: TMS 38051 TMS 38053 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Dual universal asynchronous receiver/transmitter (DUART) of MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 53 mm, with not more than 44 connecting pins and bearing: — an identification marking consisting of or including the following combination of figure: 2681 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Monolithic integrated circuit in N-MOS technology (including H-MOS) for the display of graphic symbols on a cathode-ray tube operating in stroke mode, contained in a housing the exterior dimensions of which do not exceed 28 × 61 mm, with not more than 68 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: 96 114 898 96 114 899 96 149 135 FCD 28 042 277 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Sequential control and generating circuit of C-MOS technology for the memory display, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 19 × 52 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: 82 C 432 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99	Demodulator for phase-shifted signals, of bipolar technology, with a clock signal generator and a circuit for parallel to serial conversion, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15 × 28 mm, with not more than 30 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TA 8662 or — an identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Demodulator/tone-decoder of bipolar technology for frequency decoding, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10 × 21 mm, with not more than 14 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: XR 2211 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Encoder/decoder circuit of C-MOS technology, using Manchester code (MED) for the transmission of data in continuous flux with a repeater mode, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 33 mm, with not more than 20 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HD 6409 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Encoder/decoder of N-MOS (including H-MOS) technology, for the conversion of data into serial or parallel signals, consisting of an arithmetic logic unit (ALU) and a read-only memory (ROM) with a storage capacity of 128 Kbits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15 × 60 mm, with not more than 48 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: TMS 38020 TMS 38021 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Data synchronizer and encoder/decoder of bipolar technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 13 × 13 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures or letters: SSI 532 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Pulse code modulation (PCM) codec of N-MOS (including H-MOS) technology, consisting of a sample and hold circuit digital-to-analogue converter, comparator, successive approximation register and logic function to interface to a full duplex PCM link, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 11 × 29 mm, with not more than 22 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99 *(cont'd)*	— an identification marking consisting of or including the following combination of figures and letters: 2911 A-1 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 99	Subscriber line audio-processing circuit (SLAC) with two digital signal processors, an analog-to-digital converter and a digital-to-analog converter, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AM 7901 AM 7905 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 99	Analog-to-digital signal converter, containing amplifiers, D/A and A/D converters with a supply voltage of 12 V ± 10 % and a digital serial interface with asynchronous receiver/transmitter, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 18 × 18 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 75002 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	16-bit digital-to-analog converter, incorporating a reference voltage of bipolar technology, with 16 parallel inputs, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DAC 700 DAC 701 DAC 702 DAC 703 or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 99	Analog-to-digital converter for the calculation of the average value of variable wave-forms, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 10 mm, with not more than 14 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 536 A or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	8-bit analog-to-digital parallel converter, of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 39 mm, with not more than 28 connecting pins or contact areas, and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99 *(cont'd)*	— an identification marking consisting of or including the following combinations of figures and letters: MP 7683 MP 7684 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	12-bit analog-to-digital converter, incorporating a voltage reference and clock, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 40 × 16 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 574 A or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	16-bit analog-to-digital converter of C-MOS technology, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 54 mm, with not more than 44 connecting pins or contact areas, and bearing: — an identification marking consisting of or including one the following combinations of figures and letters: CS 5016 CSZ 5116 CSZ 5316 CSZ 5126 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	7-channel analog-to-digital converter with a capacity of 15 bits per channel, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 18 mm, with not more than 44 connecting pins or contact areas, and bearing: — an identification marking consisting of or including the following combination of figures and letters: MAX 133 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Pulse code modulation (PCM) transmit/receive filter of N-MOS (including H-MOS) technology, consisting of two filters of a PCM line or trunk termination, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10 × 21 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: D 2912 A or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 11 99	Clock/calendar circuit of C-MOS technology, incorporating a quartz crystal oscillator, independent timer recorders and a timer, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99 *(cont'd)*	— an identification marking consisting of or including one of the following combinations of figures or figures and letters: MM 581 74 A MM 58167 58274 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Clock circuit of C-MOS technology, with audio and hour-count output, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: SVM 5530 7910 or — other identification markings relating to devices complying with the abovementioned description, for use in the manufacture of goods falling within Chapter 91 (a)	0
ex 8542 11 99	Clock/calendar circuit of C-MOS technology incorporating a programmable generator for periodic interruptions and square waves, and a static random-access memory with a storage capacity of 400 bits, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 18 × 34 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combination of figures and letters: MC 146 818 DS 1287 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Clock circuit of C-MOS technology consisting of a 64-bit clock counter, a 64-bit state register, an oscillator and a control logic circuit for the reading and writing cycles, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 59 × 16 mm, with not more than 48 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TOD 0815 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Function generator of bipolar technology for the generation of variable wave-forms, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10 × 21 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: XR 2206 XR 8038 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Digital signal synthesizer of C-MOS technology with one frequency generator producing one signal and able to output one sound, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 25 mm, with not more than 18 connecting pins and bearing:	

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99 *(cont'd)*	— an identification marking consisting of or including the following combination of figures and letters: UMC 3511 A or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Programmable digital signal synthesizer of C-MOS technology with 13 frequency generators each producing up to five sounds and an output capacity of up to 65 sounds, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 15 × 50 mm, with not more than 40 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: DPS 6401 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Signal synthesizer of N-MOS (including H-MOS) technology with a frequency generator, a memory of 15 instrumental tones, a digital-to-analog converter and a quartz oscillator in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 25 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: YM 2413 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Phoneme speech synthesizer of C-MOS technology, with a supply current of less than 10 mA, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CD 54121 N2L, CM 54104, SC 01 CD 54122 N2L, CM 54145 N2L, SSI 263 CD 54123 N2L, CM 54146 N2L CD 54147 N2L, CM 54166 N2L or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Monolithic integrated circuit (read/write data processor circuit) for the amplification and conversion of read signals and conversion of write signals for hard-disk drives, contained in a housing the exterior dimensions of which do not exceed 19 × 38 mm, with not more than 28 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of letters and figures: SSI 540 SSI 541 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 11 99	Programmable amplifier, of bipolar technology for signals on a digital communications bus, in the form of monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 21 mm, with not more than 44 connecting pins or contact areas and bearing: — an identification marking consisting of or including the following combination of figures and letters: HS 3182 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Repeater circuit, of bipolar technology for the regeneration of pulse-code-modulated signals, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 10 × 21 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: XR C 240 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Circuit for the recording and reproduction of speech, working at a programmable speed of not less than 8 Kbits/sec, with an amplifier and a 10 bit D/A converter, in the form of a monolithic integrated circuit of C-MOS technology, contained in a housing the exterior dimensions of which do not exceed 18 × 18 mm, with not more than 60 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: T 6668 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 11 99	Smoke detector operating in a temperature range between at least − 20 to + 50 °C, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 23 × 9 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CS 235 V 24216 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 20	Amplifier, in the form of a monolithic integrated analog circuit, the exterior dimensions of which do not exceed 3 × 3 mm for use in the manufacture of products falling within code 9021 40 00 (a)	0
ex 8542 19 20	FM receiver/amplifier of bipolar technology, in the form of an unmounted analog monolithic integrated circuit, having dimensions which do not exceed 4 × 6 mm For the manufacture of products falling within heading 9021 40 00 (a)	0
ex 8542 19 30	Amplifier, in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 2 × 4 × 4 mm, with not more than 10 connecting pins and bearing:	

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8542 19 30 *(cont'd)*	— an identification marking consisting of or including one of the following combinations of figures and letters: C 05 V 35 or — other identification markings relating to devices complying with the abovementioned description for the manufacture of products falling within code 9021 40 00 (a)	0
ex 8542 19 30	Amplifier with an input current of not more than 80 nA, in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 8 x 11 mm or the diameter of which does not exceed 10 mm, with not more than 8 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: OPA 37, OPA 111, OPA 121 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 30	Electronically adjustable differential amplifiers for at least the full range of signals from 0 to not less than 400 MHz, in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 11 x 11 mm, with not more than 16 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 0078-10 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 30	Amplifiers for the range of frequencies from 10 Hz to 30 kHz with a gain of not less than 85 dB in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 19 x 8 mm, with not more than 8 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: M 5218 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 30	Winchester disk drive amplifier for magnetic heads, in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 7 x 7mm, with not more than 10 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: A 2480 FC or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 30	Amplifier with a programmable gain factor, in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 30 x 45 mm, with not more than 32 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: 3606 G or — other identification markings relating to devices complying with the abovementioned description	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code	Description	Rate of autonomous duty (%)
ex 8542 19 30	Thermocouple amplifier for instrumentation control at temperatures from 0 to 50 °C, incorporating an alarm system, in the form of a monolithic integrated circuit, contained in a housing the external dimensions of which do not exceed 20 × 8 mm, with not more than 14 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: AD 594 AD 595 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 70	Interface and control circuit of C-MOS technology, for the generation of graphic symbols on a cathode-ray tube in the form of a monolithic integrated analog circuit, contained in a housing the external dimensions of which do not exceed 9 × 29 mm, with not more than 28 connecting pins and bearing: — an identification code consisting of or including the following combination of figures and letters: MN 1297 or — other identification relating to devices which comply with the abovementioned description	0
ex 8542 19 90	Read data signal processor for disk drives, of bipolar technology, in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 13 × 12 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: VM 443 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Filter unit, of C-MOS technology, for signals with a frequency of 300 Hz or more but not exceeding 3 000 Hz, consisting of a receiver/transmitter, an analog-to-digital converter, a dual-tone multifrequency generator (DTMF) and interface registers for a central processing unit (CPU), in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 14 × 21 mm, with not more than 60 connecting pins and bearing: — an identification marking consisting of or containing the following combination of figures and letters: STC 9130 F or — other identification markings relating to circuits complying with the abovementioned description	0
ex 8542 19 90	Four-channel track-and-hold circuit of C-MOS technology, in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 9 × 25 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: CS 31412 or: — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Pre-magnetization control circuit for audio-frequency magnetic tapes, of bipolar technology, in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 26 × 8 mm, with not more than 18 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 19 90 *(cont'd)*	— an identification marking consisting of or including the following combination of figures and letters: PC 1297 CA or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Monolithic integrated analog circuit for the reduction of audio noise by 14 dB, contained in a housing the exterior dimensions of which do not exceed 26 × 7 mm, with not more than 18 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: HA 12043 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	AM and FM receiver, of bipolar technology, in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 14 × 37 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: CXA 1030 P CXA 1240 P or — other identification markings relating to devices complying with the abovementioned description	7
ex 8542 19 90	Two channel audio signal volume and balance controller, in the form of a monolithic integrated analog circuit, contained in a housing whose dimensions do not exceed 19 × 8 mm, with not more than 14 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: M 51523 or — other identification markings relating to monolithic integrated analog circuits complying with the abovementioned description	0
ex 8542 19 90	Delay line, of C-MOS technology, for drop-out compensation of video signals, in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 10 × 7 mm, with not more than eight connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: MSM 6965 RS or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Switch-unit, of bipolar technology, for audio signals, having a distortion of not more than 0,005 %, comprising two control units and two alternating switches, in the form of a monolithic integrated analog circuit with an audio-frequency switching function, contained in a housing whose dimensions do not exceed 13 × 8 mm, with not more than 10 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: TK 15022 Z or — other identification markings relating to monolithic integrated analog circuits complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 19 90	Monolithic integrated analog circuit of bipolar technology for the overload protection of telephone exchanges, contained in a housing the exterior dimensions of which do not exceed 11 x 10 mm, with not more than three connecting pins and bearing: — an identification marking consisting of or including the following combination of figures: 1515 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Frequency generator of bipolar technology, with an operating voltage of not less than 40 and not more than 130 V AC, which generates signals oscillating between 512 (± 22 %) and 640 Hz (± 22 %) at a 10 Hz rate, in the form of a monolithic integrated analog circuit, contained in a housing the external dimensions of which do not exceed 9 x 11 mm, with not more than eight connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: QMV 155 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Temperature transducer in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 6 x 4 mm, with not more than three connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 590 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Monolithic integrated analog circuit of bipolar technology for driving direct-current motors working at 18 V/1,6 A maximum, contained in a housing the exterior dimensions of which do not exceed 9 x 26 mm, with not more than 10 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: BA 6109 BA 6209 — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Monolithic integrated analog circuit of C-MOS technology for controlling the speed of linear or rotary motors and the positioning of magnetic heads, contained in a housing the exterior dimensions of which do not exceed 14 x 38 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: A 2460 A 2461 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 19 90	Monolithic integrated analog circuit of bipolar technology for driving linear motors or motors with rotating arms, working at 20 V/2,5 A maximum, contained in a housing the exterior dimensions of which do not exceed 17 × 33 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: EL 2007 EL 2017 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Image sensor consisting of a row of not more than 3 648 photosensitive areas, a matrix linked to shift registers and storage electrodes, in the form of a monolithic integrated analog circuit, contained in a housing the exterior dimensions of which do not exceed 12 × 43 mm, with not more than 22 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: TCD 103 TCD 105 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 19 90	Interline charge-coupled image sensor with not less than 250 000 and not more than 291 000 photosensitive areas, in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 21 × 32 mm, with not more than 20 connecting pins or contact areas and bearing: — an identification marking consisting of or including one of the following combinations of figures or figures and letters: ICX 018 ICX 021 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 10	32-bit microprocessor in C-MOS technology, consisting of a single substrate layer on which are mounted two chips, comprising a central processing unit (CPU) and a memory unit, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 33 × 76 mm, with not more than 60 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures: 57-00000 57-19400 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 50	Amplifier for the frequency range 20 to 20 000 Hz, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 45 × 80 mm, with not more than 30 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: STK 4041 STK 4151 STK 4201 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	Description	Rate of autonomous duty (%)
ex 8542 20 50	Amplifier with an isolation tension of not less than 750 V in the form of a monolithic integrated circuit, contained in a housing the exterior dimensions of which do not exceed 16 × 52 mm, with not more than 40 connecting pins and a leakage of not more than 1 μA and bearing: — an identification marking consisting of or including the following combination of figures and letters: ISO 100 ISO 102 ISO 106 ISO 120 ISO 121 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 90	16-bit digital-to-analog converter, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 17 × 39 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: DAC 705 DAC 706 DAC 707 DAC 708 DAC 709 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 90	Video digital-to-analog converter (VDAC) with a maximum conversion time of 10 ns, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 20 × 35 mm, with not more than 24 connecting pins and bearing: — an identification marking consisting of or including one of the following combinations of figures and letters: VDAC 0405 H VDAC 0605 H VDAC 0805 H or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 90	Four-channel digital-to-analog converter, each channel having a capacity of 12 bits, in the form of a hybrid integrated circuit, contained in a housing the external dimensions of which do not exceed 41 × 21 mm, with not more than 28 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: AD 390 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 90	Circuit for the demodulation of signals and noise-reduction, in the form of a hybrid integrated circuit, contained in a housing the exterior dimensions of which do not exceed 8 × 44 mm, with not more than 21 connecting pins and bearing: — an identification marking consisting of or including the following combination of figures and letters: STK 3400 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 20 90	Subscriber-connection units (crosspoint switch) with not less than four and not more than 12 switches and an operating voltage of at least 150 V, in the form of a hybrid integrated circuit, contained in a housing the dimensions of which do not exceed 92 × 41 mm, with not more than 94 connecting pins and bearing:	

CN code	Description	Rate of autonomous duty (%)
ex 8542 20 90 *(cont'd)*	— an identification marking consisting of or including one of the following combinations of figures: 904 719 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8543 80 90	Electromagnetic displays consisting of seven electromagnetic coils, which by means of the residual magnetism in the stators provide indefinite memory, and seven pivoting light-reflecting segments each of which is attached to a bar magnet. The display is contained in a housing the exterior dimensions of which do not exceed 28 × 36 × 50 mm	0
ex 8543 80 90	Modulators for the range from 0,5 to 5 MHz, contained in a housing the external dimensions of which do not exceed 74 × 48 mm	0
ex 8544 19 90	Insulated winding wire of aluminium of a purity of not less than 99,5 % by weight, neither laquered, varnished nor enamelled, with a total enamelled, with a total thickness of not less than 0,15 mm and not more than 0,16 mm	0
ex 9001 10 10 ex 9001 10 90	Image reverser made up from an assembly of optical fibres	0
ex 9001 20 00	Material consisting of a polarizing film, supported on one or both sides by transparent material	0
ex 9001 90 90	Octagonal Fresnel lens of acrylic resin unmounted, for the manufacture of overhead projectors (a)	0
ex 9002 11 00	Adjustable lens unit, having a focal length of between 115 and 140 mm, a diameter of not less than 120 mm and not more than 130 mm, and comprising a combination of between four and eight glass or methacrylic lenses, each lens coated on at least one side with a magnesium fluoride layer, for use in the manufacture of video projectors (a)	0
ex 9001 90 91	Optical element comprising an octagonal Fresnel lens, for the manufacture of overhead projectors (a)	0
ex 9013 80 00	Liquid crystal devices (LCDs) consisting of a layer of liquid crystals between two glass sheets or plates, with a minimum of seven and a maximum of 120 figures or letters, whose exterior dimensions are: — 52 × 22 mm, or — 67 × 27 mm, or — 63 × 22 mm, or — 18,5 × 52 mm, or — 18,5 × 61 mm, or — 73,7 × 55,8 mm, with not more than 192 connecting pins or contact areas, for use in the manufacture of calculators (a)	0
ex 9021 30 90	Heart valves and parts thereof	0
ex 9021 30 90	Vascular protheses, neither woven nor knitted, of which the largest opening has an internal diameter not exceeding 8 mm	0
ex 9021 90 10	Receivers for hearing aids, contained in a housing the external dimensions of which excluding connecting points do not exceed 5 × 6 × 8 mm	0
ex 9110 12 00	Assembly consisting of a printed circuit on which are mounted one quartz oscillator, at least one watch circuit and at least one capacitor, of a thickness not exceeding 5 mm for the manufacture of products falling within Chapter 91 (a)	0
ex 9110 90 00 ex 9114 90 00	Assembly consisting of a printed circuit on which is mounted a watch circuit or a watch circuit and a quartz oscillator, with a thickness not exceeding 5 mm, for the manufacture of products falling within Chapter 91 (a)	0
ex 9608 91 00	Non-fibrous plastic pen-tips with an internal channel	0
ex 9613 90 00	Piezo-electric ignition mechanism	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.