**This document is meant purely as a documentation tool and the institutions do not assume any liability for its contents**

►**B**

# COUNCIL REGULATION (EC) No 1255/96

## of 27 June 1996

## temporarily suspending the autonomous Common Customs Tariff duties on certain industrial and agricultural products

(OJ L 158, 29.6.1996, p. 1)

Amended by:

| | | Official Journal | | |
|---|---|---|---|---|
| | | No | page | date |
| ►**M1** | Council Regulation (EC) No 2484/96 of 20 December 1996 | L 341 | 1 | 30.12.1996 |
| ►**M2** | Council Regulation (EC) No 1186/97 of 27 June 1997 | L 172 | 1 | 30.6.1997 |
| ►**M3** | Council Regulation (EC) No 2590/97 of 16 December 1997 | L 355 | 1 | 30.12.1997 |
| ►**M4** | Council Regulation (EC) No 1359/98 of 29 June 1998 | L 186 | 1 | 30.6.1998 |
| ►**M5** | Council Regulation (EC) No 2797/98 of 17 December 1998 | L 352 | 1 | 29.12.1998 |
| ►**M6** | Council Regulation (EC) No 1381/1999 of 28 June 1999 | L 165 | 1 | 30.6.1999 |
| ►**M7** | Council Regulation (EC) No 20/2000 of 17 December 1999 | L 8 | 1 | 12.1.2000 |

Corrected by:

►**C1** Corrigendum, OJ L 107, 7.4.1998, p. 16 (2590/97)

►**C2** Corrigendum, OJ L 125, 19.5.1999, p. 40 (2797/98)

▼B

# COUNCIL REGULATION (EC) No 1255/96

## of 27 June 1996

## temporarily suspending the autonomous Common Customs Tariff duties on certain industrial and agricultural products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 28 thereof,

Having regard to the proposal from the Commission,

Whereas production in the Community of the products specified in this Regulation is currently inadequate or non-existent; whereas producers thus cannot meet the needs of user industries in the Community;

Whereas it is in the interest of the Community to suspend partially or totally the autonomous Common Customs Tariff duties for these products;

Whereas the decision to suspend such autonomous duties should be taken by the Community;

Whereas the Regulations temporarily suspending the autonomous Common Customs Tariff duties on certain industrial and agricultural products have largely renewed previous measures; whereas, therefore, in the interests of rationalizing implementation of the measures concerned, it would seem appropriate not to limit the period of validity of this Regulation as its scope can be adapted and products added to or removed from the list through a Council Regulation, if necessary;

Whereas the amendments to the combined nomenclature and the Taric codes do not give rise to any substantive amendment; whereas, for reasons of simplification, provision should be made to empower the Commission, following receipt of the opinion of the Customs Code Committee, to make the necessary amendments and technical adaptations of the Annex to this Regulation, including the publication of a consolidated version,

HAS ADOPTED THIS REGULATION:

*Article 1*

The autonomous Common Customs Tariff duties for the products listed in the Annex hereto shall be suspended at the level indicated against each of them.

*Article 2*

The technical adaptations, including publication of a consolidated version, arising from amendments of the combined nomenclature and Taric codes shall be adopted by the Commission in accordance with the procedure laid down in Article 3.

*Article 3*

1. The Commission shall be assisted by the Customs Code Committee set up by Article 247 of Regulation (EEC) No 2913/92 [1].

2. The representative of the Commission shall submit to the Committee a draft of the measures to be taken. The Committee shall deliver its opinion on the draft within a time limit which the chairman may lay down according to the urgency of the matter. The opinion shall be delivered by the majority laid down in Article 148 (2) of the Treaty in the case of decisions which the Council is required to adopt on a proposal from the Commission. The votes of the representatives of the

[1] OJ No L 302, 19. 10. 1992, p. 1. Regulation as amended by the 1994 Act of Accession.

▼B

Member States within the Committee shall be weighted in the manner set out in that Article. The chairman shall not vote.

3. The Commission shall adopt measures which apply immediately.

However, if these measures are not in accordance with the opinion of the Committee, they shall be communicated by the Commission to the Council forthwith. In that event, the Commission shall defer application of the measures which it has decided for three months from the date of such communication.

The Council, acting by a qualified majority, may take a different decision within the period referred to in the previous indent.

*Article 4*

This Regulation shall enter into force on the day following its publication in the *Official Journal of the European Communities*.

It shall apply from 1 July 1996.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

▼**M7**

*ANNEX*

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 0603 90 00<br>ex 0604 99 10<br>ex 0604 99 90 | 10<br>10<br>10 | Flowers, flower buds, foliage, leaves and other parts of plants, not further prepared than dried, dyed or bleached, for use in the manufacture of pot pourri of subheading 3307 49 00 (a) | 0 |
| ex 0710 21 00 | 10 | Peas in pods, of the species *Pisum sativum* of the variety *Hortense axiphium*, frozen, of a thickness not exceeding 6 mm, to be used, in their pods, in the manufacture of prepared meals (a) (b) | 0 |
| ex 0711 90 60<br>ex 0711 90 60 | 11<br>91 | Mushrooms, excluding mushrooms of the species *Agaricus* spp., provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry (a) | 0 |
| ex 0712 30 00<br>ex 0712 30 00 | 17<br>24 | Mushrooms, excluding mushrooms of the species *Agaricus* spp., dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale (a) (b) | 0 |
| ex 0713 33 90 | 20 | Beans, white, dried, of the species *Phaseolus vulgaris*, of which not more than 2% by weight are retained by a screen with apertures of a diameter of 8 mm | 0 |
| ex 0804 10 00<br>ex 0804 10 00 | 11<br>21 | Dates, fresh or dried, for the processing industry, other than for the production of alcohol (a) | 0 |
| ex 0804 10 00<br>ex 0804 10 00 | 12<br>22 | Dates, fresh or dried, for packing for retail sale into immediate packings of a net content not exceeding 11 kg (a) | 0 |
| ex 0810 40 50 | 10 | Fruit of the species *Vaccinium macrocarpon*, fresh | 0 |
| ex 0810 90 85 | 10 | Rose-hips, fresh | 0 |
| 0811 90 50<br>0811 90 70<br>ex 0811 90 95<br>ex 0811 90 95 | <br><br>66<br>67 | Fruit of the genus *Vaccinium*, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter | 0 |
| ex 0811 90 95 | 40 | Rose-hips, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter | 0 |
| ex 1511 10 10<br>ex 1511 90 19<br>ex 1511 90 91<br>ex 1513 11 10<br>ex 1513 19 30<br>ex 1513 21 11<br>ex 1513 29 30 | 10<br>10<br>10<br>10<br>10<br>10<br>10 | Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of:<br>— industrial monocarboxylic fatty acids of subheading 3823 19 10,<br>— mixtures of methyl esters of fatty acids of subheading 3824 90 95,<br>— methyl esters of fatty acids of heading 2915 or 2916<br>or<br>— stearic acid of subheading 3823 11 00 (a) | 0 |
| ex 1518 00 91 | 10 | Soya-bean oil, modified with maleic acid, for the manufacture of cosmetic products (a) | 0 |
| ex 2707 99 11 | 10 | Crude light oils containing by weight:<br>— 10 % or more of vinyltoluenes,<br>— 10 % or more of indene<br>and<br>— 1 % or more but not more than 5 % of naphthalene | 0 |
| ex 2805 30 10 | 10 | Alloy of cerium and other rare-earth metals, containing by weight 47 % or more of cerium | 0 |
| ex 2805 30 10 | 20 | Alloy of lanthanum and other rare-earth metals, containing by weight 43 % or more of lanthanum | 0 |
| ex 2805 30 90 | 10 | Lanthanum of a purity by weight of 99 % or more | 0 |
| ex 2811 19 80 | 10 | Sulfamidic acid | 0 |
| ex 2811 22 00 | 10 | Silicon dioxide in the form of powder, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (a) | 0 |
| ex 2811 29 90 | 10 | Tellurium dioxide | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 2812 90 00 | 10 | Nitrogen trifluoride | 0 |
| ex 2818 30 00 | 10 | Aluminium hydroxide oxide in the form of pseudo-boehmite | 4 |
| ex 2819 90 90 | 10 | Dichromium trioxide:<br>— of a specific surface of 37 $m^2/g$ or more (as determined by the BET method),<br>— of a purity by weight of 99,5 % or more calculated on the dry substance,<br>— of a specific gravity of 1,2 $g/cm^3$ or less,<br>for the manufacture of magnetic chromium dioxide (a) | 0 |
| ex 2820 90 90 | 10 | Manganese (II,III) oxide containing by weight 70 % or more of manganese | 0 |
| ex 2821 10 00 | 10 | Diiron trioxide, in the form of powder, of a purity by weight of 99,2 % or more, for the manufacture of goods of heading No 8504 (a) | 0 |
| ex 2823 00 00 | 10 | Titanium dioxide, of a purity by weight of 99,9 % or more, with an average grain-size of 1,2 μm or more but not exceeding 1,8 μm, for the manufacture of goods of heading No 8532 or 8533 (a) | 0 |
| ex 2825 50 00 | 10 | Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride | 0 |
| ex 2826 90 90 | 10 | Potassium hexafluorophosphate | 0 |
| ex 2827 39 90 | 10 | Copper monochloride of a purity by weight of 96 % or more but not exceeding 99 % | 0 |
| ex 2827 60 00 | 10 | Titanium tetraiodide | 0 |
| ex 2830 20 00 | 10 | Zinc sulphide containing:<br>— 20,0 mg/kg or less of chloride,<br>— 0,2 mg/kg or less of copper,<br>— 0,5 mg/kg or less of iron<br>and<br>— 1,0 mg/kg or less of lead | 0 |
| ex 2836 91 00 | 20 | Lithium carbonate, containing one or more of the following impurities at the concentrations indicated:<br>— 2 mg/kg or more of arsenic,<br>— 200 mg/kg or more of calcium,<br>— 200 mg/kg or more of chlorides,<br>— 20 mg/kg or more of iron,<br>— 150 mg/kg or more of magnesium,<br>— 20 mg/kg or more of heavy metals,<br>— 300 mg/kg or more of potassium,<br>— 300 mg/kg or more of sodium,<br>— 200 mg/kg or more of sulphates,<br>determined according to the methods specified in the European Pharmacopœia | 0 |
| ex 2837 19 00 | 10 | Zinc cyanide | 0 |
| ex 2839 90 00 | 10 | Lead silicate hydrate, of a lead content by weight of (84,5 ± 1,5) %, evaluated as lead monoxide, in the form of powder | 0 |
| ex 2843 90 90 | 20 | Palladium monoxide | 0 |
| ex 2843 90 90 | 30 | Mixture of palladium phthalocyanines | 0 |
| 2845 10 00 | | Heavy water (deuterium oxide) (*Euratom*) | 0 |
| 2845 90 10 | | Deuterium and compounds thereof; hydrogen and compounds thereof, enriched in deuterium; mixtures and solutions containing these products (*Euratom*) | 0 |

▼**M7**

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 2846 10 00<br>ex 3824 90 95 | 10<br>48 | Rare-earth concentrate containing by weight 60 % or more but not more than 95 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight | 0 |
| ex 2850 00 20 | 10 | Silane | 0 |
| ex 2903 30 80 | 10 | Carbon tetrafluoride (tetrafluoromethane) | 0 |
| ex 2903 30 80 | 20 | 1,1,1,2,3,3,3-Heptafluoropropane | 0 |
| ex 2903 30 80 | 30 | Perfluoroethane | 0 |
| ex 2903 30 80 | 40 | 1,1-Difluoroethane | 0 |
| ex 2903 59 90 | 10 | 1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo=[12.2.1.1$^{6,9}$.0$^{2,13}$.0$^{5,10}$]octadeca-7,15-diene, for use in the manufacture of polyamide, polyethylene, synthetic rubber or polystyrene (a) | 0 |
| ex 2903 59 90 | 20 | Hexachlorocyclopentadiene | 0 |
| ex 2903 69 90 | 10 | Di- or tetrachlorotricyclo[8.2.2.2$^{4,7}$]hexadeca-1(12),4,6,10,13,15-hexaene, mixed isomers | 0 |
| ex 2903 69 90 | 40 | 2,6-Dichlorotoluene, of a purity by weight of 99 % or more and containing:<br>— 0,001 mg/kg or less of tetrachlorodibenzodioxines,<br>— 0,001 mg/kg or less of tetrachlorodibenzofurans,<br>— 0,2 mg/kg or less of tetrachlorobiphenyls | 0 |
| ex 2903 69 90 | 50 | 1-(Chloromethyl)naphthalene | 0 |
| ex 2904 10 00 | 30 | Sodium *p*-styrenesulphonate | 0 |
| ex 2904 20 00 | 10 | Nitromethane | 0 |
| ex 2904 20 00 | 20 | Nitroethane | 0 |
| ex 2904 20 00 | 30 | 1-Nitropropane | 0 |
| ex 2904 20 00 | 40 | 2-Nitropropane | 0 |
| ex 2904 90 20 | 10 | Tosyl chloride | 0 |
| ex 2904 90 40 | 10 | Trichloronitromethane, for the manufacture of goods of subheading 3808 20 (a) | 0 |
| ex 2904 90 85 | 10 | Quintozene (ISO) | 0 |
| ex 2905 19 00<br>ex 3824 90 95 | 10<br>56 | Potassium *tert*-butanolate (potassium *tert*-butoxide), whether or not in the form of a solution in tetrahydrofuran | 0 |
| 2905 29 10 | | Allyl alcohol | 0 |
| ex 2905 39 80 | 10 | 2-Methylpropane-1,3-diol | 0 |
| ex 2905 49 10 | 10 | Ethylidynetrimethanol | 0 |
| 2906 11 00 | | Menthol | 0 |
| ex 2906 19 00 | 10 | Cyclohex-1,4-ylenedimethanol | 0 |
| ex 2906 19 00 | 20 | 4,4'-Isopropylidenedicyclohexanol | 0 |
| ex 2906 29 00 | 10 | 2,2'-(*m*-Phenylene)dipropan-2-ol | 0 |
| ex 2907 21 00 | 10 | Resorcinol | 0 |
| ex 2907 29 00 | 10 | Disodium 1,4-dihydroanthracene-9,10-diolate, in the form of an aqueous solution | 0 |
| ex 2907 29 00 | 20 | 4,4'-(3,3,5-Trimethylcyclohexylidene)diphenol | 0 |
| ex 2907 29 00 | 30 | 4,4',4"-Ethylidynetriphenol | 0 |
| ex 2907 29 00 | 40 | Mixture of isomers of methylenediphenol | 0 |
| ex 2907 29 00 | 50 | 6,6',6"-Tricyclohexyl-4,4',4"-butane-1,1,3-triyltri(*m*-cresol) | 0 |
| ex 2908 20 00 | 10 | Disodium 3-hydroxynaphthalene-2,7-disulphonate | 0 |
| ex 2908 20 00 | 20 | Dipotassium 7-hydroxynaphthalene-1,3-disulphonate | 0 |
| ex 2908 90 00 | 10 | 4-Nitroso-*o*-cresol | 0 |
| ex 2909 19 00 | 10 | 1,2-Bis(2-chloroethoxy)ethane | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 2909 30 90 | 10 | 4-(*p*-Tolyloxy)biphenyl | 0 |
| ex 2909 30 90 | 20 | 1,2-Bis(*m*-tolyloxy)ethane | 0 |
| ex 2909 30 90 | 30 | 1,2-Diphenoxyethane | 0 |
| ex 2909 44 00 | 10 | 2-Hexyloxyethanol | 0 |
| ex 2909 49 19 | 10 | 1-*tert*-Butoxypropan-2-ol | 0 |
| ex 2909 50 90 | 10 | 4-(2-Methoxyethyl)phenol | 0 |
| ex 2910 90 00 | 30 | 2,3-Epoxypropan-1-ol (glycidol) | 0 |
| ex 2910 90 00 | 40 | Perfluoroepoxypropane | 0 |
| ex 2910 90 00<br>ex 3824 90 95 | 60<br>59 | 1,2-Epoxyoctadecane, of a purity by weight of 82 % or more | 0 |
| ex 2912 29 00 | 10 | Terephthalaldehyde | 0 |
| ex 2912 49 00 | 10 | 3-Phenoxybenzaldehyde | 0 |
| ex 2914 19 90 | 10 | 3,3-Dimethylbutan-2-one | 0 |
| 2914 21 00 | | Camphor | 0 |
| ex 2914 29 00 | 10 | Estr-4-ene-3,17-dione | 0 |
| ex 2914 50 00 | 30 | 2'-Hydroxyacetophenone | 0 |
| ex 2914 50 00 | 40 | 4'-Hydroxyacetophenone | 0 |
| ex 2914 50 00 | 50 | 6'-Methoxy-2'-acetonaphthone | 0 |
| ex 2914 70 90 | 10 | 1-Chloro-3,3-dimethylbutan-2-one | 0 |
| ex 2914 70 90 | 30 | 4,4'-Dibromobenzil | 0 |
| ex 2915 29 00 | 10 | Antimony triacetate | 0 |
| ex 2915 39 90 | 20 | 5*α*-Bromo-6*β*-hydroxy-17-oxo-androstan-3*β*-yl acetate | 0 |
| ex 2915 39 90 | 30 | But-3-ene-1,2-diyl di(acetate) | 0 |
| ex 2915 40 00 | 10 | Vinyl chloroacetate | 0 |
| ex 2915 60 19 | 10 | 2,2,4-Trimethylpentane-1,3-diol monoisobutyrate | 0 |
| ex 2915 90 80 | 20 | Trimethyl orthoacetate | 0 |
| ex 2915 90 80 | 30 | 2-Ethylbutyric acid | 0 |
| ex 2915 90 80 | 40 | Nonanoic acid (pelargonic acid) | 0 |
| ex 2916 12 90 | 10 | 2-*tert*-Butyl-6-(3-*tert*-butyl-2-hydroxy-5-methylbenzyl)= -4-methylphenyl acrylate | 0 |
| ex 2916 12 90 | 20 | 2-Ethoxyethyl acrylate | 0 |
| ex 2916 12 90 | 30 | Isobutyl acrylate | 0 |
| ex 2916 14 90 | 10 | 2,3-Epoxypropyl methacrylate | 0 |
| ex 2916 19 80 | 20 | Methyl 3,3-dimethylpent-4-enoate | 0 |
| ex 2916 20 00 | 10 | Methyl 3-(2,2-dichlorovinyl)-2,2-dimethylcyclopropane-carboxylate | 0 |
| ex 2916 20 00 | 30 | Empenthrin (ISO) | 0 |
| ex 2916 39 00 | 10 | Methyl 3-chlorobenzoate | 0 |
| ex 2916 39 00 | 20 | 3,5-Dichlorobenzoyl chloride | 3,6 |
| ex 2916 39 00 | 40 | Vinyl 4-*tert*-butylbenzoate | 0 |
| ex 2916 39 00 | 50 | 3,5-Dimethylbenzoyl chloride | 0 |
| ex 2916 39 00 | 60 | 4-Ethylbenzoyl chloride | 0 |
| ex 2917 11 00 | 20 | Bis(*p*-methylbenzyl) oxalate | 0 |
| ex 2917 19 90 | 20 | Sodium 1,2-bis(cyclohexyloxycarbonyl)ethanesulphonate | 0 |
| ex 2917 19 90 | 40 | Dodecanedioic acid, of a purity by weight of more than 98,5 % | 0 |
| ex 2917 19 90 | 50 | Glutaric anhydride | 0 |
| ex 2917 20 00 | 30 | 1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicar-boxylic anhydride | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 2917 39 80 | 10 | Dimethyl naphthalene-2,6-dicarboxylate | 0 |
| ex 2917 39 80 | 20 | Benzene-1,2,4,5-tetracarboxylic acid (pyromellitic acid) | 0 |
| ex 2917 39 80 | 30 | Benzene-1,2:4,5-tetracarboxylic dianhydride (pyromellitic dianhydride) | 0 |
| ex 2918 13 00 | 10 | L-(-)-Di-*p*-toluoyltartaric acid | 0 |
| ex 2918 17 00 | 10 | *R*-Phenylglycolic acid (D-mandelic acid) | 0 |
| ex 2918 19 99 | 40 | L-Malic acid | 0 |
| ex 2918 29 10 | 10 | 2-Hydroxy-1-naphthoic acid | 0 |
| ex 2918 29 50 | 10 | Gallic acid, of a purity by weight of 98,5 % or more calculated on the dry weight (measured by acidimetry) | 0 |
| ex 2918 29 90 | 10 | Hexamethylene bis[3-(3,5-di-*tert*-butyl-4-hydroxyphenyl)-propionate] | 0 |
| ex 2918 90 90 | 10 | 3,4-Epoxycyclohexylmethyl 3,4-epoxycyclohexanecarboxylate | 0 |
| ex 2919 00 90 | 10 | 2,2'-Methylenebis(4,6-di-*tert*-butylphenyl) phosphate, monosodium salt | 0 |
| ex 2920 10 00 | 10 | Fenitrothion (ISO) | 0 |
| ex 2920 10 00 | 20 | Tolclofos-methyl (ISO) | 0 |
| ex 2920 90 10 | 10 | Diethyl sulphate | 0 |
| 2920 90 30 | | Trimethyl phosphite | 0 |
| ex 2920 90 85 | 10 | *O,O'*-Dioctadecyl pentaerythritol bis(phosphite) | 0 |
| ex 2920 90 85 | 30 | *O,O'*-Bis(2,4-di-*tert*-butylphenyl)pentaerythritol bis(phosphite) | 0 |
| ex 2921 19 80 | 10 | Triallylamine | 0 |
| ex 2921 19 80 | 20 | Ethyl(2-methylallyl)amine | 0 |
| ex 2921 29 00 | 10 | *N,N,N',N'*-Tetrabutylhexamethylenediamine | 0 |
| ex 2921 29 00 | 20 | Tris[3-(dimethylamino)propyl]amine | 0 |
| ex 2921 29 00 | 30 | Bis[3-(dimethylamino)propyl]methylamine | 0 |
| ex 2921 30 99 | 10 | Dicyclohexyl(methyl)amine | 0 |
| ex 2921 42 10 | 10 | 2,6-Dichloro-4-nitroaniline | 0 |
| ex 2921 42 10 | 20 | 2-Bromo-4,6-dinitroaniline | 0 |
| ex 2921 42 10 | 30 | 4-Aminobenzene-1,3-disulphonic acid and its salts | 0 |
| ex 2921 42 10 | 40 | 2-Bromo-6-chloro-4-nitroaniline | 0 |
| ex 2921 42 10 | 50 | 3-Aminobenzenesulphonic acid | 0 |
| ex 2921 43 00 | 10 | 5-Amino-2-chlorotoluene-4-sulphonic acid | 0 |
| ex 2921 43 00 | 20 | 4-Amino-6-chlorotoluene-3-sulphonic acid | 0 |
| ex 2921 44 00 | 10 | Methyldiphenylamine | 0 |
| ex 2921 45 00 | 10 | 3-Aminonaphthalene-1,5-disulphonic acid, monosodium salt | 0 |
| ex 2921 45 00 | 20 | 2-Aminonaphthalene-1,5-disulphonic acid and its sodium salts | 0 |
| ex 2921 45 00 | 30 | 2-Aminonaphthalene-1-sulphonic acid | 0 |
| ex 2921 45 00 | 40 | 1-Naphthylamine | 0 |
| ex 2921 49 10 | 20 | Pendimethalin (ISO) | 3,5 |
| ex 2921 49 90 | 10 | 8-Anilinonaphthalene-1-sulphonic acid | 0 |
| ex 2921 59 90 | 10 | Mixture of isomers of 3,5-diethyltoluenediamine | 0 |
| ex 2921 59 90<br>ex 3824 90 95 | 20<br>68 | 4-(4-Aminoanilino)-3-nitrobenzenesulphonic acid | 0 |
| ex 2922 19 90 | 55 | 4,4-Dimethoxybutylamine | 0 |
| ex 2922 19 90 | 60 | 2-[2-(Dimethylamino)ethyl(methyl)amino]ethanol | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 2922 19 90 | 70 | *N,N,N′,N′*-Tetramethyl-2,2'-oxybis(ethylamine) | 0 |
| ex 2922 19 90 | 75 | 2-Amino-2-methylpropanol, for use in the manufacture of goods of subheadings 3004 90 and 3305 30 [a] | 0 |
| ex 2922 21 00 | 10 | 2-Amino-5-hydroxynaphthalene-1,7-disulphonic acid and its salts, of a purity by weight of 60 % or more | 0 |
| ex 2922 21 00 | 20 | 4-Hydroxy-7-methylaminonaphthalene-2-sulphonic acid | 0 |
| ex 2922 21 00 | 30 | 6-Amino-4-hydroxynaphthalene-2-sulphonic acid | 0 |
| ex 2922 21 00 | 40 | 7-Amino-4-hydroxynaphthalene-2-sulphonic acid | 0 |
| ex 2922 22 00 | 10 | Anisidines | 0 |
| ex 2922 29 00 | 10 | 2-Methyl-*N*-phenyl-*p*-anisidine | 0 |
| ex 2922 29 00 | 20 | 3-Aminophenol | 0 |
| ex 2922 29 00 | 30 | 4-Amino-5-methoxy-2-methylbenzenesulphonic acid | 0 |
| ex 2922 29 00 | 40 | 2-Amino-4-*tert*-pentyl-6-nitrophenol | 0 |
| ex 2922 29 00 | 50 | 6-Methoxy-*m*-toluidine | 0 |
| ex 2922 29 00 | 60 | 3,5-Dichloro-4-(1,1,2,2-tetrafluoroethoxy)aniline | 0 |
| ex 2922 29 00 | 70 | 4-Nitro-*o*-anisidine | 0 |
| ex 2922 30 00 | 10 | 1-Amino-4-bromo-9,10-dioxoanthracene-2-sulphonic acid and its salts | 0 |
| ex 2922 30 00 | 20 | 1-Aminoanthraquinone | 0 |
| ex 2922 49 70 | 10 | Ornithine aspartate (INNM) | 0 |
| ex 2922 50 00 | 50 | 2-(4-Dibutylaminosalicyloyl)benzoic acid | 0 |
| ex 2923 90 00 | 10 | Tetramethylammonium hydroxide, in the form of an aqueous solution containing:<br>— (25 ± 0,5) % by weight of tetramethylammonium hydroxide,<br>— 500 mg/kg or less of carbonate,<br>— 200 mg/kg or less of chloride<br>and<br>— 5 mg/kg or less of potassium | 0 |
| ex 2924 10 00 | 20 | 2-Acrylamido-2-methylpropanesulphonic acid and its sodium or ammonium salts | 0 |
| ex 2924 10 00 | 30 | *N*-(1,1-Dimethyl-3-oxobutyl)acrylamide | 0 |
| ex 2924 10 00 | 40 | *N,N′*-Methylenediacrylamide | 0 |
| ex 2924 21 90<br>ex 3824 90 95 | 10<br>62 | 4,4'-Dihydroxy-7,7'-ureylenedi(naphthalene-2-sulphonic acid) and its sodium salts | 0 |
| ex 2924 29 90 | 10 | Alachlor (ISO) | 0 |
| ex 2924 29 90 | 15 | Acetochlor (ISO) | 0 |
| ex 2924 29 90 | 20 | 3'-Amino-4'-methoxyacetanilide | 0 |
| ex 2924 29 90 | 25 | 3'-Diethylaminoacetanilide | 0 |
| ex 2924 29 90 | 35 | Propachlor (ISO) | 0 |
| ex 2924 29 90 | 40 | Diethofencarb (ISO) | 0 |
| ex 2924 29 90 | 45 | 7-Acetamido-4-hydroxynaphthalene-2-sulphonic acid and its sodium salts | 0 |
| ex 2924 29 90 | 50 | 3'-Diethylamino-4'-methoxyacetanilide | 0 |
| ex 2924 29 90 | 60 | 5-[*N*-(2-Acetoxyethyl)acetoxyacetamido]-*N,N′*-bis(2,3-diacetoxy= propyl)-2,4,6-triiodoisophthalamide | 0 |
| ex 2924 29 90 | 70 | 4'-Amino-*N*-methylacetanilide | 0 |
| ex 2925 11 00 | 20 | Saccharin and its sodium salt | 0 |
| ex 2925 19 80 | 10 | *N*-Phenylmaleimide | 0 |
| ex 2925 20 00 | 10 | Dicyclohexylcarbodiimide | 0 |
| ex 2926 90 99 | 10 | Methacrylonitrile | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 2926 90 99 | 30 | 2-Amino-5-nitrobenzonitrile | 0 |
| ex 2926 90 99 | 40 | Chlorothalonil (ISO) | 0 |
| ex 2926 90 99 | 45 | 2-Cyanoacetamide | 0 |
| ex 2926 90 99 | 50 | Alkyl or alkoxyalkyl esters of cyanoacetic acid | 0 |
| ex 2926 90 99 | 60 | Cyanoacetic acid in crystalline form | 0 |
| ex 2926 90 99 | 65 | Malononitrile | 0 |
| ex 2926 90 99 | 70 | Tetrachloroterephthalonitrile | 0 |
| ex 2927 00 00 | 10 | 2,2'-Dimethyl-2,2'-azodipropionamidine dihydrochloride | 0 |
| ex 2927 00 00 | 20 | 4-Anilino-2-methoxybenzenediazonium hydrogen sulphate | 0 |
| ex 2927 00 00<br>ex 3824 90 95 | 30<br>69 | 4'-Aminoazobenzene-4-sulphonic acid | 0 |
| ex 2928 00 90 | 10 | 3,3'-Bis(3,5-di-*tert*-butyl-4-hydroxyphenyl)-*N,N'*-bipropionamide | 0 |
| ex 2928 00 90 | 20 | 2,4,6-Trichlorophenylhydrazine | 0 |
| ex 2928 00 90 | 30 | *tert*-Butylhydrazine hydrochloride, for the manufacture of goods of subheading 3808 10 ([a]) | 0 |
| ex 2928 00 90 | 40 | *O*-Ethylhydroxylamine, in the form of an aqueous solution | 0 |
| ex 2928 00 90 | 50 | *N*-Isopropylhydroxylamine, in the form of an aqueous solution | 0 |
| ex 2929 10 90 | 10 | Methylenedicyclohexyl diisocyanate, mixed isomers | 0 |
| ex 2929 10 90 | 30 | 3,3'-Dimethylbiphenyl-4,4'-diyl diisocyanate | 0 |
| ex 2929 10 90 | 40 | *m*-Isopropenyl-*α,α*-dimethylbenzyl isocyanate | 0 |
| ex 2929 10 90 | 50 | *m*-Phenylenediisopropylidene diisocyanate | 0 |
| ex 2929 10 90 | 60 | Trimethylhexamethylene diisocyanate, mixed isomers | 0 |
| ex 2930 90 70 | 10 | Thiophenol | 0 |
| ex 2930 90 70 | 15 | Ethoprophos (ISO) | 0 |
| ex 2930 90 70 | 20 | 3,3-Dimethyl-1-methylthiobutanone oxime | 0 |
| ex 2930 90 70 | 25 | Thiophanate-methyl (ISO) | 0 |
| ex 2930 90 70 | 30 | 4-(4-Isopropoxyphenylsulfonyl)phenol | 0 |
| ex 2930 90 70 | 40 | 3,3'-Thiodi(propionic acid) | 0 |
| ex 2930 90 70 | 45 | 2-[(*p*-Aminophenyl)sulfonyl]ethyl hydrogen sulphate | 0 |
| ex 2930 90 70<br>ex 3824 90 95 | 50<br>51 | 2-Chlorophenylsulfonyl isocyanate, in the form of a solution in xylene | 0 |
| ex 2930 90 70<br>ex 3824 90 95 | 55<br>52 | Methyl 2-(isocyanatosulfonyl)methylbenzoate, in the form of a solution in xylene | 0 |
| ex 2930 90 70 | 60 | Methyl phenyl sulphide | 0 |
| ex 2930 90 70 | 65 | Diiodomethyl *p*-tolyl sulphone | 0 |
| ex 2930 90 70<br>ex 3824 90 95 | 70<br>71 | 2-Aminophenyl phenyl sulphone, of a purity by weight of 75 % or more | 0 |
| 2931 00 10 | | Dimethyl methylphosphonate | 0 |
| ex 2931 00 95 | 10 | 2-Diphenylphosphinobenzoic acid | 0 |
| ex 2931 00 95 | 20 | Bis(2-chloroethyl) 2-chloroethylphosphonate | 0 |
| ex 2931 00 95 | 25 | Sodium phenylphosphinate | 0 |
| ex 2931 00 95 | 30 | Bis(2-chloroethyl) vinylphosphonate | 0 |
| ex 2931 00 95 | 35 | Sodium tetraphenylborate | 0 |
| ex 2931 00 95 | 40 | *N*-(Phosphonomethyl)iminodiacetic acid | 0 |
| ex 2931 00 95 | 45 | Tributylphosphine | 0 |
| ex 2931 00 95 | 50 | Bis(2,4,4-trimethylpentyl)phosphinic acid | 0 |
| ex 2931 00 95 | 55 | Dimethyl[dimethylsilyldiindenyl]hafnium | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 2931 00 95 | 60 | Trioctylphosphine oxide | 0 |
| ex 2931 00 95 | 65 | Triethylborane | 0 |
| ex 2932 11 00 | 10 | Tetrahydrofuran, containing not more than 40 mg per litre in total of tetrahydro-2-methylfuran and tetrahydro-3-methylfuran, for the manufacture of *α*-4-hydroxybutyl-*ω*-hydroxypoly(oxytetramethylene) ([a]) | 0 |
| ex 2932 13 00 | 10 | Tetrahydrofurfuryl alcohol | 0 |
| ex 2932 19 00 | 40 | Furan of a purity by weight of 99 % or more | 0 |
| ex 2932 19 00 | 50 | 2,3-Dihydrofuran | 0 |
| ex 2932 29 80 | 10 | 2'-Anilino-6'-[ethyl(isopentyl)amino]-3'-methylspiro[isobenzofuran= -1(3*H*),9'-xanthen]-3-one | 0 |
| ex 2932 29 80 | 15 | 13,14,15,16-Tetranorlabdano-12,8*α*-lactone | 0 |
| ex 2932 29 80 | 25 | 2'-(2-Chloroanilino)-6'-dibutylaminospiro[isobenzofuran= -1(3*H*),9'-xanthen]-3-one | 0 |
| ex 2932 29 80 | 30 | 2'-Anilino-3'-methyl-6'-methyl(propyl)aminospiro[isobenzofuran= -1(3*H*),9'-xanthen]-3-one | 0 |
| ex 2932 29 80 | 35 | 6'-Diethylamino-3'-methyl-2'-(2,4-xylidino)spiro[isobenzofuran= -1(3*H*),9'-xanthen]-3-one | 0 |
| ex 2932 29 80 | 40 | 2'-Anilino-6'-(*N*-ethyl-*p*-toluidino)-3'-methylspiro[isobenzofuran= -1(3*H*),9'-xanthen]-3-one | 0 |
| ex 2932 29 80 | 45 | 2'-Anilino-6'-ethyl(isobutyl)amino-3'-methylspiro[isobenzofuran= -1(3*H*),9'-xanthen]-3-one | 0 |
| ex 2932 29 80 | 50 | 2'-Anilino-6'-cyclohexyl(methyl)amino-3'-methylspiro[isobenzofuran= -1(3*H*),9'-xanthen]-3-one | 0 |
| ex 2932 29 80 | 55 | 6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide | 0 |
| ex 2932 99 70 | 10 | Bendiocarb (ISO) | 0 |
| ex 2932 99 70 | 20 | Androsta-1,4-diene-3,17-dione 17-(2,2-dimethylpropylene) acetal | 0 |
| ex 2933 21 00 | 10 | Hydantoin | 0 |
| ex 2933 21 00 | 20 | 2-(3-Benzyl-2,5-dioxoimidazolidin-1-yl)-2'-chloro-5'-(3-dodecyl= sulfonyl-2-methylpropionamido)-4,4-dimethyl-3-oxovaleranilide | 0 |
| ex 2933 21 00 | 30 | 3'-[4,4-Dimethyl-2-(4,4-dimethyl-2,5-dioxoimidazolin-1-yl)= -3-oxovalerylamino]-4'-methoxystearanilide | 0 |
| ex 2933 21 00 | 40 | 1-[1,3-Bis(hydroxymethyl)-2,5-dioxoimidazolidin-4-yl]= -1,3-bis(hydroxymethyl)urea | 0 |
| ex 2933 29 90 | 20 | Reaction product consisting of the methyl esters of (±)-6-(4-isopropyl-4-methyl-5-oxo-2-imidazolin-2-yl)-*m*-toluic acid and (±)-2-(4-isopropyl-4-methyl-5-oxo-2-imidazolin-2-yl)-*p*-toluic acid (Imazamethabenz-methyl) | 4 |
| ex 2933 29 90 | 40 | Triflumizole (ISO) | 0 |
| ex 2933 39 95 | 10 | Cloperastine fendizoate (INNM) | 0 |
| ex 2933 39 95 | 15 | Pyridine-2,3-dicarboxylic acid | 0 |
| ex 2933 39 95 | 20 | 5-Methyl-2-pyridylamine | 0 |
| ex 2933 39 95 | 25 | Imazethapyr (ISO) | 0 |
| ex 2933 39 95 | 30 | 4,4'-Trimethylenedipiperidine | 0 |
| ex 2933 40 10 | 10 | Quinmerac (ISO) | 0 |
| ex 2933 40 90 | 20 | 5,7-Dichloro-4-(4-fluorophenoxy)quinoline | 0 |
| ex 2933 40 90 | 40 | *N*-Ethyl-5,6,7,8-tetrahydroquinolinium *p*-toluenesulphonate, in the form of a solution in water | 0 |
| ex 2933 59 70 | 10 | 1-Ethyl-6-fluoro-1,4-dihydro-4-oxo-7-piperazin-1-yl-1,8-naphthyridine= -3-carboxylic acid and its salts and esters | 0 |
| ex 2933 59 70 | 20 | 2,4-Diamino-6-chloropyrimidine | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 2933 59 70 | 30 | Mepanipyrim (ISO) | 0 |
| ex 2933 69 80 | 10 | 1,3,5-Tris(4-*tert*-butyl-3-hydroxy-2,6-dimethylbenzyl)-1,3,5-triazine= -2,4,6(1*H*,3*H*,5*H*)-trione | 0 |
| ex 2933 69 80 | 20 | 1,3,5-Tris[(3,5-di-*tert*-butyl-4-hydroxyphenyl)methyl]-1,3,5-triazine= -2,4,6(1*H*,3*H*,5*H*)-trione | 0 |
| ex 2933 69 80 | 40 | Cyanazine (ISO) | 0 |
| ex 2933 90 50 | 10 | Azepane, for the manufacture of goods of subheading 3808 30 (a) | 0 |
| ex 2933 90 95 | 10 | 2-(2*H*-Benzotriazol-2-yl)-4,6-di-*tert*-butylphenol | 0 |
| ex 2933 90 95 | 15 | 2-(2*H*-Benzotriazol-2-yl)-4,6-di-*tert*-pentylphenol | 0 |
| ex 2933 90 95 | 20 | 2-(2*H*-Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)-phenol | 0 |
| ex 2933 90 95 | 25 | 6,6'-Di-2*H*-benzotriazol-2-yl-4,4'-bis(1,1,3,3-tetramethylbutyl)= -2,2'-methylenediphenol | 0 |
| ex 2933 90 95 | 30 | Quizalofop-P-ethyl (ISO) | 0 |
| ex 2933 90 95 | 35 | Indoline | 0 |
| ex 2933 90 95 | 45 | Maleic hydrazide (ISO) | 0 |
| ex 2933 90 95 | 50 | Metconazole (ISO) | 3,2 |
| ex 2933 90 95 | 55 | 5-Nitroindole | 0 |
| ex 2933 90 95 | 60 | 1,3-Bis(3-isocyanatomethylphenyl)-1,3-diazetidine-2,4-dione (dimeric 2,4-toluene diisocyanate) | 0 |
| ex 2933 90 95 | 65 | Candesartan cilexetil (INNM) | 0 |
| ex 2934 10 00 | 10 | Hexythiazox (ISO) | 0 |
| ex 2934 10 00 | 20 | 2-(4-Methylthiazol-5-yl)ethanol | 0 |
| ex 2934 20 80 | 10 | 4-Chloro-1,3-benzothiazol-2(3*H*)-one | 0 |
| ex 2934 90 96 | 10 | 7-Chloro-5-methyl-2*H*-1,4-benzothiazin-3-(4*H*)-one | 0 |
| ex 2934 90 96 | 15 | Carboxin (ISO) | 0 |
| ex 2934 90 96 | 20 | 4-[4-(Tridecyl[branched]oxy)phenyl]-1,4-thiazinane 1,1-dioxide | 0 |
| ex 2934 90 96 | 25 | Oxycarboxin (ISO) | 0 |
| ex 2934 90 96 | 30 | Etridiazole (ISO) | 0 |
| ex 2934 90 96 | 35 | Dimethenamide (ISO) | 0 |
| ex 2934 90 96 | 40 | 2,3,5,6-Tetrahydroxy-1,4-diisobutyl-1,4-dioxo-1,4-diphosphinane | 0 |
| ex 2934 90 96 | 45 | Tris(2,3-epoxypropyl)-1,3,5-triazinanetrione | 0 |
| ex 2934 90 96 | 50 | 1-[2-(1,3-Dioxan-2-yl)ethyl]-2-ethylpyridinium bromide | 0 |
| ex 2934 90 96 | 55 | Naphth[1,2-*d*][1,2,3]oxadiazole-5-sulphonic acid | 0 |
| ex 2934 90 96<br>ex 3824 90 95 | 60<br>41 | 7-Nitronaphth[1,2-*d*][1,2,3]oxadiazole-5-sulphonic acid of a purity by weight of 60 % or more | 0 |
| ex 2935 00 90 | 10 | Salts of sulphathiazole (INN) | 0 |
| ex 2935 00 90 | 20 | Toluenesulphonamides | 0 |
| ex 2935 00 90 | 30 | Mixture of isomers consisting of *N*-ethyltoluene-2-sulphonamide and *N*-ethyltoluene-4-sulphonamide | 0 |
| ex 2935 00 90 | 40 | 1-(4,6-Dimethoxypyrimidin-2-yl)-3-(2-ethylsulfonylimidazo[1,2-a]pyridin= -3-ylsulfonyl)urea (sulfosulfuron) | 0 |
| ex 2935 00 90 | 50 | 4,4'-Oxydi(benzenesulfonohydrazide) | 0 |
| ex 2935 00 90 | 60 | 5-Amino-*N*-(2,6-dichloro-*m*-tolyl)-1*H*-1,2,4-triazole-3-sulphonamide | 0 |
| ex 2935 00 90 | 70 | Methyl 3-aminosulfonylthiophene-2-carboxylate | 0 |
| 3201 20 00 | | Wattle extract | 0 |
| ex 3201 90 90 | 10 | Tanning extracts of eucalyptus | 3,2 |

▼**M7**

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3201 90 90 | 20 | Tanning extracts derived from gambier and myrobalan fruits | 0 |
| ex 3204 15 00 | 10 | Dye C.I. Vat Orange 7 | 0 |
| ex 3204 15 00 | 20 | Dye C.I. Vat Red 15 | 0 |
| ex 3204 15 00 | 30 | Dye C.I. Vat Red 14 | 0 |
| ex 3204 15 00 | 40 | Dye C.I. Vat Brown 57 | 0 |
| ex 3204 17 00 | 10 | Dye C.I. Pigment Yellow 81 | 0 |
| ex 3204 19 00 | 10 | Nickel bis{4-methoxy-2-[6-(pentafluoroethylthio)benzothiazol-2-ylazo]= -5-(dipropylamino)benzenesulphonate} | 0 |
| ex 3204 19 00 | 20 | 13-Ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo= [*h*]indeno[2,1-*f*]chromen-13-ol | 0 |
| ex 3204 19 00 | 30 | 13-Isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo= [*h*]indeno[2,1-*f*]chromen-13-ol | 0 |
| ex 3204 19 00 | 40 | Methyl 8'-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1*H*-indole= -2,3'-naphtho[2,1-*b*][1,4]oxazine]-9'-carboxylate | 0 |
| ex 3204 19 00 | 50 | Methyl 6-(isobutyryloxy)-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate | 0 |
| ex 3204 19 00 | 60 | Ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate | 0 |
| ex 3206 42 00 | 10 | Lithopone | 0 |
| ex 3206 49 90 | 10 | Black preparation of iron-oxide pigments, in liquid form, with a maximum particle size not exceeding 20 nanometres and containing by weight 25 % or more of iron evaluated as $Fe_2O_3$, for the manufacture of goods of heading No 3304 or 9608 (a) | 0 |
| ex 3208 20 10 | 10 | Copolymer of *N*-vinylcaprolactam, *N*-vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate, in the form of a solution in ethanol containing by weight 34 % or more but not more than 40 % of copolymer | 0 |
| ex 3208 20 10<br>ex 3905 91 00 | 20<br>92 | Copolymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, partially quaternised by diethyl sulphate, in the form of a solution in ethanol | 0 |
| ex 3208 20 10 | 30 | Solution of diundecyl phthalate and a copolymer of dibutyl maleate and isobutyl methacrylate in a hydrocarbon solvent | 0 |
| ex 3208 90 19<br>ex 3911 90 99 | 10<br>35 | Copolymer of maleic acid and methyl vinyl ether, monoesterified with ethyl and/or isopropyl and/or butyl groups, in the form of a solution in ethanol, ethanol and butanol, isopropanol or isopropanol and butanol | 0 |
| ex 3208 90 19 | 20 | Copolymer of polyurethane and silicone, in the form of a solution in a mixture of butanone, toluene and cyclohexanone, containing by weight 13 % or more but not more than 16 % of copolymer | 0 |
| ex 3208 90 19 | 30 | Solution containing:<br>— (30 ± 5) % by weight of polyamide resin,<br>— (6,5 ± 3,5) % by weight of diazonaphthoquinone,<br>— (55 ± 5) % by weight of 1-methyl-2-pyrrolidone,<br>— 1 000 µg/kg or less of chloride,<br>— 1 000 µg/kg or less of potassium<br>and<br>— 1 000 µg/kg or less of iron | 0 |
| ex 3208 90 99 | 10 | Solution based on chemically modified natural polymers, containing two or more of the following dyes:<br>— methyl 8'-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1*H*-indole= -2,3'-naphtho[2,1-*b*][1,4]oxazine]-9'-carboxylate,<br>— methyl 6-(isobutyryloxy)-2,2-diphenyl-2*H*-benzo[*h*]-chromene= -5-carboxylate, | |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| | | — 13-isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo= [*h*]indeno[2,1-*f*]chromen-13-ol,<br>— ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate,<br>— 13-ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo= [*h*]indeno[2,1-*f*]chromen-13-ol | 0 |
| ex 3215 90 80 | 10 | Ink formulation, for use in the manufacture of ink-jet cartridges (a) | 0 |
| 3301 12 10 | | Essential oil of orange, not deterpenated | 0 |
| ex 3402 90 10 | 20 | Mixture of docusate sodium (INN) and sodium benzoate | 0 |
| ex 3402 90 10 | 30 | Non-aqueous surface-active preparation, containing:<br>— polyethylene glycol alkylphenyl ether,<br>— 2,4,7,9-tetramethyldec-5-yne-4,7-diol<br>and<br>— phosphoric acid esters | 0 |
| ex 3402 90 90 | 10 | Crystalline powder obtained by the reaction of trisodium phosphate with a mixture of sodium hypochlorite and sodium chloride (‘chlorinated trisodium phosphate’), containing by weight:<br>— 3,5 % or more of available chlorine, measured iodometrically<br>and<br>— 17,0 % or more of phosphorus evaluated as $P_2O_5$ | 0 |
| ex 3403 99 90 | 10 | Cutting-fluid preparation based on an aqueous solution of synthetic polypeptides | 0 |
| ex 3504 00 00 | 10 | Purified antigens obtained from genetically manipulated yeast cells, for the manufacture of detection tests for hepatitis-C (a) | 0 |
| ex 3504 00 00 | 20 | Glycoprotein 160 obtained from human immunodeficiency virus, HIV-1 strain | 0 |
| ex 3505 10 50 | 20 | *O*-(2-Hydroxyethyl)-derivative of hydrolysed waxy maize starch | 0 |
| ex 3506 91 00 | 10 | Adhesive based on an aqueous dispersion of a mixture of dimerised rosin and a copolymer of ethylene and vinyl acetate (EVA) | 0 |
| ex 3506 91 00 | 20 | Heat-activated adhesive based on phenolic resin and rubber, in the form of a film on a release paper, for use in the manufacture of brake pads for the automotive industry (a) | 0 |
| ex 3507 90 90 | 10 | Asparaginase | 0 |
| ex 3507 90 90 | 20 | Enzymatic preparation based on thermolysine | 0 |
| ex 3507 90 90 | 40 | Avian myeloblastosis virus (AMV) reverse transcriptase | 0 |
| ex 3701 30 00 | 10 | Letterpress printing plates, consisting of a metal substrate covered with a photopolymer layer, of a total thickness of 0,5 mm or more but not exceeding 0,8 mm | 0 |
| ex 3701 99 00 | 10 | Plate of quartz or of glass, covered with a film of chromium and coated with a photosensitive or electron-sensitive resin, for the manufacture of masks for the goods of heading No 8541 or 8542 (a) | 0 |
| ex 3702 31 99 | 10 | Colour negative film, for the manufacture of instant-picture film-packs (a) | 0 |
| ex 3702 43 00<br>ex 3702 44 00 | 10<br>10 | Photographic film, of a nominal width of 459, 669 or 761 mm, composed of several layers, including two polyester films, a carbon layer, an adhesive layer and a layer of a copolymer of styrene with acrylonitrile | 0 |
| ex 3703 90 10 | 10 | Paper sheet, coated with silver halide emulsion, for the manufacture of goods of subheading 3701 20 00 (a) | 0 |
| ex 3707 10 00 | 10 | Photosensitive emulsion for the sensitisation of silicon discs (a) | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3707 90 30 | 10 | Toner, in the form of powder, consisting of a copolymer of styrene and butyl acrylate and magnetite, for use as a developer in the manufacture of cartridges for fax machines (a) | 0 |
| 3805 20 00 | | Pine oil | 1,7 |
| ex 3808 20 80 | 10 | Fungicide in the form of a powder, containing by weight 65 % or more but not more than 75 % of hymexazole (ISO), not put up for retail sale | 0 |
| ex 3808 20 80 | 20 | Preparation based on diiodomethyl *p*-tolyl sulphone, not put up for retail sale | 0 |
| ex 3808 40 20 | 10 | Preparation containing by weight:<br>— 58 % or more but not more than 62 % of 1-bromo-3-chloro-5,5-dimethylhydantoin,<br>— 26 % or more but not more than 29 % of 1,3-dichloro-5,5-dimethylhydantoin,<br>— 10 % or more but not more than 12 % of 1,3-dichloro-5-ethyl-5-methylhydantoin,<br>for the manufacture of swimming-pool disinfectants (a) | 0 |
| ex 3808 40 90 | 10 | 1-Dodecylguanidine hydrochloride, in the form of a solution in isopropanol and water, containing by weight 40 % or less of 1-dodecylguanidine hydrochloride | 0 |
| ex 3809 91 00 | 10 | Mixture of 5-ethyl-2-methyl-2-oxo-1,3,2$\lambda^5$-dioxaphosphoran-5-ylmethyl methyl methylphosphonate and bis(5-ethyl-2-methyl-2-oxo-1,3,2$\lambda^5$-dioxaphosphoran-5-ylmethyl) methylphosphonate | 0 |
| ex 3809 92 00 | 10 | Paper anti-fading agent, consisting of a mixture of magnesium trisilicate and monosodium salt of 2,2'-methylenebis(4,6-di-*tert*-butylphenyl) phosphate | 0 |
| ex 3811 21 00 | 10 | Salts of dinonylnaphthalenesulphonic acid, in the form of a solution in mineral oils | 0 |
| ex 3812 30 80 | 10 | Tetraaluminium nonamagnesium dicarbonate hexacosahydroxide heptahydrate, coated with a surface-active agent | 0 |
| ex 3812 30 80 | 20 | Mixture containing predominantly bis(2,2,6,6-tetramethyl-1-octyloxy-4-piperidyl) sebacate | 0 |
| ex 3812 30 80 | 30 | Compound stabilisers containing by weight 15 % or more but not more than 40 % of sodium perchlorate and not more than 70 % of 2-(2-methoxyethoxy)ethanol | 0 |
| ex 3812 30 80 | 40 | Dialuminium tetramagnesium monocarbonate dodecahydroxide monohydrate, coated with a surface-active agent | 0 |
| ex 3812 30 80 | 50 | Aluminium magnesium zinc hydroxide carbonate hydrate, coated with a surface-active agent | 0 |
| ex 3814 00 90 | 10 | Mixture containing by weight 25 % or more but not more than 35 % of dimethyl sulfoxide and 65 % or more but not more than 75 % of monoethanolamine | 3 |
| ex 3815 12 00 | 10 | Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not exceeding 10 mm, consisting of silver on an aluminium oxide support and containing by weight 8 % or more but not more than 20 % of silver | 0 |
| ex 3815 12 00 | 20 | Catalyst consisting of palladium and rhenium, fixed on a support of active carbon, in the form of powder, containing:<br>— 0,5 % or more but not more than 1,5 % by weight of palladium,<br>— 3 % or more but not more than 5 % by weight of rhenium<br>and<br>— 0,1 mole % or more but not more than 1 mole % of alkaline metals,<br>for use in the manufacture of tetrahydrofuran (a) | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3815 19 90 | 10 | Catalyst, consisting of chromium trioxide or dichromium trioxide fixed on a support of silicon dioxide, of a pore volume, as determined by the nitrogen absorption method, of 2 $cm^3/g$ or more | 0 |
| ex 3815 19 90 | 15 | Catalyst, in the form of a powder, consisting of a mixture of metal oxides fixed on a support of silicon dioxide, containing by weight 20 % or more but not more than 40 % of molybdenum, bismuth and iron evaluated together, for use in the manufacture of acrylonitrile (a) | 0 |
| ex 3815 19 90 | 20 | Catalyst consisting of chromium oxides and titanium dioxide fixed on a support of silicon dioxide, aluminium oxide or aluminium phosphate | 0 |
| ex 3815 19 90 | 30 | Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene (a) | 0 |
| ex 3815 19 90 | 40 | Catalyst, in the form of spheres of a diameter of 4,2 mm or more but not exceeding 9 mm, consisting of a mixture of metal oxides containing predominantly oxides of molybdenum, vanadium and copper, on a support of silicon dioxide and/or aluminium oxide, for use in the manufacture of acrylic acid (a) | 0 |
| ex 3815 19 90 | 45 | Catalyst, consisting predominantly of dichromium copper tetraoxide and copper (II) oxide, containing by weight 38 % or more but not more than 48 % of copper, evaluated as copper (II) oxide, fixed on a support of silicon dioxide, for the hydrogenation of acetophenones (a) | 0 |
| ex 3815 19 90 | 50 | Catalyst consisting of organo-metallic compounds of titanium, magnesium and aluminium on a support of silicon dioxide, in the form of a suspension in tetrahydrofuran | 0 |
| ex 3815 19 90 | 55 | Catalyst consisting of a mixture of metal oxides containing chromium trioxide, fixed on a support of silicon dioxide | 0 |
| ex 3815 19 90 | 60 | Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide | 0 |
| ex 3815 19 90 | 65 | Catalyst consisting of phosphoric acid chemically bonded to a support of silicon dioxide | 0 |
| ex 3815 19 90 | 70 | Catalyst consisting of organo-metallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide | 0 |
| ex 3815 19 90 | 75 | Catalyst consisting of organo-metallic compounds of aluminium and chromium, fixed on a support of silicon dioxide | 0 |
| ex 3815 19 90 | 80 | Catalyst consisting of organo-metallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil | 0 |
| ex 3815 19 90 | 85 | Catalyst consisting of organo-metallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder | 0 |
| ex 3815 90 90 | 15 | Catalyst, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, vanadium, nickel and antimony, whether or not mixed with porcelain balls, for use in the manufacture of acrylic acid (a) | 0 |
| ex 3815 90 90 | 20 | Catalyst, in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing by weight:<br>— 20 % or more but not more than 30 % of titanium<br>and<br>— 55 % or more but not more than 72 % of chlorine | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3815 90 90 | 25 | Catalyst, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, bismuth, nickel, iron and silicon, whether or not mixed with porcelain balls, for use in the manufacture of acrylaldehyde (a) | 0 |
| ex 3815 90 90 | 30 | Catalyst, in the form of a powder, containing by weight 82 % or more of copper and of a specific surface of 0,5 $m^2$/g or more but not exceeding 8 $m^2$/g | 0 |
| ex 3815 90 90 | 35 | Catalyst, in the form of a suspension in oil, consisting of titanium trichloride and aluminium trichloride, containing by weight (on an oil-free basis):<br>— 15 % or more but not more than 30 % of titanium<br>and<br>— 40 % or more but not more than 72 % of chlorine | 0 |
| ex 3815 90 90 | 40 | Catalyst, in the form of rodlets of a length of 5 mm or more but not exceeding 8 mm, consisting of a mixture of metals oxides containing predominantly oxides of iron, molybdenum and bismuth, whether or not containing silicon dioxide as filler, for use in the manufacture of acrylic acid (a) | 0 |
| ex 3815 90 90 | 50 | Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium | 0 |
| ex 3815 90 90 | 55 | Reaction initiator, consisting of a mixture of *N,N,N',N'*-tetramethyl-2,2'-oxybis(ethylamine) and dipropylene glycols | 0 |
| ex 3815 90 90 | 60 | Catalyst, in the form of rodlets, consisting of an acid aluminosilicate (zeolite):<br>— with a mole-ratio of silicon dioxide: dialuminium trioxide of not less than 500: 1<br>and<br>— containing by weight 0,2 % or more but not more than 0,8 % of platinum | 0 |
| ex 3815 90 90 | 65 | Catalyst based on a mordenite zeolite, in the form of granules, for use in the manufacture of mixtures of methylamines containing by weight 50 % or more of dimethylamine (a) | 0 |
| ex 3815 90 90 | 70 | Catalyst, consisting of a mixture of (2-hydroxypropyl)trimethylammonium formate and dipropylene glycols | 0 |
| ex 3815 90 90 | 75 | Catalyst, consisting of a mixture of 1,4-diazabicyclo[2.2.2]octane, 2-hydroxyethyliminodi(acetic acid) and dibutyltin di(acetate), containing by weight 5 % or more but not more than 10 % of 1,4-diazabicyclo[2.2.2]octane | 0 |
| ex 3815 90 90 | 80 | Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol | 0 |
| ex 3815 90 90 | 81 | Catalyst, containing by weight 38 % or more but not more than 48 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate | 0 |
| ex 3815 90 90 | 82 | Catalyst, containing by weight 35 % or more but not more than 55 % of (2-hydroxy-1-methylethyl)trimethylammonium formate and formic acid | 0 |
| ex 3815 90 90 | 83 | Catalyst, in the form of powder, containing aluminium magnesium hydroxide hydrate, rare-earth metals oxides and divanadium pentaoxide | 0 |
| ex 3815 90 90 | 85 | Catalyst based on aluminosilicate (zeolite), for the transalkylation of alkylaromatic hydrocarbons or the oligomerisation of olefins (a) | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3823 19 10 | 91 | Mixture of fatty acids containing by weight:<br>— 2 % or more but not more than 6 % of hexanoic acid,<br>— 53 % or more but not more than 60 % of octanoic acid,<br>— 34 % or more but not more than 42 % of decanoic acid<br>and<br>— not more than 2 % of dodecanoic acid | 0 |
| ex 3824 90 15 | 10 | Acid aluminosilicate (artificial zeolite of the Y type) in the sodium form, containing by weight not more than 11 % of sodium evaluated as sodium oxide, in the form of rodlets | 0 |
| ex 3824 90 64 | 01 | Intermediate products of the antibiotics manufacturing process obtained from the fermentation of *Micromonospora purpurea*, whether or not dried | 0 |
| ex 3824 90 64 | 02 | Cholic acid and 3*α*,12*α*-dihydroxy-5*β*-cholan-24-oic acid (deoxycholic acid), crude | 0 |
| ex 3824 90 64 | 03 | Products obtained by the *N*-ethylation of sisomycin (INN) | 0 |
| ex 3824 90 64 | 04 | Intermediate products of the antibiotics manufacturing process obtained from the fermentation of *Micromonospora inyoensis*, whether or not dried | 0 |
| ex 3824 90 64 | 05 | Residues of manufacture containing by weight 40 % or more of 11*β*,17,20,21-tetrahydroxy-6-methylpregna-1,4-dien-3-one 21-acetate | 0 |
| ex 3824 90 95 | 01 | Colloidal diantimony pentaoxide | 0 |
| ex 3824 90 95 | 02 | Mixture of nitromethane and 1,2-epoxybutane | 0 |
| ex 3824 90 95 | 03 | Grains or granules, consisting of a mixture of dialuminium trioxide and zirconium dioxide, containing by weight:<br>— 70 % or more but not more than 78 % of dialuminium trioxide<br>and<br>— 19 % or more but not more than 26 % of zirconium dioxide | 5,2 |
| ex 3824 90 95 | 04 | Crude lithium hypochlorite | 0 |
| ex 3824 90 95 | 06 | Preparation, in the form of powder, containing by weight 75 % or more of zinc bis[3,5-bis(1-phenylethyl)salicylate] | 0 |
| ex 3824 90 95 | 07 | Film consisting of the oxides of either barium or calcium and either titanium or zirconium, mixed with binding materials | 0 |
| ex 3824 90 95 | 08 | Preparation consisting essentially of alkaline asphalt sulphonate, of:<br>— a specific gravity of 0,9 or more but not exceeding 1,5<br>and<br>— a solubility in water of 70 % by weight or more | 0 |
| ex 3824 90 95 | 09 | Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulphonic acid, either:<br>— on a support of mineral wax, whether or not modified chemically,<br>or<br>— in the form of a solution in an organic solvent | 0 |
| ex 3824 90 95 | 10 | Calcined bauxite (refractory grade) | 0 |
| ex 3824 90 95 | 11 | Magnetisable iron oxide, in the form of powder, containing by weight:<br>— 30 % or more but not more than 38 % of bivalent iron in relation to the total iron<br>and<br>— 1 % or more but not more than 4 % of cobalt | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3824 90 95 | 12 | Spent catalyst, in the form of rodlets of diameter of 1 mm or more but not exceeding 3 mm, containing a mixture of sulphides of tungsten and of nickel on a support of zeolite, containing by weight not more than 10 % of tungsten and not more than 10 % of nickel, for regeneration as a catalyst for hydrocarbon cracking (a) | 0 |
| ex 3824 90 95 | 13 | Mixture containing by weight:<br>— 7 % or more but not more than 9 % of 2-methyl-1,3-phenylene diisocyanate,<br>— 31 % or more but not more than 34 % of 4-methyl-1,3-phenylene diisocyanate,<br>— 10 % or more but not more than 13 % of 2,4'-methylenediphenyl diisocyanate,<br>— 46 % or more but not more than 49 % of 4,4'-methylenediphenyl diisocyanate | 0 |
| ex 3824 90 95 | 14 | Mixture of magnesium bromide 2-oxoperhydroazepin-1-ide and ε-caprolactam | 0 |
| ex 3824 90 95 | 15 | Mixture of disodium *N*-benzyloxycarbonyl-L-aspartate and sodium chloride, in the form of a solution in water | 0 |
| ex 3824 90 95 | 16 | Disodium 9,10-dihydro-9,10-dioxoanthracene-2,7-disulphonate, containing by weight 10 % or more but not more than 20 % of sodium sulphate | 0 |
| ex 3824 90 95 | 17 | Eutectic alloy wholly of potassium and sodium, containing by weight 77 % or more but not more than 79 % of potassium | 0 |
| ex 3824 90 95 | 18 | Blend of terephthaloyl dichloride and isophthaloyl dichloride | 0 |
| ex 3824 90 95 | 20 | Preparation consisting by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing by weight 7 % or more of tricyclopentadiene, and:<br>— either an aluminium-alkyl compound,<br>— or an organic complex of tungsten<br>— or an organic complex of molybdenum | 0 |
| ex 3824 90 95 | 21 | Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of methylphosphonic acid and phosphoric acid with ethane-1,2-diol | 0 |
| ex 3824 90 95 | 22 | Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of 2-chloroethyl phosphate with ethane-1,2-diol | 0 |
| ex 3824 90 95 | 23 | Mixture of sucrose esters, derived from the esterification of sucrose with industrial stearic acid | 0 |
| ex 3824 90 95 | 24 | Preparations consisting predominantly of phosphabicyclononanes and *P*-alkyl derivatives thereof, in the form of a solution in 4-*tert*-butyltoluene | 0 |
| ex 3824 90 95 | 25 | Lithium tantalate wafers, undoped | 0 |
| ex 3824 90 95 | 28 | Preparation consisting predominantly of ethylene glycol and *N,N*-dimethylformamide or ethylene glycol and γ-butyrolactone, for the manufacture of electrolytic capacitors (a) | 0 |
| ex 3824 90 95 | 29 | Preparation consisting predominantly of γ-butyrolactone and quaternary ammonium salts, for the manufacture of electrolytic capacitors (a) | 0 |
| ex 3824 90 95 | 30 | 2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated | 0 |
| ex 3824 90 95 | 31 | Copper zinc ferrite, coated with a silicone resin, in the form of granules of a size not exceeding 120 μm | 0 |
| ex 3824 90 95 | 32 | Styrene oligomer | 0 |
| ex 3824 90 95 | 33 | Preparation consisting of α-(4-allyloxycarbonylbenzoyl)-ω-allyloxypoly= [oxy(2-methylethylene)oxyterephthaloyl] and either diallyl-2,2'-oxydiethyl dicarbonate or diallyl isophthalate | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3824 90 95 | 39 | Mixture containing by weight 40 % or more but not more than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid | 0 |
| ex 3824 90 95 | 40 | Azelaic acid of a purity by weight of 75 % or more but not exceeding 85 % | 0 |
| ex 3824 90 95 | 42 | Mixed metal oxides, in the form of powder, containing by weight:<br>— either 5 % or more of barium, neodymium or magnesium and 15 % or more of titanium,<br>— or 30 % or more of lead and 5 % or more of niobium,<br>for use in the manufacture of dielectric films or for use as dielectric materials in the manufacture of multilayer ceramic capacitors (a) | 0 |
| ex 3824 90 95 | 43 | 7-Aminonaphthalene-1,3,6-trisulphonic acid and its salts, of a purity by weight of 65 % or more | 0 |
| ex 3824 90 95 | 44 | Mixture containing by weight:<br>— 60 % or more of 2-[*N*-(2-cyanoethyl)anilino]ethyl acetate<br>and<br>— 20 % or more of acetic acid | 0 |
| ex 3824 90 95 | 45 | Preparations consisting predominantly of ethylene glycol and:<br>— either diethylene glycol, dodecandioic acid and ammonia water,<br>— or silicon oxide,<br>— or ammonium hydrogen azelate,<br>— or ammonium hydrogen azelate and silicon oxide,<br>— or dodecandioic acid, ammonia water and silicon oxide,<br>for the manufacture of electrolytic capacitors (a) | 0 |
| ex 3824 90 95 | 46 | Carboxylic acid anhydride based hardener for epoxyde resin, in liquid form, of a specific weight at 25 °C of 1,15 g/cm$^3$ or more but not exceeding 1,18 g/cm$^3$ | 0 |
| ex 3824 90 95 | 49 | Mixed oxides of metals, in the form of powder, containing by weight:<br>— 70 % or more but not more than 75 % of iron oxide,<br>— 10 % or more but not more than 20 % of zinc oxide,<br>— 10 % or more but not more than 15 % of magnesium oxide,<br>— 1 % or more but not more than 5 % of manganese oxide<br>and<br>— 1 % or more but not more than 3 % of copper oxide | 0 |
| ex 3824 90 95 | 50 | Zeolites consisting of oxides of barium, aluminium and silicon, containing by weight 30 % or more but not more than 40 % of barium oxide, in the form of spheres of which 80 % or more by weight have a diameter of 0,3 mm or more but not more than 1,2 mm | 0 |
| ex 3824 90 95 | 53 | Sodium 4-hydroxynaphthalene-1-sulphonate, of a purity by weight of 70 % or more but not exceeding 80 % | 0 |
| ex 3824 90 95 | 54 | 2-Hydroxybenzonitrile, in the form of a solution in *N,N*-dimethylformamide, containing by weight 45 % or more but not more than 50 % of 2-hydroxybenzonitrile | 0 |
| ex 3824 90 95 | 55 | Mixture containing by weight 75 % or more of pentaerythritol triallyl ether | 0 |
| ex 3824 90 95 | 57 | Mixture of trialkylphosphine oxides | 0 |
| ex 3824 90 95 | 58 | Platinum oxide fixed on a porous support of aluminium oxide, containing by weight 0,1 % or more but not more than 1 % of platinum and 0,5 % or more but not more than 5 % of ethylaluminium dichloride | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3824 90 95 | 60 | $\alpha$-Phenoxycarbonyl-$\omega$-phenoxypoly[oxy(2,6-dibromo-1,4-phenylene)= isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl] | 0 |
| ex 3824 90 95 | 61 | Mixture of metal oxides, in the form of powder, containing by weight:<br>— 20 % or more of barium,<br>— 10 % or more of titanium<br>and<br>— 4 % or more of lead or 3 % or more of niobium or 0,7 % or more of zirconium,<br>for use as dielectric material in the manufacture of multilayer ceramic capacitors (a) | 0 |
| ex 3824 90 95 | 63 | Triethylborane, in the form of a solution in tetrahydrofuran | 0 |
| ex 3824 90 95 | 64 | Aluminium sodium silicate, in the form of spheres of a diameter of:<br>— either 1,6 mm or more but not exceeding 3,4 mm,<br>— or 4 mm or more but not exceeding 6 mm | 0 |
| ex 3824 90 95 | 65 | Mixture of tris(alkoxycarbonylamino)-1,3,5-triazines in which alkoxy groups are methoxy and butoxy | 0 |
| ex 3824 90 95 | 66 | Mixture of primary *tert*-alkylamines | 0 |
| ex 3824 90 95 | 67 | Preparation consisting of indium tin oxide dispersed in organic solvents | 0 |
| ex 3824 90 95 | 72 | Solution containing by weight 80 % or more of 2,4,6-trimethylbenzaldehyde in acetone | 0 |
| ex 3824 90 95 | 73 | Particles of silicon dioxide on which are covalently bonded organic compounds, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (a) | 0 |
| ex 3901 10 10 | 10 | Linear polyethylene, of a specific gravity of 0,928 or more but not exceeding 0,935 and of a melt flow index of less than 0,6 g/min, for the manufacture of shrinkmelt binder fibres (a) | 0 |
| ex 3901 10 90 | 10 | Polyethylene for the manufacture of photo-resist film for semiconductors or printed circuits (a) | 0 |
| ex 3901 10 90 | 20 | Polyethylene, in the form of granules, of a specific gravity of 0,925 (± 0,0015), a melt flow index of 0,3 g/10 min (± 0,05 g/10 min), for the manufacture of blown films of a Haze value not exceeding 6 % and an elongation at break (MD/TD) of 210/340 (a) | 0 |
| ex 3901 20 90 | 10 | Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, of a specific gravity of 0,945 or more but not exceeding 0,985, for the manufacture of films for typewriter ribbon or similar ribbon (a) | 0 |
| ex 3901 20 90 | 20 | Polyethylene, containing by weight 35 % or more but not more than 45 % of mica | 0 |
| ex 3901 90 90 | 91 | Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid | 4 |
| ex 3901 90 90 | 93 | Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticiser in the manufacture of roof sheets (a) | 0 |
| ex 3901 90 90 | 94 | Mixtures of A-B block copolymer of polystyrene and ethylene-butylene copolymer and A-B-A block copolymer of polystyrene, ethylene-butylene copolymer and polystyrene, containing by weight not more than 35 % of styrene | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3901 90 90<br>ex 3902 90 90 | 95<br>95 | Copolymer of ethylene and butylene, having hydroxyl or acrylate end-groups, containing by weight 40 % or more but not more than 60 % of butylene | 0 |
| ex 3901 90 90<br>ex 3902 90 90<br>ex 3903 90 90 | 96<br>96<br>50 | Linear A-B block copolymer of polyisoprene, whether or not epoxidised, and either ethylene-butylene copolymer or styrene-ethylene-butylene copolymer, having hydroxyl end-groups | 0 |
| ex 3901 90 90 | 97 | Copolymer of ethylene and octene, containing by weight 5 % or more but not more than 15 % of octene, of a specific gravity of less than 0,93 and a melt index of 0,80 or more but not exceeding 0,95 | 0 |
| ex 3902 10 00 | 10 | Polypropylene containing no plasticiser and not more than:<br>— 7 mg/kg of aluminium,<br>— 2 mg/kg of iron,<br>— 1 mg/kg of magnesium,<br>— 8 mg/kg of chloride | 0 |
| ex 3902 10 00 | 20 | Polypropylene, containing no plasticiser,<br>— of a melting point of more than 150 ºC (as determined by the ASTM D 3417 method),<br>— of a heat of fusion of 15 J/g or more but not exceeding 70 J/g,<br>— of an elongation at break of 1 000 % or more (as determined by the ASTM D 638 method),<br>— of a tensile modulus of 69 MPa or more but not exceeding 379 MPa (as determined by the ASTM D 638 method) | 0 |
| ex 3902 10 00 | 30 | Polypropylene, containing not more than 1 mg/kg of aluminium, 0,05 mg/kg of iron, 1 mg/kg of magnesium and 1 mg/kg of chloride, for use in the manufacture of packaging for disposable contact lenses [a] | 0 |
| ex 3902 30 00<br>ex 3903 90 90 | 91<br>25 | A-B block copolymer of polystyrene and an ethylene-propylene copolymer, containing by weight 40 % or less of styrene, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 |
| ex 3902 30 00 | 92 | Copolymer of propylene, butylene and ethylene, containing by weight more than 65 % but less than 80 % of propylene and not less than 20 % of butylene | 0 |
| ex 3902 90 90 | 92 | Polymers of 4-methylpent-1-ene | 0 |
| ex 3902 90 90 | 97 | Hydrogenated polyisobutene, in liquid form | 0 |
| ex 3903 19 00 | 20 | Polystyrene of a molecular weight ($M_n$) not exceeding 5 000 | 0 |
| ex 3903 90 90 | 10 | Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, whether or not containing a styrene-butadiene block copolymer, in one of the forms mentioned in note 6 (b) to Chapter 39, for the manufacture of sheetings for head-liners for cars [a] | 0 |
| ex 3903 90 90 | 15 | Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, also partially esterified, of an average molecular weight ($M_n$) not exceeding 3 000, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39 | 0 |
| ex 3903 90 90 | 20 | Copolymer of styrene with 2-ethylhexyl acrylate or with *n*-butyl acrylate, containing:<br>— 10 mole % or more but not more than 16 mole % of acrylate,<br>— 0,2 mg/kg or less of sodium<br>and<br>— 0,1 mg/kg or less of calcium | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3903 90 90<br>ex 3911 90 99 | 35<br>30 | Copolymer of α-methylstyrene and styrene, having a softening point exceeding 113 °C | 0 |
| ex 3903 90 90<br>ex 3906 90 90<br>ex 3911 90 99 | 40<br>40<br>50 | Copolymer of styrene with α-methylstyrene and acrylic acid, of a molecular weight ($M_n$) of 500 or more but not exceeding 6 000 | 0 |
| ex 3903 90 90<br>ex 3906 90 90 | 55<br>45 | Copolymer of styrene, methyl methacrylate, butyl acrylate and either acrylic acid or hydroxyethyl methacrylate, of a molecular weight ($M_n$) of 500 or more but not exceeding 6 000 | 0 |
| ex 3903 90 90 | 65 | Copolymer of styrene, butyl acrylate, butyl methacrylate, methyl methacrylate and acrylic acid, in the form of powder, containing by weight (81 ± 1) % of styrene, (6 ± 1) % of butyl acrylate, (5 ± 1) % of butyl methacrylate, (7 ± 1) % of methyl methacrylate and (1 ± 0,5) % of acrylic acid | 0 |
| ex 3903 90 90 | 70 | Ammonium polystyrenesulphonate, in the form of an aqueous solution | 0 |
| ex 3904 30 00 | 10 | Copolymer of vinyl chloride with vinyl acetate and maleic acid, containing by weight:<br>— 81,5 % or more but not more than 84,5 % of vinyl chloride,<br>— 13,8 % or more but not more than 16,2 % of vinyl acetate<br>and<br>— 0,8 % or more but not more than 1,2 % of maleic acid,<br>for the manufacture of goods of heading No 3215 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a) | 0 |
| ex 3904 40 00 | 91 | Copolymer of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight:<br>— 87 % or more but not more than 92 % of vinyl chloride,<br>— 2 % or more but not more than 9 % of vinyl acetate<br>and<br>— 1 % or more but not more than 8 % of vinyl alcohol,<br>in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of goods of heading No 3215 or 8523 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a) | 0 |
| ex 3904 40 00 | 92 | Copolymer of vinyl chloride, vinyl acetate, hydroxypropyl acrylate and maleic acid, containing by weight 80 % or more but not more than 83 % of vinyl chloride, 1,6 % or more but not more than 2 % of hydroxy groups and 0,25 % or more but not more than 0,38 % of carboxyl groups | 0 |
| ex 3904 50 90 | 91 | Copolymer of vinylidene chloride with vinyl chloride, containing by weight 79,5 % or more of vinylidene chloride, in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of fibres, monofilament or strip (a) | 0 |
| ex 3904 61 00 | 10 | Mixture of polytetrafluoroethylene and mica, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 |
| ex 3904 61 00 | 20 | Copolymer of tetrafluoroethylene and trifluoro(heptafluoropropoxy)ethylene, containing 3,2 % or more but not more than 4,6 % by weight of trifluoro(heptafluoropropoxy)ethylene and less than 1 mg/kg of extractable fluoride ions | 0 |
| ex 3904 69 90 | 92 | Copolymer of tetrafluoroethylene and trifluoro(trifluoromethoxy)ethylene | 0 |
| ex 3904 69 90 | 93 | Copolymer of ethylene with chlorotrifluoroethylene, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 |
| ex 3904 69 90 | 94 | Copolymer of ethylene and tetrafluoroethylene | 0 |
| ex 3904 69 90 | 96 | Polychlorotrifluoroethylene, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39 | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3905 91 00 | 91 | Copolymer of *N*-vinylcaprolactam, *N*-vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate | 0 |
| ex 3905 91 00 | 93 | Copolymer of ethylene and vinyl alcohol (EVOH) | 0 |
| ex 3905 99 90 | 93 | Polyvinyl acetate phthalate | 0 |
| ex 3905 99 90 | 94 | Polymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, containing by weight 97 % or more but not more than 99 % of vinylpyrrolidone, in the form of a solution in water | 0 |
| ex 3905 99 90 | 95 | Hexadecylated or eicosylated polyvinylpyrrolidone | 0 |
| ex 3905 99 90 | 96 | Poly(vinyl formal), in one of the forms mentioned in note 6 (b) to Chapter 39, of a molecular weight ($M_w$) of 25 000 or more but not exceeding 150 000 and containing by weight:<br>— 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl acetate<br>and<br>— 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol | 0 |
| ex 3906 10 00 | 10 | Polymethyl methacrylate, in the form of expansible beads containing 2-methylpentane as blowing agent | 0 |
| 3906 90 60 | | Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide | 0 |
| ex 3906 90 90 | 10 | Polymerisation product of acrylic acid with small quantities of a polyunsaturated monomer, for the manufacture of medicaments of heading No 3003 or 3004 (a) | 0 |
| ex 3906 90 90 | 20 | Polymerisation product of acrylic acid with small quantities of a polyunsaturated monomer, for use as a stabiliser in emulsions or dispersions with a pH of more than 13 (a) | 6 |
| ex 3906 90 90 | 30 | Copolymer of styrene with hydroxyethyl methacrylate and 2-ethylhexyl acrylate, of a molecular weight ($M_n$) of 500 or more but not exceeding 6 000 | 0 |
| ex 3906 90 90 | 50 | Acrylic polymers, containing by weight 2,5 % or more of chloroethyl vinyl ether or chloromethyl acrylate, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 |
| ex 3907 20 11 | 10 | Poly(ethylene oxide) of an average molecular weight ($M_n$) of 100 000 or more | 0 |
| ex 3907 20 29 | 10 | Polymer of dextrose, sorbitol and citric or phosphoric acid, containing by weight 90 % or more of dextrose monomer units | 0 |
| ex 3907 20 29 | 20 | Poly[oxy-1,4-phenyleneisopropylidene-1,4-phenyleneoxy-(2-hydroxytrimethylene)], of an average molecular weight ($M_w$) of more than 26 000, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 |
| ex 3907 20 99 | 10 | Bis{2-[$\omega$-hydroxy-poly(ethyleneoxy)]ethyl} hydroxy-methylphosphonate | 0 |
| ex 3907 20 99 | 15 | Poly(oxypropylene) having alkoxysilyl end-groups | 0 |
| ex 3907 20 99 | 25 | $\alpha$-4-Hydroxybutyl-$\omega$-hydroxypoly(oxytetramethylene), containing less than 1 mg/kg of halogen and less than 1 mg/kg of metal, and of a colour not exceeding 20 units on the Hazen scale | 0 |
| ex 3907 20 99 | 30 | Homopolymer of 1-chloro-2,3-epoxypropane (epichlorohydrin) | 0 |
| ex 3907 30 00 | 20 | Epoxyde resin in the form of powder, containing by weight 44 % or more but not more than 55 % of quartz and 0,5 % or more but not more than 1 % of diantimony trioxide, for the coating of film capacitors (a) | 0 |
| ex 3907 30 00 | 30 | Epoxyde resin, without solvent, containing mineral fillers (silica), without glass fibre, of a specific weight at 25 °C of 1,55 g/cm$^3$ or more but not exceeding 1,60 g/cm$^3$ | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3907 30 00 | 40 | Epoxyde resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of heading No 8533, 8535, 8536, 8541, 8542 or 8548 (a) | 0 |
| ex 3907 40 00 | 10 | Copolymer of hexane-1,6-diol, cyclohexane-1,4-dimethanol and ethylene carbonate | 0 |
| ex 3907 91 90 | 10 | Diallyl phthalate prepolymer, in the form of powder | 0 |
| ex 3907 99 19<br>ex 3907 99 99 | 10<br>10 | Poly(oxy-1,4-phenylenecarbonyl), in the form of powder | 0 |
| ex 3907 99 19 | 20 | Liquid crystal copolyester with a melting point of not less than 270 °C, whether or not containing fillers | 0 |
| ex 3908 90 00 | 10 | Poly(iminomethylene-1,3-phenylenemethyleneiminoadipoyl), in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 |
| ex 3908 90 00 | 20 | Copolymer consisting of hexamethylenediamine, isophthalic acid and terephthalic acid, in one of the forms mentioned in note 6(b) to Chapter 39 | 0 |
| ex 3909 40 00 | 10 | Polycondensation product of phenol with formaldehyde, in the form of hollow spheres of a diameter of less than 150 μm | 0 |
| ex 3910 00 00 | 10 | 3-[(2-Aminoethyl)amino]propyl(methyl)cyclosiloxane | 0 |
| ex 3910 00 00 | 20 | Block copolymer of poly(methyl-3,3,3-trifluoropropylsiloxane) and poly[methyl(vinyl)siloxane] | 0 |
| ex 3911 90 19 | 10 | Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene) | 0 |
| ex 3911 90 19 | 20 | Hydrocarbon prepolymer, obtained by the reaction of cyclopentadiene and 1,3-pentadiene | 0 |
| ex 3911 90 99 | 20 | Copolymer of dibutyl maleate and *N*-vinyl-2-pyrrolidone, in one of the forms mentioned in note 6 (a) of Chapter 39 | 0 |
| ex 3911 90 99 | 25 | Copolymer of vinyltoluene and *α*-methylstyrene | 0 |
| ex 3911 90 99 | 40 | Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not more than 16 % by weight | 0 |
| ex 3911 90 99 | 45 | Copolymer of maleic acid and methyl vinyl ether | 0 |
| ex 3911 90 99 | 55 | Solution containing:<br>— (36 ± 0,5) % by weight of polyamide with lateral ester groups,<br>— (2 ± 0,5) % by weight of acrylic ester,<br>— (48 ± 0,5) % by weight of 1-methyl-2-pyrrolidone,<br>— (12 ± 0,5) % by weight of bis(2-methoxyethyl) ether,<br>— 500 μg/kg or less of potassium<br>and<br>— 500 μg/kg or less of iron,<br>for use in the manufacture of goods of heading No 8542 (a) | 0 |
| ex 3912 11 00 | 10 | Non-plasticised cellulose triacetate, in the form of flakes, for the manufacture of cellulose triacetate yarn (a) | 0 |
| ex 3912 39 10 | 10 | Ethylcellulose, not plasticised | 0 |
| ex 3912 39 10 | 20 | Ethylcellulose, in the form of aqueous dispersion containing hexadecan-1-ol and sodium dodecyl sulphate, containing by weight (27 ± 3) % of ethylcellulose | 0 |
| ex 3912 39 80 | 10 | Cellulose, both hydroxyethylated and ethylated, insoluble in water | 0 |
| ex 3912 39 80 | 20 | Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms | 0 |
| ex 3912 90 10 | 10 | Cellulose acetate propionate, non-plasticised, in the form of powder:<br>— containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method) | |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| | | and<br>— of a viscosity not exceeding 120 poise (as determined by the ASTM D 817-72 method),<br>for the manufacture of printing inks, paints, lacquers and other coatings, and reprographic coatings (a) | 0 |
| ex 3913 90 80 | 30 | Chondroitinsulphuric acid, sodium salt | 0 |
| ex 3915 90 93 | 30 | Waste, parings and scrap of photographic, cinematographic and radiographic films | 0 |
| ex 3917 32 10 | 10 | Flexible pipe of silicone foam, with continuous channels, of a Shore A hardness of 7 or more but not exceeding 48 and a density of 0,28 g/cm$^3$ or more but not exceeding 0,92 g/cm$^3$ | 0 |
| ex 3917 32 39 | 20 | Pipe consisting of a block copolymer of polytetrafluoroethylene and polyperfluoroalkoxytrifluoroethylene, having a length of not more than 570 mm, a diameter of not more than 50 mm and a wall-thickness of not less than 30 and not more than 110 µm | 0 |
| ex 3919 10 38 | 10 | Self-adhesive tape of metallised polyurethane containing glass beads for use in the manufacture of marine life-saving equipment (a) | 0 |
| ex 3919 10 38<br>ex 3919 90 38 | 20<br>10 | Reflecting film, consisting of a layer of polyurethane with security imprints and embedded glass beads on one side and an adhesive layer on the other side, covered on one or both sides with a release layer | 0 |
| ex 3919 10 61<br>ex 3919 90 61 | 91<br>94 | Reflecting film, consisting of a layer of polyvinylchloride, a layer of alkyd polyester, with security imprints and embedded glass beads, and an adhesive layer covered with a release layer | 0 |
| ex 3919 90 10 | 10 | Shaped sheet of plastic, with an adhesive layer containing polyisobutylene and pectin, for the manufacture of colostomy bags (a) | 0 |
| ex 3919 90 31<br>ex 3920 62 19<br>ex 3920 62 90<br>ex 3920 63 00<br>ex 3920 69 00 | 40<br>20<br>20<br>30<br>30 | Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers (a) | 0 |
| ex 3919 90 61<br>ex 3919 90 69 | 92<br>92 | Polyvinyl chloride sheeting, of a thickness of less than 1 mm, coated with an adhesive in which are embedded glass balls of a diameter not exceeding 100 µm | 0 |
| ex 3919 90 61<br>ex 3919 90 69<br>ex 3920 10 89 | 93<br>93<br>25 | Adhesive film consisting of a base of a copolymer of ethylene and vinyl acetate (EVA) of a thickness of 120 µm or more and an adhesive part of acrylic type of a thickness of 10 µm or more, for the protection of the surface of silicon discs (a) | 0 |
| ex 3919 90 69 | 94 | Reflecting laminated sheet, consisting of a film of polymethyl methacrylate embossed on one side in a regular pyramidal or other shaped pattern, a film of polymethyl methacrylate containing glass microprisms or microspheres, an adhesive layer and a release sheet | 0 |
| ex 3920 10 26 | 20 | Film of polyethylene, of a thickness of 20 µm or more but not exceeding 45 µm, containing calcium carbonate in the mass, for the manufacture of napkins for babies or of sanitary towels or of tampons or of disposable surgical gowns (a) | 0 |
| ex 3920 10 26<br>ex 3920 10 89 | 30<br>20 | Film of a thickness not exceeding 0,20 mm, of a blend of polyethylene and a copolymer of ethylene with oct-1-ene, embossed in a regular rhomboidal pattern, for coating both sides of a layer of unvulcanised rubber (a) | 0 |
| ex 3920 10 28<br>ex 3920 10 89 | 92<br>30 | Polyethylene sheet, of a thickness of 0,025 mm or more but not exceeding 3 mm, of an elongation at break of 100 % or more but not exceeding 1 100 % (as determined by the ASTM D 638 and 882 methods), in rolls of a width of 4,57 m, 4,9 m, 7,01 m or 9,3 m | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3920 10 40 | 91 | Synthetic paper pulp, in the form of moist sheets, made from unconnected finely-branched polyethylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing polyvinyl alcohol dissolved in water as the moistening agent | 0 |
| ex 3920 10 40 | 92 | Laminated sheet or strip consisting of a film composed of a blend of a copolymer of ethylene with vinyl acetate and a modified ethylene-propylene-elastomer (EPM) or a modified ethylene-propylene-diene elastomer (EPDM), coated or covered on both sides with a film of a copolymer of ethylene with vinyl acetate | 0 |
| ex 3920 10 89 | 35 | Reflecting film, consisting of a layer of polyethylene with security imprints and embedded glass beads on one side and a hot-melt adhesive layer on the other side, the first side covered with a release layer | 0 |
| ex 3920 20 29 | 91 | Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, having:<br>— a thickness of 55 μm or more but not exceeding 97 μm,<br>— a tensile modulus in the machine direction of 0,75 GPa or more but not exceeding 1,45 GPa<br>and<br>— a tensile modulus in the transverse direction of 0,20 GPa or more but not exceeding 0,55 GPa | 0 |
| ex 3920 20 90 | 91 | Synthetic paper pulp, in the form of moist sheets, made from unconnected finely-branched polypropylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing polyvinyl alcohol dissolved in water as the moistening agent | 0 |
| ex 3920 20 90 | 92 | Laminated sheet or strip, consisting of a film of a thickness of 181 μm or more but not exceeding 223 μm composed of a blend of a copolymer of propylene with ethylene and a copolymer of styrene-ethylene-butylene-styrene (SEBS) coated or covered on one side with a layer of a copolymer of styrene-ethylene-butylene-styrene (SEBS) and a layer of polyester | 0 |
| ex 3920 30 00 | 20 | Laminated sheet or strip, consisting of a film composed of a blend of a thermoplastic elastomer (TPE) of styrene-butadiene-styrene (SBS) with polyethylene or polypropylene, of a thickness of 100 μm or more but not exceeding 200 μm, coated or covered on both sides with a film of polypropylene of a thickness not exceeding 20 μm | 0 |
| ex 3920 42 11<br>ex 3920 42 91 | 92<br>92 | Reflecting sheeting, consisting solely of a single layer of polyvinyl chloride, wholly embossed on one side in a regular pyramidal pattern | 0 |
| ex 3920 42 91 | 93 | Sheeting of polyvinyl chloride, stabilised against ultra-violet rays, without any holes, even microscopic, of a thickness of 60 μm or more but not exceeding 80 μm, containing 30 or more but not more than 40 parts of plasticiser to 100 parts of polyvinyl chloride | 0 |
| ex 3920 42 91 | 94 | Polyvinyl chloride sheet, with relief printing, for the manufacture of templates for textile printing (a) | 0 |
| ex 3920 51 00 | 10 | Polymethyl methacrylate plate, with an antistatic coating, of dimensions of 738 × 972 mm (± 1,5 mm) | 0 |
| ex 3920 51 00 | 20 | Plate of polymethyl methacrylate containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not exceeding 19 mm | 0 |
| ex 3920 61 00 | 10 | Polycarbonate film of a thickness not exceeding 15 μm, for the manufacture of film capacitors (a) | 0 |
| ex 3920 62 19 | 10 | Polyethylene terephthalate film, of a thickness of less than 11 μm, for the manufacture of audiodigital tapes for cassettes (a) | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3920 62 19 | 15 | Polyethylene terephtalate film, not coated with an adhesive, of a thickness not exceeding 25 µm, either:<br>— only dyed in the mass, or<br>— dyed in the mass and metallised on one side | 0 |
| ex 3920 62 19 | 25 | Film of polyethylene terephthalate only, of a total thickness not exceeding 120 µm, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material | 0 |
| ex 3920 62 19 | 30 | Polyethylene terephthalate film, of a thickness of 20 µm or more but not exceeding 30 µm, coated on one side with silicone, for use in the manufacture of window film (a) | 5,6 |
| ex 3920 62 19 | 35 | Laminated film of polyethylene terephthalate only, of a total thickness not exceeding 120 µm, consisting of one layer which is metallised only and one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material | 0 |
| ex 3920 62 19 | 40 | Film of polyethylene terephthalate, coated or covered on one side or on both sides with a layer of modified polyester, of a total thickness of 7 µm or more but not exceeding 11 µm, for the manufacture of video tapes with a magnetic layer of metallic pigments and a width of 8 mm or of 12,7 mm (a) | 0 |
| ex 3920 62 19 | 45 | Single ply film of polyethylene terephthalate only, of a thickness not exceeding 120 µm, which only:<br>— contains a colouring and/or UV-absorbing material throughout the mass<br>and<br>— is metallised on one side,<br>whether or not coated on one or both sides with a vinyl acrylate polymer but having no other coating or adhesive | 0 |
| ex 3920 62 19 | 50 | Film of polyethylene terephthalate, of a total thickness not exceeding 120 µm, of a width of 100 mm or more but not exceeding 115 mm, coated on both sides with one or more layers containing different chemicals, for the manufacture of goods of subheading 3701 20 00 (a) | 0 |
| ex 3920 62 19 | 55 | Film of polyethylene terephthalate, on one side metallised and coated with white ink and a protective layer and on the other side coated with a thermosensitive seal layer, of a width of 100 mm or more but not exceeding 150 mm, for the manufacture of goods of subheading 3701 20 00 (a) | 0 |
| ex 3920 62 19 | 60 | Film of polyethylene terephthalate, coated on one side with a layer of modified polyester, of a thickness of 20 µm (± 0,7 µm) or of 30 µm (± 0,9 µm), for the manufacture of audio-magnetic tapes of a total thickness of 33 µm or more (a) | 0 |
| ex 3920 62 19 | 62 | Polyethylene terephthalate film, of a thickness not exceeding 12 µm, coated on one side with a layer of aluminium oxide of a thickness not exceeding 350 Å | 0 |
| ex 3920 62 19 | 64 | Polyethylene terephthalate film, of a thickness of 18 µm or more but not exceeding 25 µm, having:<br>— a shrinkage of (3,4 ± 0,1) % in the machine direction (as determined by the ASTM D 1204 method)<br>and<br>— a shrinkage of (0,3 ± 0,2) % in the transverse direction (as determined by the ASTM D 1204 method) | 0 |
| ex 3920 62 19 | 65 | Polyethylene terephthalate film, of a thickness not exceeding 19 µm or of a weight of 20 g/m$^2$ or more but not exceeding 26,7 g/m$^2$, for use in the manufacture of photo-resist film (a) | 0 |

▼**M7**

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3920 62 19 | 70 | Film of polyethylene terephthalate, coated on both sides with a layer of epoxy acrylic resin, of a total thickness of 37 µm (± 3 µm) | 0 |
| ex 3920 62 19 | 75 | Film of polyethylene terephthalate, coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness not exceeding 300 µm and having a surface resistivity not exceeding 10 000 ohms (per square) (as determined by the ASTM D 257-93 method) | 0 |
| ex 3920 62 19 | 80 | Matt film of polyethylene terephthalate, of a gloss of 15 at an angle of 45º and 18 at an angle of 60º (as determined by the ASTM D 523 method) and a width of 1 600 mm or more | 0 |
| ex 3920 62 19 | 81 | Film of white polyethylene terephthalate, dyed in the mass, of a thickness of 185 µm or more but not exceeding 253 µm, coated on both sides with an antistatic layer | 0 |
| ex 3920 62 19 | 85 | Film of a total thickness of 4,5 µm (± 0,16 µm), consisting of a biaxially-oriented polyethylene terephthalate film, of a thickness of 4,4 µm, an elastic modulus (in the machine direction) of 12 kg/mm$^2$ (± 2 kg/mm$^2$) and a tensile strength (in the machine direction) of more than 28 kg/mm$^2$, and of an anti-adherent coating of a thickness of 0,1 µm | 0 |
| ex 3920 62 19 | 87 | Polyethylene terephthalate film, coated with a wax layer, a scratch resistant layer and a thermoadhesive layer, of a nominal width of 790 mm and a total thickness of 23 µm or more but not exceeding 26 µm | 0 |
| ex 3920 62 19 | 89 | Multilayer film of a thickness not exceeding 150 µm, consisting of a polyester film coated on one side with polycarbonate resin, metallised on the other side with titanium coated with polycarbonate resin and other layers containing *N,N'*-diphenyl-*N,N'*-di-*m*-tolylbiphenyl-4,4'-ylenediamine | 0 |
| ex 3920 62 90 | 30 | Film of polyethylene terephthalate, of a thickness of 500 µm (± 25 µm) | 0 |
| ex 3920 69 00 | 20 | Film of polyethylene naphthalene-2,6-dicarboxylate, of a thickness of 82 µm or more but not exceeding 88 µm | 0 |
| ex 3920 69 00 | 40 | Iridescent film of polyester and polymethyl methacrylate | 0 |
| ex 3920 69 00 | 50 | Polycondensation product of terephthalic acid with a mixture of cyclohex-1,4-ylenedimethanol and ethane-1,2-diol, in the form of a film | 0 |
| ex 3920 69 00 | 60 | Film of a copolymer of ethylene terephthalate and ethylene isophthalate, of a thickness not exceeding 2 µm | 0 |
| ex 3920 91 00 | 91 | Polyvinyl butyral film having a graduated coloured band | 6 |
| ex 3920 91 00 | 92 | Plasticised film of polyvinyl butyral, containing by weight:<br>— either 14,5 % or more but not more than 17,5 % of dihexyl adipate,<br>— or 14,5 % or more but not more than 28,5 % of dibutyl sebacate | 0 |
| ex 3920 91 00 | 93 | Film of polyethylene terephthalate, metallised on one or both sides, or laminated film of polyethylene terephthalate films, metallised on the external sides only, and having the following characteristics:<br>— a visible light transmission of 50 % or more,<br>— coated on both sides with a layer of polyvinyl butyral but not coated with an adhesive or any other material except polyvinyl butyral,<br>— a total thickness not exceeding 0,2 mm without taking the presence of polyvinyl butyral into account,<br>for use in the manufacture of heat-reflecting laminated glass ([a]) | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 3920 99 28 | 10 | Reflecting sheet of metallised polyurethane, containing glass beads, coated with a hot-melt adhesive layer, covered on one or both sides with a release sheet, in rolls of a width of 1 020 mm (± 20 mm), for slitting into safety clothing reflecting strip (a) | 0 |
| ex 3920 99 28 | 20 | Reflecting film, consisting of a layer of polyurethane with security imprints and embedded glass beads on one side and an adhesive layer on the other side, the first side covered with a release layer | 0 |
| 3920 99 53<br>ex 3920 99 59 | 55 | Ion-exchange membranes of fluorinated plastic material | 0 |
| ex 3920 99 59 | 20 | Film entirely of polyvinyl alcohol, of a thickness not exceeding 1 mm and containing by weight:<br>— 2 % or less of unhydrolysed acetate groups evaluated as vinyl acetate<br>and<br>— 5 % or more but not more than 25 % of glycerol as plasticiser,<br>for the manufacture of roof-windows (a) | 0 |
| ex 3920 99 59 | 25 | Poly(1-chlorotrifluoroethylene) film | 0 |
| ex 3920 99 59 | 30 | Film and sheet of a copolymer of ethylene with chlorotrifluoroethylene, of a thickness of 12 μm or more but not exceeding 400 μm | 0 |
| ex 3920 99 59 | 35 | Film entirely of polyvinyl alcohol, of a thickness not exceeding 1 mm and of a width of 2,20 m or more, with an extension at break, in the transverse direction, of 350 % or more | 0 |
| ex 3920 99 59 | 40 | Biaxially-oriented film of polyvinyl alcohol, coated on both sides, of a total thickness of less than 1 mm | 0 |
| ex 3920 99 59 | 45 | Iridescent film of polyester, polyethylene and an ethylene-vinyl acetate copolymer | 0 |
| ex 3920 99 59 | 50 | Polytetrafluoroethylene film, non-microporous, in the form of rolls, of a thickness of 0,019 mm or more but not exceeding 0,14 mm, impermeable to water vapour | 0 |
| ex 3921 19 00 | 91 | Microporous polypropylene film of a thickness not exceeding 100 μm | 0 |
| ex 3921 19 00 | 92 | Microporous film consisting of mixtures of cellulose acetate and cellulose nitrate, of a thickness not exceeding 200 μm | 0 |
| ex 3921 90 19 | 35 | Composite plate of polycarbonate and polybutylene terephthalate, reinforced with glass fibres | 0 |
| ex 3921 90 19 | 45 | Composite plate of polyethylene terephthalate or of polybutylene terephthalate, reinforced with glass fibres | 0 |
| ex 3921 90 60<br>ex 5407 71 00<br>ex 5903 90 99 | 91<br>20<br>10 | Woven polytetrafluoroethylene fabric, coated or covered with a copolymer of tetrafluoroethylene and trifluoroethylene having perfluorinated alkoxy side-chains ending in carboxylic acid or sulphonic acid groups, whether or not in the potassium or sodium salt form | 0 |
| ex 3926 90 91 | 20 | Reflecting sheeting or tape, consisting of a facing-strip of polyvinyl chloride embossed in a regular pyramidal pattern, heat-sealed in parallel lines or in a grid-pattern to a backing-strip of plastic material, or of knitted or woven fabric covered on one side with plastic material | 0 |
| ex 3926 90 99 | 10 | Microspheres of polymer of divinylbenzene, of a diameter of 4,5 μm or more but not exceeding 80 μm | 0 |
| ex 3926 90 99 | 20 | Tape pad, for use in the manufacture of goods of heading No 8523 (a) | 0 |
| ex 3926 90 99 | 30 | Guide pin and pole, for use in the manufacture of goods of subheadings 8523 11 00, 8523 12 00 and 8523 13 00 (a) | 0 |
| ex 4007 00 00 | 10 | Siliconated vulcanised rubber thread and cord | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 4008 11 00 | 10 | Blocks or sheets of cellular vulcanised rubber of modified ethylene-propylene-diene (EPDM) blended with chloroprene, which satisfy the Underwriters Laboratories Flammability Standard UL94HF-1 | 0 |
| ex 4016 99 88 | 10 | Soft rubber sealing stoppers for the manufacture of electrolytic capacitors (a) | 0 |
| 4105 11 91<br>4105 11 99<br>4105 12 10<br>4105 12 90<br>4105 19 10<br>4105 19 90 | | Sheep or lamb skin leather, without wool on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4108 or 4109 | 0 |
| 4106 11 90<br>4106 12 00<br>4106 19 00 | | Goat or kid skin leather, without hair on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4108 or 4109 | 0 |
| 4107 10 10<br>4107 29 10<br>4107 90 10 | | Leather of other animals, without hair on, not further prepared than tanned, other than leather of heading No 4108 or 4109 | 0 |
| ex 4802 51 90<br>ex 4802 52 20<br>ex 4802 52 80 | 10<br>10<br>10 | Overlay paper, of a width of more than 110 cm and containing by weight more than 5 % of corundum | 0 |
| ex 4805 60 90 | 20 | Paper, in cross-wise rewound spiral rolls, of a weight of less than 150 g/m$^2$ and of a thickness not exceeding 0,05 mm, for the manufacture of electrolytic capacitors (a) | 0 |
| ex 4810 99 10 | 10 | Bleached paper coated with kaolin, for use in the manufacture of tampon applicators (a) | 0 |
| ex 4811 21 00 | 10 | Impregnated paper coated or covered with a pressure-sensitive self-adhesive layer, the whole:<br>— of a tensile of 2 700 N/m or more but not exceeding 3 700 N/m in the machine direction (as determined by the EN ISO 1924-2 and ISO 3781 methods),<br>— of a stretch factor of 1,5 % or more but not exceeding 3,0 % in the machine direction (as determined by the EN ISO 1924-2 and ISO 3781 methods) | 0 |
| ex 4811 31 00 | 10 | Paper coated with acrylic polymer, with a gloss of 75 or more but not exceeding 90 (as determined by the Hunter method), of a weight of 160 g/m$^2$ or more but not exceeding 180 g/m$^2$, for use as casting paper in the manufacture of films of plastics (a) | 0 |
| ex 4811 39 00 | 10 | Kraft paper impregnated with an acrylic polymer, of a nominal weight of 85 g/m$^2$ | 0 |
| ex 4823 90 50 | 10 | Paper coated with dye retention and dye releasing agents used to produce a positive image, for the manufacture of goods of subheading 3701 20 00 (a) | 0 |
| ex 4823 90 50 | 20 | Honeycomb filter, of paper impregnated with carbon, of a thickness greater than 10 mm but not exceeding 30 mm | 0 |
| ex 4823 90 90 | 12 | Strips of paper glued to one another to form a honeycomb of a height not exceeding 13 cm, for agricultural purposes (a) | 0 |
| ex 4911 99 00 | 10 | Polyester film, partially coated with a magnetic metal layer showing a regular repeating logo or motif, for the manufacture of security threads (a) | 0 |
| 5002 00 00 | | Raw silk (not thrown) | 0 |
| ex 5004 00 10<br>ex 5004 00 90 | 10<br>10 | Yarn spun entirely from silk, not put up for retail sale | 2,5 |
| ex 5005 00 10<br>ex 5005 00 90 | 10<br>10 | Yarn spun entirely from silk waste (noil), not put up for retail sale | 0 |
| 5208 11 10 | | Fabrics for the manufacture of bandages, dressings and medical gauzes | 5,4 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 5402 41 00 | 10 | Polyamide yarn, not textured, untwisted or with a twist not exceeding 22 turns per metre, of crimpable bicomponent filaments consisting of poly(hexamethylene adipamide) with a copolyamide, for the manufacture of:<br>— knee-length stockings of subheadings 6115 20 11 and 6115 93 30,<br>— women's stockings of subheadings 6115 20 19 and 6115 93 91<br>or<br>— panty hose (tights) of subheading 6115 11 00 (a) | 0 |
| ex 5402 41 00 | 20 | Yarn of synthetic textile fibres solely of aromatic polyamides obtained by the polycondensation of *m*-phenylenediamine and isophthalic acid | 0 |
| ex 5402 43 00 | 20 | Synthetic bicomponent filament yarn, not textured, untwisted, measuring 1 650 decitex, consisting of 110 filaments each having a core of polyethylene terephthalate and a skin of polyamide-6, containing by weight 75 % or more but not exceeding 77 % of polyethylene terephthalate, for use in the manufacture of roofings (a) | 0 |
| ex 5402 49 99<br>ex 5402 69 90 | 10<br>20 | Multifilaments yarn of polytetrafluoroethylene | 0 |
| ex 5402 49 99 | 30 | Yarn of a copolymer of glycollic acid with lactic acid, for the manufacture of surgical sutures (a) | 0 |
| ex 5402 49 99<br>ex 5402 59 90<br>ex 5402 69 90 | 50<br>20<br>40 | Non-textured filament yarn of polyvinyl alcohol | 0 |
| ex 5402 49 99<br>ex 5402 69 90 | 60<br>10 | Yarn wholly of polyglycollic acid | 0 |
| ex 5402 49 99 | 70 | Synthetic filament yarn, single, containing by weight 85 % or more of acrylonitrile, in the form of a wick containing 1 000 continuous filaments or more but not more than 25 000 continuous filaments, of a weight per metre of 0,12 g or more but not exceeding 3,75 g and of a length of 100 m or more, for the manufacture of carbon-fibre yarn (a) | 0 |
| ex 5402 49 99 | 80 | Polyethylene filament yarn, untwisted, of either 55, 110, 165 or 1 760 decitex, for the manufacture of goods of heading No 5607 (a) | 0 |
| ex 5402 49 99 | 85 | Synthetic filament yarn, single, untwisted, wholly of poly(thio-1,4-phenylene) | 0 |
| ex 5404 10 90 | 10 | Monofilament of polytetrafluoroethylene | 0 |
| ex 5404 10 90 | 20 | Monofilament of poly(1,4-dioxanone) | 0 |
| ex 5404 10 90 | 30 | Monofilament of a copolymer of 1,3-dioxan-2-one with 1,4-dioxan-2,5-dione, for the manufacture of surgical sutures (a) | 0 |
| ex 5407 71 00 | 10 | Woven fabrics of polyvinyl alcohol fibres, for machine embroidery | 0 |
| ex 5501 90 90 | 10 | Polyvinyl alcohol tow | 0 |
| ex 5503 20 00 | 10 | Polyester staple fibres, loaded with zeolite impregnated with a mixture of salts of copper and silver or of salts of zinc and silver | 4 |
| ex 5503 90 10<br>ex 5503 90 90 | 10<br>30 | Acetalised, multicomponent spun fibres with a matrix fibril structure, consisting of emulsion-polymerised polyvinyl alcohol and polyvinyl chloride | 0 |
| ex 5503 90 90 | 10 | Textile fibres of polytetrafluoroethylene | 4 |
| ex 5503 90 90<br>ex 5506 90 90<br>ex 5601 30 00 | 20<br>10<br>10 | Polyvinyl alcohol fibres, whether or not acetalised | 0 |
| ex 5503 90 90 | 40 | Fibres wholly of poly(thio-1,4-phenylene) | 0 |
| ex 5601 30 00 | 20 | Polyester fibres, measuring 0,56 decitex, of a length of 3 mm or more but not exceeding 5 mm | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 5601 30 00 | 30 | Acrylic fibres, measuring 0,11 and 0,56 decitex, of a length of 3 mm or more but not exceeding 5 mm | 0 |
| ex 5603 11 10<br>ex 5603 11 90<br>ex 5603 12 10<br>ex 5603 12 90<br>ex 5603 91 10<br>ex 5603 91 90<br>ex 5603 92 10<br>ex 5603 92 90 | 10<br>10<br>10<br>10<br>10<br>10<br>10<br>10 | Polyvinyl alcohol non-wovens, in the piece or cut into rectangles:<br>— of a thickness of 200 µm or more but not exceeding 280 µm<br>and<br>— of a weight of 20 g/m² or more but not exceeding 50 g/m² | 0 |
| ex 5603 11 10<br>ex 5603 11 90<br>ex 5603 12 10<br>ex 5603 12 90 | 20<br>20<br>20<br>50 | Non-wovens, containing spunbonded fibres of polypropylene or of polypropylene and polyethylene, for the manufacture of napkins and napkin liners for babies and similar sanitary articles (a) | 0 |
| ex 5603 12 90<br>ex 5603 13 90<br>ex 5603 14 90 | 30<br>30<br>10 | Non-wovens of aromatic polyamide fibres obtained by polycondensation of *m*-phenylenediamine and isophthalic acid, in the piece or cut into rectangles | 0 |
| ex 5603 12 90<br>ex 5603 13 90 | 60<br>60 | Non-wovens of spunbonded polyethylene, of a weight of more than 60 g/m² but not exceeding 80 g/m² and an air resistance (Gurley) of 8 s or more but not exceeding 36 s (as determined by the ISO 5636/5 method) | 0 |
| ex 5603 13 90<br>ex 5603 14 90 | 40<br>20 | Non-wovens consisting of a central layer of polycarbonate fibres, laminated on each side with spunbonded filaments of polyester, of a weight of more than 130 g/m² but not exceeding 200 g/m² | 0 |
| ex 5603 92 90<br>ex 5603 93 90 | 20<br>20 | Non-wovens consisting of a melt-blown central layer of a thermoplastic elastomer laminated on each side with spunbonded fibres of polypropylene | 0 |
| ex 5603 92 90<br>ex 5603 93 90 | 40<br>10 | Non-wovens of polypropylene consisting of a melt-blown central layer, laminated on each side with spun-bonded fibres, of a thickness not exceeding 550 µm and of a weight not exceeding 80 g/m², in the piece or simply cut into rectangular shape, not impregnated | 0 |
| ex 5603 92 90 | 50 | Non-wovens of staple fibres, in rolls, of a width of 78 mm or more but not exceeding 252 mm, for the manufacture of floppy discs (a) | 0 |
| ex 5603 94 90 | 20 | Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips (a) | 0 |
| ex 5607 50 90 | 10 | Twine, unsterilised, wholly of polyglycollic acid, plaited or braided, with an inner core, for the manufacture of surgical sutures (a) | 0 |
| ex 5903 10 90<br>ex 5903 20 90<br>ex 5903 90 99 | 10<br>10<br>20 | Knitted or woven fabrics, coated or covered on one side with artificial plastic material in which are embedded microspheres | 0 |
| ex 5903 20 90 | 20 | Tape of polyester fabric laminated with a metallised polyurethane film containing glass beads, for use in the manufacture of marine life-saving equipment (a) | 0 |
| ex 5907 00 90 | 10 | Textile fabrics, coated with adhesive in which are embedded spheres of a diameter not exceeding 75 µm | 0 |
| ex 5911 10 00 | 10 | Needle-punched synthetic-fibre felts, not containing polyester, whether or not containing catalytic particles entrapped within the synthetic fibres, coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products (a) | 0 |
| ex 5911 90 90 | 10 | Yarn and strip of impregnated polytetrafluoroethylene, whether or not oiled or graphited | 0 |
| ex 5911 90 90<br>ex 8421 99 00 | 30<br>92 | Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness not exceeding 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| 6305 10 10 | | Sacks and bags, of a kind used for the packing of goods, used, of jute or of other textile bast fibres of heading No 5303 | 0 |
| ex 6305 90 00<br>ex 6305 90 00 | 10<br>91 | Sacks and bags, of a kind used for the packing of goods, used, of flax or of sisal | 0 |
| ex 6903 20 90 | 10 | Yarn of continuous ceramic filaments, each filament containing by weight:<br>— 12 % or more of diboron trioxide,<br>— 26 % or less of silicon dioxide<br>and<br>— 60 % or more of dialuminium trioxide | 0 |
| ex 6903 90 80<br>ex 6909 19 00 | 10<br>40 | Beryllium oxide, of a purity by weight of more than 99 %, in the form of blanks, bars, blocks or plates | 0 |
| ex 6909 12 00 | 20 | Plate, of dialuminium trioxide and titanium carbide, of dimensions not exceeding 48 × 48 mm, or of a diameter not exceeding 125 mm, for the manufacture of magnetic heads (a) | 0 |
| ex 6909 19 00 | 30 | Supports for catalysts, consisting of porous cordierite or mullite ceramic pieces, of an overall volume not exceeding 651, having, per $cm^2$ of the cross-section, not less than one continuous channel which may be open at both ends or stopped at one end | 0 |
| ex 6909 19 00<br>ex 8102 99 00 | 50<br>10 | Disc (target) with deposition material, consisting of molybdenum silicide:<br>— containing 1 mg/kg or less of sodium<br>and<br>— mounted on a metal support | 0 |
| ex 7006 00 90 | 10 | Glass plate, coated on one side with chromium and/or with a mixture of diindium trioxide and tin dioxide, of dimensions of 260 × 320 mm or more but not exceeding 400 × 400 mm, of a thickness not exceeding 1,2 mm, for the manufacture of liquid crystal displays (a) | 0 |
| ex 7006 00 90 | 20 | Colour filter, consisting of a glass plate with red, blue and green pixels, having a total thickness of 1,1 mm (± 0,1 mm) and exterior dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, for the manufacture of liquid crystal displays (a) | 0 |
| ex 7006 00 90 | 30 | Glass plate, uncoated, of dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, of a thickness of 0,6 mm or more but not exceeding 1,2 mm, for the manufacture of liquid crystal displays (a) | 0 |
| ex 7006 00 90 | 40 | Disk of aluminosilicate glass, with a hole in the centre, with the edges having been ground and bevelled, of a total thickness not exceeding 1,2 mm | 0 |
| ex 7011 10 00 | 10 | Glass lenses with a stippled front refractor or with a front refractor composed of prismatic elements, with an external diameter of more than 121 mm but not exceeding 125 mm | 0 |
| ex 7011 10 00 | 20 | Parabolic glass reflectors, with an external diameter of more than 121 mm but not exceeding 125 mm | 0 |
| ex 7011 20 00 | 40 | Glass face-plate:<br>— with a diagonal measurement of 366,4 mm (± 1,5 mm) and of dimensions of 246,4 × 315,4 mm (± 1,5 mm),<br>— with a diagonal measurement of 391 mm (± 1,5 mm) and of dimensions of 261,4 × 326,8 mm (± 1,5 mm),<br>— with a diagonal measurement of 442 mm (± 1,5 mm) and of dimensions of 293,4 × 369,2 mm (± 1,5 mm),<br>— with a diagonal measurement of 544,5 mm (± 1,6 mm) and of dimensions of 358 × 454 mm (± 1,6 mm), having a cylindrical curvature,<br>— with a diagonal measurement of 570,5 mm (± 1,6 mm) and of dimensions of 360 × 486 mm (± 1,6 mm),<br>— with a diagonal measurement of 629,8 mm (± 3 mm) | |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| | | and of dimensions of 406,5 × 519 mm (± 2 mm), having a cylindrical curvature,<br>or<br>— with a diagonal measurement of 753 mm (± 1,6 mm) and of dimensions of 471 × 640 mm (± 1,6 mm),<br>and with a raised edge, for the manufacture of colour cathode-ray tubes (a) | 0 |
| ex 7011 20 00 | 75 | Glass face-plate:<br>— with a diagonal measurement of 604,5 mm (± 3 mm) and of dimensions of 340 × 541 mm (± 2 mm),<br>— with a diagonal measurement of 639,3 mm (± 3 mm) and of dimensions of 413,6 × 527 mm (± 2 mm),<br>— with a diagonal measurement of 708 mm (± 3 mm) and of dimensions of 404 × 633 mm (± 2 mm),<br>— with a diagonal measurement of 723 mm (± 3 mm) and of dimensions of 477 × 602 mm (± 2 mm),<br>or<br>— with a diagonal measurement of 812,8 mm (± 3 mm) and of dimensions of 463,8 × 725,5 mm (± 2 mm),<br>having a cylindrical curvature, for the manufacture of colour cathode-ray tubes (a) | 0 |
| ex 7014 00 00 | 10 | Optical elements of glass (other than those of heading No 7015), not optically worked, other than signalling glassware | 0 |
| ex 7019 12 00 | 10 | Rovings, measuring 2 600 tex or more but not more than 3 300 tex and of a loss on ignition of 4 % or more but not exceeding 8 % by weight (as determined by the ASTM D 2584-94 method) | 0 |
| ex 7019 19 10 | 10 | Yarn of 33 tex or a multiple thereof, ± 7,5 %, obtained from continuous spun-glass filaments of a nominal diameter of 3,5 µm or of 4,5 µm, in which filaments of a diameter of 3 µm or more but not exceeding 5,2 µm predominate, other than those treated so as to improve their adhesion to elastomers | 0 |
| ex 7019 19 10 | 30 | Yarn of 22 tex ± 7,5 %, obtained from continuous spun-glass filaments of a nominal diameter of 5 µm, in which filaments of a diameter of 4,2 µm or more but not exceeding 5,8 µm predominate | 0 |
| ex 7019 19 10 | 40 | Yarn of 33, 34 or 51 tex or a multiple thereof, ± 7,5 %, obtained from continuous spun-glass filaments of a nominal diameter of 6 µm, in which filaments of a diameter of 5,1 µm or more but not exceeding 6,9 µm predominate | 0 |
| ex 7019 32 00<br>ex 7019 39 00 | 10<br>10 | Non-woven product of non-textile glass fibre, for the manufacture of air-filters or of air-filtration products (a) | 0 |
| ex 7019 90 10 | 10 | Non-textile glass fibres in which fibres of a diameter of less than 3,5 µm predominate | 0 |
| ex 7019 90 10 | 20 | Non-textile E-glass fibres, of a length not exceeding 3 mm and a diameter of 5 µm, for the manufacture of catalysts for the purification of smokes (a) | 0 |
| ex 7116 20 90 | 10 | Disc of silicon on sapphire | 0 |
| 7202 50 00 | | Ferro-silico-chromium | 0 |
| ex 7212 50 91 | 10 | Perforated steel strip, plated or coated with nickel, of a width of 140 mm or more but not exceeding 400 mm and a thickness of 60 µm or more but not exceeding 90 µm | 0 |
| ex 7212 50 99 | 10 | Cold-rolled steel, coated on both sides with a nickel-zinc layer, in the form of strip of a width of 40,15 (± 0,08) mm and a thickness of 0,3 (± 0,01) mm, containing by weight:<br>— not more than 0,1 % of carbon,<br>— not more than 0,04 % of phosphorus,<br>— not more than 0,05 % of sulphur | |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| | | and<br>— 0,2 % or more but not more than 0,5 % of manganese | 0 |
| ex 7306 30 29 | 91 | Non-alloy steel precision tube, welded and cold finished, of an external diameter exceeding 160 mm and a wall thickness exceeding 2 mm | 0 |
| ex 7409 19 00 | 10 | Sheet or plate of polytetrafluoroethylene, with aluminium oxide or titanium dioxide as a filler or reinforced with glass-fibre fabric, laminated on both sides with copper foil | 0 |
| ex 7410 21 00 | 10 | Sheet or plate of polytetrafluoroethylene, with aluminium oxide or titanium dioxide as a filler or reinforced with glass-fibre fabric, laminated on both sides with copper foil, or sheet of polyimide, laminated on one side or on both sides with copper foil | 0 |
| ex 7606 11 91<br>ex 7606 11 93 | 20<br>20 | Strip with depth-etching, of band-anodic oxidation treated aluminium of a purity by weight of 99,9 % and a thickness of less than 3 mm, for incorporation in bodies for motor vehicles (a) | 0 |
| ex 7616 99 90 | 40 | Discs of aluminium alloy, coated or covered on both sides with a nickel-phosphorus layer, having a total thickness not exceeding 3,02 mm | 0 |
| ex 7616 99 90 | 50 | Discs of aluminium alloy, of a thickness not exceeding 0,84 mm, for the manufacture of goods of subheadings 8523 20 11 and 8523 20 19 (a) | 0 |
| ex 7905 00 00 | 10 | Plate of an alloy of zinc, ground and polished on one surface and coated with an epoxide resin on the other surface, of rectangular or square shape, of a length of 300 mm or more but not exceeding 2 000 mm and of a width of 300 mm or more but not exceeding 1 000 mm, and containing:<br>— 10 mg/kg or less of iron,<br>— 10 mg/kg or less of lead,<br>— 700 mg/kg or more but not more than 900 mg/kg of aluminium<br>and<br>— 500 mg/kg or more but not more than 900 mg/kg of magnesium,<br>for the manufacture of sensitised printing plates (a) | 0 |
| ex 8101 99 00 | 10 | Disc (target) with deposition material, of tungsten or an alloy containing by weight 90 % of tungsten and 10 % of titanium:<br>— containing 100 µg/kg or less of sodium<br>and<br>— mounted on a copper or aluminium support | 0 |
| ex 8103 90 90 | 10 | Welded tube solely of tantalum, or solely of an alloy of tantalum with tungsten containing by weight 3,5 % or less of tungsten | 0 |
| ex 8104 11 00 | 30 | Unwrought magnesium, of a purity by weight of 99,95 % or more, in the form of ingots, for the manufacture of zirconium sponge or elements used in the nuclear industry (a) | 0 |
| ex 8104 90 00 | 10 | Ground and polished magnesium sheets, of dimensions not exceeding 1 500 × 2 000 mm, coated on one side with an epoxy resin insensitive to light | 0 |
| ex 8108 10 10 | 10 | Titanium sponge | 0 |
| 8108 10 90 | | Waste and scrap of titanium | 0 |
| ex 8108 90 70 | 20 | Welded titanium tubes, of an external diameter of 19,0 (± 0,1) mm, having an external structure of 36 fins per 2,54 cm, for use in the manufacture of refrigerant condensers (a) | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 8108 90 90 | 92 | Disc (target) with deposition material, of titanium:<br>— containing 50 μg/kg or less of sodium<br>and<br>— mounted on a copper or aluminium support | 0 |
| ex 8109 10 10 | 10 | Non-alloy zirconium, in the form of ingots, containing by weight more than 0,01 % of hafnium, for use in the manufacture of tubes for the chemical industry (a) | 0 |
| ex 8110 00 11 | 10 | Antimony in the form of ingots | 0 |
| ex 8112 19 00 | 10 | Beryllium, of a purity by weight of 94 % or more, in the form of bars, plates and sheets | 0 |
| ex 8112 99 30 | 10 | Alloy of niobium (columbium) and titanium, in the form of bars and rods | 0 |
| ex 8414 90 90 | 10 | Aluminium pistons, partially covered with polytetrafluoroethylene, for incorporation into compressors of air conditioning machines of motor vehicles (a) | 0 |
| ex 8414 90 90 | 20 | Pressure-regulating system, for incorporation into compressors of air-conditioning machines of motor vehicles (a) | 0 |
| ex 8418 99 90 | 91 | Welded cooling micro-elements, of an alloy of aluminium, for the manufacture of condensers (a) | 0 |
| ex 8419 19 00 | 10 | Heat accumulator for motor vehicles, of a coolant capacity of 41 or more but not exceeding 101 | 0 |
| ex 8419 89 98 | 10 | Immersion-tube (coils) bundles, consisting of an assembly of plastic tubes terminating at each end in a honeycomb-structure (end-fitting) surrounded by a pipe-connector | 0 |
| ex 8419 89 98<br>ex 8543 89 95 | 20<br>58 | Sputtering machines and apparatus, comprising disk-handling equipment, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a) | 0 |
| ex 8421 99 00 | 91 | Parts of equipment, for the purification of water by reverse osmosis, consisting of a bundle of hollow fibres of artificial plastic material with permeable walls, embedded in a block of artificial plastic material at one end and passing through a block of artificial plastic material at the other end, whether or not housed in a cylinder | 0 |
| ex 8421 99 00 | 93 | Components of separators for the separation or purification of gases from gas mixtures, consisting of a bundle of permeable hollow fibres enclosed within a container, whether or not perforated, of an overall length of 300 mm or more but not exceeding 3 700 mm and a diameter not exceeding 500 mm | 0 |
| ex 8421 99 00 | 95 | Parts of equipment for the filtration of magnetic dispersions, consisting essentially of nylon-6 fibres, enclosed in a plastic casing of a diameter of 70 mm (± 2 mm) and a length of 520 mm (± 5 mm) | 0 |
| ex 8424 89 95<br>ex 8460 21 90<br>ex 8460 40 10<br>ex 8460 90 90<br>ex 8464 20 19<br>ex 8479 89 98 | 10<br>10<br>10<br>10<br>10<br>10 | Machines and apparatus providing automated lapping, polishing, grinding, cleaning or surface lubrication of disks, comprising disk-handling equipment, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a) | 0 |
| ex 8424 89 95<br>ex 8479 89 98 | 20<br>30 | Machines and apparatus providing automated cleaning or cleaning and drying of disks, by means of de-ionised water, ultrasonic waves, chemical solutions, heat or a combination of these processes, comprising disk-handling equipment, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a) | 0 |
| ex 8439 99 10<br>ex 8439 99 90 | 10<br>10 | Suction-roll shells, not drilled, in the form of alloy-steel tubes, of a length of 5 207 mm or more and an external diameter of 754 mm or more, for use in machinery for making paper or paperboard (a) | 0 |
| ex 8455 90 00 | 10 | Helical turn device for cold-rolling mill | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 8456 10 90 | 10 | Machine-tool operating by laser beam, for the cutting of slots on the surface of a cylindrical tube for use in the manufacture of endo-vascular prosthesis ('stents') (a) | 0 |
| ex 8460 90 90<br>ex 8463 90 00<br>ex 8479 89 98 | 20<br>10<br>20 | Machine-tool providing automated creation of a texture (a headlanding zone) on the surface of disks by means of abrasion or exposure to laser beams, comprising disk-handling equipment, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a) | 0 |
| ex 8473 40 19 | 20 | Thermal printer head | 0 |
| ex 8479 89 98<br>ex 8501 10 99 | 40<br>78 | Motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8525 20 91 or 8527 90 92 (a) | 0 |
| ex 8481 80 59 | 10 | Air control valve, consisting of a stepping motor and a valve pintle, for the regulation of idle air flow in fuel injection engines | 0 |
| ex 8483 10 80 | 10 | Integrally forged and roughly shaped generator and turbine shafts of a weight exceeding 215 t | 0 |
| ex 8501 10 99 | 54 | DC motor, brushless, with an external diameter not exceeding 25,4 mm, a rated speed of 2 260 (± 15 %) or 5 420 (± 15 %) rpm, a supply voltage of 1,5 or 3 V | 0 |
| ex 8501 10 99 | 59 | DC stepping motor, with an angle of step of 1,8° (± 0,09°), a holding torque of 0,156 Nm or more, a coupling flange the exterior dimensions of which do not exceed 43 × 43 mm, a chuck of a diameter of 4 mm (± 0,1 mm), a two-phase winding and an output not exceeding 5 W | 0 |
| ex 8501 10 99 | 73 | DC motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8471 70 53 (a) | 0 |
| ex 8501 10 99 | 77 | DC motor, with brushes, with a typical running torque of 0,004 Nm (± 0,001 Nm), with a coupling flange of a diameter of 32 mm (± 0,5 mm) and a chuck of a diameter of 2 mm (± 0,004 mm), with an internal rotor, a three-phase winding, a rated speed of 2 800 (± 10 %) rpm and a supply voltage of 12 V (± 15 %) | 0 |
| ex 8502 40 90 | 10 | Rotary converter, with a ferrite core, having coils with 2 or 6 windings and a diameter of 0,1 mm, connected to a flexible printed circuit | 0 |
| ex 8503 00 91<br>ex 8503 00 99 | 31<br>32 | Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring | 0 |
| ex 8503 00 99 | 31 | Stamped collector of an electric motor, having an external diameter not exceeding 16 mm | 0 |
| ex 8504 40 99 | 20 | Direct current to direct current converter | 0 |
| ex 8504 40 99 | 30 | Static converter comprising a power switch with insulated-gate bipolar transistors (IGBTs), contained in a housing, for use in the manufacture of microwave ovens of subheading 8516 50 00 (a) | 0 |
| ex 8504 50 80 | 30 | Inductor with an inductance not exceeding 62 mH | 0 |
| ex 8504 50 80 | 40 | Multilayer monolithic inductors, contained in a housing of the SMD (surface mounted device) type the exterior dimensions of which do not exceed 1,8 × 3,4 mm, for use in the manufacture of products falling within subheading 8517 11 00, 8525 20 91 or 8527 90 92 (a) | 0 |
| 8504 90 11 | | Ferrite cores | 0 |
| ex 8504 90 18 | 32 | Part of a rotary transformer, comprising a ferrite core provided with circular grooves with copper wire windings | 0 |
| ex 8505 11 00 | 31 | Ferrite magnet having a remanence of 455 mT (± 15 mT) | 0 |
| ex 8505 19 90 | 31 | Neodymium-ferro ring with an external diameter not exceeding 13 mm, an internal diameter not exceeding 9 mm | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 8505 90 10 | 91 | Solenoid with a plunger, operating at a nominal supply voltage of 24 V at a nominal DC of 0,08 A, for use in the manufacture of products falling within heading No 8517 (a) | 0 |
| ex 8505 90 10 | 92 | Electromechanical throttle plate actuator for automotive engines | 0 |
| ex 8506 50 90 | 10 | Lithium iodine single cell battery the dimensions of which do not exceed 9 × 23 × 45 mm and a voltage not exceeding 2,8 V | 0 |
| ex 8506 50 90 | 20 | Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit | 0 |
| ex 8506 50 90 | 30 | Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions not exceeding 28 x 45 x 15 mm and a capacity of not less than 1,05 Ah | 0 |
| ex 8507 30 91<br>ex 8507 80 91<br>ex 8507 80 99 | 20<br>10<br>10 | Rectangular accumulator, with a length not exceeding 69 mm, a width not exceeding 36 mm and a thickness not exceeding 12 mm, for use in the manufacture of rechargeable batteries (a) | 0 |
| ex 8507 30 91 | 30 | Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm (± 1,5 mm) and a diameter of 14,5 mm (± 1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (a) | 0 |
| ex 8507 80 91 | 20 | Cylindrical nickel-hydride accumulator, with a length of 44 mm (± 0,5 mm) and a diameter of 10 mm (± 0,5 mm), having a nominal capacity of 450 mAh or more, for use in the manufacture of rechargeable batteries (a) | 0 |
| ex 8507 80 91 | 30 | Cylindrical nickel-hydride accumulator, with a length of 42,5 mm (± 0,5 mm) and a diameter of 14 mm (± 0,5 mm), having a nominal capacity of 855 mAh or more, for use in the manufacture of rechargeable batteries (a) | 0 |
| ex 8507 80 91 | 40 | Cylindrical nickel-hydride accumulator, with a length of 49,5 mm (± 0,5 mm) and a diameter of 10 mm (± 0,5 mm), having a nominal capacity of 540 mAh or more, for use in the manufacture of rechargeable batteries (a) | 0 |
| ex 8507 80 91 | 50 | Cylindrical nickel-hydride accumulator with a length of 66,5 mm (± 1 mm) and a diameter of 10 mm (± 0,5 mm), having a nominal capacity of 900 mAh or more, for use in the manufacture of rechargeable batteries (a) | 0 |
| ex 8507 80 99 | 20 | Cylindrical lithium-ion accumulator, with a length of 64,6 mm or more and a diameter of 18,1 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (a) | 0 |
| ex 8516 90 00 | 31 | Dual diode, consisting of a power-rectifying diode connected with a transformer protector diode through a wire, with a peak reverse power rate of 2 J or more, for use in the manufacture of products falling within subheading 8516 50 00 (a) | 0 |
| ex 8518 29 80 | 20 | Loudspeaker having a power of 5 W and an impedance of 4 ohms, with a diameter not exceeding 50 mm, for use in the manufacture of portable phones (a) | 0 |
| ex 8518 30 80 | 20 | Headphone and earphone for hearing aids, contained in a housing the exterior dimensions of which, excluding connecting points, do not exceed 5 × 6 × 8 mm | 0 |
| ex 8518 90 00 | 91 | Integrally cold-upsetted steel coreplate, in the form of a disk on one side provided with a cylinder, for use in the manufacture of loudspeakers (a) | 0 |

▼**M7**

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 8520 90 90 | 20 | Drive-unit capable of magneto-optical signal recording and optical signal reproducing, comprising at least an optical unit, DC motors and a printed circuit on which are mounted integrated circuits providing drive and signal processing functions for reading optical discs having an external diameter not exceeding 70 mm, not comprising circuits with amplification functions or power supply drive functions | 0 |
| ex 8522 90 59 | 93 | Optical unit consisting of a laser diode with one photodiode, emitting light of a nominal wavelength of 780 nm, contained in a housing with a diameter of not more than 10 mm and a height of not more than 9 mm, with not more than 10 connections and bearing:<br>— an identification marking consisting of or including (one of) the following combination(s):<br>LDGU<br>LT 022<br>or<br>— other identification markings relating to devices complying with the abovementioned description | 0 |
| ex 8522 90 59 | 94 | Electronic assembly for a laser read-head of a compact-disc player, comprising:<br>— a printed circuit,<br>— a photo-detector, in the form of a monolithic integrated circuit, contained in a housing,<br>— not more than 3 connectors,<br>— not more than 1 transistor,<br>— not more than 3 variable and 4 fixed resistors,<br>— not more than 5 capacitors,<br>the whole mounted on a support | 0 |
| ex 8522 90 98 | 31 | Thin-film recording and reproducing device, having at least 9 parallel channels for digital signals and at least 2 channels for analogue signals, to which a non-magnetic ceramic substrate is fixed, the whole rounded at one side, for use in the manufacture of magnetic heads for digital sound recording and digital/analogue sound reproducing apparatus of the cassette-type (a) | 0 |
| ex 8522 90 98 | 32 | Sound reproducing assembly, consisting of a compact-disc mechanism, comprising an optical reading system and 3 DC motors, for use in the manufacture of products falling within subheading 8527 21 20 or 8527 21 70 (a) | 0 |
| ex 8522 90 98 | 34 | Cassette-deck sub-assembly for sound recording and reproducing apparatus, for use in the manufacture of telephone-answering machines (a) | 0 |
| ex 8522 90 98 | 35 | Sound-reproducing assembly, comprising a tape deck mechanism of the cassette type, comprising a DC motor, for use in the manufacture of products falling within heading No 8519 (a) | 0 |
| ex 8522 90 98 | 36 | Roll for magnetic tape guiding and winding, for use in the manufacture of products falling within heading No 8521 or 8522 (a) | 0 |
| ex 8522 90 98 | 37 | Magnetic head for erasing video tapes, for use in the manufacture of products falling within heading No 8521 or 8522 (a) | 0 |
| ex 8522 90 98 | 38 | Read-head assembly, comprising a laser read-head, 2 motors, a flexible printed circuit, the whole mounted on a plastic support, for use in the manufacture of products falling within subheading 8519 99 12 or 8519 99 18 (a) | 0 |
| ex 8522 90 98 | 39 | Assembly consisting of a driver circuit, a tacho-sensor and a brushless DC motor | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 8522 90 98 | 40 | Compact-disc changing and selection mechanism, comprising electronic components, not comprising circuits with amplification functions or power supply drive functions, for use in the manufacture of products falling within subheading 8527 31 91 (a) | 0 |
| ex 8522 90 98 | 41 | Assembly consisting of a drive-unit, comprising at least an optical unit, DC motors and a printed circuit on which are mounted integrated circuits providing drive and signal processing functions for reading optical discs, not capable of recording, for use in the manufacture of products falling within heading No 8521 (a) | 0 |
| ex 8522 90 98 | 42 | Sound reproducing assembly, consisting of a compact-disc changing and selection mechanism, comprising an optical reading system, DC motors and an electronic assembly not comprising circuits with amplification functions or power drive functions, for use in the manufacture of products falling within heading No 8527 (a) | 0 |
| ex 8522 90 98 | 43 | Analogue sound-recording and reproducing assembly, comprising a record/playback head and a twin tape deck mechanism of the cassette type, not comprising circuits with amplification functions or power supply drive functions, for use in the manufacture of products falling within subheadings 8527 31 91 and 8527 31 98 (a) | 0 |
| ex 8528 22 00 | 10 | Video monitor comprising:<br>— a flat screen monochrome cathode-ray tube with a diagonal measurement of the screen not exceeding 110 mm and equipped with a deflector yoke,<br>and<br>— a printed circuit on which are mounted a deflection unit, a video-amplifier and a transformer,<br>the whole mounted on a chassis, for the manufacture of video entry-phones, video telephones or surveillance apparatus (a) | 0 |
| ex 8529 10 70 | 10 | Ceramic filter package comprising 2 ceramic filters and 1 ceramic resonator for a frequency of 10,7 MHz (± 30 kHz), contained in a housing | 0 |
| ex 8529 10 70 | 15 | Ceramic filter for a centre frequency of 10,7 MHz, with a bandwidth not exceeding 330 kHz at 3 dB and not exceeding 950 kHz at 20 dB, contained in a housing | 0 |
| ex 8529 10 70 | 20 | Ceramic filters for frequencies of 4,5 MHz or more but not exceeding 6,6 MHz contained in a housing | 0 |
| ex 8529 10 70 | 25 | Ceramic filter for a centre frequency of 450 kHz or more but not exceeding 470 kHz, with a bandwidth not exceeding 13 kHz at 3 dB, contained in a housing | 0 |
| ex 8529 10 70 | 30 | Ceramic filter for a frequency of 450 kHz, with a bandwidth not exceeding 18 kHz at 10 dB, contained in a housing | 0 |
| ex 8529 10 70 | 35 | Ceramic filter for a centre frequency of 455 kHz (± 1,5 kHz), with a bandwidth not exceeding 25 kHz at 6 dB and not exceeding 60 kHz at 40 dB, contained in a housing | 0 |
| ex 8529 10 70 | 45 | Ceramic filter for a centre frequency of 450 kHz (± 1,5 kHz) or 455 kHz (± 1,5 kHz), with a bandwidth not exceeding 30 kHz at 6 dB and not exceeding 70 kHz at 40 dB, contained in a housing | 0 |
| ex 8529 10 70 | 50 | Radio frequency (RF) signal isolator for frequencies of 890 MHz or more but not exceeding 1 990 MHz, having an insertion loss not exceeding 0,7 dB, contained in a housing | 0 |
| ex 8529 10 70 | 55 | Filters, excluding surface acoustic wave filters, for a center frequency of 485 MHz or more but not exceeding 1 990 MHz with an insertion loss not exceeding 3,5 dB, contained in a housing | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 8529 10 70 | 80 | Ceramic filter package, excluding surface acoustic wave filters, consisting of:<br>— a transmit filter with a centre frequency of 1 747,5 MHz and an insertion loss not exceeding 2,3 dB at a bandwidth of 75 MHz<br>and<br>— a receive filter with a centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,3 dB at a bandwidth of 75 MHz,<br>the whole contained in a housing | 0 |
| ex 8529 10 70 | 85 | Ceramic filter package, excluding surface acoustic wave filters, comprising 2 filters with one of the following combinations of characteristics:<br>— a transmit centre frequency of 902,5 MHz, a receive centre frequency of 947,5 MHz and an insertion loss not exceeding 3,2 dB at a bandwidth of 25 MHz<br>or<br>— a transmit centre frequency of 1 747,5 MHz, a receive centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,5 dB at a bandwidth of 75 MHz,<br>the whole contained in a housing | 0 |
| ex 8529 10 90 | 20 | Antenna switch, comprising:<br>— a transmit filter with a centre frequency of 942,5 MHz or more but not exceeding 1 990 MHz<br>and<br>a receive filter with a centre frequency of 847,5 MHz or more but not exceeding 1 990 MHz,<br>the whole contained in a housing | 0 |
| ex 8529 90 81 | 31 | Demagnetisation coil, with at least one of following characteristics:<br>— an internal diameter of less than 375 mm,<br>— an internal linear dimension measured on the surface profile of less than 1 178 mm,<br>with cables and connectors | 0 |
| ex 8529 90 81 | 32 | Optical unit for video projection, comprising a colour separation system, a positioning mechanism and lenses, for use in the manufacture of products falling within heading No 8528 [a] | 0 |
| ex 8529 90 81 | 34 | Assembly consisting of a lens unit, having an adjustable focal length of 4 mm or more but not exceeding 69 mm and comprising a zoom encoder, a stepping motor unit, a zoom motor unit, an iris motor unit and a photo interrupter | 0 |
| ex 8529 90 81 | 35 | Video-recording and reproducing assembly, comprising a tape deck mechanism of the cassette type, comprising a DC motor, for use in the manufacture of products falling within heading No 8525 [a] | 0 |
| ex 8529 90 81 | 36 | Assembly consisting of a monochrome cathode-ray tube with a diagonal measurement of the screen of 165 mm or more but not exceeding 230 mm and a concave focus lens mounted on a liquid-filled cooling armature, for use in the manufacture of television projection equipment [a] | 0 |
| ex 8529 90 81<br>ex 8529 90 88 | 37<br>33 | Filter, consisting of 2 piezo-electric crystals each with a frequency of 21 MHz or more but not exceeding 30 MHz and seperately mounted on a bracket, with not more than 7 connections | 0 |
| ex 8531 80 80 | 01 | Indicator lamp, consisting of 4 light-emitting diodes made from silicon-cardide (SiC) semiconductor material, operating at a nominal wavelength of 481, 560 or 630 nm, contained in a housing | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 8531 80 80 | 15 | Indicator lamp, consisting of 2 light-emitting diodes made from aluminium-gallium-arsenic (AlGaAs) or gallium-phosphor (GaP) semiconductor material, having a rectangular base, contained in a housing of the SMD (surface mounted device) type and having a lens | 0 |
| ex 8531 80 80 | 25 | Electro-accoustic transducer | 0 |
| ex 8531 80 80 | 30 | An electromagnetic display, consisting of 7 electromagnetic coils which by means of the residual magnetism in the stators provide that the last indication remains available (set state), and 7 pivoting light-reflecting segments each of which is attached to a bar magnet; assembly comprising such displays | 0 |
| ex 8536 30 30<br>ex 8536 30 90<br>ex 8536 50 80 | 11<br>31<br>96 | Thermoelectric switch with a cut-off current of 50 A or more, comprising a snap action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing | 0 |
| ex 8536 41 10<br>ex 8536 41 90<br>ex 8536 49 00 | 91<br>91<br>91 | Thermal relays contained in a hermetically sealed glass cartridge not exceeding 35 mm in length excluding wires, with a maximum leakage rate of $10^{-6}$ $cm^3$ He/sec at one bar in the temperature range 0 to 160 ºC, to be incorporated into compressors for refrigerating equipment (a) | 0 |
| ex 8536 50 11 | 31 | Switch of the printed circuit mount type, operating at a force of 4,9 N (± 0,9 N), contained in a housing | 0 |
| ex 8536 50 19 | 91 | Hall effect switch, comprising 1 magnet, 1 Hall effect sensor and 2 capacitors, contained in a housing with 3 connections and bearing:<br>— an identification marking consisting of or including (one of) the following combination(s):<br>2AV28E<br>2AV31E<br>2AV56<br>or<br>— other identification markings relating to devices complying with the abovementioned description | 0 |
| ex 8536 50 19 | 92 | Hydraulic pressure switch, incorporating a pressure sensitive snap action disc, operating at a supply voltage of 6 V or more but not exceeding 18 V | 0 |
| ex 8536 50 80 | 93 | Switch unit for coaxial cable, comprising 3 electromagnetic switches, with a switching time not exceeding 50 ms and an actuating current not exceeding 500 mA at a voltage of 12 V | 0 |
| ex 8536 50 80 | 95 | Reed switch having a switching power of 20 W or more within the range of 17 43 A.turns, in the form of a glass capsule, not containing mercury, the dimensions of which do not exceed 3 × 21 mm, for use in the manufacture of automotive airbag shock-sensors (a) | 0 |
| ex 8536 90 85 | 92 | Metallic stamped frame with connections | 0 |
| ex 8536 90 85 | 93 | Contact element with a hold-force of more than 3 N, in the form of 2 rectangular plastic frames interconnected by electric conductors | 0 |
| ex 8536 90 85<br>ex 8544 49 80 | 94<br>10 | Elastomeric connector, consisting of one or more conductor elements and of a rubber or silicon substrate | 0 |
| ex 8537 10 99 | 92 | Touch sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors | 0 |
| ex 8538 90 99 | 92 | Part of an electrothermal fuse, consisting of a tin coated copper wire attached to a cylindrical casing, the exterior dimensions of which do not exceed 5 × 48 mm | 0 |
| ex 8540 11 11 | 91 | Colour cathode-ray tube with a slit or slot mask, equipped with electron guns placed side by side (in-line technology) and with a diagonal measurement of the screen of 12 cm or more but not exceeding 26 cm | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 8540 11 11 | 93 | Colour cathode-ray tube, equipped with 1 gun with 3 rays and with a diagonal measurement of the screen of 22 cm or more but not exceeding 26 cm | 0 |
| ex 8540 11 13 | 91 | Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,42 mm and a diagonal measurement of the screen of 49 cm, for use in the manufacture of professional video monitors including security and medical monitor applications ([a]) | 0 |
| ex 8540 11 19 | 91 | Colour cathode-ray tube equipped with electron guns placed side by side (in-line technology), with a diagonal measurement of the screen of 85 cm or more | 0 |
| ex 8540 11 91 | 31 | Colour cathode-ray tube with a screen width/height ratio of 16/9 and a diagonal measurement of the screen of 39,8 cm (± 0,3 cm) | 0 |
| ex 8540 11 99 | 31 | Colour cathode-ray tube with a diagonal measurement of the screen of 85,5 cm or more | 0 |
| ex 8540 12 00 | 82 | Monochrome cathode-ray tube with a diagonal measurement of the screen of 250 mm or more but not exceeding 320 mm and an anode voltage of 18 kV or more but not exceeding 22 kV | 0 |
| ex 8540 12 00 | 83 | Monochrome cathode-ray tube, with a diagonal measurement of the screen of 150 mm or more but not exceeding 182 mm, a neck diameter of less than 30 mm and an anode voltage of 25 kV or more but not exceeding 32 kV | 0 |
| ex 8540 12 00 | 84 | Flat screen monochrome cathode-ray tube, with a diagonal measurement of the screen not exceeding 102 mm | 0 |
| ex 8540 20 80 | 91 | Photomultiplier consisting of a photo-cathode tube with 9 dynodes, for light of a wavelength of 160 nm or more but not exceeding 930 nm, of a diameter not exceeding 14 mm and a height not exceeding 94 mm | 0 |
| ex 8540 40 00<br>ex 8540 60 00 | 31<br>31 | Colour cathode-ray tube with a dot mask, equipped with 3 electron guns placed side by side (in-line technology) or 1 gun with 3 rays, with a diagonal measurement of the screen of more than 72 cm and a distance of less than 0,5 mm between dots of the same colour | 0 |
| ex 8540 40 00<br>ex 8540 60 00 | 32<br>32 | Colour cathode-ray tube with a dot mask, equipped with 3 electron guns placed side by side (in-line technology) or 1 gun with 3 rays, having a diagonal measurement of the screen not exceeding 72 cm | 0 |
| ex 8540 40 00 | 33 | Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 53 cm | 0 |
| ex 8540 40 00 | 34 | Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,39 mm and a diagonal measurement of the screen of 33 cm or more but not exceeding 38 cm | 0 |
| ex 8540 40 00 | 35 | Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 72 cm, for use in the manufacture of monitors ([a]) | 0 |
| ex 8540 40 00 | 36 | Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,30 mm and a diagonal measurement of the screen not exceeding 58 cm | 0 |
| ex 8540 50 00<br>ex 8540 60 00 | 31<br>33 | Flat screen monochrome cathode-ray tube, with a diagonal measurement of the screen of 142 mm or more but not exceeding 190 mm, a luminescence of 300 lumen or more but not exceeding 2 000 lumen, a resolution of 0,06 mm or more but not exceeding 0,1 mm, phosphor types P1 or P22 or P53 or P55 or P56, an anode voltage of more than 34 kV, a focus voltage of more than 7 kV and a cathode current of 3 mA or more | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 8540 50 00<br>ex 8540 60 00 | 32<br>34 | Monochrome cathode-ray tube with a diagonal measurement of the screen of 176 mm or more but not exceeding 520 mm and a neck diameter not exceeding 21 mm | 0 |
| ex 8540 89 00 | 91 | Displays in the form of a tube consisting of a glass housing mounted on a board, the dimensions of which do not exceed 300 × 350 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons | 0 |
| ex 8540 89 00 | 92 | Vacuum fluorescent display tube | 0 |
| ex 8540 91 00 | 31 | Electron gun, for use in the manufacture of colour cathode-ray tubes of subheading 8540 40 00 with a diagonal measurement of the screen of 34 cm or more but not exceeding 39 cm (a) | 0 |
| ex 8540 91 00 | 32 | Electron gun of colour cathode-ray tubes with an anode voltage of 27,5 kV or more but not exceeding 33 kV | 0 |
| ex 8540 91 00 | 91 | Deflector yoke for cathode-ray tubes with an operating frequency of 31 250 Hz or more but not exceeding 64 000 Hz, incorporating a quadripolar magnet | 0 |
| ex 8540 91 00 | 92 | Slit or slot mask, excluding masks with continuously vertical slits, with a diagonal measurement of 39 cm or less | 0 |
| ex 8540 91 00 | 93 | Electron gun for the production of monochrome cathode-ray tubes with a diagonal measurement of the screen of 7,6 cm or more but not exceeding 30,5 cm (a) | 0 |
| ex 8540 91 00 | 94 | Deflector yoke for colour cathode-ray tubes, with an operating frequency of 15 625 or 31 250 Hz, comprising 2 two-pole ring magnets, 2 four-pole ring magnets and 2 six-pole ring magnets | 0 |
| ex 8540 91 00 | 96 | Assembly for cathode-ray tubes with 2 or more but not more than 6 coils, a plastic support and a metal fixing ring, for the adjustment of display sharpness and/or convergence | 0 |
| ex 8540 91 00 | 97 | Slit mask, consisting of continuously vertical slits measuring more than 275 mm in the length | 0 |
| ex 8540 91 00 | 98 | Frame of molybdenum chrome steel, for use in the manufacture of cathode-ray tubes (a) | 0 |
| ex 8540 99 00 | 91 | Anode, cathode or output part, or an assembly comprising these components (magnetron core tube), for the manufacture of magnetrons of subheading 8540 71 00 (a) | 0 |
| ex 8543 19 00 | 10 | Electron beam accelerator systems, with an operating voltage or more not exceeding 1,5 MV and a beam current not exceeding 70 mA | 0 |
| ex 8543 89 95 | 46 | Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing bearing:<br>— an identification marking consisting of or including (one of) the following combination(s):<br>FA 01314<br>MHW 2707<br>MHW 9002<br>PF 0144<br>PHW 902<br>FA 01317<br>MHW 607<br>MHW 910<br>PF 0146<br>PHW 925<br>FA 01321<br>MHW 704<br>MHW 914<br>PF 0148<br>SHW 5115 | |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| | | FMC 1717<br>MHW 707<br>MHW 915<br>PF 0412<br>XHW 105<br>FMC 1819<br>MHW 720<br>MHW 916<br>PHW 2905<br>XHW 2803<br>ISO 122<br>MHW 803<br>MHW 926<br>PHW 2907<br>XHW 2902<br>MHW 105<br>MHW 820-1<br>MHW 927<br>PHW 5113<br>XHW 5115<br>MHW 1815<br>MHW 820-2<br>MHW 953<br>PHW 9012<br>XHW 903<br>MHW 2701<br>or<br>— other identification markings relating to devices complying with the abovementioned description | 0 |
| ex 8543 89 95 | 48 | Radio frequency (RF) modulator, operating with a frequency range of 43 MHz or more but not exceeding 870 MHz, capable of switching VHF and UHF signals, consisting of active and passive elements mounted on a printed circuit, contained in a housing | 0 |
| ex 8543 89 95 | 49 | Rectifier assembly of power barrier diodes, consisting of 2 diodes with an average forward current not exceeding 600 A and a repetitive reverse peak voltage not exceeding 40 V, each contained in a housing and connected by a common cathode | 0 |
| ex 8543 89 95 | 50 | Piezo-electric crystal clock oscillator with a fixed frequency, within a frequency range of 1,8 MHz to 67 MHz, contained in a housing bearing:<br>— an identification marking consisting of or including (one of) the following combination(s):<br>R4000.8<br>R4000.9<br>or<br>— other identification markings relating to devices complying with the abovementioned description | 0 |
| ex 8543 89 95 | 51 | Mechanical vibratory gyroscope driven by a 25 or 26 kHz oscillator, comprising a differential amplifier and a detector circuit, contained in a housing bearing:<br>— an identification marking consisting of or including (one of) the following combination(s):<br>ENC05D<br>or<br>— other identification markings relating to devices complying with the abovementioned description | 0 |
| ex 8543 89 95 | 52 | Opto-electronic circuit comprising one or more light-emitting diodes (LEDs) and one photodiode with amplifier circuit and an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, contained in a plastic housing bearing:<br>— an identification marking consisting of or including (one of) the following combination(s):<br>HC PL 2400 | |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| | | HC PL 2730<br>or<br>— other identification markings relating to devices complying with the abovementioned description | 0 |
| ex 8543 89 95 | 53 | Oscillator, with a centre frequency of 20 GHz or more but not exceeding 42 GHz, consisting of active and passive elements not mounted on a substrate, contained in a housing bearing:<br>— an identification marking consisting of or including (one of) the following combination(s):<br>372-02<br>372-03<br>or<br>— other identification markings relating to devices complying with the abovementioned description | 0 |
| ex 8543 89 95 | 55 | Audio-recording and reproducing circuit, capable of stereo audio data storage and simultaneous record and playback, comprising 2 or 3 monolithic integrated circuits mounted on a printed circuit or a lead frame, contained in a housing bearing:<br>— an identification marking consisting of or including (one of) the following combination(s):<br>RWA010<br>RWA100<br>RWA200<br>RWA300<br>or<br>— other identification markings relating to devices complying with the abovementioned description | 0 |
| ex 8543 89 95 | 56 | Overvoltage suppression assembly, comprising 8 diodes, having a reverse stand-off voltage not exceeding 4,5 V, a reverse leakage current not exceeding 10 µA, a peak pulse current not exceeding 30 A and a nominal capacity of 50 pF, contained in a housing | 0 |
| ex 8543 89 95 | 57 | Frequency converter, not comprising a dipole aerial, for the conversion of frequencies of 10,7 GHz or more but not exceeding 12,75 GHz to frequencies of 950 MHz or more but not exceeding 3 GHz and operating at a supply voltage of 11 V or more but not exceeding 20 V | 0 |
| ex 8543 89 95 | 59 | Charged coupled device (CCD) scanner assembly, for a real-time film scanning system, having optical functions, illumination functions and signal processing functions | 0 |
| ex 8543 90 80 | 40 | Stainless steel cathode in the form of a plate with a hanger bar and plastic side strips | 0 |
| ex 8543 90 80 | 50 | Assembly of products falling within heading No 8541 or 8542 mounted on a printed circuit, contained in a housing | 0 |
| ex 8545 90 90 | 01 | Cell and battery carbon, in the form of rods, with a length of 34 mm or more but not exceeding 160 mm and a diameter not exceeding 12 mm | 0 |
| ex 8548 90 90 | 38 | Parts, for use in the manufacture or the repair of products falling within subheading 8517 21 00 [a] | 0 |
| ex 8548 90 90 | 39 | Optical unit, consisting of a laserdiode and a photodiode, operating at a typical wavelength of 635 or 670 nm | 0 |
| ex 8548 90 90 | 40 | Infrared signal receiver unit, consisting of a photodiode and at least an amplifier in the form of a monolithic integrated circuit, contained in a housing bearing:<br>— an identification marking consisting of or including (one of) the following combination(s):<br>GP1U58XB<br>SBX 1610<br>or<br>— other identification markings relating to devices | |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| | | complying with the abovementioned description | 0 |
| ex 8548 90 90 | 41 | Unit, consisting of a resonator operating within a frequency range of 1,8 MHz or more but not exceeding 40 MHz and a capacitor, contained in a housing | 0 |
| ex 8548 90 90<br>ex 9110 90 00 | 42<br>94 | Clock/calendar circuit, consisting of a printed circuit on which are mounted at least a quartz oscillator and a monolithic integrated circuit, the whole contained in a housing bearing:<br>— an identification marking consisting of or including (one of) the following combination(s):<br>DS 1287<br>DS 1387<br>MK 48T08<br>MK 48T18<br>RTC 65271<br>DS 12887A<br>MK 48T02<br>MK 48T12<br>RTC 63421<br>RTC 72423<br>or<br>— other identification markings relating to devices complying with the abovementioned description | 0 |
| ex 8548 90 90 | 43 | Contact image sensor | 0 |
| ex 9001 10 90 | 10 | Image reverser made up from an assembly of optical fibres | 0 |
| ex 9001 20 00 | 10 | Material consisting of a polarising film, supported on one or both sides by transparent material | 0 |
| ex 9001 90 90 | 20 | Rear projection screen, comprising a Fresnel lens of plastic and a polarising sheet of plastic, for use in the manufacture of products falling within heading No 8528 (a) | 0 |
| ex 9001 90 90 | 30 | Lens of plastic, unmounted, having a focal length of 3,86 mm (± 0,1 mm) and with a diameter not exceeding 8 mm, for use in the manufacture of compact-disc players (a) | 0 |
| ex 9001 90 90 | 40 | Optical fibre plate, for use in the manufacture of screens and photocathodes for image intensifiers (a) | 0 |
| ex 9001 90 90 | 50 | Rear projection screen, comprising a lenticular plastic plate | 0 |
| ex 9001 90 90 | 60 | Prism for the splitting of light, unmounted, for use in the manufacture of charged-coupled image (CCD) cameras (a) | 0 |
| ex 9001 90 90 | 70 | Rod of neodymium-doped yttrium-aluminium garnet (YAG) material, polished at both ends | 0 |
| ex 9001 90 90 | 80 | Lens of plastic, unmounted, for use in the manufacture of products falling within subheading 9006 40 00 (a) | 0 |
| ex 9002 11 00 | 10 | Adjustable lens unit, having a focal length of 90 mm or more but not exceeding 180 mm and comprising a combination of between 4 and 8 glass or methacrylic lenses with a diameter of 120 mm or more but not exceeding 180 mm, each lens coated on at least one side with a magnesium fluoride layer, for use in the manufacture of video projectors (a) | 0 |
| ex 9002 11 00 | 50 | Lens unit, having a focal length of 75 mm or more but not exceeding 94 mm, consisting of glass or plastic lenses, with a diameter of 60 mm or more but not exceeding 180 mm | 0 |
| ex 9002 11 00 | 60 | Optical element, comprising one or more mounted lenses of plastic, for use in the manufacture of products falling within subheading 9006 40 00 (a) | 0 |
| ex 9002 19 00 | 10 | Lens unit, having a focal length of 24,96 mm (± 0,1 mm), a diameter of 16 mm and a length of 16 mm, for use in the manufacture of products falling within subheading 8517 21 00 (a) | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 9002 20 00 | 10 | Filter, consisting of a plastic polarising membrane, a glass plate and a transparent protective film, mounted on a metal frame, for use in the manufacture of products falling within heading 8528 (a) | 0 |
| ex 9002 90 90 | 10 | Optical element comprising an octagonal Fresnel lens, for use in the manufacture of overhead projectors (a) | 0 |
| ex 9002 90 90 | 20 | Lens, mounted, having a fixed focal length of 3,8 mm (± 0,19 mm) or 8 mm (± 0,4 mm), with a relative aperture of F2.0 and a diameter not exceeding 33 mm, for use in the manufacture of charged-coupled (CCD) cameras (a) | 0 |
| ex 9002 90 90 | 30 | Optical unit, comprising 1 or 2 rows of optical glass fibres in the form of lenses and with a diameter of 0,85 mm or more but not exceeding 1,15 mm, embedded between 2 plastic plates | 0 |
| ex 9002 90 90 | 50 | Lens and image gate assembly, for a real-time film scanning system, comprising a lens consisting of 9 or 11 elements and having an illumination function | 0 |
| ex 9006 91 90 | 10 | Parts, for use in the manufacture of products falling within subheading 9006 40 00 (a) | 0 |
| ex 9013 80 90 | 10 | Polarisation insensitive fibre-optic isolator, operating at a wavelength of 1 200 nm or more, contained in a cylindrical housing | 0 |
| ex 9017 90 90 | 20 | Thermal printer head, comprising at least 7 168 heater elements mounted on 2 or more ceramic supports, the whole contained in a housing the exterior dimensions of which exceed 21 × 39 × 639 mm | 0 |
| ex 9022 30 00 | 10 | X-ray tube with a target voltage of 4 kV or more but not exceeding 30 kV, a power not exceeding 9 W and a target current not exceeding 2 mA | 0 |
| ex 9031 80 34<br>ex 9031 80 39<br>ex 9031 80 99 | 10<br>30<br>10 | Machines and apparatus providing automated quality inspection of rigid magnetic disks, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a) | 0 |
| ex 9031 80 39 | 10 | Acceleration measurement device for automotive applications, comprising one or more active and/or passive elements and a sensor, the whole contained in a housing | 0 |
| ex 9031 90 80 | 20 | Read and write test head for checking the quality of rigid magnetic disks, mounted on a carrier arm | 0 |
| ex 9031 90 80 | 30 | Assembly for a laser align sensor, in the form of a printed circuit comprising optical filters and a charge-coupled image (CCD) sensor, the whole contained in a housing | 0 |
| ex 9031 90 80 | 40 | Test head for checking the mechanical quality of rigid magnetic disks, mounted on a carrier arm | 0 |
| ex 9031 90 80 | 50 | Burnishing head, for removing asperities on and polishing of the surface of rigid magnetic disks, mounted on a carrier arm | 0 |
| ex 9032 10 91 | 10 | Thermostat, comprising a snap-action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing | 0 |
| ex 9032 89 90 | 10 | Automotive airbag shock-sensor, comprising a contact capable of switching a current of 12 A at a voltage of 30 V, having a typical contact resistance of 80 mOhm | 0 |
| ex 9110 12 00 | 91 | Assembly consisting of a printed circuit on which are mounted one quartz oscillator, at least one watch circuit and, whether or not integrated, at least one capacitor, of a thickness not exceeding 5 mm | 0 |

▼M7

| CN code | TARIC | Description of goods | Rate of autonomous duty (%) |
|---|---|---|---|
| ex 9110 90 00<br>ex 9114 90 00 | 92<br>91 | Assembly consisting of a printed circuit on which is mounted a watch circuit or a watch circuit and a quartz oscillator, of a thickness not exceeding 5 mm | 0 |
| ex 9110 90 00 | 93 | Assembly consisting of a printed circuit on which is mounted at least one watch circuit, a quartz oscillator and a piezo-electric sound element, with a thickness exceeding 5 mm | 0 |
| ex 9608 91 00 | 10 | Non-fibrous plastic pen-tips with an internal channel | 0 |
| ex 9608 91 00 | 20 | Felt tips and other porous-tips for markers, without internal canal | 0 |
| ex 9612 10 10 | 10 | Ribbons of plastic with segments of different colours, providing the penetration of dyes by heat into a support (so called dye-sublimation) | 0 |
| ex 9613 90 00 | 20 | Piezo-electric ignition mechanism | 0 |

([a]) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.
([b]) However, the suspension is not allowed where processing is carried out by retail or catering undertakings.