This document is meant purely as a documentation tool and the institutions do not assume any liability for its contents

►**B**

COUNCIL REGULATION (EC) No 1255/96

of 27 June 1996

temporarily suspending the autonomous Common Customs Tariff duties on certain ►**M9** industrial, agricultural and fishery products ◄

(OJ L 158, 29.6.1996, p. 1)

Amended by:

		Official Journal		
		No	page	date
►**M1**	Council Regulation (EC) No 2484/96 of 20 December 1996	L 341	1	30.12.1996
►**M2**	Council Regulation (EC) No 1186/97 of 27 June 1997	L 172	1	30.6.1997
►**M3**	Council Regulation (EC) No 2590/97 of 16 December 1997	L 355	1	30.12.1997
►**M4**	Council Regulation (EC) No 1359/98 of 29 June 1998	L 186	1	30.6.1998
►**M5**	Council Regulation (EC) No 2797/98 of 17 December 1998	L 352	1	29.12.1998
►**M6**	Council Regulation (EC) No 1381/1999 of 28 June 1999	L 165	1	30.6.1999
►**M7**	Council Regulation (EC) No 20/2000 of 17 December 1999	L 8	1	12.1.2000
►**M8**	Council Regulation (EC) No 1297/2000 of 19 June 2000	L 153	1	26.6.2000
►**M9**	Council Regulation (EC) No 2801/2000 of 14 December 2000	L 331	1	27.12.2000
►**M10**	Council Regulation (EC) No 1159/2001 of 11 June 2001	L 169	1	23.6.2001
►**M11**	Council Regulation (EC) No 2499/2001 of 19 December 2001	L 340	1	21.12.2001
►**M12**	Council Regulation (EC) No 1120/2002 of 26 June 2002	L 171	1	29.6.2002

Corrected by:

►**C1** Corrigendum, OJ L 107, 7.4.1998, p. 16 (2590/97)

►**C2** Corrigendum, OJ L 125, 19.5.1999, p. 40 (2797/98)

▼B

COUNCIL REGULATION (EC) No 1255/96

of 27 June 1996

temporarily suspending the autonomous Common Customs Tariff duties on certain ►M9 industrial, agricultural and fishery products ◄

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 28 thereof,

Having regard to the proposal from the Commission,

Whereas production in the Community of the products specified in this Regulation is currently inadequate or non-existent; whereas producers thus cannot meet the needs of user industries in the Community;

Whereas it is in the interest of the Community to suspend partially or totally the autonomous Common Customs Tariff duties for these products;

Whereas the decision to suspend such autonomous duties should be taken by the Community;

Whereas the Regulations temporarily suspending the autonomous Common Customs Tariff duties on certain ►M9 industrial, agricultural and fishery products ◄ have largely renewed previous measures; whereas, therefore, in the interests of rationalizing implementation of the measures concerned, it would seem appropriate not to limit the period of validity of this Regulation as its scope can be adapted and products added to or removed from the list through a Council Regulation, if necessary;

Whereas the amendments to the combined nomenclature and the Taric codes do not give rise to any substantive amendment; whereas, for reasons of simplification, provision should be made to empower the Commission, following receipt of the opinion of the Customs Code Committee, to make the necessary amendments and technical adaptations of the Annex to this Regulation, including the publication of a consolidated version,

HAS ADOPTED THIS REGULATION:

Article 1

The autonomous Common Customs Tariff duties for the products listed in the Annex hereto shall be suspended at the level indicated against each of them.

Article 2

The technical adaptations, including publication of a consolidated version, arising from amendments of the combined nomenclature and Taric codes shall be adopted by the Commission in accordance with the procedure laid down in Article 3.

Article 3

1. The Commission shall be assisted by the Customs Code Committee set up by Article 247 of Regulation (EEC) No 2913/92 [1].

2. The representative of the Commission shall submit to the Committee a draft of the measures to be taken. The Committee shall deliver its opinion on the draft within a time limit which the chairman may lay down according to the urgency of the matter. The opinion shall be delivered by the majority laid down in Article 148 (2) of the

[1] OJ No L 302, 19. 10. 1992, p. 1. Regulation as amended by the 1994 Act of Accession.

▼B

Treaty in the case of decisions which the Council is required to adopt on a proposal from the Commission. The votes of the representatives of the Member States within the Committee shall be weighted in the manner set out in that Article. The chairman shall not vote.

3. The Commission shall adopt measures which apply immediately.

However, if these measures are not in accordance with the opinion of the Committee, they shall be communicated by the Commission to the Council forthwith. In that event, the Commission shall defer application of the measures which it has decided for three months from the date of such communication.

The Council, acting by a qualified majority, may take a different decision within the period referred to in the previous indent.

Article 4

This Regulation shall enter into force on the day following its publication in the *Official Journal of the European Communities*.

It shall apply from 1 July 1996.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

▼M11

ANNEX

	CN code	TARIC	Description	Rate of autonomous duty (%)
▼M12				
	ex 0302 69 99	10	Sturgeons, fresh, chilled or frozen, for processing (a) (b)	
	ex 0303 79 98	10		0
	ex 0302 69 99	20	Lump fish (*Cyclopterus lumpus*) with roe, fresh or chilled, for processing (a)	0
	ex 0302 69 99	30	Red snapper (*Lutjanus purpureus*), fresh, chilled or	
	ex 0303 79 98	20	frozen, for processing (a) (c)	0
	ex 0302 70 00	11	Hard fish roes, fresh, chilled or frozen	
	ex 0302 70 00	31		
	ex 0302 70 00	41		
	ex 0302 70 00	91		
	ex 0303 80 90	10		
	ex 0303 80 90	19		0
	ex 0303 11 00	10	Pacific salmon (*Oncorhynchus spp.*), frozen and headless,	
	ex 0303 19 00	10	for the processing industry for manufacture into pastes or spreads (a)	0
	ex 0304 10 38	45	Fillets and meat of dogfish (*Squalus acanthias*), fresh,	
	ex 0304 10 98	60	chilled or frozen	
	ex 0304 20 61	10		
	ex 0304 90 97	31		6
	ex 0305 20 00	11	Hard fish roes, salted or in brine	
	ex 0305 20 00	18		
	ex 0305 20 00	19		
	ex 0305 20 00	21		
	ex 0305 20 00	30		0
	ex 0306 19 90	10	Krill for processing (a)	
	ex 0306 29 90	10		0
▼M11				
	ex 0603 90 00	10	Flowers, flower buds, foliage, leaves and other parts of	
	ex 0604 99 90	10	plants, not further prepared than dried, dyed or bleached, for use in the manufacture of pot-pourri of subheading 3307 49 00 (a)	0
	ex 0710 21 00	10	Peas in pods, of the species *Pisum sativum* of the variety *Hortense axiphium*, frozen, of a thickness not exceeding 6 mm, to be used, in their pods, in the manufacture of prepared meals (a) (c)	0
	ex 0711 59 00	11	Mushrooms, excluding mushrooms of the genus *Agaricus*,	
	ex 0711 59 00	91	provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry (a)	0
	ex 0712 32 00	11	Mushrooms, excluding mushrooms of the genus *Agaricus*,	
	ex 0712 32 00	21	dried, whole or in identifiable slices or pieces, for treat-	
	ex 0712 33 00	11	ment other than simple repacking for retail sale (a) (c)	
	ex 0712 33 00	21		
	ex 0712 39 00	11		
	ex 0712 39 00	21		0
	ex 0804 10 00	11	Dates, fresh or dried, not put up for retail sale	
	ex 0804 10 00	21		0
	ex 0810 40 50	10	Fruit of the species *Vaccinium macrocarpon*, fresh	0
	ex 0810 90 95	10	Rose-hips, fresh	0
	0811 90 50	66	Fruit of the genus *Vaccinium*, uncooked or cooked by	
	0811 90 70	67	steaming or boiling in water, frozen, not containing added	
	ex 0811 90 95		sugar or other sweetening matter	
	ex 0811 90 95			0
▼M12				
	ex 0811 90 95	20	Boysenberries, frozen, not containing added sugar, not put up for retail sale	0
	ex 0811 90 95	30	Pineapple (*Ananas comosus*), in pieces, frozen	0

▼M12

	CN code	TARIC	Description	Rate of autonomous duty (%)
▼M11				
	ex 0811 90 95	40	Rose-hips, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter	0
▼M12				
	ex 1511 90 19 ex 1511 90 91 ex 1513 11 10 ex 1513 19 30 ex 1513 21 11 ex 1513 29 30	10 10 10 10 10 10	Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of: — industrial monocarboxylic fatty acids of subheading 3823 19 10, — mixtures of methyl esters of fatty acids of subheading 3824 90 99, — methyl esters of fatty acids of heading 2915 or 2916, — stearic acid of subheading 3823 11 00 or — goods of heading No 3401 (a)	0
▼M11				
	ex 1518 00 91	10	Soya bean oil, modified with maleic acid, for the manufacture of cosmetic products (a)	0
▼M12				
	ex 1604 11 00 ex 1604 20 10	20 20	Pacific salmon (*Oncorhynchus spp.*), for the processing industry for manufacture into pastes or spreads (a)	0
	ex 1604 30 90	10	Hard fish roes, washed, cleaned of adherent organs and simply salted or in brine, for processing (a)	0
	ex 1605 10 00 ex 1605 10 00	11 19	Crabs of the species 'King' (*Paralithodes camchaticus*), 'Hanasaki' (*Paralithodes brevipes*), 'Kegani' (*Erimacrus isenbecki*), 'Queen' and 'Snow' (*Chionoecetes spp.*), 'Red' (*Geryon quinquedens*), 'Rough stone' (*Neolithodes asperrimus*), *Lithodes antarctica*, 'Mud' (*Scylla serrata*), 'Blue' (*Portunus spp.*), simply boiled in water and shelled, whether or not frozen, in immediate packings of a net content of 2 kg or more	0
	ex 1605 10 00 ex 1605 10 00	92 94	Crabs of the species *Paralomis granulosa*	0
	ex 1902 30 10	10	Transparent noodles, cut in pieces, obtained from beans (*Vigna radiata* (L.) Wilczek), not put up for retail sale	0 0 EUR 100 kg/net
	ex 2005 90 80	70	Bamboo shoots, prepared or preserved, not put up for retail sale	0
▼M11				
	ex 2707 99 11	10	Crude light oils containing by weight: — 10 % or more of vinyltoluenes, — 10 % or more of indene, and — 1 % or more but not more than 5 % of naphthalene	0
	ex 2805 30 10	10	Alloy of cerium and other rare-earth metals, containing by weight 47 % or more of cerium	0
	ex 2805 30 10	20	Alloy of lanthanum and other rare-earth metals, containing by weight 43 % or more of lanthanum	0
	ex 2805 30 90	10	Lanthanum of a purity by weight of 99 % or more	0
	ex 2811 19 80	10	Sulphamidic acid	0
	ex 2811 22 00	10	Silicon dioxide in the form of powder, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (a)	0
	ex 2811 29 90	10	Tellurium dioxide	0
	ex 2812 90 00	10	Nitrogen trifluoride	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2818 30 00	10	Aluminium hydroxide oxide in the form of pseudo-boehmite	4
ex 2819 90 90	10	Dichromium trioxide: — of a specific surface of 37 m^2/g or more (as determined by the BET method), — of a purity by weight of 99,5 % or more calculated on the dry substance, — of a specific gravity of 1,2 g/cm^3 or less, for the manufacture of magnetic chromium dioxide (a)	0
ex 2820 90 90	10	Manganese (II,III) oxide containing by weight 70 % or more of manganese	0
ex 2821 10 00	10	Diiron trioxide, in the form of powder, of a purity by weight of 99,2 % or more, for the manufacture of goods of heading No 8504 (a)	0
ex 2823 00 00	10	Titanium dioxide, of a purity by weight of 99,9 % or more, with an average grain size of 1,2 μm or more but not exceeding 1,8 μm, for the manufacture of goods of heading No 8532 or 8533 (a)	0
ex 2825 50 00	10	Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride	0
ex 2826 90 90	10	Potassium hexafluorophosphate	0
ex 2827 39 80	10	Copper monochloride of a purity by weight of 96 % or more but not exceeding 99 %	0
ex 2827 60 00	10	Titanium tetraiodide	0
ex 2830 10 00	10	Disodium tetrasulphide, containing by weight 38 % or less of sodium calculated on the dry weight	0
ex 2830 20 00	10	Zinc sulphide containing: — 20,0 mg/kg or less of chloride, — 0,2 mg/kg or less of copper, — 0,5 mg/kg or less of iron, and — 1,0 mg/kg or less of lead	0
ex 2836 91 00	20	Lithium carbonate, containing one or more of the following impurities at the concentrations indicated: (determined according to the methods specified in the European Pharmacopœia) — 2 mg/kg or more of arsenic, — 200 mg/kg or more of calcium, — 200 mg/kg or more of chlorides, — 20 mg/kg or more of iron, — 150 mg/kg or more of magnesium, — 20 mg/kg or more of heavy metals, — 300 mg/kg or more of potassium, — 300 mg/kg or more of sodium, — 200 mg/kg or more of sulphates, determined according to the methods specified in the European Pharmacopœia	0
ex 2837 19 00	10	Zinc cyanide	0
ex 2837 19 00	20	Copper cyanide	0
ex 2839 90 00	10	Lead silicate hydrate, of a lead content by weight of (84,5 ± 1,5) %, evaluated as lead monoxide, in the form of powder	0
ex 2843 90 90	20	Palladium monoxide	0
ex 2843 90 90	30	Mixture of palladium phthalocyanines	0
2845 10 00		Heavy water (deuterium oxide) (*Euratom*)	0
2845 90 10		Deuterium and compounds thereof; hydrogen and compounds thereof, enriched in deuterium; mixtures and	

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
		solutions containing these products (*Euratom*)	0
ex 2846 10 00 ex 3824 90 99	10 48	Rare-earth concentrate containing by weight 60 % or more but not more than 95 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight	0
ex 2848 00 00	10	Phosphine	0
ex 2850 00 20	10	Silane	0
▼M12			
ex 2850 00 20	20	Arsine	0
▼M11			
ex 2903 30 80	10	Carbon tetrafluoride (tetrafluoromethane)	0
ex 2903 30 80	20	1,1,1,2,3,3,3-Heptafluoropropane	0
ex 2903 30 80	30	Perfluoroethane	0
ex 2903 30 80	40	1,1-Difluoroethane	0
ex 2903 59 90	10	1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo[12.2.1.1^{6,9}.0^{2,13}.0^{5,10}]octadeca-7,15-diene, for use in the manufacture of polyamide, polyethylene, synthetic rubber or polystyrene ([a])	0
ex 2903 59 90	20	Hexachlorocyclopentadiene	0
ex 2903 69 90	10	Di- or tetrachlorotricyclo[8.2.2.2^{4,7}]hexadeca-1(12),4,6,10,13,15-hexaene, mixed isomers	0
ex 2903 69 90	20	1,2-Bis(pentabromophenyl)ethane	0
ex 2903 69 90	40	2,6-Dichlorotoluene, of a purity by weight of 99 % or more and containing: — 0,001 mg/kg or less of tetrachlorodibenzodioxines, — 0,001 mg/kg or less of tetrachlorodibenzofurans, — 0,2 mg/kg or less of tetrachlorobiphenyls	0
ex 2903 69 90	50	1-(Chloromethyl)naphthalene	0
ex 2903 69 90	60	*α*-Chloro(ethyl)toluenes	0
ex 2904 10 00	30	Sodium *p*-styrenesulphonate	0
ex 2904 20 00	10	Nitromethane	0
ex 2904 20 00	20	Nitroethane	0
ex 2904 20 00	30	1-Nitropropane	0
ex 2904 20 00	40	2-Nitropropane	0
ex 2904 90 20	10	Tosyl chloride	0
ex 2904 90 40	10	Trichloronitromethane, for the manufacture of goods of subheading 3808 20 ([a])	0
ex 2904 90 85	10	Quintozene (ISO)	0
ex 2905 19 00 ex 3824 90 99	11 56	Potassium *tert*-butanolate (potassium *tert*-butoxide), whether or not in the form of a solution in tetrahydrofuran	0
2905 29 10		Allyl alcohol	0
ex 2905 39 80	10	2-Methylpropane-1,3-diol	0
ex 2905 39 80	20	Hexa-1,5-diene-3,4-diol	0
ex 2905 49 10	10	Ethylidynetrimethanol	0
2906 11 00		Menthol	0
ex 2906 19 00	10	Cyclohex-1,4-ylenedimethanol	0
ex 2906 19 00	20	4,4′-Isopropylidenedicyclohexanol	0
ex 2906 29 00	10	2,2′-(*m*-Phenylene)dipropan-2-ol	0
ex 2907 21 00	10	Resorcinol	0
ex 2907 29 00	10	Disodium1,4-dihydroanthracene-9,10-diolate, in the form of an aqueous solution	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2907 29 00	20	4,4′-(3,3,5-Trimethylcyclohexylidene)diphenol	0
ex 2907 29 00	30	4,4′,4″-Ethylidynetriphenol	0
ex 2907 29 00	40	Mixture of isomers of methylenediphenol	0
ex 2907 29 00	50	6,6′,6″-Tricyclohexyl-4,4′,4″-butane-1,1,3-triyltri(*m*-cresol)	0
ex 2907 29 00	60	4,4′-(1,3-Phenylenediisopropylidene)diphenol	0
ex 2908 20 00	10	Disodium-3-hydroxynaphthalene-2,7-disulphonate	0
ex 2908 20 00	20	Dipotassium-7-hydroxynaphthalene-1,3-disulphonate	0
ex 2908 20 00 ex 3824 90 99	30 74	6-Hydroxynaphthalene-2-sulphonic acid and its salts	0
ex 2908 90 00	10	4-Nitroso-*o*-cresol	0
ex 2909 19 00	10	1,2-Bis(2-chloroethoxy)ethane	0
ex 2909 30 38	10	Bis(pentabromophenyl) ether	0
ex 2909 30 90	10	4-(*p*-Tolyloxy)biphenyl	0
ex 2909 30 90	20	1,2-Bis(*m*-tolyloxy)ethane	0
ex 2909 30 90	30	1,2-Diphenoxyethane	0
ex 2909 44 00	10	2-Hexyloxyethanol	0
ex 2909 49 19	10	1-*tert*-Butoxypropan-2-ol	0
ex 2909 50 90	10	4-(2-Methoxyethyl)phenol	0
ex 2910 90 00	30	2,3-Epoxypropan-1-ol (glycidol)	0
ex 2910 90 00	40	Perfluoroepoxypropane	0
ex 2910 90 00 ex 3824 90 99	60 59	1,2-Epoxyoctadecane, of a purity by weight of 82 % or more	0
ex 2912 29 00	10	Terephthalaldehyde	0
ex 2912 49 00	10	3-Phenoxybenzaldehyde	0
ex 2914 19 90	10	3,3-Dimethylbutan-2-one	0
2914 21 00		Camphor	0
ex 2914 29 00	10	Estr-4-ene-3,17-dione	0

▼M12

ex 2914 29 00	20	Cyclohexadec-8-enone	0

▼M11

ex 2914 50 00	30	2′-Hydroxyacetophenone	0
ex 2914 50 00	40	4′-Hydroxyacetophenone	0
ex 2914 50 00	50	6′-Methoxy-2′-acetonaphthone	0
ex 2914 69 90	10	2-Ethylanthraquinone	0
ex 2914 69 90	20	2-Pentylanthraquinone	0
ex 2914 69 90	30	1,4-Dihydroxyanthraquinone	0
ex 2914 69 90	40	2,3-Dihydro-1,4-dihydroxyanthraquinone	0
ex 2914 70 90	10	1-Chloro-3,3-dimethylbutan-2-one	0
ex 2914 70 90	30	4,4′-Dibromobenzil	0
ex 2915 29 00	10	Antimony triacetate	0
ex 2915 39 90	20	5*α*-Bromo-6*β*-hydroxy-17-oxo-androstan-3*β*-yl acetate	0
ex 2915 39 90	30	But-3-ene-1,2-diyl di(acetate)	0
ex 2915 40 00	10	Vinyl chloroacetate	0
ex 2915 90 80	20	Trimethyl orthoacetate	0
ex 2915 90 80	30	2-Ethylbutyric acid	0
ex 2915 90 80	40	Nonanoic acid (pelargonic acid)	0
ex 2916 12 90	10	2-*tert*-Butyl-6-(3-*tert*-butyl-2-hydroxy-5-methylbenzyl)-4-methylphenyl acrylate	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2916 12 90	20	2-Ethoxyethyl acrylate	0
ex 2916 12 90	30	Isobutyl acrylate	0
ex 2916 13 00	10	Hydroxyzinc methacrylate, in the form of powder	0
ex 2916 13 00	20	Zinc dimethacrylate, in the form of powder	0
ex 2916 14 90	10	2,3-Epoxypropyl methacrylate	0
ex 2916 19 80	20	Methyl 3,3-dimethylpent-4-enoate	0
ex 2916 20 00	10	Methyl 3-(2,2-dichlorovinyl)-2,2-dimethylcyclopropane-carboxylate	0
ex 2916 20 00	30	Empenthrin (ISO)	0
ex 2916 20 00	40	Cyclohexanecarboxylic acid	0
ex 2916 39 00	10	Methyl 3-chlorobenzoate	0
ex 2916 39 00	20	3,5-Dichlorobenzoyl chloride	3,6
ex 2916 39 00	40	Vinyl 4-*tert*-butylbenzoate	0
ex 2916 39 00	50	3,5-Dimethylbenzoyl chloride	0
ex 2916 39 00	60	4-Ethylbenzoyl chloride	0
ex 2917 11 00	20	Bis(*p*-methylbenzyl) oxalate	0
ex 2917 19 90	20	Sodium1,2-bis(cyclohexyloxycarbonyl)ethanesulphonate	0
ex 2917 19 90	40	Dodecanedioic acid, of a purity by weight of more than 98,5 %	0
ex 2917 19 90	50	Glutaric anhydride	0
ex 2917 20 00	30	1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicar-boxylic anhydride	0
ex 2917 20 00	40	3-Methyl-1,2,3,6-tetrahydrophthalic anhydride	0
ex 2917 34 00	10	Diallyl phthalate	0
ex 2917 39 80	10	Dimethyl naphthalene-2,6-dicarboxylate	0
ex 2917 39 80	20	Benzene-1,2,4,5-tetracarboxylic acid (pyromellitic acid)	0
ex 2917 39 80	30	Benzene-1,2:4,5-tetracarboxylic dianhydride (pyromellitic dianhydride)	0
ex 2918 13 00	10	L-(-)-Di-*p*-toluoyltartaric acid	0
ex 2918 19 80	20	L-Malic acid	0
ex 2918 29 10	10	Monohydroxynaphthoic acids	0
ex 2918 29 50	10	Gallic acid, of a purity by weight of 98,5 % or more calculated on the dry weight (measured by acidimetry)	0
ex 2918 29 90	10	Hexamethylene bis[3-(3,5-di-*tert*-butyl-4-hydroxyphenyl)-propionate]	0
ex 2918 90 90	10	3,4-Epoxycyclohexylmethyl 3,4-epoxycyclohexanecarbox-ylate	0
ex 2918 90 90	20	Methyl 3-methoxyacrylate	0
ex 2919 00 90	10	2,2′-Methylenebis(4,6-di-*tert*-butylphenyl) phosphate, monosodium salt	0
ex 2919 00 90	20	Diammonium salt of tetramyristoylcardiolipin	0
ex 2920 10 00	10	Fenitrothion (ISO)	0
ex 2920 10 00	20	Tolclofos-methyl (ISO)	0
ex 2920 90 10	10	Diethyl sulphate	0
2920 90 30		Trimethyl phosphite	0
ex 2920 90 85	10	*O,O′*-Dioctadecyl pentaerythritol bis(phosphite)	0
ex 2920 90 85	30	*O,O′*-Bis(2,4-di-*tert*-butylphenyl)pentaerythritol bis(pho-sphite)	0
ex 2921 19 80	10	Triallylamine	0
ex 2921 19 80	20	Ethyl(2-methylallyl)amine	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2921 19 80	30	Allylamine	0
ex 2921 29 00	10	*N,N,N′,N′*-Tetrabutylhexamethylenediamine	0
ex 2921 29 00	20	Tris[3-(dimethylamino)propyl]amine	0
ex 2921 29 00	30	Bis[3-(dimethylamino)propyl]methylamine	0
ex 2921 30 99	10	Dicyclohexyl(methyl)amine	0
▼M12			
ex 2921 30 99	20	Cyclohex-1,3-ylenebis(methylamine), for the manufacture of dishwashing products (a)	0
▼M11			
ex 2921 42 10	10	2,6-Dichloro-4-nitroaniline	0
ex 2921 42 10	20	2-Bromo-4,6-dinitroaniline	0
ex 2921 42 10	30	4-Aminobenzene-1,3-disulphonic acid and its salts	0
ex 2921 42 10	40	2-Bromo-6-chloro-4-nitroaniline	0
ex 2921 42 10	50	3-Aminobenzenesulphonic acid	0
ex 2921 43 00	10	5-Amino-2-chlorotoluene-4-sulphonic acid	0
ex 2921 43 00	20	4-Amino-6-chlorotoluene-3-sulphonic acid	0
ex 2921 43 00	30	3-Nitro-*p*-toluidine	0
ex 2921 44 00	10	Methyldiphenylamine	0
ex 2921 45 00	10	3-Aminonaphthalene-1,5-disulphonic acid, monosodium salt	0
ex 2921 45 00	20	2-Aminonaphthalene-1,5-disulphonic acid and its sodium salts	0
ex 2921 45 00	30	2-Aminonaphthalene-1-sulphonic acid	0
ex 2921 45 00	40	1-Naphthylamine	0
ex 2921 49 10	20	Pendimethalin (ISO)	3,5
ex 2921 49 80	10	8-Anilinonaphthalene-1-sulphonic acid	0
▼M12			
ex 2921 49 80	20	*N*-1-Naphthylaniline	0
▼M11			
ex 2921 59 90	10	Mixture of isomers of 3,5-diethyltoluenediamine	0
ex 2921 59 90 ex 3824 90 99	20 68	4-(4-Aminoanilino)-3-nitrobenzenesulphonic acid	0
ex 2922 19 80	10	4,4-Dimethoxybutylamine	0
▼M12			
▼M11			
ex 2922 19 80	30	*N,N,N′,N′*-Tetramethyl-2,2′-oxybis(ethylamine)	0
ex 2922 19 80	40	2-Amino-2-methylpropanol, for use in the manufacture of goods of subheadings 3004 90 and 3305 30 (a)	0
ex 2922 21 00	10	2-Amino-5-hydroxynaphthalene-1,7-disulphonic acid and its salts, of a purity by weight of 60 % or more	0
ex 2922 21 00	20	4-Hydroxy-7-methylaminonaphthalene-2-sulphonic acid	0
ex 2922 21 00	30	6-Amino-4-hydroxynaphthalene-2-sulphonic acid	0
ex 2922 21 00	40	7-Amino-4-hydroxynaphthalene-2-sulphonic acid	0
ex 2922 22 00	10	Anisidines	0
ex 2922 29 00	10	2-Methyl-*N*-phenyl-*p*-anisidine	0
ex 2922 29 00	20	3-Aminophenol	0
ex 2922 29 00	30	4-Amino-5-methoxy-2-methylbenzenesulphonic acid	0
ex 2922 29 00	40	2-Amino-4-*tert*-pentyl-6-nitrophenol	0
ex 2922 29 00	50	6-Methoxy-*m*-toluidine	0
ex 2922 29 00	60	3,5-Dichloro-4-(1,1,2,2-tetrafluoroethoxy)aniline	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2922 29 00	70	4-Nitro-*o*-anisidine	0
ex 2922 29 00	80	3-Diethylaminophenol	0
ex 2922 39 00	10	1-Amino-4-bromo-9,10-dioxoanthracene-2-sulphonic acid and its salts	0
ex 2922 39 00	20	1-Aminoanthraquinone	0
ex 2922 39 00	30	1-Bromo-4-methylaminoanthraquinone	0
▼M12			
ex 2922 39 00	40	1,4-Diamino-2,3-dichloroanthraquinone	0
▼M11			
ex 2922 49 95	10	Ornithine aspartate (INNM)	0
ex 2922 49 95	20	12-Aminododecanoic acid	0
ex 2922 50 00	30	2-(3-Amino-4-chlorobenzoyl)benzoic acid	0
ex 2922 50 00	50	2-(4-Dibutylaminosalicyloyl)benzoic acid	0
ex 2923 90 00	10	Tetramethylammonium hydroxide, in the form of an aqueous solution containing: — (25 ± 0,5) % by weight of tetramethylammonium hydroxide, — 500 mg/kg or less of carbonate, — 200 mg/kg or less of chloride, and — 5 mg/kg or less of potassium	0
ex 2923 90 00	30	Tetramethylammonium hydroxide pentahydrate, of a purity by weight of 98 % or more	0
ex 2923 90 00	40	Benzyldimethyl(octadecyl)ammonium salts, for use in the manufacture of toner for photocopiers (a)	0
ex 2924 19 00	10	2-Acrylamido-2-methylpropanesulphonic acid and its sodium or ammonium salts	0
ex 2924 19 00	20	*N,N*′-Methylenediacrylamide	0
ex 2924 21 90 ex 3824 90 99	10 62	4,4′-Dihydroxy-7,7′-ureylenedi(naphthalene-2-sulphonic acid) and its sodium salts	0
ex 2924 29 95	10	Alachlor (ISO)	0
ex 2924 29 95	15	Acetochlor (ISO)	0
ex 2924 29 95	20	3′-Amino-4′-methoxyacetanilide	0
ex 2924 29 95	25	3′-Diethylaminoacetanilide	0
ex 2924 29 95	30	Propachlor (ISO)	0
ex 2924 29 95	35	Diethofencarb (ISO)	0
ex 2924 29 95	40	7-Acetamido-4-hydroxynaphthalene-2-sulphonic acid and its sodium salts	0
ex 2924 29 95	45	3′-Diethylamino-4′-methoxyacetanilide	0
ex 2924 29 95	50	5-[*N*-(2-Acetoxyethyl)acetoxyacetamido]-*N,N*′-bis(2,3-diacetoxy propyl)-2,4,6-triiodoisophthalamide	0
ex 2924 29 95	55	4′-Amino-*N*-methylacetanilide	0
ex 2924 29 95	60	Beflubutamid (ISO)	0
▼M12			
ex 2924 29 95	65	2-(4-Hydroxyphenyl)acetamide	0
▼M11			
ex 2924 29 95	70	4-Acetamido-2-aminobenzenesulphonic acid	0
ex 2925 11 00	20	Saccharin and its sodium salt	0
ex 2925 19 95	10	*N*-Phenylmaleimide	0
ex 2925 20 00	10	Dicyclohexylcarbodiimide	0
ex 2926 90 95	10	Methacrylonitrile	0
ex 2926 90 95	20	2-(*m*-Benzoylphenyl)propiononitrile	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2926 90 95	30	2-Amino-5-nitrobenzonitrile	0
ex 2926 90 95	40	Chlorothalonil (ISO)	0
ex 2926 90 95	45	2-Cyanoacetamide	0
ex 2926 90 95	50	Alkyl or alkoxyalkyl esters of cyanoacetic acid	0
ex 2926 90 95	60	Cyanoacetic acid in crystalline form	0
ex 2926 90 95	65	Malononitrile	0
ex 2926 90 95	70	Tetrachloroterephthalonitrile	0
ex 2927 00 00	10	2,2′-Dimethyl-2,2′-azodipropionamidine dihydrochloride	0
ex 2927 00 00	20	4-Anilino-2-methoxybenzenediazonium hydrogen sulphate	0
ex 2927 00 00 ex 3824 90 99	30 69	4′-Aminoazobenzene-4-sulphonic acid	0
ex 2927 00 00	40	2-Hydroxynaphthalene-1-diazonium-4-sulphonate	0
ex 2927 00 00 ex 3824 90 99	50 41	2-Hydroxy-6-nitronaphthalene-1-diazonium-4-sulphonate, of a purity by weight of 60 % or more	0
ex 2928 00 90	10	3,3′-Bis(3,5-di-*tert*-butyl-4-hydroxyphenyl)-*N,N*′-bipropionamide	0
ex 2928 00 90	20	2,4,6-Trichlorophenylhydrazine	0
ex 2928 00 90	40	*O*-Ethylhydroxylamine, in the form of an aqueous solution	0
ex 2928 00 90	50	*N*-Isopropylhydroxylamine, in the form of an aqueous solution	0
ex 2929 10 90	10	Methylenedicyclohexyl diisocyanates	0
ex 2929 10 90	30	3,3′-Dimethylbiphenyl-4,4′-diyl diisocyanate	0
ex 2929 10 90	40	*m*-Isopropenyl-*α,α*-dimethylbenzyl isocyanate	0
ex 2929 10 90	50	*m*-Phenylenediisopropylidene diisocyanate	0
ex 2929 10 90	60	Trimethylhexamethylene diisocyanate, mixed isomers	0
ex 2930 90 70	10	Thiophenol	0
ex 2930 90 70	15	Ethoprophos (ISO)	0
ex 2930 90 70	20	3,3-Dimethyl-1-methylthiobutanone oxime	0
ex 2930 90 70	25	Thiophanate-methyl (ISO)	0
ex 2930 90 70	30	4-(4-Isopropoxyphenylsulphonyl)phenol	0
ex 2930 90 70	40	3,3′-Thiodi(propionic acid)	0
ex 2930 90 70	45	2-[(*p*-Aminophenyl)sulphonyl]ethyl hydrogen sulphate	0
ex 2930 90 70 ex 3824 90 99	50 51	2-Chlorophenylsulphonyl isocyanate, in the form of a solution in xylene	0
ex 2930 90 70 ex 3824 90 99	55 52	Methyl 2-(isocyanatosulphonyl)methylbenzoate, in the form of a solution in xylene	0
ex 2930 90 70	60	Methyl phenyl sulphide	0
ex 2930 90 70	65	Diiodomethyl *p*-tolyl sulphone	0
ex 2930 90 70 ex 3824 90 99	70 71	2-Aminophenyl phenyl sulphone, of a purity by weight of 75 % or more	0
ex 2930 90 70	75	4,4′-[Methylenebis(oxyethylenethio)]diphenol	0
ex 2930 90 70	80	Captan (ISO)	0
ex 2930 90 70	85	Mesotrione (ISO)	0
2931 00 10		Dimethyl methylphosphonate	0
ex 2931 00 95	05	Butylethylmagnesium, in the form of a solution in heptane	0
ex 2931 00 95	10	2-Diphenylphosphinobenzoic acid	0
ex 2931 00 95	20	Bis(2-chloroethyl)2-chloroethylphosphonate	0
ex 2931 00 95	25	Sodium phenylphosphinate	0
ex 2931 00 95	30	Bis(2-chloroethyl)vinylphosphonate	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2931 00 95	35	Sodium tetraphenylborate	0
ex 2931 00 95	40	*N*-(Phosphonomethyl)iminodiacetic acid	0
ex 2931 00 95	45	Tributylphosphine	0
ex 2931 00 95	50	Bis(2,4,4-trimethylpentyl)phosphinic acid	0
ex 2931 00 95	55	Dimethyl[dimethylsilyldiindenyl]hafnium	0
ex 2931 00 95	60	Trioctylphosphine oxide	0
ex 2931 00 95	65	Triethylborane	0
ex 2931 00 95	70	*N,N*-Dimethylanilinium tetrakis(pentafluorophenyl)borate	0
ex 2931 00 95	75	{2,7-Di-*tert*-butyl-9-[(η^5-cyclopentadienyl)bis(4-triethylsilylphenyl)methyl]-4a,4b,8a,9,9a-η-fluorene}dimethylhafnium, in the form of a solution in hexane	0
ex 2931 00 95	85	Tributyl(tetradecyl)phosphonium chloride, whether or not in the form of an aqueous solution	0
ex 2931 00 95	95	Trichloro(3-chloropropyl)silane	0
ex 2932 11 00	10	Tetrahydrofuran, containing not more than 40 mg per litre in total of tetrahydro-2-methylfuran and tetrahydro-3-methylfuran, for the manufacture of α-4-hydroxybutyl-ω-hydroxypoly(oxytetramethylene) (a)	0
ex 2932 13 00	10	Tetrahydrofurfuryl alcohol	0
ex 2932 19 00	40	Furan of a purity by weight of 99 % or more	0
ex 2932 19 00	50	2,3-Dihydrofuran	0
ex 2932 29 80	10	2′-Anilino-6′-[ethyl(isopentyl)amino]-3′-methylspiro[isobenzofuran-1(3*H*),9′-xanthen]-3-one	0
ex 2932 29 80	15	13,14,15,16-Tetranorlabdano-12,8α-lactone	0
ex 2932 29 80	25	2′-(2-Chloroanilino)-6′-dibutylaminospiro[isobenzofuran-1(3*H*),9′-xanthen]-3-one	0
ex 2932 29 80	30	2′-Anilino-3′-methyl-6′-methyl(propyl)aminospiro[isobenzofuran-1(3*H*),9′-xanthen]-3-one	0
ex 2932 29 80	35	6′-Diethylamino-3′-methyl-2′-(2,4-xylidino)spiro[isobenzofuran-1(3*H*),9′-xanthen]-3-one	0
ex 2932 29 80	40	2′-Anilino-6′-(*N*-ethyl-*p*-toluidino)-3′-methylspiro[isobenzofuran-1(3*H*),9′-xanthen]-3-one	0
ex 2932 29 80	45	2′-Anilino-6′-ethyl(isobutyl)amino-3′-methylspiro[isobenzofuran-1(3*H*),9′-xanthen]-3-one	0
ex 2932 29 80	50	2′-Anilino-6′-cyclohexyl(methyl)amino-3′-methylspiro[isobenzofuran-1(3*H*),9′-xanthen]-3-one	0
ex 2932 29 80	55	6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide	0
▼M12			
ex 2932 29 80	70	3′,6′-Bis(ethylamino)-2′,7′-dimethylspiro[isobenzofuran-1(3*H*),9′-[9*H*]-xanthen]-3-one	0
▼M11			
ex 2932 99 70	10	Bendiocarb (ISO)	0
ex 2932 99 70	20	Androsta-1,4-diene-3,17-dione17-(2,2-dimethylpropylene)acetal	0
ex 2932 99 70	40	1,3:2,4-Bis-*O*-(3,4-dimethylbenzylidene)-D-glucitol	0
ex 2933 19 90	10	4,5-Diamino-l-(2-hydroxyethyl)-1*H*-pyrazole sulphate	0
ex 2933 21 00	10	Hydantoin	0
ex 2933 21 00	20	2-(3-Benzyl-2,5-dioxoimidazolidin-1-yl)-2′-chloro-5′-(3-dodecyl-sulphonyl-2-methylpropionamido)-4,4-dimethyl-3-oxovaleranilide	0
ex 2933 21 00	40	1-[1,3-Bis(hydroxymethyl)-2,5-dioxoimidazolidin-4-yl]-1,3-bis(hydroxymethyl)urea	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2933 29 90	20	Reaction product consisting of the methyl esters of (±)-6-(4-isopropyl-4-methyl-5-oxo-2-imidazolin-2-yl)-*m*-toluic acid and (±)-2-(4-isopropyl-4-methyl-5-oxo-2-imidazolin-2-yl)-*p*-toluic acid (Imazamethabenz-methyl)	4
ex 2933 29 90	40	Triflumizole (ISO)	0
▼M12			
ex 2933 29 90	50	1,3-Dimethylimidazolidin-2-one	0
▼M11			
ex 2933 39 99	10	Cloperastine fendizoate (INNM)	0
ex 2933 39 99	15	Pyridine-2,3-dicarboxylic acid	0
ex 2933 39 99	20	5-Methyl-2-pyridylamine	0
ex 2933 39 99	25	Imazethapyr (ISO)	0
ex 2933 39 99	30	4,4′-Trimethylenedipiperidine	0
ex 2933 39 99	60	2-Fluoro-6-(trifluoromethyl)pyridine	0
ex 2933 49 10	10	Quinmerac (ISO)	0
ex 2933 49 90	20	5,7-Dichloro-4-(4-fluorophenoxy)quinoline	0
ex 2933 49 90	40	*N*-Ethyl-5, 6, 7, 8-tetrahydroquinolinium *p*-toluenesulphonate, in the form of a solution in water	0
ex 2933 49 90	50	Methyl 2-[(*S*)-3-{(*E*)-3-[2-(7-chloro-2-quinolyl)vinyl]-phenyl}-3-hydroxypropyl]benzoate monohydrate	0
ex 2933 49 90	60	5,6,7,8-Tetrahydroquinoline	0
ex 2933 59 95	10	1-Ethyl-6-fluoro-1,4-dihydro-4-oxo-7-piperazin-1-yl-1,8-naphthyridine-3-carboxylic acid and its salts and esters	0
ex 2933 59 95	20	2,4-Diamino-6-chloropyrimidine	0
ex 2933 59 95	30	Mepanipyrim (ISO)	0
ex 2933 59 95	40	Guanine	0
ex 2933 59 95	50	1-Chloromethyl-4-fluoro-1,4-diazoniabicyclo[2.2.2]octane-bis(tetrafluoroborate)	0
▼M12			
ex 2933 59 95	60	2,6-Dichloro-4,8-dipiperidinopyrimido[5,4-*d*]pyrimidine	0
ex 2933 59 95	70	*N*-(4-Ethyl-2,3-dioxopiperazin-1-ylcarbonyl)-D-2-phenylglycine	0
ex 2933 59 95	80	*N*-(4-Ethyl-2,3-dioxopiperazin-1-ylcarbonyl)-D-2-(4-hydroxyphenyl)glycine	0
▼M11			
ex 2933 69 80	10	1,3,5-Tris(4-*tert*-butyl-3-hydroxy-2,6-dimethylbenzyl)-1,3,5-triazine-2,4,6(1*H*, 3*H*,5*H*)-trione	0
ex 2933 69 80	20	1,3,5-Tris[(3,5-di-*tert*-butyl-4-hydroxyphenyl)methyl]-1,3,5-triazine-2,4,6(1*H*,3*H*,5*H*)-trione	0
ex 2933 69 80	40	Cyanazine (ISO)	0
ex 2933 69 80	50	1,3,5-Tris(2,3-dibromopropyl)-1,3,5-triazinane-2,4,6-trione	0
ex 2933 69 80	60	Hexazinone (ISO)	0
ex 2933 99 30	10	Azepane, for the manufacture of goods of subheading 3808 30 (a)	0
ex 2933 99 90	10	2-(2*H*-Benzotriazol-2-yl)-4,6-di-*tert*-butylphenol	0
ex 2933 99 90	15	2-(2*H*-Benzotriazol-2-yl)-4,6-di-*tert*-pentylphenol	0
ex 2933 99 90	20	2-(2*H*-Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)-phenol	0
ex 2933 99 90	25	6,6′-Di-2*H*-benzotriazol-2-yl-4,4′-bis(1,1,3,3-tetramethylbutyl)-2,2′-methylenediphenol	0
ex 2933 99 90	30	Quizalofop-P-ethyl (ISO)	0
ex 2933 99 90	35	Indoline	0
ex 2933 99 90	45	Maleic hydrazide (ISO)	0

▼M11

	CN code	TARIC	Description	Rate of autonomous duty (%)
	ex 2933 99 90	50	Metconazole (ISO)	3,2
	ex 2933 99 90	55	5-Nitroindole	0
	ex 2933 99 90	60	1,3-Bis(3-isocyanatomethylphenyl)-1,3-diazetidine-2,4-dione (dimeric2,4-toluene diisocyanate)	0
	ex 2933 99 90	65	Candesartan cilexetil (INNM)	0
	ex 2933 99 90	70	6,7-Dihydro-5*H*-cyclopenta[*b*]pyridine	0
▼M12				
	ex 2933 99 90	75	2,3-Dichloropyrazine	0
	ex 2933 99 90	80	1-Methyltetrazole-5-thiol	0
▼M11				
	ex 2934 10 00	10	Hexythiazox (ISO)	0
	ex 2934 10 00	20	2-(4-Methylthiazol-5-yl)ethanol	0
	ex 2934 20 80	10	4-Chloro-1,3-benzothiazol-2(3*H*)-one	0
▼M12				
	ex 2934 20 80	20	*S*-(1,3-Benzothiazol-2-yl) (*Z*)-2-(2-aminothiazol-4-yl)-2-(methoxyimino)thioacetate	0
▼M11				
	ex 2934 99 90	10	7-Chloro-5-methyl-2*H*-1,4-benzothiazin-3-(4*H*)-one	0
	ex 2934 99 90	15	Carboxin (ISO)	0
	ex 2934 99 90	20	4-[4-(Tridecyl[branched]oxy)phenyl]-1,4-thiazinane1,1-dioxide	0
	ex 2934 99 90	25	Oxycarboxin (ISO)	0
	ex 2934 99 90	30	Etridiazole (ISO)	0
	ex 2934 99 90	35	Dimethenamide (ISO)	0
	ex 2934 99 90	40	2,3,5,6-Tetrahydroxy-1,4-diisobutyl-1,4-dioxo-1,4-diphosphinane	0
	ex 2934 99 90	45	Tris(2,3-epoxypropyl)-1,3,5-triazinanetrione	0
	ex 2934 99 90	50	1-[2-(1,3-Dioxan-2-yl)ethyl]-2-ethylpyridinium bromide	0
	ex 2934 99 90	55	Olmesartan medoxomil (INN)	0
▼M12				
	ex 2934 99 90	60	DL-Homocysteine thiolactone hydrochloride	0
▼M11				
	ex 2935 00 90	10	Salts of sulphathiazole (INN)	0
	ex 2935 00 90	20	Toluenesulphonamides	0
	ex 2935 00 90	30	Mixture of isomers consisting of *N*-ethyltoluene-2-sulphonamide and *N*-ethyltoluene-4-sulphonamide	0
	ex 2935 00 90	40	1-(4,6-Dimethoxypyrimidin-2-yl)-3-(2-ethylsulphonylimidazo[1,2-a]pyridin -3-ylsulphonyl)urea (sulphosulphuron)	0
	ex 2935 00 90	50	4,4′-Oxydi(benzenesulphonohydrazide)	0
	ex 2935 00 90	60	5-Amino-*N*-(2,6-dichloro-*m*-tolyl)-1*H*-1,2,4-triazole-3-sulphonamide	0
	ex 2935 00 90	70	Methyl3-aminosulphonylthiophene-2-carboxylate	0
	3201 20 00		Wattle extract	0
	ex 3201 90 90	10	Tanning extracts of eucalyptus	3,2
	ex 3201 90 90	20	Tanning extracts derived from gambier and myrobalan fruits	0
	ex 3204 15 00	10	Dye C.I. Vat Orange 7	0
	ex 3204 15 00	20	Dye C.I. Vat Red 15	0
	ex 3204 15 00	30	Dye C.I. Vat Red 14	0
	ex 3204 15 00	40	Dye C.I. Vat Brown 57	0
	ex 3204 17 00	10	Dye C.I. Pigment Yellow 81	0

▼M11

	CN code	TARIC	Description	Rate of autonomous duty (%)
	ex 3204 19 00	10	Nickelbis{4-methoxy-2-[6-(pentafluoroethylthio)benzothiazol-2-ylazo] -5-(dipropylamino)benzenesulphonate}	0
▼M12	ex 3204 19 00	15	4-{4-[3-(4-Methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromen-3-yl]phenyl}morpholine	0
▼M11	ex 3204 19 00	20	13-Ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo [*h*]indeno[2,1-*f*]chromen-13-ol	0
▼M12	ex 3204 19 00	25	Cyclohexyl 8-methyl-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate	0
▼M11	ex 3204 19 00	30	13-Isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromen-13-ol	0
▼M12	ex 3204 19 00	35	13-Butyl-13-ethoxy-6,11-dimethoxy-3,3-bis(4-methoxyphenyl)-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromene	0
▼M11	ex 3204 19 00	40	Methyl8′-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1*H*-indole-2,3′-naphtho[2,1-*b*][1,4]oxazine]-9′-carboxylate	0
▼M12	ex 3204 19 00	45	6,7-Dimethoxy-3,3-bis(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromene	0
▼M11	ex 3204 19 00	50	Methyl 6-(isobutyryloxy)-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate	0
	ex 3204 19 00	60	Ethoxycarbonylmethyl8-methyl-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate	0
	ex 3204 19 00	70	Dye C.I. Solvent Red 49	0
▼M12	ex 3206 19 00	10	Preparation based on titanium dioxide, containing by weight 66 % or more but not more than 71 % of titanium dioxide and 1 % or more but not more than 2 % of isopropoxytitanium triisostearate	0
▼M11	ex 3206 42 00	10	Lithopone	0
	ex 3206 49 90	10	Black preparation of iron-oxide pigments, in liquid form, with a maximum particle size not exceeding 20 nanometres and containing by weight 25 % or more of iron evaluated as Fe_2O_3, for the manufacture of goods of heading No 3304 or 9608 (a)	0
	ex 3208 20 10	10	Copolymer of *N*-vinylcaprolactam, *N*-vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate, in the form of a solution in ethanol containing by weight 34 % or more but not more than 40 % of copolymer	0
	ex 3208 20 10 ex 3905 91 00	20 92	Copolymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, partially quaternised by diethyl sulphate, in the form of a solution in ethanol	0
	ex 3208 20 10	30	Solution of diundecyl phthalate and a copolymer of dibutyl maleate and isobutyl methacrylate in a hydrocarbon solvent	0
	ex 3208 90 19 ex 3911 90 99	10 35	Copolymer of maleic acid and methyl vinyl ether, monoesterified with ethyl and/or isopropyl and/or butyl groups, in the form of a solution in ethanol, ethanol and butanol, isopropanol or isopropanol and butanol	0
	ex 3208 90 19	20	Copolymer of polyurethane and silicone, in the form of a solution in a mixture of butanone, toluene and cyclohexanone, containing by weight 13 % or more but not more than 16 % of copolymer	0
	ex 3208 90 19	30	Solution containing: — (30 ± 5) % by weight of polyamide resin,	

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
		— (6,5 ± 3,5) % by weight of diazonaphthoquinone, — (55 ± 5) % by weight of 1-methyl-2-pyrrolidone, — 1 000 µg/kg or less of chloride, — 1 000 µg/kg or less of potassium, and — 1 000 µg/kg or less of iron	0
ex 3208 90 19	40	Polymer of methylsiloxane, in the form of a solution in a mixture of acetone, butanol, ethanol and isopropanol, containing by weight 5 % or more but not more than 11 % of polymer of methylsiloxane	0
ex 3208 90 99	10	Solution based on chemically modified natural polymers, containing two or more of the following dyes: — methyl8′-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1*H*-indole-2,3′-naphtho[2,1-*b*][1,4]oxazine]-9′-carboxylate, — methyl6-(isobutyryloxy)-2,2-diphenyl-2*H*-benzo[*h*]-chromene-5-carboxylate, — 13-isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo [*h*]indeno[2,1-*f*]chromen-13-ol, — ethoxycarbonylmethyl8-methyl-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate, — 13-ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromen-13-ol	0

▼M12

ex 3208 90 99	20	Solution based on chemically modified natural polymers, containing two or more of the following dyes: — 4-[4-(13,13-dimethyl-3-phenyl-3,13-dihydrobenzo[-*h*]indeno[2,1-*f*]chromen-3-yl)phenyl]morpholine, — 4-{4-[3-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromen-3-yl]phenyl}morpholine, — cyclohexyl 8-methyl-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate, — ethoxycarbonylmethyl 6-acetoxy-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate, — 2-pentyl-7,7-diphenyl-7,8-benzochromeno[6,5-*d*]-1,3-dioxin-4(7*H*)-one, — 13-butyl-13-ethoxy-6,11-dimethoxy-3,3-bis(4-methoxyphenyl)-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromene, — 3-(4-methoxyphenyl)-13,13-dimethyl-3-phenyl-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromene, — 6,7-dimethoxy-3,3-bis(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromene	0

▼M11

ex 3215 90 80	10	Ink formulation, for use in the manufacture of ink-jet cartridges (a) ([a])	0
ex 3215 90 80	20	Heat-sensitive ink fixed on a plastic film	0
3301 12 10		Essential oil of orange, not deterpenated	0
ex 3402 90 10	20	Mixture of docusate sodium (INN) and sodium benzoate	0
ex 3402 90 10	30	Non-aqueous surface-active preparation, containing: — polyethylene glycol alkylphenyl ether, — 2,4,7,9-tetramethyldec-5-yne-4,7-diol, and — phosphoric acid esters	0
ex 3402 90 90	10	Crystalline powder obtained by the reaction of trisodium phosphate with a mixture of sodium hypochlorite and sodium chloride (chlorinated trisodium phosphate), containing by weight: — 3,5 % or more of available chlorine, measured iodometrically, and	

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
		— 17,0 % or more of phosphorus evaluated as P_2O_5	0
ex 3403 99 90	10	Cutting-fluid preparation based on an aqueous solution of synthetic polypeptides	0
ex 3504 00 00	10	Purified antigens obtained from genetically manipulated yeast cells, for the manufacture of detection tests for hepatitis-C (a)	0
ex 3504 00 00	20	Glycoprotein 160 obtained from Human Immunodeficiency Virus, HIV-1 strain	0
ex 3505 10 50	20	*O*-(2-Hydroxyethyl)-derivative of hydrolysed maize starch	0
ex 3506 91 00	10	Adhesive based on an aqueous dispersion of a mixture of dimerised rosin and a copolymer of ethylene and vinyl acetate (EVA)	0
ex 3506 91 00	20	Heat-activated adhesive based on phenolic resin and rubber, in the form of a film on a release paper, for use in the manufacture of brake pads for the automotive industry (a)	0
ex 3507 90 90	10	Asparaginase	0
ex 3507 90 90	20	Enzymatic preparation based on thermolysine	0
ex 3507 90 90	40	Avian myeloblastosis virus (AMV) reverse transcriptase	0
ex 3507 90 90	50	Lipase	0
ex 3701 30 00	10	Relief printing plate, of a kind used for printing on newsprint, consisting of a metal substrate coated with a photopolymer layer of a thickness of 0,2 mm or more but not exceeding 0,8 mm, not covered with a release film, of a total thickness not exceeding 1 mm	0
ex 3701 99 00	10	Plate of quartz or of glass, covered with a film of chromium and coated with a photosensitive or electron-sensitive resin, for the manufacture of masks for the goods of heading No 8541 or 8542 (a)	0
ex 3702 31 99	10	Colour negative film, for the manufacture of instant-picture film-packs (a)	0
ex 3702 43 00 ex 3702 44 00	10 10	Photographic film, of a nominal width of 459, 669 or 761 mm, composed of several layers, including two polyester films, a carbon layer, an adhesive layer and a layer of a copolymer of styrene with acrylonitrile	0
ex 3703 90 10	10	Paper sheet, coated with silver halide emulsion, for the manufacture of goods of subheading 3701 20 00 (a)	0
ex 3707 10 00	10	Photosensitive emulsion for the sensitisation of silicon discs (a)	0
ex 3707 90 30	10	Toner, in the form of powder, consisting of a copolymer of styrene and butyl acrylate and magnetite, for use as a developer in the manufacture of cartridges for facsimile machines (a)	0
3805 20 00		Pine oil	1,7
ex 3808 10 90	10	Indoxacarb (ISO) and its (*R*)isomer, fixed on a support of silicon dioxide	0
ex 3808 20 80	10	Fungicide in the form of a powder, containing by weight 65 % or more but not more than 75 % of hymexazole (ISO), not put up for retail sale	0
ex 3808 20 80	20	Preparation based on diiodomethyl *p*-tolyl sulphone, not put up for retail sale	0
▼M12			
ex 3808 20 80	30	Preparation consisting of a suspension of pyrithione zinc (INN) in water, containing by weight 24 % or more but not more than 26 % of pyrithione zinc (INN)	0
▼M11			
ex 3808 40 20	10	Preparation containing by weight: — 58 % or more but not more than 62 % of 1-bromo-3-chloro-5,5-dimethylhydantoin,	

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
		— 26 % or more but not more than 29 % of 1,3-dichloro-5,5-dimethylhydantoin, — 10 % or more but not more than 12 % of 1,3-dichloro-5-ethyl-5-methylhydantoin, for the manufacture of swimming-pool disinfectants (a)	0
ex 3808 40 90	10	1-Dodecylguanidine hydrochloride, in the form of a solution in isopropanol and water, containing by weight 40 % or less of 1-dodecylguanidine hydrochloride	0
ex 3809 91 00	10	Mixture of 5-ethyl-2-methyl-2-oxo-1,3,2λ^5-dioxaphosphoran-5-ylmethyl methyl methylphosphonate and bis(5-ethyl-2-methyl-2-oxo-1,3,2λ^5-dioxaphosphoran-5-ylmethyl) methylphosphonate	0
ex 3809 92 00	10	Paper anti-fading agent, consisting of a mixture of magnesium trisilicate and monosodium salt of 2,2′-methylenebis(4,6-di-*tert*-butylphenyl)phosphate	0
ex 3811 21 00	10	Salts of dinonylnaphthalenesulphonic acid, in the form of a solution in mineral oils	0
ex 3811 21 00	20	Additives for lubricating oils, based on complex organic molybdenum compounds, in the form of a solution in mineral oil	0
ex 3812 30 80	10	Tetraaluminium nonamagnesium dicarbonate hexacosahydroxide heptahydrate, coated with a surface-active agent	0
ex 3812 30 80	20	Mixture containing predominantly bis(2,2,6,6-tetramethyl-1-octyloxy-4-piperidyl) sebacate	0
ex 3812 30 80	30	Compound stabilisers containing by weight 15 % or more but not more than 40 % of sodium perchlorate and not more than 70 % of 2-(2-methoxyethoxy)ethanol	0
ex 3812 30 80	40	Dialuminium tetramagnesium monocarbonate dodecahydroxide monohydrate, coated with a surface-active agent	0
ex 3812 30 80	50	Aluminium magnesium zinc hydroxide carbonate hydrate, coated with a surface-active agent	0
ex 3814 00 90	10	Mixture containing by weight 25 % or more but not more than 35 % of dimethyl sulphoxide and 65 % or more but not more than 75 % of monoethanolamine	3
ex 3815 12 00	10	Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not exceeding 10 mm, consisting of silver on an aluminium oxide support and containing by weight 8 % or more but not more than 20 % of silver	0
ex 3815 12 00	20	Catalyst consisting of palladium and rhenium, fixed on a support of active carbon, in the form of powder, containing: — 0,5 % or more but not more than 1,5 % by weight of palladium, — 3 % or more but not more than 5 % by weight of rhenium and — 0,1 mole % or more but not more than 1 mole % of alkaline metals, for use in the manufacture of tetrahydrofuran (a)	0
ex 3815 19 90	10	Catalyst, consisting of chromium trioxide or dichromium trioxide fixed on a support of silicon dioxide, of a pore volume, as determined by the nitrogen absorption method, of 2 cm^3/g or more	0
ex 3815 19 90	15	Catalyst, in the form of a powder, consisting of a mixture of metal oxides fixed on a support of silicon dioxide, containing by weight 20 % or more but not more than 40 % of molybdenum, bismuth and iron evaluated together, for use in the manufacture of acrylonitrile (a)	0
ex 3815 19 90	20	Catalyst consisting of chromium oxides and titanium dioxide fixed on a support of silicon dioxide, aluminium	

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
		oxide or aluminium phosphate	0
ex 3815 19 90	30	Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene (a)	0
ex 3815 19 90	40	Catalyst, in the form of spheres of a diameter of 4,2 mm or more but not exceeding 9 mm, consisting of a mixture of metals oxides containing predominantly oxides of molybdenum, vanadium and copper, on a support of silicon dioxide and/or aluminium oxide, for use in the manufacture of acrylic acid (a)	0
ex 3815 19 90	45	Catalyst, consisting predominantly of dichromium copper tetraoxide and copper (II) oxide, containing by weight 38 % or more but not more than 48 % of copper, evaluated as copper (II) oxide, fixed on a support of silicon dioxide, for the hydrogenation of acetophenones (a)	0
ex 3815 19 90	50	Catalyst consisting of organometallic compounds of titanium, magnesium and aluminium on a support of silicon dioxide, in the form of a suspension in tetrahydrofuran	0
ex 3815 19 90	55	Catalyst consisting of a mixture of metal oxides containing chromium trioxide, fixed on a support of silicon dioxide	0
ex 3815 19 90	60	Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide	0
ex 3815 19 90	65	Catalyst consisting of phosphoric acid chemically bonded to a support of silicon dioxide	0
ex 3815 19 90	70	Catalyst consisting of organometallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide	0
ex 3815 19 90	75	Catalyst consisting of organometallic compounds of aluminium and chromium, fixed on a support of silicon dioxide	0
ex 3815 19 90	80	Catalyst consisting of organometallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil	0
ex 3815 19 90	85	Catalyst consisting of organometallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder	0
ex 3815 90 90	15	Catalyst, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, vanadium, nickel and antimony, whether or not mixed with porcelain balls, for use in the manufacture of acrylic acid (a)	0
ex 3815 90 90	20	Catalyst, in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing by weight: — 20 % or more but not more than 30 % of titanium, and — 55 % or more but not more than 72 % of chlorine	0
ex 3815 90 90	25	Catalyst, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, bismuth, nickel, iron and silicon, whether or not mixed with porcelain balls, for use in the manufacture of acrylaldehyde (a)	0
ex 3815 90 90	30	Catalyst, in the form of a powder, containing by weight 82 % or more of copper and of a specific surface of 0,5 m^2/g or more but not exceeding 8 m^2/g	0
ex 3815 90 90	35	Catalyst, in the form of a suspension in oil, consisting of titanium trichloride and aluminium trichloride, containing by weight (on an oil-free basis): — 15 % or more but not more than 30 % of titanium, and — 40 % or more but not more than 72 % of chlorine	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3815 90 90	40	Catalyst, in the form of rodlets of a length of 5 mm or more but not exceeding 8 mm, consisting of a mixture of metals oxides containing predominantly oxides of iron, molybdenum and bismuth, whether or not containing silicon dioxide as filler, for use in the manufacture of acrylic acid (a)	0
ex 3815 90 90	50	Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium	0

▼M12

▼M11

ex 3815 90 90	60	Catalyst, in the form of rodlets, consisting of an acid aluminosilicate (zeolite): — with a mole-ratio of silicon dioxide: dialuminium trioxide of not less than 500:1 and — containing by weight 0,2 % or more but not more than 0,8 % of platinum	0
ex 3815 90 90	65	Catalyst based on a mordenite zeolite, in the form of granules, for use in the manufacture of mixtures of methylamines containing by weight 50 % or more of dimethylamine	0
ex 3815 90 90	70	Catalyst, consisting of a mixture of (2-hydroxypropyl)trimethylammonium formate and dipropylene glycols	0
ex 3815 90 90	75	Catalyst, consisting of a mixture of 1,4-diazabicyclo[2.2.2]octane, 2-hydroxyethyliminodi(acetic acid) and dibutyltin di(acetate), containing by weight 5 % or more but not more than 10 % of 1,4-diazabicyclo[2.2.2]octane	0
ex 3815 90 90	80	Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol	0
ex 3815 90 90	81	Catalyst, containing by weight 38 % or more but not more than 48 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate	0
ex 3815 90 90	82	Catalyst, containing by weight 35 % or more but not more than 55 % of (2-hydroxy-1-methylethyl)trimethylammonium formate and formic acid	0
ex 3815 90 90	83	Catalyst, in the form of powder, containing aluminium magnesium hydroxide hydrate, rare-earth metals oxides and divanadium pentaoxide	0
ex 3815 90 90	85	Catalyst based on aluminosilicate (zeolite), for the transalkylation of alkylaromatic hydrocarbons or the oligomerisation of olefins (a)	0
ex 3823 19 10	91	Mixture of fatty acids containing by weight: — 2 % or more but not more than 6 % of hexanoic acid, — 53 % or more but not more than 60 % of octanoic acid, — 34 % or more but not more than 42 % of decanoic acid, and — not more than 2 % of dodecanoic acid	0
ex 3824 90 15	10	Acid aluminosilicate (artificial zeolite of the Y type) in the sodium form, containing by weight not more than 11 % of sodium evaluated as sodium oxide, in the form of rodlets	0
ex 3824 90 64	01	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of *Micromonospora purpurea*, whether or not dried	0
ex 3824 90 64	02	Cholic acid and 3*α*,12*α*-dihydroxy-5*β*-cholan-24-oic acid (deoxycholic acid), crude	0
ex 3824 90 64	03	Products obtained by the *N*-ethylation of sisomycin (INN)	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3824 90 64	04	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of *Micromonospora inyoensis*, whether or not dried	0
ex 3824 90 64	05	Residues of manufacture containing by weight 40 % or more of 11*β*,17,20,21-tetrahydroxy-6-methylpregna-1,4-dien-3-one21-acetate	0
ex 3824 90 99	01	Colloidal diantimony pentaoxide	0
ex 3824 90 99	02	Mixture of nitromethane and 1,2-epoxybutane	0
ex 3824 90 99	03	Grains or granules, consisting of a mixture of dialuminium trioxide and zirconium dioxide, containing by weight: — 70 % or more but not more than 78 % of dialuminium trioxide, and — 19 % or more but not more than 26 % of zirconium dioxide	5,2
ex 3824 90 99	04	Crude lithium hypochlorite	0
ex 3824 90 99	05	Polysilicate, modified with phosphoric acid, in the form of a solution in a mixture of ethanol, isopropanol and tetrahydrofuran, containing by weight 3 % or more but not more than 6 % of polysilicate	0
ex 3824 90 99	06	Preparation in the form: — of powder, containing by weight 75 % or more of zinc bis[3,5-bis(1-phenylethyl)salicylate], or — of aqueous dispersion, containing by weight 22 % or more but not more than 55 % of zinc bis[3,5-bis(1-phenylethyl)salicylate]	0
ex 3824 90 99	07	Film consisting of the oxides of either barium or calcium and either titanium or zirconium, mixed with binding materials	0
ex 3824 90 99	08	Preparation consisting essentially of alkaline asphalt sulphonate, of: — a specific gravity of 0,9 or more but not exceeding 1,5, and — a solubility in water of 70 % by weight or more	0
ex 3824 90 99	09	Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulphonic acid, either: — on a support of mineral wax, whether or not modified chemically, or — in the form of a solution in an organic solvent	0
ex 3824 90 99	10	Calcined bauxite (refractory grade)	0
ex 3824 90 99	11	Magnetisable iron oxide, in the form of powder, containing by weight: — 30 % or more but not more than 38 % of bivalent iron in relation to the total iron, and — 1 % or more but not more than 4 % of cobalt	0
ex 3824 90 99	12	Spent catalyst, in the form of rodlets of diameter of 1 mm or more but not exceeding 3 mm, containing a mixture of sulphides of tungsten and of nickel on a support of zeolite, containing by weight not more than 10 % of tungsten and not more than 10 % of nickel, for regeneration as a catalyst for hydrocarbon cracking ([a])	0
ex 3824 90 99	13	Mixture containing by weight: — 7 % or more but not more than 9 % of 2-methyl-1,3-phenylene diisocyanate, — 31 % or more but not more than 34 % of 4-methyl-	

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
		1,3-phenylene diisocyanate, — 10 % or more but not more than 13 % of 2,4′-methylenediphenyl diisocyanate, — 46 % or more but not more than 49 % of 4,4′-methylenediphenyl diisocyanate	0
ex 3824 90 99	14	Mixture of magnesium bromide 2-oxoperhydroazepin-1-ide and ε-caprolactam	0
ex 3824 90 99	15	Mixture of disodium *N*-benzyloxycarbonyl-L-aspartate and sodium chloride, in the form of a solution in water	0
ex 3824 90 99	16	Disodium 9,10-dihydro-9,10-dioxoanthracene-2,7-disulphonate, containing by weight 10 % or more but not more than 20 % of sodium sulphate	0
ex 3824 90 99	17	Eutectic alloy wholly of potassium and sodium, containing by weight 77 % or more but not more than 79 % of potassium	0
ex 3824 90 99	18	Blend of terephthaloyl dichloride and isophthaloyl dichloride	0
ex 3824 90 99	20	Preparation consisting by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing by weight 7 % or more of tricyclopentadiene, and: — either an aluminium-alkyl compound, — or an organic complex of tungsten, — or an organic complex of molybdenum	0
ex 3824 90 99	21	Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of methylphosphonic acid and phosphoric acid with ethane-1,2-diol	0
ex 3824 90 99	22	Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of 2-chloroethyl phosphate with ethane-1,2-diol	0
ex 3824 90 99	23	Mixture of sucrose esters, derived from the esterification of sucrose with industrial stearic acid	0
ex 3824 90 99	24	Preparations consisting predominantly of phosphabicyclononanes and *P*-alkyl derivatives thereof, in the form of a solution in 4-*tert*-butyltoluene	0
ex 3824 90 99	25	Lithium tantalate wafers, undoped	0
ex 3824 90 99	28	Preparation consisting predominantly of ethylene glycol and *N,N*-dimethylformamide or ethylene glycol and γ-butyrolactone, for the manufacture of electrolytic capacitors ([a])	0
ex 3824 90 99	29	Preparation consisting predominantly of γ-butyrolactone and quaternary ammonium salts, for the manufacture of electrolytic capacitors ([a])	0
ex 3824 90 99	30	2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated	0
ex 3824 90 99	31	Copper zinc ferrite, coated with a silicone resin, in the form of granules of a size not exceeding 120 μm	0
ex 3824 90 99	32	Styrene oligomer	0
ex 3824 90 99	33	Preparation consisting of α-(4-allyloxycarbonylbenzoyl)-ω-allyloxypoly[oxy(2-methylethylene)oxyterephthaloyl] and either diallyl-2,2′-oxydiethyl dicarbonate or diallyl isophthalate	0
ex 3824 90 99	35	Nitrosylsulphuric acid of a purity by weight of 70 % or more but not exceeding 73 %	0
ex 3824 90 99	36	Mixtures of silanol and diphosphorus pentaoxide, in the form of a solution in a mixture of ethanol and ethyl acetate, containing by weight 6 % or more but not more than 10 % of silanol and 0,1 % or more but not more than 0,3 % of diphosphorus pentaoxide	0
ex 3824 90 99	37	Sintered bauxite pellets, of a diameter not exceeding 2 mm	0
ex 3824 90 99	39	Mixture containing by weight 40 % or more but not more	

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
		than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid	0
ex 3824 90 99	40	Azelaic acid of a purity by weight of 75 % or more but not exceeding 85 %	0
ex 3824 90 99	42	Mixed metals oxides, in the form of powder, containing by weight: — either 5 % or more of barium, neodymium or magnesium and 15 % or more of titanium, — or 30 % or more of lead and 5 % or more of niobium, for use in the manufacture of dielectric films or for use as dielectric materials in the manufacture of multilayer ceramic capacitors (a)	0
ex 3824 90 99	43	7-Aminonaphthalene-1,3,6-trisulphonic acid and its salts, of a purity by weight of 65 % or more	0
ex 3824 90 99	44	Mixture containing by weight: — 60 % or more of 2-[*N*-(2-cyanoethyl)anilino]ethyl acetate, and — 20 % or more of acetic acid	0
ex 3824 90 99	45	Preparations consisting predominantly of ethylene glycol and: — either diethylene glycol, dodecandioic acid and ammonia water, — or silicon oxide, — or ammonium hydrogen azelate, — or ammonium hydrogen azelate and silicon oxide, — or dodecandioic acid, ammonia water and silicon oxide, for the manufacture of electrolytic capacitors (a)	0
ex 3824 90 99	46	Carboxylic acid anhydride based hardener for epoxyde resin, in liquid form, of a specific weight at 25 ºC of 1,15 g/cm^3 or more but not exceeding 1,18 g/cm^3	0
ex 3824 90 99	49	Mixed oxides of metals, in the form of powder, containing by weight: — 70 % or more but not more than 75 % of iron oxide, — 10 % or more but not more than 20 % of zinc oxide, — 10 % or more but not more than 15 % of magnesium oxide, — 1 % or more but not more than 5 % of manganese oxide, and — 1 % or more but not more than 3 % of copper oxide	0
ex 3824 90 99	50	Zeolites consisting of oxides of barium, aluminium and silicon, containing by weight 30 % or more but not more than 40 % of barium oxide, in the form of spheres of which 80 % or more by weight have a diameter of 0,3 mm or more but not more than 1,2 mm	0
ex 3824 90 99	53	Sodium 4-hydroxynaphthalene-1-sulphonate, of a purity by weight of 70 % or more but not exceeding 80 %	0
ex 3824 90 99	54	2-Hydroxybenzonitrile, in the form of a solution in *N,N*-dimethylformamide, containing by weight 45 % or more but not more than 50 % of 2-hydroxybenzonitrile	0
ex 3824 90 99	55	Mixture containing by weight 75 % or more of pentaerythritol triallyl ether	0
ex 3824 90 99	57	Mixture of trialkylphosphine oxides	0
ex 3824 90 99	58	Platinum oxide fixed on a porous support of aluminium oxide, containing by weight 0,1 % or more but not more than 1 % of platinum and 0,5 % or more but not more than 5 % of ethylaluminium dichloride	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3824 90 99	60	α-Phenoxycarbonyl-ω-phenoxypoly[oxy(2,6-dibromo-1,4-phenylene) isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl]	0
ex 3824 90 99	61	Mixture of metal oxides, in the form of powder, containing by weight: — 20 % or more of barium, — 10 % or more of titanium, and — 4 % or more of lead or 3 % or more of niobium or 0,7 % or more of zirconium, for use as dielectric material in the manufacture of multilayer ceramic capacitors (a)	0
ex 3824 90 99	63	Triethylborane, in the form of a solution in tetrahydrofuran	0
ex 3824 90 99	64	Aluminium sodium silicate, in the form of spheres of a diameter of: — either 1,6 mm or more but not exceeding 3,4 mm, — or 4 mm or more but not exceeding 6 mm	0
ex 3824 90 99	65	Mixture of tris(alkoxycarbonylamino)-1,3,5-triazines in which alkoxy groups are methoxy and butoxy	0
ex 3824 90 99	66	Mixture of primary *tert*-alkylamines	0
ex 3824 90 99	67	Preparation consisting of indium tin oxide dispersed in organic solvents	0
ex 3824 90 99	72	Solution containing by weight 80 % or more of 2,4,6-trimethylbenzaldehyde in acetone	0
ex 3824 90 99	73	Particles of silicon dioxide on which are covalently bonded organic compounds, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (a)	0
ex 3824 90 99	75	Mixture of 2,2-bis[2-(perfluoroalkyl)ethylthiomethyl]propane-1,3-diols	0
ex 3824 90 99	77	Diethylmethoxyborane, in the form of a solution in tetrahydrofuran	0

▼M12

ex 3824 90 99	81	Calcium oxide stabilised zirconia in the form of lumps of which 94 % or more by weight is retained on a 16 mm sieve, containing by weight: — 92 % or more of zirconium dioxide and — 2 % or more but not more than 6 % of calcium oxide	0
ex 3824 90 99 ex 3907 40 00	82 20	α-(2,4,6-Tribromophenyl)-ω-(2,4,6-tribromophenoxy)poly[oxy(2,6-dibromo-1,4-phenylene)isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl]	0

▼M11

ex 3901 10 10	10	Linear polyethylene, of a specific gravity of 0,928 or more but not exceeding 0,935 and of a melt flow index of less than 0,6 g/min, for the manufacture of shrinkmelt binder fibres (a)	0
ex 3901 10 90	10	Polyethylene for the manufacture of photo-resist film for semiconductors or printed circuits (a)	0
ex 3901 10 90	20	Polyethylene, in the form of granules, of a specific gravity of 0,925 (± 0,0015), a melt flow index of 0,3 g/10 min (± 0,05 g/10 min), for the manufacture of blown films of a Haze value not exceeding 6 % and an elongation at break (MD/TD) of 210/340 (a)	0
ex 3901 20 90	10	Polyethylene, in one of the forms mentioned in note 6(b) to Chapter 39, of a specific gravity of 0,945 or more but not exceeding 0,985, for the manufacture of films for typewriter ribbon or similar ribbon (a)	0
ex 3901 20 90	20	Polyethylene, containing by weight 35 % or more but not more than 45 % of mica	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3901 90 90	81	Copolymer of ethylene and propylene, modified with maleic anhydride, containing by weight more than 55 % of ethylene and not more than 3 % of maleic anhydride	0
ex 3901 90 90	82	Polyethylene modified with maleic anhydride, containing by weight not more than 4 % of maleic anhydride, for use in the manufacture of fuel tanks for motor vehicles (a)	0
ex 3901 90 90	91	Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid	4
ex 3901 90 90	93	Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticiser in the manufacture of roof sheets (a)	0
ex 3901 90 90	94	Mixtures of A-B block copolymer of polystyrene and ethylene-butylene copolymer and A-B-A block copolymer of polystyrene, ethylene-butylene copolymer and polystyrene, containing by weight not more than 35 % of styrene	0
ex 3901 90 90 ex 3902 90 90	95 95	Copolymer of ethylene and butylene, having hydroxyl or acrylate end-groups, containing by weight 40 % or more but not more than 60 % of butylene	0
ex 3901 90 90 ex 3902 90 90 ex 3903 90 90	96 96 50	Linear A-B block copolymer of polyisoprene, whether or not epoxidised, and either ethylene-butylene copolymer or styrene-ethylene-butylene copolymer, having hydroxyl end-groups	0

▼M12

▼M11

ex 3902 10 00	10	Polypropylene containing no plasticiser and not more than: — 7 mg/kg of aluminium, — 2 mg/kg of iron, — 1 mg/kg of magnesium, — 8 mg/kg of chloride	0
ex 3902 10 00	20	Polypropylene, containing no plasticiser, — of a melting point of more than 150 ºC (as determined by the ASTM D 3417 method), — of a heat of fusion of 15 J/g or more but not exceeding 70 J/g, — of an elongation at break of 1 000 % or more (as determined by the ASTM D 638 method), — of a tensile modulus of 69 MPa or more but not exceeding 379 MPa (as determined by the ASTM D 638 method)	0
ex 3902 10 00	30	Polypropylene, containing not more than 1 mg/kg of aluminium, 0,05 mg/kg of iron, 1 mg/kg of magnesium and 1 mg/kg of chloride, for use in the manufacture of packaging for disposable contact lenses (a)	0
ex 3902 30 00 ex 3903 90 90	91 25	A-B Block copolymer of polystyrene and an ethylene-propylene copolymer, containing by weight 40 % or less of styrene, in one of the forms mentioned in note 6(b) to Chapter 39	0
ex 3902 30 00	92	Copolymer of propylene, butylene and ethylene, containing by weight more than 65 % but less than 80 % of propylene and not less than 20 % of butylene	0
ex 3902 90 90	92	Polymers of 4-methylpent-1-ene	0
ex 3902 90 90	97	Hydrogenated polyisobutene, in liquid form	0
ex 3903 19 00	20	Polystyrene of a molecular weight (M_w)not exceeding	0
ex 3903 90 90	10	Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, whether or not containing a styrene-butadiene block copolymer, in one of the forms mentioned in note 6(b) to Chapter 39, for the manufacture of sheetings for head-liners for cars (a)	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3903 90 90	15	Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, also partially esterified, of an average molecular weight (M_w)not exceeding 3 000, in one of the forms mentioned in note 6(a) and (b) to Chapter 39	0
ex 3903 90 90	20	Copolymer of styrene with 2-ethylhexyl acrylate or with *n*-butyl acrylate, containing: — 10 mole % or more but not more than 16 mole % of acrylate, — 0,2 mg/kg or less of sodium, and — 0,1 mg/kg or less of calcium	0
ex 3903 90 90 ex 3911 90 99	35 30	Copolymer of *α*-methylstyrene and styrene, having a softening point exceeding 113 ºC	0
ex 3903 90 90 ex 3906 90 90 ex 3911 90 99	40 40 50	Copolymer of styrene with *α*-methylstyrene and acrylic acid, of a molecular weight (M_w)of 500 or more but not exceeding 6 000	0
ex 3903 90 90 ex 3906 90 90	55 45	Copolymer of styrene, methyl methacrylate, butyl acrylate and either acrylic acid or hydroxyethyl methacrylate, of a molecular weight (M_w)of 500 or more but not exceeding 6 000	0
ex 3903 90 90	65	Copolymer of styrene, butyl acrylate, butyl methacrylate, methyl methacrylate and acrylic acid, in the form of powder, containing by weight (81 ± 1) % of styrene, (6 ± 1) % of butyl acrylate, (5 ± 1) % of butyl methacrylate, (7 ± 1) % of methyl methacrylate and (1 ± 0,5) % of acrylic acid	0
ex 3903 90 90	70	Ammonium polystyrenesulphonate, in the form of an aqueous solution	0
ex 3904 22 00 ex 3926 90 99	91 80	Polyvinyl chloride, dyed in the mass, in the form of flakes, grains, pebbles or rectangular chips, for use as decorative elements in floor and wall coverings (a)	0
ex 3904 30 00	10	Copolymer of vinyl chloride with vinyl acetate and maleic acid, containing by weight: — 81,5 % or more but not more than 84,5 % of vinyl chloride, — 13,8 % or more but not more than 16,2 % of vinyl acetate, and — 0,8 % or more but not more than 1,2 % of maleic acid, for the manufacture of goods of heading No 3215 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a)	0
ex 3904 30 00	20	Copolymer of vinyl chloride, vinyl acetate and maleic acid, for use in the manufacture of polyvinyl chloride-metal heat-sealing adhesive (a)	0
ex 3904 40 00	91	Copolymer of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight: — 87 % or more but not more than 92 % of vinyl chloride, — 2 % or more but not more than 9 % of vinyl acetate and — 1 % or more but not more than 8 % of vinyl alcohol, in one of the forms mentioned in note 6(a) or (b) to Chapter 39, for the manufacture of goods of heading No 3215 or 8523 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a)	0
ex 3904 40 00	92	Copolymer of vinyl chloride, vinyl acetate, hydroxypropyl acrylate and maleic acid, containing by weight 80 % or more but not more than 83 % of vinyl chloride, 1,6 % or	

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
		more but not more than 2 % of hydroxy groups and 0,25 % or more but not more than 0,38 % of carboxyl groups	0
ex 3904 40 00	93	Copolymer of vinyl chloride and methyl acrylate, containing by weight (80 ± 1) % of vinyl chloride and (20 ± 1) % of methyl acrylate, in the form of a aqueous emulsion	0
ex 3904 50 90	91	Copolymer of vinylidene chloride with vinyl chloride, containing by weight 79,5 % or more of vinylidene chloride, in one of the forms mentioned in note 6(a) or (b) to Chapter 39, for the manufacture of fibres, monofilament or strip (a)	0
ex 3904 61 00	10	Mixture of polytetrafluoroethylene and mica, in one of the forms mentioned in note 6(b) to Chapter 39	0
ex 3904 61 00	20	Copolymer of tetrafluoroethylene and trifluoro(heptafluoropropoxy)ethylene, containing 3,2 % or more but not more than 4,6 % by weight of trifluoro(heptafluoropropoxy)ethylene and less than 1 mg/kg of extractable fluoride ions	0
ex 3904 69 90	92	Copolymer of tetrafluoroethylene and trifluoro(trifluoromethoxy)ethylene	0
ex 3904 69 90	93	Copolymer of ethylene with chlorotrifluoroethylene, in one of the forms mentioned in note 6(b) to Chapter 39	0
ex 3904 69 90	94	Copolymer of ethylene and tetrafluoroethylene	0
ex 3904 69 90	96	Polychlorotrifluoroethylene, in one of the forms mentioned in note 6(a) and (b) to Chapter 39	0
▼M12			
ex 3905 29 00	91	Copolymer of vinyl acetate, dibutyl maleate and acrylic acid, in the form of a solution in isopropyl acetate and toluene	0
▼M11			
ex 3905 91 00	91	Copolymer of *N*-vinylcaprolactam, *N*-vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate	0
ex 3905 99 90	93	Polyvinyl acetate phthalate	0
ex 3905 99 90	94	Polymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, containing by weight 97 % or more but not more than 99 % of vinylpyrrolidone, in the form of a solution in water	0
ex 3905 99 90	95	Hexadecylated or eicosylated polyvinylpyrrolidone	0
ex 3905 99 90	96	Polymer of vinyl formal, in one of the forms mentioned in note 6(b) to Chapter 39, of a molecular weight (M_w) of 25 000 or more but not exceeding 150 000 and containing by weight: — 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl acetate, and — 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol	0
ex 3906 10 00	10	Polymethyl methacrylate, in the form of expansible beads containing 2-methylpentane as blowing agent	0
3906 90 60		Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide	0
ex 3906 90 90	10	Polymerisation product of acrylic acid with small quantities of a polyunsaturated monomer, for the manufacture of medicaments of heading No 3003 or 3004 (a)	0
ex 3906 90 90	20	Polymerisation product of acrylic acid with small quantities of a polyunsaturated monomer, for use as a stabiliser in emulsions or dispersions with a pH of more than 13 (a)	6

▼M11

	CN code	TARIC	Description	Rate of autonomous duty (%)
	ex 3906 90 90	30	Copolymer of styrene with hydroxyethyl methacrylate and 2-ethylhexyl acrylate, of a molecular weight (M_w)of 500 or more but not exceeding	0
▼M12				
	ex 3906 90 90	50	Polymers of esters of acrylic acid with one or more of the following monomers in the chain: — chloromethyl vinyl ether, — chloroethyl vinyl ether, — chloromethylstyrene, — vinyl chloroacetate, — methacrylic acid, containing by weight not more than 5 % of each of the monomeric units	0
▼M11				
	ex 3906 90 90	60	Copolymer of butyl acrylate and vinyl chloride, containing by weight (58 ± 1) % of butyl acrylate and (42 ± 1) % of vinyl chloride, in the form of a aqueous emulsion	0
▼M12				
	ex 3906 90 90	70	Copolymer of ethylene dimethacrylate with either methyl methacrylate or dodecyl methacrylate	0
	ex 3906 90 90	80	Polydimethylsiloxane-graft-(polyacrylates; polymethacrylates)	0
▼M11				
	ex 3907 20 11	10	Polyethylene oxide of an average molecular weight (M_w)of 100 000 or more	0
	ex 3907 20 29	10	Polymer of dextrose, sorbitol and citric or phosphoric acid, containing by weight 90 % or more of dextrose monomer units	0
	ex 3907 20 29	20	Poly[oxy-1,4-phenyleneisopropylidene-1,4-phenyleneoxy-(2-hydroxytrimethylene)], of an average molecular weight (M_w) of more than 26 000, in one of the forms mentioned in note 6(b) to Chapter 39	0
	ex 3907 20 99	10	Bis{2-[ω-hydroxy-poly(ethyleneoxy)]ethyl} hydroxymethylphosphonate	0
	ex 3907 20 99	15	Polyoxypropylene having alkoxysilyl end-groups	0
	ex 3907 20 99	25	α-4-Hydroxybutyl-ω-hydroxypoly(oxytetramethylene), containing less than 1 mg/kg of halogen and less than 1 mg/kg of metal, and of a colour not exceeding 20 units on the Hazen scale	0
	ex 3907 20 99	30	Homopolymer of 1-chloro-2,3-epoxypropane (epichlorohydrin)	0
	ex 3907 30 00	20	Epoxyde resin in the form of powder, containing by weight 44 % or more but not more than 55 % of quartz and 0,5 % or more but not more than 1 % of diantimony trioxide, for the coating of film capacitors (a)	0
	ex 3907 30 00	30	Epoxyde resin, without solvent, containing mineral fillers (silica), without glass fibre, of a specific weight at 25 ºC of 1,55 g/cm^3 or more but not exceeding 1,60 g/cm^3	0
	ex 3907 30 00 ex 3926 90 99	40 70	Epoxide resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of heading No 8533, 8535, 8536, 8541, 8542 or 8548 (a)	0
	ex 3907 40 00	10	Copolymer of hexane-1,6-diol, cyclohexane-1,4-dimethanol and ethylene carbonate	0
▼M12				
	ex 3907 60 80	10	Copolymer of terephthalic acid and isophthalic acid with ethylene glycol, butane-1,4-diol and hexane-1,6-diol	0
	ex 3907 60 80	20	Oxygen binding copolymer (as determined by the ASTM D 1434 and 3985 methods), obtained from benzenedicar-	

▼M12

	CN code	TARIC	Description	Rate of autonomous duty (%)
			boxylic acids, ethylene glycol and polybutadiene substituted by hydroxy groups	0
▼M11				
	ex 3907 91 90	10	Diallyl phthalate prepolymer, in the form of powder	0
	ex 3907 99 19 ex 3907 99 99	10 10	Poly(oxy-1,4-phenylenecarbonyl), in the form of powder	0
	ex 3907 99 19	20	Liquid crystal copolyester with a melting point of not less than 270 ºC, whether or not containing fillers	0
	ex 3908 90 00	10	Poly(iminomethylene-1,3-phenylenemethyleneiminoadipoyl), in one of the forms mentioned in note 6(b) to Chapter 39	0
	ex 3908 90 00	20	Copolymer consisting of hexamethylenediamine, isophthalic acid and terephthalic acid, in one of the forms mentioned in note 6(b) to Chapter 39	0
	ex 3909 40 00	10	Polycondensation product of phenol with formaldehyde, in the form of hollow spheres of a diameter of less than 150 μm	0
	ex 3910 00 00	10	3-[(2-Aminoethyl)amino]propyl(methyl)cyclosiloxane	0
	ex 3910 00 00	20	Block copolymer of poly(methyl-3,3,3-trifluoropropylsiloxane) and poly[methyl(vinyl)siloxane]	0
	ex 3911 90 19	10	Poly(oxy-1,4-phenylenesulphonyl-1,4-phenyleneoxy-4,4′-biphenylene)	0
▼M12				
▼M11				
	ex 3911 90 99	20	Copolymer of dibutyl maleate and *N*-vinyl-2-pyrrolidone, in one of the forms mentioned in note 6(a) of Chapter 39	0
	ex 3911 90 99	25	Copolymer of vinyltoluene and *α*-methylstyrene	0
	ex 3911 90 99	40	Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not more than 16 % by weight	0
	ex 3911 90 99	45	Copolymer of maleic acid and methyl vinyl ether	0
	ex 3911 90 99	55	Solution containing: — (36 ± 0,5) % by weight of polyamide with lateral ester groups, — (2 ± 0,5) % by weight of acrylic ester, — (48 ± 0,5) % by weight of 1-methyl-2-pyrrolidone, — (12 ± 0,5) % by weight of bis(2-methoxyethyl) ether, — 500 μg/kg or less of potassium, and — 500 μg/kg or less of iron, for use in the manufacture of goods of heading No 8542 (a)	0
▼M12				
	ex 3911 90 99	60	Hydrocarbon prepolymer, obtained by the reaction of cyclopentadiene and 1,3-pentadiene	0
▼M11				
	ex 3912 11 00	10	Non-plasticised cellulose triacetate, in the form of flakes, for the manufacture of cellulose triacetate yarn (a)	0
	ex 3912 39 10	10	Ethylcellulose, not plasticised	0
	ex 3912 39 10	20	Ethylcellulose, in the form of aqueous dispersion containing hexadecan-1-ol and sodium dodecyl sulphate, containing by weight (27 ± 3) % of ethylcellulose	0
	ex 3912 39 80	10	Cellulose, both hydroxyethylated and ethylated, insoluble in water	0
	ex 3912 39 80	20	Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3912 90 10	10	Cellulose acetate propionate, non-plasticised, in the form of powder: — containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method), and — of a viscosity not exceeding 120 poise (as determined by the ASTM D 817-72 method), for the manufacture of printing inks, paints, lacquers and other coatings, and reprographic coatings (a)	0
ex 3913 90 80	30	Chondroitinsulphuric acid, sodium salt	0
ex 3913 90 80	40	Chitosonium pyrrolidonecarboxylate	0
ex 3915 90 93	30	Waste, parings and scrap of photographic, cinematographic and radiographic films	0
ex 3917 32 10	10	Flexible pipe of silicone foam, with continuous channels, of a Shore A hardness of 7 or more but not exceeding 48 and a density of 0,28 g/cm^3 or more but not exceeding 0,92 g/cm^3	0
▼M12			
ex 3917 32 31 ex 3917 32 99 ex 3926 90 99	91 10 45	Assembly of heat-shrinkable tubing of polyethylene with poly(vinyl acetate), arranged in parallel at equally spaced intervals and attached at one or both ends by perforated plastic strips, in rolls	0
▼M11			
ex 3917 32 39	20	Pipe consisting of a block copolymer of polytetrafluoroethylene and polyperfluoroalkoxytrifluoroethylene, of a length of not more than 600 mm, a diameter of not more than 85 mm and a wall-thickness of 30 μm or more but not exceeding 110 μm	0
ex 3919 10 31 ex 3919 10 38 ex 3919 90 31	10 30 50	Reflecting laminated sheet, consisting of a film of polycarbonate totally embossed on one side in a regular shaped pattern, covered on both sides with one or more layers of plastic material and on one side with an adhesive layer and a release sheet	0
ex 3919 10 38	10	Self-adhesive tape of metallised polyurethane containing glass beads for use in the manufacture of marine life-saving equipment (a)	0
ex 3919 10 38 ex 3919 90 38 ex 3920 99 28	20 10 20	Reflecting film, consisting of a layer of polyurethane with security imprints and embedded glass beads on one side and an adhesive layer on the other side, covered on one side or on both sides with a release film	0
ex 3919 10 61 ex 3919 90 61	91 94	Reflecting film, consisting of a layer of polyvinyl chloride, a layer of alkyd polyester, with security imprints and embedded glass beads on one side and an adhesive layer on the other side, covered on one side or on both sides with a release film	0
ex 3919 90 10	10	Shaped sheet of plastic, with an adhesive layer containing polyisobutylene and pectin, for the manufacture of colostomy bags (a)	0
ex 3919 90 10	20	Polyethylene terephthalate film, covered on one side with an anti-static layer and a hardcoat layer and on the other side with an adhesive layer and a release sheet, in the form of sheets of dimensions not exceeding 450 × 750 mm	0
ex 3919 90 31 ex 3920 62 19 ex 3920 62 90 ex 3920 63 00 ex 3920 69 00	40 20 20 30 30	Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers (a)	0
ex 3919 90 61 ex 3919 90 69	92 92	Polyvinyl chloride sheeting, of a thickness of less than 1 mm, coated with an adhesive in which are embedded glass balls of a diameter not exceeding 100 μm	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3919 90 61 ex 3919 90 69 ex 3920 10 89	93 93 25	Adhesive film consisting of a base of a copolymer of ethylene and vinyl acetate (EVA) of a thickness of 120 µm or more and an adhesive part of acrylic type of a thickness of 10 µm or more, for the protection of the surface of silicon discs (a)	0
ex 3919 90 69	94	Reflecting laminated sheet, consisting of a film of polymethyl methacrylate embossed on one side in a regular pyramidal or other shaped pattern, a film of a polymer of methyl methacrylate containing glass microprisms or microspheres, an adhesive layer and a release sheet	0
ex 3920 10 26	20	Film of polyethylene, of a thickness of 20 µm or more but not exceeding 45 µm, containing calcium carbonate in the mass, for the manufacture of napkins for babies or of sanitary towels or of tampons or of disposable surgical gowns (a)	0
ex 3920 10 26 ex 3920 10 89	30 20	Film of a thickness not exceeding 0,20 mm, of a blend of polyethylene and a copolymer of ethylene with oct-1-ene, embossed in a regular rhomboidal pattern, for coating both sides of a layer of unvulcanised rubber (a)	0
ex 3920 10 28 ex 3920 10 89	92 30	Polyethylene sheet, of a thickness of 0,025 mm or more but not exceeding 3 mm, of an elongation at break of 100 % or more but not exceeding 1 100 % (as determined by the ASTM D 638 and 882 methods), in rolls of a width of 4,57 m, 4,9 m, 7,01 m or 9,3 m	0
ex 3920 10 40	91	Synthetic paper pulp, in the form of moist sheets, made from unconnected finely-branched polyethylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing poly(vinyl alcohol) dissolved in water as the moistening agent	0
ex 3920 10 40	92	Laminated sheet or strip consisting of a film composed of a blend of a copolymer of ethylene with vinyl acetate and a modified ethylene-propylene-elastomer (EPM) or a modified ethylene-propylene-diene elastomer (EPDM), coated or covered on both sides with a film of a copolymer of ethylene with vinyl acetate	0
ex 3920 10 89	35	Reflecting film, consisting of a layer of polyethylene, a layer of polyurethane, with security imprints and embedded glass beads on one side and a hot-melt adhesive layer on the other side, covered on one side or on both sides with a release film	0
ex 3920 20 29	91	Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, having: — a thickness of 55 µm or more but not exceeding 97 µm, — a tensile modulus in the machine direction of 0,75 GPa or more but not exceeding 1,45 Gpa, and — a tensile modulus in the transverse direction of 0,20 GPa or more but not exceeding 0,55 GPa	0
ex 3920 20 90	91	Synthetic paper pulp, in the form of moist sheets, made from unconnected finely-branched polypropylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing polyvinyl alcohol dissolved in water as the moistening agent	0
ex 3920 20 90	92	Laminated sheet or strip, consisting of a film of a thickness of 181 µm or more but not exceeding 223 µm composed of a blend of a copolymer of propylene with ethylene and a copolymer of styrene-ethylene-butylene-styrene (SEBS) coated or covered on one side with a layer of a copolymer of styrene-ethylene-butylene-styrene (SEBS) and a layer of polyester	0
ex 3920 20 90	93	Polypropylene sheet, of a thickness of 0,5 mm or more but not exceeding 1,0 mm, having a tensile strength at break of 14,7 MPa or more but not exceeding 21 MPa (as determined by the ASTM D 638 method), in rolls of a width of 3,81 m	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3920 30 00	20	Laminated sheet or strip, consisting of a film composed of a blend of a thermoplastic elastomer (TPE) of styrene-butadiene-styrene (SBS) with polyethylene or polypropylene, of a thickness of 100 µm or more but not exceeding 200 µm, coated or covered on both sides with a film of polypropylene of a thickness not exceeding 20 µm	0
ex 3920 43 10 ex 3920 49 10	91 91	Reflecting sheeting, consisting solely of a single layer of polyvinyl chloride, wholly embossed on one side in a regular pyramidal pattern	0
ex 3920 43 10	92	Sheeting of polyvinyl chloride, stabilised against ultra-violet rays, without any holes, even microscopic, of a thickness of 60 µm or more but not exceeding 80 µm, containing 30 or more but not more than 40 parts of plasticiser to 100 parts of polyvinyl chloride	0
ex 3920 43 10	93	Polyvinyl chloride sheet, with relief printing, of a kind used in the templates for textile printing	0
ex 3920 43 10 ex 3920 49 10	94 93	Film of a gloss level of 70 or more, measured at 60 º using a gloss meter (as determined by the ISO 2813:2000 method), consisting of one or two layers of polyvinyl chloride coated on both sides with a layer of plastic, of a thickness of 0,26 mm or more but not exceeding 1,0 mm, covered on the gloss surface with a protective film of polyethylene, in rolls of a width of 1 000 mm or more but not exceeding 1 450 mm, for use in the manufacture of goods of heading No 9403 (a)	0
ex 3920 43 10 ex 3920 49 10	95 92	Reflecting laminated sheet, consisting of a film of polyvinyl chloride and a film of an other plastic totally embossed in a regular pyramidal pattern, covered on one side with a release sheet	0
ex 3920 51 00	10	Polymethyl methacrylate plate, with an anti-static coating, of dimensions of 738 × 972 mm (± 1,5 mm)	0
ex 3920 51 00	20	Plate of polymethyl methacrylate containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not exceeding 19 mm	0
ex 3920 61 00	10	Polycarbonate film of a thickness not exceeding 15 µm, for the manufacture of film capacitors (a)1	0
ex 3920 62 19	05	Coextruded opaque sheet of polyethylene terephthalate, of a thickness of 50 µm or more but not exceeding 350 µm, consisting especially of a layer containing carbon black	0
ex 3920 62 19	10	Polyethylene terephthalate film, of a thickness of less than 11 µm, for the manufacture of audiodigital tapes for cassettes	0
ex 3920 62 19	15	Polyethylene terephtalate film, not coated with an adhesive, of a thickness not exceeding 25 µm, either: — only dyed in the mass, or — dyed in the mass and metallised on one side	0
ex 3920 62 19	25	Film of polyethylene terephthalate only, of a total thickness not exceeding 120 µm, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0
ex 3920 62 19	30	Polyethylene terephthalate film, of a thickness of 20 µm or more but not exceeding 30 µm, coated on one side with silicone, for use in the manufacture of window film (a)	5,6
ex 3920 62 19	35	Laminated film of polyethylene terephthalate only, of a total thickness not exceeding 120 µm, consisting of one layer which is metallised only and one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0
ex 3920 62 19	40	Film of polyethylene terephthalate, coated or covered on one side or on both sides with a layer of modified polyester, of a total thickness of 7 µm or more but not	

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
		exceeding 11 μm, for the manufacture of video tapes with a magnetic layer of metallic pigments and a width of 8 mm or of 12,7 mm (a)	0
ex 3920 62 19	45	Single ply film of polyethylene terephthalate only, of a thickness not exceeding 120 μm, which only: — contains a colouring and/or UV-absorbing material throughout the mass, and — is metallised on one side, whether or not coated on one or both sides with a vinyl acrylate polymer but having no other coating or adhesive	0
ex 3920 62 19	50	Film of polyethylene terephthalate, of a total thickness not exceeding 120 μm, of a width of 100 mm or more but not exceeding 115 mm, coated on both sides with one or more layers containing different chemicals, for the manufacture of goods of subheading 3701 20 00 (a)	0
ex 3920 62 19	55	Film of polyethylene terephthalate, on one side metallised and coated with white ink and a protective layer and on the other side coated with a thermosensitive seal layer, of a width of 100 mm or more but not exceeding 150 mm, for the manufacture of goods of subheading 3701 20 00 (a)	0
ex 3920 62 19	60	Film of polyethylene terephthalate, coated on one side with a layer of modified polyester, of a thickness of 20 μm (± 0,7 μm) or of 30 μm (± 0,9 μm), for the manufacture of audio magnetic tapes of a total thickness of 33 μm or more (a)	0
ex 3920 62 19	62	Polyethylene terephthalate film, of a thickness not exceeding 12 μm, coated on one side with a layer of aluminium oxide of a thickness not exceeding 35 nm	0
ex 3920 62 19	64	Polyethylene terephthalate film, of a thickness of 18 μm or more but not exceeding 25 μm, having: — a shrinkage of (3,4 ± 0,1) % in the machine direction (as determined by the ASTM D 1204 method), and — a shrinkage of (0,3 ± 0,2) % in the transverse direction (as determined by the ASTM D 1204 method)	0
ex 3920 62 19	65	Polyethylene terephthalate film, of a thickness not exceeding 19 μm or of a weight of 20 g/m^2 or more but not exceeding 26,7 g/m^2, for use in the manufacture of photo-resist film (a)	0
ex 3920 62 19	70	Film of polyethylene terephthalate, coated on both sides with a layer of epoxy acrylic resin, of a total thickness of 37 μm (± 3 μm)	0
ex 3920 62 19	75	Film of polyethylene terephthalate, coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness not exceeding 300 μm and having a surface resistivity not exceeding 10 000 ohms (per square) (as determined by the ASTM D 257-93 method)	0
ex 3920 62 19	80	Mat film of polyethylene terephthalate, of a gloss of 15 at an angle of 45 º and 18 at an angle of 60 º (as determined by the ASTM D 523 method) and a width of 1 600 mm or more	0
ex 3920 62 19	81	Film of white polyethylene terephthalate, dyed in the mass, of a thickness of 185 μm or more but not exceeding 253 μm, coated on both sides with an antistatic layer	0
ex 3920 62 19	85	Film of a total thickness of 4,5 μm (± 0,16 μm), consisting of a biaxially-oriented polyethylene terephthalate film, of an elastic modulus (in the machine direction) of 12 kg/mm^2 (± 2 kg/mm^2) and a tensile strength (in the machine direction) of more than 28 kg/mm^2, and of an anti-adherent coating	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3920 62 19	87	Polyethylene terephthalate film, coated with a wax layer, a scratch-resistant layer and a thermoadhesive layer, of a nominal width of 790 mm and a total thickness of 23 µm or more but not exceeding 26 µm	0
ex 3920 62 19	88	Laminated sheet, consisting of a biaxially oriented film of polyethylene terephthalate, covered on one side or on both sides with a layer of polyethylene terephthalate, for use in the manufacture of identity cards, credit cards and similar products (including 'smart' cards) (a)	0
ex 3920 62 19	89	Multilayer film of a thickness not exceeding 150 µm, consisting of a polyester film coated on one side with polycarbonate resin, metallised on the other side with titanium coated with polycarbonate resin and other layers containing *N,N′*-diphenyl-*N,N′*-di-*m*-tolylbiphenyl-4,4′-ylenediamine	0
ex 3920 62 90	30	Film of polyethylene terephthalate, of a thickness of 500 µm (± 25 µm)	0
ex 3920 62 90	40	Strips of polyethylene terephthalate, covered on both sides with a layer of chemically modified polyester, of a width not exceeding 16 mm and a thickness of 0,5 mm or more but not exceeding 2 mm, having a tensile strength at break of 0,7 GPa or more (as determined by the ASTM D 638 method)	0
ex 3920 69 00	20	Film of polyethylene naphthalene-2, 6-dicarboxylate, of a thickness of 0,6 µm or more but not exceeding 10 µm or 82 µm or more but not exceeding 88 µm	0
ex 3920 69 00	40	Iridescent film of polyester and polymethyl methacrylate	0
ex 3920 69 00	50	Polycondensation product of terephthalic acid with a mixture of cyclohex-1,4-ylenedimethanol and ethane-1,2-diol, in the form of a film	0
ex 3920 69 00	60	Film of a copolymer of ethylene terephthalate and ethylene isophthalate, of a thickness not exceeding 2 µm	0
ex 3920 91 00	91	Polyvinyl butyral film having a graduated coloured band	6
ex 3920 91 00	93	Film of polyethylene terephthalate, metallised on one or both sides, or laminated film of polyethylene terephthalate films, metallised on the external sides only, and having the following characteristics: — a visible light transmission of 50 % or more, — coated on both sides with a layer of polyvinyl butyral but not coated with an adhesive or any other material except polyvinyl butyral, — a total thickness not exceeding 0,2 mm without taking the presence of polyvinyl butyral into account, for use in the manufacture of heat-reflecting laminated glass (a)	0
ex 3920 99 28	10	Reflecting sheet of metallised polyurethane, containing glass beads, coated with a hot-melt adhesive layer, covered on one or both sides with a release sheet, in rolls of a width of 1 020 mm (± 20 mm), for slitting into safety clothing reflecting strip (a)	0
ex 3920 99 28 ex 3921 90 55 ex 7410 21 00	30 10 30	Film of polyimide, not containing epoxyde resin and/or glass fibres: — metallised by sputtering with copper on one side or on both sides, — metallised by sputtering with copper and plated on one side or on both sides with refined copper, or — covered on one side or on both sides with a copper foil	0
3920 99 53 ex 3920 99 59	55	Ion-exchange membranes of fluorinated plastic material	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3920 99 59	20	Film entirely of polyvinyl alcohol, of a thickness not exceeding 1 mm and containing by weight: — 2 % or less of unhydrolysed acetate groups evaluated as vinyl acetate, and — 5 % or more but not more than 25 % of glycerol as plasticiser, for the manufacture of roof windows (a)	0
ex 3920 99 59	25	Poly(1-chlorotrifluoroethylene) film	0
ex 3920 99 59	30	Film and sheet of a copolymer of ethylene with chlorotrifluoroethylene, of a thickness of 12 μm or more but not exceeding 400 μm	0
ex 3920 99 59	35	Film entirely of polyvinyl alcohol, of a thickness not exceeding 1 mm and of a width of 2,20 m or more, with an extension at break, in the transverse direction, of 350 % or more	0
ex 3920 99 59	40	Biaxially-oriented film of polyvinyl alcohol, coated on both sides, of a total thickness of less than 1 mm	0
ex 3920 99 59	45	Iridescent film of polyester, polyethylene and an ethylene-vinyl acetate copolymer	0
ex 3920 99 59	50	Polytetrafluoroethylene film, non-microporous, in the form of rolls, of a thickness of 0,019 mm or more but not exceeding 0,14 mm, impermeable to water vapour	0
▼M12			
ex 3921 14 00	10	Cellular film of regenerated cellulose, of a thickness not exceeding 350 μm	0
▼M11			
ex 3921 19 00	91	Microporous polypropylene film of a thickness not exceeding 100 μm	0
ex 3921 19 00	92	Microporous film consisting of mixtures of cellulose acetate and cellulose nitrate, of a thickness not exceeding 200 μm	0
ex 3921 19 00	93	Strip of microporous polytetrafluoroethylene on a support of a non-woven, for use in the manufacture of filters for kidney dialysis equipment (a)	0
ex 3921 90 19	35	Composite plate of polycarbonate and polybutylene terephthalate, reinforced with glass fibres	0
ex 3921 90 19	45	Composite plate of polyethylene terephthalate or of polybutylene terephthalate, reinforced with glass fibres	0
ex 3921 90 60 ex 5407 71 00 ex 5903 90 99	91 20 10	Woven polytetrafluoroethylene fabric, coated or covered with a copolymer of tetrafluoroethylene and trifluoroethylene having perfluorinated alkoxy side-chains ending in carboxylic acid or sulphonic acid groups, whether or not in the potassium or sodium salt form	0
ex 3921 90 60	92	Reinforced polypropylene sheet, of a thickness of 0,91 mm or more but not exceeding 1,12 mm, having a breaking strength of 890 N or more but not exceeding 1 500 N (as determined by the ASTM D 751 method), in rolls of a width of 3,81 m	0
ex 3926 90 91	20	Reflecting sheeting or tape, consisting of a facing-strip of polyvinyl chloride embossed in a regular pyramidal pattern, heat sealed in parallel lines or in a grid pattern to a backing strip of plastic material, or of knitted or woven fabric covered on one side with plastic material	0
ex 3926 90 99	10	Microspheres of polymer of divinylbenzene, of a diameter of 4,5 μm or more but not exceeding 80 μm	0
ex 3926 90 99	20	Tape pad, for use in the manufacture of goods of heading No 8523 (a)	0
ex 3926 90 99	30	Guide pin and pole, for use in the manufacture of goods of subheadings 8523 11 00, 8523 12 00 and 8523 13 00 (a)	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3926 90 99	35	Microspheres of polyalkylsiloxane, on which are covalently bonded organic compounds, of a diameter of 1 µm or more but not exceeding 30 µm	0
▼M12			
ex 3926 90 99	55	Flat product of polyethylene, perforated in opposing directions, of a thickness of 600 µm or more but not exceeding 1 200 µm and of a weight of 21 g/m² or more but not exceeding 42 g/m²	0
▼M11			
ex 4007 00 00	10	Siliconated vulcanised rubber thread and cord	0
▼M12			
ex 4007 00 00	20	Extruded natural rubber thread, free from nitrosamine, for use in the food industry (a)	0
ex 4007 00 00	30	Extruded natural rubber thread, coated with silicone and talc	0
▼M11			
ex 4008 11 00	10	Blocks or sheets of cellular vulcanised rubber of modified ethylene-propylene-diene (EPDM) blended with chloroprene, which satisfy the Underwriters Laboratories Flammability Standard UL94HF-1	0
ex 4016 99 88	10	Soft rubber sealing stoppers for the manufacture of electrolytic capacitors (a)	0
4105 10 10 4105 10 90 4105 30 91 4105 30 99		Sheep or lamb skin leather, without wool on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4114	0
4106 21 10 4106 21 90 4106 22 90		Goat or kid skin leather, without hair on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4114	0
4106 31 10 4106 31 90 4106 32 10 4106 32 90 4106 40 90 4106 91 00 4106 92 00		Leather of other animals, without hair on, not further prepared than tanned, other than leather of heading No 4114	0
ex 4802 54 90 ex 4802 55 00 ex 4802 57 00 ex 4802 61 90 ex 4802 69 90	10 10 10 10 10	Overlay paper, of a width of more than 110 cm and containing by weight more than 5 % of corundum	0
▼M12			
ex 4803 00 90 ex 5603 13 90 ex 5603 93 90	10 80 30	Polyethylene non-woven, covered on both sides with a non-woven of polypropylene and wood pulp, containing by weight 45 % or more but not more than 56 % of wood pulp, of a weight of 70 g/m² or more but not exceeding 90 g/m², in rolls, for use in the manufacture of wet wipes (a)	0
▼M11			
ex 4805 91 99	20	Paper, in cross-wise rewound spiral rolls, of a weight of less than 150 g/m² and of a thickness not exceeding 0,05 mm, for the manufacture of electrolytic capacitors (a)	0
ex 4810 99 10	10	Bleached paper coated with kaolin, for use in the manufacture of tampon applicators (a)	0
ex 4811 41 10	10	Impregnated paper coated or covered with a pressure-sensitive self-adhesive layer, the whole: — of a tensile of 2 700 N/m or more but not exceeding 3 700 N/m in the machine direction (as determined by the EN ISO 1924-2 and ISO 3781 methods), — of a stretch factor of 1,5 % or more but not exceeding 3,0 % in the machine direction (as determined by the EN ISO 1924-2 and ISO 3781 methods)	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 4811 51 00	10	Paper coated with acrylic polymer, with a gloss of 75 or more but not exceeding 90 (as determined by the Hunter method), of a weight of 160 g/m^2 or more but not exceeding 180 g/m^2, for use as casting paper in the manufacture of films of plastics (a)	0
ex 4811 59 00	10	Kraft paper impregnated with an acrylic polymer, of a weight of 83 g/m^2 or more but not exceeding 87 g/m^2 or 176 g/m^2 or more but not exceeding 216 g/m^2	0
ex 4823 90 50	10	Paper coated with dye-retention and dye-releasing agents used to produce a positive image, for the manufacture of goods of subheading 3701 20 00 (a)	0
ex 4823 90 50	20	Honeycomb filter, of paper impregnated with carbon, of a thickness greater than 10 mm but not exceeding 30 mm	0
ex 4823 90 90	12	Strips of paper glued to one another to form a honeycomb of a height not exceeding 13 cm, for agricultural purposes (a)	0
ex 4911 99 00	10	Polyester film, partially coated with a magnetic metal layer showing a regular repeating logo or motif, for the manufacture of security threads (a)	0
ex 5004 00 10	10	Yarn spun entirely from silk, not put up for retail sale	
ex 5004 00 90	10		2,5
ex 5005 00 10	10	Yarn spun entirely from silk waste (noil), not put up for retail sale	
ex 5005 00 90	10		0
5208 11 10		Fabrics for the manufacture of bandages, dressings and medical gauzes	5,2
ex 5402 41 00	10	Polyamide yarn, not textured, untwisted or with a twist not exceeding 22 turns per metre, of crimpable bicomponent filaments consisting of polyhexamethylene adipamide with a copolyamide, for the manufacture of: — knee-length stockings of subheadings 6115 20 11 and 6115 93 30, — women's stockings of subheadings 6115 20 19 and 6115 93 91, or — pantyhose (tights) of subheading 6115 11 00 (a)	0
ex 5402 41 00	20	Yarn of synthetic textile fibres solely of aromatic polyamides obtained by the polycondensation of *m*-phenylenediamine and isophthalic acid	0
ex 5402 43 00	20	Synthetic bicomponent filament yarn, not textured, untwisted, measuring 1 650 decitex, consisting of 110 filaments each having a core of polyethylene terephthalate and a skin of polyamide-6, containing by weight 75 % or more but not exceeding 77 % of polyethylene terephthalate, for use in the manufacture of roofings (a)	0
ex 5402 49 99	10	Multifilaments yarn of polytetrafluoroethylene	
ex 5402 69 90	20		0
ex 5402 49 99	30	Yarn of a copolymer of glycollic acid with lactic acid, for the manufacture of surgical sutures (a)	0
ex 5402 49 99	50	Non-textured filament yarn of polyvinyl alcohol	
ex 5402 59 90	20		
ex 5402 69 90	40		0
ex 5402 49 99	60	Yarn wholly of polyglycollic acid	
ex 5402 69 90	10		0
ex 5402 49 99	70	Synthetic filament yarn, single, containing by weight 85 % or more of acrylonitrile, in the form of a wick containing 1 000 continuous filaments or more but not more than 25 000 continuous filaments, of a weight per metre of 0,12 g or more but not exceeding 3,75 g and of a length of 100 m or more, for the manufacture of carbon-fibre yarn (a)	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 5402 49 99	80	Polyethylene filament yarn, untwisted, of either 55, 110, 165 or 1 760 decitex, for the manufacture of goods of heading No 5607 (a)	0
ex 5402 49 99	85	Synthetic filament yarn, single, untwisted, wholly of poly(thio-1,4-phenylene)	0
ex 5404 10 90	10	Monofilament of polytetrafluoroethylene	0
ex 5404 10 90	20	Monofilament of poly(1,4-dioxanone)	0
ex 5404 10 90	30	Monofilament of a copolymer of 1,3-dioxan-2-one with 1,4-dioxan-2,5-dione, for the manufacture of surgical sutures (a)	0
▼M12			
ex 5404 10 90	40	Monofilaments of a stabilised blend of polyester with polyurethane, of 67 decitex or more and of which no cross-sectional dimension exceeds 1 mm	0
▼M11			
ex 5404 90 90	20	Strip of polyimide	0
ex 5407 71 00	10	Woven fabrics of polyvinyl alcohol fibres, for machine embroidery	0
ex 5501 90 90	10	Polyvinyl alcohol tow	0
ex 5503 20 00	10	Polyester staple fibres, loaded with zeolite impregnated with a mixture of salts of copper and silver or of salts of zinc and silver	4
▼M12			
ex 5503 90 10 ex 5503 90 90	10 30	Acetalised, multicomponent spun fibres with a matrix fibril structure, consisting of emulsion-polymerised poly(-vinyl alcohol) and poly(vinyl chloride)	0
▼M11			
ex 5503 90 90	10	Textile fibres of polytetrafluoroethylene	4
ex 5503 90 90 ex 5506 90 90 ex 5601 30 00	20 10 10	Polyvinyl alcohol fibres, whether or not acetalised	0
ex 5503 90 90	40	Fibres wholly of poly(thio-1,4-phenylene)	0
ex 5601 30 00	20	Polyester fibres, measuring 0,56 decitex, of a length of 3 mm or more but not exceeding 5 mm	0
ex 5601 30 00	30	Acrylic fibres, measuring 0,11 and 0,56 decitex, of a length of 3 mm or more but not exceeding 5 mm	0
ex 5603 11 10 ex 5603 11 90 ex 5603 12 10 ex 5603 12 90 ex 5603 91 10 ex 5603 91 90 ex 5603 92 10 ex 5603 92 90	10 10 10 10 10 10 10 10	Poly(vinyl alcohol) non-wovens, in the piece or cut into rectangles: — of a thickness of 200 µm or more but not exceeding 280 µm, and — of a weight of 20 g/m² or more but not exceeding 50 g/m²	0
ex 5603 11 10 ex 5603 11 90 ex 5603 12 10 ex 5603 12 90	20 20 20 50	Non-wovens, containing spunbonded fibres of polypropylene or of polypropylene and polyethylene, for the manufacture of napkins and napkin liners for babies and similar sanitary articles (a)	0
ex 5603 12 90 ex 5603 13 90 ex 5603 14 90	30 30 10	Non-wovens of aromatic polyamide fibres obtained by polycondensation of *m*-phenylenediamine and isophthalic acid, in the piece or cut into rectangles	0
ex 5603 12 90 ex 5603 13 90	60 60	Non-woven of spunbonded polyethylene, of a weight of more than 60 g/m² but not exceeding 80 g/m² and an air resistance (Gurley) of 8 s or more but not exceeding 36 s (as determined by the ISO 5636/5 method)	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 5603 12 90 ex 5603 13 90 ex 5603 92 90 ex 5603 93 90	70 70 40 10	Non-wovens of polypropylene, consisting of a meltblown layer, laminated on each side with spunbonded filaments of polypropylene, of a thickness not exceeding 550 µm and of a weight not exceeding 80 g/m², in the piece or simply cut into squares or rectangles, not impregnated	0
ex 5603 13 90 ex 5603 14 90	40 20	Non-wovens consisting of a central layer of polycarbonate fibres, laminated on each side with spunbonded filaments of polyester, of a weight of more than 130 g/m² but not exceeding 200 g/m²	0
ex 5603 92 90 ex 5603 93 90	20 20	Non-wovens consisting of a meltblown central layer of a thermoplastic elastomer laminated on each side with spunbonded filaments of polypropylene	0
ex 5603 92 90	50	Non-wovens of staple fibres, in rolls, of a width of 78 mm or more but not exceeding 252 mm, for the manufacture of floppy discs (a)	0
ex 5603 94 90	20	Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips (a)	0
ex 5607 50 90	10	Twine, unsterilised, wholly of polyglycollic acid, plaited or braided, with an inner core, for the manufacture of surgical sutures (a)	0
ex 5903 10 90 ex 5903 20 90 ex 5903 90 99	10 10 20	Knitted or woven fabrics, coated or covered on one side with artificial plastic material in which are embedded microspheres	0
ex 5903 20 90	20	Tape of polyester fabric laminated with a metallised polyurethane film containing glass beads, for use in the manufacture of marine life-saving equipment (a)	0
ex 5907 00 90	10	Textile fabrics, coated with adhesive in which are embedded spheres of a diameter not exceeding 75 µm	0
ex 5911 10 00	10	Needle-punched synthetic-fibre felts, not containing polyester, whether or not containing catalytic particles entrapped within the synthetic fibres, coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products (a)	0
ex 5911 90 90	10	Yarn and strip of impregnated polytetrafluoroethylene, whether or not oiled or graphited	0
ex 5911 90 90 ex 8421 99 00	30 92	Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness not exceeding 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more	0
6305 10 10		Sacks and bags, of a kind used for the packing of goods, used, of jute or of other textile bast fibres of heading No 5303	0
ex 6305 90 00 ex 6305 90 00	10 91	Sacks and bags, of a kind used for the packing of goods, used, of flax or of sisal	0
ex 6307 90 10	10	Sterile mesh-implant, consisting of a knitted fabric of polypropylene monofilaments, with rounded edges, in forms covered by a square of dimensions not exceeding 31 × 31 cm	0
ex 6813 90 90	10	Friction material, of a thickness of less than 20 mm, not mounted, for the manufacture of friction components of a kind used in automatic transmissions and clutches (a)	0
ex 6903 20 90	10	Yarn of continuous ceramic filaments, each filament containing by weight: — 12 % or more of diboron trioxide, — 26 % or less of silicon dioxide, and — 60 % or more of dialuminium trioxide	0
ex 6903 90 80 ex 6909 19 00	10 40	Beryllium oxide, of a purity by weight of more than 99 %, in the form of blanks, bars, blocks or plates	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 6903 90 80	20	Silicon carbide reactor tubes and holders, of a kind used for insertion into diffusion and oxidation furnaces for production of semi-conductor materials	0
ex 6909 12 00	20	Plate, of dialuminium trioxide and titanium carbide, of dimensions not exceeding 48 × 48 mm, or of a diameter not exceeding 125 mm, for the manufacture of magnetic heads (a)	0
ex 6909 19 00	30	Supports for catalysts, consisting of porous cordierite or mullite ceramic pieces, of an overall volume not exceeding 65 l, having, per cm^2 of the cross-section, not less than one continuous channel which may be open at both ends or stopped at one end	0
ex 7006 00 90	10	Glass plate, coated on one side with chromium and/or with a mixture of diindium trioxide and tin dioxide, of dimensions of 260 × 320 mm or more but not exceeding 400 × 400 mm, of a thickness not exceeding 1,2 mm, for the manufacture of liquid crystal displays (a)	0
ex 7006 00 90	20	Colour filter, consisting of a glass plate with red, blue and green pixels, having a total thickness of 1,1 mm (± 0,1 mm) and exterior dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, for the manufacture of liquid crystal displays (a)	0
ex 7006 00 90	30	Glass plate, uncoated, of dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, of a thickness of 0,6 mm or more but not exceeding 1,2 mm, for the manufacture of liquid crystal displays (a)	0
ex 7006 00 90	40	Disc of glass, with a hole in the centre, with the edges having been worked, of a total thickness not exceeding 1,5 mm	0
ex 7011 10 00	10	Glass lenses with a stippled front refractor or with a front refractor composed of prismatic elements, with an external diameter of more than 121 mm but not exceeding 125 mm	0
ex 7011 10 00	20	Parabolic glass reflectors, with an external diameter of more than 121 mm but not exceeding 125 mm	0
ex 7011 20 00	40	Glass faceplate: — with a diagonal measurement of 366,4 mm (± 1,5 mm) and of dimensions of 246,4 × 315,4 mm (± 1,5 mm), — with a diagonal measurement of 391 mm (± 1,5 mm) and of dimensions of 261,4 × 326,8 mm (± 1,5 mm), — with a diagonal measurement of 442 mm (± 1,5 mm) and of dimensions of 293,4 × 369,2 mm (± 1,5 mm), — with a diagonal measurement of 544,5 mm (± 1,6 mm) and of dimensions of 358 × 454 mm (± 1,6 mm), having a cylindrical curvature, — with a diagonal measurement of 570,5 mm (± 1,6 mm) and of dimensions of 360 × 486 mm (± 1,6 mm), — with a diagonal measurement of 629,8 mm (± 3 mm) and of dimensions of 406,5 × 519 mm (± 2 mm), having a cylindrical curvature, or — with a diagonal measurement of 753 mm (± 1,6 mm) and of dimensions of 471 × 640 mm (± 1,6 mm), and with a raised edge, for the manufacture of colour cathode-ray tubes (a)	0
ex 7011 20 00	75	Glass faceplate: — with a diagonal measurement of 604,5 mm (± 3 mm) and of dimensions of 340 × 541 mm (± 2 mm), — with a diagonal measurement of 639,3 mm (± 3 mm) and of dimensions of 413,6 × 527 mm (± 2 mm), — with a diagonal measurement of 708 mm (± 3 mm) and of dimensions of 404 × 633 mm (± 2 mm), — with a diagonal measurement of 723 mm (± 3 mm) and of dimensions of 477 × 602 mm (± 2 mm),	

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
		or — with a diagonal measurement of 812,8 mm (± 3 mm) and of dimensions of 463,8 × 725,5 mm (± 2 mm), having a cylindrical curvature, for the manufacture of colour cathode-ray tubes (a)	0
ex 7011 20 00	80	Glass bulb for monochrome cathode-ray tube, of a diagonal measurement of 3,8 cm or more but not exceeding 51 cm and a nominal neck diameter of 13 mm, 20 mm, 29 mm or 37 mm	0
ex 7014 00 00	10	Optical elements of glass (other than those of heading No 7015), not optically worked, other than signalling glassware	0
ex 7019 12 00	10	Rovings, measuring 2 600 tex or more but not more than 3 300 tex and of a loss on ignition of 4 % or more but not exceeding 8 % by weight (as determined by the ASTM D 2584-94 method)	0

▼M12

ex 7019 12 00	15	Rovings, measuring 650 tex or more but not more than 2 500 tex, coated with a layer of polyurethane whether or not mixed with other materials	0

▼M11

ex 7019 12 00	30	Rovings, measuring 1 693 tex (± 10%), coated with a layer of styrene-butadiene rubber (SBR)	0
ex 7019 12 00	40	Rovings, measuring 2 040 tex (± 10 %), coated with carbon	0
ex 7019 19 10	10	Yarn of 33 tex or a multiple thereof, ± 7,5 %, obtained from continuous spun-glass filaments of a nominal diameter of 3,5 µm or of 4,5 µm, in which filaments of a diameter of 3 µm or more but not exceeding 5,2 µm predominate, other than those treated so as to improve their adhesion to elastomers	0
ex 7019 19 10	30	Yarn of 22 tex ± 7,5 %, obtained from continuous spun-glass filaments of a nominal diameter of 5 µm, in which filaments of a diameter of 4,2 µm or more but not exceeding 5,8 µm predominate	0
ex 7019 19 10	40	Yarn of 33, 34 or 51 tex or a multiple thereof, ± 7,5 %, obtained from continuous spun-glass filaments of a nominal diameter of 6 µm, in which filaments of a diameter of 5,1 µm or more but not exceeding 6,9 µm predominate	0
ex 7019 32 00 ex 7019 39 00	10 10	Non-woven product of non-textile glass fibre, for the manufacture of air filters or of air-filtration products (a)	0
ex 7019 90 10	10	Non-textile glass fibres in which fibres of a diameter of less than 3,5 µm predominate	0
ex 7019 90 10	20	Non-textile E-glass fibres, of a length not exceeding 3 mm and a diameter of 5 µm, for the manufacture of catalysts for the purification of smokes (a)	0
ex 7116 20 90	10	Disc of silicon on sapphire	0
7202 50 00		Ferro-silico-chromium	0
ex 7212 50 91	10	Perforated steel strip, plated or coated with nickel, of a width of 140 mm or more but not exceeding 400 mm and a thickness of 40 µm or more but not exceeding 140 µm	0
ex 7212 50 99	10	Cold-rolled steel, coated on both sides with a nickel-zinc layer, in the form of strip of a width of 40,15 (± 0,08) mm and a thickness of 0,3 (± 0,01) mm, containing by weight: — not more than 0,1 % of carbon, — not more than 0,04 % of phosphorus, — not more than 0,05 % of sulphur,	

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
		and — 0,2 % or more but not more than 0,5 % of manganese	0
ex 7306 30 29	91	Non-alloy steel precision tube, welded and cold finished, of an external diameter exceeding 160 mm and a wall thickness exceeding 2 mm	0
ex 7409 19 00	10	Sheet or plate of polytetrafluoroethylene, with aluminium oxide or titanium dioxide as a filler or reinforced with glass-fibre fabric, laminated on both sides with copper foil	0
ex 7410 21 00	10	Sheet or plate of polytetrafluoroethylene, containing aluminium oxide or titanium dioxide as filler or reinforced with glass-fibre fabric, covered on both sides with copper foil	0

▼M12

ex 7419 99 00 ex 7616 99 90	91 60	Disc (target) with deposition material, consisting of molybdenum silicide: — containing 1 mg/kg or less of sodium and — mounted on a copper or aluminium support	0

▼M11

ex 7419 99 00 ex 7616 99 90	92 70	Disc (target) with deposition material, of tungsten or an alloy containing by weight 90 % of tungsten and 10 % of titanium: — containing 100 µg/kg or less of sodium, and — mounted on a copper or aluminium support	0
ex 7419 99 00 ex 7616 99 90	93 80	Disc (target) with deposition material, of titanium: — containing 50 µg/kg or less of sodium, and — mounted on a copper or aluminium support	0
ex 7606 11 91 ex 7606 11 93	20 20	Strip with depth-etching, of band-anodic oxidation treated aluminium of a purity by weight of 99,9 % and a thickness of less than 3 mm, for incorporation in bodies for motor vehicles (a)	0
ex 7613 00 00 ex 8708 99 98	20 10	Aluminium container, seamless, for compressed natural gas or compressed hydrogen, wholly embedded in an overwrap of epoxy-carbon fibres composite, of a capacity of 172 l (± 10 %) and an unfilled weight not exceeding 64 kg	0
ex 7616 99 90	40	Discs of aluminium alloy, coated or covered on both sides with a nickel-phosphorus layer, having a total thickness not exceeding 3,02 mm	0
ex 7616 99 90	50	Discs of aluminium alloy, of a thickness not exceeding 0,84 mm, for the manufacture of goods of subheading 8523 20 10 (a)	0
ex 7905 00 00	10	Plate of an alloy of zinc, ground and polished on one surface and coated with an epoxide resin on the other surface, of rectangular or square shape, of a length of 300 mm or more but not exceeding 2 000 mm and of a width of 300 mm or more but not exceeding 1 000 mm, and containing: — 10 mg/kg or less of iron, — 10 mg/kg or less of lead, — 700 mg/kg or more but not more than 900 mg/kg of aluminium, and — 500 mg/kg or more but not more than 900 mg/kg of magnesium, for the manufacture of sensitised printing plates (a)	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8103 90 90	10	Welded tube solely of tantalum, or solely of an alloy of tantalum with tungsten containing by weight 3,5 % or less of tungsten	0
ex 8104 11 00	30	Unwrought magnesium, of a purity by weight of 99,95 % or more, in the form of ingots, for the manufacture of zirconium sponge or elements used in the nuclear industry (a)	0
ex 8104 90 00	10	Ground and polished magnesium sheets, of dimensions not exceeding 1 500 × 2 000 mm, coated on one side with an epoxy resin insensitive to light	0
ex 8104 90 00	20	Sections, of extruded magnesium, of a length of 800 mm or more but not exceeding 2 900 mm and a width of 15 mm or more but not exceeding 70 mm	0
ex 8108 20 00	10	Titanium sponge	0
8108 30 00		Waste and scrap of titanium	0
ex 8108 90 70	20	Welded titanium tubes, of an external diameter of 19,0 (± 0,1) mm, having an external structure of 36 fins per 2,54 cm, for use in the manufacture of refrigerant condensers (a)	0
ex 8109 20 00	10	Non-alloy zirconium, in the form of ingots, containing by weight more than 0,01 % of hafnium, for use in the manufacture of tubes for the chemical industry (a)	0
ex 8110 10 00	10	Antimony in the form of ingots	0
ex 8112 19 00	10	Beryllium, of a purity by weight of 94 % or more, in the form of bars, plates and sheets	0
ex 8112 99 30	10	Alloy of niobium (columbium) and titanium, in the form of bars and rods	0
ex 8407 31 00	10	Two stroke internal combustion engine, of a cylinder capacity not exceeding 30 cm^3 for use in the manufacture of portable motorised scooters falling within subheading 8711 10 00 (a)	0

▼M12

ex 8408 90 31	10	Diesel engines of a power not exceeding 15 kW, with two or three cylinders, for use in the manufacture of vehicle mounted temperature control systems (a)	0
ex 8408 90 33	10	Diesel engines of a power not exceeding 30 kW, with four cylinders, for use in the manufacture of vehicle mounted temperature control systems (a)	0
ex 8414 30 99	10	Open shaft reciprocating compressor, for use in the manufacture of vehicle mounted temperature control systems (a)	0

▼M11

ex 8414 90 90	10	Aluminium pistons, partially covered with polytetrafluoroethylene, for incorporation into compressors of air-conditioning machines of motor vehicles (a)	0
ex 8414 90 90	20	Pressure-regulating system, for incorporation into compressors of air-conditioning machines of motor vehicles (a)	0
ex 8418 99 90	91	Welded cooling microelements, of an alloy of aluminium, for the manufacture of condensers (a)	0
ex 8419 19 00	10	Heat accumulator for motor vehicles, of a coolant capacity of 4 l or more but not exceeding 10 l	0
ex 8419 89 98	10	Immersion-tube (coils) bundles, consisting of an assembly of plastic tubes terminating at each end in a honeycomb structure (end-fitting) surrounded by a pipe-connector	0
ex 8419 89 98 ex 8543 89 95	20 58	Sputtering machines and apparatus, comprising disc-handling equipment, for use in the manufacture of products falling within subheading 8523 20 10 (a)	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8421 99 00	91	Parts of equipment, for the purification of water by reverse osmosis, consisting of a bundle of hollow fibres of artificial plastic material with permeable walls, embedded in a block of artificial plastic material at one end and passing through a block of artificial plastic material at the other end, whether or not housed in a cylinder	0
ex 8421 99 00	93	Components of separators for the separation or purification of gases from gas mixtures, consisting of a bundle of permeable hollow fibres enclosed within a container, whether or not perforated, of an overall length of 300 mm or more but not exceeding 3 700 mm and a diameter not exceeding 500 mm	0
ex 8421 99 00	95	Parts of equipment for the filtration of magnetic dispersions, consisting essentially of nylon-6 fibres, enclosed in a plastic casing of a diameter of 70 mm (± 2 mm) and a length of 520 mm (± 5 mm)	0
ex 8422 30 00 ex 8479 89 98	10 70	Machines and apparatus, other than injection moulding machines, for the manufacture of ink-jet printer cartridges (a)	0
ex 8424 89 95 ex 8460 21 90 ex 8460 40 10 ex 8460 90 90 ex 8464 20 19 ex 8479 89 98	10 10 10 10 10 10	Machines and apparatus providing automated lapping, polishing, grinding, cleaning or surface lubrication of discs, comprising disc handling equipment, for use in the manufacture of products falling within subheading 8523 20 10 (a)	0
ex 8424 89 95 ex 8479 89 98	20 30	Machines and apparatus providing automated cleaning or cleaning and drying of discs, by means of de-ionised water, ultra sonic waves, chemical solutions, heat or a combination of these processes, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 10 (a)	0
ex 8439 99 10 ex 8439 99 90	10 10	Suction-roll shells, not drilled, in the form of alloy-steel tubes, of a length of 5 207 mm or more and an external diameter of 754 mm or more, for use in machinery for making paper or paperboard (a)	0

▼M12

ex 8454 30 10	10	Casting machines for casting under pressure of metal alloys in thixotropic (semi-solid) form	0

▼M11

ex 8455 90 00	10	Helical turn device for cold-rolling mill	0
ex 8456 10 90	10	Machine tool operating by laser beam, for the cutting of slots on the surface of a cylindrical tube for use in the manufacture of endo-vascular prosthesis (stents) (a)	0
ex 8460 90 90 ex 8463 90 00 ex 8479 89 98	20 10 20	Machine-tool providing automated creation of a texture (a head landing zone) on the surface of discs by means of abrasion or exposure to laser beams, comprising disk-handling equipment, for use in the manufacture of products falling within subheading 8523 20 10 (a)	0
ex 8473 40 19	20	Thermal printer head	0
ex 8479 89 98 ex 8501 10 99	40 78	Motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8525 20 91 or 8527 90 92 (a)	0
ex 8481 80 59	10	Air control valve, consisting of a stepping motor and a valve pintle, for the regulation of idle air flow in fuel injection engines	0
ex 8483 10 80	10	Integrally forged and roughly shaped generator and turbine shafts of a weight exceeding 215 tonnes	0
ex 8501 10 99	54	DC motor, brushless, with an external diameter not exceeding 25,4 mm, a rated speed of 2 260 (± 15 %) or 5 420 (± 15 %) rpm, a supply voltage of 1,5 or 3 V	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8501 10 99	59	DC stepping motor, with an angle of step of 1,8º (± 0,09º), a holding torque of 0,156 Nm or more, a coupling flange the exterior dimensions of which do not exceed 43 × 43 mm, a chuck of a diameter of 4 mm (± 0,1 mm), a two-phase winding and an output not exceeding 5 W	0
ex 8501 10 99	73	DC motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8471 70 53 (a)	0
ex 8501 10 99	77	DC motor, with brushes, with a typical running torque of 0,004 Nm (± 0,001 Nm), with a coupling flange of a diameter of 32 mm (± 0,5 mm) and a chuck of a diameter of 2 mm (± 0,004 mm), with an internal rotor, a three-phase winding, a rated speed of 2 800 (± 10 %) rpm and a supply voltage of 12 V (± 15 %)	0
ex 8502 40 90	10	Rotary converter, with a ferrite core, having coils with 2 or 6 windings and a diameter of 0,1 mm, connected to a flexible printed circuit	0
ex 8503 00 91 ex 8503 00 99	31 32	Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring	0
ex 8503 00 99	31	Stamped collector of an electric motor, having an external diameter not exceeding 16 mm	0
ex 8504 40 99	20	Direct current to direct current converter	0
ex 8504 40 99	30	Static converter comprising a power switch with insulated-gate bipolar transistors (IGBTs), contained in a housing, for use in the manufacture of microwave ovens of subheading 8516 50 00 (a)	0
ex 8504 50 80	30	Inductor with an inductance not exceeding 62 mH	0
ex 8504 50 80	40	Multilayer monolithic inductors, contained in a housing of the SMD (surface mounted device) type, the exterior dimensions of which do not exceed 1,8 × 3,4 mm, for use in the manufacture of products falling within subheading 8517 11 00, 8525 20 91 or 8527 90 92 (a)	0
8504 90 11		Ferrite cores	0
ex 8504 90 18	32	Part of a rotary transformer, comprising a ferrite core provided with circular grooves with copper wire windings	0
ex 8505 11 00	31	Ferrite magnet having a remanence of 455 mT (± 15 mT)	0
ex 8505 19 90	31	Neodymium-ferro ring with an external diameter not exceeding 13 mm, an internal diameter not exceeding 9 mm	0
ex 8505 90 10	91	Solenoid with a plunger, operating at a nominal supply voltage of 24 V at a nominal DC of 0,08 A, for use in the manufacture of products falling within heading No 8517 (a)	0
ex 8505 90 10	92	Electromechanical throttle plate actuator for automotive engines	0
ex 8506 50 90	10	Lithium iodine single cell battery, the dimensions of which do not exceed 9 × 23 × 45 mm and a voltage not exceeding 2,8 V	0
ex 8506 50 90	20	Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit	0
ex 8506 50 90	30	Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions not exceeding 28 × 45 × 15 mm and a capacity of not less than 1,05 Ah	0
ex 8507 30 91 ex 8507 80 91 ex 8507 80 99	20 10 10	Rectangular accumulator, with a length not exceeding 69 mm, a width not exceeding 36 mm and a thickness not exceeding 12 mm, for use in the manufacture of rechargeable batteries (a)	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8507 30 91	30	Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm (± 1,5 mm) and a diameter of 14,5 mm (± 1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (a)	0

▼M12

ex 8507 80 91	80	Cylindrical nickel-hydride accumulator, of a diameter not exceeding 14,5 mm, for the manufacture of rechargeable batteries (a)	0

▼M11

ex 8507 80 99	20	Cylindrical lithium-ion accumulator, with a length of 64,6 mm or more and a diameter of 18,1 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
ex 8516 90 00	31	Dual diode, consisting of a power rectifying diode connected with a transformer protector diode through a wire, with a peak reverse power rate of 2 J or more, for use in the manufacture of products falling within subheading 8516 50 00 (a)	0
ex 8518 29 80	20	Loudspeaker having a power of 5 W and an impedance of 4 ohms, with a diameter not exceeding 50 mm, for use in the manufacture of portable phones (a)	0
ex 8518 30 80	20	Headphone and earphone for hearing aids, contained in a housing the exterior dimensions of which, excluding connecting points, do not exceed 5 × 6 × 8 mm	0
ex 8518 90 00	91	Integrally cold-upsetted steel coreplate, in the form of a disk on one side provided with a cylinder, for use in the manufacture of loudspeakers (a)	0
ex 8520 90 90	20	Drive-unit capable of magnetooptical signal recording and optical signal reproducing, comprising at least an optical unit, DC motors and a printed circuit on which are mounted integrated circuits providing drive and signal processing functions for reading optical discs having an external diameter not exceeding 70 mm, not comprising circuits with amplification functions or power supply drive functions	0
ex 8522 90 59	93	Optical unit consisting of a laser diode with one photo-diode, emitting light of a nominal wavelength of 780 nm, contained in a housing with a diameter of not more than 10 mm and a height of not more than 9 mm, with not more than 10 connections and bearing: — an identification marking consisting of or including (one of) the following combination(s): LDGU LT 022, or — other identification markings relating to devices complying with the abovementioned description	0
ex 8522 90 59	94	Electronic assembly for a laser read head of a compact disc player, comprising: — a printed circuit, — a photo-detector, in the form of a monolithic integrated circuit, contained in a housing, — not more than 3 connectors, — not more than 1 transistor, — not more than 3 variable and 4 fixed resistors, — not more than 5 capacitors, the whole mounted on a support	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8522 90 98	31	Thin-film recording and reproducing device, having at least 9 parallel channels for digital signals and at least 2 channels for analogue signals, to which a non-magnetic ceramic substrate is fixed, the whole rounded at one side, for use in the manufacture of magnetic heads for digital sound recording and digital/analogue sound reproducing apparatus of the cassette type (a)	0
▼M12			
▼M11			
ex 8522 90 98	34	Cassette-deck sub-assembly for sound recording and reproducing apparatus, for use in the manufacture of telephone answering machines (a)	0
ex 8522 90 98	35	Sound-reproducing assembly, comprising a tape deck mechanism of the cassette type, comprising a DC motor, for use in the manufacture of products falling within heading No 8519 (a)	0
ex 8522 90 98	36	Roll for magnetic tape guiding and winding, for use in the manufacture of products falling within heading No 8521 or 8522 (a)	0
ex 8522 90 98	37	Magnetic head for erasing video tapes, for use in the manufacture of products falling within heading No 8521 or 8522 (a)	0
▼M12			
▼M11			
ex 8522 90 98	39	Assembly consisting of a driver circuit, a tachosensor and a brushless DC motor	0
▼M12			
▼M11			
ex 8522 90 98	43	Analogue sound-recording and reproducing assembly, comprising a record/playback head and a twin tape deck mechanism of the cassette type, not comprising circuits with amplification functions or power supply drive functions, for use in the manufacture of products falling within subheadings 8527 31 91 and 8527 31 98 (a)	0
▼M12			
ex 8522 90 98	44	Assembly for optical discs, comprising at least an optical unit and DC motors, not capable of double layer recording	0
▼M11			
ex 8528 21 90	20	Colour video monitor having an operating voltage of not less than 10 V and not exceeding 35 V, comprising a liquid crystal display (LCD), whether or not contained in a housing	0
ex 8528 22 00	10	Video monitor comprising: — a flat-screen monochrome cathode-ray tube with a diagonal measurement of the screen not exceeding 110 mm and equipped with a deflector yoke, and — a printed circuit on which are mounted a deflection unit, a video amplifier and a transformer, the whole mounted on a chassis, for the manufacture of video entry-phones, video telephones or surveillance apparatus (a)	0
ex 8529 10 70	10	Ceramic filter package comprising 2 ceramic filters and 1 ceramic resonator for a frequency of 10,7 MHz (± 30 kHz), contained in a housing	0
ex 8529 10 70	15	Ceramic filter for a centre frequency of 10,7 MHz, with a bandwidth not exceeding 330 kHz at 3 dB and not exceeding 950 kHz at 20 dB, contained in a housing	0
ex 8529 10 70	20	Ceramic filters for frequencies of 4,5 MHz or more but not exceeding 6,6 MHz contained in a housing	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8529 10 70	25	Ceramic filter for a centre frequency of 450 kHz or more but not exceeding 470 kHz, with a bandwidth not exceeding 13 kHz at 3 dB, contained in a housing	0
ex 8529 10 70	30	Ceramic filter for a frequency of 450 kHz, with a bandwidth not exceeding 18 kHz at 10 dB, contained in a housing	0
ex 8529 10 70	35	Ceramic filter for a centre frequency of 455 kHz (± 1,5 kHz), with a bandwidth not exceeding 25 kHz at 6 dB and not exceeding 60 kHz at 40 dB, contained in a housing	0
ex 8529 10 70	45	Ceramic filter for a centre frequency of 450 kHz (± 1,5 kHz) or 455 kHz (± 1,5 kHz), with a bandwidth not exceeding 30 kHz at 6 dB and not exceeding 70 kHz at 40 dB, contained in a housing	0
ex 8529 10 70	50	Radio frequency (RF) signal isolator for frequencies of 890 MHz or more but not exceeding 1 990 MHz, having an insertion loss not exceeding 0,7 dB, contained in a housing	0
ex 8529 10 70	55	Filters, excluding surface acoustic wave filters, for a centre frequency of 485 MHz or more but not exceeding 1 990 MHz with an insertion loss not exceeding 3,5 dB, contained in a housing	0
ex 8529 10 70	80	Ceramic filter package, excluding surface acoustic wave filters, consisting of: — a transmit filter with a centre frequency of 1 747,5 MHz and an insertion loss not exceeding 2,3 dB at a bandwidth of 75 MHz, and — a receive filter with a centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,3 dB at a bandwidth of 75 MHz, the whole contained in a housing	0
ex 8529 10 70	85	Ceramic filter package, excluding surface acoustic wave filters, comprising 2 filters with one of the following combinations of characteristics: — a transmit centre frequency of 902,5 MHz, a receive centre frequency of 947,5 MHz and an insertion loss not exceeding 3,2 dB at a bandwidth of 25 MHz, or — a transmit centre frequency of 1 747,5 MHz, a receive centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,5 dB at a bandwidth of 75 MHz, the whole contained in a housing	0
ex 8529 10 90	20	Antenna switch, comprising: — a transmit filter with a centre frequency of 942,5 MHz or more but not exceeding 1 990 MHz, and — a receive filter with a centre frequency of 847,5 MHz or more but not exceeding 1 990 MHz, the whole contained in a housing	0
ex 8529 90 81	31	Demagnetisation coil, with cables and connectors	0
ex 8529 90 81	32	Optical unit for video projection, comprising a colour separation system, a positioning mechanism and lenses, for use in the manufacture of products falling within heading No 8528 [a]	0
ex 8529 90 81	34	Assembly consisting of a lens unit, having an adjustable focal length of 4 mm or more but not exceeding 69 mm and comprising a zoom encoder, a stepping motor unit, a zoom motor unit, an iris motor unit and a photo interrupter	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8529 90 81	35	Video-recording and reproducing assembly, comprising a tape deck mechanism of the cassette type, comprising a DC motor, for use in the manufacture of products falling within heading No 8528 (a)	0
ex 8529 90 81	36	Assembly consisting of a monochrome cathode-ray tube with a diagonal measurement of the screen of 143 mm or more but not exceeding 230 mm and a concave focus lens mounted on a liquid-filled cooling armature	0
ex 8529 90 81 ex 8529 90 88	37 33	Filter, consisting of 2 piezo-electric crystals each with a frequency of 21 MHz or more but not exceeding 30 MHz and separately mounted on a bracket, with not more than 7 connections	0
ex 8529 90 81	40	Assembly comprising prisms, digital micromirror device (DMD) chips and electronic control circuits, for use in the manufacture of video projectors (a)	0
ex 8529 90 81	41	Digital micromirror device (DMD)chips, for use in the manufacture of video projectors (a)	0
ex 8531 80 80	01	Indicator lamp, consisting of 4 light-emitting diodes made from silicon-cardide (SiC) semi-conductor material, operating at a nominal wavelength of 481, 560 or 630 nm, contained in a housing	0
ex 8531 80 80	15	Indicator lamp, consisting of 2 light-emitting diodes made from aluminium-gallium-arsenic (AlGaAs) or gallium-phosphor (GaP) semi-conductor material, having a rectangular base, contained in a housing of the SMD (surface mounted device) type and having a lens	0
ex 8531 80 80	25	Electroaccoustic transducer	0
ex 8531 80 80	30	An electromagnetic display, consisting of 7 electromagnetic coils which by means of the residual magnetism in the stators provide that the last indication remains available (set state), and 7 pivoting light-reflecting segments each of which is attached to a bar magnet; assembly comprising such displays	0
ex 8536 30 30 ex 8536 30 90 ex 8536 50 80	11 31 96	Thermoelectric switch with a cut-off current of 50 A or more, comprising a snap action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing	0
ex 8536 41 10 ex 8536 41 90 ex 8536 49 00	91 91 91	Thermal relays contained in a hermetically sealed glass cartridge not exceeding 35 mm in length excluding wires, with a maximum leakage rate of 10^{-6} cm^3 He/sec at one bar in the temperature range 0 ºC to 160 ºC, to be incorporated into compressors for refrigerating equipment (a)	0
ex 8536 50 11	31	Switch of the printed circuit mount type, operating at a force of 4,9 N (± 0,9 N), contained in a housing	0
ex 8536 50 15	32	Rotary switch in form of a wheel with a diameter of between 15 and 16 mm and contacts for closing the circuit, for a rated voltage of 12 V at 50 mA	0
ex 8536 50 19	91	Hall effect switch, comprising 1 magnet, 1 Hall effect sensor and 2 capacitors, contained in a housing with 3 connections and bearing: — an identification marking consisting of or including (one of) the following combination(s): 2AV28E 2AV31E 2AV56 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8536 50 19	92	Hydraulic pressure switch, incorporating a pressure sensitive snap action disc, operating at a supply voltage of 6 V or more but not exceeding 18 V	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8536 50 80	93	Switch unit for coaxial cable, comprising 3 electromagnetic switches, with a switching time not exceeding 50 ms and an actuating current not exceeding 500 mA at a voltage of 12 V	0
ex 8536 50 80	95	Reed switch having a switching power of 20 W or more within the range of 17 to 43 A.turn, in the form of a glass capsule, not containing mercury, the dimensions of which do not exceed 3 × 21 mm, for use in the manufacture of automotive airbag shock-sensors (a)	0
ex 8536 90 85	92	Metallic stamped frame with connections	0
ex 8536 90 85	93	Contact element with a hold-force of more than 3 N, in the form of 2 rectangular plastic frames interconnected by electric conductors	0
ex 8536 90 85 ex 8544 49 80	94 10	Elastomeric connector, consisting of one or more conductor elements and of a rubber or silicon substrate	0
ex 8537 10 99	92	Touch-sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors	0
▼M12			
ex 8537 10 99	93	Electronic control units for a voltage of 12 V, for use in the manufacture of vehicle mounted temperature control systems (a)	0
▼M11			
ex 8538 90 99	92	Part of an electrothermal fuse, consisting of a tin-coated copper wire attached to a cylindrical casing, the exterior dimensions of which do not exceed 5 × 48 mm	0
ex 8540 11 11	91	Colour cathode-ray tube with a slit or slot mask, equipped with electron guns placed side by side (inline technology) and with a diagonal measurement of the screen of 12 cm or more but not exceeding 26 cm	0
ex 8540 11 11	93	Colour cathode-ray tube, equipped with 1 gun with 3 rays and with a diagonal measurement of the screen of 22 cm or more but not exceeding 26 cm	0
ex 8540 11 13	91	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,42 mm and a diagonal measurement of the screen of 49 cm, for use in the manufacture of professional video monitors including security and medical monitor applications (a)	0
ex 8540 11 19	91	Colour cathode-ray tube equipped with electron guns placed side by side (inline technology), with a diagonal measurement of the screen of 85 cm or more	0
ex 8540 11 91	31	Colour cathode-ray tube with a screen width/height ratio of 16/9 and a diagonal measurement of the screen of 39,8 cm (± 0,3 cm)	0
ex 8540 11 99	31	Colour cathode-ray tube with a diagonal measurement of the screen of 85,5 cm or more	0
ex 8540 12 00	82	Monochrome cathode-ray tube with a diagonal measurement of the screen of 250 mm or more but not exceeding 320 mm and an anode voltage of 18 kV or more but not exceeding 22 kV	0
ex 8540 12 00	83	Monochrome cathode-ray tube, with a diagonal measurement of the screen of 150 mm or more but not exceeding 182 mm, a neck diameter of less than 30 mm and an anode voltage of 25 kV or more but not exceeding 32 kV	0
ex 8540 12 00	84	Flat-screen monochrome cathode-ray tube, with a diagonal measurement of the screen not exceeding 102 mm	0
ex 8540 20 80	91	Photomultiplier consisting of a photocathode tube with 9 dynodes, for light of a wavelength of 160 nm or more but not exceeding 930 nm, of a diameter not exceeding 14 mm and a height not exceeding 94 mm	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8540 40 00 ex 8540 60 00	31 31	Colour cathode-ray tube with a dot mask, equipped with 3 electron guns placed side by side (inline technology) or 1 gun with 3 rays, with a diagonal measurement of the screen of more than 72 cm and a distance of less than 0,5 mm between dots of the same colour	0
ex 8540 40 00 ex 8540 60 00	32 32	Colour cathode-ray tube with a dot mask, equipped with 3 electron guns placed side by side (in-line technology) or 1 gun with 3 rays, having a diagonal measurement of the screen not exceeding 72 cm	0
ex 8540 40 00	33	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 53 cm	0
ex 8540 40 00	34	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,39 mm and a diagonal measurement of the screen of 33 cm or more but not exceeding 38 cm	0
ex 8540 40 00	35	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 72 cm, for use in the manufacture of monitors (a)	0
ex 8540 40 00	36	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,30 mm and a diagonal measurement of the screen not exceeding 58 cm	0
ex 8540 50 00 ex 8540 60 00	31 33	Flat-screen monochrome cathode-ray tube, with a diagonal measurement of the screen of 142 mm or more but not exceeding 190 mm, a luminescence of 300 lumen or more but not exceeding 2 000 lumen, a resolution of 0,06 mm or more but not exceeding 0,1 mm, phosphor types P1 or P22 or P53 or P55 or P56, an anode voltage of more than 34 kV, a focus voltage of more than 7 kV and a cathode current of 3 mA or more	0
ex 8540 50 00 ex 8540 60 00	32 34	Monochrome cathode-ray tube with a diagonal measurement of the screen of 176 mm or more but not exceeding 520 mm and a neck diameter not exceeding 21 mm	0
ex 8540 89 00	91	Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 300 × 350 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0
ex 8540 89 00	92	Vacuum fluorescent display tube	0
ex 8540 91 00	31	Electron gun, for use in the manufacture of colour cathode-ray tubes of subheading 8540 40 00 with a diagonal measurement of the screen of 34 cm or more but not exceeding 39 cm (a)	0
ex 8540 91 00	32	Electron gun of colour cathode-ray tubes with an anode voltage of 27,5 kV or more but not exceeding 33 kV	0
ex 8540 91 00	91	Deflector yoke for cathode-ray tubes with an operating frequency of 31 250 Hz or more but not exceeding 64 000 Hz, incorporating a quadripolar magnet	0
ex 8540 91 00	92	Slit or slot mask, excluding masks with continuously vertical slits, with a diagonal measurement of 39 cm or less	0
ex 8540 91 00	93	Electron gun for the production of monochrome cathode-ray tubes with a diagonal measurement of the screen of 7,6 cm or more but not exceeding 30,5 cm (a)	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8540 91 00	94	Deflector yoke for colour cathode-ray tubes, with an operating frequency of 15 625 or 31 250 Hz, comprising 2 two-pole ring magnets, 2 four-pole ring magnets and 2 six-pole ring magnets	0
ex 8540 91 00	96	Assembly for cathode-ray tubes with 2 or more but not more than 6 coils, a plastic support and a metal fixing ring, for the adjustment of display sharpness and/or convergence	0
ex 8540 91 00	97	Slit mask, consisting of continuously vertical slits measuring more than 275 mm in the length	0
ex 8540 91 00	98	Frame of molybdenum chrome steel, for use in the manufacture of cathode-ray tubes (a)	0
ex 8540 99 00	91	Anode, cathode or output part, or an assembly comprising these components (magnetron core tube), for the manufacture of magnetrons of subheading 8540 71 00 (a)	0
ex 8543 19 00	10	Electron beam accelerator systems, with an operating voltage not exceeding 1,5 MV and a beam current not exceeding 70 mA	0
ex 8543 89 95	46	Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing bearing: — an identification marking consisting of or including (one of) the following combination(s): FA 01314 FA 01317 FA 01321 FMC 1717 FMC 1819 ISO 122 MHW 105 MHW 1815 MHW 2701, MHW 2707 MHW 607 MHW 704 MHW 707 MHW 720 MHW 803 MHW 820-1 MHW 820-2 MHW 9002 MHW 910 MHW 914 MHW 915 MHW 916 MHW 926 MHW 927 MHW 953 PF 0144 PF 0146 PF 0148 PF 0412 PHW 2905 PHW 2907 PHW 5113 PHW 9012 PHW 902 PHW 925 SHW 5115 XHW 105 XHW 2803 XHW 2902 XHW 5115 XHW 903, or — other identification markings relating to devices complying with the abovementioned description	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8543 89 95	48	Radio frequency (RF) modulator, operating with a frequency range of 43 MHz or more but not exceeding 870 MHz, capable of switching VHF and UHF signals, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0
ex 8543 89 95	49	Rectifier assembly of power barrier diodes, consisting of 2 diodes with an average forward current not exceeding 600 A and a repetitive reverse peak voltage not exceeding 40 V, each contained in a housing and connected by a common cathode	0
ex 8543 89 95	50	Piezo-electric crystal clock oscillator with a fixed frequency, within a frequency range of 1,8 MHz to 67 MHz, contained in a housing bearing: — an identification marking consisting of or including (one of) the following combination(s): R4000.8 R4000.9, or — other identification markings relating to devices complying with the abovementioned description	0
ex 8543 89 95	51	Mechanical vibratory gyroscope driven by a 25 or 26 kHz oscillator, comprising a differential amplifier and a detector circuit, contained in a housing bearing: — an identification marking consisting of or including (one of) the following combination(s): ENC05D, or — other identification markings relating to devices complying with the abovementioned description	0
ex 8543 89 95	52	Optoelectronic circuit comprising one or more light-emitting diodes (LEDs) and one photodiode with amplifier circuit and an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, contained in a plastic housing bearing: — an identification marking consisting of or including (one of) the following combination(s): HC PL 2400 HC PL 2730, or — other identification markings relating to devices complying with the abovementioned description	0
ex 8543 89 95	53	Oscillator, with a centre frequency of 20 GHz or more but not exceeding 42 GHz, consisting of active and passive elements not mounted on a substrate, contained in a housing bearing: — an identification marking consisting of or including (one of) the following combination(s): 372-02 372-03, or — other identification markings relating to devices complying with the abovementioned description	0
ex 8543 89 95	55	Audio-recording and reproducing circuit, capable of stereo audio data storage and simultaneous record and playback, comprising 2 or 3 monolithic integrated circuits mounted on a printed circuit or a lead frame, contained in a housing bearing: — an identification marking consisting of or including (one of) the following combination(s): RWA010 RWA100	

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
		RWA200 RWA300, or — other identification markings relating to devices complying with the abovementioned description	0
ex 8543 89 95	56	Overvoltage suppression assembly, comprising 8 diodes, having a reverse stand-off voltage not exceeding 4,5 V, a reverse leakage current not exceeding 10 μA, a peak pulse current not exceeding 30 A and a nominal capacitance of 50 pF, contained in a housing	0

▼M12

▼M11

ex 8543 89 95	59	Charged coupled device (CCD) scanner assembly, for a real-time film scanning system, having optical functions, illumination functions and signal-processing functions	0

▼M12

ex 8543 89 95	60	Temperature compensated oscillator, comprising a printed circuit on which are mounted at least a piezo-electric crystal and an adjustable capacitor, contained in a housing	0
ex 8543 89 95	61	Voltage controlled oscillator (VCO), other than temperature compensated oscillators, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0
ex 8543 90 80	40	Stainless steel cathode in the form of a plate with a hanger bar, whether or not with plastic side strips	0

▼M11

ex 8543 90 80	50	Assembly of products falling within heading No 8541 or 8542 mounted on a printed circuit, contained in a housing	0
ex 8545 90 90	01	Cell and battery carbon, in the form of rods, with a length of 34 mm or more but not exceeding 160 mm and a diameter not exceeding 12 mm	0
ex 8548 90 90	38	Parts, for use in the manufacture or the repair of products falling within subheading 8517 21 00 ([a])	0
ex 8548 90 90	39	Optical unit, consisting of a laserdiode and a photodiode, operating at a typical wavelength of 635 or 670 nm	0
ex 8548 90 90	40	Infrared signal receiver unit, consisting of a photodiode and at least an amplifier in the form of a monolithic integrated circuit, contained in a housing bearing: — an identification marking consisting of or including (one of) the following combination(s): GP1U58XB SBX 1610, or — other identification markings relating to devices complying with the abovementioned description	0
ex 8548 90 90	41	Unit, consisting of a resonator operating within a frequency range of 1,8 MHz or more but not exceeding 40 MHz and a capacitor, contained in a housing	0

▼**M11**

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8548 90 90 ex 9110 90 00	42 94	Clock/calendar circuit, consisting of a printed circuit on which are mounted at least a quartz oscillator and a monolithic integrated circuit, the whole contained in a housing bearing: — an identification marking consisting of or including (one of) the following combination(s): DS 1287 DS 1387 MK 48T08 MK 48T18 RTC 65271 DS 12887A MK 48T02 MK 48T12 RTC 63421 RTC 72423, or — other identification markings relating to devices complying with the abovementioned description	0
ex 8548 90 90	43	Contact image sensor	0
ex 8711 10 00 ex 8714 19 00	10 10	Portable motorised scooter disassembled kit	0
ex 9001 10 90	10	Image reverser made up from an assembly of optical fibres	0
ex 9001 20 00	10	Material consisting of a polarising film, supported on one or both sides by transparent material	0
ex 9001 90 90	20	Rear-projection screen, comprising a Fresnel lens of plastic and a polarising sheet of plastic, for use in the manufacture of products falling within heading No 8528 [a]	0
ex 9001 90 90	30	Lens of plastic, unmounted, having a focal length of 3,86 mm (± 0,1 mm) and with a diameter not exceeding 8 mm, for use in the manufacture of compact disc players [a]	0
ex 9001 90 90	40	Optical fibre plate, for use in the manufacture of screens and photocathodes for image intensifiers [a]	0
ex 9001 90 90	50	Rear-projection screen, comprising a lenticular plastic plate	0
ex 9001 90 90	60	Prism for the splitting of light, unmounted, for use in the manufacture of charged-coupled image (CCD) cameras [a]	0
ex 9001 90 90	70	Rod of neodymium-doped yttrium-aluminium garnet (YAG) material, polished at both ends	0
ex 9001 90 90	80	Lens of plastic, unmounted, for use in the manufacture of products falling within subheading 9006 40 00 [a]	0
ex 9002 11 00	10	Adjustable lens unit, having a focal length of 90 mm or more but not exceeding 180 mm and comprising a combination of between 4 and 8 glass or methacrylic lenses with a diameter of 120 mm or more but not exceeding 180 mm, each lens coated on at least one side with a magnesium fluoride layer, for use in the manufacture of video projectors [a]	0
ex 9002 11 00	50	Lens unit, having a focal length of 25 mm or more but not exceeding 150 mm, consisting of glass or plastic lenses, with a diameter of 60 mm or more but not exceeding 190 mm	0
ex 9002 11 00	60	Optical element, comprising one or more mounted lenses of plastic, for use in the manufacture of products falling within subheading 9006 40 00 [a]	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 9002 19 00	10	Lens unit, having a focal length of 24,96 mm (± 0,1 mm), a diameter of 16 mm and a length of 16 mm, for use in the manufacture of products falling within subheading 8517 21 00 (a)	0
ex 9002 20 00	10	Filter, consisting of a plastic polarising membrane, a glass plate and a transparent protective film, mounted on a metal frame, for use in the manufacture of products falling within heading 8528 (a)	0
ex 9002 90 90	20	Lens, mounted, having a fixed focal length of 3,8 mm (± 0,19 mm) or 8 mm (± 0,4 mm), with a relative aperture of F2.0 and a diameter not exceeding 33 mm, for use in the manufacture of charged-coupled (CCD) cameras (a)	0
ex 9002 90 90	30	Optical unit, comprising 1 or 2 rows of optical glass fibres in the form of lenses and with a diameter of 0,85 mm or more but not exceeding 1,15 mm, embedded between 2 plastic plates	0
ex 9002 90 90	50	Lens and image gate assembly, for a real-time film scanning system, comprising a lens consisting of 9 or 11 elements and having an illumination function	0
ex 9006 91 90	10	Parts, for use in the manufacture of products falling within subheading 9006 40 00 (a)	0
ex 9013 80 90	10	Polarisation-insensitive fibre-optic isolator, operating at a wavelength of 1 200 nm or more, contained in a cylindrical housing	0
ex 9013 80 90	20	Optical switch, comprising at least one optical input and two optical outputs and with electrical connectors	0
ex 9017 90 90	20	Thermal printer head, comprising at least 7 168 heater elements mounted on 2 or more ceramic supports, the whole contained in a housing the exterior dimensions of which exceed 21 × 39 × 639 mm	0
ex 9022 30 00	10	X-ray tube with a target voltage of 4 kV or more but not exceeding 30 kV, a power not exceeding 9 W and a target current not exceeding 2 mA	0
▼M12			
ex 9027 10 90	10	Sensor element for gas or smoke analysis in motor vehicles, essentially consisting of a zirconium-ceramic element in a metal housing	0
▼M11			
ex 9031 80 34 ex 9031 80 39 ex 9031 80 99	10 30 10	Machines and apparatus providing automated quality inspection of rigid magnetic disss, for use in the manufacture of products falling within subheading 8523 20 10 (a)	0
▼M12			
ex 9031 80 34 ex 9031 80 39	30 50	Apparatus for measuring the angle and direction of rotation of motor vehicles, consisting of at least one yaw rate sensor in the form of a monocrystalline quartz, whether or not combined with one or more measuring sensors, the whole contained in a housing	0
▼M11			
ex 9031 80 39	10	Acceleration measurement device for automotive applications, comprising one or more active and/or passive elements and one or more sensors, the whole contained in a housing	0
ex 9031 80 39	40	Machines and apparatus for the automatic testing of the integrity of ink-jet cartridge housings (a)	0
ex 9031 90 80	20	Read and write test head for checking the quality of rigid magnetic disks, mounted on a carrier arm	0
ex 9031 90 80	30	Assembly for a laser align sensor, in the form of a printed circuit comprising optical filters and a charge-coupled image (CCD) sensor, the whole contained in a housing	0
ex 9031 90 80	40	Test head for checking the mechanical quality of rigid magnetic disks, mounted on a carrier arm	0

▼M11

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 9031 90 80	50	Burnishing head, for removing asperities on and polishing of the surface of rigid magnetic disks, mounted on a carrier arm	0
ex 9032 10 91	10	Thermostat, comprising a snap-action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing	0
ex 9032 89 90	10	Automotive airbag shock-sensor, comprising a contact capable of switching a current of 12 A at a voltage of 30 V, having a typical contact resistance of 80 mohm	0
ex 9106 90 10	10	Timer assembly, for use in the manufacture of goods of subheading 8516 50 00 (a)	0
ex 9110 12 00	91	Assembly consisting of a printed circuit on which are mounted one quartz oscillator, at least one watch circuit and, whether or not integrated, at least one capacitor, of a thickness not exceeding 5 mm	0
ex 9110 90 00 ex 9114 90 00	92 91	Assembly consisting of a printed circuit on which is mounted a watch circuit or a watch circuit and a quartz oscillator, of a thickness not exceeding 5 mm	0
ex 9110 90 00	93	Assembly consisting of a printed circuit on which is mounted at least one watch circuit, a quartz oscillator and a piezo-electric sound element, with a thickness exceeding 5 mm	0
ex 9608 91 00	10	Non-fibrous plastic pen tips with an internal channel	0
ex 9608 91 00	20	Felt tips and other porous tips for markers, without internal canal	0
ex 9612 10 10	10	Ribbons of plastic with segments of different colours, providing the penetration of dyes by heat into a support (dye-sublimation)	0
▼M12			
ex 9613 90 00	20	Piezo-electric ignition mechanism, whether or not with complementary elements	0

▼M11

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

(b) The suspension shall apply to fish intended to undergo any operation unless they are intended to undergo exclusively one or more of the following operations:
— cleaning, gutting, tailing, heading,
— cutting (excluding filleting or cutting of frozen blocks),
— sampling, sorting,
— labelling,
— packing,
— chilling,
— freezing,
— deep freezing,
— thawing, separation.

The suspension is not allowed for products intended, in addition, to undergo treatment (or operations) qualifying for suspension where such treatment (or operations) is (are) carried out at retail or catering level. The suspension of customs duties shall apply only to fish intended for human consumption.

►M12 ——— ◄

►M12 (c) ◄ However, the suspension is not allowed where processing is carried out by retail or catering undertakings.