This document is meant purely as a documentation tool and the institutions do not assume any liability for its contents

►B

COUNCIL REGULATION (EC) No 1255/96

of 27 June 1996

temporarily suspending the autonomous Common Customs Tariff duties on certain ►M9 industrial, agricultural and fishery products ◄

(OJ L 158, 29.6.1996, p. 1)

Amended by:

		Official Journal		
		No	page	date
►M1	Council Regulation (EC) No 2484/96 of 20 December 1996	L 341	1	30.12.1996
►M2	Council Regulation (EC) No 1186/97 of 27 June 1997	L 172	1	30.6.1997
►M3	Council Regulation (EC) No 2590/97 of 16 December 1997	L 355	1	30.12.1997
►M4	Council Regulation (EC) No 1359/98 of 29 June 1998	L 186	1	30.6.1998
►M5	Council Regulation (EC) No 2797/98 of 17 December 1998	L 352	1	29.12.1998
►M6	Council Regulation (EC) No 1381/1999 of 28 June 1999	L 165	1	30.6.1999
►M7	Council Regulation (EC) No 20/2000 of 17 December 1999	L 8	1	12.1.2000
►M8	Council Regulation (EC) No 1297/2000 of 19 June 2000	L 153	1	26.6.2000
►M9	Council Regulation (EC) No 2801/2000 of 14 December 2000	L 331	1	27.12.2000
►M10	Council Regulation (EC) No 1159/2001 of 11 June 2001	L 169	1	23.6.2001
►M11	Council Regulation (EC) No 2499/2001 of 19 December 2001	L 340	1	21.12.2001
►M12	Council Regulation (EC) No 1120/2002 of 26 June 2002	L 171	1	29.6.2002
►M13	Council Regulation (EC) No 2264/2002 of 19 December 2002	L 350	1	27.12.2002
►M14	Council Regulation (EC) No 1048/2003 of 16 June 2003	L 161	1	30.6.2003
►M15	Council regulation (EC) No 2285/2003 of 22 December 2003	L 341	1	30.12.2003
►M16	Council Regulation (EC) No 1241/2004 of 5 July 2004	L 238	1	8.7.2004
►M17	Council Regulation (EC) No 2271/2004 of 22 December 2004	L 396	13	31.12.2004
►M18	Council Regulation (EC) No 989/2005 of 27 June 2005	L 168	1	30.6.2005
►M19	Council Regulation (EC) No 300/2006 of 30 January 2006	L 56	1	25.2.2006
►M20	Council Regulation (EC) No 963/2006 of 27 June 2006	L 176	3	30.6.2006
►M21	Council Regulation (EC) No 1897/2006 of 19 December 2006	L 395	1	30.12.2006
►M22	Council Regulation (EC) No 729/2007 of 25 June 2007	L 166	4	28.6.2007
►M23	Council Regulation (EC) No 1527/2007 of 17 December 2007	L 349	7	31.12.2007
►M24	Council Regulation (EC) No 595/2008 of 16 June 2008	L 164	1	25.6.2008
►M25	Council Regulation (EC) No 1/2009 of 18 December 2008	L 1	1	5.1.2009
►M26	Council Regulation (EC) No 564/2009 of 25 June 2009	L 168	4	30.6.2009

▼B

COUNCIL REGULATION (EC) No 1255/96

of 27 June 1996

temporarily suspending the autonomous Common Customs Tariff duties on certain ►M9 industrial, agricultural and fishery products ◄

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 28 thereof,

Having regard to the proposal from the Commission,

Whereas production in the Community of the products specified in this Regulation is currently inadequate or non-existent; whereas producers thus cannot meet the needs of user industries in the Community;

Whereas it is in the interest of the Community to suspend partially or totally the autonomous Common Customs Tariff duties for these products;

Whereas the decision to suspend such autonomous duties should be taken by the Community;

Whereas the Regulations temporarily suspending the autonomous Common Customs Tariff duties on certain ►M9 industrial, agricultural and fishery products ◄ have largely renewed previous measures; whereas, therefore, in the interests of rationalizing implementation of the measures concerned, it would seem appropriate not to limit the period of validity of this Regulation as its scope can be adapted and products added to or removed from the list through a Council Regulation, if necessary;

Whereas the amendments to the combined nomenclature and the Taric codes do not give rise to any substantive amendment; whereas, for reasons of simplification, provision should be made to empower the Commission, following receipt of the opinion of the Customs Code Committee, to make the necessary amendments and technical adaptations of the Annex to this Regulation, including the publication of a consolidated version,

HAS ADOPTED THIS REGULATION:

Article 1

The autonomous Common Customs Tariff duties for the products listed in the Annex hereto shall be suspended at the level indicated against each of them.

Article 2

The technical adaptations, including publication of a consolidated version, arising from amendments of the combined nomenclature and Taric codes shall be adopted by the Commission in accordance with the procedure laid down in Article 3.

Article 3

1. The Commission shall be assisted by the Customs Code Committee set up by Article 247 of Regulation (EEC) No 2913/92 ([1]).

2. The representative of the Commission shall submit to the Committee a draft of the measures to be taken. The Committee shall

([1]) OJ No L 302, 19. 10. 1992, p. 1. Regulation as amended by the 1994 Act of Accession.

▼B

deliver its opinion on the draft within a time limit which the chairman may lay down according to the urgency of the matter. The opinion shall be delivered by the majority laid down in Article 148 (2) of the Treaty in the case of decisions which the Council is required to adopt on a proposal from the Commission. The votes of the representatives of the Member States within the Committee shall be weighted in the manner set out in that Article. The chairman shall not vote.

3. The Commission shall adopt measures which apply immediately.

However, if these measures are not in accordance with the opinion of the Committee, they shall be communicated by the Commission to the Council forthwith. In that event, the Commission shall defer application of the measures which it has decided for three months from the date of such communication.

The Council, acting by a qualified majority, may take a different decision within the period referred to in the previous indent.

Article 4

This Regulation shall enter into force on the day following its publication in the *Official Journal of the European Communities*.

It shall apply from 1 July 1996.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

▼M25

ANNEX

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 0302 69 99	30	Red snapper (*Lutjanus purpureus*), fresh, chilled, for processing (1) (2)	0 %	31.12.2013
*ex 0302 70 00	89	Hard fish roes, fresh, chilled or frozen	0 %	31.12.2013
ex 0303 80 90	19			
▼M26				
————————				
▼M25				
*ex 0305 20 00	11	Hard fish roes, salted or in brine	0 %	31.12.2013
ex 0305 20 00	30			
*ex 0710 21 00	10	Peas in pods, of the species *Pisum sativum* of the variety *Hortense axiphium*, frozen, of a thickness of not more than 6 mm, to be used, in their pods, in the manufacture of prepared meals (1) (2)	0 %	31.12.2013
*ex 0710 80 95	50	Bamboo shoots, frozen, not put up for retail sale	0 %	31.12.2013
*ex 0711 59 00	11	Mushrooms, excluding mushrooms of the genera *Agaricus, Calocybe, Clitocybe, Lepista, Leucoagaricus, Leucopaxillus, Lyophyllum* and *Tricholoma*, provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry (1)	0 %	31.12.2011
*ex 0712 32 00	10	Mushrooms, excluding mushrooms of the genus *Agaricus*, dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale (1) (2)	0 %	31.12.2013
ex 0712 33 00	10			
ex 0712 39 00	31			
*ex 0804 10 00	10	Dates, fresh or dried, not put up for retail sale	0 %	31.12.2013
*ex 0810 40 50	10	Fruit of the species *Vaccinium macrocarpon*, fresh	0 %	31.12.2013
*0811 90 50	69	Fruit of the genus *Vaccinium*, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter	0 %	31.12.2013
0811 90 70				
ex 0811 90 95				
*ex 0811 90 95	20	Boysenberries, frozen, not containing added sugar, not put up for retail sale	0 %	31.12.2013
*ex 0811 90 95	30	Pineapple (*Ananas comosus*), in pieces, frozen	0 %	31.12.2013
*ex 0811 90 95	40	Rose-hips, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter	0 %	31.12.2013
▼M26				
————————				
**ex 1511 90 19	10	Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of:	0 %	1.7.2009-31.12.2013
**ex 1511 90 91	10	— industrial monocarboxylic fatty acids of subheading 3823 19 10,		

▼M26

CN code	TARIC	Description	Rate of autonomous duty	Validity period
**ex 1513 11 10	10	— methyl esters of fatty acids of heading 2915 or 2916,		
**ex 1513 19 30	10	— fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the manufacture of cosmetics, washing products or pharmaceutical products,		
**ex 1513 21 10	10	— fatty alcohols of subheading 2905 16, pure or mixed, used for the manufacture of cosmetics, washing products or pharmaceutical products,		
**ex 1513 29 30	10	— stearic acid of subheading 3823 11 00, or — goods of heading No 3401 ([4])		

▼M25

*ex 1515 90 99	92	Vegetable oil, refined, containing by weight 35 % or more but not more than 50 % of arachidonic acid or 35 % or more but not more than 50 % of docosahexaenoic acid	0 %	31.12.2013
ex 1517 90 99	10	Vegetable oil, refined, containing by weight 35 % or more but not more than 50 % arachidonic acid or 35 % or more but not more than 50 % docosahexaenoic acid and standardized with high oleic sunflower oil (HOSO)	0 %	31.12.2011

▼M26

ex 1518 00 99	10	Jojoba oil, hydrogenated and texturised	0 %	1.7.2009-31.12.2013

▼M25

*ex 1604 11 00	20	Pacific salmon (*Oncorhynchus* spp.), for the processing industry for manufacture into pastes or spreads ([1])	0 %	31.12.2013
*ex 1604 30 90	10	Hard fish roes, washed, cleaned of adherent organs and simply salted or in brine, for processing ([1])	0 %	31.12.2013
*ex 1605 10 00 ex 1605 10 00	11 19	Crabs of the species 'King' (*Paralithodes camchaticus*), 'Hanasaki' (*Paralithodes brevipes*), 'Kegani' (*Erimacrus isenbecki*), 'Queen' and 'Snow' (*Chionoecetes* spp.), 'Red' (*Geryon quinquedens*), 'Rough stone' (*Neolithodes asperrimus*), *Lithodes santolla*, 'Mud' (*Scylla serrata*), 'Blue' (*Portunus* spp.), simply boiled in water and shelled, whether or not frozen, in immediate packings of a net content of 2 kg or more	0 %	31.12.2013
*ex 1902 30 10 ex 1903 00 00	10 20	Transparent noodles, cut in pieces, obtained from beans (*Vigna radiata* (L.) Wilczek), not put up for retail sale	0 %	31.12.2013
*ex 2005 91 00	10	Bamboo shoots, prepared or preserved, in immediate packings of a net content of more than 5 kg	0 %	31.12.2013
ex 2008 60 19 ex 2008 60 39	30 30	Sweet cherries containing added spirit, whether or not with a sugar content of 9 % by weight, of a diameter of not more than 19,9 mm, with stone, for use in chocolate products ([1])	10 % ([3])	31.12.2012

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2009 80 79	87	Frozen boysenberry juice concentrate with a Brix value of 61 or more, but not more than 65	0 %	31.12.2011
ex 2009 80 99	93	Untreated frozen coconut water, not put up for retail sale	0 %	31.12.2011
*ex 2106 10 20	10	Soya protein isolate, containing by weight 6,6 % or more but not more than 8,6 % of calcium phosphate	0 %	31.12.2013
*ex 2710 11 25	10	Mixture of isomers 2.4,4-trimethylpent-1-ene and 2.4,4-trimethylpent-2-ene	0 %	31.12.2013
▼M26				
ex 2804 50 90	10	Tellurium of a purity by weight of 99,99 % or more, but not more than 99,999 % by weight	0 %	1.7.2009-31.12.2013
▼M25				
*ex 2804 70 00	10	Yellow phosphorus	0 %	31.12.2013
*ex 2805 30 10	10	Alloy of cerium and other rare-earth metals, containing by weight 47 % or more of cerium	0 %	31.12.2013
*ex 2805 30 90	10	Lanthanum of a purity by weight of 99 % or more	0 %	31.12.2013
*ex 2811 19 80	10	Sulphamidic acid	0 %	31.12.2013
*ex 2811 22 00	10	Silicon dioxide in the form of powder, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges ([1])	0 %	31.12.2013
ex 2811 22 00	20	Microspheres of amorphous silicon of a particle size of 5 μm (± 1 μm), for use in the manufacture of cosmetic products ([1])	0 %	31.12.2011
ex 2811 22 00	30	Balls of porous white silica of a particle size of more than 1 μm for use in the manufacture of cosmetic products ([1])	0 %	31.12.2011
*ex 2812 90 00	10	Nitrogen trifluoride	0 %	31.12.2013
*ex 2812 90 00	20	Silicon tetrafluoride	0 %	31.12.2013
*ex 2818 30 00	10	Aluminium hydroxide oxide in the form of pseudo-boehmite	4 %	31.12.2013
2819 10 00		Chromium trioxide	0 %	31.12.2011
*ex 2823 00 00	10	Titanium dioxide, of a purity by weight of 99,9 % or more, with an average grain-size of 1,2 μm or more but not more than 1,8 μm, for the manufacture of goods of heading No 8532 or 8533 ([1])	0 %	31.12.2013
*ex 2825 50 00	10	Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride	0 %	31.12.2013
*ex 2827 39 85	10	Copper monochloride of a purity by weight of 96 % or more but not more than 99 %	0 %	31.12.2013
*ex 2827 39 85	20	Antimony pentachloride of a purity by weight of 99 % or more	0 %	31.12.2011

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26				
ex 2827 39 85	30	Manganese dichloride	0 %	1.7.2009-31.12.2013
▼M25				
*ex 2827 49 90	10	Hydrated zirconium dichloride oxide	0 %	31.12.2013
*ex 2830 10 00	10	Disodium tetrasulphide, containing by weight 38 % or less of sodium calculated on the dry weight	0 %	31.12.2013
*ex 2833 29 80	10	Manganese sulphate monohydrate	0 %	31.12.2013
ex 2835 10 00	10	Sodium hypophosphite monohydrate	0 %	31.12.2012
*ex 2836 91 00	20	Lithium carbonate, containing one or more of the following impurities at the concentrations indicated: — 2 mg/kg or more of arsenic, — 200 mg/kg or more of calcium, — 200 mg/kg or more of chlorides, — 20 mg/kg or more of iron, — 150 mg/kg or more of magnesium, — 20 mg/kg or more of heavy metals, — 300 mg/kg or more of potassium, — 300 mg/kg or more of sodium, — 200 mg/kg or more of sulphates, determined according to the methods specified in the European Pharmacopœia	0 %	31.12.2013
*ex 2836 99 17	10	Zirconium (IV) basic carbonate	0 %	31.12.2013
*ex 2837 19 00	20	Copper cyanide	0 %	31.12.2013
ex 2837 20 00	10	Tetrasodium hexacyanoferrate (II)	0 %	31.12.2011
ex 2839 19 00	10	Disodium disilicate	0 %	31.12.2012
*ex 2839 90 90	10	Lead silicate hydrate, of a lead content by weight of (84,5 ± 1,5) %, evaluated as lead monoxide, in the form of powder	0 %	31.12.2013
*ex 2839 90 90	20	Calcium silicate	0 %	31.12.2013
2841 30 00		Sodium dichromate	0 %	31.12.2013
ex 2841 80 00	10	Diammonium wolframate (ammonium paratungstate)	0 %	31.12.2012
ex 2841 90 85	10	Lithium cobalt(III) oxide with a cobalt content of at least 59 %	0 %	31.12.2012
*ex 2842 10 00	10	Synthetic Beta Zeolite powder	0 %	31.12.2013
ex 2843 29 00	10	Silver oxide, nitrate- and carbonate-free, with a silver content of at least 99,99 % by weight of the metal content, for the manufacture of silver oxide batteries [1]	0 %	31.12.2011
*2845 10 00		Heavy water (deuterium oxide) (*Euratom*)	0 %	31.12.2013
*2845 90 10		Deuterium and compounds thereof; hydrogen and compounds thereof, enriched in deuterium; mixtures and solutions containing these products (*Euratom*)	0 %	31.12.2013
ex 2845 90 90	10	Helium-3	0 %	31.12.2011
*ex 2845 90 90	20	Water enriched at a level of 95 % or more *by weight* with oxygen-18	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2845 90 90	30	Carbon monoxide ^{13}C	0 %	31.12.2011
*ex 2845 90 90	40	Iron boride enriched at a level of more than 95 % by weight with boron-10	0 %	31.12.2013
*ex 2846 10 00 ex 3824 90 97	10 48	Rare-earth concentrate containing by weight 60 % or more but not more than 95 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight	0 %	31.12.2013
*ex 2846 10 00	20	Dicerium tricarbonate, whether or not hydrated	0 %	31.12.2013
*ex 2846 10 00	30	Cerium lanthanum carbonate, whether or not hydrated	0 %	31.12.2013
*ex 2846 10 00	40	Cerium lanthanum neodymium praseodymium carbonate, whether or not hydrated	0 %	31.12.2013
*2846 90 00		Compounds, inorganic or organic, of rare-earth metals, of yttrium or of scandium or of mixtures of these metals, other than those of subheading 2846 10 00	0 %	31.12.2013
*ex 2848 00 00	10	Phosphine	0 %	31.12.2013
*ex 2850 00 20	10	Silane	0 %	31.12.2013
*ex 2850 00 20	20	Arsine	0 %	31.12.2013
ex 2850 00 20	30	Titanium nitride with a particle size of not more than 250 nm	0 %	31.12.2012
*ex 2850 00 60	10	Sodium azide	0 %	31.12.2013
*ex 2903 39 90	10	Carbon tetrafluoride (tetrafluoromethane)	0 %	31.12.2013
*ex 2903 39 90	30	Perfluoroethane	0 %	31.12.2013
*ex 2903 39 90	40	1,1-Difluoroethane	0 %	31.12.2013
*ex 2903 39 90	50	1.1,1.3,3-Pentafluoropropane	0 %	31.12.2013
ex 2903 39 90	70	1.1,1,2 Tetrafluoroethane, certified odourless containing a maximum: — 600 ppm by weight of 1.1,2,2-Tetrafluorethane, — 2 ppm by weight of pentafluoroethane, — 2 ppm by weight of chlorodifluoromethane, — 2 ppm by weight of chloropentafluoroethane, — 2 ppm by weight of dichlorodifluoromethane For use in the manufacture of pharmaceutical grade propellant for medical metred dose inhalers (1)	0 %	31.12.2011

▼M26

ex 2903 39 90	75	Trans-1,3,3,3-tetrafluoroprop-1-ene	0 %	1.7.2009-31.12.2013

▼M25

ex 2903 39 90	80	Hexafluoropropene	0 %	31.12.2011
*ex 2903 43 00	10	1.1,1-Trichlorotrifluoroethane	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2903 59 80	10	1.6,7.8,9.14,15.16,17.17,18,18-Dodeca-chloropentacyclo [12.2.1.16.9,$^{02.13,05,10}$] octadeca-7,15-diene	0 %	31.12.2013
ex 2903 59 80	30	Octafluorocyclopentene	0 %	31.12.2011
*ex 2903 69 90	10	Di- or tetrachlorotricyclo[8.2.2.2^{4,7}] hexadeca-1(12),4.6,10.13,15-hexaene, mixed isomers	0 %	31.12.2013
*ex 2903 69 90	20	1,2-*Bis*(pentabromophenyl)ethane	0 %	31.12.2013
*ex 2903 69 90	40	2,6-Dichlorotoluene, of a purity by weight of 99 % or more and containing: — 0,001 mg/kg or less of tetrachlorodibenzodioxines, — 0,001 mg/kg or less of tetrachlorodibenzofurans, — 0,2 mg/kg or less of tetrachlorobiphenyls	0 %	31.12.2013
▼M26				
ex 2903 69 90	50	Fluorobenzene	0 %	1.7.2009-31.12.2013
ex 2903 69 90	60	α-Chloro(ethyl)toluenes	0 %	1.7.2009-31.12.2013
▼M25				
ex 2904 10 00	40	Sodium toluene-4-sulphonate	0 %	31.12.2012
*ex 2904 20 00	40	2-Nitropropane	0 %	31.12.2013
▼M26				
ex 2904 90 40	10	Trichloronitromethane, for the manufacture of goods of subheading 3808 92 (4)	0 %	1.7.2009-31.12.2013
▼M25				
*ex 2904 90 95	20	1-Chloro-2,4-dinitrobenzene	0 %	31.12.2013
*ex 2905 19 00 ex 3824 90 97	11 56	Potassium *tert*-butanolate (potassium *tert*-butoxide), whether or not in the form of a solution in tetrahydrofuran	0 %	31.12.2013
*ex 2905 19 00	30	2,6-Dimethylheptan-4-ol	0 %	31.12.2013
*2906 11 00		Menthol	0 %	31.12.2013
*ex 2906 19 00	10	Cyclohex-1,4-ylenedimethanol	0 %	31.12.2013
*ex 2906 19 00	20	4,4'-Isopropylidenedicyclohexanol	0 %	31.12.2013
*ex 2906 29 00	20	1-Hydroxymethyl-4-methyl-2.3,5,6-tetra-fluorobenzene	0 %	31.12.2013
*ex 2907 19 90	10	2.3,5-Trimethylphenol	0 %	31.12.2013
*ex 2907 19 90	20	Biphenyl-4-ol	0 %	31.12.2013
*ex 2907 21 00	10	Resorcinol	0 %	31.12.2013
*ex 2907 29 00	20	4,4'-(3.3,5-Trimethylcyclohexylidene) diphenol	0 %	31.12.2013
*ex 2907 29 00	30	4,4',4'-Ethylidynetriphenol	0 %	31.12.2013
*ex 2907 29 00	50	6,6',6'-Tricyclohexyl-4,4',4'-butane-1.1,3-triyltri(*m*-cresol)	0 %	31.12.2013
*ex 2907 29 00	70	2,2',2',6,6',6'-Hexa-*tert*-butyl-α, α', α'-(mesitylene-2.4,6-triyl)tri-*p*-cresol	0 %	31.12.2013
*ex 2907 29 00	85	Phloroglucinol whether or not hydrated	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2908 99 90	30	4-Nitrophenol	0 %	31.12.2013
*ex 2909 19 90	20	*Bis*(2-chloroethyl) ether	0 %	31.12.2013
*ex 2909 19 90	30	Mixture of isomers of nonafluorobutyl methyl ether or nonafluorobutyl ethyl ether, of a purity by weight of 99 % or more	0 %	31.12.2013
ex 2909 19 90	50	3-Ethoxy-perfluoro-2-methylhexane	0 %	31.12.2011
▼M26				
ex 2909 19 90	60	1-Methoxyheptafluoropropane	0 %	1.7.2009-31.12.2013
▼M25				
*ex 2909 30 38	10	*Bis*(pentabromophenyl) ether	0 %	31.12.2013
*ex 2909 50 00	10	4-(2-Methoxyethyl)phenol	0 %	31.12.2013
*ex 2909 60 00	10	*Bis*(α, α-dimethylbenzyl) peroxide	0 %	31.12.2013
*ex 2910 90 00	30	2,3-Epoxypropan-1-ol (glycidol)	0 %	31.12.2013
*ex 2910 90 00	60	1,2-Epoxyoctadecane, of a purity by weight of 82 % or more	0 %	31.12.2013
*ex 2912 29 00	30	α, α,3-trimethylbenzenepropanal	0 %	31.12.2013
*ex 2912 49 00	10	3-Phenoxybenzaldehyde	0 %	31.12.2013
ex 2912 49 00	20	4-Hydroxybenzaldehyde	0 %	31.12.2011
ex 2914 19 90	20	Heptan-2-one	0 %	31.12.2012
ex 2914 19 90	30	3-Methylbutanone	0 %	31.12.2012
ex 2914 19 90	40	Pentan-2-one	0 %	31.12.2012
*2914 21 00		Camphor	0 %	31.12.2013
*ex 2914 29 00	20	Cyclohexadec-8-enone	0 %	31.12.2013
ex 2914 39 00	20	Stearoyl benzoyl methane	0 %	31.12.2012
ex 2914 39 00	30	Benzophenone	0 %	31.12.2012
ex 2914 39 00	40	1,3-Diphenylpropane-1,3-dione	0 %	31.12.2012
*ex 2914 39 00	50	4-Phenylbenzophenone	0 %	31.12.2013
*ex 2914 39 00	60	4-Methylbenzophenone	0 %	31.12.2013
*ex 2914 50 00	30	2'-Hydroxyacetophenone	0 %	31.12.2013
ex 2914 50 00	60	2,2-Dimethoxy-2-phenylacetophenone	0 %	31.12.2012
*ex 2914 50 00	70	16α,17α-Epoxy-3β-hydroxypregn-5-en-20-one	0 %	31.12.2012
*ex 2914 50 00	80	2',6'-dihydroxyacetophenone	0 %	31.12.2013
*ex 2914 69 90	10	2-Ethylanthraquinone	0 %	31.12.2013
*ex 2914 69 90	20	2-Pentylanthraquinone	0 %	31.12.2013
*ex 2914 69 90	30	1,4-Dihydroxyanthraquinone	0 %	31.12.2013
*ex 2914 70 00	10	1-Chloro-3,3-dimethylbutan-2-one	0 %	31.12.2013
*ex 2914 70 00	40	Perfluoro(2-methylpentan-3-one)	0 %	31.12.2013
*ex 2914 70 00	50	3'-Chloropropiophenone	0 %	31.12.2013
*ex 2915 29 00	10	Antimony triacetate	0 %	31.12.2013
*ex 2915 39 00	40	*tert*-Butyl acetate	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2915 39 00	50	3-Acetylphenyl acetate	0 %	31.12.2013
*ex 2915 90 00	40	Nonanoic acid (pelargonic acid)	0 %	31.12.2013
*ex 2916 12 00	10	2-*tert*-Butyl-6-(3-*tert*-butyl-2-hydroxy-5-methylbenzyl)-4-methylphenyl acrylate	0 %	31.12.2013
*ex 2916 12 00	20	2-Ethoxyethyl acrylate	0 %	31.12.2013
*ex 2916 12 00	30	Isobutyl acrylate	0 %	31.12.2013
*ex 2916 12 00	40	2,4-Di-*tert*-pentyl-6-[1-(3,5-di-*tert*-pentyl-2-hydroxyphenyl)ethyl]phenylacrylate	0 %	31.12.2013
*ex 2916 13 00	20	Zinc dimethacrylate, in the form of powder	0 %	31.12.2013
*ex 2916 14 00	10	2,3-Epoxypropyl methacrylate	0 %	31.12.2013
*ex 2916 19 95	20	Methyl 3,3-dimethylpent-4-enoate	0 %	31.12.2013
*ex 2916 20 00	50	Ethyl 2,2-dimethyl-3-(2-methylpropenyl) cyclopropanecarboxylate	0 %	31.12.2013
*ex 2916 39 00	20	3,5-Dichlorobenzoyl chloride	3,6 %	31.12.2013
*ex 2916 39 00	40	Vinyl 4-*tert*-butylbenzoate	0 %	31.12.2013
ex 2916 39 00	45	2-Chlorobenzoic acid	0 %	31.12.2011
*ex 2916 39 00	50	3,5-Dimethylbenzoyl chloride	0 %	31.12.2013
ex 2916 39 00	55	4-*tert*-Butylbenzoic acid	0 %	31.12.2012
*ex 2916 39 00	60	4-Ethylbenzoyl chloride	0 %	31.12.2013
*ex 2916 39 00	65	2-(4-nitrophenyl)butyric acid	0 %	31.12.2013
*ex 2916 39 00	70	Ibuprofen (INN)	0 %	31.12.2013
*ex 2916 39 00	80	Ethyl 2-(4-nitrophenyl)butyrate	0 %	31.12.2013
*ex 2917 11 00	20	*Bis*(*p*-methylbenzyl) oxalate	0 %	31.12.2013
*ex 2917 19 90	20	Sodium 1,2-*bis*(cyclohexyloxycarbonyl) ethanesulphonate	0 %	31.12.2013
*ex 2917 19 90	40	Dodecanedioic acid, of a purity by weight of more than 98,5 %	0 %	31.12.2013
*ex 2917 19 90	70	Itaconic acid	0 %	31.12.2013
*ex 2917 20 00	30	1.4,5.6,7,7-Hexachloro-8.9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride	0 %	31.12.2013
*ex 2917 20 00	40	3-Methyl-1.2,3,6-tetrahydrophthalic anhydride	0 %	31.12.2013
*ex 2917 34 90	10	Diallyl phthalate	0 %	31.12.2013
*ex 2918 19 85	20	L-Malic acid	0 %	31.12.2013
*ex 2918 29 00	10	Monohydroxynaphthoic acids	0 %	31.12.2013
*ex 2918 29 00	30	Octadecyl-3-(3,5-di-*tert*-butyl-4-hydroxy-phenyl)propionate	0 %	31.12.2011
*ex 2918 29 00	50	Hexamethylene *bis*[3-(3,5-di-*tert*-butyl-4-hydroxyphenyl)propionate]	0 %	31.12.2013
*ex 2918 30 00	30	Methyl-2-benzoylbenzoate	0 %	31.12.2013
*ex 2918 30 00	40	Phthalaldehydic acid	0 %	31.12.2013
*ex 2918 99 90	10	3,4-Epoxycyclohexylmethyl 3,4-epoxycyclohexanecarboxylate	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2918 99 90	30	Methyl 2-(4-hydroxyphenoxy)propionate	0 %	31.12.2013
*ex 2918 99 90	40	*trans*-4-Hydroxy-3-methoxycinnamic acid	0 %	31.12.2013
*ex 2918 99 90	50	Methyl 3.4,5-trimethoxybenzoate	0 %	31.12.2013
*ex 2918 99 90	60	3.4,5-Trimethoxybenzoic acid	0 %	31.12.2013
*ex 2919 90 00	10	2,2'-Methylenebis(4,6-di-*tert*-butylphenyl) phosphate, monosodium salt	0 %	31.12.2013
*ex 2919 90 00	30	Aluminium hydroxybis[2,2'-methylenebis (4,6-di-*tert*-butylphenyl)phosphate]	0 %	31.12.2013
*ex 2919 90 00	40	Tri-n-hexylphosphate	0 %	31.12.2013
*ex 2920 19 00	10	Fenitrothion (ISO)	0 %	31.12.2013
*ex 2920 19 00	20	Tolclofos-methyl (ISO)	0 %	31.12.2013
*ex 2920 90 10	10	Diethyl sulphate	0 %	31.12.2013
*ex 2920 90 10	20	Diallyl 2,2'-oxydiethyl dicarbonate	0 %	31.12.2013
*ex 2920 90 10	40	Dimethyl carbonate	0 %	31.12.2013
*ex 2920 90 10	50	Di-*tert*-butyl dicarbonate	0 %	31.12.2013
*2920 90 30		Trimethyl phosphite	0 %	31.12.2013
*2920 90 40		Triethyl phosphite	0 %	31.12.2011
*ex 2920 90 85	10	*O,O'*-Dioctadecyl pentaerythritol *bis* (phosphite)	0 %	31.12.2013
*ex 2921 19 85	20	Ethyl(2-methylallyl)amine	0 %	31.12.2013
*ex 2921 19 85	30	Allylamine	0 %	31.12.2013
*ex 2921 19 85	40	Tris(diethylamido)tert-butylimido tantalum (V)	0 %	31.12.2013
*ex 2921 19 85	50	Tetrakis (Ethylmethylamino) hafnium (IV)	0 %	31.12.2013

▼M26

ex 2921 19 85	60	Tetrakis(ethylmethylamino) zirconium (IV)	0 %	1.7.2009-31.12.2013

▼M25

*ex 2921 29 00	10	*N, N,N',N'* Tetrabutylhexamethylenediamine	0 %	31.12.2013
*ex 2921 29 00	20	Tris[3-(dimethylamino)propyl]amine	0 %	31.12.2013
*ex 2921 29 00	30	*Bis*[3-(dimethylamino)propyl]methylamine	0 %	31.12.2013
*ex 2921 30 99	10	Dicyclohexyl(methyl)amine	0 %	31.12.2013
*ex 2921 30 99	20	Cyclohex-1,3-ylenebis(methylamine), for the manufacture of dishwashing products ([1])	0 %	31.12.2013
*ex 2921 42 00	10	2,6-Dichloro-4-nitroaniline	0 %	31.12.2013
*ex 2921 42 00	15	4-Amino-3-nitrobenzenesulphonic acid	0 %	31.12.2013
*ex 2921 42 00	25	Sodium hydrogen 2-aminobenzene-1,4-disulphonate	0 %	31.12.2013
*ex 2921 42 00	35	2-Nitroaniline	0 %	31.12.2013
*ex 2921 42 00	45	2.4,5-Trichloroaniline	0 %	31.12.2013
*ex 2921 42 00	50	3-Aminobenzenesulfonic acid	0 %	31.12.2013
*ex 2921 42 00	70	2-Aminobenzene-1,4-disulfonic acid	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2921 42 00	80	4-Chloro-2-nitroaniline	0 %	31.12.2013
*ex 2921 42 00	85	3,5-Dichloroaniline	0 %	31.12.2013
*ex 2921 43 00	10	5-Amino-2-chlorotoluene-4-sulphonic acid	0 %	31.12.2013
*ex 2921 43 00	20	4-Amino-6-chlorotoluene-3-sulphonic acid	0 %	31.12.2013
*ex 2921 43 00	30	3-Nitro-*p*-toluidine	0 %	31.12.2013
*ex 2921 43 00	40	4-Aminotoluene-3-sulphonic acid	0 %	31.12.2013
*ex 2921 44 00	20	Diphenylamine	0 %	31.12.2013
*ex 2921 45 00	10	Sodium hydrogen 3-aminonaphthalene-1,5-disulphonate	0 %	31.12.2013
*ex 2921 45 00	20	2-Aminonaphthalene-1,5-disulphonic acid and its sodium salts	0 %	31.12.2013
*ex 2921 45 00	40	1-Naphthylamine	0 %	31.12.2013
*ex 2921 49 00	20	Pendimethalin (ISO)	3,5 %	31.12.2013
*ex 2921 49 00	40	*N*-1-Naphthylaniline	0 %	31.12.2013

▼M26

———————

**ex 2921 51 19	20	Toluene diamine (TDA), containing by weight 78 % or more but not more than 82 % of 4-methyl-m-phenylenediamine and 18 % or more but not more than 22 % of 2-methyl-m-phenylenediamine, and with a residual tar content of not more than 0,23 % by weight	0 %	1.7.2009-31.12.2013

▼M25

*ex 2921 51 19	30	2-Methyl-*p*-phenylenediamine sulphate	0 %	31.12.2013
*ex 2921 51 19	40	*p*-Phenylenediamine	0 %	31.12.2011
*ex 2921 51 19	50	Mono- and dichloroderivatives of *p*-phenylenediamine and *p*-diaminotoluene	0 %	31.12.2013
*ex 2921 59 90	10	Mixture of isomers of 3.5-diethyltoluenediamine	0 %	31.12.2013
ex 2921 59 90	30	3,3'-dichlorobenzidine dihydrochloride	0 %	31.12.2012
*ex 2921 59 90	40	4,4'-Diaminostilbene-2,2'-disulphonic acid	0 %	31.12.2013
*ex 2922 19 80	10	4,4-Dimethoxybutylamine	0 %	31.12.2013
*ex 2922 19 80	30	*N,N, N ',N '*-Tetramethyl-2,2'-oxybis(ethylamine)	0 %	31.12.2013
*ex 2922 19 80	50	2-(2-Methoxyphenoxy)ethylamine	0 %	31.12.2013
*ex 2922 19 80	60	*N, N, N '*-trimethyl-*N '*-(2-hydroxy-ethyl) 2,2'-oxybis(ethylamine)	0 %	31.12.2013
ex 2922 19 80	70	D-(-)-threo-2-amino-1-(*p*-nitrophenyl) propane-1,3-diol	0 %	31.12.2011
*ex 2922 21 00	10	2-Amino-5-hydroxynaphthalene-1,7-disulphonic acid and its salts, of a purity by weight of 60 % or more	0 %	31.12.2013
*ex 2922 21 00	30	6-Amino-4-hydroxynaphthalene-2-sulphonic acid	0 %	31.12.2013
*ex 2922 21 00	40	7-Amino-4-hydroxynaphthalene-2-sulphonic acid	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2922 21 00	50	Sodium hydrogen 4-amino-5-hydroxy-naphthalene-2,7-disulphonate	0 %	31.12.2013
*ex 2922 29 00	10	2-Methyl-*N*-phenyl-*p*-anisidine	0 %	31.12.2013
*ex 2922 29 00	20	3-Aminophenol	0 %	31.12.2013
*ex 2922 29 00	25	5-Amino-*o*-cresol	0 %	31.12.2013
ex 2922 29 00	35	2-Amino-4,6-dinitrophenol sodium salt, containing at least 20 % water	0 %	31.12.2011
*ex 2922 29 00	45	Anisidines	0 %	31.12.2013
▼M26				
ex 2922 29 00	46	*p*-Anisidine-3-sulphonic acid	0 %	1.7.2009-31.12.2013
▼M25				
*ex 2922 29 00	50	6-Methoxy-*m*-toluidine	0 %	31.12.2013
*ex 2922 29 00	70	4-Nitro-*o*-anisidine	0 %	31.12.2013
*ex 2922 29 00	80	3-Diethylaminophenol	0 %	31.12.2013
*ex 2922 39 00	10	1-Amino-4-bromo-9,10-dioxoanthracene-2-sulphonic acid and its salts	0 %	31.12.2013
ex 2922 39 00	70	*p*-[(2-Chloroethyl)ethylamino]benzaldehyde	0 %	31.12.2011
*ex 2922 43 00	10	Anthranilic acid	0 %	31.12.2013
*ex 2922 49 85	10	Ornithine aspartate (INNM)	0 %	31.12.2013
*ex 2922 49 85	40	Norvaline	0 %	31.12.2013
*ex 2922 49 85	50	D-(-)-Dihydrophenylglycine	0 %	31.12.2013
*ex 2922 49 85	60	Ethyl-4-dimethylaminobenzoate	0 %	31.12.2012
*ex 2922 49 85	70	2-Ethylhexyl-4-dimethylaminobenzoate	0 %	31.12.2013
*ex 2922 50 00	70	2-(1-Hydroxycyclohexyl)-2-(4-methoxy-phenyl)ethylammonium acetate	0 %	31.12.2013
*ex 2923 90 00	10	Tetramethylammonium hydroxide, in the form of an aqueous solution containing: — 25 (± 0,5) % by weight of tetramethy-lammonium hydroxide, — 500 mg/kg or less of carbonate, — 200 mg/kg or less of chloride and — 5 mg/kg or less of potassium	0 %	31.12.2013
*ex 2923 90 00	25	Tetrakis(dimethylditetradecylammonium) molybdate	0 %	31.12.2013
ex 2923 90 00	35	Tetrabutylammonium fluoride trihydrate	0 %	31.12.2011
*ex 2923 90 00	70	Tetrapropylammonium hydroxide, in the form of an aqueous solution containing: — 40 (± 2) % by weight of tetrapropy-lammonium hydroxide, — 0,3 % by weight or less of carbonate, — 0,1 % by weight or less of tripropy-lamine, — 500 mg/kg or less of bromide and — 25 mg/kg or less of potassium and sodium taken together	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2923 90 00	80	Diallyldimethylammonium chloride, in the form of an aqueous solution containing by weight 63 % or more but not more than 67 % of diallyldimethylammonium chloride	0 %	31.12.2013
*ex 2924 19 00	10	2-Acrylamido-2-methylpropanesulphonic acid and its sodium or ammonium salts	0 %	31.12.2013
*ex 2924 19 00	30	Methyl 2-acetamido-3-chloropropionate	0 %	31.12.2013
*ex 2924 19 00	40	*N*-(1,1-Dimethyl-3-oxobutyl)acrylamide	0 %	31.12.2013
*ex 2924 19 00	50	Acrylamide	0 %	31.12.2013
*ex 2924 19 00	60	*N,N*-Dimethylacrylamide	0 %	31.12.2011
*ex 2924 19 00	70	Methylcarbamate	0 %	31.12.2013
*ex 2924 21 00	10	4,4'-Dihydroxy-7,7'-ureylenedi (naphthalene-2-sulfonic acid) and its sodium salts	0 %	31.12.2013
*ex 2924 29 98	10	Alachlor (ISO)	0 %	31.12.2013
*ex 2924 29 98	15	Acetochlor (ISO)	0 %	31.12.2013
*ex 2924 29 98	25	3'-Diethylaminoacetanilide	0 %	31.12.2013
*ex 2924 29 98	30	Propachlor (ISO)	0 %	31.12.2013
*ex 2924 29 98	65	2-(4-Hydroxyphenyl)acetamide	0 %	31.12.2013
*ex 2924 29 98	75	3-Amino-*p*-anisanilide	0 %	31.12.2013
*ex 2924 29 98	80	5'-Chloro-3-hydroxy-2',4'-dimethoxy-2-naphtanilide	0 %	31.12.2013
*ex 2924 29 98	85	*p*-Aminobenzamide	0 %	31.12.2013
*ex 2924 29 98	86	Anthranilamide of a purity by weight of 99,5 % or more	0 %	31.12.2012
*ex 2924 29 98	87	Paracetamol (INN)	0 %	31.12.2013
*ex 2924 29 98	88	5'-chloro-3-hydroxy-2'-methyl-2-naphthanilide	0 %	31.12.2013
*ex 2924 29 98	89	Flutolanil (ISO)	0 %	31.12.2013
*ex 2924 29 98	91	3-Hydroxy-2'-methoxy-2-naphthanilide	0 %	31.12.2013
*ex 2924 29 98	92	3-Hydroxy-2-naphthanilide	0 %	31.12.2013
*ex 2924 29 98	93	3-Hydroxy-2'-methyl-2-naphthanilide	0 %	31.12.2013
*ex 2924 29 98	94	2'-Ethoxy-3-hydroxy-2-naphthanilide	0 %	31.12.2013
*ex 2924 29 98	96	4'-Chloro-3-hydroxy-2',5'-dimethoxy-2-naphthanilide	0 %	31.12.2013
*ex 2924 29 98	97	1,1-Cyclohexanediacetic acid monoamide	0 %	31.12.2013
*ex 2925 11 00	20	Saccharin and its sodium salt	0 %	31.12.2013
*ex 2925 19 95	10	*N*-Phenylmaleimide	0 %	31.12.2013
*ex 2925 29 00	10	Dicyclohexylcarbodiimide	0 %	31.12.2013
*ex 2926 90 95	20	2-(*m*-Benzoylphenyl)propiononitrile	0 %	31.12.2013
▼M26				
ex 2926 90 95	35	2-Bromo-2(bromomethyl)pentanedinitrile	0 %	1.7.2009-31.12.2013
▼M25				
*ex 2926 90 95	45	2-Cyanoacetamide	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2926 90 95	50	Alkyl or alkoxyalkyl esters of cyanoacetic acid	0 %	31.12.2013
ex 2926 90 95	55	Methyl-2-cyano-2-phenylbutyrate	0 %	31.12.2011
*ex 2926 90 95	60	Cyanoacetic acid in crystalline form	0 %	31.12.2013
ex 2926 90 95	61	*m*-(1-Cyanoethyl)benzoic acid	0 %	31.12.2011
*ex 2926 90 95	65	Malononitrile	0 %	31.12.2013
*ex 2926 90 95	80	Ethyl 2-cyano-2-phenylbutyrate	0 %	31.12.2013
*ex 2926 90 95	81	4-Aminobenzonitrile	0 %	31.12.2013
*ex 2926 90 95	86	Ethylenediaminetetraacetonitrile	0 %	31.12.2013
*ex 2926 90 95	87	Nitrilotriacetonitrile	0 %	31.12.2013
*ex 2926 90 95	88	1,3-Propylenediaminetetraacetonitrile	0 %	31.12.2013
*ex 2926 90 95	89	Butyronitrile	0 %	31.12.2013
*ex 2927 00 00	10	2,2'-Dimethyl-2,2'-azodipropionamidine dihydrochloride	0 %	31.12.2013
*ex 2927 00 00	20	4-Anilino-2-methoxybenzenediazonium hydrogen sulphate	0 %	31.12.2013
*ex 2927 00 00	30	4'-Aminoazobenzene-4-sulphonic acid	0 %	31.12.2013
*ex 2927 00 00	40	2-Hydroxynaphthalene-1-diazonium-4-sulphonate	0 %	31.12.2013
*ex 2927 00 00	50	2-Hydroxy-6-nitronaphthalene-1-diazonium-4-sulphonate, of a purity by weight of 60 % or more	0 %	31.12.2013
*ex 2927 00 00	60	4,4'-Dicyano-4,4'-azodivaleric acid	0 %	31.12.2013
*ex 2928 00 90	10	3,3'-*Bis*(3,5-di-*tert*-butyl-4-hydroxyphenyl)-*N,N*' bipropionamide	0 %	31.12.2013
ex 2928 00 90	15	1,1'-(Hydroxyimino)*bis*-(2-propanol)	0 %	31.12.2011
*ex 2928 00 90	20	2.4,6-Trichlorophenylhydrazine	0 %	31.12.2013
*ex 2928 00 90	40	*O*-Ethylhydroxylamine, in the form of an aqueous solution	0 %	31.12.2013
*ex 2928 00 90	60	Adipohydrazide	0 %	31.12.2013

▼M26

ex 2928 00 90	70	Butanone oxime	0 %	1.7.2009-31.12.2013

▼M25

*ex 2928 00 90	80	Cyflufenamid (ISO)	0 %	31.12.2013
*ex 2929 10 00	10	Methylenedicyclohexyl diisocyanates	0 %	31.12.2013
*ex 2929 10 00	40	*m*-Isopropenyl-*α,* *α*-dimethylbenzyl isocyanate	0 %	31.12.2013
*ex 2929 10 00	50	*m*-Phenylenediisopropylidene diisocyanate	0 %	31.12.2013
*ex 2929 10 00	60	Trimethylhexamethylene diisocyanate, mixed isomers	0 %	31.12.2013
*ex 2929 10 00	80	1,3-*Bis*(isocyanatomethyl) benzene	0 %	31.12.2011
ex 2930 20 00	10	Prosulfocarb (ISO)	0 %	31.12.2012
*ex 2930 90 85	15	Ethoprophos (ISO)	0 %	31.12.2013
*ex 2930 90 85	25	Thiophanate-methyl (ISO)	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2930 90 85	30	4-(4-Isopropoxyphenylsulphonyl)phenol	0 %	31.12.2013
ex 2930 90 85	35	Glutathione	0 %	31.12.2011
*ex 2930 90 85	40	3,3'-Thiodi(propionic acid)	0 %	31.12.2013
*ex 2930 90 85	45	2-[(*p*-Aminophenyl)sulphonyl]ethyl hydrogen sulphate	0 %	31.12.2013
*ex 2930 90 85	60	Methyl phenyl sulphide	0 %	31.12.2013
ex 2930 90 85	66	Diphenyl sulphide	0 %	31.12.2012
ex 2930 90 85	67	3-Bromomethyl-2-chloro-4-(methylsulphonyl)-benzoic acid	0 %	31.12.2012
ex 2930 90 85	68	Clethodim (ISO)	0 %	31.12.2012
ex 2930 90 85	69	2-Amino-4-methylsulphonyl-*N*-methylaniline	0 %	31.12.2012
ex 2930 90 85	71	Triphenylsulphonium chloride	0 %	31.12.2012
*ex 2930 90 85	76	2,2'-Dithiodi(benzoic acid)	0 %	31.12.2013
*ex 2930 90 85	77	4-[4-(2-Propenyloxy)phenylsulphonyl] phenol	0 %	31.12.2013
ex 2930 90 85	78	4-Mercaptomethyl-3,6-dithia-1,8-octanedithiol	0 %	31.12.2011
*ex 2930 90 85	80	Captan (ISO)	0 %	31.12.2013
ex 2930 90 85	82	Sodium toluene-4-sulphinate	0 %	31.12.2012
ex 2930 90 85	83	Methyl-*p*-tolyl sulphone	0 %	31.12.2012
*ex 2930 90 85	86	4-Hydroxybenzenethiol	0 %	31.12.2013
*ex 2930 90 85	87	3-Sulphinobenzoic acid	0 %	31.12.2013
ex 2930 90 85	89	Potassium- or sodium-salt of O-ethyl-, O-isopropyl-, O-butyl-, O-isobutyl- or O-pentyl-dithiocarbonates	0 %	31.12.2011
*2931 00 10		Dimethyl methylphosphonate	0 %	31.12.2013
*ex 2931 00 95	05	Butylethylmagnesium, in the form of a solution in heptane	0 %	31.12.2013

▼M26

ex 2931 00 95	20	Methylcyclopentadienyl manganese tricarbonyl containing not more than 4,9 % by weight of cyclopentadienyl manganese tricarbonyl	0 %	1.7.2009-31.12.2013

▼M25

*ex 2931 00 95	40	*N*-(Phosphonomethyl)iminodiacetic acid	0 %	31.12.2013
*ex 2931 00 95	50	*Bis*(2.4,4-trimethylpentyl)phosphinic acid	0 %	31.12.2013
*ex 2931 00 95	85	Tributyl(tetradecyl)phosphonium chloride, whether or not in the form of an aqueous solution	0 %	31.12.2013
*ex 2931 00 95	86	Mixture of the isomers 9-icosyl-9-phosphabicyclo[3.3.1]nonane and 9-icosyl-9-phosphabicyclo[4.2.1]nonane	0 %	31.12.2013
*ex 2931 00 95	87	Tris(4-methylpentan-2-oximino)methylsilane	0 %	31.12.2013
ex 2931 00 95	91	Trimethylsilane	0 %	31.12.2011

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2931 00 95	96	3-(Hydroxyphenylphosphinoyl)propionic acid	0 %	31.12.2013
*ex 2931 00 95	97	Potassium 4-tolylphosphinate, in the form of an aqueous solution	0 %	31.12.2013
▼M26				
ex 2932 13 00	10	Tetrahydrofurfuryl alcohol	0 %	1.7.2009-31.12.2013
ex 2932 19 00	40	Furan of a purity by weight of 99 % or more	0 %	1.7.2009-31.12.2013
ex 2932 19 00	41	2,2 di(tetrahydrofuryl)propane	0 %	1.7.2009-31.12.2013
▼M25				
*ex 2932 19 00	70	Furfurylamine	0 %	31.12.2013
*ex 2932 19 00	75	Tetrahydro-2-methylfuran	0 %	31.12.2013
*ex 2932 29 85	10	2'-Anilino-6'-[ethyl(isopentyl)amino]-3'-methylspiro[isobenzofuran-1(3*H*),9'-xanthen]-3-one	0 %	31.12.2013
*ex 2932 29 85	35	6'-Diethylamino-3'-methyl-2'-(2,4-xylidino)spiro[isobenzofuran-1(3*H*),9'-xanthen]-3-one	0 %	31.12.2013
*ex 2932 29 85	55	6-Dimethylamino-3,3-*bis*(4-dimethylamino-phenyl)phthalide	0 %	31.12.2013
*ex 2932 29 85	60	6'-(Dibutylamino)-3'-methyl-2'-(phenylamino)-spiro[isobenzofuran-1(3*H*),9'-[9*H*]xanthen]-3-one	0 %	31.12.2011
*ex 2932 29 85	70	3',6'-*Bis*(ethylamino)-2',7'-dimethylspiro[isobenzofuran-1(3*H*),9'-[9*H*]-xanthen]-3-one	0 %	31.12.2013
ex 2932 29 85	71	6'-(Diethylamino)-3'-methyl-2'-(phenylamino)-spiro[isobenzofuran-1(3*H*),9'-[9*H*]xanthen]-3-one	0 %	31.12.2011
ex 2932 29 85	72	2'-[*Bis*(phenylmethyl)amino]-6'-(diethylamino)-spiro[isobenzofuran-1(3*H*),9'-[9*H*]xanthen]-3-one	0 %	31.12.2011
*ex 2932 29 85	80	Gibberellic acid with a minimum purity by weight of 88 %	0 %	31.12.2013
*ex 2932 29 85	84	Decahydro-3a,6.6,9a-tetramethylnaphth [2,1-b] furan-2 (1H)-one	0 %	31.12.2013
*ex 2932 29 85	85	Hexan-4-olide	0 %	31.12.2013
*ex 2932 99 00	10	Bendiocarb (ISO)	0 %	31.12.2013
*ex 2932 99 00	30	Carbofuran (ISO)	0 %	31.12.2013
▼M26				
ex 2932 99 00	35	1,2,3-trideoxy-4,6:5,7-bis-O-[(4-propyl-phenyl)methylene]-nonitol	0 %	1.7.2009-31.12.2013
▼M25				
*ex 2932 99 00	40	1.3:2,4-*Bis*-O-(3,4-dimethylbenzylidene)-D-glucitol	0 %	31.12.2013
*ex 2932 99 00	70	1.3:2,4-*bis*-*O*-Benzylidene-*D*-glucitol	0 %	31.12.2011
*ex 2932 99 00	75	3-(3,4-Methylenedioxyphenyl)-2-methyl-propanal	0 %	31.12.2011
*ex 2932 99 00	80	1.3:2,4-*bis*-*O*-(4-Methylbenzylidene)-*D*-glucitol	0 %	31.12.2011

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2933 19 90	30	3-Methyl-1-*p*-tolyl-5-pyrazolone	0 %	31.12.2013
*ex 2933 19 90	40	Edaravone (INN)	0 %	31.12.2013
*ex 2933 19 90	50	Fenpyroximate (ISO)	0 %	31.12.2013
*ex 2933 19 90	60	Pyraflufen-ethyl (ISO)	0 %	31.12.2013
*ex 2933 19 90	70	4,5-Diamino-1-(2-hydroxyethyl)-pyrazol-sulphate	0 %	31.12.2013
*ex 2933 21 00	10	Hydantoin	0 %	31.12.2013
ex 2933 21 00	50	1-Bromo-3-chloro-5,5-dimethylhydantoin	0 %	31.12.2011
*ex 2933 21 00	60	DL-*p*-Hydroxyphenylhydantoin	0 %	31.12.2011
*ex 2933 21 00	70	*α*-(4-Methoxybenzoyl)-*α*-(1-benzyl-5-ethoxy-3-hydantoinyl)-2-chloro-5-dodecy-loxycarbonylacetanilide	0 %	31.12.2011
*ex 2933 29 90	40	Triflumizole (ISO)	0 %	31.12.2013
*ex 2933 29 90	50	1,3-Dimethylimidazolidin-2-one	0 %	31.12.2013
*ex 2933 39 99	15	Pyridine-2,3-dicarboxylic acid	0 %	31.12.2013
*ex 2933 39 99	25	Imazethapyr (ISO)	0 %	31.12.2013
*ex 2933 39 99	35	Aminopyralid (ISO)	0 %	31.12.2013
*ex 2933 39 99	40	2-Chloropyridine	0 %	31.12.2013
ex 2933 39 99	50	*N*-Fluoro-2,6-dichloropyridinium tetrafluor-oborate	0 %	31.12.2011
*ex 2933 39 99	60	2-Fluoro-6-(trifluoromethyl)pyridine	0 %	31.12.2013
*ex 2933 39 99	65	Acetamiprid (ISO)	0 %	31.12.2013
*ex 2933 39 99	75	Picolinafen (ISO)	0 %	31.12.2013
*ex 2933 49 10	10	Quinmerac (ISO)	0 %	31.12.2013

▼M26

ex 2933 49 10	20	3-Hydroxy-2-methylquinoline-4-carboxylic acid	0 %	1.7.2009-31.12.2013

▼M25

*ex 2933 49 90	50	Methyl 2-[(*S*)-3-{(*E*)-3-[2-(7-chloro-2-quinolyl)vinyl]phenyl}-3-hydroxypropyl] benzoate monohydrate	0 %	31.12.2013
*ex 2933 49 90	60	5.6,7,8-Tetrahydroquinoline	0 %	31.12.2013
*ex 2933 49 90	70	Quinolin-8-ol	0 %	31.12.2013
ex 2933 52 00	10	Malonylurea (barbituric acid)	0 %	31.12.2011
*ex 2933 59 95	15	(2*R*)-4-Oxo-4-[3-(trifluoromethyl)-5,6-dihydro[1.2,4]triazolo[4,3-*a*] pyrazin-7(8*H*)-yl]-1-(2.4,5-trifluorophenyl)butyl-2-ammonium phosphate monohydrate	0 %	31.12.2013
*ex 2933 59 95	20	2,4-Diamino-6-chloropyrimidine	0 %	31.12.2013
*ex 2933 59 95	25	2,5-Diamino-4,6-dihydroxypyrimidine monohydrochloride monohydrate	0 %	31.12.2013
*ex 2933 59 95	30	Mepanipyrim (ISO)	0 %	31.12.2013
ex 2933 59 95	35	4-Amino-2,6-dichloropyrimidine	0 %	31.12.2011
*ex 2933 59 95	40	Guanine	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2933 59 95	60	2,6-Dichloro-4,8-dipiperidinopyrimido[5,4-*d*]pyrimidine	0 %	31.12.2013
*ex 2933 59 95	70	*N*-(4-Ethyl-2,3-dioxopiperazin-1-ylcarbonyl)-D-2-phenylglycine	0 %	31.12.2013
*ex 2933 69 80	20	1.3,5-Tris[(3,5-di-*tert*-butyl-4-hydroxy-phenyl)methyl]-1.3,5-triazine-2.4,6(1*H*,3*H*,5*H*)-trione	0 %	31.12.2013
*ex 2933 69 80	50	1.3,5-Tris(2,3-dibromopropyl)-1.3,5-triazinane-2.4,6-trione	0 %	31.12.2013
*ex 2933 69 80	80	Tris(2-hydroxyethyl)-1.3,5-triazinetrione	0 %	31.12.2013
*ex 2933 79 00	10	Ezetimibe (INN)	0 %	31.12.2013
ex 2933 79 00	30	5-Vinyl-2-pyrrolidone	0 %	31.12.2012
*ex 2933 79 00	40	3,3-pentamethylene-4-butyrolactam	0 %	31.12.2013

▼M26

ex 2933 79 00	50	6-Bromo-3-methyl-3H-dibenz(f,ij)isoquinoline-2,7-dione	0 %	1.7.2009-31.12.2013

▼M25

*ex 2933 99 80	10	2-(2*H*-Benzotriazol-2-yl)-4,6-di-*tert*-butylphenol	0 %	31.12.2013
*ex 2933 99 80	15	2-(2*H*-Benzotriazol-2-yl)-4,6-di-*tert*-pentylphenol	0 %	31.12.2013
*ex 2933 99 80	20	2-(2*H*-Benzotriazol-2-yl)-4,6-*bis*(1-methyl-1-phenylethyl)phenol	0 %	31.12.2013
*ex 2933 99 80	25	6,6'-Di-2*H*-benzotriazol-2-yl-4,4'-*bis*(1.1,3,3-tetramethylbutyl)-2,2'-methylenediphenol	0 %	31.12.2013
*ex 2933 99 80	30	Quizalofop-P-ethyl (ISO)	0 %	31.12.2013
*ex 2933 99 80	40	*trans*-4-Hydroxy-L-proline	0 %	31.12.2013
*ex 2933 99 80	45	Maleic hydrazide (ISO)	0 %	31.12.2013
*ex 2933 99 80	50	Metconazole (ISO)	3,2 %	31.12.2013
*ex 2933 99 80	60	1,3-*Bis*(3-isocyanatomethylphenyl)-1,3-diazetidine-2,4-dione (dimeric 2,4-toluene diisocyanate)	0 %	31.12.2013
*ex 2933 99 80	65	Candesartan cilexetil (INNM)	0 %	31.12.2013
*ex 2933 99 80	69	[(3R)-4-(4-chlorobenzyl)-7-fluoro-5-(methylsulphonyl)-1.2,3,4-tetrahydrocyclopenta[*b*]indole-3-yl]acetic acid	0 %	31.12.2011
*ex 2933 99 80	70	6,7-Dihydro-5*H*-cyclopenta[*b*]pyridine	0 %	31.12.2013
*ex 2933 99 80	71	10-methoxyiminostilbene	0 %	31.12.2013
*ex 2933 99 80	72	1.4,7-Trimethyl-1.4,7-Triazacyclononane	0 %	31.12.2013
*ex 2933 99 80	73	5-(acetoacetylamino)benzimidazolone	0 %	31.12.2013
*ex 2933 99 80	74	Imidazo[1,2-b] pyridazine-hydrochloride	0 %	31.12.2013
*ex 2933 99 80	76	Manganese(2+), *bis*(octahydro-1.4,7-trimethyl-1H-1.4,7-triazonine-N1,N4,N7) tri-μ-oxodi-, acetate (1:2)	0 %	31.12.2013
*ex 2933 99 80	77	Manganese(2+), *bis*(octahydro-1.4,7-trimethyl-1H-1.4,7-triazonine-N1,N4,N7) tri-μ-oxodi-, sulphate (1:1)	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2933 99 80	78	3-Amino-3-azabicyclo (3.3.0) octane hydrochloride	0 %	31.12.2013
*ex 2933 99 80	81	1.2,3-Benzotriazole	0 %	31.12.2011
*ex 2933 99 80	82	Tolytriazol	0 %	31.12.2013
*ex 2933 99 80	88	2,6-Dichloroquinoxaline	0 %	31.12.2013
*ex 2933 99 80	89	Carbendazim (ISO)	0 %	31.12.2013
*ex 2934 10 00	10	Hexythiazox (ISO)	0 %	31.12.2013
*ex 2934 10 00	20	2-(4-Methylthiazol-5-yl)ethanol	0 %	31.12.2013
*ex 2934 10 00	40	(Z)-2-(2-tert-butoxycarbonylaminothiazol-4-yl)-2-pentenoic acid	0 %	31.12.2013
*ex 2934 10 00	50	2-(2-Formylaminothiazol-4-yl)acetic acid	0 %	31.12.2013
*ex 2934 20 80	10	4-Chloro-1,3-benzothiazol-2(3*H*)-one	0 %	31.12.2013
ex 2934 20 80	40	1,2-Benzisothiazol-3(2H)-one (Benzisothiazolinone (BIT))	0 %	31.12.2012
*ex 2934 20 80	50	S-(1,3-Benzothiazol-2-yl)-(Z)-2-(2-aminothiazol-4-yl)-2-(acetyloxyimino)thioacetate	0 %	31.12.2013
*ex 2934 99 90	15	Carboxin (ISO)	0 %	31.12.2013
*ex 2934 99 90	35	Dimethenamide (ISO)	0 %	31.12.2013
*ex 2934 99 90	45	Tris(2,3-epoxypropyl)-1.3,5-triazinanetrione	0 %	31.12.2013
*ex 2934 99 90	55	Olmesartan medoxomil (INN)	0 %	31.12.2013
*ex 2934 99 90	60	DL-Homocysteine thiolactone hydrochloride	0 %	31.12.2013
*ex 2934 99 90	65	Methyl 3-aminothiophene-2-carboxylate	0 %	31.12.2013

▼M26

ex 2934 99 90	66	Tetrahydrothiophene-1,1-dioxide	0 %	1.7.2009-31.12.2013

▼M25

*ex 2934 99 90	72	1-[3-(5-Nitro-2-furyl)allylideneamino] imidazolidine-2,4-dione	0 %	31.12.2013
ex 2934 99 90	74	2-Isopropylthioxanthone	0 %	31.12.2012
ex 2934 99 90	75	(4*R-cis*)-1,1-Dimethylethyl-6-[2[2-(4-fluorophenyl)-5-(1-isopropyl)-3-phenyl-4-[(phenylamino)carbonyl]-1*H*-pyrrol-1-yl] ethyl]-2,2-dimethyl-1,3-dioxane-4-acetate	0 %	31.12.2011
ex 2934 99 90 ex 3204 20 00	76 10	2,5-Thiophenediylbis(5-*tert*-butyl-1,3-benzoxazole)	0 %	31.12.2011
ex 2934 99 90	77	Potassium 5-methyl-1.3,4-oxadiazole-2-carboxylate	0 %	31.12.2011
ex 2934 99 90	78	1.2,4-Thiadiazole-3-acetic acid 5-[(ethoxycarbonyl)amino]- methyl ester	0 %	31.12.2012
*ex 2934 99 90	79	Thiophen-2-ethanol	0 %	31.12.2013
*ex 2934 99 90	81	2-(5-Amino-1.2,4-thiadiazol-3-yl)-(Z)-2-methoxyiminoacetic acid	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 2934 99 90	82	2-Methyl-1-[4-(methylthio)phenyl]-2-morpholinopropan-1-one	0 %	31.12.2013
*ex 2935 00 90	15	Flupyrsulfuron-methyl-sodium (ISO)	0 %	31.12.2013
*ex 2935 00 90	20	Toluenesulphonamides	0 %	31.12.2013
*ex 2935 00 90	25	Triflusulfuron-methyl (ISO)	0 %	31.12.2013
*ex 2935 00 90	35	Chlorsulfuron (ISO)	0 %	31.12.2013
*ex 2935 00 90	45	Rimsulfuron (ISO)	0 %	31.12.2013
*ex 2935 00 90	50	4,4'-Oxydi(benzenesulphonohydrazide)	0 %	31.12.2013
*ex 2935 00 90	55	Thifensulfuron-methyl (ISO)	0 %	31.12.2013
*ex 2935 00 90	65	Tribenuron-methyl (ISO)	0 %	31.12.2013
*ex 2935 00 90	75	Metsulfuron-methyl (ISO)	0 %	31.12.2013
ex 2935 00 90	76	4-Toluenesulphonyl urea	0 %	31.12.2011
*ex 2935 00 90	81	4-Amino-*N*-(4-aminophenyl)benzenesulphonamide	0 %	31.12.2013
*ex 2935 00 90	82	*N*-(5,7-Dimethoxy[1.2,4]triazolo[1,5-a] pyrimidin-2-yl)-2-methoxy-4-(trifluoromethyl)pyridine-3-sulphonamide	0 %	31.12.2013
*ex 2935 00 90	83	3-amino-N, N-diethyl-4-methoxybenzenesulphonamide	0 %	31.12.2013
*ex 2935 00 90	85	*N*-[4-(Isopropylaminoacetyl)phenyl]methanesulphonamide hydrochloride	0 %	31.12.2013
*ex 2935 00 90	86	4-(*m*-Tolylamino)pyridine-3-sulphonamide	0 %	31.12.2013
*ex 2935 00 90	88	N-(2-(4-Amino-N-ethyl-m-toluidino)ethyl) methanesulphonamide sesquisulphate monohydrate	0 %	31.12.2013
ex 2935 00 90	89	3-(3-Bromo-6-fluoro-2-methylindol-1-ylsulphonyl)-*N, N*-dimethyl-1.2,4-triazol-1-sulphonamide	0 %	31.12.2011
*ex 2938 90 90	10	Hesperidin	0 %	31.12.2013
*3201 20 00		Wattle extract	0 %	31.12.2013
*ex 3201 90 90	20	Tanning extracts derived from gambier and myrobalan fruits	0 %	31.12.2013
ex 3204 13 00	10	C.I. Basic Red 1 dye	0 %	31.12.2011
ex 3204 15 00	10	Dye C.I. Vat Orange 7 (C.I. Pigment Orange 43)	0 %	31.12.2012
*ex 3204 15 00	60	Dyestuff C.I. Vat Blue 4	0 %	31.12.2013
*ex 3204 17 00	10	Dye C.I. Pigment Yellow 81	0 %	31.12.2013
*ex 3204 17 00	30	Dye C.I. Pigment Yellow 97	0 %	31.12.2012
*ex 3204 19 00	15	4-{4-[3-(4-Methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo [*h*]indeno[2,1-*f*]chromen-3-yl]phenyl}morpholine	0 %	31.12.2013
*ex 3204 19 00	25	Cyclohexyl 8-methyl-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate	0 %	31.12.2013
*ex 3204 19 00	65	6-Methoxy-7-morpholino-13-ethyl-13-methoxy-3,3-*bis*-(4-methoxyphenyl)-3,13-dihydrobenzo[h]indeno[2,1-f]chromene	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3204 19 00	70	Dye C.I. Solvent Red 49	0 %	31.12.2013
*ex 3204 19 00	75	6,7-Dimethoxy-13-ethyl-13-methoxy-3,3-*bis*-(4-methoxyphenyl)-3,13-dihydrobenzo[h]indeno[2,1-f]chromene	0 %	31.12.2013
*ex 3204 19 00	80	((R) and (S) isomers of 6.7-Dimethoxy-13-ethyl-13-[2-(2-methoxyethoxy)-ethoxy]-3-(4-methoxyphenyl)-3-(4-fluorophenyl)-3,13-dihydrobenzo[h]indeno[2,1-f] chromene	0 %	31.12.2013
*ex 3204 19 00	81	6,11-Difluoro-3,3-di-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[*h*] indeno[2,1-f]chromene	0 %	31.12.2013
*ex 3204 19 00	82	3-(4-Fluorophenyl)-3-(4-piperidinophenyl)-13,13-dimethyl-3,13-dihydrobenzo[*h*] indeno[2,1-f]chromene	0 %	31.12.2013
*ex 3204 19 00	83	6,7-Dimethoxy-11-cyano-3,3-di-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[*h*]indeno[2,1-f]chromene	0 %	31.12.2013
*ex 3205 00 00	10	Aluminium lakes prepared from dyes for use in the manufacture of pigments for the pharmaceutical industry (1)	0 %	31.12.2013
*ex 3206 11 00	10	Titanium dioxide coated with isopropoxytitanium triisostearate, containing by weight 1,5 % or more but not more than 2,5 % of isopropoxytitanium triisostearate	0 %	31.12.2013
*ex 3206 42 00	10	Lithopone	0 %	31.12.2013
*3206 50 00		Inorganic products of a kind used as luminophores	0 %	31.12.2013
*ex 3207 30 00	10	Preparation containing: — not more than 85 % by weight of silver, — not less than 2 % by weight of palladium, — barium titanate, — terpineol, and — ethyl cellulose, used for screen printing in the manufacture of multilayer ceramic capacitors (1)	0 %	31.12.2013

▼M26

ex 3207 40 80	20	Glass flakes coated with silver, of an average diameter of 40 (± 10) µm	0 %	1.7.2009-31.12.2013

▼M25

*ex 3207 40 80	30	Glass frit, for use in the manufacture of cathode-ray tubes (1)	0 %	31.12.2013
*ex 3208 10 90 ex 3707 90 90	10 60	Anti-reflection coating, consisting of an ester based polymer modified with a chromophore group, in the form of a solution of either 2-methoxy-1-propanol, 2-methoxy-1-methylethyl acetate or methyl-2-hydroxyisobutyrate, containing by weight not more than 10 % of polymer	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3208 20 10	10	Copolymer of *N*-vinylcaprolactam, *N*-vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate, in the form of a solution in ethanol containing by weight 34 % or more but not more than 40 % of copolymer	0 %	31.12.2013
▼M26				
ex 3208 20 10	20	Immersion topcoat solution containing by weight 2 % or more but not more than 15 % of acrylate-methacrylate-alkenesulphonate-copolymers with fluorinated side chains, in a solution of n-butanol and/or 4-methyl-2-pentanol and/or diisoamylether	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3208 20 10	40	Poly(1H,1H-heptafluorobutyl methacrylate) dissolved in a mixture of methyl perfluorobutyl ether and methyl perfluoroisobutyl ether	0 %	31.12.2011
*ex 3208 90 19	10	Copolymer of maleic acid and methyl vinyl ether, monoesterified with ethyl and/or isopropyl and/or butyl groups, in the form of a solution in ethanol, ethanol and butanol, isopropanol or isopropanol and butanol	0 %	31.12.2013
ex 3208 90 19 ex 3902 90 90	15 94	Modified, chlorinated polyolefins, whether or not in a solution or dispersion	0 %	31.12.2013
*ex 3208 90 19	40	Polymer of methylsiloxane, in the form of a solution in a mixture of acetone, butanol, ethanol and isopropanol, containing by weight 5 % or more but not more than 11 % of polymer of methylsiloxane	0 %	31.12.2013
▼M26				
ex 3208 90 19	50	Solution containing by weight: — (65 ± 10) % of γ-butyrolactone, — (30 ± 10) % of polyamide resin, — (3,5 ± 1,5) % of naphthoquinone ester derivative, and — (1,5 ± 0,5) % of arylsilicic acid.	0 %	1.7.2009-31.12.2013
▼M25				
ex 3208 90 19	60	Copolymer of hydroxystyrene and either styrene or alkoxystyrene or both, dissolved in ethyl lactate	0 %	31.12.2011
ex 3208 90 19	75	Acenaphthalene copolymer in ethyl lactate solution	0 %	31.12.2012
*ex 3208 90 19	85	Mixture containing by weight: — 30~45 % Polyamide resin; — 2~10 % Diazonaphthoquinone; — 50~65 % γ-Butyrolactone.	0 %	31.12.2013
*ex 3208 90 91	10	Preparation on the basis of polyhydroxyamide containing at least naphthoquinone ester derivate or tosylate dissolved in γ-butyrolactone and/or 2-methoxy-1-methylethyl acetate	0 %	31.12.2012

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3208 90 99	10	Solution based on chemically modified natural polymers, containing two or more of the following dyes: — methyl 8'-acetoxy-1.3,3.5,6-pentamethyl-2,3-dihydrospiro[1*H*-indole-2,3'-naphtho[2,1-*b*][1,4]oxazine]-9'-carboxylate, — methyl 6-(isobutyryloxy)-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate, — 13-isopropyl-3,3-*bis*(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromen-13-ol, — ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate, — 13-ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo[*h*]indeno [2,1-*f*]chromen-13-ol	0 %	31.12.2013
*ex 3208 90 99	20	Solution based on chemically modified natural polymers, containing two or more of the following dyes: — 4-[4-(13,13-dimethyl-3-phenyl-3,13-dihydrobenzo [*h*]indeno[2,1-*f*]chromen-3-yl)phenyl]morpholine, — 4-{4-[3-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo [*h*]indeno [2,1-*f*]chromen-3-yl]phenyl} morpholine, — cyclohexyl 8-methyl-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate, — ethoxycarbonylmethyl 6-acetoxy-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate, — 2-pentyl-7,7-diphenylbenzo[*h*] chromeno[6,5-*d*]-1,3-dioxin-4(7*H*)-one, — 13-butyl-13-ethoxy-6,11-dimethoxy-3,3-*bis*(4-methoxyphenyl)-3,13-dihydrobenzo [*h*]indeno[2,1-*f*]chromene, — 3-(4-methoxyphenyl)-13,13-dimethyl-3-phenyl-3,13-dihydrobenzo [*h*]indeno [2,1-*f*]chromene, — 6,7-dimethoxy-3,3-*bis*(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo [*h*]indeno[2,1-*f*]chromene	0 %	31.12.2013
*ex 3215 11 00 ex 3215 19 00	10 10	Printing ink, liquid, consisting of a dispersion of a vinyl acrylate copolymer and colour pigments in isoparaffins, containing by weight not more than 13 % of vinyl acrylate copolymer and colour pigments	0 %	31.12.2013
*ex 3215 90 80	10	Ink formulation, for use in the manufacture of ink-jet cartridges (1)	0 %	31.12.2013
*ex 3215 90 80	20	Heat sensitive ink fixed on a plastic film	0 %	31.12.2013

▼M26

ex 3215 90 80	30	Ink, containing by weight 5 % or more, but not more than 10 % of amorphous silicon dioxide, filled into disposable cartridges, for use in the marking of integrated circuits (4)	0 %	1.7.2009-31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*3301 12 10		Essential oil of orange, not deterpenated	0 %	31.12.2013
*ex 3402 13 00	10	Vinyl copolymer surface active agent based on polypropylene glycol	0 %	31.12.2013
ex 3402 13 00	20	Surfactant containing 1,4-dimethyl-1,4-*bis* (2-methylpropyl)-2-butyne-1,4-diyl ether, polymerized with oxirane, methyl terminated	0 %	31.12.2012
*ex 3402 90 10	20	Mixture of docusate sodium (INN) and sodium benzoate	0 %	31.12.2013
*ex 3402 90 10	40	Amphoteric fluorinated surfactant in a mixture of water and ethanol, containing by weight 25 % or more but not more than 30 % surfactant	0 %	31.12.2013
*ex 3403 99 90	10	Cutting-fluid preparation based on an aqueous solution of synthetic polypeptides	0 %	31.12.2013
*ex 3505 10 50	20	*O*-(2-Hydroxyethyl)-derivative of hydrolysed maize starch	0 %	31.12.2013
*ex 3506 91 00	10	Adhesive based on an aqueous dispersion of a mixture of dimerised rosin and a copolymer of ethylene and vinyl acetate (EVA)	0 %	31.12.2013
*ex 3506 91 00	30	Two component microencapsulated epoxy adhesive dispersed in a solvent	0 %	31.12.2013
*ex 3506 91 00	40	Acrylic pressure sensitive adhesive with a thickness of 0,076 mm or more but not more than 0,127 mm, put up in rolls of a width of 45,7 cm or more but not not more than 78,5 cm supplied on a release liner with an initial peel adhesion release value of not less than 15N/25 mm (measured according to ASTM D3330)	0 %	31.12.2012
*ex 3701 30 00	10	Relief printing plate, of a kind used for printing on newsprint, consisting of a metal substrate coated with a photopolymer layer of a thickness of 0,2 mm or more but not more than 0,8 mm, not covered with a release film, of a total thickness of not more than 1 mm	0 %	31.12.2013
*ex 3701 99 00	10	Plate of quartz or of glass, covered with a film of chromium and coated with a photo-sensitive or electron-sensitive resin, for the manufacture of masks for the goods of heading No 8541 or 8542 ([1])	0 %	31.12.2013
*ex 3707 10 00	10	Photosensitive emulsion for the sensitization of silicon discs ([1])	0 %	31.12.2013
*ex 3707 10 00	15	Sensitising emulsion, consisting of diazooxonaphtalenesulphonic acid ester and phenolic resins, containing by weight not more than 12 % of diazooxonaphtalenesulphonic acid ester, in 2-methoxy-1-methylethyl acetate or ethyl lactate	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3707 10 00	25	Sensitising emulsion containing: — phenolic or acrylic resins — a maximum 2 % by weight of light sensitive acid precursor, in a solution containing 2-methoxy-1-methylethyl acetate or ethyl lactate	0 %	31.12.2013
*ex 3707 10 00	30	Preparation based on photosensitive acrylic containing polymer, containing colour pigments, 2-methoxy-1-methylethylacetate and cyclohexanone and whether or not containing ethyl-3-ethoxypropionate	0 %	31.12.2013
ex 3707 10 00	35	Sensitising emulsion, consisting of acrylate and/or methacrylate polymers, containing by weight not more than 7 % photosensitive acid precursors dissolved in an organic solvent containing at least 2-methoxy-1-methylethyl acetate	0 %	31.12.2011
*ex 3707 10 00	40	Sensitising emulsion, containing: — not more than 10 % by weight of naphthoquinonediazide esters, — 2 % or more but not more than 20 % by weight of copolymers of hydroxystyrene — not more than 7 % by weight of epoxy-containing derivatives dissolved in 1-ethoxy-2-propyl acetate and/or ethyl lactate	0 %	31.12.2011
ex 3707 90 30	10	Toner, in the form of powder, consisting of a copolymer of styrene and butyl acrylate and either magnetite or carbon black, for use as a developer in the manufacture of cartridges for facsimile machines or computer printers ([1])	0 %	31.12.2013
*ex 3707 90 30	20	Toner, based on a polyol resin, in the form of powder	0 %	31.12.2013
*ex 3707 90 30	40	Polyester resin based toner, manufactured by a polymerisation process, for use as a developer in the manufacture of computer printer and copier cartridges ([1])	0 %	31.12.2013
*ex 3707 90 90	10	Anti-reflection coating, consisting of a modified methacrylic polymer, containing by weight not more than 10 % of polymer, in the form of a solution in 2-methoxy-1-methylethyl acetate and 1-methoxypropan-2-ol	0 %	31.12.2013
*ex 3707 90 90 ex 3824 90 97	30 91	Anti-reflection coating, in the form of an aqueous solution, containing by weight: — not more than 2 % of perhalogenated sulphonic acid derivatives, — not more than 1 % of a vinyl polymer	0 %	31.12.2013
*ex 3801 20 90	10	Colloidal graphite in suspension in water, for use as internal coating in colour cathode-ray tubes ([1])	0 %	31.12.2013
*3805 90 10		Pine oil	1,7 %	31.12.2013
*ex 3808 91 90	10	Indoxacarb (ISO) and its (*R*) isomer, fixed on a support of silicon dioxide	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26				
**ex 3808 91 90	30	Preparation containing endospores or spores and protein crystals derived from either: — *Bacillus thuringiensis* Berliner subsp. *aizawai* and *kurstaki*, or — *Bacillus thuringiensis* subsp. *kurstaki*, or — *Bacillus thuringiensis* subsp. *israelensis*.	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3808 91 90	40	Spinosad (ISO)	0 %	31.12.2013
▼M26				
ex 3808 91 90	50	*Spodoptera exigua* nuclear polyhedrosis virus (SeNPV) in an aqueous glycerol suspension	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3808 92 90	10	Fungicide in the form of a powder, containing by weight 65 % or more but not more than 75 % of hymexazole (ISO), not put up for retail sale	0 %	31.12.2013
*ex 3808 92 90	30	Preparation consisting of a suspension of pyrithione zinc (INN) in water, containing by weight 24 % or more but not more than 26 % of pyrithione zinc (INN)	0 %	31.12.2013
ex 3808 93 15	10	Preparation based on a concentrate containing by weight 45 % or more but not more than 55 % of the active herbicidal ingredient Penoxsulam as an aqueous suspension	0 %	31.12.2012
ex 3808 93 27	20	Organic solution of Clethodim (ISO), with a Clethodim content of 37 % (± 2 %) or 70 % (± 2 %) by weight	0 %	31.12.2012
*ex 3809 91 00	10	Mixture of 5-ethyl-2-methyl-2-oxo-1.3,2λ^5-dioxaphosphoran-5-ylmethyl methyl methylphosphonate and *bis*(5-ethyl-2-methyl-2-oxo-1.3,2λ^5-dioxaphosphoran-5-ylmethyl) methylphosphonate	0 %	31.12.2013
*ex 3809 92 00	10	Paper anti-fading agent, consisting of a mixture of magnesium trisilicate and monosodium salt of 2,2'-methylenebis(4,6-di-*tert*-butylphenyl) phosphate	0 %	31.12.2013
*ex 3810 10 00	10	Soldering paste, consisting of a mixture of metals and resin containing by weight: — 70 % or more, but not more than 90 % of tin — not more than 10 % of one or more metals of silver, copper, bismuth, zinc, or indium for use in the electro technical industry (1)	0 %	31.12.2013

▼M25

	CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26					
	ex 3811 19 00	10	Solution of more than 61 % but not more than 63 % by weight of methylcyclopentadienyl manganese tricarbonyl in an aromatic hydrocarbon solvent, containing by weight not more than: — 4,9 % of 1,2,4-trimethyl-benzene, — 4,9 % of naphthalene, and — 0,5 % of 1,3,5-trimethyl-benzene.	0 %	1.7.2009-31.12.2013
▼M25					
	*ex 3811 21 00	10	Salts of dinonylnaphthalenesulphonic acid, in the form of a solution in mineral oils	0 %	31.12.2013
	ex 3811 21 00	20	Additives for lubricating oils, based on complex organic molybdenum compounds, in the form of a solution in mineral oil	0 %	31.12.2013
▼M26					
	ex 3811 90 00	10	Dinonylnaphthylsulphonic acid salt, in a mineral oil solution	0 %	1.7.2009-31.12.2013
▼M25					
	*ex 3811 90 00	20	Corrosion inhibitor, containing reaction products of fatty acids and tall oil with formaldehyde and (Z)-*N*-9-octadecenyl-1,3-propanediamine	0 %	31.12.2011
	*ex 3812 30 80	20	Mixture containing predominantly *bis* (2.2,6,6-tetramethyl-1-octyloxy-4-piperidyl) sebacate	0 %	31.12.2013
	*ex 3812 30 80	30	Compound stabilisers containing by weight 15 % or more but not more than 40 % of sodium perchlorate and not more than 70 % of 2-(2-methoxyethoxy)ethanol	0 %	31.12.2013
	*ex 3814 00 90	20	Mixture containing by weight: — 69 % or more but not more than 71 % of 1-methoxypropan-2-ol, — 29 % or more but not more than 31 % of 2-methoxy-1-methylethyl acetate	0 %	31.12.2013
	*ex 3814 00 90	40	Azeotrope mixtures containing isomers of nonafluorobutyl methyl ether and/or nonafluorobutyl ethyl ether	0 %	31.12.2013
	*ex 3815 12 00	10	Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not more than 10 mm, consisting of silver on an aluminium oxide support and containing by weight 8 % or more but not more than 40 % of silver	0 %	31.12.2013
	*ex 3815 19 90	10	Catalyst, consisting of chromium trioxide or dichromium trioxide fixed on a support of silicon dioxide, of a pore volume, as determined by the nitrogen absorption method, of 2 cm^3/g or more	0 %	31.12.2013
	*ex 3815 19 90	15	Catalyst, in the form of a powder, consisting of a mixture of metal oxides fixed on a support of silicon dioxide, containing by weight 20 % or more but not more than 40 % of molybdenum, bismuth and iron evaluated together, for use in the manufacture of acrylonitrile [1]	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3815 19 90	30	Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene (1)	0 %	31.12.2013
*ex 3815 19 90	40	Catalyst, in the form of spheres of a diameter of 4.2 mm or more but not more than 9 mm, consisting of a mixture of metals oxides containing predominantly oxides of molybdenum, vanadium and copper, on a support of silicon dioxide and/or aluminium oxide, for use in the manufacture of acrylic acid (1)	0 %	31.12.2013
*ex 3815 19 90	41	Catalysts in the form of tablets, consisting of 60 % (± 2 %) by weight of copper oxide on a support of aluminium oxide	0 %	31.12.2012
*ex 3815 19 90	50	Catalyst consisting of organo-metallic compounds of titanium, magnesium and aluminium on a support of silicon dioxide, in the form of a suspension in tetrahydrofuran	0 %	31.12.2013
*ex 3815 19 90	60	Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide	0 %	31.12.2013
*ex 3815 19 90	65	Catalyst consisting of phosphoric acid chemically bonded to a support of silicon dioxide	0 %	31.12.2013
*ex 3815 19 90	70	Catalyst consisting of organo-metallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide	0 %	31.12.2013
*ex 3815 19 90	75	Catalyst consisting of organo-metallic compounds of aluminium and chromium, fixed on a support of silicon dioxide	0 %	31.12.2013
*ex 3815 19 90	80	Catalyst consisting of organo-metallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil	0 %	31.12.2013
*ex 3815 19 90	85	Catalyst consisting of organo-metallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder	0 %	31.12.2013
*ex 3815 19 90	86	Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polyolefins (1)	0 %	31.12.2013
ex 3815 90 90	16	Initiator based on dimethylaminopropyl urea	0 %	31.12.2012
*ex 3815 90 90	20	Catalyst, in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing by weight: — 20 % or more but not more than 30 % of titanium and — 55 % or more but not more than 72 % of chlorine	0 %	31.12.2013
*ex 3815 90 90	50	Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3815 90 90	70	Catalyst, consisting of a mixture of (2-hydroxypropyl)trimethylammonium formate and dipropylene glycols	0 %	31.12.2013
*ex 3815 90 90	71	Catalyst, containing *N*-(2-hydroxypropyl-lammonium)diazabicyclo (2.2,2) octane-2-ethyl hexanoate, dissolved in ethane-1,2-diol	0 %	31.12.2011

▼M26

———————

**ex 3815 90 90	77	Catalyst powder in an aqueous suspension containing by weight: — 1 % or more but not more than 3 % of palladium, — 0,25 % or more but not more than 3 % of lead, — 0,25 % or more but not more than 0,5 % of lead hydroxide, — 5,5 % or more but not more than 10 % of aluminium, — 4 % or more but not more than 10 % of magnesium, — 30 % or more but not more than 50 % of silicon dioxide.	0 %	1.7.2009-31.12.2013

▼M25

*ex 3815 90 90	80	Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol	0 %	31.12.2013
*ex 3815 90 90	81	Catalyst, containing by weight 69 % or more but not more than 79 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate	0 %	31.12.2013
*ex 3815 90 90	84	Powder catalyst containing by weight a minimum 96 % of oxides of copper, chromium and iron	0 %	31.12.2013
ex 3815 90 90	85	Catalyst based on aluminosilicate (zeolite), for the alkylation of aromatic hydrocarbons, for the transalkylation of alkylaromatic hydrocarbons or for the oligomerization of olefins ([1])	0 %	31.12.2012
*ex 3815 90 90	86	Catalyst, in the form of rodlets, consisting of an aluminosilicate (zeolite), containing by weight 2 % or more but not more than 3 % of rare-earth metal oxides and less than 1 % of disodium oxide	0 %	31.12.2013
*ex 3815 90 90	87	Reaction initiator, consisting of diisopropyl peroxydicarbonate, in the form of a solution in diallyl 2,2'-oxydiethyl dicarbonate	0 %	31.12.2013
*ex 3815 90 90	88	Catalyst, consisting of titanium tetrachloride and magnesium chloride, containing by weight on an oil- and hexane-free basis: — 4 % or more but not more than 10 % of titanium and — 10 % or more but not more than 20 % magnesium	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3815 90 90	89	Rhodococcus rhodocrous J1 bacteria, containing enzymes, suspended in a poly-acrylamide gel or in water, for use as a catalyst in the production of acrylamide by the hydration of acrylonitrile ([1])	0 %	31.12.2011

▼M26

———————

**ex 3817 00 50	10	Mixture of alkylbenzenes (C14-26) containing by weight: — 35 % or more but not more than 60 % of eicosylbenzene, — 25 % or more but not more than 50 % of docosylbenzene, — 5 % or more but not more than 25 % of tetracosylbenzene.	0 %	1.7.2009-31.12.2013

▼M25

*ex 3817 00 80	10	Mixture of alkylnaphthalenes, containing by weight: — 88 % or more but not more than 98 % of hexadecylnaphthalene — 2 % or more but not more than 12 % of dihexadecylnaphthalene	0 %	31.12.2013

▼M26

ex 3817 00 80	20	Mixture of branched alkyl benzenes mainly containing dodecyl benzenes	0 %	1.7.2009-31.12.2013

▼M25

*ex 3819 00 00	20	Fire resistant hydraulic fluid based on phosphate ester	0 %	31.12.2013
*ex 3824 90 15	10	Acid aluminosilicate (artificial zeolite of the Y type) in the sodium form, containing by weight not more than 11 % of sodium evaluated as sodium oxide, in the form of rodlets	0 %	31.12.2013
*ex 3824 90 97	09	Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulphonic acid, either: — on a support of mineral wax, whether or not modified chemically, or — in the form of a solution in an organic solvent	0 %	31.12.2013
*ex 3824 90 97	10	Calcined bauxite (refractory grade)	0 %	31.12.2013
*ex 3824 90 97	12	Oligomer of tetrafluoroethylene, having one iodoethyl end-group	0 %	31.12.2013
ex 3824 90 97	13	Preparations containing not less than 92 % but not more than 96,5 % by weight of 1.3:2,4-*bis*-*O*-(4-methylbenzylidene)-*D*-glucitol and also containing carboxylic acid derivatives and an alkyl sulphate	0 %	31.12.2011
ex 3824 90 97	14	Calcium phosphonate phenate, dissolved in mineral oil	0 %	31.12.2011

▼M26

ex 3824 90 97	15	Structured silica alumina phosphate	0 %	1.7.2009-31.12.2013

▼M26

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3824 90 97	16	Mixture of bis{4-(3-(3-phenoxycarbonylamino)tolyl)ureido}phenylsulphone, diphenyltoluene-2,4-dicarbamate and 1-[4-(4-aminobenzenesulphonyl)-phenyl]-3-(3-phenoxycarbonylamino-tolyl)-urea	0 %	1.7.2009-31.12.2013
ex 3824 90 97	17	Mixture of acetates of 3-butylene-1,2-diol with a content by weight of 65 % or more but not more than 90 %	0 %	1.7.2009-31.12.2013

▼M25

ex 3824 90 97	18	4-Methylmandelic acid, crude	0 %	31.12.2011
*ex 3824 90 97	20	Preparation consisting by weight of 83 % or more of 3a,4.7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing by weight 7 % or more of tricyclopentadiene, and: — either an aluminium-alkyl compound, — or an organic complex of tungsten — or an organic complex of molybdenum	0 %	31.12.2013
ex 3824 90 97	22	Preparations containing not less than 47 % by weight of 1.3:2,4-*bis*-*O*-benzylidene-*D*-glucitol	0 %	31.12.2011
*ex 3824 90 97	25	Lithium tantalate wafers, undoped	0 %	31.12.2013
*ex 3824 90 97	29	Preparation consisting predominantly of γ-butyrolactone and quaternary ammonium salts, for the manufacture of electrolytic capacitors ([1])	0 %	31.12.2013
*ex 3824 90 97	30	2.4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated	0 %	31.12.2013
*ex 3824 90 97	34	Mixture of phytosterols in the form of a crystalline waxy powder, containing by weight: — 36 % or more, but not more than 79 % of sitosterols, — 15 % or more, but not more than 34 % of sitostanols, — 4 % or more, but not more than 25 % of campesterols, — 0 % or more, but not more than 14 % of campestanols	0 %	31.12.2013
ex 3824 90 97	36	Preparation based on 2.5,8,11-tetramethyl-6-dodecyn-5,8-diol ethoxylate	0 %	31.12.2012
*ex 3824 90 97	37	Liquid crystal mixture for use in the manufacture of displays ([1])	0 %	31.12.2012
*ex 3824 90 97	38	Alkyl carbonate-based preparation, also containing a UV absorber, for use in the manufacture of spectacle lenses ([1])	0 %	31.12.2012
*ex 3824 90 97	39	Mixture containing by weight 40 % or more but not more than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid	0 %	31.12.2013
*ex 3824 90 97	40	Azelaic acid of a purity by weight of 75 % or more but not mote than 85 %	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3824 90 97	42	Mixed metals oxides, in the form of powder, containing by weight: — either 5 % or more of barium, neodymium or magnesium and 15 % or more of titanium, — or 30 % or more of lead and 5 % or more of niobium, for use in the manufacture of dielectric films or for use as dielectric materials in the manufacture of multilayer ceramic capacitors ([1])	0 %	31.12.2013
ex 3824 90 97	44	Mixture of phytosterols, not in the form of powder, containing by weight: — 75 % or more of sterols, — not more than 25 % of stanols, for use in the manufacture of stanol/sterol esters ([1])	0 %	31.12.2012
ex 3824 90 97	45	Preparations consisting predominantly of ethylene glycol and: — either diethylene glycol, dodecandioic acid and ammonia water, — or N, N-dimethylformamide, — or γ-butyrolactone, — or silicon oxide, — or ammonium hydrogen azelate, — or ammonium hydrogen azelate and silicon oxide, — or dodecandioic acid, ammonia water and silicon oxide, for the manufacture of electrolytic capacitors ([1])	0 %	31.12.2013
ex 3824 90 97	46	Carboxylic acid anhydride based hardener for epoxide resin, in liquid form, of a specific weight at 25 °C of 1.15 g/cm^3 or more but not more than 1,18 g/cm^3	0 %	31.12.2013
ex 3824 90 97	47	4-Methoxysalicylaldehyde, dissolved in *N*-methyl pyrrolidone	0 %	31.12.2012
*ex 3824 90 97	52	Poly(tetramethylene glycol) *bis*[(2-benzoyl-phenoxy)acetate] with an average polymer chain length of less than 5 monomer units	0 %	31.12.2013
*ex 3824 90 97	53	Poly(ethylene glycol) *bis*(*p*-dimethyl) aminobenzoate with an average polymer chain length of less than 5 monomer units	0 %	31.12.2013
*ex 3824 90 97	54	2-Hydroxybenzonitrile, in the form of a solution in *N,N*-dimethylformamide, containing by weight 45 % or more but not more than 55 % of 2-hydroxybenzo-nitrile	0 %	31.12.2013
*ex 3824 90 97	60	*α*-Phenoxycarbonyl-*ω*-phenoxypoly[oxy (2,6-dibromo-1,4-phenylene) isopropy-lidene(3,5-dibromo-1,4-phenylene) oxycarbonyl]	0 %	31.12.2013
*ex 3824 90 97	63	Triethylborane, in the form of a solution in tetrahydrofuran	0 %	31.12.2013

▼**M25**

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3824 90 97	64	Aluminium sodium silicate, in the form of spheres of a diameter of: — either 1,6 mm or more but not more than 3,4 mm, — or 4 mm or more but not more than 6 mm	0 %	31.12.2013
ex 3824 90 97	70	Paste containing by weight 75 % or more, but not more than 85 % of copper, and also containing inorganic oxides, ethyl cellulose and a solvent	0 %	31.12.2012
*ex 3824 90 97	72	Solution containing by weight 80 % or more of 2.4,6-trimethylbenzaldehyde in acetone	0 %	31.12.2013
*ex 3824 90 97	73	Particles of silicon dioxide on which are covalently bonded organic compounds, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (1)	0 %	31.12.2013
*ex 3824 90 97	75	Poly(tetramethylene glycol) *bis*(9-oxo-9H-thioxanthen-1-yloxy)acetate with an average polymer chain length of less than 5 monomer units	0 %	31.12.2013
*ex 3824 90 97	77	Diethylmethoxyborane, in the form of a solution in tetrahydrofuran	0 %	31.12.2013
ex 3824 90 97	78	Mixture of phytosterols derived from wood and wood based oils (tall oil), in the form of powder with a particle size not more than 300 μm, containing by weight: — 60 % or more, but not more than 80 % of sitosterols, — not more than 15 % of campesterols, — not more than 5 % of stigmasterols, — not more than 15 % of betasitostanols	0 %	31.12.2012
*ex 3824 90 97	79	Mixture of 80 % (± 10 %) of 1-[2-(2-aminobutoxy)ethoxy]but-2-ylamine and 20 %(± 10 %) of 1-({[2-(2-aminobutoxy) ethoxy]methyl} propoxy)but-2-ylamine	0 %	31.12.2013
*ex 3824 90 97	82	α-(2.4,6-Tribromophenyl)-ω-(2.4,6-tribromophenoxy)poly[oxy(2,6-dibromo-1,4-phenylene)isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl]	0 %	31.12.2013
*ex 3824 90 97	84	Reaction product, containing by weight: — 1 % or more but not more than 40 % of molybdenum oxide, — 10 % or more but not more than 50 % of nickel oxide, — 30 % or more but not more than 70 % of tungsten oxide	0 %	31.12.2013
*ex 3824 90 97	89	Oligomer of tetrafluoroethylene, having tetrafluoroiodoethyl end-groups	0 %	31.12.2013
*ex 3824 90 97	90	Hollow spheres of fused aluminosilicate containing 65-80 % amorphous aluminosilicate, with the following characteristics: — a melting point of between 1 600 °C and 1800 °C, — a density of 0,6-0,8 g/cm^3, for use in the manufacture of particle filters in motor vehicles (1)	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3824 90 97	95	Mixture of phytosterols, in the form of flakes, containing by weight 80 % or more of sterols and not more than 4 % of stanols	0 %	31.12.2013
*ex 3824 90 97	97	Preparation containing by weight either 10 % or more but not more than 20 % of lithiumfluorophosphate or 5 % or more but not more than 10 % of lithium perchlorate in mixtures of organic solvents	0 %	31.12.2013
*ex 3901 10 90	20	Polyethylene, in the form of granules, of a specific gravity of 0,925 (± 0,0015), a melt flow index of 0,3 g/10 min (± 0,05 g/10 min), for the manufacture of blown films of a Haze value not more than 6 % and an elongation at break (MD/TD) of 210/340 ([1])	0 %	31.12.2013
*ex 3901 20 90	10	Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, of a specific gravity of 0,945 or more but not more than 0,985, for the manufacture of films for typewriter ribbon or similar ribbon ([1])	0 %	31.12.2013
*ex 3901 20 90	20	Polyethylene, containing by weight 35 % or more but not more than 45 % of mica	0 %	31.12.2013
*ex 3901 90 90	91	Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid	4 %	31.12.2013
*ex 3901 90 90	92	Chlorosulphonated polyethylene	0 %	31.12.2013
*ex 3901 90 90	93	Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticizer in the manufacture of roof sheets ([1])	0 %	31.12.2013
*ex 3901 90 90	94	Mixtures of A-B block copolymer of polystyrene and ethylene-butylene copolymer and A-B-A block copolymer of polystyrene, ethylene-butylene copolymer and polystyrene, containing by weight not more than 35 % of styrene	0 %	31.12.2013
*ex 3901 90 90	97	Chlorinated polyethylene, in the form of powder	0 %	31.12.2013
*ex 3902 10 00	10	Polypropylene containing no plasticizer and not more than: — 7 mg/kg of aluminium, — 2 mg/kg of iron, — 1 mg/kg of magnesium, — 8 mg/kg of chloride	0 %	31.12.2013
*ex 3902 10 00	20	Polypropylene, containing no plasticiser, — of a melting point of more than 150 °C (as determined by the ASTM D 3417 method), — of a heat of fusion of 15 J/g or more but not more than 70 J/g, — of an elongation at break of 1 000 % or more (as determined by the ASTM D 638 method), — of a tensile modulus of 69 MPa or more but not more than 379 MPa (as determined by the ASTM D 638 method)	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3902 10 00	30	Polypropylene, containing not more than 1 mg/kg of aluminium, 0,05 mg/kg of iron, 1 mg/kg of magnesium and 1 mg/kg of chloride, for use in the manufacture of packaging for disposable contact lenses (1)	0 %	31.12.2013

▼M26

———————

**ex 3902 20 00	10	Polyisobutylene, of a number average molecular weight (M_n) of 700 or more but not more than 800	0 %	1.7.2009-31.12.2013
ex 3902 20 00	20	Hydrogenated polyisobutene, in liquid form	0 %	1.7.2009-31.12.2013

▼M25

*ex 3902 30 00	91	A-B Block copolymer of polystyrene and an ethylene-propylene copolymer, containing by weight 40 % or less of styrene, in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	31.12.2013
*ex 3902 90 90	52	Amorphous poly-alpha-olefin copolymer blend of poly(propylene-co-1-butene) and petroleum hydrocarbon resin	0 %	31.12.2013

▼M26

ex 3902 90 90	55	Thermoplastic elastomer, with an A-B-A block copolymer structure of polystyrene, polyisobutylene and polystyrene containing by weight 10 % or more but not more than 35 % of polystyrene	0 %	1.7.2009-31.12.2013

▼M25

*ex 3902 90 90	92	Polymers of 4-methylpent-1-ene	0 %	31.12.2013
ex 3902 90 90	93	Synthetic poly-alpha-olefin having a viscosity of at least 38 × $10^{-6}m^2s^{-1}$ (38 centistokes) at 100 °C measured using the ASTM D 445 method	0 %	31.12.2011

▼M26

———————

▼M25

ex 3902 90 90	98	Synthetic poly-alpha-olefin with a viscosity at 100° Celsius (measured according to method ASTM D 445) ranging from 3 centistokes to 9 centistokes and obtained by polymerization of a mixture of dodecene and tetradecene, containing a maximum of 40 % of tetradecene	0 %	31.12.2011
*ex 3903 11 00	10	White expandable polystyrene beads with a thermal conductivity of not more than 0,034 W/mK at a density of 14,0 kg/m^3 (± 1,5 kg/m^3), containing 50 % recycled material	0 %	31.12.2013
*ex 3903 19 00	30	Crystalline polystyrene with a melting point of 268 °C or more but not more than 272 °C and a setting point of 247 °C or more but not more than 252 °C, whether or not containing additives and filling material	0 %	31.12.2011
*ex 3903 90 90	35	Copolymer of α-methylstyrene and styrene, having a softening point of more than 113 °C	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26				
_____				
**ex 3903 90 90 **ex 3911 90 99	40 50	Copolymer of styrene with α-methylstyrene and acrylic acid, of a number average molecular weight (M_n) of 500 or more but not more than 6 000	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3903 90 90	65	Copolymer of styrene, butyl acrylate, butyl methacrylate, methyl methacrylate and acrylic acid, in the form of powder, containing by weight 81 (± 1) % of styrene, 6 (± 1) % of butyl acrylate, 5 (± 1) % of butyl methacrylate, 7 (± 1) % of methyl methacrylate and 1 (± 0,5) % of acrylic acid	0 %	31.12.2013
*ex 3903 90 90	75	Copolymer of styrene and vinyl pyrrolidone, containing by weight not more than 1 % of sodium dodecyl sulphate, in the form of an aqueous emulsion, for the manufacture of goods of subheading 3305 20 00 or of hair dyes of subheading 3305 90 90 (1)	0 %	31.12.2013
*ex 3903 90 90	80	Granules of copolymer of styrene and divinylbenzene of a minimum diameter of 150 μm and a maximum diameter of 800 μm and containing by weight: — minimum 65 % styrene, — maximum 25 % divinylbenzene for use in the manufacture of ion exchange resins (1)	0 %	31.12.2013
▼M26				
_____				
▼M25				
*ex 3903 90 90	86	Mixture containing by weight: — 45 % or more but not more than 65 % of polymers of styrene — 35 % or more but not more than 45 % of poly(phenylene ether) — not more than 10 % of other additives	0 %	31.12.2013
ex 3904 10 00	20	Poly(vinyl chloride) powder, not mixed with any other substances, with a degree of polymerisation of 1 000 (± 100) monomer units, a coefficient of heat transmission (K-value) of 60 or more, but not more than 70, a bulk density of 0,35 g/cm^3 or more, but not more than 0,55 g/cm^3, a volatile material content of less than 0,35 % by weight, a medium average grain size of 40 μm or more, but not more than 70 μm and a sieve non-passing fraction at a mesh width of 120 μm of not more than 1 % by weight, not containing any vinyl acetate monomers, for the manufacture of battery separators (1)	0 %	31.12.2012

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3904 40 00	91	Copolymer of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight: — 87 % or more but not more than 92 % of vinyl chloride, — 2 % or more but not more than 9 % of vinyl acetate and — 1 % or more but not more than 8 % of vinyl alcohol, in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of goods of heading No 3215 or 8523 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink ([1])	0 %	31.12.2013
*ex 3904 40 00	93	Copolymer of vinyl chloride and methyl acrylate, containing by weight 80 (± 1) % of vinyl chloride and 20 (± 1) % of methyl acrylate, in the form of a aqueous emulsion	0 %	31.12.2013
*ex 3904 61 00	10	Mixture of polytetrafluoroethylene and mica, in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	31.12.2013
*ex 3904 61 00	20	Copolymer of tetrafluoroethylene and trifluoro(heptafluoropropoxy)ethylene, containing 3,2 % or more but not more than 4,6 % by weight of trifluoro(heptafluoropropoxy)ethylene and less than 1 mg/kg of extractable fluoride ions	0 %	31.12.2013
*ex 3904 61 00	30	Polytetrafluoroethylene, in the form of powder, of a specific surface of 8 m^2/g or more but not more than 12 m^2/g, a particle size distribution of 10 % of less than 10 μm and 90 % of less than 35 μm and an average particle size of 20 μm	0 %	31.12.2013

▼M26

ex 3904 69 90	81	Poly(vinylidene fluoride) powder or in an aqueous suspension	0 %	1.7.2009-31.12.2013

▼M25

*ex 3904 69 90	93	Copolymer of ethylene with chlorotrifluoroethylene, in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	31.12.2013
*ex 3904 69 90	94	Copolymer of ethylene and tetrafluoroethylene	0 %	31.12.2013
*ex 3904 69 90	96	Polychlorotrifluoroethylene, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39	0 %	31.12.2013
*ex 3904 69 90	97	Copolymer of chlorotrifluoroethylene and vinylidene difluoride	0 %	31.12.2013
*ex 3905 99 90	94	Polymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, containing by weight 97 % or more but not more than 99 % of vinylpyrrolidone, in the form of a solution in water	0 %	31.12.2013
*ex 3905 99 90	95	Hexadecylated or eicosylated polyvinylpyrrolidone	0 %	31.12.2013

▼M26

_____

▼M26

CN code	TARIC	Description	Rate of autonomous duty	Validity period
**ex 3905 99 90	96	Polymer of vinyl formal, in one of the forms mentioned in note 6(b) to Chapter 39, of a weight average molecular weight (M_w) of 25 000 or more but not more than 150 000 and containing by weight: — 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl acetate, and — 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol.	0 %	1.7.2009-31.12.2013

▼M25

*ex 3905 99 90	97	Povidone (INN)-iodine	0 %	31.12.2013
*ex 3905 99 90	98	Poly(vinyl pyrrolidone) partially substituted by triacontyl groups, containing by weight 78 % or more but not more than 82 % of triacontyl groups	0 %	31.12.2013
*3906 90 60		Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide	0 %	31.12.2013
*ex 3906 90 90	10	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for the manufacture of medicaments of heading No 3003 or 3004 ([1])	0 %	31.12.2013
*ex 3906 90 90	15	Photosensitive resin consisting of modified acrylate, acrylic monomer, catalyst (photo-initiator) and stabilizer	0 %	31.12.2013
*ex 3906 90 90	20	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for use as a stabilizer in emulsions or dispersions with a pH of more than 13 ([1])	6 %	31.12.2013

▼M26

ex 3906 90 90	25	Transparent liquid, insoluble in water, containing by weight: — 50 % or more, but not more than 51 % of poly(methyl metacrylate) copolymer, — 37 % or more, but not more than 39 % of xylene, and — 11 % or more, but not more than 13 % of n-butyl acetate.	0 %	1.7.2009-31.12.2013
**ex 3906 90 90	30	Copolymer of styrene with hydroxyethyl methacrylate and 2-ethylhexyl acrylate, of a number average molecular weight (M_n) of 500 or more but not more than 6 000	0 %	1.7.2009-31.12.2013
ex 3906 90 90	35	White powder of 1,2-ethanediol dimethacrylate-methyl methacrylate copolymer of a particle size of not more than 18 µm, insoluble in water	0 %	1.7.2009-31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3906 90 90	50	Polymers of esters of acrylic acid with one or more of the following monomers in the chain: — chloromethyl vinyl ether, — chloroethyl vinyl ether, — chloromethylstyrene, — vinyl chloroacetate, — methacrylic acid, — butenedioic acid monobutyl ester, containing by weight not more than 5 % of each of the monomeric units, in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	31.12.2013
▼M26				
ex 3906 90 90	65	Polyalkylacrylate, chemically modified with cobalt, with a melting temperature (Tm) of 65 °C (± 5 °C), measured with Differential Scanning Calorimetry (DSC)	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3906 90 90	80	Polydimethylsiloxane-graft-(polyacrylates; polymethacrylates)	0 %	31.12.2013
*ex 3906 90 90	85	Non aqueous dispersion type polymers of esters of acrylic acid with a hydrolyzable silyl group at one or both polymer ends	0 %	31.12.2013
▼M26				
_____				
**ex 3907 20 11	10	Poly(ethylene oxide) of a number average molecular weight (M_n) of 100 000 or more	0 %	1.7.2009-31.12.2013
**ex 3907 20 11	20	Bis[Methoxypoly[ethyleneglycol)]-maleimidopropionamide, chemically modified with lysine, of a number average molecular weight (M_n) of 40 000	0 %	1.7.2009-31.12.2013
**ex 3907 20 11	30	Bis[Methoxypoly[ethyleneglycol)], chemically modified with lysine, bis (maleimide) terminated, of a number average molecular weight (M_n) of 40 000	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3907 20 21	10	Mixture, containing by weight 70 % or more but not more than 80 % of a polymer of glycerol and 1,2-epoxypropane and 20 % or more but not more than 30 % of a copolymer of dibutyl maleate and *N*-vinyl-2-pyrrolidone	0 %	31.12.2013
▼M26				
_____				
**ex 3907 20 21	20	Copolymer of tetrahydrofuran and tetrahydro-3-methylfuran with a number average molecular weight (M_n) of 3 500 (± 100)	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3907 20 29	10	Products containing co-polymers of dextrose, sorbitol and citric or phosphoric acid, containing not less than 90 % by weight of co-polymers on the ashfree and anhydrous basis	0 %	31.12.2011

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3907 20 99	15	Poly(oxypropylene) having alkoxysilyl end-groups	0 %	31.12.2013
*ex 3907 20 99	30	Homopolymer of 1-chloro-2,3-epoxy-propane (epichlorohydrin)	0 %	31.12.2013
*ex 3907 20 99	35	Polyethylene glycol chemically modified with an isocyanate group containing a carbodiimide group, in the form of a solution in 2-methoxy-1-methylethyl acetate	0 %	31.12.2013
*ex 3907 20 99	45	Copolymer of ethylene oxide and propylene oxide, having aminopropyl and methoxy end-groups	0 %	31.12.2013
▼M26				
ex 3907 20 99	50	Vinyl-silyl terminated perfluoropolyether polymer or an assortment of two components consisting of the same type of vinyl-silyl terminated perfluoropolyether polymer as the main ingredient	0 %	1.7.2009-31.12.2013
ex 3907 20 99	55	Succinimidyl ester of methoxy poly (ethylene glycol)propionic acid, of a number average molecular weight (Mn) of 5 000	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3907 30 00 ex 3926 90 97	40 70	Epoxide resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of heading No 8533, 8535, 8536, 8541, 8542 or 8548 ([1])	0 %	31.12.2013
▼M26				
**ex 3907 30 00	50	Liquid epoxide resin of 2-propene-nitrile/1,3-butadiene-epoxide copolymer, not containing any solvent, with: — a zinc borate hydrate content of not more than 40 % by weight, — a diantimony trioxide content of not more than 5 % by weight.	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3907 60 80	10	Copolymer of terephthalic acid and isophthalic acid with ethylene glycol, butane-1,4-diol and hexane-1,6-diol	0 %	31.12.2013
*ex 3907 60 80	30	Oxygen binding concentrate consisting of a blend of: — a copolymer obtained from poly-ethylene terephthalate, pyromellitic dianhydride (PMDA) and a hydroxyl substituted polybutadiene — a barrier co-polymer (as determined by the ASTM method F1115-95 (2001)) obtained from xylylene diamines and adipic acid, and — organic dyes and/or organic and inorganic pigments where the first co-polymer predominates	0 %	31.12.2013
*3907 70 00		Poly(lactic acid)	0 %	31.12.2013
*ex 3907 99 19 ex 3907 99 98	10 10	Poly(oxy-1,4-phenylenecarbonyl), in the form of powder	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3907 99 19	20	Liquid crystal copolyester with a melting point of not less than 270 °C, whether or not containing fillers	0 %	31.12.2013
ex 3907 99 19	50	Semi-crystalline polycyclohexylenedimethylene terephthalate polymer resin, containing by weight 10 % or more but not more than 40 % of glass fibre, in the form of granules or pellets	0 %	31.12.2011
ex 3907 99 19	60	Copolymer of terephthalic acid and isophthalic acid with bisphenol A	0 %	31.12.2012
▼M26				
ex 3908 90 00	10	Poly(iminomethylene-1,3-phenylenemethyleneiminoadipoyl), in one of the forms mentioned in note 6(b) to Chapter 39	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3908 90 00	20	Copolymer consisting of hexamethylenediamine, isophthalic acid and terephthalic acid, in one of the forms mentioned in note 6(b) to Chapter 39	0 %	31.12.2013
*ex 3908 90 00	30	Reaction product of mixtures of octadecanecarboxylic acids polymerised with an aliphatic polyetherdiamine	0 %	31.12.2013
*ex 3908 90 00	50	Oxygen binding concentrate consisting of a blend of: — a copolymer obtained from polyethylene terephthalate, pyromellitic dianhydride (PMDA) and a hydroxyl substituted polybutadiene — a barrier co-polymer (as determined by the ASTM method F1115-95 (2001)) obtained from xylylene diamines and adipic acid, and — organic dyes and/or organic and inorganic pigments where the second co-polymer predominates	0 %	31.12.2013
*ex 3909 40 00	10	Polycondensation product of phenol with formaldehyde, in the form of hollow spheres of a diameter of less than 150 μm	0 %	31.12.2013
*ex 3910 00 00	20	Block copolymer of poly(methyl-3.3,3-trifluoropropylsiloxane) and poly[methyl (vinyl)siloxane]	0 %	31.12.2013
ex 3910 00 00	40	Biocompatible silicones for the manufacture of long term surgical implants (1)	0 %	31.12.2011
ex 3910 00 00	50	Silicone based pressure sensitive adhesive in solvent containing copoly(dimethylsiloxane/diphenylsiloxane) gum	0 %	31.12.2012
▼M26				
**ex 3911 10 00	81	Non-hydrogenated Hydrocarbon Resin, obtained by polymerisation of C-5 to C-10 alkenes, cyclopentadiene and dicyclopentadiene, with a Gardner Colour of more than 10 for the pure product or with a Gardner Colour of more than 8 for the 50 % solution by volume in toluene (as determined by the ASTM method D6166)	0 %	1.7.2009-31.12.2013

▼M26

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3911 90 19	10	Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene)	0 %	1.7.2009-31.12.2013
▼M25				
ex 3911 90 19	30	Copolymer of ethyleneimine and ethyleneimine dithiocarbamate, in an aqueous solution of sodium hydroxide	0 %	31.12.2012
*ex 3911 90 99	25	Copolymer of vinyltoluene and α-methylstyrene	0 %	31.12.2013
*ex 3911 90 99	40	Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not more than 16 % by weight	0 %	31.12.2013
*ex 3911 90 99	45	Copolymer of maleic acid and methyl vinyl ether	0 %	31.12.2013
*ex 3911 90 99	65	Calcium zinc salt of a copolymer of maleic acid and methyl vinyl ether	0 %	31.12.2013
ex 3911 90 99	86	Copolymer of methyl vinyl ether and maleic acid anhydride	0 %	31.12.2011
*ex 3912 39 10	10	Ethylcellulose, not plasticized	0 %	31.12.2013
*ex 3912 39 10	20	Ethylcellulose, in the form of an aqueous dispersion containing hexadecan-1-ol and sodium dodecyl sulphate, containing by weight 27 (± 3) % of ethylcellulose	0 %	31.12.2013
*ex 3912 39 80	20	Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms	0 %	31.12.2013
*ex 3912 90 10	10	Cellulose acetate propionate, non-plasticised, in the form of powder: — containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method) and — of a viscosity of not more than 120 poise (as determined by the ASTM D 817-72 method), for the manufacture of printing inks, paints, lacquers and other coatings, and reprographic coatings ([1])	0 %	31.12.2013
*ex 3912 90 10	20	Hydroxypropyl methylcellulose phthalate	0 %	31.12.2013
*ex 3913 90 00	81	Blend of cyanoethyl pullulan and cyanoethyl poly(vinyl alcohol)	0 %	31.12.2013
▼M26				
ex 3913 90 00	85	Sterile sodium hyaluronate	0 %	1.7.2009-31.12.2013

_____

▼M26

CN code	TARIC	Description	Rate of autonomous duty	Validity period
**ex 3913 90 00	92	Protein, chemically modified by carboxylation and/or phthalic acid addition, having a weight average molecular weight (M_w) of 100 000 to 300 000	0 %	1.7.2009-31.12.2013

▼M25

*ex 3913 90 00	94	Granules containing by weight: — 35 % or more but less than 75 % of a high amylose extruded biopolymer produced from corn starch, — 5 % or more but less than 16 % polyvinyl alcohol, — 10 % or more but less than 46 % of polyol plasticisers, — 0,25 % or more but less than 3 % of stearic acid, — whether or not containing 30 % (± 10 %) of biodegradable polyester resin but never to a level that exceeds the amount of the high amylose biopolymer	0 %	31.12.2011
*ex 3913 90 00	95	Chondroitinsulphuric acid, sodium salt	0 %	31.12.2013
ex 3913 90 00	96	Powder consisting of 90 % (± 5 %) by weight of a high amylose extruded biopolymer produced from corn starch, 10 % (± 5 %) by weight of a synthetic polymer and 0,5 % (± 0,25 %) of stearic acid	0 %	31.12.2011

▼M26

_____

▼M25

*ex 3917 32 39	20	Pipe consisting of a block copolymer of polytetrafluoroethylene and polyperfluoroalkoxytrifluoroethylene, of a length of not more than 600 mm, a diameter of not more than 85 mm and a wall-thickness of 30 μm or more but not more than 110 μm	0 %	31.12.2013
*ex 3919 10 19 ex 3919 10 38 ex 3919 90 38	10 20 10	Reflecting film, consisting of a layer of polyurethane, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film	0 %	31.12.2013
*ex 3919 10 19	20	Rolls of two-sided adhesive tape: — coated with non-vulcanised natural or synthetic rubber — with a width of 20 mm or more but not more than 40 mm — containing silicone, aluminium hydroxide, acryl and urethane	0 %	31.12.2013
*ex 3919 10 31 ex 3919 10 38 ex 3919 90 31 ex 3920 61 00	10 30 50 20	Reflecting laminated sheet, consisting of a film of polycarbonate totally embossed on one side in a regular shaped pattern, covered on both sides with one or more layers of plastic material, whether or not covered on one side with an adhesive layer and a release sheet	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3919 10 38	40	Double-sided, self-adhesive modified epoxy resin foil, put up in rolls, 10 to 20 cm wide, 10 to 210 m long and with a total thickness of 10 to 50 μm, not for retail sale	0 %	31.12.2011
*ex 3919 10 61	91	Reflecting film, consisting of a layer of poly(vinyl chloride), a layer of alkyd polyester, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, only visible by means of a retroreflecting lighting, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film	0 %	31.12.2013
ex 3919 10 61 ex 3919 90 61	92 95	Black polyvinyl chloride film having a high gloss of more than 90 degrees as determined by test method ASTM D 2457 covered on one side with a protective polyethylene terephthalate film and on the other side a pressure sensitive adhesive with channels and a polyethylene terephthalate release liner	0 %	31.12.2011
ex 3919 10 61 ex 3919 90 61	93 96	Reinforced polyethylene foam tape, coated on both sides with an acrylic micro channelled pressure sensitive adhesive and on one side a liner, with an application thickness of 0,38 mm or more but not more than 1,53 mm	0 %	31.12.2012

▼M26

_____

**ex 3919 10 61	94	Adhesive film consisting of a base of a copolymer of ethylene and vinyl acetate (EVA) of a thickness of 70 μm or more and an adhesive part of acrylic tape of a thickness of 5 μm or more, for the protection of the surface of silicon discs [4]	0 %	1.7.2009-31.12.2013
**ex 3919 10 69	92			
**ex 3919 90 61	93			
**ex 3919 90 69	93			
ex 3920 10 89	25			

▼M25

ex 3919 10 69 ex 3919 90 69	91 96	Acrylic foam tape, covered on one side with a heat activatable adhesive or an acrylic pressure sensitive adhesive and on the other side with an acrylic pressure sensitive adhesive and a release sheet, of a peel adhesion at an angle of 90° of more than 25 N/cm (as determined by the ASTM D 3330 method)	0 %	31.12.2012
*ex 3919 10 69	95	Reflecting laminated sheet showing a regular pattern, consisting of a film of poly(methylmethacrylate), followed by a layer of acrylic polymer containing microprisms, a film of poly(methylmethacrylate), an adhesive layer and a release sheet	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26				
ex 3919 10 69 ex 3919 90 69	96 98	Self-adhesive reflecting laminated sheet showing a regular pattern, consisting of a film of acrylic polymer followed by a layer of poly(methyl methacrylate) containing microprisms and whether or not containing an additional layer of polyester and adhesive with a final release sheet	0 %	1.7.2009-31.12.2013
_____				
**ex 3919 90 31	45	Transparent poly(ethylene terephtalate) self-adhesive film, free from impurities or faults, coated on one side with an acrylic pressure sensitive adhesive and a protective liner, and on the other side having an anti-static layer of ionic based organic compound choline and a printable dust-proof layer of modified long chain alkyl organic compound, having a total thickness without the liner of 54 μm or more but not more than 64 μm and a width of more than 1 295 mm but not more than 1 305 mm	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3919 90 31	60	Film consisting of 1 to 3 laminated layers of poly(ethylene terephthalate) and a copolymer of terephthalic acid, sebacic acid and ethylene glycol, coated on one side with an acrylic abrasion resistant coating and on the other side with an acrylic pressure sensitive adhesive, a water soluble methylcellulose coating and a poly(ethylene terephthalate) protective liner	0 %	31.12.2013
ex 3919 90 31	65	Film consisting of a multi-layer construction of poly(ethylene terephthalate) and copolymer of butylacrylate and methyl-methacrylate, coated on one side with an acrylic abrasion resistant coating incorporating nanoparticles of antimony tin oxide and carbon black, and on the other side with an acrylic pressure sensitive adhesive and a silicone-coated poly (ethylene terephthalate) protective liner	0 %	31.12.2012
*ex 3919 90 31	75	Poly(ethylene terephthalate) film, with an adhesive strength of not more than 0,147 N/25 mm and an electrostatic discharge of not more than 500 V	0 %	31.12.2013
ex 3919 90 31	80	Polyester film coated on both sides with an acrylic and/or rubber pressure sensitive adhesive put up in rolls of a width of 45,7 cm or more but not more than 78,5 cm (supplied with a release liner)	0 %	31.12.2012
▼M26				
_____				
**ex 3919 90 61	51	Transparent poly(ethylene) self-adhesive film, free from impurities or faults, coated on one side with an acrylic pressure sensitive adhesive, with a thickness of 60 μm or more, but not more than 70 μm, and with a width of more than 1 245 mm but not more than 1 255 mm	0 %	1.7.2009-31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3919 90 61	52	Reflecting layered sheet on rolls, with a width of more than 20 cm, showing an embossed regular pattern, consisting of polyvinyl chloride film coated on one side with a layer, based on acryl polymers and on the other side: — a layer of polyurethane containing glass micro beads, — an adhesive layer, and — a release sheet	0 %	31.12.2013

▼M26

ex 3919 90 61	55	Film of poly(vinyl chloride) with a thickness of 78 μm or more, covered on one side with an acrylic adhesive layer of a thickness of 8 μm or more and with a release sheet, with an adhesive strength of 1 764 mN/25 mm or more, for use in the cutting of silicon (4)	0 %	1.7.2009-31.12.2013

▼M25

*ex 3919 90 61 ex 3919 90 69	92 92	Poly(vinyl chloride) sheeting, of a thickness of less than 1 mm, coated with an adhesive in which are embedded glass balls of a diameter of not more than 100 μm	0 %	31.12.2013
*ex 3919 90 61 ex 9001 20 00	97 40	Polarizer film, in rolls, consisting of a multilayered polyvinyl alcohol film, supported on either side by a triacetyl cellulose film, with a pressure sensitive adhesive and release film on one side	0 %	31.12.2012
*ex 3919 90 69	94	Reflecting laminated sheet consisting of a film of poly(methyl methacrylate) embossed on one side in a regular shaped pattern, a film of a polymer containing glass microspheres, an adhesive layer and a release sheet	0 %	31.12.2013
*ex 3919 90 69 ex 3920 51 00	95 30	Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 μm or more but not more than 90 μm, whether or not covered on one side with an adhesive layer and a release sheet	0 %	31.12.2013
ex 3919 90 69	97	Rolls of biaxially oriented polypropylene film with: — a self adhesive coating, — a width of 363 mm or more, but not more than 507 mm, — a total film thickness of 10 μm or more but not more than 100 μm, for use in the protection of LCD displays during the manufacturing of LCD modules (1)	0 %	31.12.2012
*ex 3920 10 26 ex 3920 10 89	30 20	Film of a thickness of not more than 0,20 mm, of a blend of polyethylene and a copolymer of ethylene with oct-1-ene, embossed in a regular rhomboidal pattern, for coating both sides of a layer of unvulcanized rubber (1)	0 %	31.12.2013
*ex 3920 10 26	40	Film of polyethylene, of a kind used for typewriter ribbon	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3920 10 28	91	Poly(ethylene) film of a thickness of 19 μm (± 1), printed with a graphic design which consists of eight different colours on one side of the film, and one colour on the opposite side, the graphic design also has the following characteristics: — is repetitive and equally spaced along the length of the film — is equally and visibly aligned when viewed from the back or front of the film	0 %	31.12.2013
ex 3920 10 89	40	Composite sheet containing an acrylic coating and laminated to a high-density polyethylene layer, of a total thickness of 0,8 mm or more but not more than 1,2 mm	0 %	31.12.2011
*ex 3920 20 21	30	Biaxially oriented polypropylene film with a coextruded layer of polyethylene on one side and a total thickness of 11,5 μm or more but not more than 13,5 μm.	0 %	31.12.2013
*ex 3920 20 29	92	Mono-axial oriented film, of a total thickness of not more than 75 μm, consisting of two or three layers, each layer containing a mixture of polypropylene and polyethylene, with a core layer whether or not containing titanium dioxide, having: — a tensile strength in the machine direction of 175 MPa or more but not more than 270 MPa and — a tensile strength in the transverse direction of 20 MPa or more but not more than 40 MPa as determined by test method ASTM D882/ISO 527-3	0 %	31.12.2013
*ex 3920 20 90	92	Laminated sheet or strip, consisting of a film of a thickness of 181 μm or more but not more than 223 μm composed of a blend of a copolymer of propylene with ethylene and a copolymer of styrene-ethylene-butylene-styrene (SEBS) coated or covered on one side with a layer of a copolymer of styrene-ethylene-butylene-styrene (SEBS) and a layer of polyester	0 %	31.12.2013
*ex 3920 43 10	92	Sheeting of poly(vinyl chloride), stabilized against ultraviolet rays, without any holes, even microscopic, of a thickness of 60 μm or more but not more than 80 μm, containing 30 or more but not more than 40 parts of plasticizer to 100 parts of poly (vinyl chloride)	0 %	31.12.2013
*ex 3920 43 10 ex 3920 49 10	94 93	Film of a specular gloss of 70 or more, measured at an angle of 60° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of one or two layers of poly(vinyl chloride) coated on both sides with a layer of plastic, of a thickness of 0,26 mm or more but not more than 1,0 mm, covered on the gloss surface with a protective film of polyethylene, in rolls of a width of 1 000 mm or more but not more than 1 450 mm, for use in the manufacture of goods of heading No 9403 ([1])	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3920 43 10	95	Reflecting laminated sheet, consisting of a film of poly(vinyl chloride) and a film of an other plastic totally embossed in a regular pyramidal pattern, covered on one side with a release sheet	0 %	31.12.2013
*ex 3920 43 10	96	Film, of a specular gloss of 70 or more measured at an angle of 60° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of a layer of poly(ethylene terephthalate) and a layer of coloured poly(vinyl chloride), for coating panels and doors of a kind used in the manufacture of domestic appliances ([1])	0 %	31.12.2013
*ex 3920 43 10	97	Film embossed to a depth of not more than 12 µm, of a specular gloss of 7 or more but not more than 17, measured at an angle of 60° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of at least two layers of poly(vinyl chloride), of a total thickness of not more than 0,5 mm, covered on the embossed side with a protective film, in rolls of a width of 1 400 mm or more but not more than 1 420 mm, for use in the manufacture of goods of heading No 9403 ([1])	0 %	31.12.2013
*ex 3920 51 00	10	Poly(methyl methacrylate) plate, with an antistatic coating, of dimensions of 738 × 972 mm (± 1,5 mm)	0 %	31.12.2013
*ex 3920 51 00	20	Plate of poly(methyl methacrylate) containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not more than 19 mm	0 %	31.12.2013
*ex 3920 51 00	40	Sheets of polymethylmethacrylate plastic complying with standards EN 4364 (MIL-P-5425E), EN 4365 (MIL-P-8184) and EN 4366 (MIL-PRF-25690)	0 %	31.12.2013
ex 3920 59 90	10	Non-cellular and non-laminated sheet of modified copolymer of acrylonitrile-methyl acrylate with a thickness of 1,0 mm or more but not more than 1,3 mm, put up in rolls	0 %	31.12.2011
*ex 3920 62 19 ex 3920 62 19	01 03	Coextruded opaque sheet of poly(ethylene terephthalate), of a thickness of 50 µm or more but not more than 350 µm, consisting especially of a layer containing carbon black	0 %	31.12.2013
*ex 3920 62 19 ex 3920 62 19	07 09	Poly(ethylene terephtalate) film, not coated with an adhesive, of a thickness of not more than 25 µm, either: — only dyed in the mass, or — dyed in the mass and metallized on one side	0 %	31.12.2013
*ex 3920 62 19 ex 3920 62 19	11 13	Film of poly(ethylene terephthalate) only, of a total thickness of not more than 120 µm, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3920 62 19 ex 3920 62 19	14 16	Poly(ethylene terephthalate) film, of a thickness of 20 μm or more but not more than 150 μm, coated on one side with silicone, for use in the manufacture of window film (1)	3 %	31.12.2011
*ex 3920 62 19 ex 3920 62 19	17 19	Laminated film of poly(ethylene terephthalate) only, of a total thickness of not more than 120 μm, consisting of one layer which is metallised only and one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0 %	31.12.2013
▼M26				
ex 3920 62 19	20	Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers (4)	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3920 62 19 ex 3920 62 19	21 23	Film of poly(ethylene terephthalate), coated or covered on one side or on both sides with a layer of modified polyester, of a total thickness of 7 μm or more but not more than 11 μm, for the manufacture of video tapes with a magnetic layer of metallic pigments and a width of 8 mm or of 12,7 mm (1)	0 %	31.12.2013
*ex 3920 62 19 ex 3920 62 19	37 39	Poly(ethylene terephthalate) film, of a thickness of not more than 12 μm, coated on one side with a layer of aluminium oxide of a thickness of not more than 35 nm	0 %	31.12.2013
*ex 3920 62 19 ex 3920 62 19	41 43	Poly(ethylene terephthalate) film, of a thickness of 18 μm or more but not more than 25 μm, having: — a shrinkage of (3,4 ± 0,1) % in the machine direction (as determined by the ASTM D 1204 method) and — a shrinkage of (0,3 ± 0,2) % in the transverse direction (as determined by the ASTM D 1204 method)	0 %	31.12.2013
*ex 3920 62 19 ex 3920 62 19	51 53	Film of poly(ethylene terephthalate), poly (ethylene naphtalate) or similar polyester, coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness of not more than 300 μm and having a surface resistivity of not more than 10 000 ohms (per square) (as determined by the ASTM D 257-99 method)	0 %	31.12.2013
*ex 3920 62 19 ex 3920 62 19	54 56	Matt film of poly(ethylene terephthalate), of a specular gloss of 15 measured at an angle of 45° and 18 measured at an angle of 60° using a glossmeter (as determined by the ISO 2813:2000 method) and a width of 1 600 mm or more	0 %	31.12.2013
*ex 3920 62 19 ex 3920 62 19	57 59	Film of white poly(ethylene terephthalate), dyed in the mass, of a thickness of 185 μm or more but not more than 253 μm, coated on both sides with an antistatic layer	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3920 62 19 ex 3920 69 00	73 40	Iridescent film of polyester and poly (methyl methacrylate)	0 %	31.12.2013
▼M26				
ex 3920 62 19 ex 3920 62 19	75 77	Transparent polyethylene terephthalate film, coated on both sides by thin layers of 7-80 nm each of organic substances on the basis of acryl, giving good adhesion property with surface tension of 37 Dyne/cm, with a light transmission of more than 93 %, a haze value of less than 1,3 %, a total thickness of 125 μm or 188 μm and a width of 850 mm or more, but not more than 1 600 mm	0 %	1.7.2009-31.12.2013
▼M25				
ex 3920 62 19 ex 3920 62 19	80 82	Poly(ethylene terephtalate) film of a thickness of not more than 20 μm, coated on both sides with a gas barrier layer consisting of a polymeric matrix in which silica has been dispersed and of a thickness of not more than 2 μm	0 %	31.12.2012
*ex 3920 62 19	88	Laminated sheet, consisting of a biaxially oriented film of poly(ethylene terephthalate), covered on one side or on both sides with a layer of poly(ethylene terephthalate), for use in the manufacture of identity cards, credit cards and similar products (including 'smart' cards) (1)	0 %	31.12.2013
*ex 3920 69 00	20	Film of poly(ethylene naphthalene-2,6-dicarboxylate)	0 %	31.12.2013
ex 3920 79 90	10	Cellulose acetyl butyrate film, whether or not combined with a polycarbonate layer, of a thickness of not more than 0,81 mm containing a micro-louvre with a typical viewing angle of 30 degrees measured on each side of the surface normal	0 %	31.12.2012
*ex 3920 91 00	91	Poly(vinyl butyral) film having a graduated coloured band	3 %	31.12.2013
*ex 3920 91 00	92	Plasticized film of polyvinyl butyral, containing by weight: — either 14,5 % or more but not more than 17,5 % of dihexyl adipate, — or 14,5 % or more but not more than 28,5 % of dibutyl sebacate	0 %	31.12.2013
*ex 3920 91 00	93	Film of poly(ethylene terephthalate), whether or not metallised on one or both sides, or laminated film of poly(ethylene terephthalate) films, metallised on the external sides only, and having the following characteristics: — a visible light transmission of 50 % or more, — coated on one or both sides with a layer of poly(vinyl butyral) but not coated with an adhesive or any other material except poly(vinyl butyral), — a total thickness of not more than 0,2 mm without taking the presence of poly(vinyl butyral) into account, for use in the manufacture of heat-reflecting or decorative laminated glass (1)	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26				
ex 3920 91 00	95	Co-extruded trilayer poly(vinyl butyral) film with a graduated colour band containing by weight 29 % or more but not more than 31 % of 2,2'-ethylenedioxydiethyl bis(2-ethylhexanoate) as a plasticiser	0 %	1.7.2009-31.12.2013
▼M25				
ex 3920 92 00	30	Polyamide film of a thickness of not more than 20 μm, coated on both sides with a gas barrier layer which consists of a polymeric matrix in which silica has been dispersed and of a thickness of not more than 2 μm	0 %	31.12.2012
▼M26				
_____				
**ex 3920 99 28	40	Polymer film containing the following monomers: — Poly (tetramethylene ether glycol), — Bis (4-isocyanotocyclohexyl) methane, — 1,4-Butanediol or 1,3-Butanediol, — with a thickness of 0,25 mm or more but not more than 5,0 mm, — embossed with a regular pattern on one surface, and — covered with a release sheet.	0 %	1.7.2009-31.12.2013
▼M25				
ex 3920 99 28	50	Thermoplastic polyurethane film, of a thickness of 250 μm or more but not more than 350 μm, covered on one side with a removable protective film	0 %	31.12.2011
*ex 3920 99 59	25	Poly(1-chlorotrifluoroethylene) film	0 %	31.12.2013
*ex 3920 99 59	50	Polytetrafluoroethylene film, non-microporous, in the form of rolls, of a thickness of 0,019 mm or more but not more than 0,14 mm, impermeable to water vapour	0 %	31.12.2013
*ex 3920 99 59	55	Ion-exchange membranes of fluorinated plastic material	0 %	31.12.2013
*ex 3920 99 59	60	Film of a vinyl alcohol copolymer, soluble in cold water, of a thickness of 34 μm or more but not more than 90 μm, a tensile strength at break of 20 MPa or more but not more than 45 MPa and an elongation at break of 250 % or more but not more than 900 %	0 %	31.12.2013
*ex 3920 99 90	20	Anisotropic conductive film, in rolls, of a width of 1,5 mm or more but not more than 3,15 mm and a maximum length of 300 m, used for joining electronic components in the production of LCD or plasma displays	0 %	31.12.2013
*ex 3921 13 10	10	Sheet of polyurethane foam, of a thickness of 3 mm (± 15 %) and of a specific gravity of 0,09435 or more but not more than 0,10092	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3921 19 00	91	Microporous polypropylene film of a thickness of not more than 100 μm	0 %	31.12.2013
▼M26				
ex 3921 19 00	93	Strip of microporous polytetrafluoroethylene on a support of a non-woven, for use in the manufacture of filters for kidney dialysis equipment (4)	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3921 19 00	95	Film of polyethersulfone, of a thickness of not more than 200 μm	0 %	31.12.2013
*ex 3921 19 00	96	Cellular film, consisting of a layer of polyethylene of a thickness of 90 μm or more but not more than 140 μm and a layer of regenerated cellulose of a thickness of 10 μm or more but not more than 40 μm	0 %	31.12.2013
*ex 3921 90 19	45	Composite plate of poly(ethylene terephthalate) or of poly(butylene terephthalate), reinforced with glass fibres	0 %	31.12.2013
*ex 3921 90 19	55	Poly(ethylene terephthalate) film, laminated on one side or on both sides with a layer of unidirectional nonwoven poly(ethylene terephthalate) and impregnated with polyurethane or epoxide resin	0 %	31.12.2013
▼M26				
**ex 3921 90 55	20	Pre-impregnated reinforced fibreglass containing cyanate ester resin or bismaleimide (B) triazine (T) resin mixed with epoxide resin, measuring: — 469,9 mm (± 2 mm) × 622,3 mm (± 2 mm), or — 469,9 mm (± 2 mm) × 414,2 mm (± 2 mm), or — 546,1 mm (± 2 mm) × 622,3 mm (± 2 mm).	0 %	1.7.2009-31.12.2013
▼M25				
*ex 3921 90 60 ex 5407 71 00 ex 5903 90 99	91 20 10	Woven polytetrafluoroethylene fabric, coated or covered with a copolymer of tetrafluoroethylene and trifluoroethylene having perfluorinated alkoxy side-chains ending in carboxylic acid or sulphonic acid groups, whether or not in the potassium or sodium salt form	0 %	31.12.2013
*ex 3921 90 60	93	Film, of a specular gloss of 30 or more but not more than 60 measured at an angle of 60° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of a layer of poly(ethylene terephthalate) and a layer of coloured poly(vinyl chloride), joined by a metallized adhesive coating, for coating panels and doors of a kind used in the manufacture of domestic appliances (1)	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 3923 30 90	10	Polyethylene container, for compressed hydrogen: — with aluminium bosses at both ends, — wholly embedded in an overwrap of carbon fibres impregnated with epoxide resin, — of a diameter of 213 mm or more, but not more than 368 mm, — a length of 860 mm or more, but not more than 1 260 mm and — a capacity of 18 litres or more, but not more than 50 litres	0 %	31.12.2013
*ex 3926 90 92	20	Reflecting sheeting or tape, consisting of a facing-strip of poly(vinyl chloride) embossed in a regular pyramidal pattern, heat-sealed in parallel lines or in a grid-pattern to a backing-strip of plastic material, or of knitted or woven fabric covered on one side with plastic material	0 %	31.12.2013
*ex 3926 90 97	10	Microspheres of a polymer of divinylbenzene, of a diameter of 4,5 μm or more but not more than 80 μm	0 %	31.12.2013
*ex 3926 90 97	15	Glass fibre reinforced plastic traverse leaf spring for use in the manufacture of motor vehicle suspension systems (1)	0 %	31.12.2013
*ex 3926 90 97	25	Unexpansible microspheres of a copolymer of acrylonitrile, methacrylonitrile and isobornyl methacrylate, of a diameter of 3 μm or more but not more than 4,6 μm	0 %	31.12.2013
*ex 3926 90 97	55	Flat product of polyethylene, perforated in opposing directions, of a thickness of 600 μm or more but not more than 1 200 μm and of a weight of 21 g/m^2 or more but not more than 42 g/m^2	0 %	31.12.2013
*ex 4007 00 00	10	Siliconated vulcanised rubber thread and cord	0 %	31.12.2013
*ex 4016 99 97	20	Soft rubber sealing stoppers for the manufacture of electrolytic capacitors (1)	0 %	31.12.2013
*4105 10 10 4105 10 90 4105 30 91 4105 30 99		Sheep or lamb skin leather, without wool on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4 114	0 %	31.12.2013
*4106 21 10 4106 22 90		Goat or kid skin leather, without hair on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4 114	0 %	31.12.2013
*4106 31 10 4106 32 90 4106 40 90 4106 92 00		Leather of other animals, without hair on, not further prepared than tanned, other than leather of heading No 4 114	0 %	31.12.2013
ex 5004 00 10	10	Silk yarn (other than yarn spun from silk waste) not put up for retail sale, unbleached, scoured or bleached, entirely of silk	0 %	31.12.2011
ex 5004 00 90	10	Yarn spun entirely from silk, not put up for retail sale	2,5 %	31.12.2011

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 5005 00 10 ex 5005 00 90	10 10	Yarn spun entirely from silk waste (noil), not put up for retail sale	0 %	31.12.2013
*ex 5205 31 00	10	Six ply yarn of bleached cotton, measuring 925 dtex or more but not more than 989 dtex per single yarn, for the manufacture of tampons (1)	0 %	31.12.2013
*5208 11 10		Fabrics for the manufacture of bandages, dressings and medical gauzes	5,2 %	31.12.2013
*ex 5402 45 00	20	Yarn of synthetic textile fibres solely of aromatic polyamides obtained by the poly-condensation of *m*-phenylenediamine and isophthalic acid	0 %	31.12.2013
*ex 5402 47 00	10	Synthetic bicomponent filament yarn, not textured, untwisted, measuring 1 650 decitex or more but not more than 1 800 decitex, consisting of 110 filaments or more but not more than 120 filaments, each having a core of poly(ethylene terephthalate) and a skin of polyamide-6, containing by weight 75 % or more but not more than 77 % of poly(ethylene terephthalate), for use in the manufacture of roofings (1)	0 %	31.12.2011
*ex 5402 49 00	30	Yarn of a copolymer of glycollic acid with lactic acid, for the manufacture of surgical sutures (1)	0 %	31.12.2013
*ex 5402 49 00	50	Non-textured filament yarn of poly(vinyl alcohol)	0 %	31.12.2013
*ex 5402 49 00	70	Synthetic filament yarn, single, containing by weight 85 % or more of acrylonitrile, in the form of a wick containing 1 000 continuous filaments or more but not more than 25 000 continuous filaments, of a weight per metre of 0,12 g or more but not more than 3,75 g and of a length of 100 m or more, for the manufacture of carbon-fibre yarn (1)	0 %	31.12.2013
*ex 5404 19 00	20	Monofilament of poly(1,4-dioxanone)	0 %	31.12.2013
*ex 5404 19 00	50	Monofilaments of polyester or poly (butylene terephthalate), with crosssectional dimension of 0,5 mm or more but not more than 1 mm, for use in the manufacture of zippers (1)	0 %	31.12.2013
*ex 5404 90 90	20	Strip of polyimide	0 %	31.12.2013
ex 5407 10 00	10	Textile fabric, consisting of warp filament yarns of polyamide-6.6 and weft filament yarns of polyamide-6.6, polyurethane and a copolymer of terephthalic acid, *p*-phenylenediamine and 3,4'-oxybis (phenyleneamine)	0 %	31.12.2012
*ex 5503 11 00 ex 5601 30 00	10 40	Synthetic staple fibres of a copolymer of terephthalic acid, *p*-phenylenediamine and 3,4'-oxybis(phenyleneamine), of a length of not more than 7 mm	0 %	31.12.2013
*ex 5503 90 00 ex 5506 90 00 ex 5601 30 00	20 10 10	Poly(vinyl alcohol) fibres, whether or not acetalized	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 5603 11 10 ex 5603 11 90 ex 5603 12 10 ex 5603 12 90 ex 5603 91 10 ex 5603 91 90 ex 5603 92 10 ex 5603 92 90	10 10 10 10 10 10 10 10	Poly(vinyl alcohol) non-wovens, in the piece or cut into rectangles: — of a thickness of 200 μm or more but not more than 280 μm and — of a weight of 20 g/m^2 or more but not more than 50 g/m^2	0 %	31.12.2013
ex 5603 11 10 ex 5603 11 90	20 20	Nonwovens, not weighing more than 20 g/m^2, containing spunbonded and meltblown filaments put together in a sandwich way with the two outer layers containing fine endless filaments (not less than 10 μm but not more than 20 μm in diameter) and the inner layer containing super-fine endless filaments (not less than 1 μm but not more than 5 μm in diameter), for the manufacture of napkins and napkin liners for babies and similar sanitary napkins ([1])	0 %	31.12.2012
*ex 5603 12 90 ex 5603 13 90 ex 5603 14 90 ex 5603 92 90 ex 5603 93 90 ex 5603 94 90	30 30 10 60 40 30	Non-wovens of aromatic polyamide fibres obtained by polycondensation of *m*-phenylenediamine and isophthalic acid, in the piece or cut into rectangles	0 %	31.12.2013
ex 5603 12 90	50	Non-woven: — weighing 30 g/m^2 or more, but not more than 60 g/m^2, — containing fibres of polypropylene or of polypropylene and polyethylene, — whether or not printed, with: — on one side, 65 % of the total surface area having circular bobbles of 4 mm in diameter, consisting of anchored, elevated un-bonded curly fibres, suitable for the engagement of extruded hook materials, and the remaining 35 % of the surface area being bonded, — and on other side a smooth untextured surface, for use in the manufacture of napkins and napkin liners for babies and similar sanitary articles ([1])	0 %	31.12.2012
*ex 5603 12 90 ex 5603 13 90	60 60	Non-woven of spunbonded polyethylene, of a weight of more than 60 g/m^2 but not more than 80 g/m^2 and an air resistance (Gurley) of 8 s or more but not more than 36 s (as determined by the ISO 5636/5 method)	0 %	31.12.2013
*ex 5603 12 90 ex 5603 13 90 ex 5603 92 90 ex 5603 93 90	70 70 40 10	Non-wovens of polypropylene, consisting of a meltblown layer, laminated on each side with spunbonded filaments of polypropylene, of a thickness of not more than 550 μm and of a weight of not more than 80 g/m^2, in the piece or simply cut into squares or rectangles, not impregnated	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26				
ex 5603 13 10 ex 5603 14 10	10 10	Electrically non-conductive non-wovens, consisting of a central film of poly (ethylene terephthalate) laminated on each side with unidirectionally aligned fibres of poly(ethylene terephthalate), coated on both sides with high grade temperature resistant electrical non-conductive resin, weighing 147 g/m^2 or more but not more than 265 g/m^2, with non-isotropic tensile strength on both directions, to be used as electrical insulation material	0 %	1.7.2009-31.12.2013
▼M25				
*ex 5603 14 90	30	Non-wovens, consisting of a central elastomeric film laminated on each side with spunbonded filaments of polypropylene, of a weight of 200 g/m^2 or more but not more than 300 g/m^2	0 %	31.12.2013
*ex 5603 92 90 ex 5603 93 90	20 20	Non-wovens consisting of a meltblown central layer of a thermoplastic elastomer laminated on each side with spunbonded filaments of polypropylene	0 %	31.12.2013
*ex 5603 92 90 ex 5603 94 90	70 40	Non-wovens, consisting of multiple layers of a mixture of meltblown fibres and staple fibres of polypropylene and polyester, whether or not laminated on one side or on both sides with spunbonded filaments of polypropylene, of a total thickness of not more than 50 mm	0 %	31.12.2013
*ex 5603 94 90	20	Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips ([1])	0 %	31.12.2013
*ex 5803 00 10	91	Gauze of cotton, of a width of less than 1 500 mm	0 %	31.12.2013
*ex 5903 10 90 ex 5903 20 90 ex 5903 90 99	10 10 20	Knitted or woven fabrics, coated or covered on one side with artificial plastic material in which are embedded microspheres	0 %	31.12.2013
*ex 5906 99 90	10	Rubberised textile fabric, consisting of warp yarns of polyamide-6.6 and weft yarns of polyamide-6.6, polyurethane and a copolymer of terephthalic acid, *p*-phenylenediamine and 3,4'-oxybis(phenyleneamine)	0 %	31.12.2013
*ex 5907 00 00	10	Textile fabrics, coated with adhesive in which are embedded spheres of a diameter of not more than 150 μm	0 %	31.12.2011
*ex 5911 10 00	10	Needle-punched synthetic-fibre felts, not containing polyester, whether or not containing catalytic particles entrapped within the synthetic fibres, coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products ([1])	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 5911 90 90 ex 8421 99 00	30 92	Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness of not more than 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more	0 %	31.12.2013
*ex 6805 10 00 ex 6805 20 00 ex 6805 30 80	10 10 10	Abrasive in the form of identically shaped particles on a support	0 %	31.12.2013
*ex 6813 89 00	10	Friction material, of a thickness of less than 20 mm, not mounted, for the manufacture of friction components of a kind used in automatic transmissions and clutches (1)	0 %	31.12.2013
*ex 6903 90 90	20	Silicon carbide reactor tubes and holders, of a kind used for insertion into diffusion and oxidation furnaces for production of semiconductor materials	0 %	31.12.2013
*ex 6909 19 00	30	Supports for catalysts, consisting of porous cordierite or mullite ceramic pieces, of an overall volume of not more than 65 l, having, per cm^2 of the cross-section, not less than one continuous channel which may be open at both ends or stopped at one end	0 %	31.12.2013
*ex 6909 19 00 ex 6914 90 90	50 20	Ceramic articles made of continuous filaments of ceramic oxides, containing by weight: — 2 % or more of diboron trioxide, — 28 % or less of silicon dioxide and — 60 % or more of dialuminium trioxide	0 %	31.12.2013
*ex 6909 19 00	60	Supports for catalysts, consisting of porous ceramic pieces, of a blend of silicon carbide and silicon, with a hardness of less than 9 on the Mohs scale, with a total volume of not more than 65 litres, having, per cm^2 of the surface of the cross section one or more closed channels at the tail end	0 %	31.12.2013
*ex 6914 90 90	30	Ceramic microspheres, transparent, obtained from silicon dioxide and zirconium dioxide, of a diameter of more than 125 μm	0 %	31.12.2013
*ex 7002 10 00	10	Balls of E-glass, of a diameter of 18,5 mm or more but not more than 26 mm	0 %	31.12.2013
*ex 7005 10 25	10	Float glass: — of a thickness of 2,0 mm or more but not more than 2,4 mm, — coated on one surface with a fluorine doped tin dioxide reflective layer	0 %	31.12.2012

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 7005 10 30	10	Float glass: — of a thickness of 4,0 mm or more but not more than 4,2 mm, — with a light transmission of 91 % or more measured using a D-type light source, — coated on one surface with a fluorine doped tin dioxide reflective layer	0 %	31.12.2012
*ex 7006 00 90	50	Glass plate of a diagonal size of 81 cm or more, but not more than 186 cm, provided either with a mesh film or a sputtered conductive layer for EMC shielding and a near-infrared absorbing film, with optional additional anti-reflex/colour enhancement layers on one or both sides	0 %	31.12.2013
ex 7006 00 90 ex 8529 90 92	60 46	Soda-lime glass plates with: — a strain point of more than 570 °C — a thickness of 1,7 mm or more but not more than 2,9 mm — dimensions of 1 144 mm (± 0,5 mm) × 670 mm (± 0,5 mm) or 1 164 mm (± 0,5 mm) × 649 mm (± 0,5 mm) and — whether or not containing: — an Indium-Tin Oxide film, or — a grid of electrodes made from silver paste covered by dielectric material	0 %	31.12.2012
*ex 7007 19 20	10	Glass plate of a diagonal size of 81,28 cm (± 1,5 cm) or more, but not more than 185,42 cm (± 1,5 cm), consisting of tempered glass; provided either with a mesh film and a near-infrared absorbing film or a sputtered conductive layer, with optional additional anti-reflex layer on one or both sides, for use in the manufacture of products falling within heading 8 528 ([1])	0 %	31.12.2013
ex 7007 19 20	20	Tempered or semi-tempered glass plate of a diagonal size of 81 cm or more, but not more than 186 cm, with one or more polymer layers, whether or not painted or with coloured or black ceramics around the surrounding edges, for use in the manufacture of goods falling within heading 8 528 ([1])	0 %	31.12.2012
*ex 7007 29 00	10	Glass plate of a diagonal size of 81,28 cm (± 1,5 cm) or more, but not more than 185,42 cm (± 1,5 cm), consisting of 2 sandwich plates laminated together; provided either with a mesh film and a near-infrared absorbing film or a sputtered conductive layer, with optional additional anti-reflex layer on one or both sides	0 %	31.12.2013
*ex 7011 10 00	10	Glass lenses with a stippled front refractor or with a front refractor composed of prismatic elements, with an external diameter of more than 121 mm but not more than 125 mm	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26				
7011 20 00		Glass envelopes (including bulbs and tubes), open, and glass parts thereof, without fittings, for cathode ray tubes	0 %	1.7.2009-31.12.2013
▼M25				
*ex 7014 00 00	10	Optical elements of glass (other than those of heading No 7015), not optically worked, other than signalling glassware	0 %	31.12.2013
*ex 7019 12 00	10	Rovings, measuring 2 600 tex or more but not more than 3 300 tex and of a loss on ignition of 4 % or more but not more than 8 % by weight (as determined by the ASTM D 2584-94 method)	0 %	31.12.2013
*ex 7019 12 00	15	Rovings, measuring 650 tex or more but not more than 2 500 tex, coated with a layer of polyurethane whether or not mixed with other materials	0 %	31.12.2013
*ex 7019 12 00	50	Rovings, measuring 392 tex or more but not more than 2 884 tex, coated with a layer of an acrylic copolymer	0 %	31.12.2013
*ex 7019 12 00	70	Rovings, measuring 417 tex or more but not more than 3 180 tex, coated with a layer of poly(sodium acrylate) and poly (acrylic acid)	0 %	31.12.2013
*ex 7019 19 10	10	Yarn of 33 tex or a multiple thereof (± 7,5 %), obtained from continuous spun-glass filaments of a nominal diameter of 3,5 µm or of 4,5 µm, in which filaments of a diameter of 3 µm or more but not more than 5,2 µm predominate, other than those treated so as to improve their adhesion to elastomers	0 %	31.12.2013
▼M26				
ex 7019 19 10	30	Yarn of E-glass of 22 tex (± 1,6 tex), obtained from continuous spun-glass filaments of a nominal diameter of 7 µm, in which filaments of a diameter of 6,35 µm or more but not more than 7,61 µm predominate	0 %	1.7.2009-31.12.2013
▼M25				
*ex 7019 19 10	50	Yarn of E-glass of 68 or 74 tex (± 7 %), obtained from continuous spun-glass filaments of a nominal diameter of 9 µm, in which filaments of a diameter of 8,1 µm or more but not more than 9,9 µm predominate, for the manufacture of woven fabrics for electrical laminates (prepregs) [1]	0 %	31.12.2013
*ex 7019 19 10 ex 7019 90 99	60 30	High modulus glass cord (K) impregnated with rubber, obtained from twisted high modulus glass filament yarns, coated with a latex comprising a resorcinol-formaldehyde resin with or without vinylpyridine and/or hydrogenated acrylonitrile-butadiene rubber (HNBR)	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 7019 19 10 ex 7019 90 99	70 20	Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formal-dehyde-vinylpyridine resin and an acrylo-nitrile-butadiene rubber (NBR)	0 %	31.12.2013
*ex 7019 19 10 ex 7019 90 99	80 10	Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formal-dehyde resin and chlorosulphonated poly-ethylene	0 %	31.12.2013
ex 7019 39 00	50	Non-woven product of non-textile glass fibre, for the manufacture of air filters (1)	0 %	31.12.2011
*ex 7019 40 00	10	Woven fabrics of rovings, impregnated with epoxy resin, with a coefficient of thermal expansion between 30 °C and 120 °C (measured according to IPC-TM-650) of — 10 ppm per °C or more, but not more than 12 ppm per °C in the length and width and — 20 ppm per °C or more, but not more than 30 ppm per °C in the thickness, with a glass transition temperature of 152 °C or more, but not more than 153 °C (measured according IPC-TM-650)	0 %	31.12.2013
*ex 7019 90 10	10	Non-textile glass fibres in which fibres of a diameter of less than 4,6 μm predominate	0 %	31.12.2013
ex 7201 10 11	10	Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm	0 %	31.12.2011
ex 7201 10 30	10	Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm, containing by weight not more than 1 % of silicon	0 %	31.12.2011
*7202 50 00		Ferro-silico-chromium	0 %	31.12.2013

▼M26

ex 7320 90 10	91	Flat spiral spring of tempered steel, with: — a thickness of 2,67 mm or more, but not more than 4,11 mm, — a width of 12,57 mm or more, but not more than 16,01 mm, — a torque of 18,05 Nm or more, but not more than 73,5 Nm, — an angle between the free position and the nominal position in exercise of 76° or more, but not more than 218°, for use in the manufacture of tensioners for power transmission belts, for internal combustion engines (4)	0 %	1.7.2009-31.12.2013

▼M25

ex 7326 20 80	20	Metal fleece, consisting of a mass of stainless steel wires of diameters ranging from 0,022 mm to 0,070 mm, compacted by sintering and rolling	0 %	31.12.2011

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26				
ex 7410 11 00 ex 7410 21 00	10 60	Copper foil of a thickness of not more than 0,15 mm, coated with resin, free of halogen, with: — a decomposition temperature of 350 °C or more (measured according to ASTM D 3850), and — a time to delamination at 260 °C of more than 40 minutes and at 288 °C of more than 5 minutes (measured according to IPC-TM-650).	0 %	1.7.2009-31.12.2013
▼M25				
*ex 7410 21 00	10	Sheet or plate of polytetrafluoroethylene, containing aluminium oxide or titanium dioxide as filler or reinforced with glass-fibre fabric, covered on both sides with copper foil	0 %	31.12.2013
*ex 7410 21 00	30	Film of polyimide, not containing epoxide resin and/or glass fibre, covered on one side or on both sides with a copper foil	0 %	31.12.2013
▼M26				
**ex 7410 21 00	40	Sheet or plates — consisting of at least a central layer of paper or one central sheet of any type of non-woven fibre, laminated on each side with glass-fibre fabric and impregnated with epoxide resin, or — consisting of multiple layers of paper, impregnated with phenolic resin, coated on one or both sides with a copper film with a maximum thickness of 0,15 mm	0 %	1.7.2009-31.12.2013
**ex 7410 21 00	50	Plates — consisting of at least one layer of fibreglass fabric impregnated with epoxide resin, — covered on one or both sides with copper foil with a thickness of not more than 0,15 mm, and — with a dielectric constant (DK) of less than 3,9 and a loss factor (Df) of less than 0,015 at a measuring frequency of 10 GHz, as measured according to IPC-TM-650.	0 %	1.7.2009-31.12.2013
▼M25				
*ex 7419 99 90 ex 7616 99 90	91 60	Disc (target) with deposition material, consisting of molybdenum silicide: — containing 1 mg/kg or less of sodium and — mounted on a copper or aluminium support	0 %	31.12.2013
ex 7601 20 99	10	Sheets and billets of secondary aluminium alloy containing lithium	0 %	31.12.2012

▼M25

	CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26					
	ex 7604 21 00	10	Profiles made of aluminium alloy conforming to EN standard AW-6063 T5	0 %	1.7.2009-31.12.2013
	ex 7604 29 90	30	— anodised, — whether or not lacquered, — with a wall thickness of 0,5 mm (± 1,2 %) or more but not more than 0,8 mm (± 1,2 %), for use in the manufacture of goods of subheading 8302 (4)		
▼M25					
	*ex 7605 19 00	10	Not alloyed aluminium wire, of a diameter of 2 mm or more but not more than 6 mm, covered with a layer of copper of a thickness of 0,032 mm or more but not more than 0,117 mm	0 %	31.12.2013
	ex 7606 12 10 ex 7607 11 90	10 20	Strip of an alloy of aluminium and magnesium, containing by weight: — 93,3 % or more of aluminium, — 2,2 % or more but not more than 5 % of magnesium, and — not more than 1,8 % of other elements, in rolls, of a thickness of 0,14 mm or more but not more than 0,40 mm and a width of 12,5 mm or more but not more than 89 mm, with a tensile strength of 285 N/mm^2 or more and an elongation at break of 1,0 % or more	0 %	31.12.2012
▼M26					
	———————				
▼M25					
	ex 7607 11 90	10	Plain aluminium foil with the following parameters: — an aluminium content of 99,98 % or more — a thickness of 0,070 mm or more but not more than 0,115 mm — with a cubic texture of a kind used for high voltage etching (1)	0 %	31.12.2011
	ex 7607 20 99	10	Aluminium laminated film of a total thickness of not more than 0,123 mm, comprising of a layer of aluminium of a thickness of not more than 0,040 mm, polyamide and polypropylene base films, and a protective coating against corrosion by hydrofluoric acid, for use in the manufacture of lithium polymer batteries (1)	0 %	31.12.2012
	*ex 7613 00 00	20	Aluminium container, seamless, for compressed natural gas or compressed hydrogen, wholly embedded in an overwrap of epoxy-carbon fibres composite, of a storage capacity of 172 l (± 10 %) and an unfilled weight of not more than 64 kg	0 %	31.12.2013
	*ex 7616 99 90	15	Honeycomb aluminium blocks of the type used in the manufacture of aircraft parts	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*8104 11 00		Unwrought magnesium, containing at least 99,8 % by weight of magnesium	0 %	31.12.2013
*ex 8104 90 00	10	Ground and polished magnesium sheets, of dimensions not more than 1 500 × 2 000 mm, coated on one side with an epoxy resin insensitive to light	0 %	31.12.2013
*ex 8108 20 00	10	Titanium sponge	0 %	31.12.2013
*ex 8108 20 00	20	Titanium alloy ingots	0 %	31.12.2013
▼M26				
ex 8108 20 00	30	Titanium powder of which 90 % by weight or more passes through a sieve with an aperture of 0,224 mm	0 %	1.7.2009-31.12.2013
▼M25				
*ex 8108 30 00	10	Waste and scrap of titanium and titanium alloys, except those containing by weight 1 % or more but not more than 2 % of aluminium	0 %	31.12.2013
ex 8108 90 30	10	Titanium alloy rods complying with standard EN 2002-1 or EN 4267	0 %	31.12.2012
ex 8108 90 30	20	Bars, rods and wire of alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, for use in the manufacture of silencers and exhaust pipes of subheadings 8708 92 or 8714 19 ([1])	0 %	31.12.2012
*ex 8108 90 50	10	Alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, in sheets or rolls, of a thickness of 0,49 mm or more but not more than 3,1 mm, of a width of 1 000 mm or more but not more than 1 254 mm, for the manufacture of goods of subheading 8714 19 00 ([1])	0 %	31.12.2013
*ex 8108 90 50	20	Alloy of titanium, aluminium and vanadium, containing by weight 2,5 % or more but not more than 3,5 % of aluminium and 2,0 % or more but not more than 3,0 % of vanadium, in sheets or rolls, of a thickness of 0,6 mm or more but not more than 0,9 mm, of a width of not more than 1 000 mm, for the manufacture of goods of subheading 8714 19 00 ([1])	0 %	31.12.2013
*ex 8108 90 50	30	Alloy of titanium and silicon, containing by weight 0,15 % or more but not more than 0,60 % of silicon, in sheets or rolls, for use in the manufacture of: — exhaust systems for internal combustion engines or — tubes and pipes of subheading 8108 90 60 ([1])	0 %	31.12.2012
ex 8108 90 50	40	Titanium-alloy sheets for the manufacture of structural parts of aircrafts ([1])	0 %	31.12.2012
ex 8108 90 50	50	Plates, sheets, strips and foils of an alloy of titanium, copper and niobium, containing by weight 0,8 % or more but not more than 1,2 % of copper and 0,4 % or more but not more than 0,6 % of niobium	0 %	31.12.2012

▼**M25**

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8108 90 50	60	Plates, sheets, strips and foils of an alloy of titanium, aluminium, silicon and niobium, containing by weight: — 0,4 % or more but not more than 0,6 % of aluminium, — 0,35 % or more but not more than 0,55 % of silicon and — 0,1 % or more but not more than 0,3 % of niobium	0 %	31.12.2013
*ex 8109 20 00	10	Non-alloy zirconium, in the form of ingots, containing by weight more than 0,01 % of hafnium, for use in the manufacture of tubes for the chemical industry (1)	0 %	31.12.2013
*ex 8110 10 00	10	Antimony in the form of ingots	0 %	31.12.2013
*ex 8112 99 30	10	Alloy of niobium (columbium) and titanium, in the form of bars and rods	0 %	31.12.2013
*ex 8113 00 90	10	Carrier plate of aluminium silicon carbide (AlSiC-9) for electronic circuits	0 %	31.12.2012
*ex 8305 20 00	10	Staples of a width of 12 mm (± 1 mm) and a depth of 8 mm (± 1 mm) for use in copiers and printers (1)	0 %	31.12.2013
*ex 8309 90 90	10	Aluminium can ends with so-called 'ring pull' full aperture with a diameter of 136,5 mm (± 1 mm)	0 %	31.12.2013
*ex 8401 30 00	20	Non-irradiated hexagonal fuel modules (elements) for use in nuclear reactors (1)	0 %	31.12.2013
*ex 8407 31 00	10	Two stroke internal combustion engine, of a cylinder capacity of not more than 30 cm^3 for use in the manufacture of portable motorised scooters falling within subheading 8711 10 00 (1)	0 %	31.12.2012
ex 8407 33 90 ex 8407 90 80 ex 8407 90 90	10 10 10	Spark-ignition reciprocating or rotary internal combustion piston engines, having a cylinder capacity of not less than 300 cm^3 and a power of not less than 6 kW but not exceeding 20,0 kW, for the manufacture of: — self-propelled lawn mowers, with a seat of sub-heading 8433 11 51 — tractors of subheading 8701 90 11, whose main function is that of a lawn mower — four stroke mowers with motor of a cylinder capacity of not less than 300 cc of subheading 8433 20 10 or — snowploughs and snow blowers of subheading 8430 20 (1)	0 %	31.12.2012
*ex 8407 90 10	10	Four-stroke petrol engines of a cylinder capacity of not more than 250 cm^3 for use in the manufacture of lawnmowers of sub-heading 8433 11, mowers with motor of subheading 8433 20 10, rotovators of sub-heading 8432 29 50, garden shredders of sub-heading 8436 80 90 or scarifiers of subheading 8432 29 10 (1)	0 %	31.12.2011

▼**M25**

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8407 90 10	20	Two-stroke internal combustion engines, having a cylinder capacity of not more than 125 cm^3, for the manufacture of lawnmowers of sub-heading 8433 11 or snowploughs and snow blowers of subheading 8430 20 (1)	0 %	31.12.2013
*ex 8408 90 41	20	Diesel engines of a power of not more than 15 kW, with 2 or 3 cylinders, for use in the manufacture of vehicle mounted temperature control systems (1)	0 %	31.12.2013
*ex 8408 90 43	20	Diesel engines of a power of not more than 30 kW, with 4 cylinders, for use in the manufacture of vehicle mounted temperature control systems (1)	0 %	31.12.2013
ex 8413 91 00	20	Manganese-silicon-bronze swash plates with a copper content of 58 % or more but not more than 63 % by weight for incorporation into fluid pumps for air conditioners of motor vehicles	0 %	31.12.2011
*ex 8414 30 89	20	Vehicle air conditioning system part, consisting of an open shaft reciprocating compressor of a power of more than 0,4 kW but not more than 10 kW	0 %	31.12.2013
*ex 8414 59 20	30	Axial fan: — with an electric motor, — of an output of not more than 125 W for use in the manufacture of computers (1)	0 %	31.12.2013
*ex 8414 90 00	20	Aluminium pistons, partially covered with polytetrafluoroethylene, for incorporation into compressors of air conditioning machines of motor vehicles (1)	0 %	31.12.2013
*ex 8414 90 00	30	Pressure-regulating system, for incorporation into compressors of air conditioning machines of motor vehicles (1)	0 %	31.12.2013
*ex 8414 90 00	40	Drive part, for compressors of air conditioning machines of motor vehicles (1)	0 %	31.12.2013
ex 8414 90 00	50	Cross-flow fan, of 97,4 mm (± 0,2 mm) diameter and 645 mm (± 1 mm) or 873 mm (+ 0,5/-1 mm) height made from anti-static, anti-bacterial and heat-resistant, glass fiber reinforced plastic with a minimum temperature resistance of 70 °C, for use in the manufacture of indoor air conditioning units (1)	0 %	31.12.2011
ex 8415 90 00	20	Evaporator made of aluminium for use in the manufacture of air conditioning machines for automobiles (1)	0 %	31.12.2011
ex 8419 89 98	30	Apparatus for vapour deposition of parylene for use in the manufacture of drug eluting stents (1)	0 %	31.12.2012

▼**M25**

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8419 89 98	40	Solution preparation apparatus for the treatment of materials by a process involving a change of temperature for use in the manufacture of drug-eluting stents (1)	0 %	31.12.2012
*ex 8421 99 00	91	Parts of equipment, for the purification of water by reverse osmosis, consisting of a bundle of hollow fibres of artificial plastic material with permeable walls, embedded in a block of artificial plastic material at one end and passing through a block of artificial plastic material at the other end, whether or not housed in a cylinder	0 %	31.12.2013
*ex 8421 99 00	93	Components of separators for the separation or purification of gases from gas mixtures, consisting of a bundle of permeable hollow fibres enclosed within a container, whether or not perforated, of an overall length of 300 mm or more but not more than 3 700 mm and a diameter of not more than 500 mm	0 %	31.12.2013
*ex 8422 30 00 ex 8479 89 97	10 30	Machines and apparatus, other than injection moulding machines, for the manufacture of ink-jet printer cartridges (1)	0 %	31.12.2013
*ex 8439 99 10 ex 8439 99 90	10 10	Suction-roll shells, produced by centrifugal casting, not drilled, in the form of alloy-steel tubes, of a length of 3 000 mm or more and an external diameter of 550 mm or more	0 %	31.12.2013
ex 8462 21 80	10	Numerically controlled stent crimping machine comprising a base, a pneumatic crimp head and a motorised product positioning mechanism (V-block) to crimp a stent onto the balloon of a catheter using radial pressure in the manufacture of drug eluting stents (1)	0 %	31.12.2012
*ex 8477 59 80	10	Machinery for working rubber or plastic for use in the manufacture of drug-eluting stents (1)	0 %	31.12.2012
*ex 8477 80 99	10	Machines for casting or for surface modification of plastic membranes of heading No 3921	0 %	31.12.2013
*ex 8481 80 59	10	Air control valve, consisting of a stepping motor and a valve pintle, for the regulation of idle air flow in fuel injection engines	0 %	31.12.2013
*ex 8481 80 79	20	Solenoid valve device that can withstand a pressure of 875 bar	0 %	31.12.2013
ex 8481 80 99	50	Service valve, consisting a combination of a two way valve on the liquid line and a three way valve on the gas line with: — a minimum enclosing pressure of 30 kgf/cm^2, — a minimum withstanding pressure of 45 kgf/cm^2, for use in the manufacture of outdoor air conditioning units (1)	0 %	31.12.2011

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8481 80 99	60	Four way valve, consisting of: — a core plunger, — a sealing plunger, — a 220 V-240 V AC 50/60 Hz solenoid coil, — a working pressure up to 4.3 Mpa, — a housing for directing the flow of the refrigerant, for use in the manufacture of outdoor air conditioning units (1)	0 %	31.12.2011
*ex 8483 40 51	20	Gear box, having a differential with wheel axle, for use in the manufacture of self-propelled lawnmowers with a seat of subheading 8433 11 51 (1)	0 %	31.12.2013
*ex 8483 40 59	20	Hydrostatic speed changer, having a hydro pump and a differential with wheel axle, for use in the manufacture of self-propelled lawnmowers with a seat of subheading 8433 11 51 (1)	0 %	31.12.2013
ex 8501 10 93	20	Single phased 50 Hz, AC motor driven by permanent single capacitor and having a power output of less than 37 W, for use in the manufacture of indoor split air conditioning units (1)	0 %	31.12.2011
*ex 8501 10 99	54	DC motor, brushless, with an external diameter of not more than 25,4 mm, a rated speed of 2 260 (± 15 %) or 5 420 (± 15 %) rpm, a supply voltage of 1,5 V or 3 V	0 %	31.12.2013
*ex 8501 10 99	79	DC motor with brushes and an internal rotor with a three-phase winding, of a specified temperature range covering at least - 20 °C to + 70 °C	0 %	31.12.2013

▼M26

ex 8501 10 99	80	DC stepping motor, with: — an angle of step of 7,5° (± 0,5°), — a pull-out torque at 25 °C of 25 mNm or more, — a pull-out pulse rate of 1 960 pps or more, — a two-phase winding, and — a rated voltage of 10,5 V or more, but not more than 16,0 V.	0 %	1.7.2009-31.12.2013

▼M25

*ex 8501 10 99	81	DC stepping motor, with an angle of step of 18° or more, a holding torque of 0,5 mNm or more, a coupling bracket the exterior dimensions of which do not exceed 22 × 68 mm, a two phase winding and an output of not more than 5 W	0 %	31.12.2013
*ex 8501 10 99	82	DC motor, brushless, with an external diameter of not more than 29 mm, a rated speed of 1 500 (± 15 %) or 6 800 (± 15 %) rpm, a supply voltage of 2 V or 8 V	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8501 31 00	30	DC motor, brushless, with a three-phase winding, an external diameter of 85 mm or more, but not more than 115 mm, a nominal torque of 2.23 Nm (± 1,0 Nm), of an output of more than 120 W but not more than 520 W, calculated with 1 550 RPM (± 350 RPM) at a supply voltage of 12 V equipped with electronic circuit with sensors using the Hall effect, for use with an electric power steering control module (power steering motor) (1)	0 %	31.12.2011
*ex 8503 00 91 ex 8503 00 99	31 32	Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring	0 %	31.12.2013
*ex 8503 00 99	31	Stamped collector of an electric motor, having an external diameter of not more than 16 mm	0 %	31.12.2013
*ex 8504 31 80	20	Transformer for use in the manufacture of inverters in LCD modules (1)	0 %	31.12.2012
*ex 8504 31 80	30	Switching transformers, having a power handling capacity of not more than 1 kVA for use in the manufacture of static converters (1)	0 %	31.12.2013
*ex 8504 40 90	20	Direct current to direct current converter	0 %	31.12.2013
*ex 8504 40 90	30	Static converter comprising a power switch with insulated-gate bipolar transistors (IGBTs), contained in a housing, for use in the manufacture of microwave ovens of subheading 8516 50 00 (1)	0 %	31.12.2013
▼M26				
ex 8504 40 90	40	Static converters for use in the manufacture of single-phase electric motor controls with a power supply of not more than 3 kW (4)	0 %	1.7.2009-31.12.2013
▼M25				
*ex 8504 50 95	20	Inductor with an inductance of not more than 62 mH	0 %	31.12.2013
*ex 8504 50 95	30	Multilayer monolithic inductors, contained in a housing of the SMD (surface mounted device) type the exterior dimensions of which do not exceed 1,8 × 3,4 mm, for use in the manufacture of products falling within subheading 8517 11 00, 8517 12 00 or 8517 69 31 (1)	0 %	31.12.2013
*ex 8504 90 11	10	Ferrite cores, other than for deflection yokes	0 %	31.12.2013
ex 8504 90 18	40	Trans coil for boosting DC voltage and isolating high and low voltages for use in the manufacture of products falling within subheading 8504 31 80 (1)	0 %	31.12.2011
*ex 8505 11 00	31	Ferrite magnet having a remanence of 455 mT (± 15 mT)	0 %	31.12.2013
*ex 8505 11 00	33	Magnets consisting of an alloy of neodymium, iron and boron, either in the shape of a rounded rectangle with measurements of not more than 15 × 10 × 2 mm, or in the shape of a disc with a diameter of not more than 90 mm, whether or not containing a hole in the centre	0 %	31.12.2013

▼**M25**

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8505 19 90	31	Neodymium-ferro ring with an external diameter of not more than 13 mm, an internal diameter of not more than 9 mm	0 %	31.12.2013
*ex 8505 20 00	30	Electromagnetic clutch, for use in the manufacture of compressors of air conditioning machines of motor vehicles (1)	0 %	31.12.2013
*ex 8505 90 10	91	Solenoid with a plunger, operating at a nominal supply voltage of 24 V at a nominal DC of 0,08 A, for use in the manufacture of products falling within heading No 8517 (1)	0 %	31.12.2013
*ex 8506 50 90	10	Lithium iodine single cell battery the dimensions of which do not exceed 9 × 23 × 45 mm and a voltage of not more than 2,8 V	0 %	31.12.2013
*ex 8506 50 90	20	Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit	0 %	31.12.2013
*ex 8506 50 90	30	Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions of not more than 28 × 45 × 15 mm and a capacity of not less than 1,05 Ah	0 %	31.12.2013
*ex 8507 30 20	30	Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm (± 1,5 mm) and a diameter of 14,5 mm (± 1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (1)	0 %	31.12.2013
*ex 8507 80 20 ex 8507 80 30	20 20	Rectangular accumulator, with a length of not more than 69 mm, a width of not more than 36 mm and a thickness of not more than 12 mm, for use in the manufacture of rechargeable batteries (1)	0 %	31.12.2013
*ex 8507 80 20	30	Cylindrical nickel-hydride accumulator, of a diameter of not more than 14,5 mm, for the manufacture of rechargeable batteries (1)	0 %	31.12.2013
*ex 8507 80 30	30	Cylindrical lithium-ion accumulator, with a length of 64,6 mm or more and a diameter of 18,1 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (1)	0 %	31.12.2013
*ex 8507 80 30	40	Rectangular lithium-ion-accumulator, with — a length of 80 mm or more, but not more than 1 000 mm, — a width of 25 mm or more, but not more than 150 mm, — a height of 100 mm or more, but not more than 500 mm, — a weight of 0,5 kg or more, but not more than 30 kg, — a capacity of 20 Ah or more, but not more than 1 000 Ah, for use in the manufacture of rechargeable power-supply units for incorporation into goods of heading No 8903 (1)	0 %	31.12.2011

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8507 80 30	50	Lithium-ion-accumulator, with a distance between the poles of 55 mm or more, for use in the manufacture of rechargeable power-supply units for incorporation in electric motorcycles of subheading No 8711 90 (1)	0 %	31.12.2012
*ex 8518 30 95	20	Headphone and earphone for hearing aids, contained in a housing the exterior dimensions of which, excluding connecting points, do not exceed 5 × 6 × 8 mm	0 %	31.12.2013
*ex 8518 90 00	91	Integrally cold-upsetted steel coreplate, in the form of a disk on one side provided with a cylinder, for use in the manufacture of loudspeakers (1)	0 %	31.12.2013

▼M26

———————

**ex 8519 81 35	10	Unmounted or incomplete assembly, comprising at least one optical unit and DC motors and operational control circuit, with digital/analogue converter, for use in the manufacture of CD players, radio-broadcast receivers of a kind used in motor vehicles or navigational aid apparatus (4)	0 %	1.7.2009-31.12.2013

▼M25

*ex 8522 90 49	50	Electronic assembly for a laser read-head of a compact disc player, comprising: — a printed circuit, — a photo-detector, in the form of a monolithic integrated circuit, contained in a housing, — not more than 3 connectors, — not more than 1 transistor, — not more than 3 variable and 4 fixed resistors, — not more than 5 capacitors, the whole mounted on a support	0 %	31.12.2013
*ex 8522 90 49	70	Assembly, comprising at least a flexible printed circuit, a laser driver integrated circuit and a signal converter integrated circuit	0 %	31.12.2013
*ex 8522 90 80	65	Assembly for optical discs, comprising at least an optical unit and DC motors, whether or not capable of double layer recording	0 %	31.12.2013
*ex 8522 90 80	70	Video tape recording/reproducing assembly comprising at least a motor and a printed circuit board containing integrated circuits with driver or control functions, whether or not incorporating a transformer, for use in the manufacture of products falling within heading No 8521 (1)	0 %	31.12.2013
*ex 8522 90 80	75	Optical reading head for CD player, consisting of one laser diode, one photodetector integrated circuit and one beam splitter	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8522 90 80	80	Laser optical drive unit assembly (so called mecha units) for the recording and/or reproduction of digital video and/or audio signals, comprising at least a laser optical reading and/or writing unit, one or more DC motors and not containing a printed circuit board or containing a printed circuit board not capable of signal processing for sounds and images, for use in the manufacture of products falling within headings No 8519, 8521, 8526, 8527, 8528 or 8543 ([1])	0 %	31.12.2013
*ex 8522 90 80	81	Laser optical pick up unit for the reproduction of optical signals from CD or DVD and the recording of optical signal on DVD, comprising at least — a laser diode, — a laser driver integrated circuit, — a photo detector integrated circuit, — a front monitor integrated circuit and an actuator, for use in the manufacture of products falling within heading No 8521 ([1])	0 %	31.12.2011

▼M26

_____

**ex 8522 90 80	83	Blu-ray optical pick up unit for the reproduction/recording of optical signals from/to DVD discs and the reproduction of optical signals from CD and Blu-ray disc comprising at least: — three kinds of wavelength laser diodes, — laser driver integrated circuit, — photo detector integrated circuit, — front monitor integrated circuit and an actuator, for use in the manufacture of products falling within heading No 8521 ([4])	0 %	1.7.2009-31.12.2013
**ex 8522 90 80	84	Blu-ray drive mechanism or unit, whether or not recordable, for the reproduction or recording of optical signals from or to Blu-ray and DVD disks and the reproduction of optical signals from CD disks, comprising at least: — an optical pick up unit with three kinds of laser, — spindle motor, — stepping motor, — with or without printed circuit board mounted drive control integrated circuit, motor driver integrated circuit and memory, for use in the manufacture of products falling within heading No 8521 ([4])	0 %	1.7.2009-31.12.2013

▼M25

*ex 8522 90 80	85	Video head drum, with video heads or with video and audio heads and an electric motor, for use in the manufacture of products falling within heading No 8521 ([1])	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8522 90 80	95	Drive-unit capable of magnetooptical signal recording and optical signal reproduction, comprising at least an optical unit, DC motors and a printed circuit on which are mounted integrated circuits providing drive and signal processing functions for reading optical discs having an external diameter of not more than 70 mm, not comprising circuits with amplification functions or power supply drive functions	0 %	31.12.2013
ex 8522 90 80	96	Hard disk drive, for incorporation in products of heading 8521 (1)	0 %	31.12.2012
*ex 8522 90 80 ex 8529 90 65	97 50	Tuner transforming high-frequency signals into mid-frequency signals, for use in the manufacture of products falling under No 8521 and No 8528 (1)	0 %	31.12.2011
*ex 8525 80 19	20	Assembly for television cameras of dimensions of not more than 10 × 15 × 18 mm, comprising an image sensor, an objective and a color processor, having an image resolution of not more than 1 024 × 1 280 pixel, whether or not fitted with cable and/or housing, for the manufacture of goods of subheading 8517 12 00 (1)	0 %	31.12.2013

▼M26

———————

**ex 8525 80 19	30	Compact chassis-type closed circuit television (CCTV) cameras, of a weight of not more than 250 g, whether or not contained in a housing, of dimensions of not more than 50 mm × 60 mm × 89,5 mm, with a single sensor Charge-Couple Device (CCD), with effective pixels of not more than 440 000, for use in CCTV surveillance systems (4)	0 %	1.7.2009-31.12.2013

▼M25

ex 8525 80 19	40	Assembly for cameras used in computer notebooks of dimensions of not more than 15 × 25 × 25 mm, comprising an image sensor, an objective and a colour processor, having an image resolution of not more than 1 600 × 1 200 pixel, whether or not fitted with cable and/or housing, whether or not mounted on a base and containing a LED chip (1)	0 %	31.12.2011
*ex 8528 49 10	10	Video monitor comprising: — a flat screen monochrome cathode-ray tube with a diagonal measurement of the screen of not more than 110 mm and equipped with a deflector yoke, and — a printed circuit on which are mounted a deflection unit, a video-amplifier and a transformer, the whole mounted or not on a chassis, for the manufacture of video entry-phones, video telephones or surveillance apparatus (1)	0 %	31.12.2013

▼**M25**

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8528 59 90	20	Liquid cristal display colour video monitor having a DC input voltage of 7 V or more but not more than 30 V, with a diagonal measurement of the screen of 33,2 cm or less, suitable for the incorporation into goods of chapters 84 to 90 and 94	0 %	31.12.2013
*ex 8529 10 80	20	Ceramic filter package comprising 2 ceramic filters and 1 ceramic resonator for a frequency of 10,7 MHz (± 30 kHz), contained in a housing	0 %	31.12.2013
*ex 8529 10 80	35	Ceramic filter for a centre frequency of 450 kHz or more but not more than 470 kHz, with a bandwidth of not more than 13 kHz at 3 dB, contained in a housing	0 %	31.12.2013
*ex 8529 10 80	50	Ceramic filter for a centre frequency of 450 kHz (± 1,5 kHz) or 455 kHz (± 1,5 kHz), with a bandwidth of not more than 30 kHz at 6 dB and not more than 70 kHz at 40 dB, contained in a housing	0 %	31.12.2013
*ex 8529 10 80	60	Filters, excluding surface acoustic wave filters, for a center frequency of 485 MHz or more but not more than 1 990 MHz with an insertion loss of not more than 3,5 dB, contained in a housing	0 %	31.12.2013
*ex 8529 90 65 ex 8548 90 90	30 44	Parts of TV-apparatus, having micro-processor and video-processor functions, comprising at least a micro-controller and a video-processor, mounted on a leadframe and contained in a plastic housing	0 %	31.12.2013
ex 8529 90 65	60	Tuner transforming high frequency signals to mid frequency signals for use in the manufacture of sattelite or terrestrial TV receivers for set-top boxes (1)	0 %	31.12.2011
*ex 8529 90 65	70	Unit driver consisting of an electronic integrated circuit and a flexible printed circuit, for use in the manufacture of LCD modules (1)	0 %	31.12.2011
*ex 8529 90 65	75	Modules for driving addressing pixels, comprising at least semiconductor chips	0 %	31.12.2012
*ex 8529 90 65	80	Scan driver boards for generating electric pulses for scanning to certain electrodes in a glass panel, comprising at least semiconductor chips	0 %	31.12.2012
*ex 8529 90 92	32	Optical unit for video projection, comprising a colour separation system, a positioning mechanism and lenses, for use in the manufacture of products falling within heading No 8528 (1)	0 %	31.12.2013
*ex 8529 90 92	40	Assembly comprising prisms, digital micro-mirror device (DMD) chips and electronic control circuits, for the manufacture of television projection equipments or video projectors (1)	0 %	31.12.2013
*ex 8529 90 92	41	Digital micromirror device (DMD)-chips, for use in the manufacture of video projectors (1)	0 %	31.12.2013

▼**M25**

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8529 90 92	42	Heat sinks and cooling fins of aluminium, for maintaining the operating temperature of transistors and integrated circuits in television sets (1)	0 %	31.12.2013
*ex 8529 90 92	43	Plasma display module incorporating only address and display electrodes, with or without driver and/or control electronics for pixel address only and with or without a power supply	0 %	31.12.2013
*ex 8529 90 92	44	LCD modules, solely consisting of one or more TFT glass or plastic cells, not combined with touch screen facilities, with or without backlight unit, with or without inverters and one or more printed circuit boards with control electronics for pixel addressing	0 %	31.12.2013
*ex 8529 90 92	45	Integrated circuit package with TV reception functionality containing a channel decoder die, tuner die, power management die, GSM filters and discrete as well as embedded passive circuit elements for reception of digitally broadcasting videosignals of DVB-T and DVB-H formats	0 %	31.12.2013
*ex 8529 90 97	60	Frame for use in the manufacture of high frequency tuners (1)	0 %	31.12.2013
*ex 8531 80 95	40	Electro-accoustic transducer	0 %	31.12.2013
*ex 8535 90 00	20	Printed circuit board in the form of plates consisting of isolating material with electrical connections and solder points, for use in the manufacture of back light units for LCD modules (1)	0 %	31.12.2013
*ex 8536 30 30	11	Thermo-electric switch with a cut-off current of 50 A or more, comprising a snap action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing	0 %	31.12.2013
*ex 8536 49 00	91	Thermal relays contained in a hermetically sealed glass cartridge of not more than 35 mm in length excluding wires, with a maximum leakage rate of 10^{-6} cm^3 He/sec at one bar in the temperature range 0 to 160 °C, to be incorporated into compressors for refrigerating equipment (1)	0 %	31.12.2013
*ex 8536 50 11	31	Switch of the printed circuit mount type, operating at a force of 4,9 N (± 0,9 N), contained in a housing	0 %	31.12.2013
*ex 8536 50 11	32	Mechanical tact switch for connecting electronic circuits, operating at a voltage of not more than 60 V and at a current strength of not more than 50 mA, for use in the manufacture of television sets (1)	0 %	31.12.2013
*ex 8536 50 19	91	Hall effect switch, comprising 1 magnet, 1 Hall effect sensor and 2 capacitors, contained in a housing with 3 connections	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8536 50 19 ex 8536 50 80	93 97	Devices, having adjustable controller and switching functions, comprising one ore more monolithic integrated circuits whether or not combined with semiconductor elements, mounted together on a leadframe and contained in a plastic housing	0 %	31.12.2013
*ex 8536 50 80	93	Switch unit for coaxial cable, comprising 3 electromagnetic switches, with a switching time of not more than 50 ms and an actuating current of not more than 500 mA at a voltage of 12 V	0 %	31.12.2013
*ex 8536 50 80	95	Reed switch having a switching power of 20 W or more within the range of 17-43 A. turn, in the form of a glass capsule, not containing mercury, the dimensions of which do not exceed 3 × 21 mm, for use in the manufacture of automotive airbag shock-sensors ([1])	0 %	31.12.2013
*ex 8536 50 80	98	Mechanical push-button switch for connecting electronic circuits, operating at a voltage of 220 V or more but not more than 250 V and at a current strength of not more than 5 A, for use in the manufacture of television sets ([1])	0 %	31.12.2013
ex 8536 69 90	20	Pitch connector for use in the manufacture of LCD television reception apparatus ([1])	0 %	31.12.2012
*ex 8536 90 85	92	Metallic stamped frame with connections	0 %	31.12.2013
*ex 8536 90 85 ex 8544 49 93	94 10	Elastomeric connector, of rubber or silicone, consisting of one or more conductor elements	0 %	31.12.2013
*ex 8537 10 99	92	Touch sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors	0 %	31.12.2013
*ex 8537 10 99	93	Electronic control units for a voltage of 12 V, for use in the manufacture of vehicle mounted temperature control systems ([1])	0 %	31.12.2013
*ex 8537 10 99 ex 8543 70 90	94 20	Unit consisting of two junction field effect transistors contained in a dual lead frame housing	0 %	31.12.2013
*ex 8537 10 99 ex 8543 70 90	95 25	Unit consisting of two metal oxide semiconductor field effect transistors contained in a dual lead frame housing	0 %	31.12.2013
*ex 8538 90 99	92	Part of an electrothermal fuse, consisting of a tin coated copper wire attached to a cylindrical casing, the exterior dimensions of which do not exceed 5 × 48 mm	0 %	31.12.2013
*ex 8539 39 00	20	Cold cathode (CCFL) or External Electrode (EEFL) fluorescent lamps, of a diameter of not more than 5 mm and with a length of more than 120 mm but not more than 1 570 mm	0 %	31.12.2011

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8540 11 11	95	Colour cathode-ray tube with a slot mask, equipped with an electron gun and a deflection yoke and with a screen width/-height ratio of 4/3 and a diagonal measurement of the screen of not more than 42 cm	0 %	31.12.2011
*ex 8540 11 15	20	Full square curved screen colour cathode-ray tube, equipped with an electron gun and a deflection yoke and with a screen width/height ratio of 4/3 and a diagonal measurement of the screen of 68 cm (± 2 mm)	0 %	31.12.2011
ex 8540 11 19	91	Colour cathode-ray tube equipped with electron guns placed side by side (in-line technology), with a diagonal measurement of the screen of 79 cm or more	0 %	31.12.2011
*ex 8540 11 19	93	Colour cathode-ray tube equipped with an electron gun and a deflection yoke, with a screen width/height ratio of 4/3 and a diagonal measurement of the screen of more than 72 cm	0 %	31.12.2013
*ex 8540 11 91	31	Colour cathode-ray tube with a screen width/height ratio of 16/9 and a diagonal measurement of the screen of 39,8 cm (± 0,3 cm)	0 %	31.12.2013
ex 8540 20 80	91	Photomultiplier consisting of a photo-cathode tube with 9 or 10 dyodes, for light of a wavelength of 160 nm or more but not more than 930 nm, of a diameter of not more than 14 mm and a height of not more than 94 mm	0 %	31.12.2011
*ex 8540 71 00	20	Continuous wave magnetron with a fixed frequency of 2 460 MHz, packaged magnet, probe output, for use in the manufacture of products falling within subheading 8516 50 00 ([1])	0 %	31.12.2013
*ex 8540 89 00	91	Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 300 mm × 350 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0 %	31.12.2013
*ex 8540 89 00	92	Vacuum fluorescent display tube	0 %	31.12.2013
*ex 8540 91 00	32	Electron gun of colour cathode-ray tubes with an anode voltage of 27,5 kV or more but not more than 36 kV	0 %	31.12.2013

▼M26

ex 8540 91 00	40	Deflection yoke of cathode-ray tubes	0 %	1.7.2009-31.12.2013
ex 8540 91 00	50	Metal anode button to enable electrical contact with the anode inside the colour picture tube	0 %	1.7.2009-31.12.2013

▼**M25**

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8540 91 00	92	Slit or slot mask, excluding masks with continuously vertical slits, with a diagonal measurement of 69 cm or less	0 %	31.12.2011
ex 8540 91 00	95	Slit or slot mask (shadow mask), excluding masks with continuously vertical slits, with a diagonal measurement of 697,5 mm or more, but not more than 782,9 mm	0 %	31.12.2012
ex 8540 91 00	96	Assembly for cathode-ray tubes with 2 or more but not more than 6 coils, a plastic support and a metal fixing ring, for the adjustment of display sharpness and/or convergence	0 %	31.12.2013
*ex 8543 70 90	30	Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0 %	31.12.2013
*ex 8543 70 90	35	Radio frequency (RF) modulator, operating with a frequency range of 43 MHz or more but not moer than 870 MHz, capable of switching VHF and UHF signals, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0 %	31.12.2013
*ex 8543 70 90	45	Piezo-electric crystal oscillator with a fixed frequency, within a frequency range of 1.8 MHz to 67 MHz, contained in a housing	0 %	31.12.2013
*ex 8543 70 90	55	Opto-electronic circuit comprising one or more light-emitting diodes (LEDs), whether or not equipped with an integrated driving circuit, and one photodiode with amplifier circuit, whether or not with an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, whether or not with an integrated logic gate arrays circuit or other integrated circuits, contained in a housing	0 %	31.12.2013
*ex 8543 70 90	60	Oscillator, with a centre frequency of 20 GHz or more but not more than 42 GHz, consisting of active and passive elements not mounted on a substrate, contained in a housing	0 %	31.12.2013
*ex 8543 70 90	65	Audio recording and reproducing circuit, capable of stereo audio data storage and simultaneous record and playback, comprising 2 or 3 monolithic integrated circuits mounted on a printed circuit or a lead frame, contained in a housing	0 %	31.12.2013
*ex 8543 70 90	80	Temperature compensated oscillator, comprising a printed circuit on which are mounted at least a piezo-electric crystal and an adjustable capacitor, contained in a housing	0 %	31.12.2013
*ex 8543 70 90	85	Voltage controlled oscillator (VCO), other than temperature compensated oscillators, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26				
_____				
**ex 8543 70 90	90	Fuel cell module containing at least polymer electrolyte membrane fuel cells in a housing with an integrated cooling system, for use in the manufacture of motor vehicle propulsion systems (4)	0 %	1.7.2009-31.12.2013
▼M25				
*ex 8543 90 00	20	Stainless steel cathode in the form of a plate with a hanger bar, whether or not with plastic side strips	0 %	31.12.2013
*ex 8543 90 00	30	Assembly of products falling within heading No 8541 or 8542 mounted on a printed circuit, contained in a housing	0 %	31.12.2013
ex 8543 90 00	40	Part of an electrolysis device, consisting of a pan of nickel equipped with a wire mesh of nickel, fixed via ribs of nickel, and a pan of titanium equipped with a wire mesh of titanium, fixed via ribs of titanium, of which both pans are fixed together back to back	0 %	31.12.2012
▼M26				
ex 8544 42 90	10	Data transmission cable capable of bit rate transmission of 600 Mbit/s or more, with: — a voltage of 1,25 V (± 0,25 V), — connectors fitted at each end, at least one of which contains pins with a pitch of 0,5 mm, — outer screening shielding, — twisted pair copper wires with an impedance of 100 Ω and a twist pitch of not more than 8 mm, used solely for communication between LCD panel and video processing electronic circuits	0 %	1.7.2009-31.12.2013
ex 8544 49 93	20	PET/PVC insulated flexible cable with: — a voltage of not more than 60 V, — a current of not more than 1 A, — a heat resistance of not more than 105 °C, — individual wires of a thickness of 0,05 mm (± 0,01 mm) and a width of not more than 0,65 mm (± 0,03 mm), — distance between conductors of not more than 0,5 mm, and — pitch (distance from centreline to centreline of conductors) of not more than 1,08 mm.	0 %	1.7.2009-31.12.2013
▼M25				
*ex 8545 19 90	20	Carbon electrodes, for use in the manufacture of zinc-carbon batteries (1)	0 %	31.12.2013
*ex 8547 10 10	10	Insulated fitting of ceramics, containing by weight 90 % or more of aluminium oxide, metallized, in the form of a hollow cylindrical body of an external diameter of 20 mm or more but not more than 250 mm, for the manufacture of vacuum interrupters (1)	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
*ex 8548 90 90	41	Unit, consisting of a resonator operating within a frequency range of 1,8 MHz or more but not more than 40 MHz and a capacitor, contained in a housing	0 %	31.12.2013
*ex 8548 90 90	43	Contact image sensor	0 %	31.12.2013
*ex 8548 90 90	47	Unit consisting of two or more light emitting diode chips operating at a typical wavelength of 440 nm or more but not more than 660 nm, contained in a lead frame housing whose exterior dimensions — without fittings — do not exceed 12 × 12 mm	0 %	31.12.2013
*ex 8548 90 90	48	Optical unit, consisting at least of a laserdiode and a photodiode operating at a typical wavelength of 635 nm or more but not more than 815 nm	0 %	31.12.2013
*ex 8548 90 90	49	LCD modules, solely consisting of one or more TFT glass or plastic cells, combined with touch screen facilities, with or without backlight unit, with or without inverters and one or more printed circuit boards with control electronics for pixel addressing only	0 %	31.12.2013
ex 8704 23 91	20	Motor chassis with a self-ignition capacity of at least 8,500 cm^3, fitted with a cabin on either 3, 4 or 5 wheels having a wheelbase of at least 480 cm, not containing working machinery, to be built into special purpose motor vehicles with a width of at least 300 cm to distribute fertlizers ([1])	0 %	31.12.2012
ex 8708 99 97	20	Metal housing caps for incorporation into balancing-arms or spherical bearings used in the suspension systems for the front wheels of motor vehicles ([1])	0 %	31.12.2011
*ex 9001 10 90	10	Image reverser made up from an assembly of optical fibres	0 %	31.12.2013
ex 9001 20 00	10	Material consisting of a polarising film, whether or not on rolls, supported on one or both sides by transparent material	0 %	31.12.2012

▼M26

ex 9001 20 00 ex 9001 90 00	20 55	Optical, diffuser, reflector or prism sheets, unprinted diffuser plates, whether or not possessing polarising properties, specifically cut	0 %	1.7.2009-31.12.2013

▼M25

*ex 9001 90 00	35	Rear projection screen, comprising a lenticular plastic plate	0 %	31.12.2013
*ex 9001 90 00	45	Rod of neodymium-doped yttrium-aluminium garnet (YAG) material, polished at both ends	0 %	31.12.2013

▼M26

———————

ex 9001 90 00	60	Reflector or diffuser sheets in rolls	0 %	1.1.2009-31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 9001 90 00	70	Polyethylene terephthalate film with a thickness of less than 300 μm according to ASTM D2103, having on one side prisms of acrylic resin with a prism angle of 90° and a prism pitch of 50 μm	0 %	31.12.2011
ex 9001 90 00	75	Front filter comprising glass panels with special printing and film coating, for use in the manufacture of plasma display modules ([1])	0 %	31.12.2012
*ex 9001 90 00	76	Plasma display panel (PDP) filter	0 %	31.12.2013
*ex 9002 11 00	10	Adjustable lens unit, having a focal length of 90 mm or more but not more than 180 mm and comprising a combination of between 4 and 8 glass or methacrylic lenses with a diameter of 120 mm or more but not more than 180 mm, each lens coated on at least one side with a magnesium fluoride layer, for use in the manufacture of video projectors ([1])	0 %	31.12.2013
*ex 9002 11 00	50	Lens unit, having a focal length of 25 mm or more but not more than 150 mm, consisting of glass or plastic lenses, with a diameter of 60 mm or more but not more than 190 mm	0 %	31.12.2013
*ex 9002 20 00	10	Filter, consisting of a plastic polarising membrane, a glass plate and a transparent protective film, mounted on a metal frame, for use in the manufacture of products falling within heading 8528 ([1])	0 %	31.12.2013
*ex 9002 90 00	20	Lens, mounted, having a fixed focal length of 3,8 mm (± 0,19 mm) or 8 mm (± 0,4 mm), with a relative aperture of F2,0 and a diameter of not more than 33 mm, for use in the manufacture of charged-coupled (CCD) cameras ([1])	0 %	31.12.2013
*ex 9002 90 00	30	Optical unit, comprising 1 or 2 rows of optical glass fibres in the form of lenses and with a diameter of 0,85 mm or more but not more than 1,15 mm, embedded between 2 plastic plates	0 %	31.12.2013

▼M26

ex 9013 20 00	10	Carbon dioxide laser, stimulated by high frequency, having an output power of 12 Watt or more, but not more than 200 Watt	0 %	1.7.2009-31.12.2013
ex 9013 20 00	20	Laser head assemblies for use in the manufacture of measuring or checking machines for semiconductor wafers or devices ([4])	0 %	1.7.2009-31.12.2013
ex 9013 20 00	30	Laser for use in the manufacture of measuring or checking machines for semiconductor wafers or devices ([4])	0 %	1.7.2009-31.12.2013

▼M25

*ex 9022 30 00	10	X-ray tube with a target voltage of 4 kV or more but not more than 30 kV, a power of not more than 9 W and a target current of not more than 2 mA	0 %	31.12.2013

▼M25

CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26				
ex 9022 90 90	10	Panels for x-ray apparatus (x-ray flat panel sensors/x-ray sensors) consisting of a glass plate with a matrix of thin-film transistors, covered with a film of amorphous silicon, coated with a scintillator layer of caesium iodide and a metallised protective layer, with an active surface of 409,6 mm^2 × 409,6 mm^2 and a pixel size of 200 μm^2 × 200 μm^2	0 %	1.7.2009-31.12.2013
▼M25				
*ex 9027 10 90	10	Sensor element for gas or smoke analysis in motor vehicles, essentially consisting of a zirconium-ceramic element in a metal housing	0 %	31.12.2013
*ex 9031 80 34	30	Apparatus for measuring the angle and direction of rotation of motor vehicles, consisting of at least one yaw rate sensor in the form of a monocrystalline quartz, whether or not combined with one or more measuring sensors, the whole contained in a housing	0 %	31.12.2013
*ex 9031 80 38	10	Acceleration measurement device for automotive applications, comprising one or more active and/or passive elements and one or more sensors, the whole contained in a housing	0 %	31.12.2013
*ex 9031 90 85	20	Assembly for a laser align sensor, in the form of a printed circuit comprising optical filters and a charge-coupled image (CCD) sensor, the whole contained in a housing	0 %	31.12.2013
ex 9032 10 89	20	Thermostat, damper or bimetal with, — an opening temperature of + 7 °C (± 1,5 °C), closing temperature of - 4 °C(± 1,5 °C)for damper thermostat, — an opening temperature of + 8 °C (± 3 °C) for bimetal thermostat; for use in the manufacture of frost free refrigerators ([1])	0 %	31.12.2012
*ex 9032 89 00	20	Automotive airbag shock-sensor, comprising a contact capable of switching a current of 12 A at a voltage of 30 V, having a typical contact resistance of 80 mOhm	0 %	31.12.2013
*ex 9032 89 00	30	Electronic controller of electric power steering (EPS controller)	0 %	31.12.2013
ex 9032 89 00	40	Digital valve controller for controlling liquids and gases	0 %	31.12.2012
ex 9107 00 00	20	Mechanical timer for use in the manufacture of no-frost refrigerators ([1])	0 %	31.12.2011
*ex 9405 40 35	10	Electric light assembly of synthetic material containing 3 fluorescent tubes (RBG) of a diameter of 3,0 mm (± 0,2 mm), of a length of 420 mm (± 1 mm) or more, but not more than 600 mm (± 1 mm), for the manufacture of goods of heading 8528 ([1])	0 %	31.12.2013

▼M25

	CN code	TARIC	Description	Rate of autonomous duty	Validity period
▼M26					
	ex 9405 40 39	10	Ambient light module with a length of 300 mm or more, but not more than 600 mm, based on a light engine of a series of three or more, but not more than nine specific one chip red green and blue light emitting diodes mounted on a PCB, with light coupled to the front and/or back of the flat TV set (4)	0 %	1.7.2009-31.12.2013
	ex 9405 40 39	20	LED array of white silicone, containing: — an LED matrix module measuring 38,6 mm × 20,6 mm (± 0,1 mm), equipped with 128 red and green LED chips, and — a flexible printed circuit board, equipped with a Negative Temperature Coefficient Thermistor.	0 %	1.7.2009-31.12.2013
▼M25					
	*ex 9608 91 00	10	Non-fibrous plastic pen-tips with an internal channel	0 %	31.12.2013
	*ex 9608 91 00	20	Felt tips and other porous-tips for markers, without internal canal	0 %	31.12.2013
	*ex 9612 10 10	10	Ribbons of plastic with segments of different colours, providing the penetration of dyes by heat into a support (so called dye-sublimation)	0 %	31.12.2013

(1) Entry under this subheading is subject to conditions laid down in the relevant Community provisions (see Articles 291 to 300 of Commission Regulation (EEC) No 2454/93 — OJ L 253, 11.10.1993, p. 1).
(2) However, the measure is not allowed where processing is carried out by retail or catering undertakings.
(3) The specific additional duty is applicable.
►M26 (4) Entry under this subheading is subject to conditions laid down in the relevant Community provisions (see Articles 291 to 300 of Commission Regulation (EEC) No 2454/93 (OJ L 253, 11.10.1993, p. 1)). ◄
(*) New heading, modified heading or heading for which the duration of validity has been prolonged.
►M26 (**) Amended position. ◄