I

(Acts whose publication is obligatory)

COUNCIL REGULATION (EC) No 1381/1999

of 28 June 1999

amending Regulation (EC) No 1255/96 temporarily suspending the autonomous Common Customs Tariff duties on certain industrial and agricultural products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 26 thereof,

Having regard to the proposal from the Commission,

Whereas:

(1) It is in the interest of the Community to suspend partially or totally the autonomous Common Customs Tariff duties for a number of new products not listed in the Annex to Regulation (EC) No 1255/96[1];

(2) The products referred to in the said Regulation, for which it is no longer in the Community's interest to maintain suspension of autonomous Common Customs Tariff duties or for which it is necessary to amend the description in the light of technical developments, are to be withdrawn from the list in the Annex thereto;

(3) For the sake of clarity, products whose description requires amendment should be regarded as new products,

HAS ADOPTED THIS REGULATION:

Article 1

The Annex to Regulation (EC) No 1255/96 is hereby amended as follows:

1. the products set out in Annex I to this Regulation shall be inserted;

2. the products for which the codes are set out in Annex II to this Regulation shall be deleted.

Article 2

This Regulation shall enter into force on the third day following that of its publication in the *Official Journal of the European Communities*.

It shall apply with effect from 1 July 1999.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg, 28 June 1999.

For the Council

The President

M. NAUMANN

---

[1] OJ L 158, 29.6.1996, p. 1. Regulation as last amended by Regulation (EC) No 2797/98 (OJ L 352, 29.12.1998, p. 1).

ANNEX I

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 0713 33 90	20	Beans, white, dried, of the species *Phaseolus vulgaris*, of which not more than 2 % by weight are retained by a screen with apertures of a diameter of 8 mm	0
ex 2903 30 80	40	1,1-Difluoroethane	0
ex 2903 69 90	50	1-(Chloromethyl)naphthalene	0
ex 2907 29 00	50	6,6',6"-Tricyclohexyl-4,4',4"-butane-1,1,3-triyltri(*m*-cresol)	0
ex 2909 30 90	20	1,2-Bis(*m*-tolyloxy)ethane	0
ex 2909 30 90	30	1,2-Diphenoxyethane	0
ex 2916 12 90	30	Isobutyl acrylate	0
ex 2922 21 00	30	6-Amino-4-hydroxynaphthalene-2-sulfonic acid	0
ex 2922 21 00	40	7-Amino-4-hydroxynaphthalene-2-sulfonic acid	0
ex 2924 21 90 ex 3824 90 95	10 62	4,4'-Dihydroxy-7,7'-ureylenedi(naphthalene-2-sulphonic acid) and its sodium salts	0
ex 2924 29 90	45	7-Acetamido-4-hydroxynaphthalene-2-sulfonic acid and its sodium salts	0
ex 2930 90 70	60	Methyl phenyl sulfide	0
ex 2931 00 95	65	Triethylborane	0
ex 2933 39 95	35	3,5-Dimethylpiperidine	0
ex 2933 59 70	20	2,4-Diamino-6-chloropyrimidine	0
ex 2934 90 96	55	Naphth[1,2-*d*][1,2,3]oxadiazole-5-sulfonic acid	0
ex 3208 20 10	30	Solution of diundecyl phthalate and a copolymer of dibutyl maleate and isobutyl methacrylate in a hydrocarbon solvent	0
ex 3815 19 90	45	Catalyst, consisting predominantly of dichromium copper tetraoxide and copper (II) oxide, containing by weight 38 % or more but not more than 48 % of copper, evaluated as copper (II) oxide, fixed on a support of silicon dioxide, for the hydrogenation of acetophenones (a)	0
ex 3815 90 90	75	Catalyst, consisting of a mixture of 1,4-diazabicyclo[2.2.2]octane, 2-hydroxyethyliminodi(acetic acid) and dibutyltin di(acetate), containing by weight 5 % or more but not more than 10 % of 1,4-diazabicyclo[2.2.2]octane	0
ex 3815 90 90	81	Catalyst, containing by weight 38 % or more but not more than 48 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate	0
ex 3815 90 90	82	Catalyst, containing by weight 35 % or more but not more than 55 % of (2-hydroxy-1-methylethyl)trimethylammonium formate and formic acid	0
ex 3815 90 90	83	Catalyst, in the form of powder, containing aluminium magnesium hydroxide hydrate, rare-earth metals oxides and divanadium pentaoxide	0
ex 3815 90 90	85	Catalyst based on aluminosilicate (zeolite), for the transalkylation of alkylaromatic hydrocarbons or the oligomerisation of olefins (a)	0
ex 3824 90 95	63	Triethylborane, in the form of a solution in tetrahydrofuran	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3824 90 95	64	Aluminium sodium silicate, in the form of spheres of a diameter of: — either 1,6 mm or more but not exceeding 3,4 mm, — or 4 mm or more but not exceeding 6 mm	0
ex 3824 90 95	65	Mixture of tris(alkoxycarbonylamino)-1,3,5-triazines in which alkoxy groups are methoxy and butoxy	0
ex 3824 90 95	66	Mixture of primary *tert*-alkylamines	0
ex 3824 90 95	67	Preparation consisting of indium tin oxide dispersed in organic solvents	0
ex 3904 30 00	10	Copolymer of vinyl chloride with vinyl acetate and maleic acid, containing by weight: — 81,5 % or more but not more than 84,5 % of vinyl chloride, — 13,8 % or more but not more than 16,2 % of vinyl acetate and — 0,8 % or more but not more than 1,2 % of maleic acid, for the manufacture of goods of heading No 3215 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a)	0
3906 90 60		Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide	0
ex 3906 90 90	50	Acrylic polymers, containing by weight 2,5 % or more of chloroethyl vinyl ether or chloromethyl acrylate, in one of the forms mentioned in note 6(b) to Chapter 39	0
ex 3911 90 19	20	Hydrocarbon prepolymer, obtained by the reaction of cyclopentadiene and 1,3-pentadiene	0
ex 3915 90 93	30	Waste, parings and scrap of photographic, cinematographic and radiographic films	0
ex 3919 90 69	94	Reflecting laminated sheet, consisting of a film of polymethyl methacrylate embossed on one side in a regular pyramidal or other shaped pattern, a film of polymethyl methacrylate containing glass microprisms or microspheres, an adhesive layer and a release sheet	0
ex 3920 30 00	20	Laminated sheet or strip, consisting of a film composed of a blend of a thermoplastic elastomer (TPE) of styrene-butadiene-styrene (SBS) with polyethylene or polypropylene, of a thickness of 100 µm or more but not exceeding 200 µm, coated or covered on both sides with a film of polypropylene of a thickness not exceeding 20 µm	0
ex 3920 51 00	20	Plate of polymethyl methacrylate containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not exceeding 19 mm	0
ex 3920 62 19	81	Film of white polyethylene terephthalate, dyed in the mass, of a thickness of 185 µm or more but not exceeding 253 µm, coated on both sides with an antistatic layer	0
ex 3920 62 19	85	Film of a total thickness of 4,5 µm (± 0,16 µm), consisting of a biaxially-oriented polyethylene terephthalate film, of a thickness of 4,4 µm, an elastic modulus (in the machine direction) of 12 kg/mm² (± 2 kg/mm²) and a tensile strength (in the machine direction) of more than 28 kg/mm², and of an anti-adherent coating of a thickness of 0,1 µm	0
ex 3920 62 90	30	Film of polyethylene terephthalate, of a thickness of 500 µm (± 25 µm)	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3920 91 00	93	Film of polyethylene terephthalate, metallised on one or both sides, or laminated film of polyethylene terephthalate films, metallised on the external sides only, and having the following characteristics: — a visible light transmission of 50 % or more, — coated on both sides with a layer of polyvinyl butyral but not coated with an adhesive or any other material except polyvinyl butyral, — a total thickness not exceeding 0,2 mm without taking the presence of polyvinyl butyral into account, for use in the manufacture of heat-reflecting laminated glass (a)	0
ex 3920 99 59	55	Ion-exchange membranes of fluorinated plastic material, other than those of subheading 3920 99 53	0
ex 3921 90 60 ex 5407 71 00 ex 5903 90 99	91 20 10	Woven polytetrafluoroethylene-fibre fabric, coated or covered with a copolymer of tetrafluoroethylene and trifluoroethylene having perfluorinated alkoxy side-chains ending in carboxylic acid or sulphonic acid groups, whether or not in the potassium or sodium salt form	0
ex 3926 90 99	20	Tape pad, for use in the manufacture of goods of heading No 8523 (a)	0
ex 3926 90 99	30	Guide pin and pole, for use in the manufacture of goods of subheadings 8523 11 00, 8523 12 00 and 8523 13 00 (a)	0
ex 5607 50 90	10	Twine, unsterilised, wholly of polyglycollic acid, plaited or braided, with an inner core, for the manufacture of surgical sutures (a)	0
ex 5907 00 90	10	Textile fabrics, coated with adhesive in which are embedded spheres of a diameter not exceeding 75 µm	0
ex 7212 50 99	10	Cold-rolled steel, coated on both sides with a nickel-zinc layer, in the form of strip of a width of 40,15 (± 0,08) mm and a thickness of 0,3 (± 0,01) mm, containing by weight: — not more than 0,1 % of carbon, — not more than 0,04 % of phosphorus, — not more than 0,05 % of sulphur and — 0,2 % or more but not more than 0,5 % of manganese	0
ex 8424 89 95 ex 8479 89 98	30 50	Machines and apparatus for the application of adhesives, soldering pastes or epoxy dots on printed circuit boards	0
ex 8479 89 98	60	Machines and apparatus for the placement or removal of active/passive components or connecting elements on/from printed circuit boards	0
ex 8520 90 90	20	Drive-unit capable of magneto-optical signal recording and optical signal reproducing, comprising at least an optical unit, DC motors and a printed circuit on which are mounted integrated circuits providing drive and signal processing functions for reading optical discs having an external diameter not exceeding 70 mm, not comprising circuits with amplification functions or power supply drive functions	0
ex 8533 40 10	31	Package of potentiometers (so-called focus block), with a supply voltage of 9,3 kV or more but not exceeding 28 kV, contained in a housing with connectors	0
ex 8536 50 19	92	Hydraulic pressure switch, incorporating a pressure sensitive snap action disc, operating at a supply voltage of 6 V or more but not exceeding 18 V	0
ex 8536 90 85 ex 8544 49 80	94 10	Elastomeric connector, consisting of one or more conductor elements and of a rubber or silicon substrate	0
ex 8540 11 70	32	Colour cathode-ray tube with a diagonal measurement of the screen of 85,5 cm or more	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8543 89 95	57	Frequency converter, not comprising a dipole aerial, for the conversion of frequencies of 10,7 GHz or more but not exceeding 12,75 GHz to frequencies of 950 MHz or more but not exceeding 3 GHz and operating at a supply voltage of 11 V or more but not exceeding 20 V	0
ex 9022 30 00	10	X-ray tube with a target voltage of 4 kV or more but not exceeding 30 kV, a power not exceeding 9 W and a target current not exceeding 2 mA	0
ex 9026 20 30	10	Pressure measurement device for automotive applications, comprising active and passive elements mounted on a printed circuit and a sensor, the whole contained in a housing	0
ex 9026 90 90	10	Ceramic pressure sensitive module, containing passive components and a printed circuit, for use in the manufacture of pressure measurement devices for automobiles (a)	0
ex 9110 12 00	91	Assembly consisting of a printed circuit on which are mounted one quartz oscillator, at least one watch circuit and, whether or not integrated, at least one capacitor, of a thickness not exceeding 5 mm	0
ex 9110 90 00 ex 9114 90 00	92 91	Assembly consisting of a printed circuit on which is mounted a watch circuit or a watch circuit and a quartz oscillator, of a thickness not exceeding 5 mm	0
ex 9110 90 00	93	Assembly consisting of a printed circuit on which is mounted at least one watch circuit, a quartz oscillator and a piezo-electric sound element, with a thickness exceeding 5 mm	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

ANEXO II — BILAG II — ANHANG II — ΠΑΡΑΡΤΗΜΑ II — ANNEX II — ANNEXE II — ALLEGATO II — BIJLAGE II — ANEXO II — LIITE II — BILAGA II

Código NC KN-kode KN-Code Κωδικός ΣΟ CN code Code NC Codice NC GN-code Código NC CN-koodi KN-nummer	Taric
ex 0713 33 90	20
ex 2825 10 00	10
ex 2905 39 80	20
ex 3815 90 90	85
ex 3920 30 00	20
ex 3920 62 19	85
ex 5402 39 10	10
ex 5407 71 00	20
ex 5903 90 99	10

Código NC KN-kode KN-Code Κωδικός ΣΟ CN code Code NC Codice NC GN-code Código NC CN-koodi KN-nummer	Taric
ex 5907 00 90	10
ex 8536 50 80	94
ex 8536 90 85	94
ex 8543 89 95	57
ex 9031 80 39	20
ex 9110 12 00	91
ex 9110 90 00	92
ex 9110 90 00	93
ex 9114 90 00	91