I

*(Legislative acts)*

# REGULATIONS

## COUNCIL REGULATION (EU) No 12/2010

## of 22 December 2009

## amending Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial, agricultural and fishery products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the Commission,

Whereas:

(1) Council Regulation (EC) No 1255/96 [1] partially or totally suspends the autonomous common customs tariff duties for a number of products during certain periods. It is in the interest of the Union to insert 87 new products in the list of suspensions set out in the Annex to that Regulation.

(2) A limited number of products listed in the Annex to Regulation (EC) No 1255/96 should be withdrawn from the list because it is no longer in the interest of the Union to maintain the suspension of autonomous common customs tariff duties for those products.

(3) For some products listed in that Annex the description needs to be modified in order to take account of technical product developments and economic trends on the market. For 110 other products, the CN and TARIC codes should be adapted as a consequence of changes introduced in the Combined Nomenclature, applicable as from 1 January 2010. The entries for those products should be considered as withdrawn from the list and should be reinserted as new products.

(4) For ease of comprehension, in view of the large number of amendments coming into force on 1 January 2010, the Annex to Regulation (EC) No 1255/96 should be replaced by a completely new version which has effect from the same date. In the interest of clarity the new and amended entries should be marked with an asterisk in the first column of the Annex.

(5) Experience has shown the need to provide for an expiry date for the suspensions listed in Regulation (EC) No 1255/96 to ensure that account is taken of technological and economic changes. This should not exclude the premature termination of certain measures or their continuation beyond the suspension period, if economic reasons are submitted, in accordance with the principles laid down in the Commission Communication of 25 April 1998 concerning autonomous tariff suspensions and quotas.

(6) Regulation (EC) No 1255/96 should therefore be amended accordingly.

(7) Since the suspensions laid down in this Regulation have to take effect from 1 January 2010, this Regulation should apply from the same date and enter into force immediately,

HAS ADOPTED THIS REGULATION:

*Article 1*

The Annex to Regulation (EC) No 1255/96 is hereby replaced by the text in the Annex to this Regulation.

[1] OJ L 158, 29.6.1996, p. 1.

*Article 2*

The temporary suspensions of the autonomous duties of the common customs tariff for the products set out in the Annex to Regulation (EC) No 1255/96 as amended by this Regulation shall apply from 1 January 2010. They shall expire on the dates listed in that Annex.

*Article 3*

This Regulation shall enter into force on the day of its publication in the *Official Journal of the European Union*.

It shall apply from 1 January 2010.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 22 December 2009.

*For the Council*
*The President*
A. CARLGREN

*ANNEX*

'*ANNEX*

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 0302 69 99 | 30 | Red snapper (*Lutjanus purpureus*), fresh, chilled, for processing (1) (2) | 0 % | 1.1.2010-31.12.2013 |
| *ex 0302 70 00 | 95 | Hard fish roes, fresh, chilled or frozen | 0 % | 1.1.2010-31.12.2013 |
| ex 0303 80 90 | 81 | | | |
| ex 0305 20 00 | 11 | Hard fish roes, salted or in brine | 0 % | 1.1.2010-31.12.2013 |
| ex 0305 20 00 | 30 | | | |
| ex 0710 21 00 | 10 | Peas in pods, of the species *Pisum sativum* of the variety *Hortense axiphium*, frozen, of a thickness of not more than 6 mm, to be used, in their pods, in the manufacture of prepared meals (1) (2) | 0 % | 1.1.2010-31.12.2013 |
| ex 0710 80 95 | 50 | Bamboo shoots, frozen, not put up for retail sale | 0 % | 1.1.2010-31.12.2013 |
| ex 0711 59 00 | 11 | Mushrooms, excluding mushrooms of the genera *Agaricus, Calocybe, Clitocybe, Lepista, Leucoagaricus, Leucopaxillus, Lyophyllum* and *Tricholoma*, provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 0712 32 00 | 10 | Mushrooms, excluding mushrooms of the genus *Agaricus*, dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale (1) (2) | 0 % | 1.1.2010-31.12.2013 |
| ex 0712 33 00 | 10 | | | |
| ex 0712 39 00 | 31 | | | |
| ex 0804 10 00 | 10 | Dates, fresh or dried, not put up for retail sale | 0 % | 1.1.2010-31.12.2013 |
| ex 0810 40 50 | 10 | Fruit of the species *Vaccinium macrocarpon*, fresh | 0 % | 1.1.2010-31.12.2013 |
| 0811 90 50 | | Fruit of the genus *Vaccinium*, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter | 0 % | 1.1.2010-31.12.2013 |
| 0811 90 70 | | | | |
| ex 0811 90 95 | 69 | | | |
| ex 0811 90 95 | 20 | Boysenberries, frozen, not containing added sugar, not put up for retail sale | 0 % | 1.1.2010-31.12.2013 |
| ex 0811 90 95 | 30 | Pineapple (*Ananas comosus*), in pieces, frozen | 0 % | 1.1.2010-31.12.2013 |
| ex 0811 90 95 | 40 | Rose-hips, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter | 0 % | 1.1.2010-31.12.2013 |
| ex 1511 90 19 | 10 | Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of: | 0 % | 1.1.2010-31.12.2013 |
| ex 1511 90 91 | 10 | — industrial monocarboxylic fatty acids of subheading 3823 19 10, | | |
| ex 1513 11 10 | 10 | — methyl esters of fatty acids of heading 2915 or 2916, | | |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 1513 19 30 | 10 | — fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the manufacture of cosmetics, washing products or pharmaceutical products, | | |
| ex 1513 21 10 | 10 | — fatty alcohols of subheading 2905 16, pure or mixed, used for the manufacture of cosmetics, washing products or pharmaceutical products, | | |
| ex 1513 29 30 | 10 | — stearic acid of subheading 3823 11 00 or<br>— goods of heading No 3401<br>(1) | | |
| ex 1515 90 99 | 92 | Vegetable oil, refined, containing by weight 35 % or more but not more than 50 % of arachidonic acid or 35 % or more but not more than 50 % of docosahexaenoic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 1517 90 99 | 10 | Vegetable oil, refined, containing by weight 35 % or more but not more than 50 % arachidonic acid or 35 % or more but not more than 50 % docosahexaenoic acid and standardized with high oleic sunflower oil (HOSO) | 0 % | 1.1.2010-31.12.2011 |
| ex 1518 00 99 | 10 | Jojoba oil, hydrogenated and texturised | 0 % | 1.1.2010-31.12.2013 |
| ex 1604 11 00 | 20 | Pacific salmon (*Oncorhynchus spp.*), for the processing industry for manufacture into pastes or spreads (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 1604 30 90 | 10 | Hard fish roes, washed, cleaned of adherent organs and simply salted or in brine, for processing (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 1605 10 00<br>ex 1605 10 00 | 11<br>19 | Crabs of the species "King" (*Paralithodes camchaticus*), "Hanasaki" (*Paralithodes brevipes*), "Kegani" (*Erimacrus isenbecki*), "Queen" and "Snow" (*Chionoecetes spp.*), "Red" (*Geryon quinquedens*), "Rough stone" (*Neolithodes asperrimus*), *Lithodes santolla*, "Mud" (*Scylla serrata*), "Blue" (*Portunus spp.*), simply boiled in water and shelled, whether or not frozen, in immediate packings of a net content of 2 kg or more | 0 % | 1.1.2010-31.12.2013 |
| ex 1902 30 10<br>ex 1903 00 00 | 10<br>20 | Transparent noodles, cut in pieces, obtained from beans (*Vigna radiata* (L.) Wilczek), not put up for retail sale | 0 % | 1.1.2010-31.12.2013 |
| ex 2005 91 00 | 10 | Bamboo shoots, prepared or preserved, in immediate packings of a net content of more than 5 kg | 0 % | 1.1.2010-31.12.2013 |
| ex 2008 60 19<br>ex 2008 60 39 | 30<br>30 | Sweet cherries containing added spirit, whether or not with a sugar content of 9 % by weight, of a diameter of not more than 19,9 mm, with stone, for use in chocolate products (1) | 10 % (3) | 1.1.2010-31.12.2012 |
| *ex 2009 49 30 | 91 | Pineapple juice, other than in powder form:<br>— with a Brix value of more than 20 but not more than 67,<br>— a value of more than EUR 30 per 100 kg net weight,<br>— containing added sugars | 0 % | 1.1.2010-31.12.2014 |
| *ex 2009 80 79 | 82 | Cranberry juice concentrate with a Brix value of 40 or more but not more than 66 | 0 % | 1.1.2010-31.12.2014 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2009 80 79 | 87 | Frozen boysenberry juice concentrate with a Brix value of 61 or more, but not more than 65 | 0 % | 1.1.2010-31.12.2011 |
| ex 2009 80 99 | 93 | Untreated frozen coconut water, not put up for retail sale | 0 % | 1.1.2010-31.12.2011 |
| ex 2106 10 20 | 10 | Soya protein isolate, containing by weight 6,6 % or more but not more than 8,6 % of calcium phosphate | 0 % | 1.1.2010-31.12.2013 |
| ex 2710 11 25 | 10 | Mixture of isomers 2,4,4-trimethylpent-1-ene and 2,4,4-trimethylpent-2-ene | 0 % | 1.1.2010-31.12.2013 |
| ex 2804 50 90 | 10 | Tellurium of a purity by weight of 99,99 % or more, but not more than 99,999 % by weight | 0 % | 1.1.2010-31.12.2013 |
| ex 2805 30 10 | 10 | Alloy of cerium and other rare-earth metals, containing by weight 47 % or more of cerium | 0 % | 1.1.2010-31.12.2013 |
| ex 2805 30 90 | 10 | Lanthanum of a purity by weight of 99 % or more | 0 % | 1.1.2010-31.12.2013 |
| ex 2811 19 80 | 10 | Sulphamidic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2811 22 00 | 10 | Silicon dioxide in the form of powder, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 2811 22 00 | 20 | Microspheres of amorphous silicon of a particle size of 5 µm (± 1 µm), for use in the manufacture of cosmetic products (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 2811 22 00 | 30 | Balls of porous white silica of a particle size of more than 1 µm for use in the manufacture of cosmetic products (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 2812 90 00 | 10 | Nitrogen trifluoride | 0 % | 1.1.2010-31.12.2013 |
| ex 2812 90 00 | 20 | Silicon tetrafluoride | 0 % | 1.1.2010-31.12.2013 |
| *ex 2818 20 00 | 10 | Activated alumina with a specific surface area of at least 350 $m^2/g$ | 0 % | 1.1.2010-31.12.2014 |
| ex 2818 30 00 | 10 | Aluminium hydroxide oxide in the form of pseudo-boehmite | 4 % | 1.1.2010-31.12.2013 |
| 2819 10 00 | | Chromium trioxide | 0 % | 1.1.2010-31.12.2011 |
| ex 2823 00 00 | 10 | Titanium dioxide, of a purity by weight of 99,9 % or more, with an average grain-size of 1,2 µm or more but not more than 1,8 µm, for the manufacture of goods of heading No 8532 or 8533 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 2825 50 00 | 10 | Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride | 0 % | 1.1.2010-31.12.2013 |
| ex 2827 39 85 | 10 | Copper monochloride of a purity by weight of 96 % or more but not more than 99 % | 0 % | 1.1.2010-31.12.2013 |
| ex 2827 39 85 | 20 | Antimony pentachloride of a purity by weight of 99 % or more | 0 % | 1.1.2010-31.12.2011 |
| ex 2827 39 85 | 30 | Manganese dichloride | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2827 49 90 | 10 | Hydrated zirconium dichloride oxide | 0 % | 1.1.2010-31.12.2013 |
| ex 2830 10 00 | 10 | Disodium tetrasulphide, containing by weight 38 % or less of sodium calculated on the dry weight | 0 % | 1.1.2010-31.12.2013 |
| ex 2833 29 80 | 10 | Manganese sulphate monohydrate | 0 % | 1.1.2010-31.12.2013 |
| ex 2835 10 00 | 10 | Sodium hypophosphite monohydrate | 0 % | 1.1.2010-31.12.2012 |
| ex 2836 91 00 | 20 | Lithium carbonate, containing one or more of the following impurities at the concentrations indicated:<br>— 2 mg/kg or more of arsenic,<br>— 200 mg/kg or more of calcium,<br>— 200 mg/kg or more of chlorides,<br>— 20 mg/kg or more of iron,<br>— 150 mg/kg or more of magnesium,<br>— 20 mg/kg or more of heavy metals,<br>— 300 mg/kg or more of potassium,<br>— 300 mg/kg or more of sodium,<br>— 200 mg/kg or more of sulphates,<br>determined according to the methods specified in the European Pharmacopœia | 0 % | 1.1.2010-31.12.2013 |
| ex 2836 99 17 | 10 | Zirconium (IV) basic carbonate | 0 % | 1.1.2010-31.12.2013 |
| ex 2837 19 00 | 20 | Copper cyanide | 0 % | 1.1.2010-31.12.2013 |
| ex 2837 20 00 | 10 | Tetrasodium hexacyanoferrate (II) | 0 % | 1.1.2010-31.12.2011 |
| ex 2839 19 00 | 10 | Disodium disilicate | 0 % | 1.1.2010-31.12.2012 |
| ex 2839 90 90 | 10 | Lead silicate hydrate, of a lead content by weight of (84,5 ± 1,5) %, evaluated as lead monoxide, in the form of powder | 0 % | 1.1.2010-31.12.2013 |
| ex 2839 90 90 | 20 | Calcium silicate | 0 % | 1.1.2010-31.12.2013 |
| 2841 30 00 | | Sodium dichromate | 0 % | 1.1.2010-31.12.2013 |
| ex 2841 80 00 | 10 | Diammonium wolframate (ammonium paratungstate) | 0 % | 1.1.2010-31.12.2012 |
| ex 2841 90 85 | 10 | Lithium cobalt (III) oxide with a cobalt content of at least 59 % | 0 % | 1.1.2010-31.12.2012 |
| ex 2842 10 00 | 10 | Synthetic Beta Zeolite powder | 0 % | 1.1.2010-31.12.2013 |
| *ex 2842 10 00 | 20 | Synthetic Chabasite Zeolite powder | 0 % | 1.1.2010-31.12.2014 |
| *ex 2842 90 10 | 10 | Sodium selenate | 0 % | 1.1.2010-31.12.2014 |
| ex 2843 29 00 | 10 | Silver oxide, nitrate- and carbonate-free, with a silver content of at least 99,99 % by weight of the metal content, for the manufacture of silver oxide batteries [1] | 0 % | 1.1.2010-31.12.2011 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| 2845 10 00 | | Heavy water (deuterium oxide) (*Euratom*) | 0 % | 1.1.2010-31.12.2013 |
| 2845 90 10 | | Deuterium and compounds thereof; hydrogen and compounds thereof, enriched in deuterium; mixtures and solutions containing these products (*Euratom*) | 0 % | 1.1.2010-31.12.2013 |
| ex 2845 90 90 | 10 | Helium-3 | 0 % | 1.1.2010-31.12.2011 |
| ex 2845 90 90 | 20 | Water enriched at a level of 95 % or more *by weight* with oxygen-18 | 0 % | 1.1.2010-31.12.2013 |
| ex 2845 90 90 | 30 | Carbon monoxide $^{13}C$ | 0 % | 1.1.2010-31.12.2011 |
| ex 2845 90 90 | 40 | Iron boride enriched at a level of more than 95 % by weight with boron-10 | 0 % | 1.1.2010-31.12.2013 |
| ex 2846 10 00<br>ex 3824 90 97 | 10<br>48 | Rare-earth concentrate containing by weight 60 % or more but not more than 95 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight | 0 % | 1.1.2010-31.12.2013 |
| ex 2846 10 00 | 20 | Dicerium tricarbonate, whether or not hydrated | 0 % | 1.1.2010-31.12.2013 |
| ex 2846 10 00 | 30 | Cerium lanthanum carbonate, whether or not hydrated | 0 % | 1.1.2010-31.12.2013 |
| ex 2846 10 00 | 40 | Cerium lanthanum neodymium praseodymium carbonate, whether or not hydrated | 0 % | 1.1.2010-31.12.2013 |
| 2846 90 00 | | Compounds, inorganic or organic, of rare-earth metals, of yttrium or of scandium or of mixtures of these metals, other than those of subheading 2846 10 00 | 0 % | 1.1.2010-31.12.2013 |
| ex 2848 00 00 | 10 | Phosphine | 0 % | 1.1.2010-31.12.2013 |
| ex 2850 00 20 | 10 | Silane | 0 % | 1.1.2010-31.12.2013 |
| ex 2850 00 20 | 20 | Arsine | 0 % | 1.1.2010-31.12.2013 |
| ex 2850 00 20 | 30 | Titanium nitride with a particle size of not more than 250 nm | 0 % | 1.1.2010-31.12.2012 |
| ex 2850 00 60 | 10 | Sodium azide | 0 % | 1.1.2010-31.12.2013 |
| ex 2903 39 90 | 10 | Carbon tetrafluoride (tetrafluoromethane) | 0 % | 1.1.2010-31.12.2013 |
| ex 2903 39 90 | 30 | Perfluoroethane | 0 % | 1.1.2010-31.12.2013 |
| ex 2903 39 90 | 40 | 1,1-Difluoroethane | 0 % | 1.1.2010-31.12.2013 |
| ex 2903 39 90 | 50 | 1,1,1,3,3-Pentafluoropropane | 0 % | 1.1.2010-31.12.2013 |
| ex 2903 39 90 | 70 | 1,1,1,2 Tetrafluoroethane, certified odourless containing a maximum:<br>— 600 ppm by weight of 1,1,2,2-Tetrafluoroethane,<br>— 2 ppm by weight of pentafluoroethane,<br>— 2 ppm by weight of chlorodifluoromethane, | 0 % | 1.1.2010-31.12.2011 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| | | — 2 ppm by weight of chloropentafluoroethane,<br>— 2 ppm by weight of dichlorodifluoromethane<br>For use in the manufacture of pharmaceutical grade propellant for medical metred dose inhalers (1) | | |
| ex 2903 39 90 | 75 | *Trans*-1,3,3,3-tetrafluoroprop-1-ene | 0 % | 1.1.2010-31.12.2013 |
| ex 2903 39 90 | 80 | Hexafluoropropene | 0 % | 1.1.2010-31.12.2011 |
| ex 2903 43 00 | 10 | 1,1,1-Trichlorotrifluoroethane | 0 % | 1.1.2010-31.12.2013 |
| ex 2903 59 80 | 10 | 1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo [12.2.1.1$^{6,9}$.0$^{2,13}$.0$^{5,10}$]octadeca-7,15-diene | 0 % | 1.1.2010-31.12.2013 |
| ex 2903 59 80 | 30 | Octafluorocyclopentene | 0 % | 1.1.2010-31.12.2011 |
| ex 2903 69 90 | 10 | Di- or tetrachlorotricyclo[8.2.2.2$^{4,7}$]hexadeca-1(12),4,6,10,13,15-hexaene, mixed isomers | 0 % | 1.1.2010-31.12.2013 |
| ex 2903 69 90 | 20 | 1,2-Bis(pentabromophenyl)ethane | 0 % | 1.1.2010-31.12.2013 |
| ex 2903 69 90 | 40 | 2,6-Dichlorotoluene, of a purity by weight of 99 % or more and containing:<br>— 0,001 mg/kg or less of tetrachlorodibenzodioxines,<br>— 0,001 mg/kg or less of tetrachlorodibenzofurans,<br>— 0,2 mg/kg or less of tetrachlorobiphenyls | 0 % | 1.1.2010-31.12.2013 |
| ex 2903 69 90 | 50 | Fluorobenzene | 0 % | 1.1.2010-31.12.2013 |
| ex 2903 69 90 | 60 | α-Chloro(ethyl)toluenes | 0 % | 1.1.2010-31.12.2013 |
| ex 2904 10 00 | 40 | Sodium toluene-4-sulphonate | 0 % | 1.1.2010-31.12.2012 |
| ex 2904 20 00 | 40 | 2-Nitropropane | 0 % | 1.1.2010-31.12.2013 |
| ex 2904 90 40 | 10 | Trichloronitromethane, for the manufacture of goods of subheading 3808 92 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 2904 90 95 | 20 | 1-Chloro-2,4-dinitrobenzene | 0 % | 1.1.2010-31.12.2013 |
| *ex 2904 90 95 | 30 | Tosyl chloride | 0 % | 1.1.2010-31.12.2014 |
| ex 2905 19 00<br>ex 3824 90 97 | 11<br>56 | Potassium *tert*-butanolate (potassium *tert*-butoxide), whether or not in the form of a solution in tetrahydrofuran | 0 % | 1.1.2010-31.12.2013 |
| ex 2905 19 00 | 30 | 2,6-Dimethylheptan-4-ol | 0 % | 1.1.2010-31.12.2013 |
| *ex 2905 29 90 | 10 | 3,5-Dimethylhex-1-yn-3-ol | 0 % | 1.1.2010-31.12.2014 |
| *ex 2905 49 00 | 10 | Ethylidynetrimethanol | 0 % | 1.1.2010-31.12.2014 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 2905 59 98 | 20 | 2,2,2-Trifluoroethanol | 0 % | 1.1.2010-31.12.2014 |
| 2906 11 00 | | Menthol | 0 % | 1.1.2010-31.12.2013 |
| ex 2906 19 00 | 10 | Cyclohex-1,4-ylenedimethanol | 0 % | 1.1.2010-31.12.2013 |
| ex 2906 19 00 | 20 | 4,4′-Isopropylidenedicyclohexanol | 0 % | 1.1.2010-31.12.2013 |
| *ex 2906 29 00 | 10 | 2,2'-(*m*-Phenylene)dipropan-2-ol | 0 % | 1.1.2010-31.12.2014 |
| ex 2906 29 00 | 20 | 1-Hydroxymethyl-4-methyl-2,3,5,6-tetrafluorobenzene | 0 % | 1.1.2010-31.12.2013 |
| ex 2907 19 90 | 10 | 2,3,5-Trimethylphenol | 0 % | 1.1.2010-31.12.2013 |
| ex 2907 19 90 | 20 | Biphenyl-4-ol | 0 % | 1.1.2010-31.12.2013 |
| ex 2907 21 00 | 10 | Resorcinol | 0 % | 1.1.2010-31.12.2013 |
| ex 2907 29 00 | 20 | 4,4′-(3,3,5-Trimethylcyclohexylidene)diphenol | 0 % | 1.1.2010-31.12.2013 |
| ex 2907 29 00 | 30 | 4,4′,4″-Ethylidynetriphenol | 0 % | 1.1.2010-31.12.2013 |
| ex 2907 29 00 | 50 | 6,6′,6″-Tricyclohexyl-4,4′,4″-butane-1,1,3-triyltri(*m*-cresol) | 0 % | 1.1.2010-31.12.2013 |
| ex 2907 29 00 | 70 | 2,2',2″,6,6',6″-Hexa-*tert*-butyl-α,α',α″-(mesitylene-2,4,6-triyl)tri-*p*-cresol | 0 % | 1.1.2010-31.12.2013 |
| ex 2907 29 00 | 85 | Phloroglucinol whether or not hydrated | 0 % | 1.1.2010-31.12.2013 |
| ex 2908 99 90 | 30 | 4-Nitrophenol | 0 % | 1.1.2010-31.12.2013 |
| ex 2909 19 90 | 20 | Bis(2-chloroethyl) ether | 0 % | 1.1.2010-31.12.2013 |
| ex 2909 19 90 | 30 | Mixture of isomers of nonafluorobutyl methyl ether or nonafluorobutyl ethyl ether, of a purity by weight of 99 % or more | 0 % | 1.1.2010-31.12.2013 |
| ex 2909 19 90 | 50 | 3-Ethoxy-perfluoro-2-methylhexane | 0 % | 1.1.2010-31.12.2011 |
| ex 2909 19 90 | 60 | 1-Methoxyheptafluoropropane | 0 % | 1.1.2010-31.12.2013 |
| ex 2909 30 38 | 10 | Bis(pentabromophenyl) ether | 0 % | 1.1.2010-31.12.2013 |
| ex 2909 50 00 | 10 | 4-(2-Methoxyethyl)phenol | 0 % | 1.1.2010-31.12.2013 |
| ex 2909 60 00 | 10 | Bis(α,α-dimethylbenzyl) peroxide | 0 % | 1.1.2010-31.12.2013 |
| ex 2910 90 00 | 30 | 2,3-Epoxypropan-1-ol (glycidol) | 0 % | 1.1.2010-31.12.2013 |
| ex 2910 90 00 | 60 | 1,2-Epoxyoctadecane, of a purity by weight of 82 % or more | 0 % | 1.1.2010-31.12.2013 |
| ex 2912 29 00 | 30 | α,α,3-Trimethylbenzenepropanal | 0 % | 1.1.2010-31.12.2013 |
| ex 2912 49 00 | 10 | 3-Phenoxybenzaldehyde | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2912 49 00 | 20 | 4-Hydroxybenzaldehyde | 0 % | 1.1.2010-31.12.2011 |
| ex 2914 19 90 | 20 | Heptan-2-one | 0 % | 1.1.2010-31.12.2012 |
| ex 2914 19 90 | 30 | 3-Methylbutanone | 0 % | 1.1.2010-31.12.2012 |
| ex 2914 19 90 | 40 | Pentan-2-one | 0 % | 1.1.2010-31.12.2012 |
| 2914 21 00 | | Camphor | 0 % | 1.1.2010-31.12.2013 |
| ex 2914 29 00 | 20 | Cyclohexadec-8-enone | 0 % | 1.1.2010-31.12.2013 |
| ex 2914 39 00 | 20 | Stearoyl benzoyl methane | 0 % | 1.1.2010-31.12.2012 |
| ex 2914 39 00 | 30 | Benzophenone | 0 % | 1.1.2010-31.12.2012 |
| ex 2914 39 00 | 40 | 1,3-Diphenylpropane-1,3-dione | 0 % | 1.1.2010-31.12.2012 |
| ex 2914 39 00 | 50 | 4-Phenylbenzophenone | 0 % | 1.1.2010-31.12.2013 |
| ex 2914 39 00 | 60 | 4-Methylbenzophenone | 0 % | 1.1.2010-31.12.2013 |
| ex 2914 50 00 | 30 | 2'-Hydroxyacetophenone | 0 % | 1.1.2010-31.12.2013 |
| ex 2914 50 00 | 60 | 2,2-Dimethoxy-2-phenylacetophenone | 0 % | 1.1.2010-31.12.2012 |
| ex 2914 50 00 | 70 | 16α,17α-Epoxy-3β-hydroxypregn-5-en-20-one | 0 % | 1.1.2010-31.12.2012 |
| ex 2914 50 00 | 80 | 2′,6'-dihydroxyacetophenone | 0 % | 1.1.2010-31.12.2013 |
| ex 2914 69 90 | 10 | 2-Ethylanthraquinone | 0 % | 1.1.2010-31.12.2013 |
| ex 2914 69 90 | 20 | 2-Pentylanthraquinone | 0 % | 1.1.2010-31.12.2013 |
| ex 2914 69 90 | 30 | 1,4-Dihydroxyanthraquinone | 0 % | 1.1.2010-31.12.2013 |
| ex 2914 70 00 | 10 | 1-Chloro-3,3-dimethylbutan-2-one | 0 % | 1.1.2010-31.12.2013 |
| ex 2914 70 00 | 40 | Perfluoro(2-methylpentan-3-one) | 0 % | 1.1.2010-31.12.2013 |
| ex 2914 70 00 | 50 | 3′-Chloropropiophenone | 0 % | 1.1.2010-31.12.2013 |
| ex 2915 29 00 | 10 | Antimony triacetate | 0 % | 1.1.2010-31.12.2013 |
| ex 2915 39 00 | 40 | *tert*-Butyl acetate | 0 % | 1.1.2010-31.12.2013 |
| ex 2915 39 00 | 50 | 3-Acetylphenyl acetate | 0 % | 1.1.2010-31.12.2013 |
| ex 2915 90 00 | 40 | Nonanoic acid (pelargonic acid) | 0 % | 1.1.2010-31.12.2013 |
| ex 2916 12 00 | 10 | 2-*tert*-Butyl-6-(3-*tert*-butyl-2-hydroxy-5-methylbenzyl)-4-methylphenyl acrylate | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2916 12 00 | 20 | 2-Ethoxyethyl acrylate | 0 % | 1.1.2010-31.12.2013 |
| ex 2916 12 00 | 30 | Isobutyl acrylate | 0 % | 1.1.2010-31.12.2013 |
| ex 2916 12 00 | 40 | 2,4-Di-*tert*-pentyl-6-[1-(3,5-di-*tert*-pentyl-2-hydroxyphenyl)ethyl]phenyl-acrylate | 0 % | 1.1.2010-31.12.2013 |
| *ex 2916 13 00 | 10 | Hydroxyzinc methacrylate powder | 0 % | 1.1.2010-31.12.2014 |
| ex 2916 13 00 | 20 | Zinc dimethacrylate, in the form of powder | 0 % | 1.1.2010-31.12.2013 |
| ex 2916 14 00 | 10 | 2,3-Epoxypropyl methacrylate | 0 % | 1.1.2010-31.12.2013 |
| ex 2916 19 95 | 20 | Methyl 3,3-dimethylpent-4-enoate | 0 % | 1.1.2010-31.12.2013 |
| ex 2916 20 00 | 50 | Ethyl 2,2-dimethyl-3-(2-methylpropenyl)cyclopropanecarboxylate | 0 % | 1.1.2010-31.12.2013 |
| ex 2916 39 00 | 20 | 3,5-Dichlorobenzoyl chloride | 3,6 % | 1.1.2010-31.12.2013 |
| ex 2916 39 00 | 40 | Vinyl 4-*tert*-butylbenzoate | 0 % | 1.1.2010-31.12.2013 |
| ex 2916 39 00 | 45 | 2-Chlorobenzoic acid | 0 % | 1.1.2010-31.12.2011 |
| ex 2916 39 00 | 50 | 3,5-Dimethylbenzoyl chloride | 0 % | 1.1.2010-31.12.2013 |
| ex 2916 39 00 | 55 | 4-*tert*-Butylbenzoic acid | 0 % | 1.1.2010-31.12.2012 |
| ex 2916 39 00 | 60 | 4-Ethylbenzoyl chloride | 0 % | 1.1.2010-31.12.2013 |
| ex 2916 39 00 | 65 | 2-(4-nitrophenyl)butyric acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2916 39 00 | 70 | Ibuprofen (INN) | 0 % | 1.1.2010-31.12.2013 |
| ex 2916 39 00 | 80 | Ethyl 2-(4-nitrophenyl)butyrate | 0 % | 1.1.2010-31.12.2013 |
| ex 2917 11 00 | 20 | Bis(*p*-methylbenzyl) oxalate | 0 % | 1.1.2010-31.12.2013 |
| ex 2917 19 90 | 20 | Sodium 1,2-bis(cyclohexyloxycarbonyl)ethanesulphonate | 0 % | 1.1.2010-31.12.2013 |
| ex 2917 19 90 | 70 | Itaconic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2917 20 00 | 30 | 1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride | 0 % | 1.1.2010-31.12.2013 |
| ex 2917 20 00 | 40 | 3-Methyl-1,2,3,6-tetrahydrophthalic anhydride | 0 % | 1.1.2010-31.12.2013 |
| ex 2917 34 90 | 10 | Diallyl phthalate | 0 % | 1.1.2010-31.12.2013 |
| *ex 2917 39 95 | 10 | Bis(2-ethylhexyl)-1,4-benzenedicarboxylate | 0 % | 1.1.2010-31.12.2014 |
| *ex 2918 19 98 | 20 | L-Malic acid | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2918 29 00 | 10 | Monohydroxynaphthoic acids | 0 % | 1.1.2010-31.12.2013 |
| ex 2918 29 00 | 30 | Octadecyl-3-(3,5-di-*tert*-butyl-4-hydroxyphenyl)propionate | 0 % | 1.1.2010-31.12.2011 |
| ex 2918 29 00 | 50 | Hexamethylene bis[3-(3,5-di-*tert*-butyl-4-hydroxyphenyl)propionate] | 0 % | 1.1.2010-31.12.2013 |
| ex 2918 30 00 | 30 | Methyl-2-benzoylbenzoate | 0 % | 1.1.2010-31.12.2013 |
| ex 2918 30 00 | 40 | Phthalaldehydic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2918 99 90 | 10 | 3,4-Epoxycyclohexylmethyl 3,4-epoxycyclohexanecarboxylate | 0 % | 1.1.2010-31.12.2013 |
| ex 2918 99 90 | 30 | Methyl 2-(4-hydroxyphenoxy)propionate | 0 % | 1.1.2010-31.12.2013 |
| ex 2918 99 90 | 40 | *trans*-4-Hydroxy-3-methoxycinnamic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2918 99 90 | 50 | Methyl 3,4,5-trimethoxybenzoate | 0 % | 1.1.2010-31.12.2013 |
| ex 2918 99 90 | 60 | 3,4,5-Trimethoxybenzoic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2919 90 00 | 10 | 2,2'-Methylenebis(4,6-di-*tert*-butylphenyl) phosphate, monosodium salt | 0 % | 1.1.2010-31.12.2013 |
| ex 2919 90 00 | 30 | Aluminium hydroxybis[2,2′-methylenebis(4,6-di-*tert*-butylphenyl) phosphate] | 0 % | 1.1.2010-31.12.2013 |
| ex 2919 90 00 | 40 | Tri-n-hexylphosphate | 0 % | 1.1.2010-31.12.2013 |
| ex 2920 19 00 | 10 | Fenitrothion (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2920 19 00 | 20 | Tolclofos-methyl (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2920 90 10 | 10 | Diethyl sulphate | 0 % | 1.1.2010-31.12.2013 |
| ex 2920 90 10 | 20 | Diallyl 2,2′-oxydiethyl dicarbonate | 0 % | 1.1.2010-31.12.2013 |
| ex 2920 90 10 | 40 | Dimethyl carbonate | 0 % | 1.1.2010-31.12.2013 |
| ex 2920 90 10 | 50 | Di-*tert*-butyl dicarbonate | 0 % | 1.1.2010-31.12.2013 |
| 2920 90 30 | | Trimethyl phosphite | 0 % | 1.1.2010-31.12.2013 |
| 2920 90 40 | | Triethyl phosphite | 0 % | 1.1.2010-31.12.2011 |
| ex 2920 90 85 | 10 | *O,O'*-Dioctadecyl pentaerythritol bis(phosphite) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2921 19 99 | 20 | Ethyl(2-methylallyl)amine | 0 % | 1.1.2010-31.12.2013 |
| *ex 2921 19 99 | 30 | Allylamine | 0 % | 1.1.2010-31.12.2013 |
| *ex 2921 19 99 | 40 | Tris(diethylamido)tert-butylimido tantalum (V) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2921 19 99 | 50 | Tetrakis (Ethylmethylamino) hafnium (IV) | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 2921 19 99 | 60 | Tetrakis(ethylmethylamino) zirconium (IV) | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 29 00 | 10 | *N,N,N′,N′*-Tetrabutylhexamethylenediamine | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 29 00 | 20 | Tris[3-(dimethylamino)propyl]amine | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 29 00 | 30 | Bis[3-(dimethylamino)propyl]methylamine | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 30 99 | 10 | Dicyclohexyl(methyl)amine | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 30 99 | 20 | Cyclohex-1,3-ylenebis(methylamine), for the manufacture of dishwashing products ([1]) | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 42 00 | 10 | 2,6-Dichloro-4-nitroaniline | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 42 00 | 15 | 4-Amino-3-nitrobenzenesulphonic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 42 00 | 25 | Sodium hydrogen 2-aminobenzene-1,4-disulphonate | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 42 00 | 35 | 2-Nitroaniline | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 42 00 | 45 | 2,4,5-Trichloroaniline | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 42 00 | 50 | 3-Aminobenzenesulfonic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 42 00 | 70 | 2-Aminobenzene-1,4-disulfonic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 42 00 | 80 | 4-Chloro-2-nitroaniline | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 42 00 | 85 | 3,5-Dichloroaniline | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 43 00 | 10 | 5-Amino-2-chlorotoluene-4-sulphonic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 43 00 | 20 | 4-Amino-6-chlorotoluene-3-sulphonic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 43 00 | 30 | 3-Nitro-*p*-toluidine | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 43 00 | 40 | 4-Aminotoluene-3-sulphonic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 44 00 | 20 | Diphenylamine | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 45 00 | 10 | Sodium hydrogen 3-aminonaphthalene-1,5-disulphonate | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 45 00 | 20 | 2-Aminonaphthalene-1,5-disulphonic acid and its sodium salts | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 45 00 | 40 | 1-Naphthylamine | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 49 00 | 20 | Pendimethalin (ISO) | 3,5 % | 1.1.2010-31.12.2013 |
| ex 2921 49 00 | 40 | N-1-Naphthylaniline | 0 % | 1.1.2010-31.12.2013 |
| *ex 2921 49 00 | 60 | N-Benzyl-*N*-ethylaniline | 0 % | 1.1.2010-31.12.2014 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2921 51 19 | 20 | Toluene diamine (TDA), containing by weight 78 % or more but not more than 82 % of 4-methyl-m-phenylenediamine and 18 % or more but not more than 22 % of 2-methyl-m-phenylenediamine, and with a residual tar content of not more than 0,23 % by weight | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 51 19 | 30 | 2-Methyl-*p*-phenylenediamine sulphate | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 51 19 | 40 | *p*-Phenylenediamine | 0 % | 1.1.2010-31.12.2011 |
| ex 2921 51 19 | 50 | Mono- and dichloroderivatives of *p*-phenylenediamine and *p*-diamino-toluene | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 59 90 | 10 | Mixture of isomers of 3,5-diethyltoluenediamine | 0 % | 1.1.2010-31.12.2013 |
| ex 2921 59 90 | 30 | 3,3'-dichlorobenzidine dihydrochloride | 0 % | 1.1.2010-31.12.2012 |
| ex 2921 59 90 | 40 | 4,4′-Diaminostilbene-2,2′-disulphonic acid | 0 % | 1.1.2010-31.12.2013 |
| *ex 2921 59 90 | 50 | *N*-Ethyl-*N*',*N*'-dimethyl-*N*-phenyl-ethylene-1,2-diamine | 0 % | 1.1.2010-31.12.2014 |
| *ex 2922 19 85 | 30 | *N*,*N*,*N*′,*N*′-Tetramethyl-2,2′-oxybis(ethylamine) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2922 19 85 | 50 | 2-(2-Methoxyphenoxy)ethylamine | 0 % | 1.1.2010-31.12.2013 |
| *ex 2922 19 85 | 60 | *N*,*N*,*N*'-trimethyl-*N*'-(2-hydroxy-ethyl) 2,2′-oxybis(ethylamine) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2922 19 85 | 70 | D-(-)-threo-2-amino-1-(*p*-nitrophenyl)propane-1,3-diol | 0 % | 1.1.2010-31.12.2011 |
| *ex 2922 19 85 | 80 | *N*-[2-[2-(Dimethylamino)ethoxy]ethyl]-*N*-methyl-1,3-propanediamine | 0 % | 1.1.2010-31.12.2014 |
| ex 2922 21 00 | 10 | 2-Amino-5-hydroxynaphthalene-1,7-disulphonic acid and its salts, of a purity by weight of 60 % or more | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 21 00 | 30 | 6-Amino-4-hydroxynaphthalene-2-sulphonic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 21 00 | 40 | 7-Amino-4-hydroxynaphthalene-2-sulphonic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 21 00 | 50 | Sodium hydrogen 4-amino-5-hydroxynaphthalene-2,7-disulphonate | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 29 00 | 10 | 2-Methyl-*N*-phenyl-*p*-anisidine | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 29 00 | 20 | 3-Aminophenol | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 29 00 | 25 | 5-Amino-*o*-cresol | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 29 00 | 35 | 2-Amino-4,6-dinitrophenol sodium salt, containing at least 20 % water | 0 % | 1.1.2010-31.12.2011 |
| ex 2922 29 00 | 45 | Anisidines | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 29 00 | 46 | *p*-Anisidine-3-sulphonic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 29 00 | 50 | 6-Methoxy-*m*-toluidine | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 2922 29 00 | 55 | 3-Amino-4-hydroxybenzenesulphonic acid | 0 % | 1.1.2010-31.12.2014 |
| *ex 2922 29 00 | 65 | 4-Trifluoromethoxyaniline | 0 % | 1.1.2010-31.12.2014 |
| ex 2922 29 00 | 70 | 4-Nitro-*o*-anisidine | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 29 00 | 80 | 3-Diethylaminophenol | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 39 00 | 10 | 1-Amino-4-bromo-9,10-dioxoanthracene-2-sulphonic acid and its salts | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 39 00 | 70 | *p*-[(2-Chloroethyl)ethylamino]benzaldehyde | 0 % | 1.1.2010-31.12.2011 |
| ex 2922 43 00 | 10 | Anthranilic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 49 85 | 10 | Ornithine aspartate (INNM) | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 49 85 | 40 | Norvaline | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 49 85 | 50 | D-(-)-Dihydrophenylglycine | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 49 85 | 60 | Ethyl-4-dimethylaminobenzoate | 0 % | 1.1.2010-31.12.2012 |
| ex 2922 49 85 | 70 | 2-Ethylhexyl-4-dimethylaminobenzoate | 0 % | 1.1.2010-31.12.2013 |
| *ex 2922 50 00 | 40 | 4,4-Dimethoxybutylamine | 0 % | 1.1.2010-31.12.2013 |
| ex 2922 50 00 | 70 | 2-(1-Hydroxycyclohexyl)-2-(4-methoxyphenyl)ethylammonium acetate | 0 % | 1.1.2010-31.12.2013 |
| ex 2923 90 00 | 10 | Tetramethylammonium hydroxide, in the form of an aqueous solution containing:<br>— 25 (± 0,5) % by weight of tetramethylammonium hydroxide,<br>— 500 mg/kg or less of carbonate,<br>— 200 mg/kg or less of chloride and<br>— 5 mg/kg or less of potassium | 0 % | 1.1.2010-31.12.2013 |
| ex 2923 90 00 | 25 | Tetrakis(dimethylditetradecylammonium) molybdate | 0 % | 1.1.2010-31.12.2013 |
| ex 2923 90 00 | 35 | Tetrabutylammonium fluoride trihydrate | 0 % | 1.1.2010-31.12.2011 |
| *ex 2923 90 00 | 45 | Tetrabutylammonium hydroxide in the form of an aqueous solution containing 55 % (± 1 %) by weight of tetrabutylammonium hydroxide | 0 % | 1.1.2010-31.12.2014 |
| ex 2923 90 00 | 70 | Tetrapropylammonium hydroxide, in the form of an aqueous solution containing:<br>— 40 (± 2) % by weight of tetrapropylammonium hydroxide,<br>— 0,3 % by weight or less of carbonate,<br>— 0,1 % by weight or less of tripropylamine,<br>— 500 mg/kg or less of bromide and<br>— 25 mg/kg or less of potassium and sodium taken together | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2923 90 00 | 80 | Diallyldimethylammonium chloride, in the form of an aqueous solution containing by weight 63 % or more but not more than 67 % of diallyldimethylammonium chloride | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 19 00 | 10 | 2-Acrylamido-2-methylpropanesulphonic acid and its sodium or ammonium salts | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 19 00 | 30 | Methyl 2-acetamido-3-chloropropionate | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 19 00 | 40 | N-(1,1-Dimethyl-3-oxobutyl)acrylamide | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 19 00 | 50 | Acrylamide | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 19 00 | 60 | N,N-Dimethylacrylamide | 0 % | 1.1.2010-31.12.2011 |
| ex 2924 19 00 | 70 | Methylcarbamate | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 21 00 | 10 | 4,4'-Dihydroxy-7,7'-ureylenedi(naphthalene-2-sulfonic acid) and its sodium salts | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 10 | Alachlor (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 15 | Acetochlor (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 25 | 3′-Diethylaminoacetanilide | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 30 | Propachlor (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 65 | 2-(4-Hydroxyphenyl)acetamide | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 75 | 3-Amino-*p*-anisanilide | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 80 | 5'-Chloro-3-hydroxy-2',4'-dimethoxy-2-naphthanilide | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 85 | *p*-Aminobenzamide | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 86 | Anthranilamide of a purity by weight of 99,5 % or more | 0 % | 1.1.2010-31.12.2012 |
| ex 2924 29 98 | 87 | Paracetamol (INN) | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 88 | 5'-Chloro-3-hydroxy-2'-methyl-2-naphthanilide | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 89 | Flutolanil (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 91 | 3-Hydroxy-2′-methoxy-2-naphthanilide | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 92 | 3-Hydroxy-2-naphthanilide | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 93 | 3-Hydroxy-2′-methyl-2-naphthanilide | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 94 | 2′-Ethoxy-3-hydroxy-2-naphthanilide | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2924 29 98 | 96 | 4′-Chloro-3-hydroxy-2′,5′-dimethoxy-2-naphthanilide | 0 % | 1.1.2010-31.12.2013 |
| ex 2924 29 98 | 97 | 1,1-Cyclohexanediacetic acid monoamide | 0 % | 1.1.2010-31.12.2013 |
| ex 2925 11 00 | 20 | Saccharin and its sodium salt | 0 % | 1.1.2010-31.12.2013 |
| ex 2925 19 95 | 10 | N-Phenylmaleimide | 0 % | 1.1.2010-31.12.2013 |
| ex 2925 29 00 | 10 | Dicyclohexylcarbodiimide | 0 % | 1.1.2010-31.12.2013 |
| ex 2926 90 95 | 20 | 2-(*m*-Benzoylphenyl)propiononitrile | 0 % | 1.1.2010-31.12.2013 |
| ex 2926 90 95 | 35 | 2-Bromo-2(bromomethyl)pentanedinitrile | 0 % | 1.1.2010-31.12.2013 |
| ex 2926 90 95 | 45 | 2-Cyanoacetamide | 0 % | 1.1.2010-31.12.2013 |
| ex 2926 90 95 | 50 | Alkyl or alkoxyalkyl esters of cyanoacetic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2926 90 95 | 55 | Methyl-2-cyano-2-phenylbutyrate | 0 % | 1.1.2010-31.12.2011 |
| ex 2926 90 95 | 60 | Cyanoacetic acid in crystalline form | 0 % | 1.1.2010-31.12.2013 |
| ex 2926 90 95 | 61 | *m*-(1-Cyanoethyl)benzoic acid | 0 % | 1.1.2010-31.12.2011 |
| *ex 2926 90 95 | 63 | 1-(Cyanoacetyl)-3-ethylurea | 0 % | 1.1.2010-31.12.2014 |
| *ex 2926 90 95 | 64 | Esfenvalerate of a purity by weight of 83 % or more in a mixture of its own isomers | 0 % | 1.1.2010-31.12.2014 |
| ex 2926 90 95 | 65 | Malononitrile | 0 % | 1.1.2010-31.12.2013 |
| *ex 2926 90 95 | 74 | Chlorothalonil (ISO) | 0 % | 1.1.2010-31.12.2014 |
| ex 2926 90 95 | 80 | Ethyl 2-cyano-2-phenylbutyrate | 0 % | 1.1.2010-31.12.2013 |
| ex 2926 90 95 | 81 | 4-Aminobenzonitrile | 0 % | 1.1.2010-31.12.2013 |
| ex 2926 90 95 | 86 | Ethylenediaminetetraacetonitrile | 0 % | 1.1.2010-31.12.2013 |
| ex 2926 90 95 | 87 | Nitrilotriacetonitrile | 0 % | 1.1.2010-31.12.2013 |
| ex 2926 90 95 | 88 | 1,3-Propylenediaminetetraacetonitrile | 0 % | 1.1.2010-31.12.2013 |
| ex 2926 90 95 | 89 | Butyronitrile | 0 % | 1.1.2010-31.12.2013 |
| ex 2927 00 00 | 10 | 2,2′-Dimethyl-2,2′-azodipropionamidine dihydrochloride | 0 % | 1.1.2010-31.12.2013 |
| ex 2927 00 00 | 20 | 4-Anilino-2-methoxybenzenediazonium hydrogen sulphate | 0 % | 1.1.2010-31.12.2013 |
| ex 2927 00 00 | 30 | 4′-Aminoazobenzene-4-sulphonic acid | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2927 00 00 | 40 | 2-Hydroxynaphthalene-1-diazonium-4-sulphonate | 0 % | 1.1.2010-31.12.2013 |
| ex 2927 00 00 | 50 | 2-Hydroxy-6-nitronaphthalene-1-diazonium-4-sulphonate, of a purity by weight of 60 % or more | 0 % | 1.1.2010-31.12.2013 |
| ex 2927 00 00 | 60 | 4,4′-Dicyano-4,4′-azodivaleric acid | 0 % | 1.1.2010-31.12.2013 |
| *ex 2927 00 00 | 70 | Tetrasodium 3,3'-[azoxybis[(2-methoxy-4,1-phenylene)azo]]bis[4,5-dihydroxynaphthalene-2,7-disulphonate] | 0 % | 1.1.2010-31.12.2014 |
| ex 2928 00 90 | 10 | 3,3'-Bis(3,5-di-*tert*-butyl-4-hydroxyphenyl)-*N*,*N*'-bipropionamide | 0 % | 1.1.2010-31.12.2013 |
| ex 2928 00 90 | 15 | 1,1′-(Hydroxyimino)bis-(2-propanol) | 0 % | 1.1.2010-31.12.2011 |
| ex 2928 00 90 | 20 | 2,4,6-Trichlorophenylhydrazine | 0 % | 1.1.2010-31.12.2013 |
| ex 2928 00 90 | 40 | O-Ethylhydroxylamine, in the form of an aqueous solution | 0 % | 1.1.2010-31.12.2013 |
| ex 2928 00 90 | 60 | Adipohydrazide | 0 % | 1.1.2010-31.12.2013 |
| ex 2928 00 90 | 70 | Butanone oxime | 0 % | 1.1.2010-31.12.2013 |
| ex 2928 00 90 | 80 | Cyflufenamid (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2929 10 00 | 10 | Methylenedicyclohexyl diisocyanates | 0 % | 1.1.2010-31.12.2013 |
| ex 2929 10 00 | 40 | *m*-Isopropenyl-*α*,*α*-dimethylbenzyl isocyanate | 0 % | 1.1.2010-31.12.2013 |
| ex 2929 10 00 | 50 | *m*-Phenylenediisopropylidene diisocyanate | 0 % | 1.1.2010-31.12.2013 |
| ex 2929 10 00 | 60 | Trimethylhexamethylene diisocyanate, mixed isomers | 0 % | 1.1.2010-31.12.2013 |
| ex 2929 10 00 | 80 | 1,3-Bis(isocyanatomethyl)benzene | 0 % | 1.1.2010-31.12.2011 |
| ex 2930 20 00 | 10 | Prosulfocarb (ISO) | 0 % | 1.1.2010-31.12.2012 |
| *ex 2930 90 99 | 15 | Ethoprophos (ISO) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2930 90 99 | 25 | Thiophanate-methyl (ISO) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2930 90 99 | 30 | 4-(4-Isopropoxyphenylsulphonyl)phenol | 0 % | 1.1.2010-31.12.2013 |
| *ex 2930 90 99 | 35 | Glutathione | 0 % | 1.1.2010-31.12.2011 |
| *ex 2930 90 99 | 40 | 3,3′-Thiodi(propionic acid) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2930 90 99 | 45 | 2-[(*p*-Aminophenyl)sulphonyl]ethyl hydrogen sulphate | 0 % | 1.1.2010-31.12.2013 |
| *ex 2930 90 99 | 60 | Methyl phenyl sulphide | 0 % | 1.1.2010-31.12.2013 |
| *ex 2930 90 99 | 62 | Zinc bis(benzenesulfinate) | 0 % | 1.1.2010-31.12.2014 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 2930 90 99 | 64 | 3-Chloro-2-methylphenyl methyl sulphide | 0 % | 1.1.2010-31.12.2014 |
| *ex 2930 90 99 | 66 | Diphenyl sulphide | 0 % | 1.1.2010-31.12.2012 |
| *ex 2930 90 99 | 67 | 3-Bromomethyl-2-chloro-4-(methylsulphonyl)-benzoic acid | 0 % | 1.1.2010-31.12.2012 |
| *ex 2930 90 99 | 68 | Clethodim (ISO) | 0 % | 1.1.2010-31.12.2012 |
| *ex 2930 90 99 | 69 | 2-Amino-4-methylsulphonyl-*N*-methylaniline | 0 % | 1.1.2010-31.12.2012 |
| *ex 2930 90 99 | 71 | Triphenylsulphonium chloride | 0 % | 1.1.2010-31.12.2012 |
| *ex 2930 90 99 | 76 | 2,2'-Dithiodi(benzoic acid) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2930 90 99 | 77 | 4-[4-(2-Propenyloxy)phenylsulphonyl]phenol | 0 % | 1.1.2010-31.12.2013 |
| *ex 2930 90 99 | 78 | 4-Mercaptomethyl-3,6-dithia-1,8-octanedithiol | 0 % | 1.1.2010-31.12.2011 |
| *ex 2930 90 99 | 80 | Captan (ISO) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2930 90 99 | 82 | Sodium toluene-4-sulphinate | 0 % | 1.1.2010-31.12.2012 |
| *ex 2930 90 99 | 83 | Methyl-*p*-tolyl sulphone | 0 % | 1.1.2010-31.12.2012 |
| *ex 2930 90 99 | 86 | 4-Hydroxybenzenethiol | 0 % | 1.1.2010-31.12.2013 |
| *ex 2930 90 99 | 87 | 3-Sulphinobenzoic acid | 0 % | 1.1.2010-31.12.2013 |
| *ex 2930 90 99 | 89 | Potassium- or sodium-salt of O-ethyl-, O-isopropyl-, O-butyl-, O-isobutyl- or O-pentyl-dithiocarbonates | 0 % | 1.1.2010-31.12.2011 |
| 2931 00 10 | | Dimethyl methylphosphonate | 0 % | 1.1.2010-31.12.2013 |
| *ex 2931 00 99 | 05 | Butylethylmagnesium, in the form of a solution in heptane | 0 % | 1.1.2010-31.12.2013 |
| *ex 2931 00 99 | 20 | Methylcyclopentadienyl manganese tricarbonyl containing not more than 4,9 % by weight of cyclopentadienyl manganese tricarbonyl | 0 % | 1.1.2010-31.12.2013 |
| *ex 2931 00 99 | 24 | Methyl tris (2-pentanoneoxime) silane | 0 % | 1.1.2010-31.12.2014 |
| *ex 2931 00 99 | 40 | N-(Phosphonomethyl)iminodiacetic acid | 0 % | 1.1.2010-31.12.2013 |
| *ex 2931 00 99 | 50 | Bis(2,4,4-trimethylpentyl)phosphinic acid | 0 % | 1.1.2010-31.12.2013 |
| *ex 2931 00 99 | 55 | Dimethyl[dimethylsilyldiindenyl]hafnium | 0 % | 1.1.2010-31.12.2014 |
| *ex 2931 00 99 | 70 | *N*,*N*-Dimethylanilinium tetrakis(pentafluorophenyl)borate | 0 % | 1.1.2010-31.12.2014 |
| *ex 2931 00 99 | 85 | Tributyl(tetradecyl)phosphonium chloride, whether or not in the form of an aqueous solution | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 2931 00 99 | 86 | Mixture of the isomers 9-icosyl-9-phosphabicyclo[3.3.1]nonane and 9-icosyl-9-phosphabicyclo[4.2.1]nonane | 0 % | 1.1.2010-31.12.2013 |
| *ex 2931 00 99 | 87 | Tris(4-methylpentan-2-oximino)methylsilane | 0 % | 1.1.2010-31.12.2013 |
| *ex 2931 00 99 | 89 | Tetrabutylphosphonium acetate in the form of an aqueous solution | 0 % | 1.1.2010-31.12.2014 |
| *ex 2931 00 99 | 91 | Trimethylsilane | 0 % | 1.1.2010-31.12.2011 |
| *ex 2931 00 99 | 96 | 3-(Hydroxyphenylphosphinoyl)propionic acid | 0 % | 1.1.2010-31.12.2013 |
| *ex 2931 00 99 | 97 | Potassium 4-tolylphosphinate, in the form of an aqueous solution | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 13 00 | 10 | Tetrahydrofurfuryl alcohol | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 19 00 | 40 | Furan of a purity by weight of 99 % or more | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 19 00 | 41 | 2,2 di(tetrahydrofuryl)propane | 0 % | 1.1.2010-31.12.2013 |
| *ex 2932 19 00 | 45 | 1,6-Dichloro-1,6-dideoxy-$\beta$-D-fructofuranosyl-4-chloro-4 deoxy-$\alpha$-D-galactopyranoside | 0 % | 1.1.2010-31.12.2014 |
| ex 2932 19 00 | 70 | Furfurylamine | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 19 00 | 75 | Tetrahydro-2-methylfuran | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 29 85 | 10 | 2′-Anilino-6′-[ethyl(isopentyl)amino]-3′-methylspiro[isobenzofuran-1(3*H*),9′-xanthen]-3-one | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 29 85 | 35 | 6′-Diethylamino-3′-methyl-2′-(2,4-xylidino)spiro[isobenzofuran-1(3*H*),9′-xanthen]-3-one | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 29 85 | 55 | 6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 29 85 | 60 | 6′-(Dibutylamino)-3′-methyl-2′-(phenylamino)-spiro[isobenzofuran-1(3*H*),9′-[9*H*]xanthen]-3-one | 0 % | 1.1.2010-31.12.2011 |
| ex 2932 29 85 | 70 | 3′,6′-Bis(ethylamino)-2′,7′-dimethylspiro[isobenzofuran-1(3*H*),9′-[9*H*]-xanthen]-3-one | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 29 85 | 71 | 6′-(Diethylamino)-3′-methyl-2′-(phenylamino)-spiro[isobenzofuran-1(3*H*),9′-[9*H*]xanthen]-3-one | 0 % | 1.1.2010-31.12.2011 |
| ex 2932 29 85 | 72 | 2'-[Bis(phenylmethyl)amino]-6'-(diethylamino)-spiro[isobenzofuran-1(3*H*),9'-[9*H*]xanthen]-3-one | 0 % | 1.1.2010-31.12.2011 |
| ex 2932 29 85 | 80 | Gibberellic acid with a minimum purity by weight of 88 % | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 29 85 | 84 | Decahydro-3a,6,6,9a-tetramethylnaphth [2,1-b] furan-2 (1H)-one | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 29 85 | 85 | Hexan-4-olide | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 99 00 | 10 | Bendiocarb (ISO) | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2932 99 00 | 30 | Carbofuran (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 99 00 | 35 | 1,2,3-Trideoxy-4,6:5,7-bis-O-[(4-propylphenyl)methylene]-nonitol | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 99 00 | 40 | 1,3:2,4-Bis-O-(3,4-dimethylbenzylidene)-D-glucitol | 0 % | 1.1.2010-31.12.2013 |
| ex 2932 99 00 | 70 | 1,3:2,4-*bis*-O-Benzylidene-*D*-glucitol | 0 % | 1.1.2010-31.12.2011 |
| ex 2932 99 00 | 75 | 3-(3,4-Methylenedioxyphenyl)-2-methylpropanal | 0 % | 1.1.2010-31.12.2011 |
| ex 2932 99 00 | 80 | 1,3:2,4-*bis*-O-(4-Methylbenzylidene)-*D*-glucitol | 0 % | 1.1.2010-31.12.2011 |
| ex 2933 19 90 | 30 | 3-Methyl-1-*p*-tolyl-5-pyrazolone | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 19 90 | 40 | Edaravone (INN) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 19 90 | 50 | Fenpyroximate (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 19 90 | 60 | Pyraflufen-ethyl (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 19 90 | 70 | 4,5-Diamino-1-(2-hydroxyethyl)-pyrazolsulphate | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 21 00 | 10 | Hydantoin | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 21 00 | 50 | 1-Bromo-3-chloro-5,5-dimethylhydantoin | 0 % | 1.1.2010-31.12.2011 |
| ex 2933 21 00 | 60 | DL-*p*-Hydroxyphenylhydantoin | 0 % | 1.1.2010-31.12.2011 |
| ex 2933 21 00 | 70 | *α*-(4-Methoxybenzoyl)-*α*-(1-benzyl-5-ethoxy-3-hydantoinyl)-2-chloro-5-dodecyloxycarbonylacetanilide | 0 % | 1.1.2010-31.12.2011 |
| ex 2933 29 90 | 40 | Triflumizole (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 29 90 | 50 | 1,3-Dimethylimidazolidin-2-one | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 39 99 | 15 | Pyridine-2,3-dicarboxylic acid | 0 % | 1.1.2010-31.12.2013 |
| *ex 2933 39 99 | 24 | 2-Chloromethyl-4-methoxy-3,5-dimethylpyridine hydrochloride | 0 % | 1.1.2010-31.12.2014 |
| ex 2933 39 99 | 25 | Imazethapyr (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 39 99 | 35 | Aminopyralid (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 39 99 | 40 | 2-Chloropyridine | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 39 99 | 50 | N-Fluoro-2,6-dichloropyridinium tetrafluoroborate | 0 % | 1.1.2010-31.12.2011 |
| *ex 2933 39 99 | 55 | Pyriproxyfen (ISO) of a purity by weight of 97 % or more | 0 % | 1.1.2010-31.12.2014 |
| ex 2933 39 99 | 60 | 2-Fluoro-6-(trifluoromethyl)pyridine | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 39 99 | 65 | Acetamiprid (ISO) | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2933 39 99 | 75 | Picolinafen (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 49 10 | 10 | Quinmerac (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 49 10 | 20 | 3-Hydroxy-2-methylquinoline-4-carboxylic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 49 90 | 50 | Methyl 2-[(*S*)-3-{(*E*)-3-[2-(7-chloro-2-quinolyl)vinyl]phenyl}-3-hydroxypropyl] benzoate monohydrate | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 49 90 | 60 | 5,6,7,8-Tetrahydroquinoline | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 49 90 | 70 | Quinolin-8-ol | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 52 00 | 10 | Malonylurea (barbituric acid) | 0 % | 1.1.2010-31.12.2011 |
| ex 2933 59 95 | 15 | (2*R*)-4-Oxo-4-[3-(trifluoromethyl)-5,6-dihydro[1,2,4]triazolo[4,3-*a*]pyrazin-7(8*H*)-yl]-1-(2,4,5-trifluorophenyl)butyl-2-ammonium phosphate monohydrate | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 59 95 | 20 | 2,4-Diamino-6-chloropyrimidine | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 59 95 | 25 | 2,5-Diamino-4,6-dihydroxypyrimidine monohydrochloride monohydrate | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 59 95 | 30 | Mepanipyrim (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 59 95 | 35 | 4-Amino-2,6-dichloropyrimidine | 0 % | 1.1.2010-31.12.2011 |
| ex 2933 59 95 | 40 | Guanine | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 59 95 | 60 | 2,6-Dichloro-4,8-dipiperidinopyrimido[5,4-*d*]pyrimidine | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 59 95 | 70 | *N*-(4-Ethyl-2,3-dioxopiperazin-1-ylcarbonyl)-D-2-phenylglycine | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 69 80 | 20 | 1,3,5-Tris[(3,5-di-*tert*-butyl-4-hydroxyphenyl)methyl]-1,3,5-triazine-2,4,6(1*H*,3*H*,5*H*)-trione | 0 % | 1.1.2010-31.12.2013 |
| *ex 2933 69 80 | 30 | 1,3,5-Tris[3-(dimethylamino)propyl]hexahydro-1,3,5-triazine | 0 % | 1.1.2010-31.12.2014 |
| ex 2933 69 80 | 50 | 1,3,5-Tris(2,3-dibromopropyl)-1,3,5-triazinane-2,4,6-trione | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 69 80 | 80 | Tris(2-hydroxyethyl)-1,3,5-triazinetrione | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 79 00 | 10 | Ezetimibe (INN) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 79 00 | 30 | 5-Vinyl-2-pyrrolidone | 0 % | 1.1.2010-31.12.2012 |
| ex 2933 79 00 | 40 | 3,3-Pentamethylene-4-butyrolactam | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 79 00 | 50 | 6-Bromo-3-methyl-3H-dibenz(f,ij)isoquinoline-2,7-dione | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 10 | 2-(2*H*-Benzotriazol-2-yl)-4,6-di-*tert*-butylphenol | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2933 99 80 | 15 | 2-(2*H*-Benzotriazol-2-yl)-4,6-di-*tert*-pentylphenol | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 20 | 2-(2*H*-Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 25 | 6,6′-Di-2*H*-benzotriazol-2-yl-4,4′-bis(1,1,3,3-tetramethylbutyl)-2,2′-methylenediphenol | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 30 | Quizalofop-P-ethyl (ISO) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2933 99 80 | 35 | 1,3,3-Trimethyl-2-methyleneindoline | 0 % | 1.1.2010-31.12.2014 |
| ex 2933 99 80 | 40 | *trans*-4-Hydroxy-L-proline | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 45 | Maleic hydrazide (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 50 | Metconazole (ISO) | 3,2 % | 1.1.2010-31.12.2013 |
| *ex 2933 99 80 | 55 | Pyridaben (ISO) | 0 % | 1.1.2010-31.12.2014 |
| ex 2933 99 80 | 60 | 1,3-Bis(3-isocyanatomethylphenyl)-1,3-diazetidine-2,4-dione (dimeric 2,4-toluene diisocyanate) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 65 | Candesartan cilexetil (INNM) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 69 | [(3R)-4-(4-chlorobenzyl)-7-fluoro-5-(methylsulphonyl)-1,2,3,4-tetrahydro-cyclopenta[*b*]indole-3-yl]acetic acid | 0 % | 1.1.2010-31.12.2011 |
| ex 2933 99 80 | 70 | 6,7-Dihydro-5*H*-cyclopenta[*b*]pyridine | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 71 | 10-methoxyiminostilbene | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 72 | 1,4,7-Trimethyl-1,4,7-Triazacyclononane | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 73 | 5-(acetoacetylamino)benzimidazolone | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 74 | Imidazo[1,2-b] pyridazine-hydrochloride | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 76 | Manganese(2+), bis(octahydro-1,4,7-trimethyl-1H-1,4,7-triazonine-N1,N4,N7)tri-μ-oxodi-, acetate (1:2) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 77 | Manganese(2+), bis(octahydro-1,4,7-trimethyl-1H-1,4,7-triazonine-N1,N4,N7)tri-μ-oxodi-, sulphate (1:1) | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 78 | 3-Amino-3-azabicyclo (3.3.0) octane hydrochloride | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 81 | 1,2,3-Benzotriazole | 0 % | 1.1.2010-31.12.2011 |
| ex 2933 99 80 | 82 | Tolytriazol | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 88 | 2,6-Dichloroquinoxaline | 0 % | 1.1.2010-31.12.2013 |
| ex 2933 99 80 | 89 | Carbendazim (ISO) | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 2934 10 00 | 10 | Hexythiazox (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 10 00 | 20 | 2-(4-Methylthiazol-5-yl)ethanol | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 10 00 | 40 | (Z)-2-(2-tert-butoxycarbonylaminothiazol-4-yl)-2-pentenoic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 10 00 | 50 | 2-(2-Formylaminothiazol-4-yl)acetic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 20 80 | 10 | 4-Chloro-1,3-benzothiazol-2(3*H*)-one | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 20 80 | 40 | 1,2-Benzisothiazol-3(2H)-one (Benzisothiazolinone (BIT)) | 0 % | 1.1.2010-31.12.2012 |
| ex 2934 20 80 | 50 | S-(1,3-Benzothiazol-2-yl)-(Z)-2-(2-aminothiazol-4-yl)-2-(acetyloxyimino)thioacetate | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 99 90 | 15 | Carboxin (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 99 90 | 35 | Dimethenamide (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 99 90 | 45 | Tris(2,3-epoxypropyl)-1,3,5-triazinanetrione | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 99 90 | 55 | Olmesartan medoxomil (INN) | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 99 90 | 60 | DL-Homocysteine thiolactone hydrochloride | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 99 90 | 65 | Methyl 3-aminothiophene-2-carboxylate | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 99 90 | 66 | Tetrahydrothiophene-1,1-dioxide | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 99 90 | 72 | 1-[3-(5-Nitro-2-furyl)allylideneamino]imidazolidine-2,4-dione | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 99 90 | 74 | 2-Isopropylthioxanthone | 0 % | 1.1.2010-31.12.2012 |
| ex 2934 99 90 | 75 | (4*R*-*cis*)-1,1-Dimethylethyl-6-[2[2-(4-fluorophenyl)-5-(1-isopropyl)-3-phenyl-4-[(phenylamino)carbonyl]-1*H*-pyrrol-1-yl]ethyl]-2,2-dimethyl-1,3-dioxane-4-acetate | 0 % | 1.1.2010-31.12.2011 |
| ex 2934 99 90<br>ex 3204 20 00 | 76<br>10 | 2,5-Thiophenediylbis(5-*tert*-butyl-1,3-benzoxazole) | 0 % | 1.1.2010-31.12.2011 |
| ex 2934 99 90 | 77 | Potassium 5-methyl-1,3,4-oxadiazole-2-carboxylate | 0 % | 1.1.2010-31.12.2011 |
| ex 2934 99 90 | 78 | 1,2,4-Thiadiazole-3-acetic acid 5-[(ethoxycarbonyl)amino]-methyl ester | 0 % | 1.1.2010-31.12.2012 |
| ex 2934 99 90 | 79 | Thiophen-2-ethanol | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 99 90 | 81 | 2-(5-Amino-1,2,4-thiadiazol-3-yl)-(Z)-2-methoxyiminoacetic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 2934 99 90 | 82 | 2-Methyl-1-[4-(methylthio)phenyl]-2-morpholinopropan-1-one | 0 % | 1.1.2010-31.12.2013 |
| *ex 2934 99 90 | 83 | Flumioxazin (ISO) of a purity by weight of 96 % or more | 0 % | 1.1.2010-31.12.2014 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 2934 99 90 | 84 | Etoxazole (ISO) of a purity by weight of 94,8 % or more | 0 % | 1.1.2010-31.12.2014 |
| ex 2935 00 90 | 15 | Flupyrsulfuron-methyl-sodium (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2935 00 90 | 20 | Toluenesulphonamides | 0 % | 1.1.2010-31.12.2013 |
| ex 2935 00 90 | 25 | Triflusulfuron-methyl (ISO) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2935 00 90 | 30 | Mixture of isomers consisting of *N*-ethyltoluene-2-sulphonamide and *N*-ethyltoluene-4-sulphonamide | 0 % | 1.1.2010-31.12.2014 |
| ex 2935 00 90 | 35 | Chlorsulfuron (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2935 00 90 | 45 | Rimsulfuron (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2935 00 90 | 50 | 4,4′-Oxydi(benzenesulphonohydrazide) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2935 00 90 | 53 | 2,4-Dichloro-5-sulphamoylbenzoic acid | 0 % | 1.1.2010-31.12.2014 |
| ex 2935 00 90 | 55 | Thifensulfuron-methyl (ISO) | 0 % | 1.1.2010-31.12.2013 |
| *ex 2935 00 90 | 63 | Nicosulphuron (ISO), of a purity by weight of 91 % or more | 0 % | 1.1.2010-31.12.2014 |
| ex 2935 00 90 | 65 | Tribenuron-methyl (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2935 00 90 | 75 | Metsulfuron-methyl (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 2935 00 90 | 76 | 4-Toluenesulphonyl urea | 0 % | 1.1.2010-31.12.2011 |
| ex 2935 00 90 | 81 | 4-Amino-*N*-(4-aminophenyl)benzenesulphonamide | 0 % | 1.1.2010-31.12.2013 |
| ex 2935 00 90 | 82 | N-(5,7-Dimethoxy[1,2,4]triazolo[1,5-a]pyrimidin-2-yl)-2-methoxy-4-(trifluoromethyl)pyridine-3-sulphonamide | 0 % | 1.1.2010-31.12.2013 |
| ex 2935 00 90 | 83 | 3-amino-N,N-diethyl-4-methoxybenzenesulphonamide | 0 % | 1.1.2010-31.12.2013 |
| ex 2935 00 90 | 85 | N-[4-(Isopropylaminoacetyl)phenyl]methanesulphonamide hydrochloride | 0 % | 1.1.2010-31.12.2013 |
| ex 2935 00 90 | 86 | 4-(*m*-Tolylamino)pyridine-3-sulphonamide | 0 % | 1.1.2010-31.12.2013 |
| ex 2935 00 90 | 88 | N-(2-(4-Amino-N-ethyl-m-toluidino)ethyl)methanesulphonamide sesquisulphate monohydrate | 0 % | 1.1.2010-31.12.2013 |
| ex 2935 00 90 | 89 | 3-(3-Bromo-6-fluoro-2-methylindol-1-ylsulphonyl)-*N*,*N*-dimethyl-1,2,4-triazol-1-sulphonamide | 0 % | 1.1.2010-31.12.2011 |
| ex 2938 90 90 | 10 | Hesperidin | 0 % | 1.1.2010-31.12.2013 |
| 3201 20 00 | | Wattle extract | 0 % | 1.1.2010-31.12.2013 |
| ex 3201 90 90 | 20 | Tanning extracts derived from gambier and myrobalan fruits | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3204 13 00 | 10 | C.I. Basic Red 1 dye | 0 % | 1.1.2010-31.12.2011 |
| ex 3204 15 00 | 10 | Dye C.I. Vat Orange 7 (C.I. Pigment Orange 43) | 0 % | 1.1.2010-31.12.2012 |
| ex 3204 15 00 | 60 | Dyestuff C.I. Vat Blue 4 | 0 % | 1.1.2010-31.12.2013 |
| ex 3204 17 00 | 10 | Dye C.I. Pigment Yellow 81 | 0 % | 1.1.2010-31.12.2013 |
| ex 3204 17 00 | 30 | Dye C.I. Pigment Yellow 97 | 0 % | 1.1.2010-31.12.2012 |
| *ex 3204 17 00 | 40 | Dye C.I pigment yellow 120 | 0 % | 1.1.2010-31.12.2014 |
| *ex 3204 17 00 | 50 | Dye C.I pigment yellow 180 | 0 % | 1.1.2010-31.12.2014 |
| *ex 3204 19 00 | 11 | Photochromic dye, 3-(4-butoxyphenyl-6,7-dimethoxy-3-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromene-11-carbonitrile | 0 % | 1.1.2010-31.12.2014 |
| ex 3204 19 00 | 15 | 4-{4-[3-(4-Methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo [*h*]indeno[2,1-*f*]chromen-3-yl]phenyl}morpholine | 0 % | 1.1.2010-31.12.2013 |
| *ex 3204 19 00 | 21 | Photochromic dye, 4-(3-(4-butoxyphenyl)-6-methoxy-3-(4-methoxyphenyl)-13,13-dimethyl-11-(trifluoromethyl)-3,13-dihydrobenzo[*h*] indeno[2,1-*f*]chromen-7-yl)morpholine | 0 % | 1.1.2010-31.12.2014 |
| ex 3204 19 00 | 25 | Cyclohexyl 8-methyl-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate | 0 % | 1.1.2010-31.12.2013 |
| *ex 3204 19 00 | 31 | Photochromic dye, *N*-hexyl-6,7-dimethoxy-3,3-bis(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[*h*]indeno [2,1-*f*]chromene-11-carboxamide | 0 % | 1.1.2010-31.12.2014 |
| *ex 3204 19 00 | 41 | Photochromic dye, 4,4'-(13,13-dimethyl-3,13-dihydrobenzo[*h*]indeno [2,1-*f*]chromene-3,3-diyl)diphenol | 0 % | 1.1.2010-31.12.2014 |
| *ex 3204 19 00 | 51 | Photochromic dye, 4-(4-(6,11-difluoro-13,13-dimethyl-3-phenyl-3,13-dihydrobenzo[*h*]indeno[2,1-*f* ]chromen-3-yl)phenyl)morpholine | 0 % | 1.1.2010-31.12.2014 |
| *ex 3204 19 00 | 61 | Photochromic dye, 3-(4-butoxyphenyl)-6,7-dimethoxy-3-(4-methoxyphenyl)-13,13-dimethyl-11-(trifluoromethyl)-3,13-dihydrobenzo[*h*] indeno[2,1-*f* ]chromene | 0 % | 1.1.2010-31.12.2014 |
| ex 3204 19 00 | 65 | 6-Methoxy-7-morpholino-13-ethyl-13-methoxy-3,3-bis-(4-methoxyphenyl)-3,13-dihydrobenzo[h]indeno[2,1-f]chromene | 0 % | 1.1.2010-31.12.2013 |
| ex 3204 19 00 | 70 | Dye C.I. Solvent Red 49 | 0 % | 1.1.2010-31.12.2013 |
| ex 3204 19 00 | 75 | 6,7-Dimethoxy-13-ethyl-13-methoxy-3,3-bis-(4-methoxyphenyl)-3,13-dihydrobenzo[h]indeno[2,1-f]chromene | 0 % | 1.1.2010-31.12.2013 |
| ex 3204 19 00 | 80 | (R) and (S) isomers of 6,7-Dimethoxy-13-ethyl-13-[2-(2-methoxyethoxy)-ethoxy]-3-(4-methoxyphenyl)-3-(4-fluorophenyl)-3,13-dihydrobenzo[h] indeno[2,1-f]chromene | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3204 19 00 | 81 | 6,11-Difluoro-3,3-di-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[*h*]indeno[2,1-f]chromene | 0 % | 1.1.2010-31.12.2013 |
| ex 3204 19 00 | 82 | 3-(4-Fluorophenyl)-3-(4-piperidinophenyl)-13,13-dimethyl-3,13-dihydrobenzo[*h*]indeno[2,1-f]chromene | 0 % | 1.1.2010-31.12.2013 |
| ex 3204 19 00 | 83 | 6,7-Dimethoxy-11-cyano-3,3-di-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[*h*]indeno[2,1-f]chromene | 0 % | 1.1.2010-31.12.2013 |
| ex 3205 00 00 | 10 | Aluminium lakes prepared from dyes for use in the manufacture of pigments for the pharmaceutical industry (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3206 11 00 | 10 | Titanium dioxide coated with isopropoxytitanium triisostearate, containing by weight 1,5 % or more but not more than 2,5 % of isopropoxytitanium triisostearate | 0 % | 1.1.2010-31.12.2013 |
| ex 3206 42 00 | 10 | Lithopone | 0 % | 1.1.2010-31.12.2013 |
| 3206 50 00 | | Inorganic products of a kind used as luminophores | 0 % | 1.1.2010-31.12.2013 |
| ex 3207 30 00 | 10 | Preparation containing:<br>— not more than 85 % by weight of silver,<br>— not less than 2 % by weight of palladium,<br>— barium titanate,<br>— terpineol, and<br>— ethyl cellulose,<br>used for screen printing in the manufacture of multilayer ceramic capacitors (1) | 0 % | 1.1.2010-31.12.2013 |
| *ex 3207 40 85 | 20 | Glass flakes coated with silver, of an average diameter of 40 (± 10) µm | 0 % | 1.1.2010-31.12.2013 |
| *ex 3207 40 85 | 30 | Glass frit, for use in the manufacture of cathode-ray tubes (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3208 10 90<br>ex 3707 90 90 | 10<br>60 | Anti-reflection coating, consisting of an ester based polymer modified with a chromophore group, in the form of a solution of either 2-methoxy-1-propanol, 2-methoxy-1-methylethyl acetate or methyl-2-hydroxyisobutyrate, containing by weight not more than 10 % of polymer | 0 % | 1.1.2010-31.12.2013 |
| ex 3208 20 10 | 10 | Copolymer of *N*-vinylcaprolactam, *N*-vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate, in the form of a solution in ethanol containing by weight 34 % or more but not more than 40 % of copolymer | 0 % | 1.1.2010-31.12.2013 |
| ex 3208 20 10 | 20 | Immersion topcoat solution containing by weight 2 % or more but not more than 15 % of acrylate-methacrylate-alkenesulphonate-copolymers with fluorinated side chains, in a solution of n-butanol and/or 4-methyl-2-pentanol and/or diisoamylether | 0 % | 1.1.2010-31.12.2013 |
| ex 3208 20 10 | 40 | Poly(1H,1H-heptafluorobutyl methacrylate) dissolved in a mixture of methyl perfluorobutyl ether and methyl perfluoroisobutyl ether | 0 % | 1.1.2010-31.12.2011 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3208 90 19 | 10 | Copolymer of maleic acid and methyl vinyl ether, monoesterified with ethyl and/or isopropyl and/or butyl groups, in the form of a solution in ethanol, ethanol and butanol, isopropanol or isopropanol and butanol | 0 % | 1.1.2010-31.12.2013 |
| ex 3208 90 19<br>ex 3902 90 90 | 15<br>94 | Modified, chlorinated polyolefins, whether or not in a solution or dispersion | 0 % | 1.1.2010-31.12.2013 |
| ex 3208 90 19 | 40 | Polymer of methylsiloxane, in the form of a solution in a mixture of acetone, butanol, ethanol and isopropanol, containing by weight 5 % or more but not more than 11 % of polymer of methylsiloxane | 0 % | 1.1.2010-31.12.2013 |
| ex 3208 90 19 | 50 | Solution containing by weight:<br>— (65 ± 10) % of γ-butyrolactone,<br>— (30 ± 10) % of polyamide resin,<br>— (3,5 ± 1,5) % of naphthoquinone ester derivative and<br>— (1,5 ± 0,5) % of arylsilicic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 3208 90 19 | 60 | Copolymer of hydroxystyrene and either styrene or alkoxystyrene or both, dissolved in ethyl lactate | 0 % | 1.1.2010-31.12.2011 |
| ex 3208 90 19 | 75 | Acenaphthalene copolymer in ethyl lactate solution | 0 % | 1.1.2010-31.12.2012 |
| ex 3208 90 19 | 85 | Mixture containing by weight:<br>— 30~45 % Polyamide resin;<br>— 2~10 % Diazonaphthoquinone;<br>— 50~65 % γ-Butyrolactone. | 0 % | 1.1.2010-31.12.2013 |
| ex 3208 90 91 | 10 | Preparation on the basis of polyhydroxyamide containing at least naphthoquinone ester derivate or tosylate dissolved in γ-butyrolactone and/or 2-methoxy-1-methylethyl acetate | 0 % | 1.1.2010-31.12.2012 |
| ex 3208 90 99 | 10 | Solution based on chemically modified natural polymers, containing two or more of the following dyes:<br>— methyl 8'-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1*H*-indole-2,3'-naphtho[2,1-*b*][1,4]oxazine]-9'-carboxylate,<br>— methyl 6-(isobutyryloxy)-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate,<br>— 13-isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromen-13-ol,<br>— ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate,<br>— 13-ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo[*h*]indeno[2,1-*f*]chromen-13-ol | 0 % | 1.1.2010-31.12.2013 |
| ex 3208 90 99 | 20 | Solution based on chemically modified natural polymers, containing two or more of the following dyes:<br>— 4-[4-(13,13-dimethyl-3-phenyl-3,13-dihydrobenzo [*h*]indeno[2,1-*f*]chromen-3-yl)phenyl]morpholine, | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| | | — 4-{4-[3-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo [*h*]indeno[2,1-*f*]chromen-3-yl]phenyl}morpholine,<br>— cyclohexyl 8-methyl-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate,<br>— ethoxycarbonylmethyl 6-acetoxy-2,2-diphenyl-2*H*-benzo[*h*]chromene-5-carboxylate,<br>— 2-pentyl-7,7-diphenylbenzo[*h*]chromeno[6,5-*d*]-1,3-dioxin-4(7*H*)-one,<br>— 13-butyl-13-ethoxy-6,11-dimethoxy-3,3-bis(4-methoxyphenyl)-3,13-dihydrobenzo [*h*]indeno[2,1-*f*]chromene,<br>— 3-(4-methoxyphenyl)-13,13-dimethyl-3-phenyl-3,13-dihydrobenzo [*h*]indeno[2,1-*f*]chromene,<br>— 6,7-dimethoxy-3,3-bis(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo [*h*]indeno[2,1-*f*]chromene | | |
| ex 3215 11 00<br>ex 3215 19 00 | 10<br>10 | Printing ink, liquid, consisting of a dispersion of a vinyl acrylate copolymer and colour pigments in isoparaffins, containing by weight not more than 13 % of vinyl acrylate copolymer and colour pigments | 0 % | 1.1.2010-31.12.2013 |
| *ex 3215 90 00 | 10 | Ink formulation, for use in the manufacture of ink-jet cartridges (1) | 0 % | 1.1.2010-31.12.2013 |
| *ex 3215 90 00 | 20 | Heat sensitive ink fixed on a plastic film | 0 % | 1.1.2010-31.12.2013 |
| *ex 3215 90 00 | 30 | Ink, containing by weight 5 % or more, but not more than 10 % of amorphous silicon dioxide, filled into disposable cartridges, for use in the marking of integrated circuits (1) | 0 % | 1.1.2010-31.12.2013 |
| 3301 12 10 | | Essential oil of orange, not deterpenated | 0 % | 1.1.2010-31.12.2013 |
| ex 3402 13 00 | 10 | Vinyl copolymer surface active agent based on polypropylene glycol | 0 % | 1.1.2010-31.12.2013 |
| ex 3402 13 00 | 20 | Surfactant containing 1,4-dimethyl-1,4-*bis*(2-methylpropyl)-2-butyne-1,4-diyl ether, polymerized with oxirane, methyl terminated | 0 % | 1.1.2010-31.12.2012 |
| ex 3402 90 10 | 20 | Mixture of docusate sodium (INN) and sodium benzoate | 0 % | 1.1.2010-31.12.2013 |
| ex 3402 90 10 | 40 | Amphoteric fluorinated surfactant in a mixture of water and ethanol, containing by weight 25 % or more but not more than 30 % surfactant | 0 % | 1.1.2010-31.12.2013 |
| *ex 3402 90 10 | 60 | Surface-active preparation, containing 2-ethylhexyloxymethyl oxirane | 0 % | 1.1.2010-31.12.2014 |
| *ex 3402 90 10 | 70 | Surface-active preparation, containing ethoxylated 2,4,7,9-tetramethyl-5-decyne-4,7-diol | 0 % | 1.1.2010-31.12.2014 |
| *ex 3403 99 00 | 10 | Cutting-fluid preparation based on an aqueous solution of synthetic polypeptides | 0 % | 1.1.2010-31.12.2013 |
| *ex 3504 00 90 | 10 | Avidin | 0 % | 1.1.2010-31.12.2014 |
| ex 3505 10 50 | 20 | *O*-(2-Hydroxyethyl)-derivative of hydrolysed maize starch | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3506 91 00 | 10 | Adhesive based on an aqueous dispersion of a mixture of dimerised rosin and a copolymer of ethylene and vinyl acetate (EVA) | 0 % | 1.1.2010-31.12.2013 |
| ex 3506 91 00 | 30 | Two component microencapsulated epoxy adhesive dispersed in a solvent | 0 % | 1.1.2010-31.12.2013 |
| *ex 3506 91 00 | 40 | Acrylic pressure sensitive adhesive with a thickness of 0,076 mm or more but not more than 0,127 mm, put up in rolls of a width of 45,7 cm or more but not more than 132 cm supplied on a release liner with an initial peel adhesion release value of not less than 15 N/25 mm (measured according to ASTM D3330) | 0 % | 1.1.2010-31.12.2014 |
| ex 3701 30 00 | 10 | Relief printing plate, of a kind used for printing on newsprint, consisting of a metal substrate coated with a photopolymer layer of a thickness of 0,2 mm or more but not more than 0,8 mm, not covered with a release film, of a total thickness of not more than 1 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 3701 99 00 | 10 | Plate of quartz or of glass, covered with a film of chromium and coated with a photosensitive or electron-sensitive resin, for the manufacture of masks for the goods of heading No 8541 or 8542 ([1]) | 0 % | 1.1.2010-31.12.2013 |
| *ex 3705 90 90 | 10 | Photomasks for photographically transferring circuit diagram patterns onto semiconductor wafers | 0 % | 1.1.2010-31.12.2014 |
| ex 3707 10 00 | 10 | Photosensitive emulsion for the sensitization of silicon discs ([1]) | 0 % | 1.1.2010-31.12.2013 |
| ex 3707 10 00 | 15 | Sensitising emulsion, consisting of diazooxonaphthalenesulphonic acid ester and phenolic resins, containing by weight not more than 12 % of diazooxonaphtalenesulphonic acid ester, in 2-methoxy-1-methylethyl acetate or ethyl lactate | 0 % | 1.1.2010-31.12.2013 |
| ex 3707 10 00 | 25 | Sensitising emulsion containing:<br>— phenolic or acrylic resins<br>— a maximum 2 % by weight of light sensitive acid precursor,<br>in a solution containing 2-methoxy-1-methylethyl acetate or ethyl lactate | 0 % | 1.1.2010-31.12.2013 |
| ex 3707 10 00 | 30 | Preparation based on photosensitive acrylic containing polymer, containing colour pigments, 2-methoxy-1-methylethylacetate and cyclo-hexanone and whether or not containing ethyl-3-ethoxypropionate | 0 % | 1.1.2010-31.12.2013 |
| ex 3707 10 00 | 35 | Sensitising emulsion, consisting of acrylate and/or methacrylate polymers, containing by weight not more than 7 % photosensitive acid precursors dissolved in an organic solvent containing at least 2-methoxy-1-methylethyl acetate | 0 % | 1.1.2010-31.12.2011 |
| ex 3707 10 00 | 40 | Sensitising emulsion, containing:<br>— not more than 10 % by weight of naphthoquinonediazide esters,<br>— 2 % or more but not more than 20 % by weight of copolymers of hydroxystyrene<br>— not more than 7 % by weight of epoxy-containing derivatives<br>dissolved in 1-ethoxy-2-propyl acetate and/or ethyl lactate | 0 % | 1.1.2010-31.12.2011 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 3707 10 00 | 45 | Photosensitive emulsion consisting of cyclized polyisoprene containing:<br>— 55 % or more but not more than 75 % by weight of xylene and<br>— 12 % or more but not more than 18 % by weight of ethylbenzene | 0 % | 1.1.2010-31.12.2014 |
| *ex 3707 10 00 | 50 | Photosensitive emulsion containing by weight:<br>— 20 % or more but not more than 45 % of copolymers of acrylates and/or methacrylates and hydroxystyrene derivatives,<br>— 25 % or more but not more than 50 % of organic solvent containing at least ethyl lactate and/or propylene glycolmethylether acetate,<br>— 5 % or more but not more then 30 % of acrylates,<br>— not more than 12 % of a photoinitiator | 0 % | 1.1.2010-31.12.2014 |
| *ex 3707 90 20 | 10 | Toner, in the form of powder, consisting of a copolymer of styrene and butyl acrylate and either magnetite or carbon black, for use as a developer in the manufacture of cartridges for facsimile machines or computer printers (1) | 0 % | 1.1.2010-31.12.2013 |
| *ex 3707 90 20 | 20 | Toner, based on a polyol resin, in the form of powder | 0 % | 1.1.2010-31.12.2013 |
| *ex 3707 90 20 | 40 | Polyester resin based toner, manufactured by a polymerisation process, for use as a developer in the manufacture of computer printer and copier cartridges (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3707 90 90 | 10 | Anti-reflection coating, consisting of a modified methacrylic polymer, containing by weight not more than 10 % of polymer, in the form of a solution in 2-methoxy-1-methylethyl acetate and 1-methoxypropan-2-ol | 0 % | 1.1.2010-31.12.2013 |
| ex 3707 90 90<br><br>ex 3824 90 97 | 30<br><br>91 | Anti-reflection coating, in the form of an aqueous solution, containing by weight:<br>— not more than 2 % of perhalogenated sulphonic acid derivatives,<br>— not more than 1 % of a vinyl polymer | 0 % | 1.1.2010-31.12.2013 |
| ex 3801 20 90 | 10 | Colloidal graphite in suspension in water, for use as internal coating in colour cathode-ray tubes (1) | 0 % | 1.1.2010-31.12.2013 |
| 3805 90 10 | | Pine oil | 1,7 % | 1.1.2010-31.12.2013 |
| ex 3808 91 90 | 10 | Indoxacarb (ISO) and its (*R*) isomer, fixed on a support of silicon dioxide | 0 % | 1.1.2010-31.12.2013 |
| *ex 3808 91 90 | 30 | Preparation containing endospores or spores and protein crystals derived from either:<br>— *Bacillus thuringiensis Berliner* subsp. *aizawai* and *kurstaki* or,<br>— *Bacillus thuringiensis* subsp. *kurstaki* or,<br>— *Bacillus thuringiensis* subsp. *israelensis* or,<br>— *Bacillus thuringiensis* subsp. *aizawai* or,<br>— *Bacillus thuringiensis* subsp. *tenebrionis* | 0 % | 1.1.2010-31.12.2014 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3808 91 90 | 40 | Spinosad (ISO) | 0 % | 1.1.2010-31.12.2013 |
| ex 3808 91 90 | 50 | *Spodoptera exigua* nuclear polyhedrosis virus (SeNPV) in an aqueous glycerol suspension | 0 % | 1.1.2010-31.12.2013 |
| ex 3808 92 90 | 10 | Fungicide in the form of a powder, containing by weight 65 % or more but not more than 75 % of hymexazole (ISO), not put up for retail sale | 0 % | 1.1.2010-31.12.2013 |
| ex 3808 92 90 | 30 | Preparation consisting of a suspension of pyrithione zinc (INN) in water, containing by weight 24 % or more but not more than 26 % of pyrithione zinc (INN) | 0 % | 1.1.2010-31.12.2013 |
| ex 3808 93 15 | 10 | Preparation based on a concentrate containing by weight 45 % or more but not more than 55 % of the active herbicidal ingredient Penoxsulam as an aqueous suspension | 0 % | 1.1.2010-31.12.2012 |
| ex 3808 93 27 | 20 | Organic solution of Clethodim (ISO), with a Clethodim content of 37 % (± 2 %) or 70 % (± 2 %) by weight | 0 % | 1.1.2010-31.12.2012 |
| ex 3809 91 00 | 10 | Mixture of 5-ethyl-2-methyl-2-oxo-1,3,2$\lambda^5$-dioxaphosphoran-5-ylmethyl methyl methylphosphonate and bis(5-ethyl-2-methyl-2-oxo-1,3,2$\lambda^5$-dioxaphosphoran-5-ylmethyl) methylphosphonate | 0 % | 1.1.2010-31.12.2013 |
| ex 3809 92 00 | 10 | Paper anti-fading agent, consisting of a mixture of magnesium trisilicate and monosodium salt of 2,2′-methylenebis(4,6-di-*tert*-butylphenyl) phosphate | 0 % | 1.1.2010-31.12.2013 |
| *ex 3809 92 00 | 20 | Defoamer, consisting of a mixture of oxydipropanol and 2,5,8,11-tetramethyldodec-6-yn-5,8-diol | 0 % | 1.1.2010-31.12.2014 |
| ex 3810 10 00 | 10 | Soldering paste, consisting of a mixture of metals and resin containing by weight:<br>— 70 % or more, but not more than 90 % of tin<br>— not more than 10 % of one or more metals of silver, copper, bismuth, zinc, or indium<br>for use in the electro technical industry [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3811 19 00 | 10 | Solution of more than 61 % but not more than 63 % by weight of methylcyclopentadienyl manganese tricarbonyl in an aromatic hydrocarbon solvent, containing by weight not more than:<br>— 4,9 % of 1,2,4-trimethyl-benzene,<br>— 4,9 % of naphthalene, and<br>— 0,5 % of 1,3,5-trimethyl-benzene | 0 % | 1.1.2010-31.12.2013 |
| ex 3811 21 00 | 10 | Salts of dinonylnaphthalenesulphonic acid, in the form of a solution in mineral oils | 0 % | 1.1.2010-31.12.2013 |
| ex 3811 21 00 | 20 | Additives for lubricating oils, based on complex organic molybdenum compounds, in the form of a solution in mineral oil | 0 % | 1.1.2010-31.12.2013 |
| ex 3811 90 00 | 10 | Dinonylnaphthylsulphonic acid salt, in a mineral oil solution | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3811 90 00 | 20 | Corrosion inhibitor, containing reaction products of fatty acids and tall oil with formaldehyde and (Z)-*N*-9-octadecenyl-1,3-propanediamine | 0 % | 1.1.2010-31.12.2011 |
| ex 3812 30 80 | 20 | Mixture containing predominantly bis(2,2,6,6-tetramethyl-1-octyloxy-4-piperidyl) sebacate | 0 % | 1.1.2010-31.12.2013 |
| ex 3812 30 80 | 30 | Compound stabilisers containing by weight 15 % or more but not more than 40 % of sodium perchlorate and not more than 70 % of 2-(2-methoxyethoxy)ethanol | 0 % | 1.1.2010-31.12.2013 |
| ex 3814 00 90 | 20 | Mixture containing by weight:<br>— 69 % or more but not more than 71 % of 1-methoxypropan-2-ol,<br>— 29 % or more but not more than 31 % of 2-methoxy-1-methylethyl acetate | 0 % | 1.1.2010-31.12.2013 |
| ex 3814 00 90 | 40 | Azeotrope mixtures containing isomers of nonafluorobutyl methyl ether and/or nonafluorobutyl ethyl ether | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 12 00 | 10 | Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not more than 10 mm, consisting of silver on an aluminium oxide support and containing by weight 8 % or more but not more than 40 % of silver | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 19 90 | 10 | Catalyst, consisting of chromium trioxide or dichromium trioxide fixed on a support of silicon dioxide, of a pore volume, as determined by the nitrogen absorption method, of 2 $cm^3/g$ or more | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 19 90 | 15 | Catalyst, in the form of a powder, consisting of a mixture of metal oxides fixed on a support of silicon dioxide, containing by weight 20 % or more but not more than 40 % of molybdenum, bismuth and iron evaluated together, for use in the manufacture of acrylonitrile [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 19 90 | 30 | Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 19 90 | 40 | Catalyst, in the form of spheres of a diameter of 4,2 mm or more but not more than 9 mm, consisting of a mixture of metals oxides containing predominantly oxides of molybdenum, vanadium and copper, on a support of silicon dioxide and/or aluminium oxide, for use in the manufacture of acrylic acid [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 19 90 | 41 | Catalysts in the form of tablets, consisting of 60 % (± 2 %) by weight of copper oxide on a support of aluminium oxide | 0 % | 1.1.2010-31.12.2012 |
| ex 3815 19 90 | 50 | Catalyst consisting of organo-metallic compounds of titanium, magnesium and aluminium on a support of silicon dioxide, in the form of a suspension in tetrahydrofuran | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 19 90 | 60 | Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 19 90 | 65 | Catalyst consisting of phosphoric acid chemically bonded to a support of silicon dioxide | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3815 19 90 | 70 | Catalyst consisting of organo-metallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 19 90 | 75 | Catalyst consisting of organo-metallic compounds of aluminium and chromium, fixed on a support of silicon dioxide | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 19 90 | 80 | Catalyst consisting of organo-metallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 19 90 | 85 | Catalyst consisting of organo-metallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 19 90 | 86 | Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polyolefins [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 90 90 | 16 | Initiator based on dimethylaminopropyl urea | 0 % | 1.1.2010-31.12.2012 |
| ex 3815 90 90 | 20 | Catalyst, in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing by weight:<br>— 20 % or more but not more than 30 % of titanium and<br>— 55 % or more but not more than 72 % of chlorine | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 90 90 | 50 | Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 90 90 | 70 | Catalyst, consisting of a mixture of (2-hydroxypropyl)trimethyl-ammonium formate and dipropylene glycols | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 90 90 | 71 | Catalyst, containing *N*-(2-hydroxypropylammonium)diazabicyclo (2,2,2) octane-2-ethyl hexanoate, dissolved in ethane-1,2-diol | 0 % | 1.1.2010-31.12.2011 |
| ex 3815 90 90 | 77 | Catalyst powder in an aqueous suspension containing by weight:<br>— 1 % or more but not more than 3 % of palladium,<br>— 0,25 % or more but not more than 3 % of lead,<br>— 0,25 % or more but not more than 0,5 % of lead hydroxide,<br>— 5,5 % or more but not more than 10 % of aluminium,<br>— 4 % or more but not more than 10 % of magnesium,<br>— 30 % or more but not more than 50 % of silicon dioxide | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 90 90 | 80 | Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 90 90 | 81 | Catalyst, containing by weight 69 % or more but not more than 79 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 90 90 | 84 | Powder catalyst containing by weight a minimum 96 % of oxides of copper, chromium and iron | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3815 90 90 | 85 | Catalyst based on aluminosilicate (zeolite), for the alkylation of aromatic hydrocarbons, for the transalkylation of alkylaromatic hydrocarbons or for the oligomerization of olefins (1) | 0 % | 1.1.2010-31.12.2012 |
| ex 3815 90 90 | 86 | Catalyst, in the form of rodlets, consisting of an aluminosilicate (zeolite), containing by weight 2 % or more but not more than 3 % of rare-earth metal oxides and less than 1 % of disodium oxide | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 90 90 | 87 | Reaction initiator, consisting of diisopropyl peroxydicarbonate, in the form of a solution in diallyl 2,2′-oxydiethyl dicarbonate | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 90 90 | 88 | Catalyst, consisting of titanium tetrachloride and magnesium chloride, containing by weight on an oil- and hexane-free basis:<br>— 4 % or more but not more than 10 % of titanium and<br>— 10 % or more but not more than 20 % magnesium | 0 % | 1.1.2010-31.12.2013 |
| ex 3815 90 90 | 89 | Rhodococcus rhodocrous J1 bacteria, containing enzymes, suspended in a polyacrylamide gel or in water, for use as a catalyst in the production of acrylamide by the hydration of acrylonitrile (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 3817 00 50 | 10 | Mixture of alkylbenzenes (C14-26) containing by weight:<br>— 35 % or more but not more than 60 % of eicosylbenzene,<br>— 25 % or more but not more than 50 % of docosylbenzene,<br>— 5 % or more but not more than 25 % of tetracosylbenzene | 0 % | 1.1.2010-31.12.2013 |
| ex 3817 00 80 | 10 | Mixture of alkylnaphthalenes, containing by weight:<br>— 88 % or more but not more than 98 % of hexadecylnaphthalene<br>— 2 % or more but not more than 12 % of dihexadecylnaphthalene | 0 % | 1.1.2010-31.12.2013 |
| ex 3817 00 80 | 20 | Mixture of branched alkyl benzenes mainly containing dodecyl benzenes | 0 % | 1.1.2010-31.12.2013 |
| ex 3819 00 00 | 20 | Fire resistant hydraulic fluid based on phosphate ester | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 15 | 10 | Acid aluminosilicate (artificial zeolite of the Y type) in the sodium form, containing by weight not more than 11 % of sodium evaluated as sodium oxide, in the form of rodlets | 0 % | 1.1.2010-31.12.2013 |
| *ex 3824 90 97 | 07 | Film containing oxides of barium or calcium combined with either oxides of titanium or zirconium, in an acrylic binding material | 0 % | 1.1.2010-31.12.2014 |
| ex 3824 90 97 | 09 | Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulphonic acid, either:<br>— on a support of mineral wax, whether or not modified chemically, or<br>— in the form of a solution in an organic solvent | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 10 | Calcined bauxite (refractory grade) | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 12 | Oligomer of tetrafluoroethylene, having one iodoethyl end-group | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3824 90 97 | 13 | Preparations containing not less than 92 % but not more than 96,5 % by weight of 1,3:2,4-*bis*-O-(4-methylbenzylidene)-*D*-glucitol and also containing carboxylic acid derivatives and an alkyl sulphate | 0 % | 1.1.2010-31.12.2011 |
| ex 3824 90 97 | 14 | Calcium phosphonate phenate, dissolved in mineral oil | 0 % | 1.1.2010-31.12.2011 |
| ex 3824 90 97 | 15 | Structured silica alumina phosphate | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 16 | Mixture of bis{4-(3-(3-phenoxycarbonylamino)tolyl)ureido}phenylsulphone, diphenyltoluene-2,4-dicarbamate and 1-[4-(4-aminobenzenesulphonyl)-phenyl]-3-(3-phenoxycarbonylamino-tolyl)-urea | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 17 | Mixture of acetates of 3-butylene-1,2-diol with a content by weight of 65 % or more but not more than 90 % | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 18 | 4-Methylmandelic acid, crude | 0 % | 1.1.2010-31.12.2011 |
| ex 3824 90 97 | 20 | Preparation consisting by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing by weight 7 % or more of tricyclopentadiene, and:<br>— either an aluminium-alkyl compound,<br>— or an organic complex of tungsten<br>— or an organic complex of molybdenum | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 22 | Preparations containing not less than 47 % by weight of 1,3:2,4-*bis*-O-benzylidene-*D*-glucitol | 0 % | 1.1.2010-31.12.2011 |
| ex 3824 90 97 | 25 | Lithium tantalate wafers, undoped | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 29 | Preparation consisting predominantly of γ-butyrolactone and quaternary ammonium salts, for the manufacture of electrolytic capacitors [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 30 | 2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 34 | Mixture of phytosterols in the form of a crystalline waxy powder, containing by weight:<br>— 36 % or more, but not more than 79 % of sitosterols,<br>— 15 % or more, but not more than 34 % of sitostanols,<br>— 4 % or more, but not more than 25 % of campesterols,<br>— 0 % or more, but not more than 14 % of campestanols | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 36 | Preparation based on 2,5,8,11-tetramethyl-6-dodecyn-5,8-diol ethoxylate | 0 % | 1.1.2010-31.12.2012 |
| ex 3824 90 97 | 37 | Liquid crystal mixture for use in the manufacture of displays [1] | 0 % | 1.1.2010-31.12.2012 |
| ex 3824 90 97 | 38 | Alkyl carbonate-based preparation, also containing a UV absorber, for use in the manufacture of spectacle lenses [1] | 0 % | 1.1.2010-31.12.2012 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3824 90 97 | 39 | Mixture containing by weight 40 % or more but not more than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 40 | Azelaic acid of a purity by weight of 75 % or more but not mote than 85 % | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 42 | Mixed metals oxides, in the form of powder, containing by weight:<br>— either 5 % or more of barium, neodymium or magnesium and 15 % or more of titanium,<br>— or 30 % or more of lead and 5 % or more of niobium,<br>for use in the manufacture of dielectric films or for use as dielectric materials in the manufacture of multilayer ceramic capacitors (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 44 | Mixture of phytosterols, not in the form of powder, containing by weight:<br>— 75 % or more of sterols,<br>— not more than 25 % of stanols,<br>for use in the manufacture of stanol/sterol esters (1) | 0 % | 1.1.2010-31.12.2012 |
| ex 3824 90 97 | 45 | Preparations consisting predominantly of ethylene glycol and:<br>— either diethylene glycol, dodecandioic acid and ammonia water,<br>— or N,N-dimethylformamide,<br>— or γ-butyrolactone,<br>— or silicon oxide,<br>— or ammonium hydrogen azelate,<br>— or ammonium hydrogen azelate and silicon oxide,<br>— or dodecandioic acid, ammonia water and silicon oxide,<br>for the manufacture of electrolytic capacitors (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 46 | Carboxylic acid anhydride based hardener for epoxide resin, in liquid form, of a specific weight at 25 °C of 1,15 g/cm$^3$ or more but not more than 1,18 g/cm$^3$ | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 47 | 4-Methoxysalicylaldehyde, dissolved in *N*-methyl pyrrolidone | 0 % | 1.1.2010-31.12.2012 |
| ex 3824 90 97 | 52 | Poly(tetramethylene glycol) bis[(2-benzoyl-phenoxy)acetate] with an average polymer chain length of less than 5 monomer units | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 53 | Poly(ethylene glycol) bis(*p*-dimethyl)aminobenzoate with an average polymer chain length of less than 5 monomer units | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 54 | 2-Hydroxybenzonitrile, in the form of a solution in *N,N*-dimethyl-formamide, containing by weight 45 % or more but not more than 55 % of 2-hydroxybenzonitrile | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 60 | α-Phenoxycarbonyl-ω-phenoxypoly[oxy(2,6-dibromo-1,4-phenylene) isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl] | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3824 90 97 | 63 | Triethylborane, in the form of a solution in tetrahydrofuran | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 64 | Aluminium sodium silicate, in the form of spheres of a diameter of:<br>— either 1,6 mm or more but not more than 3,4 mm,<br>— or 4 mm or more but not more than 6 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 70 | Paste containing by weight 75 % or more, but not more than 85 % of copper, and also containing inorganic oxides, ethyl cellulose and a solvent | 0 % | 1.1.2010-31.12.2012 |
| ex 3824 90 97 | 72 | Solution containing by weight 80 % or more of 2,4,6-trimethylbenzaldehyde in acetone | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 73 | Particles of silicon dioxide on which are covalently bonded organic compounds, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 75 | Poly(tetramethylene glycol) bis(9-oxo-9H-thioxanthen-1-yloxy)acetate with an average polymer chain length of less than 5 monomer units | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 77 | Diethylmethoxyborane, in the form of a solution in tetrahydrofuran | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 78 | Mixture of phytosterols derived from wood and wood based oils (tall oil), in the form of powder with a particle size not more than 300 μm, containing by weight:<br>— 60 % or more, but not more than 80 % of sitosterols,<br>— not more than 15 % of campesterols,<br>— not more than 5 % of stigmasterols,<br>— not more than 15 % of betasitostanols | 0 % | 1.1.2010-31.12.2012 |
| ex 3824 90 97 | 79 | Mixture of 80 % (± 10 %) of 1-[2-(2-aminobutoxy)ethoxy]but-2-ylamine and 20 % (± 10 %) of 1-({[2-(2-aminobutoxy)ethoxy]methyl} propoxy) but-2-ylamine | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 82 | α-(2,4,6-Tribromophenyl)-ω-(2,4,6-tribromophenoxy)poly[oxy(2,6-dibromo-1,4-phenylene)isopropylidene(3,5-dibromo-1,4-phenylene) oxycarbonyl] | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 84 | Reaction product, containing by weight:<br>— 1 % or more but not more than 40 % of molybdenum oxide,<br>— 10 % or more but not more than 50 % of nickel oxide,<br>— 30 % or more but not more than 70 % of tungsten oxide | 0 % | 1.1.2010-31.12.2013 |
| ex 3824 90 97 | 89 | Oligomer of tetrafluoroethylene, having tetrafluoroiodoethyl end-groups | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3824 90 97 | 90 | Hollow spheres of fused aluminosilicate containing 65-80 % amorphous aluminosilicate, with the following characteristics:<br>— a melting point of between 1 600 °C and 1 800 °C,<br>— a density of 0,6-0,8 g/cm$^3$,<br>for use in the manufacture of particle filters in motor vehicles (1) | 0 % | 1.1.2010-31.12.2013 |
| *ex 3824 90 97 | 92 | Preparation, consisting of 2,4,7,9-tetramethyldec-5-yne-4,7-diol and silicon dioxide | 0 % | 1.1.2010-31.12.2014 |
| *ex 3824 90 97 | 95 | Mixture of phytosterols, in the form of flakes and balls, containing by weight 80 % or more of sterols and not more than 4 % of stanols | 0 % | 1.1.2010-31.12.2014 |
| ex 3824 90 97 | 97 | Preparation containing by weight either 10 % or more but not more than 20 % of lithiumfluorophosphate or 5 % or more but not more than 10 % of lithium perchlorate in mixtures of organic solvents | 0 % | 1.1.2010-31.12.2013 |
| ex 3901 10 90 | 20 | Polyethylene, in the form of granules, of a specific gravity of 0,925 (± 0,0015), a melt flow index of 0,3 g/10 min (± 0,05 g/10 min), for the manufacture of blown films of a Haze value not more than 6 % and an elongation at break (MD/TD) of 210/340 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3901 20 90 | 10 | Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, of a specific gravity of 0,945 or more but not more than 0,985, for the manufacture of films for typewriter ribbon or similar ribbon (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3901 20 90 | 20 | Polyethylene, containing by weight 35 % or more but not more than 45 % of mica | 0 % | 1.1.2010-31.12.2013 |
| ex 3901 90 90 | 91 | Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid | 4 % | 1.1.2010-31.12.2013 |
| ex 3901 90 90 | 92 | Chlorosulphonated polyethylene | 0 % | 1.1.2010-31.12.2013 |
| ex 3901 90 90 | 93 | Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticizer in the manufacture of roof sheets (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3901 90 90 | 94 | Mixtures of A-B block copolymer of polystyrene and ethylene-butylene copolymer and A-B-A block copolymer of polystyrene, ethylene-butylene copolymer and polystyrene, containing by weight not more than 35 % of styrene | 0 % | 1.1.2010-31.12.2013 |
| ex 3901 90 90 | 97 | Chlorinated polyethylene, in the form of powder | 0 % | 1.1.2010-31.12.2013 |
| ex 3902 10 00 | 10 | Polypropylene containing no plasticizer and not more than:<br>— 7 mg/kg of aluminium,<br>— 2 mg/kg of iron,<br>— 1 mg/kg of magnesium,<br>— 8 mg/kg of chloride | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3902 10 00 | 20 | Polypropylene, containing no plasticiser,<br>— of a melting point of more than 150 °C (as determined by the ASTM D 3417 method),<br>— of a heat of fusion of 15 J/g or more but not more than 70 J/g,<br>— of an elongation at break of 1 000 % or more (as determined by the ASTM D 638 method),<br>— of a tensile modulus of 69 MPa or more but not more than 379 MPa (as determined by the ASTM D 638 method) | 0 % | 1.1.2010-31.12.2013 |
| ex 3902 10 00 | 30 | Polypropylene, containing not more than 1 mg/kg of aluminium, 0,05 mg/kg of iron, 1 mg/kg of magnesium and 1 mg/kg of chloride, for use in the manufacture of packaging for disposable contact lenses [1] | 0 % | 1.1.2010-31.12.2013 |
| *ex 3902 10 00 | 40 | Polypropylene, containing no plasticizer:<br>— of a tensile strength: of 32-44 MPa (as determined by the ASTM D638 method);<br>— of a flexural strength of 50-66 MPa (as determined by the ASTM D790 method);<br>— of a Melt Flow Rate (MFR) at 230 °C/2,16 kg of 5-15 g/10 min (as determined by the ASTM D1238 method);<br>— with 40 % or more but not more than 80 % by weight of polypropylene,<br>— with 10 % or more but not more than 30 % by weight of glass fibre,<br>— with 10 % or more but not more than 30 % by weight of mica | 0 % | 1.1.2010-31.12.2014 |
| ex 3902 20 00 | 10 | Polyisobutylene, of a number average molecular weight ($M_n$) of 700 or more but not more than 800 | 0 % | 1.1.2010-31.12.2013 |
| ex 3902 20 00 | 20 | Hydrogenated polyisobutene, in liquid form | 0 % | 1.1.2010-31.12.2013 |
| ex 3902 30 00 | 91 | A-B Block copolymer of polystyrene and an ethylene-propylene copolymer, containing by weight 40 % or less of styrene, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 % | 1.1.2010-31.12.2013 |
| ex 3902 90 90 | 52 | Amorphous poly-alpha-olefin copolymer blend of poly(propylene-co-1-butene) and petroleum hydrocarbon resin | 0 % | 1.1.2010-31.12.2013 |
| ex 3902 90 90 | 55 | Thermoplastic elastomer, with an A-B-A block copolymer structure of polystyrene, polyisobutylene and polystyrene containing by weight 10 % or more but not more than 35 % of polystyrene | 0 % | 1.1.2010-31.12.2013 |
| ex 3902 90 90 | 92 | Polymers of 4-methylpent-1-ene | 0 % | 1.1.2010-31.12.2013 |
| ex 3902 90 90 | 93 | Synthetic poly-alpha-olefin having a viscosity of at least $38 \times 10^{-6} m^2 s^{-1}$ (38 centistokes) at 100 °C measured using the ASTM D 445 method | 0 % | 1.1.2010-31.12.2011 |
| ex 3902 90 90 | 98 | Synthetic poly-alpha-olefin with a viscosity at 100 °C (measured according to method ASTM D 445) ranging from 3 centistokes to 9 centistokes and obtained by polymerization of a mixture of dodecene and tetradecene, containing a maximum of 40 % of tetradecene | 0 % | 1.1.2010-31.12.2011 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3903 11 00 | 10 | White expandable polystyrene beads with a thermal conductivity of not more than 0,034 W/mK at a density of 14,0 kg/m$^3$ (± 1,5 kg/m$^3$), containing 50 % recycled material | 0 % | 1.1.2010-31.12.2013 |
| *ex 3903 19 00 | 30 | Crystalline polystyrene with a melting point of 268 °C or more but not more than 272 °C and a setting point of 232 °C or more but not more than 242 °C, whether or not containing additives and filling material | 0 % | 1.1.2010-31.12.2011 |
| ex 3903 90 90 | 35 | Copolymer of α-methylstyrene and styrene, having a softening point of more than 113 °C | 0 % | 1.1.2010-31.12.2013 |
| ex 3903 90 90<br>ex 3911 90 99 | 40<br>50 | Copolymer of styrene with α-methylstyrene and acrylic acid, of a number average molecular weight ($M_n$) of 500 or more but not more than 6 000 | 0 % | 1.1.2010-31.12.2013 |
| ex 3903 90 90 | 65 | Copolymer of styrene, butyl acrylate, butyl methacrylate, methyl methacrylate and acrylic acid, in the form of powder, containing by weight 81 (± 1) % of styrene, 6 (± 1) % of butyl acrylate, 5 (± 1) % of butyl methacrylate, 7 (± 1) % of methyl methacrylate and 1 (± 0,5) % of acrylic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 3903 90 90 | 75 | Copolymer of styrene and vinyl pyrrolidone, containing by weight not more than 1 % of sodium dodecyl sulphate, in the form of an aqueous emulsion, for the manufacture of goods of subheading 3305 20 00 or of hair dyes of subheading 3305 90 90 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3903 90 90 | 80 | Granules of copolymer of styrene and divinylbenzene of a minimum diameter of 150 µm and a maximum diameter of 800 µm and containing by weight:<br>— minimum 65 % styrene,<br>— maximum 25 % divinylbenzene<br>for use in the manufacture of ion exchange resins (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3903 90 90 | 86 | Mixture containing by weight:<br>— 45 % or more but not more than 65 % of polymers of styrene<br>— 35 % or more but not more than 45 % of poly(phenylene ether)<br>— not more than 10 % of other additives | 0 % | 1.1.2010-31.12.2013 |
| *ex 3904 10 00 | 20 | Poly(vinyl chloride) powder, not mixed with any other substances or containing any vinyl acetate monomers, with:<br>— a degree of polymerisation of 1 000 (± 300) monomer units,<br>— a coefficient of heat transmission (K-value) of 60 or more, but not more than 70,<br>— a volatile material content of less than 2,00 % by weight,<br>— a sieve non-passing fraction at a mesh width of 120 µm of not more than 1 % by weight,<br>for use in the manufacture of battery separators<br>(1) | 0 % | 1.1.2010-31.12.2014 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 3904 30 00 | 20 | Copolymer of vinyl chloride with vinyl acetate and maleic acid, containing by weight:<br>— 80,5 % or more but not more than 81,5 % of vinyl chloride,<br>— 16,5 % or more but not more than 17,5 % of vinyl acetate and<br>— 1,5 % or more but not more than 2,5 % of maleic acid,<br>for use in the heat-sealing of plastics onto steel substrate for industrial uses (1) | 0 % | 1.1.2010-31.12.2014 |
| ex 3904 40 00 | 91 | Copolymer of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight:<br>— 87 % or more but not more than 92 % of vinyl chloride,<br>— 2 % or more but not more than 9 % of vinyl acetate and<br>— 1 % or more but not more than 8 % of vinyl alcohol,<br>in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of goods of heading No 3215 or 8523 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3904 40 00 | 93 | Copolymer of vinyl chloride and methyl acrylate, containing by weight 80 (± 1) % of vinyl chloride and 20 (± 1) % of methyl acrylate, in the form of a aqueous emulsion | 0 % | 1.1.2010-31.12.2013 |
| *ex 3904 50 90 | 92 | Vinylidene-chloride methacrylate co-polymer for use in the manufacture of monofilaments<br>(1) | 0 % | 1.1.2010-31.12.2014 |
| ex 3904 61 00 | 10 | Mixture of polytetrafluoroethylene and mica, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 % | 1.1.2010-31.12.2013 |
| ex 3904 61 00 | 20 | Copolymer of tetrafluoroethylene and trifluoro(heptafluoro-propoxy)ethylene, containing 3,2 % or more but not more than 4,6 % by weight of trifluoro(heptafluoropropoxy)ethylene and less than 1 mg/kg of extractable fluoride ions | 0 % | 1.1.2010-31.12.2013 |
| ex 3904 61 00 | 30 | Polytetrafluoroethylene, in the form of powder, of a specific surface of 8 $m^2/g$ or more but not more than 12 $m^2/g$, a particle size distribution of 10 % of less than 10 μm and 90 % of less than 35 μm and an average particle size of 20 μm | 0 % | 1.1.2010-31.12.2013 |
| ex 3904 69 90 | 81 | Poly(vinylidene fluoride) powder or in an aqueous suspension | 0 % | 1.1.2010-31.12.2013 |
| ex 3904 69 90 | 93 | Copolymer of ethylene with chlorotrifluoroethylene, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 % | 1.1.2010-31.12.2013 |
| ex 3904 69 90 | 94 | Copolymer of ethylene and tetrafluoroethylene | 0 % | 1.1.2010-31.12.2013 |
| ex 3904 69 90 | 96 | Polychlorotrifluoroethylene, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39 | 0 % | 1.1.2010-31.12.2013 |
| ex 3904 69 90 | 97 | Copolymer of chlorotrifluoroethylene and vinylidene difluoride | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3905 99 90 | 94 | Polymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, containing by weight 97 % or more but not more than 99 % of vinylpyrrolidone, in the form of a solution in water | 0 % | 1.1.2010-31.12.2013 |
| ex 3905 99 90 | 95 | Hexadecylated or eicosylated polyvinylpyrrolidone | 0 % | 1.1.2010-31.12.2013 |
| ex 3905 99 90 | 96 | Polymer of vinyl formal, in one of the forms mentioned in note 6 (b) to Chapter 39, of a weight average molecular weight ($M_w$) of 25 000 or more but not more than 150 000 and containing by weight:<br>— 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl acetate and<br>— 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol | 0 % | 1.1.2010-31.12.2013 |
| ex 3905 99 90 | 97 | Povidone (INN)-iodine | 0 % | 1.1.2010-31.12.2013 |
| ex 3905 99 90 | 98 | Poly(vinyl pyrrolidone) partially substituted by triacontyl groups, containing by weight 78 % or more but not more than 82 % of triacontyl groups | 0 % | 1.1.2010-31.12.2013 |
| 3906 90 60 | | Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide | 0 % | 1.1.2010-31.12.2013 |
| ex 3906 90 90 | 10 | Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for the manufacture of medicaments of heading No 3003 or 3004 [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3906 90 90 | 15 | Photosensitive resin consisting of modified acrylate, acrylic monomer, catalyst (photoinitiator) and stabilizer | 0 % | 1.1.2010-31.12.2013 |
| ex 3906 90 90 | 20 | Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for use as a stabilizer in emulsions or dispersions with a pH of more than 13 [1] | 6 % | 1.1.2010-31.12.2013 |
| ex 3906 90 90 | 25 | Transparent liquid, insoluble in water, containing by weight:<br>— 50 % or more, but not more than 51 % of poly(methyl metacrylate) copolymer,<br>— 37 % or more, but not more than 39 % of xylene and<br>— 11 % or more, but not more than 13 % of n-butyl acetate | 0 % | 1.1.2010-31.12.2013 |
| ex 3906 90 90 | 30 | Copolymer of styrene with hydroxyethyl methacrylate and 2-ethylhexyl acrylate, of a number average molecular weight ($M_n$) of 500 or more but not more than 6 000 | 0 % | 1.1.2010-31.12.2013 |
| ex 3906 90 90 | 35 | White powder of 1,2-ethanediol dimethacrylate-methyl methacrylate copolymer of a particle size of not more than 18 μm, insoluble in water | 0 % | 1.1.2010-31.12.2013 |
| *ex 3906 90 90 | 41 | Poly(alkyl acrylate) with an ester alkyl chain of C10 to C30 | 0 % | 1.1.2010-31.12.2014 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3906 90 90 | 50 | Polymers of esters of acrylic acid with one or more of the following monomers in the chain:<br>— chloromethyl vinyl ether,<br>— chloroethyl vinyl ether,<br>— chloromethylstyrene,<br>— vinyl chloroacetate,<br>— methacrylic acid,<br>— butenedioic acid monobutyl ester,<br>containing by weight not more than 5 % of each of the monomeric units, in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 % | 1.1.2010-31.12.2013 |
| ex 3906 90 90 | 65 | Polyalkylacrylate, chemically modified with cobalt, with a melting temperature (Tm) of 65 °C (± 5 °C), measured with Differential Scanning Calorimetry (DSC) | 0 % | 1.1.2010-31.12.2013 |
| ex 3906 90 90 | 80 | Polydimethylsiloxane-graft-(polyacrylates; polymethacrylates) | 0 % | 1.1.2010-31.12.2013 |
| ex 3906 90 90 | 85 | Non-aqueous dispersion type polymers of esters of acrylic acid with a hydrolyzable silyl group at one or both polymer ends | 0 % | 1.1.2010-31.12.2013 |
| ex 3907 20 11 | 10 | Poly(ethylene oxide) of a number average molecular weight ($M_n$) of 100 000 or more | 0 % | 1.1.2010-31.12.2013 |
| ex 3907 20 11 | 20 | Bis[Methoxypoly[ethyleneglycol)]-maleimidopropionamide, chemically modified with lysine, of a number average molecular weight ($M_n$) of 40 000 | 0 % | 1.1.2010-31.12.2013 |
| ex 3907 20 11 | 30 | Bis[Methoxypoly[ethyleneglycol)], chemically modified with lysine, bis(maleimide) terminated, of a number average molecular weight ($M_n$) of 40 000 | 0 % | 1.1.2010-31.12.2013 |
| *ex 3907 20 20 | 11 | Mixture, containing by weight 70 % or more but not more than 80 % of a polymer of glycerol and 1,2-epoxypropane and 20 % or more but not more than 30 % of a copolymer of dibutyl maleate and *N*-vinyl-2-pyrrolidone | 0 % | 1.1.2010-31.12.2013 |
| *ex 3907 20 20 | 12 | Copolymer of tetrahydrofuran and tetrahydro-3-methylfuran with a number average molecular weight ($M_n$) of 3 500 (± 100) | 0 % | 1.1.2010-31.12.2013 |
| *ex 3907 20 20 | 91 | Products containing co-polymers of dextrose, sorbitol and citric or phosphoric acid, containing not less than 90 % by weight of co-polymers on the ashfree and anhydrous basis | 0 % | 1.1.2010-31.12.2011 |
| ex 3907 20 99 | 15 | Poly(oxypropylene) having alkoxysilyl end-groups | 0 % | 1.1.2010-31.12.2013 |
| ex 3907 20 99 | 30 | Homopolymer of 1-chloro-2,3-epoxypropane (epichlorohydrin) | 0 % | 1.1.2010-31.12.2013 |
| ex 3907 20 99 | 35 | Polyethylene glycol chemically modified with an isocyanate group containing a carbodiimide group, in the form of a solution in 2-methoxy-1-methylethyl acetate | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3907 20 99 | 45 | Copolymer of ethylene oxide and propylene oxide, having aminopropyl and methoxy end-groups | 0 % | 1.1.2010-31.12.2013 |
| ex 3907 20 99 | 50 | Vinyl-silyl terminated perfluoropolyether polymer or an assortment of two components consisting of the same type of vinyl-silyl terminated perfluoropolyether polymer as the main ingredient | 0 % | 1.1.2010-31.12.2013 |
| ex 3907 20 99 | 55 | Succinimidyl ester of methoxy poly(ethylene glycol)propionic acid, of a number average molecular weight (Mn) of 5 000 | 0 % | 1.1.2010-31.12.2013 |
| ex 3907 30 00<br>ex 3926 90 97 | 40<br>70 | Epoxide resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of heading No 8533, 8535, 8536, 8541, 8542 or 8548 [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3907 30 00 | 50 | Liquid epoxide resin of 2-propenenitrile/1,3-butadiene-epoxide copolymer, not containing any solvent, with:<br>— a zinc borate hydrate content of not more than 40 % by weight,<br>— a diantimony trioxide content of not more than 5 % by weight | 0 % | 1.1.2010-31.12.2013 |
| ex 3907 60 80 | 10 | Copolymer of terephthalic acid and isophthalic acid with ethylene glycol, butane-1,4-diol and hexane-1,6-diol | 0 % | 1.1.2010-31.12.2013 |
| ex 3907 60 80 | 30 | Oxygen binding concentrate consisting of a blend of:<br>— a copolymer obtained from polyethylene terephthalate, pyromellitic dianhydride (PMDA) and a hydroxyl substituted polybutadiene<br>— a barrier co-polymer (as determined by the ASTM method F1115-95 (2001)) obtained from xylylene diamines and adipic acid, and<br>— organic dyes and/or organic and inorganic pigments<br>where the first co-polymer predominates | 0 % | 1.1.2010-31.12.2013 |
| 3907 70 00 | | Poly(lactic acid) | 0 % | 1.1.2010-31.12.2013 |
| *ex 3907 99 90 | 10 | Poly(oxy-1,4-phenylenecarbonyl), in the form of powder | 0 % | 1.1.2010-31.12.2013 |
| *ex 3907 99 90 | 20 | Liquid crystal copolyester with a melting point of not less than 270 °C, whether or not containing fillers | 0 % | 1.1.2010-31.12.2013 |
| *ex 3907 99 90 | 50 | Semi-crystalline polycyclohexylenedimethylene terephthalate polymer resin, containing by weight 10 % or more but not more than 40 % of glass fibre, in the form of granules or pellets | 0 % | 1.1.2010-31.12.2011 |
| *ex 3907 99 90 | 60 | Copolymer of terephthalic acid and isophthalic acid with bisphenol A | 0 % | 1.1.2010-31.12.2012 |
| ex 3908 90 00 | 10 | Poly(iminomethylene-1,3-phenylenemethyleneiminoadipoyl), in one of the forms mentioned in note 6 (b) to Chapter 39 | 0 % | 1.1.2010-31.12.2013 |
| ex 3908 90 00 | 20 | Copolymer consisting of hexamethylenediamine, isophthalic acid and terephthalic acid, in one of the forms mentioned in note 6(b) to Chapter 39 | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3908 90 00 | 30 | Reaction product of mixtures of octadecanecarboxylic acids polymerised with an aliphatic polyetherdiamine | 0 % | 1.1.2010-31.12.2013 |
| ex 3908 90 00 | 50 | Oxygen binding concentrate consisting of a blend of:<br>— a copolymer obtained from polyethylene terephthalate, pyromellitic dianhydride (PMDA) and a hydroxyl substituted polybutadiene<br>— a barrier co-polymer (as determined by the ASTM method F1115-95 (2001)) obtained from xylylene diamines and adipic acid, and<br>— organic dyes and/or organic and inorganic pigments<br>where the second co-polymer predominates | 0 % | 1.1.2010-31.12.2013 |
| ex 3909 40 00 | 10 | Polycondensation product of phenol with formaldehyde, in the form of hollow spheres of a diameter of less than 150 μm | 0 % | 1.1.2010-31.12.2013 |
| *ex 3909 50 90 | 10 | UV-curable liquid photopolymer consisting of a mixture containing by weight 60 % or more of polyurethanes and 30 % (± 8 %) of acrylates | 0 % | 1.1.2010-31.12.2014 |
| ex 3910 00 00 | 20 | Block copolymer of poly(methyl-3,3,3-trifluoropropylsiloxane) and poly[methyl(vinyl)siloxane] | 0 % | 1.1.2010-31.12.2013 |
| ex 3910 00 00 | 40 | Biocompatible silicones for the manufacture of long term surgical implants [1] | 0 % | 1.1.2010-31.12.2011 |
| ex 3910 00 00 | 50 | Silicone based pressure sensitive adhesive in solvent containing copoly(dimethylsiloxane/diphenylsiloxane) gum | 0 % | 1.1.2010-31.12.2012 |
| ex 3911 10 00 | 81 | Non-hydrogenated Hydrocarbon Resin, obtained by polymerization of C-5 to C-10 alkenes, cyclopentadiene and dicyclopentadiene, with a Gardner Colour of more than 10 for the pure product or with a Gardner Colour of more than 8 for the 50 % solution by volume in toluene (as determined by the ASTM method D6166) | 0 % | 1.1.2010-31.12.2013 |
| ex 3911 90 19 | 10 | Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4′-biphenylene) | 0 % | 1.1.2010-31.12.2013 |
| ex 3911 90 19 | 30 | Copolymer of ethyleneimine and ethyleneimine dithiocarbamate, in an aqueous solution of sodium hydroxide | 0 % | 1.1.2010-31.12.2012 |
| ex 3911 90 99 | 25 | Copolymer of vinyltoluene and α-methylstyrene | 0 % | 1.1.2010-31.12.2013 |
| *ex 3911 90 99 | 31 | Copolymers of butadiene and maleic acid, whether or not containing its ammonium salts | 0 % | 1.1.2010-31.12.2014 |
| ex 3911 90 99 | 40 | Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not more than 16 % by weight | 0 % | 1.1.2010-31.12.2013 |
| ex 3911 90 99 | 45 | Copolymer of maleic acid and methyl vinyl ether | 0 % | 1.1.2010-31.12.2013 |
| ex 3911 90 99 | 65 | Calcium zinc salt of a copolymer of maleic acid and methyl vinyl ether | 0 % | 1.1.2010-31.12.2013 |
| ex 3911 90 99 | 86 | Copolymer of methyl vinyl ether and maleic acid anhydride | 0 % | 1.1.2010-31.12.2011 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 3912 39 85 | 10 | Ethylcellulose, not plasticized | 0 % | 1.1.2010-31.12.2013 |
| *ex 3912 39 85 | 20 | Ethylcellulose, in the form of an aqueous dispersion containing hexadecan-1-ol and sodium dodecyl sulphate, containing by weight 27 (± 3) % of ethylcellulose | 0 % | 1.1.2010-31.12.2013 |
| *ex 3912 39 85 | 30 | Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms | 0 % | 1.1.2010-31.12.2013 |
| ex 3912 90 10 | 10 | Cellulose acetate propionate, non-plasticised, in the form of powder:<br>— containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method) and<br>— of a viscosity of not more than 120 poise (as determined by the ASTM D 817-72 method),<br>for the manufacture of printing inks, paints, lacquers and other coatings, and reprographic coatings ([1]) | 0 % | 1.1.2010-31.12.2013 |
| ex 3912 90 10 | 20 | Hydroxypropyl methylcellulose phthalate | 0 % | 1.1.2010-31.12.2013 |
| ex 3913 90 00 | 81 | Blend of cyanoethyl pullulan and cyanoethyl poly(vinyl alcohol) | 0 % | 1.1.2010-31.12.2013 |
| ex 3913 90 00 | 85 | Sterile sodium hyaluronate | 0 % | 1.1.2010-31.12.2013 |
| ex 3913 90 00 | 92 | Protein, chemically modified by carboxylation and/or phthalic acid addition, having a weight average molecular weight ($M_w$) of 100 000 to 300 000 | 0 % | 1.1.2010-31.12.2013 |
| ex 3913 90 00 | 94 | Granules containing by weight:<br>— 35 % or more but less than 75 % of a high amylose extruded biopolymer produced from corn starch,<br>— 5 % or more but less than 16 % polyvinyl alcohol,<br>— 10 % or more but less than 46 % of polyol plasticisers,<br>— 0,25 % or more but less than 3 % of stearic acid,<br>— whether or not containing 30 % (± 10 %) of biodegradable polyester resin but never to a level that exceeds the amount of the high amylose biopolymer | 0 % | 1.1.2010-31.12.2011 |
| ex 3913 90 00 | 95 | Chondroitinsulphuric acid, sodium salt | 0 % | 1.1.2010-31.12.2013 |
| ex 3913 90 00 | 96 | Powder consisting of 90 % (± 5 %) by weight of a high amylose extruded biopolymer produced from corn starch, 10 % (± 5 %) by weight of a synthetic polymer and 0,5 % (± 0,25 %) of stearic acid | 0 % | 1.1.2010-31.12.2011 |
| *ex 3917 32 00 | 91 | Pipe consisting of a block copolymer of polytetrafluoroethylene and polyperfluoroalkoxytrifluoroethylene, of a length of not more than 600 mm, a diameter of not more than 85 mm and a wall-thickness of 30 µm or more but not more than 110 µm | 0 % | 1.1.2010-31.12.2013 |
| *ex 3917 40 00 | 91 | Plastic connectors containing O-rings, a retainer clip and a release system for insertion into car fuel hoses | 0 % | 1.1.2010-31.12.2014 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 3919 10 19<br>ex 3919 10 80<br>ex 3919 90 00 | 10<br>25<br>31 | Reflecting film, consisting of a layer of polyurethane, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film | 0 % | 1.1.2010-31.12.2013 |
| ex 3919 10 19 | 20 | Rolls of two-sided adhesive tape:<br>— coated with non-vulcanised natural or synthetic rubber<br>— with a width of 20 mm or more but not more than 40 mm<br>— containing silicone, aluminium hydroxide, acryl and urethane | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 10 80<br>ex 3919 90 00<br>ex 3920 61 00 | 21<br>21<br>20 | Reflecting laminated sheet, consisting of a film of polycarbonate totally embossed on one side in a regular shaped pattern, covered on both sides with one or more layers of plastic material, whether or not covered on one side with an adhesive layer and a release sheet | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 10 80 | 30 | Double-sided, self-adhesive modified epoxy resin foil, put up in rolls, 10 to 20 cm wide, 10 to 210 m long and with a total thickness of 10 to 50 µm, not for retail sale | 0 % | 1.1.2010-31.12.2011 |
| *ex 3919 10 80 | 35 | Reflecting film, consisting of a layer of poly(vinyl chloride), a layer of alkyd polyester, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, only visible by means of a retroreflecting lighting, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 10 80<br>ex 3919 90 00 | 40<br>43 | Black polyvinyl chloride film having a high gloss of more than 90 degrees as determined by test method ASTM D 2457 covered on one side with a protective polyethylene terephthalate film and on the other side a pressure sensitive adhesive with channels and a polyethylene terephthalate release liner | 0 % | 1.1.2010-31.12.2011 |
| *ex 3919 10 80<br>ex 3919 90 00 | 45<br>45 | Reinforced polyethylene foam tape, coated on both sides with an acrylic micro channelled pressure sensitive adhesive and on one side a liner, with an application thickness of 0,38 mm or more but not more than 1,53 mm | 0 % | 1.1.2010-31.12.2012 |
| *ex 3919 10 80<br>ex 3919 90 00<br>ex 3920 10 89 | 50<br>41<br>25 | Adhesive film consisting of a base of a copolymer of ethylene and vinyl acetate (EVA) of a thickness of 70 µm or more and an adhesive part of acrylic tape of a thickness of 5 µm or more, for the protection of the surface of silicon discs ([1]) | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 10 80<br>ex 3919 90 00 | 55<br>53 | Acrylic foam tape, covered on one side with a heat activatable adhesive or an acrylic pressure sensitive adhesive and on the other side with an acrylic pressure sensitive adhesive and a release sheet, of a peel adhesion at an angle of 90 ° of more than 25 N/cm (as determined by the ASTM D 3330 method) | 0 % | 1.1.2010-31.12.2012 |
| *ex 3919 10 80 | 60 | Reflecting laminated sheet showing a regular pattern, consisting of a film of poly(methylmethacrylate), followed by a layer of acrylic polymer containing microprisms, a film of poly(methylmethacrylate), an adhesive layer and a release sheet | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 3919 10 80<br><br>ex 3919 90 00 | 65<br><br>57 | Self-adhesive reflecting laminated sheet showing a regular pattern, consisting of a film of acrylic polymer followed by a layer of poly(methyl methacrylate) containing microprisms and whether or not containing an additional layer of polyester and adhesive with a final release sheet | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 90 00 | 19 | Transparent poly(ethylene terephthalate) self-adhesive film, free from impurities or faults, coated on one side with an acrylic pressure sensitive adhesive and a protective liner, and on the other side having an antistatic layer of ionic based organic compound choline and a printable dust-proof layer of modified long chain alkyl organic compound, having a total thickness without the liner of 54 µm or more but not more than 64 µm and a width of more than 1 295 mm but not more than 1 305 mm | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 90 00 | 23 | Film consisting of 1 to 3 laminated layers of poly(ethylene terephthalate) and a copolymer of terephthalic acid, sebacic acid and ethylene glycol, coated on one side with an acrylic abrasion resistant coating and on the other side with an acrylic pressure sensitive adhesive, a water soluble methylcellulose coating and a poly(ethylene terephthalate) protective liner | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 90 00 | 25 | Film consisting of a multi-layer construction of poly(ethylene terephthalate) and copolymer of butylacrylate and methylmethacrylate, coated on one side with an acrylic abrasion resistant coating incorporating nanoparticles of antimony tin oxide and carbon black, and on the other side with an acrylic pressure sensitive adhesive and a silicone-coated poly(ethylene terephthalate) protective liner | 0 % | 1.1.2010-31.12.2012 |
| *ex 3919 90 00 | 27 | Poly(ethylene terephthalate) film, with an adhesive strength of not more than 0,147 N/25 mm and an electrostatic discharge of not more than 500 V | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 90 00 | 29 | Polyester film coated on both sides with an acrylic and/or rubber (pressure sensitive) adhesive put up in rolls of a width of 45,7 cm or more but not more than 132 cm (supplied with a release liner) | 0 % | 1.1.2010-31.12.2014 |
| *ex 3919 90 00 | 33 | Transparent poly(ethylene) self-adhesive film, free from impurities or faults, coated on one side with an acrylic pressure sensitive adhesive, with a thickness of 60 µm or more, but not more than 70 µm, and with a width of more than 1 245 mm but not more than 1 255 mm | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 90 00 | 35 | Reflecting layered sheet on rolls, with a width of more than 20 cm, showing an embossed regular pattern, consisting of polyvinyl chloride film coated on one side with a layer, based on acryl polymers and on the other side:<br>— a layer of polyurethane containing glass micro beads,<br>— an adhesive layer, and<br>— a release sheet | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 90 00 | 37 | UV sensitive film of poly(vinyl chloride):<br>— with a thickness of 78 µm or more,<br>— covered on one side with an acrylic adhesive layer of a thickness of 8 µm or more and with a release sheet, | 0 % | 1.1.2010-31.12.2014 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| | | — with an adhesive strength of 1 764 mN/25 mm or more,<br>for use in the cutting of silicon<br>(1) | | |
| *ex 3919 90 00 | 39 | Poly(vinyl chloride) sheeting, of a thickness of less than 1 mm, coated with an adhesive in which are embedded glass balls of a diameter of not more than 100 μm | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 90 00<br>ex 9001 20 00 | 47<br>40 | Polarizer film, in rolls, consisting of a multilayered polyvinyl alcohol film, supported on either side by a triacetyl cellulose film, with a pressure sensitive adhesive and release film on one side | 0 % | 1.1.2010-31.12.2012 |
| *ex 3919 90 00 | 49 | Reflecting laminated sheet consisting of a film of poly(methyl methacrylate) embossed on one side in a regular shaped pattern, a film of a polymer containing glass microspheres, an adhesive layer and a release sheet | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 90 00<br>ex 3920 51 00 | 51<br>30 | Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 μm or more but not more than 90 μm, whether or not covered on one side with an adhesive layer and a release sheet | 0 % | 1.1.2010-31.12.2013 |
| *ex 3919 90 00 | 55 | Rolls of biaxially oriented polypropylene film with:<br>— a self adhesive coating,<br>— a width of 363 mm or more, but not more than 507 mm,<br>— a total film thickness of 10 μm or more but not more than 100 μm,<br>for use in the protection of LCD displays during the manufacturing of LCD modules (1) | 0 % | 1.1.2010-31.12.2012 |
| *ex 3920 10 25<br>ex 3920 10 89 | 10<br>20 | Film of a thickness of not more than 0,20 mm, of a blend of polyethylene and a copolymer of ethylene with oct-1-ene, embossed in a regular rhomboidal pattern, for coating both sides of a layer of unvulcanized rubber (1) | 0 % | 1.1.2010-31.12.2013 |
| *ex 3920 10 25 | 20 | Film of polyethylene, of a kind used for typewriter ribbon | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 10 28 | 91 | Poly(ethylene) film of a thickness of 19 μm (± 1), printed with a graphic design which consists of eight different colours on one side of the film, and one colour on the opposite side, the graphic design also has the following characteristics:<br>— is repetitive and equally spaced along the length of the film<br>— is equally and visibly aligned when viewed from the back or front of the film | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 10 89 | 40 | Composite sheet containing an acrylic coating and laminated to a high-density polyethylene layer, of a total thickness of 0,8 mm or more but not more than 1,2 mm | 0 % | 1.1.2010-31.12.2011 |
| ex 3920 20 21 | 30 | Biaxially oriented polypropylene film with a coextruded layer of polyethylene on one side and a total thickness of 11,5 μm or more but not more than 13,5 μm. | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3920 20 29 | 92 | Mono-axial oriented film, of a total thickness of not more than 75 μm, consisting of two or three layers, each layer containing a mixture of polypropylene and polyethylene, with a core layer whether or not containing titanium dioxide, having:<br>— a tensile strength in the machine direction of 175 MPa or more but not more than 270 MPa and<br>— a tensile strength in the transverse direction of 20 MPa or more but not more than 40 MPa<br>as determined by test method ASTM D882/ISO 527-3 | 0 % | 1.1.2010-31.12.2013 |
| *ex 3920 20 29 | 93 | Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, having:<br>— a thickness of 55 μm or more but not more than 97 μm,<br>— a tensile modulus in the machine direction of 0,75 GPa or more but not more than 1,45 GPa, and<br>— a tensile modulus in the transverse direction of 0,20 GPa or more but not more than 0,55 GPa | 0 % | 1.1.2010-31.12.2014 |
| *ex 3920 20 80 | 92 | Laminated sheet or strip, consisting of a film of a thickness of 181 μm or more but not more than 223 μm composed of a blend of a copolymer of propylene with ethylene and a copolymer of styrene-ethylene-butylene-styrene (SEBS) coated or covered on one side with a layer of a copolymer of styrene-ethylene-butylene-styrene (SEBS) and a layer of polyester | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 43 10 | 92 | Sheeting of poly(vinyl chloride), stabilized against ultraviolet rays, without any holes, even microscopic, of a thickness of 60 μm or more but not more than 80 μm, containing 30 or more but not more than 40 parts of plasticizer to 100 parts of poly(vinyl chloride) | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 43 10<br>ex 3920 49 10 | 94<br>93 | Film of a specular gloss of 70 or more, measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of one or two layers of poly(vinyl chloride) coated on both sides with a layer of plastic, of a thickness of 0,26 mm or more but not more than 1,0 mm, covered on the gloss surface with a protective film of polyethylene, in rolls of a width of 1 000 mm or more but not more than 1 450 mm, for use in the manufacture of goods of heading No 9403 [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 43 10 | 95 | Reflecting laminated sheet, consisting of a film of poly(vinyl chloride) and a film of an other plastic totally embossed in a regular pyramidal pattern, covered on one side with a release sheet | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 43 10 | 96 | Film, of a specular gloss of 70 or more measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of a layer of poly(ethylene terephthalate) and a layer of coloured poly(vinyl chloride), for coating panels and doors of a kind used in the manufacture of domestic appliances [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 43 10 | 97 | Film embossed to a depth of not more than 12 μm, of a specular gloss of 7 or more but not more than 17, measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of at least two layers of poly(vinyl chloride), of a total thickness of not more than 0,5 mm, covered on the embossed side with a protective film, in rolls of a width of 1 400 mm or more but not more than 1 420 mm, for use in the manufacture of goods of heading No 9403 [1] | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3920 51 00 | 10 | Poly(methyl methacrylate) plate, with an antistatic coating, of dimensions of 738 × 972 mm (± 1,5 mm) | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 51 00 | 20 | Plate of poly(methyl methacrylate) containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not more than 19 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 51 00 | 40 | Sheets of polymethylmethacrylate plastic complying with standards EN 4364 (MIL-P-5425E), EN 4365 (MIL-P-8184) and EN 4366 (MIL-PRF-25690) | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 59 90 | 10 | Non-cellular and non-laminated sheet of modified copolymer of acrylonitrile-methyl acrylate with a thickness of 1,0 mm or more but not more than 1,3 mm, put up in rolls | 0 % | 1.1.2010-31.12.2011 |
| ex 3920 62 19<br>ex 3920 62 19 | 01<br>03 | Coextruded opaque sheet of poly(ethylene terephthalate), of a thickness of 50 µm or more but not more than 350 µm, consisting especially of a layer containing carbon black | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 62 19<br>ex 3920 62 19 | 07<br>09 | Poly(ethylene terephthalate) film, not coated with an adhesive, of a thickness of not more than 25 µm, either:<br>— only dyed in the mass, or<br>— dyed in the mass and metallized on one side | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 62 19<br>ex 3920 62 19 | 11<br>13 | Film of poly(ethylene terephthalate) only, of a total thickness of not more than 120 µm, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 62 19<br>ex 3920 62 19 | 14<br>16 | Poly(ethylene terephthalate) film, of a thickness of 20 µm or more but not more than 150 µm, coated on one side with silicone, for use in the manufacture of window film [1] | 3 % | 1.1.2010-31.12.2011 |
| ex 3920 62 19<br>ex 3920 62 19 | 17<br>19 | Laminated film of poly(ethylene terephthalate) only, of a total thickness of not more than 120 µm, consisting of one layer which is metallised only and one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 62 19 | 20 | Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 62 19<br>ex 3920 62 19 | 21<br>23 | Film of poly(ethylene terephthalate), coated or covered on one side or on both sides with a layer of modified polyester, of a total thickness of 7 µm or more but not more than 11 µm, for the manufacture of video tapes with a magnetic layer of metallic pigments and a width of 8 mm or of 12,7 mm [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 62 19<br>ex 3920 62 19 | 37<br>39 | Poly(ethylene terephthalate) film, of a thickness of not more than 12 µm, coated on one side with a layer of aluminium oxide of a thickness of not more than 35 nm | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3920 62 19<br><br>ex 3920 62 19 | 41<br><br>43 | Poly(ethylene terephthalate) film, of a thickness of 18 µm or more but not more than 25 µm, having:<br><br>— a shrinkage of (3,4 ± 0,1) % in the machine direction (as determined by the ASTM D 1204 method) and<br><br>— a shrinkage of (0,3 ± 0,2) % in the transverse direction (as determined by the ASTM D 1204 method) | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 62 19<br><br>ex 3920 62 19 | 51<br><br>53 | Film of poly(ethylene terephthalate), poly(ethylene naphthalate) or similar polyester, coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness of not more than 300 µm and having a surface resistivity of not more than 10 000 ohms (per square) (as determined by the ASTM D 257-99 method) | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 62 19<br><br>ex 3920 62 19 | 54<br><br>56 | Matt film of poly(ethylene terephthalate), of a specular gloss of 15 measured at an angle of 45 ° and 18 measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method) and a width of 1 600 mm or more | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 62 19<br><br>ex 3920 62 19 | 57<br><br>59 | Film of white poly(ethylene terephthalate), dyed in the mass, of a thickness of 185 µm or more but not more than 253 µm, coated on both sides with an antistatic layer | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 62 19<br><br>ex 3920 69 00 | 73<br><br>40 | Iridescent film of polyester and poly(methyl methacrylate) | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 62 19<br><br>ex 3920 62 19 | 75<br><br>77 | Transparent polyethylene terephthalate film, coated on both sides by thin layers of 7-80 nm each of organic substances on the basis of acryl, giving good adhesion property with surface tension of 37 Dyne/cm, with a light transmission of more than 93 %, a haze value of less than 1,3 %, a total thickness of 125 µm or 188 µm and a width of 850 mm or more, but not more than 1 600 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 62 19<br><br>ex 3920 62 19 | 80<br><br>82 | Poly(ethylene terephtalate) film of a thickness of not more than 20 µm, coated on both sides with a gas barrier layer consisting of a polymeric matrix in which silica has been dispersed and of a thickness of not more than 2 µm | 0 % | 1.1.2010-31.12.2012 |
| ex 3920 62 19 | 88 | Laminated sheet, consisting of a biaxially oriented film of poly(ethylene terephthalate), covered on one side or on both sides with a layer of poly(ethylene terephthalate), for use in the manufacture of identity cards, credit cards and similar products (including “smart” cards) [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 69 00 | 20 | Film of poly(ethylene naphthalene-2,6-dicarboxylate) | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 79 90 | 10 | Cellulose acetyl butyrate film, whether or not combined with a polycarbonate layer, of a thickness of not more than 0,81 mm containing a micro-louvre with a typical viewing angle of 30 degrees measured on each side of the surface normal | 0 % | 1.1.2010-31.12.2012 |
| ex 3920 91 00 | 91 | Poly(vinyl butyral) film having a graduated coloured band | 3 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3920 91 00 | 92 | Plasticised film of polyvinyl butyral, containing by weight:<br>— either 14,5 % or more but not more than 17,5 % of dihexyl adipate,<br>— or 14,5 % or more but not more than 28,5 % of dibutyl sebacate | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 91 00 | 93 | Film of poly(ethylene terephthalate), whether or not metallised on one or both sides, or laminated film of poly(ethylene terephthalate) films, metallised on the external sides only, and having the following characteristics:<br>— a visible light transmission of 50 % or more,<br>— coated on one or both sides with a layer of poly(vinyl butyral) but not coated with an adhesive or any other material except poly(vinyl butyral),<br>— a total thickness of not more than 0,2 mm without taking the presence of poly(vinyl butyral) into account,<br>for use in the manufacture of heat-reflecting or decorative laminated glass [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 91 00 | 95 | Co-extruded trilayer poly(vinyl butyral) film with a graduated colour band containing by weight 29 % or more but not more than 31 % of 2,2′-ethylenedioxydiethyl bis(2-ethylhexanoate) as a plasticiser | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 92 00 | 30 | Polyamide film of a thickness of not more than 20 µm, coated on both sides with a gas barrier layer which consists of a polymeric matrix in which silica has been dispersed and of a thickness of not more than 2 µm | 0 % | 1.1.2010-31.12.2012 |
| ex 3920 99 28 | 40 | Polymer film containing the following monomers:<br>— Poly (tetramethylene ether glycol),<br>— Bis (4-isocyanotocyclohexyl) methane,<br>— 1,4-Butanediol or 1,3-Butanediol,<br>— with a thickness of 0,25 mm or more but not more than 5,0 mm,<br>— embossed with a regular pattern on one surface,<br>— and covered with a release sheet | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 99 28 | 50 | Thermoplastic polyurethane film, of a thickness of 250 µm or more but not more than 350 µm, covered on one side with a removable protective film | 0 % | 1.1.2010-31.12.2011 |
| ex 3920 99 59 | 25 | Poly(1-chlorotrifluoroethylene) film | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 99 59 | 50 | Polytetrafluoroethylene film, non-microporous, in the form of rolls, of a thickness of 0,019 mm or more but not more than 0,14 mm, impermeable to water vapour | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 99 59 | 55 | Ion-exchange membranes of fluorinated plastic material | 0 % | 1.1.2010-31.12.2013 |
| ex 3920 99 59 | 60 | Film of a vinyl alcohol copolymer, soluble in cold water, of a thickness of 34 µm or more but not more than 90 µm, a tensile strength at break of 20 MPa or more but not more than 45 MPa and an elongation at break of 250 % or more but not more than 900 % | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 3920 99 90 | 20 | Anisotropic conductive film, in rolls, of a width of 1,5 mm or more but not more than 3,15 mm and a maximum length of 300 m, used for joining electronic components in the production of LCD or plasma displays | 0 % | 1.1.2010-31.12.2013 |
| ex 3921 13 10 | 10 | Sheet of polyurethane foam, of a thickness of 3 mm (± 15 %) and of a specific gravity of 0,09435 or more but not more than 0,10092 | 0 % | 1.1.2010-31.12.2013 |
| ex 3921 19 00 | 91 | Microporous polypropylene film of a thickness of not more than 100 µm | 0 % | 1.1.2010-31.12.2013 |
| ex 3921 19 00 | 93 | Strip of microporous polytetrafluoroethylene on a support of a non-woven, for use in the manufacture of filters for kidney dialysis equipment (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3921 19 00 | 95 | Film of polyethersulfone, of a thickness of not more than 200 µm | 0 % | 1.1.2010-31.12.2013 |
| ex 3921 19 00 | 96 | Cellular film, consisting of a layer of polyethylene of a thickness of 90 µm or more but not more than 140 µm and a layer of regenerated cellulose of a thickness of 10 µm or more but not more than 40 µm | 0 % | 1.1.2010-31.12.2013 |
| *ex 3921 90 10 | 10 | Composite plate of poly(ethylene terephthalate) or of poly(butylene terephthalate), reinforced with glass fibres | 0 % | 1.1.2010-31.12.2013 |
| *ex 3921 90 10 | 20 | Poly(ethylene terephthalate) film, laminated on one side or on both sides with a layer of unidirectional nonwoven poly(ethylene terephthalate) and impregnated with polyurethane or epoxide resin | 0 % | 1.1.2010-31.12.2013 |
| ex 3921 90 55 | 20 | Pre-impregnated reinforced fibreglass containing cyanate ester resin or bismaleimide (B) triazine (T) resin mixed with epoxide resin, measuring:<br>— 469,9 mm (± 2 mm) × 622,3 mm (± 2 mm), or<br>— 469,9 mm (± 2 mm) × 414,2 mm (± 2 mm), or<br>— 546,1 mm (± 2 mm) × 622,3 mm (± 2 mm) | 0 % | 1.1.2010-31.12.2013 |
| ex 3921 90 60<br>ex 5407 71 00<br>ex 5903 90 99 | 91<br>20<br>10 | Woven polytetrafluoroethylene fabric, coated or covered with a copolymer of tetrafluoroethylene and trifluoroethylene having perfluorinated alkoxy side-chains ending in carboxylic acid or sulphonic acid groups, whether or not in the potassium or sodium salt form | 0 % | 1.1.2010-31.12.2013 |
| ex 3921 90 60 | 93 | Film, of a specular gloss of 30 or more but not more than 60 measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of a layer of poly(ethylene terephthalate) and a layer of coloured poly(vinyl chloride), joined by a metallised adhesive coating, for coating panels and doors of a kind used in the manufacture of domestic appliances (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 3923 30 90 | 10 | Polyethylene container, for compressed hydrogen:<br>— with aluminium bosses at both ends,<br>— wholly embedded in an overwrap of carbon fibres impregnated with epoxide resin, | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| | | — of a diameter of 213 mm or more, but not more than 368 mm,<br>— a length of 860 mm or more, but not more than 1 260 mm and<br>— a capacity of 18 litres or more, but not more than 50 litres | | |
| ex 3926 90 92 | 20 | Reflecting sheeting or tape, consisting of a facing-strip of poly(vinyl chloride) embossed in a regular pyramidal pattern, heat-sealed in parallel lines or in a grid-pattern to a backing-strip of plastic material, or of knitted or woven fabric covered on one side with plastic material | 0 % | 1.1.2010-31.12.2013 |
| ex 3926 90 97 | 10 | Microspheres of a polymer of divinylbenzene, of a diameter of 4,5 µm or more but not more than 80 µm | 0 % | 1.1.2010-31.12.2013 |
| ex 3926 90 97 | 15 | Glass fibre reinforced plastic traverse leaf spring for use in the manufacture of motor vehicle suspension systems [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 3926 90 97 | 25 | Unexpansible microspheres of a copolymer of acrylonitrile, methacrylonitrile and isobornyl methacrylate, of a diameter of 3 µm or more but not more than 4,6 µm | 0 % | 1.1.2010-31.12.2013 |
| ex 3926 90 97 | 55 | Flat product of polyethylene, perforated in opposing directions, of a thickness of 600 µm or more but not more than 1 200 µm and of a weight of 21 g/m$^2$ or more but not more than 42 g/m$^2$ | 0 % | 1.1.2010-31.12.2013 |
| ex 4007 00 00 | 10 | Siliconated vulcanised rubber thread and cord | 0 % | 1.1.2010-31.12.2013 |
| ex 4016 99 97 | 20 | Soft rubber sealing stoppers for the manufacture of electrolytic capacitors [1] | 0 % | 1.1.2010-31.12.2013 |
| 4105 10 10<br>4105 10 90<br>4105 30 91<br>4105 30 99 | | Sheep or lamb skin leather, without wool on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4114 | 0 % | 1.1.2010-31.12.2013 |
| 4106 21 10<br>4106 22 90 | | Goat or kid skin leather, without hair on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4114 | 0 % | 1.1.2010-31.12.2013 |
| 4106 31 10<br>4106 32 90<br>4106 40 90<br>4106 92 00 | | Leather of other animals, without hair on, not further prepared than tanned, other than leather of heading No 4114 | 0 % | 1.1.2010-31.12.2013 |
| ex 5004 00 10 | 10 | Silk yarn (other than yarn spun from silk waste) not put up for retail sale, unbleached, scoured or bleached, entirely of silk | 0 % | 1.1.2010-31.12.2011 |
| ex 5004 00 90 | 10 | Yarn spun entirely from silk, not put up for retail sale | 2,5 % | 1.1.2010-31.12.2011 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 5005 00 10<br>ex 5005 00 90 | 10<br>10 | Yarn spun entirely from silk waste (noil), not put up for retail sale | 0 % | 1.1.2010-31.12.2013 |
| ex 5205 31 00 | 10 | Six ply yarn of bleached cotton, measuring 925 dtex or more but not more than 989 dtex per single yarn, for the manufacture of tampons (1) | 0 % | 1.1.2010-31.12.2013 |
| 5208 11 10 | | Fabrics for the manufacture of bandages, dressings and medical gauzes | 5,2 % | 1.1.2010-31.12.2013 |
| ex 5402 45 00 | 20 | Yarn of synthetic textile fibres solely of aromatic polyamides obtained by the polycondensation of *m*-phenylenediamine and isophthalic acid | 0 % | 1.1.2010-31.12.2013 |
| ex 5402 47 00 | 10 | Synthetic bicomponent filament yarn, not textured, untwisted, measuring 1 650 decitex or more but not more than 1 800 decitex, consisting of 110 filaments or more but not more than 120 filaments, each having a core of poly(ethylene terephthalate) and a skin of polyamide-6, containing by weight 75 % or more but not more than 77 % of poly(ethylene terephthalate), for use in the manufacture of roofings (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 5402 49 00 | 30 | Yarn of a copolymer of glycollic acid with lactic acid, for the manufacture of surgical sutures (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 5402 49 00 | 50 | Non-textured filament yarn of poly(vinyl alcohol) | 0 % | 1.1.2010-31.12.2013 |
| ex 5402 49 00 | 70 | Synthetic filament yarn, single, containing by weight 85 % or more of acrylonitrile, in the form of a wick containing 1 000 continuous filaments or more but not more than 25 000 continuous filaments, of a weight per metre of 0,12 g or more but not more than 3,75 g and of a length of 100 m or more, for the manufacture of carbon-fibre yarn (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 5404 19 00 | 20 | Monofilament of poly(1,4-dioxanone) | 0 % | 1.1.2010-31.12.2013 |
| *ex 5404 19 00 | 30 | Unsterilised monofilament of a copolymer of 1,3-dioxan-2-one with 1,4-dioxan-2,5-dione, for the manufacture of surgical sutures (1) | 0 % | 1.1.2010-31.12.2014 |
| ex 5404 19 00 | 50 | Monofilaments of polyester or poly(butylene terephthalate), with cross-sectional dimension of 0,5 mm or more but not more than 1 mm, for use in the manufacture of zippers (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 5404 90 90 | 20 | Strip of polyimide | 0 % | 1.1.2010-31.12.2013 |
| ex 5407 10 00 | 10 | Textile fabric, consisting of warp filament yarns of polyamide-6,6 and weft filament yarns of polyamide-6,6, polyurethane and a copolymer of terephthalic acid, *p*-phenylenediamine and 3,4′-oxybis (phenyleneamine) | 0 % | 1.1.2010-31.12.2012 |
| ex 5503 11 00<br>ex 5601 30 00 | 10<br>40 | Synthetic staple fibres of a copolymer of terephthalic acid, *p*-phenylenediamine and 3,4'-oxybis(phenyleneamine), of a length of not more than 7 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 5503 90 00<br>ex 5506 90 00<br>ex 5601 30 00 | 20<br>10<br>10 | Poly(vinyl alcohol) fibres, whether or not acetalized | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 5603 11 10<br>ex 5603 11 90<br>ex 5603 12 10<br>ex 5603 12 90<br>ex 5603 91 10<br>ex 5603 91 90<br>ex 5603 92 10<br>ex 5603 92 90 | 10<br>10<br>10<br>10<br>10<br>10<br>10<br>10 | Poly(vinyl alcohol) non-wovens, in the piece or cut into rectangles:<br>— of a thickness of 200 µm or more but not more than 280 µm and<br>— of a weight of 20 g/m$^2$ or more but not more than 50 g/m$^2$ | 0 % | 1.1.2010-31.12.2013 |
| ex 5603 11 10<br>ex 5603 11 90 | 20<br>20 | Nonwovens, not weighing more than 20 g/m$^2$, containing spunbonded and meltblown filaments put together in a sandwich way with the two outer layers containing fine endless filaments (not less than 10 µm but not more than 20 µm in diameter) and the inner layer containing super-fine endless filaments (not less than 1 µm but not more than 5 µm in diameter), for the manufacture of napkins and napkin liners for babies and similar sanitary napkins [1] | 0 % | 1.1.2010-31.12.2012 |
| ex 5603 12 90<br>ex 5603 13 90<br>ex 5603 14 90<br>ex 5603 92 90<br>ex 5603 93 90<br>ex 5603 94 90 | 30<br>30<br>10<br>60<br>40<br>30 | Non-wovens of aromatic polyamide fibres obtained by polycondensation of *m*-phenylenediamine and isophthalic acid, in the piece or cut into rectangles | 0 % | 1.1.2010-31.12.2013 |
| ex 5603 12 90 | 50 | Non-woven:<br>— weighing 30 g/m$^2$ or more, but not more than 60 g/m$^2$,<br>— containing fibres of polypropylene or of polypropylene and polyethylene,<br>— whether or not printed, with:<br>— on one side, 65 % of the total surface area having circular bobbles of 4 mm in diameter, consisting of anchored, elevated un-bonded curly fibres, suitable for the engagement of extruded hook materials, and the remaining 35 % of the surface area being bonded,<br>— and on other side a smooth untextured surface,<br>for use in the manufacture of napkins and napkin liners for babies and similar sanitary articles [1] | 0 % | 1.1.2010-31.12.2012 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 5603 12 90<br>ex 5603 13 90 | 60<br>60 | Non-woven of spunbonded polyethylene, of a weight of more than 60 g/m$^2$ but not more than 80 g/m$^2$ and an air resistance (Gurley) of 8 s or more but not more than 36 s (as determined by the ISO 5636/5 method) | 0 % | 1.1.2010-31.12.2013 |
| ex 5603 12 90<br>ex 5603 13 90<br>ex 5603 92 90<br>ex 5603 93 90 | 70<br>70<br>40<br>10 | Non-wovens of polypropylene, consisting of a meltblown layer, laminated on each side with spunbonded filaments of polypropylene, of a thickness of not more than 550 µm and of a weight of not more than 80 g/m$^2$, in the piece or simply cut into squares or rectangles, not impregnated | 0 % | 1.1.2010-31.12.2013 |
| ex 5603 13 10<br>ex 5603 14 10 | 10<br>10 | Electrically nonconductive nonwovens, consisting of a central film of poly(ethylene terephthalate) laminated on each side with unidirectionally aligned fibres of poly(ethylene terephthalate), coated on both sides with high grade temperature resistant electrical nonconductive resin, weighing 147 g/m$^2$ or more but not more than 265 g/m$^2$, with non-isotropic tensile strength on both directions, to be used as electrical insulation material | 0 % | 1.1.2010-31.12.2013 |
| ex 5603 14 90 | 30 | Non-wovens, consisting of a central elastomeric film laminated on each side with spunbonded filaments of polypropylene, of a weight of 200 g/m$^2$ or more but not more than 300 g/m$^2$ | 0 % | 1.1.2010-31.12.2013 |
| ex 5603 92 90<br>ex 5603 93 90 | 20<br>20 | Non-wovens consisting of a meltblown central layer of a thermoplastic elastomer laminated on each side with spunbonded filaments of polypropylene | 0 % | 1.1.2010-31.12.2013 |
| ex 5603 92 90<br>ex 5603 94 90 | 70<br>40 | Non-wovens, consisting of multiple layers of a mixture of meltblown fibres and staple fibres of polypropylene and polyester, whether or not laminated on one side or on both sides with spunbonded filaments of polypropylene, of a total thickness of not more than 50 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 5603 94 90 | 20 | Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips [1] | 0 % | 1.1.2010-31.12.2013 |
| *ex 5607 50 90 | 10 | Unsterilised twine of poly(glycolic acid) or of poly(glycolic acid) and its copolymers with lactic acid, plaited or braided, with an inner core, for the manufacture of surgical sutures [1] | 0 % | 1.1.2010-31.12.2014 |
| ex 5803 00 10 | 91 | Gauze of cotton, of a width of less than 1 500 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 5903 10 90<br>ex 5903 20 90<br>ex 5903 90 99 | 10<br>10<br>20 | Knitted or woven fabrics, coated or covered on one side with artificial plastic material in which are embedded microspheres | 0 % | 1.1.2010-31.12.2013 |
| ex 5906 99 90 | 10 | Rubberised textile fabric, consisting of warp yarns of polyamide-6,6 and weft yarns of polyamide-6,6, polyurethane and a copolymer of terephthalic acid, *p*-phenylenediamine and 3,4′-oxybis(phenyleneamine) | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 5907 00 00 | 10 | Textile fabrics, coated with adhesive in which are embedded spheres of a diameter of not more than 150 μm | 0 % | 1.1.2010-31.12.2011 |
| ex 5911 10 00 | 10 | Needle-punched synthetic-fibre felts, not containing polyester, whether or not containing catalytic particles entrapped within the synthetic fibres, coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 5911 90 90<br>ex 8421 99 00 | 30<br>92 | Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness of not more than 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more | 0 % | 1.1.2010-31.12.2013 |
| *ex 5911 90 90 | 40 | Multi-layered non-woven polyester polishing pads, impregnated with polyurethane | 0 % | 1.1.2010-31.12.2014 |
| ex 6805 10 00<br>ex 6805 20 00<br>ex 6805 30 80 | 10<br>10<br>10 | Abrasive in the form of identically shaped particles on a support | 0 % | 1.1.2010-31.12.2013 |
| ex 6813 89 00 | 10 | Friction material, of a thickness of less than 20 mm, not mounted, for the manufacture of friction components of a kind used in automatic transmissions and clutches (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 6903 90 90 | 20 | Silicon carbide reactor tubes and holders, of a kind used for insertion into diffusion and oxidation furnaces for production of semiconductor materials | 0 % | 1.1.2010-31.12.2013 |
| ex 6909 19 00 | 30 | Supports for catalysts, consisting of porous cordierite or mullite ceramic pieces, of an overall volume of not more than 65 l, having, per $cm^2$ of the cross-section, not less than one continuous channel which may be open at both ends or stopped at one end | 0 % | 1.1.2010-31.12.2013 |
| ex 6909 19 00<br>ex 6914 90 90 | 50<br>20 | Ceramic articles made of continuous filaments of ceramic oxides, containing by weight:<br>— 2 % or more of diboron trioxide,<br>— 28 % or less of silicon dioxide and<br>— 60 % or more of dialuminium trioxide | 0 % | 1.1.2010-31.12.2013 |
| ex 6909 19 00 | 60 | Supports for catalysts, consisting of porous ceramic pieces, of a blend of silicon carbide and silicon, with a hardness of less than 9 on the Mohs scale, with a total volume of not more than 65 litres, having, per $cm^2$ of the surface of the cross section one or more closed channels at the tail end | 0 % | 1.1.2010-31.12.2013 |
| ex 6914 90 90 | 30 | Ceramic microspheres, transparent, obtained from silicon dioxide and zirconium dioxide, of a diameter of more than 125 μm | 0 % | 1.1.2010-31.12.2013 |
| ex 7002 10 00 | 10 | Balls of E-glass, of a diameter of 18,5 mm or more but not more than 26 mm | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 7005 10 25 | 10 | Float glass:<br>— of a thickness of 2,0 mm or more but not more than 2,4 mm,<br>— coated on one surface with a fluorine doped tin dioxide reflective layer | 0 % | 1.1.2010-31.12.2012 |
| ex 7005 10 30 | 10 | Float glass:<br>— of a thickness of 4,0 mm or more but not more than 4,2 mm,<br>— with a light transmission of 91 % or more measured using a D-type light source,<br>— coated on one surface with a fluorine doped tin dioxide reflective layer | 0 % | 1.1.2010-31.12.2012 |
| ex 7006 00 90 | 50 | Glass plate of a diagonal size of 81 cm or more, but not more than 186 cm, provided either with a mesh film or a sputtered conductive layer for EMC shielding and a near-infrared absorbing film, with optional additional anti-reflex/colour enhancement layers on one or both sides | 0 % | 1.1.2010-31.12.2013 |
| ex 7006 00 90<br>ex 8529 90 92 | 60<br>46 | Soda-lime glass plates with:<br>— a strain point of more than 570 °C<br>— a thickness of 1,7 mm or more but not more than 2,9 mm<br>— dimensions of 1 144 mm (± 0,5 mm) × 670 mm (± 0,5 mm) or 1 164 mm (± 0,5 mm) × 649 mm (± 0,5 mm)<br>and<br>— whether or not containing:<br>— an Indium-Tin Oxide film, or<br>— a grid of electrodes made from silver paste covered by dielectric material | 0 % | 1.1.2010-31.12.2012 |
| ex 7007 19 20 | 10 | Glass plate of a diagonal size of 81,28 cm (± 1,5 cm) or more, but not more than 185,42 cm (± 1,5 cm), consisting of tempered glass; provided either with a mesh film and a near-infrared absorbing film or a sputtered conductive layer, with optional additional anti-reflex layer on one or both sides, for use in the manufacture of products falling within heading 8528 [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 7007 19 20 | 20 | Tempered or semi-tempered glass plate of a diagonal size of 81 cm or more, but not more than 186 cm, with one or more polymer layers, whether or not painted or with coloured or black ceramics around the surrounding edges, for use in the manufacture of goods falling within heading 8528 [1] | 0 % | 1.1.2010-31.12.2012 |
| ex 7007 29 00 | 10 | Glass plate of a diagonal size of 81,28 cm (± 1,5 cm) or more, but not more than 185,42 cm (± 1,5 cm), consisting of 2 sandwich plates laminated together; provided either with a mesh film and a near-infrared absorbing film or a sputtered conductive layer, with optional additional anti-reflex layer on one or both sides | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 7011 10 00 | 10 | Glass lenses with a stippled front refractor or with a front refractor composed of prismatic elements, with an external diameter of more than 121 mm but not more than 125 mm | 0 % | 1.1.2010-31.12.2013 |
| 7011 20 00 | | Glass envelopes (including bulbs and tubes), open, and glass parts thereof, without fittings, for cathode ray tubes | 0 % | 1.1.2010-31.12.2013 |
| ex 7014 00 00 | 10 | Optical elements of glass (other than those of heading No 7015), not optically worked, other than signalling glassware | 0 % | 1.1.2010-31.12.2013 |
| ex 7019 12 00 | 10 | Rovings, measuring 2 600 tex or more but not more than 3 300 tex and of a loss on ignition of 4 % or more but not more than 8 % by weight (as determined by the ASTM D 2584-94 method) | 0 % | 1.1.2010-31.12.2013 |
| ex 7019 12 00 | 15 | Rovings, measuring 650 tex or more but not more than 2 500 tex, coated with a layer of polyurethane whether or not mixed with other materials | 0 % | 1.1.2010-31.12.2013 |
| ex 7019 12 00 | 50 | Rovings, measuring 392 tex or more but not more than 2 884 tex, coated with a layer of an acrylic copolymer | 0 % | 1.1.2010-31.12.2013 |
| ex 7019 12 00 | 70 | Rovings, measuring 417 tex or more but not more than 3 180 tex, coated with a layer of poly(sodium acrylate) and poly(acrylic acid) | 0 % | 1.1.2010-31.12.2013 |
| ex 7019 19 10 | 10 | Yarn of 33 tex or a multiple thereof (± 7,5 %), obtained from continuous spun-glass filaments of a nominal diameter of 3,5 µm or of 4,5 µm, in which filaments of a diameter of 3 µm or more but not more than 5,2 µm predominate, other than those treated so as to improve their adhesion to elastomers | 0 % | 1.1.2010-31.12.2013 |
| ex 7019 19 10 | 30 | Yarn of E-glass of 22 tex (± 1,6 tex), obtained from continuous spun-glass filaments of a nominal diameter of 7 µm, in which filaments of a diameter of 6,35 µm or more but not more than 7,61 µm predominate | 0 % | 1.1.2010-31.12.2013 |
| ex 7019 19 10<br>ex 7019 90 99 | 60<br>30 | High modulus glass cord (K) impregnated with rubber, obtained from twisted high modulus glass filament yarns, coated with a latex comprising a resorcinol-formaldehyde resin with or without vinylpyridine and/or hydrogenated acrylonitrile-butadiene rubber (HNBR) | 0 % | 1.1.2010-31.12.2013 |
| ex 7019 19 10<br>ex 7019 90 99 | 70<br>20 | Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formaldehyde-vinylpyridine resin and an acrylonitrile-butadiene rubber (NBR) | 0 % | 1.1.2010-31.12.2013 |
| ex 7019 19 10<br>ex 7019 90 99 | 80<br>10 | Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formaldehyde resin and chlorosulphonated polyethylene | 0 % | 1.1.2010-31.12.2013 |
| ex 7019 39 00 | 50 | Non-woven product of non-textile glass fibre, for the manufacture of air filters [1] | 0 % | 1.1.2010-31.12.2011 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 7019 40 00 | 10 | Woven fabrics of rovings, impregnated with epoxy resin, with a coefficient of thermal expansion between 30 °C and 120 °C (measured according to IPC-TM-650) of<br>— 10 ppm per °C or more, but not more than 12 ppm per °C in the length and width and<br>— 20 ppm per °C or more, but not more than 30 ppm per °C in the thickness, with a glass transition temperature of 152 °C or more, but not more than 153 °C (measured according IPC-TM-650) | 0 % | 1.1.2010-31.12.2013 |
| ex 7019 90 10 | 10 | Non-textile glass fibres in which fibres of a diameter of less than 4,6 µm predominate | 0 % | 1.1.2010-31.12.2013 |
| ex 7201 10 11 | 10 | Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm | 0 % | 1.1.2010-31.12.2011 |
| ex 7201 10 30 | 10 | Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm, containing by weight not more than 1 % of silicon | 0 % | 1.1.2010-31.12.2011 |
| 7202 50 00 | | Ferro-silico-chromium | 0 % | 1.1.2010-31.12.2013 |
| ex 7320 90 10 | 91 | Flat spiral spring of tempered steel, with:<br>— a thickness of 2,67 mm or more, but not more than 4,11 mm,<br>— a width of 12,57 mm or more, but not more than 16,01 mm,<br>— a torque of 18,05 Nm or more, but not more than 73,5 Nm<br>— an angle between the free position and the nominal position in exercise of 76 ° or more, but not more than 218 °<br>for use in the manufacture of tensioners for power transmission belts, for internal combustion engines [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 7326 20 80 | 20 | Metal fleece, consisting of a mass of stainless steel wires of diameters ranging from 0,022 mm to 0,070 mm, compacted by sintering and rolling | 0 % | 1.1.2010-31.12.2011 |
| ex 7410 11 00<br>ex 7410 21 00 | 10<br>60 | Copper foil of a thickness of not more than 0,15 mm, coated with resin, free of halogen, with:<br>— a decomposition temperature of 350 °C or more (measured according to ASTM D 3850) and<br>— a time to delamination at 260 °C of more than 40 minutes and at 288 °C of more than 5 minutes (measured according to IPC-TM-650) | 0 % | 1.1.2010-31.12.2013 |
| ex 7410 21 00 | 10 | Sheet or plate of polytetrafluoroethylene, containing aluminium oxide or titanium dioxide as filler or reinforced with glass-fibre fabric, covered on both sides with copper foil | 0 % | 1.1.2010-31.12.2013 |
| ex 7410 21 00 | 30 | Film of polyimide, not containing epoxide resin and/or glass fibre, covered on one side or on both sides with a copper foil | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 7410 21 00 | 40 | Sheet or plates<br>— consisting of at least a central layer of paper or one central sheet of any type of nonwoven fibre, laminated on each side with glass-fibre fabric and impregnated with epoxide resin, or<br>— consisting of multiple layers of paper, impregnated with phenolic resin,<br>coated on one or both sides with a copper film with a maximum thickness of 0,15 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 7410 21 00 | 50 | Plates<br>— consisting of at least one layer of fibreglass fabric impregnated with epoxide resin,<br>— covered on one or both sides with copper foilwith a thickness of not more than 0,15 mm and<br>— with a dielectric constant (DK) of less than 3,9 and a loss factor (Df) of less than 0,015 at a measuring frequency of 10 GHz, as measured according to IPC-TM-650 | 0 % | 1.1.2010-31.12.2013 |
| ex 7419 99 90<br><br>ex 7616 99 90 | 91<br><br>60 | Disc (target) with deposition material, consisting of molybdenum silicide:<br>— containing 1 mg/kg or less of sodium and<br>— mounted on a copper or aluminium support | 0 % | 1.1.2010-31.12.2013 |
| ex 7601 20 99 | 10 | Sheets and billets of secondary aluminium alloy containing lithium | 0 % | 1.1.2010-31.12.2012 |
| ex 7604 21 00<br><br>ex 7604 29 90 | 10<br><br>30 | Profiles made of aluminium alloy conforming to EN standard AW-6063 T5<br>— anodized<br>— whether or not lacquered<br>— with a wall thickness of 0,5 mm (± 1,2 %) or more but not more than 0,8 mm (± 1,2 %)<br>for use in the manufacture of goods of subheading 8302<br>(1) | 0 % | 1.1.2010-31.12.2013 |
| ex 7605 19 00 | 10 | Not alloyed aluminium wire, of a diameter of 2 mm or more but not more than 6 mm, covered with a layer of copper of a thickness of 0,032 mm or more but not more than 0,117 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 7606 12 10 | 10 | Strip of an alloy of aluminium and magnesium, containing by weight: | 0 % | 1.1.2010-31.12.2012 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 7607 11 90 | 20 | — 93,3 % or more of aluminium,<br>— 2,2 % or more but not more than 5 % of magnesium, and<br>— not more than 1,8 % of other elements,<br>in rolls, of a thickness of 0,14 mm or more but not more than 0,40 mm and a width of 12,5 mm or more but not more than 89 mm, with a tensile strength of 285 N/mm$^2$ or more and an elongation at break of 1,0 % or more | | |
| ex 7607 11 90 | 10 | Plain aluminium foil with the following parameters:<br>— an aluminium content of 99,98 % or more<br>— a thickness of 0,070 mm or more but not more than 0,115 mm<br>— with a cubic texture<br>of a kind used for high voltage etching (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 7607 20 99 | 10 | Aluminium laminated film of a total thickness of not more than 0,123 mm, comprising of a layer of aluminium of a thickness of not more than 0,040 mm, polyamide and polypropylene base films, and a protective coating against corrosion by hydrofluoric acid, for use in the manufacture of lithium polymer batteries (1) | 0 % | 1.1.2010-31.12.2012 |
| ex 7613 00 00 | 20 | Aluminium container, seamless, for compressed natural gas or compressed hydrogen, wholly embedded in an overwrap of epoxy-carbon fibres composite, of a storage capacity of 172 l (± 10 %) and an unfilled weight of not more than 64 kg | 0 % | 1.1.2010-31.12.2013 |
| ex 7616 99 90 | 15 | Honeycomb aluminium blocks of the type used in the manufacture of aircraft parts | 0 % | 1.1.2010-31.12.2013 |
| 8104 11 00 | | Unwrought magnesium, containing at least 99,8 % by weight of magnesium | 0 % | 1.1.2010-31.12.2013 |
| ex 8104 90 00 | 10 | Ground and polished magnesium sheets, of dimensions not more than 1 500 × 2 000 mm, coated on one side with an epoxy resin insensitive to light | 0 % | 1.1.2010-31.12.2013 |
| ex 8108 20 00 | 10 | Titanium sponge | 0 % | 1.1.2010-31.12.2013 |
| ex 8108 20 00 | 20 | Titanium alloy ingots | 0 % | 1.1.2010-31.12.2013 |
| ex 8108 20 00 | 30 | Titanium powder of which 90 % by weight or more passes through a sieve with an aperture of 0,224 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 8108 30 00 | 10 | Waste and scrap of titanium and titanium alloys, except those containing by weight 1 % or more but not more than 2 % of aluminium | 0 % | 1.1.2010-31.12.2013 |
| *ex 8108 90 30 | 10 | Titanium alloy rods complying with standard EN 2002-1, EN 4267 or DIN 65040 | 0 % | 1.1.2010-31.12.2014 |
| ex 8108 90 30 | 20 | Bars, rods and wire of alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, for use in the manufacture of silencers and exhaust pipes of subheadings 8708 92 or 8714 19 (1) | 0 % | 1.1.2010-31.12.2012 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 8108 90 50 | 10 | Alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, in sheets or rolls, of a thickness of 0,49 mm or more but not more than 3,1 mm, of a width of 1 000 mm or more but not more than 1 254 mm, for the manufacture of goods of subheading 8714 19 00 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8108 90 50 | 20 | Alloy of titanium, aluminium and vanadium, containing by weight 2,5 % or more but not more than 3,5 % of aluminium and 2,0 % or more but not more than 3,0 % of vanadium, in sheets or rolls, of a thickness of 0,6 mm or more but not more than 0,9 mm, of a width of not more than 1 000 mm, for the manufacture of goods of subheading 8714 19 00 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8108 90 50 | 30 | Alloy of titanium and silicon, containing by weight 0,15 % or more but not more than 0,60 % of silicon, in sheets or rolls, for use in the manufacture of:<br>— exhaust systems for internal combustion engines or<br>— tubes and pipes of subheading 8108 90 60<br>(1) | 0 % | 1.1.2010-31.12.2012 |
| ex 8108 90 50 | 40 | Titanium-alloy sheets for the manufacture of structural parts of aircrafts (1) | 0 % | 1.1.2010-31.12.2012 |
| ex 8108 90 50 | 50 | Plates, sheets, strips and foils of an alloy of titanium, copper and niobium, containing by weight 0,8 % or more but not more than 1,2 % of copper and 0,4 % or more but not more than 0,6 % of niobium | 0 % | 1.1.2010-31.12.2012 |
| ex 8108 90 50 | 60 | Plates, sheets, strips and foils of an alloy of titanium, aluminium, silicon and niobium, containing by weight:<br>— 0,4 % or more but not more than 0,6 % of aluminium,<br>— 0,35 % or more but not more than 0,55 % of silicon and<br>— 0,1 % or more but not more than 0,3 % of niobium | 0 % | 1.1.2010-31.12.2013 |
| ex 8109 20 00 | 10 | Non-alloy zirconium, in the form of ingots, containing by weight more than 0,01 % of hafnium, for use in the manufacture of tubes for the chemical industry (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8110 10 00 | 10 | Antimony in the form of ingots | 0 % | 1.1.2010-31.12.2013 |
| ex 8112 99 30 | 10 | Alloy of niobium (columbium) and titanium, in the form of bars and rods | 0 % | 1.1.2010-31.12.2013 |
| ex 8113 00 90 | 10 | Carrier plate of aluminium silicon carbide (AlSiC-9) for electronic circuits | 0 % | 1.1.2010-31.12.2012 |
| ex 8305 20 00 | 10 | Staples of a width of 12 mm (± 1 mm) and a depth of 8 mm (± 1 mm) for use in copiers and printers (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8309 90 90 | 10 | Aluminium can ends with so-called "ring pull" full aperture with a diameter of 136,5 mm (± 1 mm) | 0 % | 1.1.2010-31.12.2013 |
| ex 8401 30 00 | 20 | Non-irradiated hexagonal fuel modules (elements) for use in nuclear reactors (1) | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 8405 90 00<br>ex 8708 21 10<br>ex 8708 21 90 | 10<br>10<br>10 | Metal casing for automobile safety belt pre-tension gas generators | 0 % | 1.1.2010-31.12.2014 |
| ex 8407 31 00 | 10 | Two stroke internal combustion engines, of a cylinder capacity of not more than 30 $cm^3$ for use in the manufacture of portable motorised scooters falling within subheading 8711 10 00 (1) | 0 % | 1.1.2010-31.12.2012 |
| *ex 8407 33 00<br>ex 8407 90 80<br>ex 8407 90 90 | 10<br>10<br>10 | Spark-ignition reciprocating or rotary internal combustion piston engines, having a cylinder capacity of not less than 300 $cm^3$ and a power of not less than 6 kW but not exceeding 20,0 kW, for the manufacture of:<br>— self-propelled lawn mowers, with a seat of sub-heading 8433 11 51<br>— tractors of subheading 8701 90 11, whose main function is that of a lawn mower<br>— four stroke mowers with motor of a cylinder capacity of not less than 300 cc of subheading 8433 20 10 or<br>— snowploughs and snow blowers of subheading 8430 20<br>(1) | 0 % | 1.1.2010-31.12.2012 |
| ex 8407 90 10 | 10 | Four-stroke petrol engines of a cylinder capacity of not more than 250 $cm^3$ for use in the manufacture of lawnmowers of sub-heading 8433 11, mowers with motor of subheading 8433 20 10, rotovators of sub-heading 8432 29 50, garden shredders of sub-heading 8436 80 90 or scarifiers of subheading 8432 29 10 (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 8407 90 10 | 20 | Two-stroke internal combustion engines, having a cylinder capacity of not more than 125 $cm^3$, for the manufacture of lawnmowers of sub-heading 8433 11 or snowploughs and snow blowers of subheading 8430 20 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8408 90 41 | 20 | Diesel engines of a power of not more than 15 kW, with 2 or 3 cylinders, for use in the manufacture of vehicle mounted temperature control systems (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8408 90 43 | 20 | Diesel engines of a power of not more than 30 kW, with 4 cylinders, for use in the manufacture of vehicle mounted temperature control systems (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8413 91 00 | 20 | Manganese-silicon-bronze swash plates with a copper content of 58 % or more but not more than 63 % by weight for incorporation into fluid pumps for air conditioners of motor vehicles | 0 % | 1.1.2010-31.12.2011 |
| ex 8414 30 89 | 20 | Vehicle air conditioning system part, consisting of an open shaft reciprocating compressor of a power of more than 0,4 kW but not more than 10 kW | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 8414 59 20 | 30 | Axial fan:<br>— with an electric motor,<br>— of an output of not more than 125 W<br>for use in the manufacture of computers (1) | 0 % | 1.1.2010-31.12.2013 |
| *ex 8414 90 00 | 20 | Aluminium pistons, for incorporation into compressors of air conditioning machines of motor vehicles (1) | 0 % | 1.1.2010-31.12.2014 |
| ex 8414 90 00 | 30 | Pressure-regulating system, for incorporation into compressors of air conditioning machines of motor vehicles (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8414 90 00 | 40 | Drive part, for compressors of air conditioning machines of motor vehicles (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8414 90 00 | 50 | Cross-flow fan, of 97,4 mm (± 0,2 mm) diameter and 645 mm (± 1 mm) or 873 mm (+ 0,5/- 1 mm) height made from anti-static, anti-bacterial and heat-resistant, glass fiber reinforced plastic with a minimum temperature resistance of 70 °C, for use in the manufacture of indoor air conditioning units (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 8415 90 00 | 20 | Evaporator made of aluminium for use in the manufacture of air conditioning machines for automobiles (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 8419 89 98 | 30 | Apparatus for vapour deposition of parylene for use in the manufacture of drug eluting stents (1) | 0 % | 1.1.2010-31.12.2012 |
| ex 8419 89 98 | 40 | Solution preparation apparatus for the treatment of materials by a process involving a change of temperature for use in the manufacture of drug-eluting stents (1) | 0 % | 1.1.2010-31.12.2012 |
| ex 8421 99 00 | 91 | Parts of equipment, for the purification of water by reverse osmosis, consisting of a bundle of hollow fibres of artificial plastic material with permeable walls, embedded in a block of artificial plastic material at one end and passing through a block of artificial plastic material at the other end, whether or not housed in a cylinder | 0 % | 1.1.2010-31.12.2013 |
| ex 8421 99 00 | 93 | Components of separators for the separation or purification of gases from gas mixtures, consisting of a bundle of permeable hollow fibres enclosed within a container, whether or not perforated, of an overall length of 300 mm or more but not more than 3 700 mm and a diameter of not more than 500 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 8422 30 00<br>ex 8479 89 97 | 10<br>30 | Machines and apparatus, other than injection moulding machines, for the manufacture of ink-jet printer cartridges (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8439 99 10<br>ex 8439 99 90 | 10<br>10 | Suction-roll shells, produced by centrifugal casting, not drilled, in the form of alloy-steel tubes, of a length of 3 000 mm or more and an external diameter of 550 mm or more | 0 % | 1.1.2010-31.12.2013 |
| ex 8462 21 80 | 10 | Numerically controlled stent crimping machine comprising a base, a pneumatic crimp head and a motorised product positioning mechanism (V-block) to crimp a stent onto the balloon of a catheter using radial pressure in the manufacture of drug eluting stents (1) | 0 % | 1.1.2010-31.12.2012 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 8467 99 00<br><br>ex 8536 50 11 | 10<br><br>35 | Mechanical switches for connecting electrical circuits, with:<br><br>— a voltage of 14,4 V or more but not more than 42 V,<br>— an amperage of 10 A or more but not more than 42 A,<br>for use in the manufacture of machines falling within heading 8467<br>(1) | 0 % | 1.1.2010-31.12.2014 |
| ex 8477 59 80 | 10 | Machinery for working rubber or plastic for use in the manufacture of drug-eluting stents (1) | 0 % | 1.1.2010-31.12.2012 |
| ex 8477 80 99 | 10 | Machines for casting or for surface modification of plastic membranes of heading No 3921 | 0 % | 1.1.2010-31.12.2013 |
| *ex 8479 89 97 | 40 | Isobaric pressure exchanger with a flow rate of not more than 50 $m^3$/hr, whether or not with a booster pump | 0 % | 1.1.2010-31.12.2014 |
| *ex 8481 30 91 | 91 | Steel check (non-return) valves with:<br>— an opening pressure of not more than 800 kPa<br>— an external diameter not more than 37 mm | 0 % | 1.1.2010-31.12.2014 |
| ex 8481 80 59 | 10 | Air control valve, consisting of a stepping motor and a valve pintle, for the regulation of idle air flow in fuel injection engines | 0 % | 1.1.2010-31.12.2013 |
| ex 8481 80 79 | 20 | Solenoid valve device that can withstand a pressure of 875 bar | 0 % | 1.1.2010-31.12.2013 |
| ex 8481 80 99 | 50 | Service valve, consisting a combination of a two way valve on the liquid line and a three way valve on the gas line with:<br>— a minimum enclosing pressure of 30 kgf/$cm^2$,<br>— a minimum withstanding pressure of 45 kgf/$cm^2$,<br>for use in the manufacture of outdoor air conditioning units (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 8481 80 99 | 60 | Four way valve, consisting of:<br>— a core plunger,<br>— a sealing plunger,<br>— a 220 V-240 V AC 50/60 Hz solenoid coil,<br>— a working pressure up to 4,3 Mpa,<br>— a housing<br>for directing the flow of the refrigerant, for use in the manufacture of outdoor air conditioning units (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 8483 40 51 | 20 | Gear box, having a differential with wheel axle, for use in the manufacture of self-propelled lawnmowers with a seat of subheading 8433 11 51 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8483 40 59 | 20 | Hydrostatic speed changer, having a hydro pump and a differential with wheel axle, for use in the manufacture of self-propelled lawnmowers with a seat of subheading 8433 11 51 (1) | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 8501 10 93 | 20 | Single phased 50 Hz, AC motor driven by permanent single capacitor and having a power output of less than 37 W, for use in the manufacture of indoor split air conditioning units (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 8501 10 99 | 54 | DC motor, brushless, with an external diameter of not more than 25,4 mm, a rated speed of 2 260 (± 15 %) or 5 420 (± 15 %) rpm, a supply voltage of 1,5 V or 3 V | 0 % | 1.1.2010-31.12.2013 |
| ex 8501 10 99 | 79 | DC motor with brushes and an internal rotor with a three-phase winding, of a specified temperature range covering at least – 20 °C to + 70 °C | 0 % | 1.1.2010-31.12.2013 |
| ex 8501 10 99 | 80 | DC stepping motor, with:<br>— an angle of step of 7,5 ° (± 0,5 °),<br>— a pull-out torque at 25 °C of 25 mNm or more,<br>— a pull-out pulse rate of 1 960 pps or more,<br>— a two-phase winding, and<br>— a rated voltage of 10,5 V or more, but not more than 16,0 V | 0 % | 1.1.2010-31.12.2013 |
| ex 8501 10 99 | 81 | DC stepping motor, with an angle of step of 18 ° or more, a holding torque of 0,5 mNm or more, a coupling bracket the exterior dimensions of which do not exceed 22 × 68 mm, a two phase winding and an output of not more than 5 W | 0 % | 1.1.2010-31.12.2013 |
| ex 8501 10 99 | 82 | DC motor, brushless, with an external diameter of not more than 29 mm, a rated speed of 1 500 (± 15 %) or 6 800 (± 15 %) rpm, a supply voltage of 2 V or 8 V | 0 % | 1.1.2010-31.12.2013 |
| ex 8501 31 00 | 30 | DC motor, brushless, with a three-phase winding, an external diameter of 85 mm or more, but not more than 115 mm, a nominal torque of 2,23 Nm (± 1,0 Nm), of an output of more than 120 W but not more than 520 W, calculated with 1 550 RPM (± 350 RPM) at a supply voltage of 12 V equipped with electronic circuit with sensors using the Hall effect, for use with an electric power steering control module (power steering motor) (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 8503 00 91<br>ex 8503 00 99 | 31<br>32 | Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring | 0 % | 1.1.2010-31.12.2013 |
| ex 8503 00 99 | 31 | Stamped collector of an electric motor, having an external diameter of not more than 16 mm | 0 % | 1.1.2010-31.12.2013 |
| *ex 8503 00 99 | 33 | Stator for brushless motor of electrical power steering with a roundness tolerance of 50 µm | 0 % | 1.1.2010-31.12.2011 |
| *ex 8503 00 99 | 34 | Rotor for brushless motor of electrical power steering with a roundness tolerance of 50 µm | 0 % | 1.1.2010-31.12.2011 |
| *ex 8503 00 99 | 35 | Transmitter resolver for brushless motors of electrical power steering | 0 % | 1.1.2010-31.12.2014 |
| ex 8504 31 80 | 20 | Transformer for use in the manufacture of inverters in LCD modules (1) | 0 % | 1.1.2010-31.12.2012 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 8504 31 80 | 30 | Switching transformers, having a power handling capacity of not more than 1 kVA for use in the manufacture of static converters (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8504 40 90 | 20 | Direct current to direct current converter | 0 % | 1.1.2010-31.12.2013 |
| ex 8504 40 90 | 30 | Static converter comprising a power switch with insulated-gate bipolar transistors (IGBTs), contained in a housing, for use in the manufacture of microwave ovens of subheading 8516 50 00 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8504 40 90 | 40 | Static converters for use in the manufacture of single-phase electric motor controls with a power supply of not more than 3 kW (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8504 50 95 | 20 | Inductor with an inductance of not more than 62 mH | 0 % | 1.1.2010-31.12.2013 |
| ex 8504 50 95 | 30 | Multilayer monolithic inductors, contained in a housing of the SMD (surface mounted device) type the exterior dimensions of which do not exceed 1,8 × 3,4 mm, for use in the manufacture of products falling within subheading 8517 11 00, 8517 12 00 or 8517 69 31 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8504 90 11 | 10 | Ferrite cores, other than for deflection yokes | 0 % | 1.1.2010-31.12.2013 |
| ex 8504 90 18 | 40 | Trans coil for boosting DC voltage and isolating high and low voltages for use in the manufacture of products falling within subheading 8504 31 80 (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 8505 11 00 | 31 | Ferrite magnet having a remanence of 455 mT (± 15 mT) | 0 % | 1.1.2010-31.12.2013 |
| ex 8505 11 00 | 33 | Magnets consisting of an alloy of neodymium, iron and boron, either in the shape of a rounded rectangle with measurements of not more than 15 × 10 × 2 mm, or in the shape of a disc with a diameter of not more than 90 mm, whether or not containing a hole in the centre | 0 % | 1.1.2010-31.12.2013 |
| ex 8505 19 90 | 31 | Neodymium-ferro ring with an external diameter of not more than 13 mm, an internal diameter of not more than 9 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 8505 20 00 | 30 | Electromagnetic clutch, for use in the manufacture of compressors of air conditioning machines of motor vehicles (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8505 90 10 | 91 | Solenoid with a plunger, operating at a nominal supply voltage of 24 V at a nominal DC of 0,08 A, for use in the manufacture of products falling within heading No 8517 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8506 50 90 | 10 | Lithium iodine single cell battery the dimensions of which do not exceed 9 × 23 × 45 mm and a voltage of not more than 2,8 V | 0 % | 1.1.2010-31.12.2013 |
| ex 8506 50 90 | 20 | Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit | 0 % | 1.1.2010-31.12.2013 |
| ex 8506 50 90 | 30 | Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions of not more than 28 × 45 × 15 mm and a capacity of not less than 1,05 Ah | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 8507 30 20 | 30 | Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm (± 1,5 mm) and a diameter of 14,5 mm (± 1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8507 80 20<br>ex 8507 80 30 | 20<br>20 | Rectangular accumulator, with a length of not more than 69 mm, a width of not more than 36 mm and a thickness of not more than 12 mm, for use in the manufacture of rechargeable batteries (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8507 80 20 | 30 | Cylindrical nickel-hydride accumulator, of a diameter of not more than 14,5 mm, for the manufacture of rechargeable batteries (1) | 0 % | 1.1.2010-31.12.2013 |
| *ex 8507 80 30 | 30 | Cylindrical lithium-ion accumulator, with a length of 63 mm or more and a diameter of 17,2 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (1) | 0 % | 1.1.2010-31.12.2014 |
| ex 8507 80 30 | 40 | Rectangular lithium-ion-accumulator, with<br>— a length of 80 mm or more, but not more than 1 000 mm,<br>— a width of 25 mm or more, but not more than 150 mm,<br>— a height of 100 mm or more, but not more than 500 mm,<br>— a weight of 0,5 kg or more, but not more than 30 kg,<br>— a capacity of 20 Ah or more, but not more than 1 000 Ah,<br>for use in the manufacture of rechargeable power-supply units for incorporation into goods of heading No 8903 (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 8507 80 30 | 50 | Lithium-ion-accumulator, with a distance between the poles of 55 mm or more, for use in the manufacture of rechargeable power-supply units for incorporation in electric motorcycles of subheading No 8711 90 (1) | 0 % | 1.1.2010-31.12.2012 |
| ex 8518 30 95 | 20 | Headphone and earphone for hearing aids, contained in a housing the exterior dimensions of which, excluding connecting points, do not exceed 5 × 6 × 8 mm | 0 % | 1.1.2010-31.12.2013 |
| *ex 8518 40 89 | 91 | Circuit Board sub-assembly, comprising digital audio signal decoding, audio signal processing and amplification with dual and/or multi-channel functionality | 0 % | 1.1.2010-31.12.2014 |
| ex 8518 90 00 | 91 | Integrally cold-upsetted steel coreplate, in the form of a disk on one side provided with a cylinder, for use in the manufacture of loudspeakers (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8519 81 35 | 10 | Unmounted or incomplete assembly, comprising at least one optical unit and DC motors and operational control circuit, with digital/analogue converter, for use in the manufacture of CD players, radio-broadcast receivers of a kind used in motor vehicles or navigational aid apparatus (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8522 90 49 | 50 | Electronic assembly for a laser read-head of a compact disc player, comprising:<br>— a printed circuit,<br>— a photo-detector, in the form of a monolithic integrated circuit, contained in a housing, | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| | | — not more than 3 connectors,<br>— not more than 1 transistor,<br>— not more than 3 variable and 4 fixed resistors,<br>— not more than 5 capacitors,<br>the whole mounted on a support | | |
| ex 8522 90 49 | 70 | Assembly, comprising at least a flexible printed circuit, a laser driver integrated circuit and a signal converter integrated circuit | 0 % | 1.1.2010-31.12.2013 |
| ex 8522 90 80 | 65 | Assembly for optical discs, comprising at least an optical unit and DC motors, whether or not capable of double layer recording | 0 % | 1.1.2010-31.12.2013 |
| ex 8522 90 80 | 70 | Video tape recording/reproducing assembly comprising at least a motor and a printed circuit board containing integrated circuits with driver or control functions, whether or not incorporating a transformer, for use in the manufacture of products falling within heading No 8521 [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 8522 90 80 | 75 | Optical reading head for CD player, consisting of one laser diode, one photodetector integrated circuit and one beam splitter | 0 % | 1.1.2010-31.12.2013 |
| ex 8522 90 80 | 80 | Laser optical drive unit assembly (so called mecha units) for the recording and/or reproduction of digital video and/or audio signals, comprising at least a laser optical reading and/or writing unit, one or more DC motors and not containing a printed circuit board or containing a printed circuit board not capable of signal processing for sounds and images, for use in the manufacture of products falling within headings No 8519, 8521, 8526, 8527, 8528 or 8543 [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 8522 90 80 | 81 | Laser optical pick up unit for the reproduction of optical signals from CD or DVD and the recording of optical signal on DVD, comprising at least<br>— a laser diode,<br>— a laser driver integrated circuit,<br>— a photo detector integrated circuit,<br>— a front monitor integrated circuit and an actuator,<br>for use in the manufacture of products falling within heading No 8521 [1] | 0 % | 1.1.2010-31.12.2011 |
| *ex 8522 90 80 | 83 | Blu-ray optical pick-up unit, whether or not recordable, for use with Blu-ray, DVD and CD discs, comprising at least:<br>— laser diodes operating at three different wavelengths,<br>— a photo detector integrated circuit,<br>— a monitor (detector) integrated circuit and<br>— an actuator,<br>for the manufacture of products falling within heading 8521 [1] | 0 % | 1.1.2010-31.12.2013 |
| *ex 8522 90 80 | 84 | Blu-ray drive mechanism, whether or not recordable, for use with Blu-ray, DVD and CD discs, comprising at least:<br>— an optical pick up unit with laser diodes operating at three different wavelengths, | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| | | — a spindle motor,<br>— a stepping motor,<br>for use in the manufacture of products falling within heading No 8521 (1) | | |
| ex 8522 90 80 | 85 | Video head drum, with video heads or with video and audio heads and an electric motor, for use in the manufacture of products falling within heading No 8521 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8522 90 80 | 95 | Drive-unit capable of magnetooptical signal recording and optical signal reproduction, comprising at least an optical unit, DC motors and a printed circuit on which are mounted integrated circuits providing drive and signal processing functions for reading optical discs having an external diameter of not more than 70 mm, not comprising circuits with amplification functions or power supply drive functions | 0 % | 1.1.2010-31.12.2013 |
| ex 8522 90 80 | 96 | Hard disk drive, for incorporation in products of heading 8521 (1) | 0 % | 1.1.2010-31.12.2012 |
| ex 8522 90 80<br>ex 8529 90 65 | 97<br>50 | Tuner transforming high-frequency signals into mid-frequency signals, for use in the manufacture of products falling under No 8521 and No 8528 (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 8525 80 19 | 20 | Assembly for television cameras of dimensions of not more than 10 × 15 × 18 mm, comprising an image sensor, an objective and a color processor, having an image resolution of not more than 1 024 × 1 280 pixel, whether or not fitted with cable and/or housing, for the manufacture of goods of subheading 8517 12 00 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8525 80 19 | 30 | Compact chassis-type closed circuit television (CCTV) cameras, of a weight of not more than 250 g, whether or not contained in a housing, of dimensions of not more than 50 mm × 60 mm × 89,5 mm, with a single sensor Charge-Couple Device (CCD), with effective pixels of not more than 440 000, for use in CCTV surveillance systems (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8525 80 19 | 40 | Assembly for cameras used in computer notebooks of dimensions of not more than 15 × 25 × 25 mm, comprising an image sensor, an objective and a colour processor, having an image resolution of not more than 1 600 × 1 200 pixel, whether or not fitted with cable and/or housing, whether or not mounted on a base and containing a LED chip (1) | 0 % | 1.1.2010-31.12.2011 |
| *ex 8527 91 99<br>ex 8529 90 65 | 10<br>35 | Assembly consisting of at least:<br>— an audio frequency amplifier unit, comprising at least an audio frequency amplifier and a sound generator,<br>— a transformer and<br>— a radio broadcast receiver | 0 % | 1.1.2010-31.12.2014 |
| ex 8528 49 10 | 10 | Video monitor comprising:<br>— a flat screen monochrome cathode-ray tube with a diagonal measurement of the screen of not more than 110 mm and equipped with a deflector yoke, and | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| | | — a printed circuit on which are mounted a deflection unit, a video-amplifier and a transformer,<br>the whole mounted or not on a chassis, for the manufacture of video entry-phones, video telephones or surveillance apparatus (1) | | |
| ex 8528 59 90 | 20 | Liquid cristal display colour video monitor having a DC input voltage of 7 V or more but not more than 30 V, with a diagonal measurement of the screen of 33,2 cm or less, suitable for the incorporation into goods of chapters 84 to 90 and 94 | 0 % | 1.1.2010-31.12.2013 |
| ex 8529 10 80 | 20 | Ceramic filter package comprising 2 ceramic filters and 1 ceramic resonator for a frequency of 10,7 MHz (± 30 kHz), contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8529 10 80 | 35 | Ceramic filter for a centre frequency of 450 kHz or more but not more than 470 kHz, with a bandwidth of not more than 13 kHz at 3 dB, contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8529 10 80 | 50 | Ceramic filter for a centre frequency of 450 kHz (± 1,5 kHz) or 455 kHz (± 1,5 kHz), with a bandwidth of not more than 30 kHz at 6 dB and not more than 70 kHz at 40 dB, contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8529 10 80 | 60 | Filters, excluding surface acoustic wave filters, for a center frequency of 485 MHz or more but not more than 1 990 MHz with an insertion loss of not more than 3,5 dB, contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8529 90 65<br>ex 8548 90 90 | 30<br>44 | Parts of TV-apparatus, having micro-processor and video-processor functions, comprising at least a micro-controller and a video-processor, mounted on a leadframe and contained in a plastic housing | 0 % | 1.1.2010-31.12.2013 |
| *ex 8529 90 65 | 45 | Satellite radio receiver module transforming satellite high frequency signals to digital audio coded signal, for use in the manufacture of products falling within heading 8527 (1) | 0 % | 1.1.2010-31.12.2014 |
| ex 8529 90 65 | 60 | Tuner transforming high frequency signals to mid frequency signals for use in the manufacture of satellite or terrestrial TV receivers for set-top boxes (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 8529 90 65 | 70 | Unit driver consisting of an electronic integrated circuit and a flexible printed circuit, for use in the manufacture of LCD modules (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 8529 90 65 | 75 | Modules for driving addressing pixels, comprising at least semiconductor chips | 0 % | 1.1.2010-31.12.2012 |
| ex 8529 90 65 | 80 | Scan driver boards for generating electric pulses for scanning to certain electrodes in a glass panel, comprising at least semiconductor chips | 0 % | 1.1.2010-31.12.2012 |
| ex 8529 90 92 | 32 | Optical unit for video projection, comprising a colour separation system, a positioning mechanism and lenses, for use in the manufacture of products falling within heading No 8528 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8529 90 92 | 40 | Assembly comprising prisms, digital micromirror device (DMD) chips and electronic control circuits, for the manufacture of television projection equipments or video projectors (1) | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 8529 90 92 | 41 | Digital micromirror device (DMD)-chips, for use in the manufacture of video projectors (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8529 90 92 | 42 | Heat sinks and cooling fins of aluminium, for maintaining the operating temperature of transistors and integrated circuits in television sets (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8529 90 92 | 43 | Plasma display module incorporating only address and display electrodes, with or without driver and/or control electronics for pixel address only and with or without a power supply | 0 % | 1.1.2010-31.12.2013 |
| ex 8529 90 92 | 44 | LCD modules, solely consisting of one or more TFT glass or plastic cells, not combined with touch screen facilities, with or without backlight unit, with or without inverters and one or more printed circuit boards with control electronics for pixel addressing only | 0 % | 1.1.2010-31.12.2013 |
| ex 8529 90 92 | 45 | Integrated circuit package with TV reception functionality containing a channel decoder die, tuner die, power management die, GSM filters and discrete as well as embedded passive circuit elements for reception of digitally broadcasting videosignals of DVB-T and DVB-H formats | 0 % | 1.1.2010-31.12.2013 |
| *ex 8529 90 92 | 47 | Area image sensors (“progressive scan” Interline CCD-Sensor) for digital video cameras in the form of analogue, monolithic integrated circuit with pixels of less than 10 µm × 10 µm and with viewing panel, either polychromic or monochromic, and with a lenslet (micro lens) array with one lenslet mounted on each individual pixel | 0 % | 1.1.2010-31.12.2014 |
| *ex 8529 90 92 | 48 | Aluminium die cast heat sink, for maintaining the operating temperature of transistors and integrated circuits, for use in the manufacture of products falling within heading 8527 (1) | 0 % | 1.1.2010-31.12.2014 |
| *ex 8529 90 92<br><br>ex 8536 69 90 | 49<br><br>83 | AC Socket with a noise filter, composed of:<br><br>— AC socket (for power cord connection) of 230 V,<br>— integrated noise filter composed of capacitors and inductors,<br>— cable connector for connecting an AC Socket with the PDP Power Supply Unit,<br>whether or not equipped with a metal support, which joins the AC Socket to the PDP TV set | 0 % | 1.1.2010-31.12.2014 |
| ex 8529 90 97 | 60 | Frame for use in the manufacture of high frequency tuners (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8531 80 95 | 40 | Electro-accoustic transducer | 0 % | 1.1.2010-31.12.2013 |
| ex 8535 90 00 | 20 | Printed circuit board in the form of plates consisting of isolating material with electrical connections and solder points, for use in the manufacture of back light units for LCD modules (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8536 30 30 | 11 | Thermo-electric switch with a cut-off current of 50 A or more, comprising a snap action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 8536 49 00 | 91 | Thermal relays contained in a hermetically sealed glass cartridge of not more than 35 mm in length excluding wires, with a maximum leakage rate of $10^{-6}$ $cm^3$ He/sec at one bar in the temperature range 0 to 160 °C, to be incorporated into compressors for refrigerating equipment (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8536 50 11 | 31 | Switch of the printed circuit mount type, operating at a force of 4,9 N (± 0,9 N), contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8536 50 11 | 32 | Mechanical tact switch for connecting electronic circuits, operating at a voltage of not more than 60 V and at a current strength of not more than 50 mA, for use in the manufacture of television sets (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8536 50 19 | 91 | Hall effect switch, comprising 1 magnet, 1 Hall effect sensor and 2 capacitors, contained in a housing with 3 connections | 0 % | 1.1.2010-31.12.2013 |
| ex 8536 50 19<br>ex 8536 50 80 | 93<br>97 | Devices, having adjustable controller and switching functions, comprising one ore more monolithic integrated circuits whether or not combined with semiconductor elements, mounted together on a leadframe and contained in a plastic housing | 0 % | 1.1.2010-31.12.2013 |
| *ex 8536 50 80 | 81 | Mechanical speed governer switches for connecting electrical circuits, with:<br>— a voltage of 240 V or more but not more than 250 V,<br>— an amperage of 4 A or more but not more than 6 A,<br>for use in the manufacture of machines falling within heading 8467<br>(1) | 0 % | 1.1.2010-31.12.2014 |
| *ex 8536 50 80 | 82 | Mechanical switches for connecting electrical circuits, with:<br>— a voltage of 240 V or more but not more than 300 V,<br>— an amperage of 3 A or more but not more than 15 A,<br>for use in the manufacture of machines falling within heading 8467<br>(1) | 0 % | 1.1.2010-31.12.2014 |
| ex 8536 50 80 | 93 | Switch unit for coaxial cable, comprising 3 electromagnetic switches, with a switching time of not more than 50 ms and an actuating current of not more than 500 mA at a voltage of 12 V | 0 % | 1.1.2010-31.12.2013 |
| ex 8536 50 80 | 95 | Reed switch having a switching power of 20 W or more within the range of 17 - 43 A.turn, in the form of a glass capsule, not containing mercury, the dimensions of which do not exceed 3 × 21 mm, for use in the manufacture of automotive airbag shock-sensors (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8536 50 80 | 98 | Mechanical push-button switch for connecting electronic circuits, operating at a voltage of 220 V or more but not more than 250 V and at a current strength of not more than 5 A, for use in the manufacture of television sets (1) | 0 % | 1.1.2010-31.12.2013 |
| *ex 8536 69 90 | 81 | Pitch connector for use in the manufacture of LCD television reception apparatus (1) | 0 % | 1.1.2010-31.12.2012 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| *ex 8536 69 90 | 82 | Modular jack connector for local area networks, integrating at least:<br>— a pulse transformer, including a wide-band ferrite core,<br>— a common mode coil,<br>— a resistor,<br>— a capacitor,<br>for use in the manufacture of products falling within heading 8521 and 8528 (1) | 0 % | 1.1.2010-31.12.2014 |
| ex 8536 90 85 | 92 | Metallic stamped frame with connections | 0 % | 1.1.2010-31.12.2013 |
| ex 8536 90 85<br>ex 8544 49 93 | 94<br>10 | Elastomeric connector, of rubber or silicone, consisting of one or more conductor elements | 0 % | 1.1.2010-31.12.2013 |
| ex 8537 10 99 | 92 | Touch sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors | 0 % | 1.1.2010-31.12.2013 |
| ex 8537 10 99 | 93 | Electronic control units for a voltage of 12 V, for use in the manufacture of vehicle mounted temperature control systems (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8537 10 99<br>ex 8543 70 90 | 94<br>20 | Unit consisting of two junction field effect transistors contained in a dual lead frame housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8537 10 99<br>ex 8543 70 90 | 95<br>25 | Unit consisting of two metal oxide semiconductor field effect transistors contained in a dual lead frame housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8538 90 99 | 92 | Part of an electrothermal fuse, consisting of a tin coated copper wire attached to a cylindrical casing, the exterior dimensions of which do not exceed 5 × 48 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 8539 39 00 | 20 | Cold cathode (CCFL) or External Electrode (EEFL) fluorescent lamps, of a diameter of not more than 5 mm and with a length of more than 120 mm but not more than 1 570 mm | 0 % | 1.1.2010-31.12.2011 |
| ex 8540 11 11 | 95 | Colour cathode-ray tube with a slot mask, equipped with an electron gun and a deflection yoke and with a screen width/height ratio of 4/3 and a diagonal measurement of the screen of not more than 42 cm | 0 % | 1.1.2010-31.12.2011 |
| ex 8540 11 15 | 20 | Full square curved screen colour cathode-ray tube, equipped with an electron gun and a deflection yoke and with a screen width/height ratio of 4/3 and a diagonal measurement of the screen of 68 cm (± 2 mm) | 0 % | 1.1.2010-31.12.2011 |
| ex 8540 11 19 | 91 | Colour cathode-ray tube equipped with electron guns placed side by side (in-line technology), with a diagonal measurement of the screen of 79 cm or more | 0 % | 1.1.2010-31.12.2011 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 8540 11 19 | 93 | Colour cathode-ray tube equipped with an electron gun and a deflection yoke, with a screen width/height ratio of 4/3 and a diagonal measurement of the screen of more than 72 cm | 0 % | 1.1.2010-31.12.2013 |
| ex 8540 11 91 | 31 | Colour cathode-ray tube with a screen width/height ratio of 16/9 and a diagonal measurement of the screen of 39,8 cm (± 0,3 cm) | 0 % | 1.1.2010-31.12.2013 |
| ex 8540 20 80 | 91 | Photomultiplier consisting of a photocathode tube with 9 or 10 diodes, for light of a wavelength of 160 nm or more but not more than 930 nm, of a diameter of not more than 14 mm and a height of not more than 94 mm | 0 % | 1.1.2010-31.12.2011 |
| ex 8540 71 00 | 20 | Continuous wave magnetron with a fixed frequency of 2 460 MHz, packaged magnet, probe output, for use in the manufacture of products falling within subheading 8516 50 00 [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 8540 89 00 | 91 | Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 300 mm × 350 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons | 0 % | 1.1.2010-31.12.2013 |
| ex 8540 89 00 | 92 | Vacuum fluorescent display tube | 0 % | 1.1.2010-31.12.2013 |
| ex 8540 91 00 | 32 | Electron gun of colour cathode-ray tubes with an anode voltage of 27,5 kV or more but not more than 36 kV | 0 % | 1.1.2010-31.12.2013 |
| ex 8540 91 00 | 40 | Deflection yoke of cathode-ray tubes | 0 % | 1.1.2010-31.12.2013 |
| ex 8540 91 00 | 50 | Metal anode button to enable electrical contact with the anode inside the colour picture tube | 0 % | 1.1.2010-31.12.2013 |
| ex 8540 91 00 | 92 | Slit or slot mask, excluding masks with continuously vertical slits, with a diagonal measurement of 69 cm or less | 0 % | 1.1.2010-31.12.2011 |
| ex 8540 91 00 | 95 | Slit or slot mask ("shadow mask"), excluding masks with continuously vertical slits, with a diagonal measurement of 697,5 mm or more, but not more than 782,9 mm | 0 % | 1.1.2010-31.12.2012 |
| ex 8540 91 00 | 96 | Assembly for cathode-ray tubes with 2 or more but not more than 6 coils, a plastic support and a metal fixing ring, for the adjustment of display sharpness and/or convergence | 0 % | 1.1.2010-31.12.2013 |
| ex 8543 70 90 | 30 | Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8543 70 90 | 35 | Radio frequency (RF) modulator, operating with a frequency range of 43 MHz or more but not more than 870 MHz, capable of switching VHF and UHF signals, consisting of active and passive elements mounted on a printed circuit, contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8543 70 90 | 45 | Piezo-electric crystal oscillator with a fixed frequency, within a frequency range of 1,8 MHz to 67 MHz, contained in a housing | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 8543 70 90 | 55 | Opto-electronic circuit comprising one or more light-emitting diodes (LEDs), whether or not equipped with an integrated driving circuit, and one photodiode with amplifier circuit, whether or not with an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, whether or not with an integrated logic gate arrays circuit or other integrated circuits, contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8543 70 90 | 60 | Oscillator, with a centre frequency of 20 GHz or more but not more than 42 GHz, consisting of active and passive elements not mounted on a substrate, contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8543 70 90 | 65 | Audio recording and reproducing circuit, capable of stereo audio data storage and simultaneous record and playback, comprising 2 or 3 monolithic integrated circuits mounted on a printed circuit or a lead frame, contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8543 70 90 | 80 | Temperature compensated oscillator, comprising a printed circuit on which are mounted at least a piezo-electric crystal and an adjustable capacitor, contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8543 70 90 | 85 | Voltage controlled oscillator (VCO), other than temperature compensated oscillators, consisting of active and passive elements mounted on a printed circuit, contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8543 70 90 | 90 | Fuel cell module containing at least polymer electrolyte membrane fuel cells in a housing with an integrated cooling system, for use in the manufacture of motor vehicle propulsion systems [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 8543 90 00 | 20 | Stainless steel cathode in the form of a plate with a hanger bar, whether or not with plastic side strips | 0 % | 1.1.2010-31.12.2013 |
| ex 8543 90 00 | 30 | Assembly of products falling within heading No 8541 or 8542 mounted on a printed circuit, contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8543 90 00 | 40 | Part of an electrolysis device, consisting of a pan of nickel equipped with a wire mesh of nickel, fixed via ribs of nickel, and a pan of titanium equipped with a wire mesh of titanium, fixed via ribs of titanium, of which both pans are fixed together back to back | 0 % | 1.1.2010-31.12.2012 |
| ex 8544 42 90 | 10 | Data transmission cable capable of bit rate transmission of 600 Mbit/s or more, with:<br>— a voltage of 1,25 V (± 0,25 V)<br>— connectors fitted at each end, at least one of which contains pins with a pitch of 0,5 mm,<br>— outer screening shielding,<br>— twisted pair copper wires with an impedance of 100 Ω and a twist pitch of not more than 8 mm<br>used solely for communication between LCD panel and video processing electronic circuits | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 8544 49 93 | 20 | PET/PVC insulated flexible cable with:<br>— a voltage of not more than 60 V,<br>— a current of not more than 1 A<br>— a heat resistance of not more than 105 °C,<br>— individual wires of a thickness of 0,05 mm (± 0,01 mm) and a width of not more than 0,65 mm (± 0,03 mm)<br>— distance between conductors of not more than 0,5 mm and<br>— pitch (distance from centreline to centreline of conductors) of not more than 1,08 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 8545 19 90 | 20 | Carbon electrodes, for use in the manufacture of zinc-carbon batteries (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8547 10 10 | 10 | Insulated fitting of ceramics, containing by weight 90 % or more of aluminium oxide, metallised, in the form of a hollow cylindrical body of an external diameter of 20 mm or more but not more than 250 mm, for the manufacture of vacuum interrupters (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 8548 90 90 | 41 | Unit, consisting of a resonator operating within a frequency range of 1,8 MHz or more but not more than 40 MHz and a capacitor, contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 8548 90 90 | 43 | Contact image sensor | 0 % | 1.1.2010-31.12.2013 |
| ex 8548 90 90 | 47 | Unit consisting of two or more light emitting diode chips operating at a typical wavelength of 440 nm or more but not more than 660 nm, contained in a lead frame housing whose exterior dimensions - without fittings – do not exceed 12 × 12 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 8548 90 90 | 48 | Optical unit, consisting at least of a laserdiode and a photodiode operating at a typical wavelength of 635 nm or more but not more than 815 nm | 0 % | 1.1.2010-31.12.2013 |
| ex 8548 90 90 | 49 | LCD modules, solely consisting of one or more TFT glass or plastic cells, combined with touch screen facilities, with or without backlight unit, with or without inverters and one or more printed circuit boards with control electronics for pixel addressing only | 0 % | 1.1.2010-31.12.2013 |
| ex 8704 23 91 | 20 | Motor chassis with a self-ignition capacity of at least 8 500 $cm^3$, fitted with a cabin on either 3, 4 or 5 wheels having a wheelbase of at least 480 cm, not containing working machinery, to be built into special purpose motor vehicles with a width of at least 300 cm to distribute fertlizers (1) | 0 % | 1.1.2010-31.12.2012 |
| ex 8708 99 97 | 20 | Metal housing caps for incorporation into balancing-arms or spherical bearings used in the suspension systems for the front wheels of motor vehicles (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 9001 10 90 | 10 | Image reverser made up from an assembly of optical fibres | 0 % | 1.1.2010-31.12.2013 |
| ex 9001 20 00 | 10 | Material consisting of a polarising film, whether or not on rolls, supported on one or both sides by transparent material | 0 % | 1.1.2010-31.12.2012 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 9001 20 00<br><br>ex 9001 90 00 | 20<br><br>55 | Optical, diffuser, reflector or prism sheets, unprinted diffuser plates, whether or not possessing polarising properties, specifically cut | 0 % | 1.1.2010-31.12.2013 |
| *ex 9001 90 00 | 21 | Multi-Optical-Path (MOP) film, in rolls, based on polyethylene terephthalate (PET) material:<br>— having a total thickness of 100 µm or more, but not more than 240 µm,<br>— having a total transmittance of more than 55 % but not more than 65 %, determined by standard method JIS K7105 related to ASTM D1003 and<br>— haze more than 70 % but not more than 80 %, determined by standard method JIS K7105 related to ASTM D1003 | 0 % | 1.1.2010-31.12.2014 |
| ex 9001 90 00 | 35 | Rear projection screen, comprising a lenticular plastic plate | 0 % | 1.1.2010-31.12.2013 |
| ex 9001 90 00 | 45 | Rod of neodymium-doped yttrium-aluminium garnet (YAG) material, polished at both ends | 0 % | 1.1.2010-31.12.2013 |
| ex 9001 90 00 | 60 | Reflector or diffuser sheets in rolls | 0 % | 1.1.2010-31.12.2013 |
| *ex 9001 90 00 | 65 | Optical film with a minimum of 5 multi-layer structures, including a back side reflector, a front side coating and a contrast filter with a pitch of not more than 0,65 µm, for use in the manufacture of front projection screens [1] | 0 % | 1.1.2010-31.12.2014 |
| ex 9001 90 00 | 70 | Polyethylene terephthalate film with a thickness of less than 300 µm according to ASTM D2103, having on one side prisms of acrylic resin with a prism angle of 90 ° and a prism pitch of 50 µm | 0 % | 1.1.2010-31.12.2011 |
| ex 9001 90 00 | 75 | Front filter comprising glass panels with special printing and film coating, for use in the manufacture of plasma display modules [1] | 0 % | 1.1.2010-31.12.2012 |
| ex 9001 90 00 | 76 | Plasma display panel (PDP) filter | 0 % | 1.1.2010-31.12.2013 |
| ex 9002 11 00 | 10 | Adjustable lens unit, having a focal length of 90 mm or more but not more than 180 mm and comprising a combination of between 4 and 8 glass or methacrylic lenses with a diameter of 120 mm or more but not more than 180 mm, each lens coated on at least one side with a magnesium fluoride layer, for use in the manufacture of video projectors [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 9002 11 00 | 50 | Lens unit, having a focal length of 25 mm or more but not more than 150 mm, consisting of glass or plastic lenses, with a diameter of 60 mm or more but not more than 190 mm | 0 % | 1.1.2010-31.12.2013 |
| ex 9002 20 00 | 10 | Filter, consisting of a plastic polarising membrane, a glass plate and a transparent protective film, mounted on a metal frame, for use in the manufacture of products falling within heading 8528 [1] | 0 % | 1.1.2010-31.12.2013 |
| ex 9002 90 00 | 20 | Lens, mounted, having a fixed focal length of 3,8 mm (± 0,19 mm) or 8 mm (± 0,4 mm), with a relative aperture of F2.0 and a diameter of not more than 33 mm, for use in the manufacture of charged-coupled (CCD) cameras [1] | 0 % | 1.1.2010-31.12.2013 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 9002 90 00 | 30 | Optical unit, comprising 1 or 2 rows of optical glass fibres in the form of lenses and with a diameter of 0,85 mm or more but not more than 1,15 mm, embedded between 2 plastic plates | 0 % | 1.1.2010-31.12.2013 |
| ex 9013 20 00 | 10 | Carbon dioxide laser, stimulated by high frequency, having an output power of 12 Watt or more, but not more than 200 Watt | 0 % | 1.1.2010-31.12.2013 |
| ex 9013 20 00 | 20 | Laser head assemblies for use in the manufacture of measuring or checking machines for semiconductor wafers or devices (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 9013 20 00 | 30 | Laser for use in the manufacture of measuring or checking machines for semiconductor wafers or devices (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 9022 30 00 | 10 | X-ray tube with a target voltage of 4 kV or more but not more than 30 kV, a power of not more than 9 W and a target current of not more than 2 mA | 0 % | 1.1.2010-31.12.2013 |
| ex 9022 90 90 | 10 | Panels for x-ray apparatus (x-ray flat panel sensors/x-ray sensors) consisting of a glass plate with a matrix of thin-film transistors, covered with a film of amorphous silicon, coated with a scintillator layer of caesium iodide and a metallised protective layer, with an active surface of 409,6 $mm^2$ × 409,6 $mm^2$ and a pixel size of 200 $\mu m^2$ × 200 $\mu m^2$ | 0 % | 1.1.2010-31.12.2013 |
| ex 9027 10 90 | 10 | Sensor element for gas or smoke analysis in motor vehicles, essentially consisting of a zirconium-ceramic element in a metal housing | 0 % | 1.1.2010-31.12.2013 |
| ex 9031 80 34 | 30 | Apparatus for measuring the angle and direction of rotation of motor vehicles, consisting of at least one yaw rate sensor in the form of a monocrystalline quartz, whether or not combined with one or more measuring sensors, the whole contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 9031 80 38 | 10 | Acceleration measurement device for automotive applications, comprising one or more active and/or passive elements and one or more sensors, the whole contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| ex 9031 90 85 | 20 | Assembly for a laser align sensor, in the form of a printed circuit comprising optical filters and a charge-coupled image (CCD) sensor, the whole contained in a housing | 0 % | 1.1.2010-31.12.2013 |
| *ex 9031 90 85 | 30 | Steering angle sensor comprising:<br>— a mechanical part, which transfers the rotation of the steering wheel to the sensor and<br>— an electronic circuit with microcontroller, which detects the position of the steering wheel | 0 % | 1.1.2010-31.12.2014 |
| ex 9032 10 89 | 20 | Thermostat, damper or bimetal with,<br>— an opening temperature of + 7 °C (± 1,5 °C), closing temperature of – 4 °C (± 1,5 °C) for damper thermostat,<br>— an opening temperature of + 8 °C (± 3 °C) for bimetal thermostat;<br>for use in the manufacture of frost free refrigerators (1) | 0 % | 1.1.2010-31.12.2012 |

| CN code | TARIC | Description | Rate of autonomous duty | Validity period |
|---|---|---|---|---|
| ex 9032 89 00 | 20 | Automotive airbag shock-sensor, comprising a contact capable of switching a current of 12 A at a voltage of 30 V, having a typical contact resistance of 80 mOhm | 0 % | 1.1.2010-31.12.2013 |
| ex 9032 89 00 | 30 | Electronic controller of electric power steering (EPS controller) | 0 % | 1.1.2010-31.12.2013 |
| ex 9032 89 00 | 40 | Digital valve controller for controlling liquids and gases | 0 % | 1.1.2010-31.12.2012 |
| ex 9107 00 00 | 20 | Mechanical timer for use in the manufacture of no-frost refrigerators (1) | 0 % | 1.1.2010-31.12.2011 |
| ex 9405 40 35 | 10 | Electric light assembly of synthetic material containing 3 fluorescent tubes (RBG) of a diameter of 3,0 mm (± 0,2 mm), of a length of 420 mm (± 1 mm) or more, but not more than 600 mm (± 1 mm), for the manufacture of goods of heading 8528 (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 9405 40 39 | 10 | Ambient light module with a length of 300 mm or more, but not more than 600 mm, based on a light engine of a series of 3 or more, but not more than 9 specific one chip red green and blue light emitting diodes mounted on a PCB, with light coupled to the front and/or back of the Flat TV set (1) | 0 % | 1.1.2010-31.12.2013 |
| ex 9405 40 39 | 20 | LED array of white silicone, containing:<br>— an LED matrix module measuring 38,6 mm × 20,6 mm (± 0,1 mm), equipped with 128 red and green LED chips, and<br>— a flexible printed circuit board, equipped with a Negative Temperature Coefficient Thermistor | 0 % | 1.1.2010-31.12.2013 |
| ex 9608 91 00 | 10 | Non-fibrous plastic pen-tips with an internal channel | 0 % | 1.1.2010-31.12.2013 |
| ex 9608 91 00 | 20 | Felt tips and other porous-tips for markers, without internal canal | 0 % | 1.1.2010-31.12.2013 |
| ex 9612 10 10 | 10 | Ribbons of plastic with segments of different colours, providing the penetration of dyes by heat into a support (so called dye-sublimation) | 0 % | 1.1.2010-31.12.2013 |

(1) The relief from or reduction of customs duties shall be subject to the conditions laid down in the relevant provisions of the Union with a view to customs control of the use of such goods (see Articles 291 to 300 of Commission Regulation (EEC) No 2454/93 (OJ L 253, 11.10.1993, p. 1)).
(2) However, the measure is not allowed where processing is carried out by retail or catering undertakings.
(3) The specific additional duty is applicable.
(*) New heading, modified heading or heading for which the duration of validity has been prolonged'