COUNCIL REGULATION (EU) No 566/2010

of 29 June 2010

amending Regulation (EC) No 1255/96 temporarily suspending the autonomous Common Customs Tariff duties on certain industrial, agricultural and fishery products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

(1) It is in the interest of the Union to suspend totally the autonomous Common Customs Tariff duties on a number of new products not listed in the Annex to Regulation (EC) No 1255/96 ([1]).

(2) The CN and TARIC codes 1518 00 99 10, 3907 20 20 91, 7410 11 00 10, 7410 21 00 60 and 9031 90 85 30 for four products which are currently listed in the Annex to Regulation (EC) No 1255/96 should be deleted because it is no longer in the interest of the Union to maintain the suspension of autonomous Common Customs Tariff duties for those products.

(3) It is necessary to modify the description of twelve suspensions in the Annex to Regulation (EC) No 1255/96 in order to take account of technical product developments and economic trends on the market. Those suspensions should be deleted from the list in that Annex and reinserted as new suspensions using new descriptions. In the interest of clarity, those suspensions should be marked with an asterisk in the first column of Annex I and of Annex II to this Regulation.

(4) Experience has shown that is is necessary to provide for an expiry date to the suspensions listed in Regulation (EC) No 1255/96 to ensure that account is taken of technological and economic changes. This should not exclude the premature termination of certain measures or their continuation beyond that period, if justified by economic reasons, in accordance with the principles laid down in the Commission communication of 1998 concerning autonomous tariff suspensions and quotas ([2]).

(5) Regulation (EC) No 1255/96 should therefore be amended accordingly.

(6) Since the suspensions laid down in this Regulation should take effect from 1 July 2010, this Regulation should apply from the same date and enter into force immediately,

HAS ADOPTED THIS REGULATION:

Article 1

The Annex to Regulation (EC) No 1255/96 is hereby amended as follows:

1. the rows for the products listed in Annex I to this Regulation are inserted;

2. the rows for the products for which the CN and TARIC codes are set out in Annex II to this Regulation are deleted.

Article 2

This Regulation shall enter into force on the day of its publication in the *Official Journal of the European Union*.

It shall apply from 1 July 2010.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg, 29 June 2010.

For the Council
The President
E. ESPINOSA

([1]) OJ L 158, 29.6.1996, p. 1.

([2]) OJ C 128, 25.4.1998, p. 2.

ANNEX I

Products referred to in Article 1(1)

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 1515 19 10	10	Linseed oil of an iodine index of 190 or more measured according to ISO standard 150-2006	0 %	1.7.2010-31.12.2010
ex 1516 20 96	10	Refined, bleached, hydrogenated soya bean oil in the form of flakes of a kind used in the manufacture of cosmetics	0 %	1.7.2010-31.12.2010
ex 1516 20 96	20	Jojoba oil, hydrogenated and interesterified, without any further chemical modification and not subjected to any texturisation process	0 %	1.7.2010-31.12.2014
ex 2008 99 49	20	Sweetened dried cranberries	0 %	1.7.2010-31.12.2014
ex 2008 99 49	30	Seedless boysenberry puree not containing added spirit, whether or not containing added sugar	0 %	1.7.2010-31.12.2014
ex 2008 99 99	40			
ex 2805 30 90	20	Samarium of a purity by weight of 99,90 % or more	0 %	1.7.2010-31.12.2014
ex 2904 10 00	30	Sodium *p*-styrenesulphonate	0 %	1.7.2010-31.12.2014
ex 2904 10 00	50	Sodium 2-methylprop-2-ene-1-sulphonate	0 %	1.7.2010-31.12.2014
ex 2905 19 00	40	2,6-Dimethylheptan-2-ol	0 %	1.7.2010-31.12.2014
ex 2905 29 90	20	Dec-9-en-1-ol	0 %	1.7.2010-31.12.2014
ex 2909 30 90	10	2-(Phenylmethoxy)naphthalene	0 %	1.7.2010-31.12.2014
ex 2909 30 90	20	1,2-Bis(3-methyl-phenoxy)ethane	0 %	1.7.2010-31.12.2014
ex 2915 90 00	50	Allyl heptanoate	0 %	1.7.2010-31.12.2014
ex 2917 11 00	30	Cobalt oxalate	0 %	1.7.2010-31.12.2014
ex 2917 19 10	10	Dimethyl malonate	0 %	1.7.2010-31.12.2014
ex 2917 19 90	30	Ethylene brassylate	0 %	1.7.2010-31.12.2014
ex 2918 99 90	20	Methyl 3-methoxyacrylate	0 %	1.7.2010-31.12.2014
ex 2918 99 90	70	Allyl-(3-methylbutoxy)acetate	0 %	1.7.2010-31.12.2014
ex 2921 19 50	10	Diethylamino-triethoxysilane	0 %	1.7.2010-31.12.2014
ex 2929 90 00	20			
ex 2922 19 85	40	2-(Dimethylamino) ethyl benzoate	0 %	1.7.2010-31.12.2014
ex 2922 49 85	15	DL-Aspartic acid used for the manufacture of food-integrators (1)	0 %	1.7.2010-31.12.2014
ex 2922 50 00	20	1-[2-Amino-1-(4-methoxyphenyl)-ethyl]-cyclohexanol hydrochloride	0 %	1.7.2010-31.12.2014
ex 2924 29 98	20	2-Chloro-*N*-(2-ethyl-6-methylphenyl)-*N*-(propan-2-yloxymethyl)acetamide	0 %	1.7.2010-31.12.2014
ex 2926 90 95	70	Methacrylonitrile	0 %	1.7.2010-31.12.2014
ex 2926 90 95	75	Ethyl 2-cyano-2-ethyl-3-methylhexanoate	0 %	1.7.2010-31.12.2014
ex 2929 10 00	15	3,3'-Dimethylbiphenyl-4,4'-diyl diisocyanate	0 %	1.7.2010-31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2930 90 99	81	Disodium hexamethylene-1,6-bisthiosulfate dihydrate	3 %	1.7.2010-31.12.2014
ex 2930 90 99	84	2-Chloro-4-(methylsulphonyl)benzoic acid	0 %	1.7.2010-31.12.2014
ex 2931 00 99	92	Trimethylborane	0 %	1.7.2010-31.12.2014
ex 2933 39 99	20	Copper pyrithione powder	0 %	1.7.2010-31.12.2014
ex 2933 39 99	30	Fluazinam (ISO)	0 %	1.7.2010-31.12.2014
ex 2933 39 99	45	5-Difluoromethoxy-2-[[(3,4-dimethoxy-2-pyridyl)methyl]thio]-1*H*-benzimidazole	0 %	1.7.2010-31.12.2014
ex 2933 39 99	47	(-)-*trans*-4-(4'-Fluorophenyl)-3-hydroxymethyl-*N*-methylpiperidine	0 %	1.7.2010-31.12.2014
ex 2933 39 99	48	Flonicamid (ISO)	0 %	1.7.2010-31.12.2014
ex 2933 59 95	45	1-[3-(Hydroxymethyl)pyridin-2-yl]-4-methyl-2-phenylpiperazine	0 %	1.7.2010-31.12.2014
ex 2933 59 95	50	2-(2-Piperazin-1-ylethoxy)ethanol	0 %	1.7.2010-31.12.2014
ex 2933 59 95	55	Thiopental (INNM)	0 %	1.7.2010-31.12.2014
ex 2933 59 95	65	1-Chloromethyl-4-fluoro-1,4-diazoniabicyclo[2.2.2]octane bis(tetrafluoroborate)	0 %	1.7.2010-31.12.2014
ex 2933 59 95	75	(2R,3S/2S,3R)-3-(6-Chloro-5-fluoro pyrimidin-4-yl)-2-(2,4-difluorophenyl)-1-(1*H*-1,2,4-triazol-1-yl)butan-2-ol hydrochloride	0 %	1.7.2010-31.12.2014
ex 2933 79 00	60	3,3-Pentamethylene-4-butyrolactam	0 %	1.7.2010-31.12.2014
ex 2933 99 80	32	5-[4'-(Bromomethyl)biphenyl-2-yl]-2-trityl-2*H*-tetrazole	0 %	1.7.2010-31.12.2014
ex 2933 99 80	37	8-Chloro-5,10-dihydro-11*H*-dibenzo [*b*,*e*] [1,4]diazepin-11-one	0 %	1.7.2010-31.12.2014
ex 2934 10 00	60	Fosthiazate (ISO)	0 %	1.7.2010-31.12.2014
ex 2934 99 90	20	Thiophene	0 %	1.7.2010-31.12.2014
ex 2934 99 90	30	Dibenzo[b,f][1,4]thiazepin-11(10H)-one	0 %	1.7.2010-31.12.2014
ex 2935 00 90	77	[[4-[2-[[(3-Ethyl-2,5-dihydro-4-methyl-2-oxo-1*H*-pyrrol-1-yl)carbonyl]amino] ethyl]phenyl]sulfonyl]-carbamic acid ethyl ester	0 %	1.7.2010-31.12.2014
ex 3701 30 00	20	Photosensitive plate consisting of a photopolymer layer on a polyester foil of a total thickness of more than 0,43 mm but not more than 3,18 mm	0 %	1.7.2010-31.12.2014
* ex 3707 10 00	35	Sensitising emulsion or preparation, comprising of acrylate and/or methacrylate polymers, containing by weight not more than 7 % photosensitive acid precursors dissolved in an organic solvent containing at least 2-methoxy-1-methylethyl acetate	0 %	1.7.2010-31.12.2011
ex 3707 90 90	70			
ex 3707 10 00	55	Rolls of polyethylene terephthalate film: — covered on one side with a dry layer of acrylic photopolymer resin, — coated with a polyethylene protection foil	0 %	1.7.2010-31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3707 90 90	40	Anti reflection coating, in the form of an aqueous solution, containing by weight not more than: — 2 % of halogen-free alkyl sulphonic acid, and — 5 % of a fluorinated polymer	0 %	1.7.2010-31.12.2014
* ex 3808 92 90	30	Preparation consisting of a suspension of pyrithione zinc (INN) in water, containing by weight: — 24 % or more but not more than 26 % of pyrithione zinc (INN), or — 39 % or more but not more than 41 % of pyrithione zinc (INN)	0 %	1.7.2010-31.12.2013
ex 3808 92 90	50	Preparations based on copper pyrithione	0 %	1.7.2010-31.12.2014
ex 3808 93 23	10	Herbicide containing flazasulfuron (ISO) as an active ingredient	0 %	1.7.2010-31.12.2014
ex 3808 93 90	10	Preparation, in the form of granules, containing by weight: — 38,8 % or more but not more than 41,2 % of Gibberellin A3, or — 9,5 % or more but not more than 10,5 % of Gibberellin A4 and A7	0 %	1.7.2010-31.12.2014
ex 3824 90 97	05	Mixture of methylmethacrylate monomer and butylacrylate monomer in a solution of xylene and butylacetate, containing by weight more than 54 % but not more than 56 % of solvents	0 %	1.7.2010-31.12.2014
ex 3824 90 97	06	Paraffin with a level of chlorination of 70 % or more	0 %	1.7.2010-31.12.2014
ex 3824 90 97	08	Mixture of divinylbenzene-isomers and ethylvinylbenzene-isomers, containing by weight 56 % or more but not more than 80 % of divinylbenzene	0 %	1.7.2010-31.12.2014
ex 3824 90 97	11	Mixture of phytosterols, not in powder form, containing by weight: — 40 % or more, but not more than 58 % of beta-sitosterols — 20 % or more, but not more than 28 % of campesterols — 14 % or more, but not more than 23 % of stigmasterols — 0 % or more, but not more than 15 % of other sterols	0 %	1.7.2010-31.12.2014
ex 3824 90 97	21	Mixture of 2-propenoic acid, (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyloxy-2,1-ethanediyl)ester with 2-propenoic acid, (2,4,6-trioxo-1,3,5-triazine-1,3,5(2*H*,4*H*,6*H*)-triyl)tri-2,1-ethanediyl ester and 1-hydroxy-cyclohexyl-phenyl ketone in the solution of methyl ethyl ketone and toluene	0 %	1.7.2010-31.12.2014
ex 3824 90 97	23	Mixture of urethane acrylates, tripropylene glycoldiacrylate, ethoxylated bisphenol A acrylate and poly(ethyleneglycol) 400 diacrylate	0 %	1.7.2010-31.12.2014
* ex 3824 90 97	44	Mixture of phytosterols, not in the form of powder, containing by weight: — 75 % or more of sterols, — not more than 25 % of stanols, for use in the manufacture of stanols/sterols or stanol/sterol esters (1)	0 %	1.7.2010-31.12.2012
ex 3824 90 97	66	Mixture of primary *tert*-alkylamines	0 %	1.7.2010-31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3824 90 97	88	Oligomeric reaction product, consisting of bis(4-hydroxyphenyl) sulfone and 1,1'-oxybis(2-chloroethane)	0 %	1.7.2010-31.12.2014
* ex 3901 10 90	20	Polyethylene, in the form of granules, of a specific gravity of 0,925 (± 0,0015), a melt flow index of 0,3 g/10 min (± 0,05 g/10 min), for the manufacture of blown films of a haze value not more than 6 % and an elongation at break (MD/TD) of 210/340(1)	0 %	1.7.2010-31.12.2013
ex 3902 90 90	60	Non-hydrogenated 100 % aliphatic resin (polymer), with the following characteristics: — liquid at room temperature — obtained by cationic polymerisation of C-5 alkenes monomers — with a number average molecular weight (Mn) of 370 (± 50) — with a weight average molecular weight (Mw) of 500 (± 100)	0 %	1.7.2010-31.12.2014
* ex 3906 90 90	35	White powder of 1,2-ethanediol dimethacrylate-methyl methacrylate copolymer of a particle size of not more than 18 µm, insoluble in water	0 %	1.7.2010-31.12.2013
ex 3907 91 90	10	Diallyl phthalate prepolymer, in powder form	0 %	1.7.2010-31.12.2014
ex 3907 99 90	70	Copolymer of poly(ethylene terephthalate) and cyclohexane dimethanol, containing more than 10 % by weight of cyclohexane dimethanol	0 %	1.7.2010-31.12.2014
ex 3910 00 00	60	Polydimethylsiloxane, whether or not polyethylene glycol and trifluoropropyl substituted, with methacrylate end groups	0 %	1.7.2010-31.12.2014
ex 3916 20 00	91	Profiles of poly(vinyl chloride) of a kind used in the manufacture of sheet pilings and facings, containing the following additives: — titanium dioxide — poly(methyl methacrylate) — calcium carbonate — binding agents	0 %	1.7.2010-31.12.2014
ex 3919 10 80	23	Reflecting film, consisting of several layers including: — poly(vinyl chloride); — polyurethane with, on one side, imprints against counterfeiting, alteration or substitution of data or duplication, and on the other side, a layer of glass microspheres; — a layer incorporating a security and/or official mark which changes appearance with angle of view; — metallized aluminium; — and adhesive, covered on one side with a release liner	0 %	1.7.2010-31.12.2014
ex 3919 10 80	27	Polyester film:	0 %	1.7.2010-31.12.2014
ex 3919 90 00	20	— coated on one side with an acrylic thermal release adhesive that debonds at temperatures of 90 °C or more but not more than 200 °C, and a polyester liner, and — on the other side not coated or coated with an acrylic pressure sensitive adhesive or with an acrylic thermal release adhesive that debonds at temperatures of 90 °C or more but not more than 200 °C, and a polyester liner		

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3919 10 80	32	Polytetrafluoroethylene film: — with a thickness of 110 μm or more, — with a surface resistance of between 10^2-10^{14} ohms as determined by test method ASTM D 257, — coated on one side with an acrylic pressure sensitive adhesive	0 %	1.7.2010-31.12.2014
ex 3919 10 80	37	Polytetrafluoroethylene film: — with a thickness of 100 μm or more, — an elongation at break of not more than 100 %, — coated on one side with a pressure sensitive silicon adhesive	0 %	1.7.2010-31.12.2014
* ex 3919 10 80	40	Black poly(vinyl chloride) film:	0 %	1.7.2010-31.12.2011
* ex 3919 90 00	43	— with a gloss of more than 30 degrees according to ASTM D2457, — whether or not covered on one side with a protective poly(ethylene terephthalate) film, and on the other side with a pressure sensitive adhesive with channels and a release liner		
* ex 3919 90 00	19	Transparent poly(ethylene terephthalate) self-adhesive film: — free from impurities or faults, — coated on one side with an acrylic pressure sensitive adhesive and a protective liner, and on the other side with an antistatic layer of ionic organic choline compound, — whether or not with a printable dust-proof layer of modified long chain alkyl organic compound, — with a total thickness without the liner of 54 μm or more but not more than 64 μm, and — a width of more than 1 295 mm but not more than 1 305 mm	0 %	1.7.2010-31.12.2013
ex 3919 90 00	22	Black polypropylene film: — with a gloss of more than 20 degrees as determined by test method ASTM D2457, — whether or not covered on one side with a protective polyethylene terephthalate film and on the other side with a pressure sensitive adhesive with channels and a release liner	0 %	1.7.2010-31.12.2014
ex 3919 90 00	24	Reflecting laminated sheet: — consisting of an epoxy acrylate layer embossed on one side in a regular shaped pattern, — covered on both sides with one or more layers of plastic material and — covered on one side with an adhesive layer and a release sheet	0 %	1.7.2010-31.12.2014
ex 3919 90 00	26	Ethylene vinyl acetate film: — of a thickness of 100 μm or more, — coated on one side with an acrylic pressure sensitive or UV-sensitive adhesive and a polyester liner	0 %	1.7.2010-31.12.2014
ex 3919 90 00	28	Poly(vinyl chloride) or polyethylene or any other polyolefine film: — of a thickness of 65 μm or more, — coated on one side with an acrylic UV-sensitive adhesive and a polyester liner	0 %	1.7.2010-31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Validity period
* ex 3919 90 00	37	UV sensitive film of poly(vinyl chloride): — with a thickness of 78 µm or more, — covered on one side with an adhesive layer and with a release sheet, — with an adhesive strength of 1 764 mN/25 mm or more	0 %	1.7.2010-31.12.2014
ex 3920 59 90	20	Reflecting laminated sheet, consisting of an epoxy acrylate layer embossed on one side in a regular shaped pattern, covered on both sides with one or more layers of plastic material	0 %	1.7.2010-31.12.2014
ex 3920 62 19	24	Film of poly(ethylene terephthalate) of a thickness of 186 µm or more but not more than 191 µm coated on one side with an acrylic layer in a matrix pattern	0 %	1.7.2010-31.12.2014
ex 3920 62 19	26			
* ex 3920 62 19	75	Transparent polyethylene terephthalate film:	0 %	1.7.2010-31.12.2013
* ex 3920 62 19	77	— coated on both sides with layers of organic substances on the basis of acryl of a thickness of 7 nm or more but not more than 80 nm, — with a surface tension of 36 Dyne/cm or more but not more than 39 Dyne/cm, — with a light transmission of more than 93 %, — with a haze value of not more than 1,3 %, — with a total thickness of 10 µm or more but not more than 350 µm, — with a width of 800 mm or more but not more than 1 600 mm		
ex 3920 91 00	51	Poly(vinyl butyral) film containing by weight 25 % or more but not more than 28 % of tri-isobutyl phosphate as a plasticizer	0 %	1.7.2010-31.12.2014
ex 3920 91 00	52	Poly(vinyl butyral) film: — containing by weight 26 % or more but not more than 30 % of triethyleneglycol bis(2-ethyl hexanoate) as a plasticizer, — with a thickness of 0,73 mm or more but not more than 1,50 mm	0 %	1.7.2010-31.12.2014
ex 3921 90 55	25	Prepreg sheets or rolls containing polyimide resin	0 %	1.7.2010-31.12.2014
ex 7019 40 00	20			
ex 3921 90 55	30	Prepreg sheets or rolls containing brominated epoxy resin reinforced with glass fabric, having — a flow of not more than 3,6 mm (as determined by IPC-TM 650.2.3.17.2), and — a glass transition temperature (Tg) of more than 170 °C (as determined by IPC-TM 650.2.4.25) for use in the manufacture of printed circuit boards (1)	0 %	1.7.2010-31.12.2014
ex 6909 19 00	20	Silicon nitride (Si_3N_4) balls	0 %	1.7.2010-31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 7019 19 10	55	Glass cord impregnated with rubber or plastic, obtained from K or U glass filaments, made up of: — 9 % or more but not more than 16 % of magnesium oxide, — 19 % or more but not more than 25 % of aluminium oxide, — 0 % or more but not more than 2 % of boron oxide, — without calcium oxide, coated with a latex comprising at least a resorcinol-formaldehyde resin and chlorosulphonated polyethylene	0 %	1.7.2010-31.12.2014
ex 7325 99 10	20	Anchor head of hot dipped galvanized ductile cast iron of the kind used in the production of earth anchors	0 %	1.7.2010-31.12.2014
* ex 7410 21 00	30	Film of polyimide, whether or not containing epoxide resin and/or glass fibre, covered on one side or on both sides with a copper foil	0 %	1.7.2010-31.12.2013
* ex 8108 20 00	20	Raw ingots from the fusion of titanium and titanium alloys, of a diameter of not more than 380 mm	0 %	1.7.2010-31.12.2013
ex 8414 30 81	50	Hermetic or semi-hermetic variable-speed electric scroll compressors, with a nominal power rating of 0.5 kW or more, but not more than 5 kW, with a displacement volume of not more than 35 cm^3, of the type used in refrigeration equipment	0 %	1.7.2010-31.12.2014
ex 8418 99 10	50	Evaporator composed of aluminium fins and a copper coil of the kind used in refrigeration equipment	0 %	1.7.2010-31.12.2014
ex 8418 99 10	60	Condenser composed of two concentric copper tubes of the kind used in refrigeration equipment	0 %	1.7.2010-31.12.2014
ex 8501 31 00	40	Permanently excited DC-motor with — a multiple-phase winding, — an external diameter of 30 mm or more, but not more than 75 mm, — a rated speed of not more than 15 000 rpm, — an output of 45 W or more, but not more than 300 W and — a supply voltage of 9 V or more, but not more than 25 V	0 %	1.7.2010-31.12.2014
* ex 8504 40 90	40	Semiconductor power modules comprising: — power transistors, — integrated circuits, — whether or not containing diodes and with or without thermistors, — an operating voltage of not more than 600 V, — not more than three electrical outputs each containing two power switches (whether MOSFET (Metal Oxide Semiconductor Field-Effect Transistor) or IGBT (Insulated Gate Bi-polar Transistors)) and internal drives, and — a rms (root mean square) current rating of not more than 15.7 A	0 %	1.7.2010-31.12.2013

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8516 90 00	60	Ventilation sub-assembly of an electric deep-fat fryer — fitted with a motor having a power rating of 8 W at 4 600 revolutions per minute, — governed by an electronic circuit, — operating at ambient temperatures above 110 °C, — fitted with a thermoregulator	0 %	1.7.2010-31.12.2014
ex 8521 90 00	20	Digital video recorder: — without a hard disk drive, — with or without a DVD-RW, — with motion detection, — with a USB serial port, for use in the manufacture of Closed-circuit television (CCTV) surveillance systems (1)	0 %	1.7.2010-31.12.2014
ex 8522 90 49	60	Printed circuit board assembly comprising:	0 %	1.7.2010-31.12.2014
ex 8527 99 00	10	— a radio tuner (capable of receiving and decoding radio signals and transmitting those signals within the assembly) without signal processing capabilities,		
ex 8529 90 65	25	— a microprocessor capable of receiving remote control messages and controlling the tuner chipset, for use in the manufacture of home entertainment systems (1)		
ex 8522 90 49	65	Printed circuit board subassembly, comprising:	0 %	1.7.2010-31.12.2014
ex 8527 99 00	20	— a radio tuner, capable of receiving and decoding radio signals and transmitting those signals within the assembly, with a signal decoder,		
ex 8529 90 65	40	— a radio frequency (RF) remote control receiver, — an infrared remote control signal transmitter, — a SCART signal generator — a TV state sensor for use in the manufacture of home entertainment systems (1)		

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8525 80 19	25	Long wavelength infrared camera (LWIR camera) (according to ISO/TS 16949), with: — a sensitivity in the wavelength area of 8 µm or more, but not more than 14 µm, — a resolution of 324 × 256 pixels, — a weight of not more than 400 g, — measurements of not more than 70 mm × 67 mm × 75 mm, — a waterproof housing and an automotive-qualified plug and — a deviation of the output signal over the entire work temperature range of not more than 20 %	0 %	1.7.2010-31.12.2014
ex 8525 80 19	35	Image scanning cameras, using: — a 'Dynamic overlay lines' system — an output NTSC video signal — a voltage of 6,5 V — an illuminance of 0,5 lux or more	0 %	1.7.2010-31.12.2014
* ex 8704 23 91	20	Motor chassis with a self-ignition capacity of at least 8 000 cm^3, fitted with a cabin on either 3, 4 or 5 wheels having a wheelbase of at least 480 cm, not containing working machinery, to be built into special purpose motor vehicles with a width of at least 300 cm (1)	0 %	1.7.2010-31.12.2012

(*) Modified CN or TARIC code or product description.

ANNEX II

Products referred to in Article 1(2)

CN code	TARIC
ex 1518 00 99	10
*ex 3707 10 00	35
*ex 3808 92 90	30
*ex 3824 90 97	44
*ex 3901 10 90	20
*ex 3906 90 90	35
ex 3907 20 20	91
*ex 3919 10 80	40
*ex 3919 90 00	19
*ex 3919 90 00	37
*ex 3919 90 00	43
*ex 3920 62 19	75
*ex 3920 62 19	77
ex 7410 11 00	10
*ex 7410 21 00	30
ex 7410 21 00	60
*ex 8108 20 00	20
*ex 8504 40 90	40
*ex 8704 23 91	20
ex 9031 90 85	30

(*) Suspension relating to a product in the Annex to Regulation (EC) No 1255/96 for which the CN or TARIC code or the product description is modified by this Regulation.