STATUTORY INSTRUMENTS

1963 No. 1646

ROAD TRAFFIC

The Motor Vehicles (Construction and Use) Regulations 1963

Made - - - - 26*th September* 1963
Laid before Parliament 11*th October* 1963
Coming into Operation 1*st November* 1963

ARRANGEMENT OF REGULATIONS

PART I.—PRELIMINARY

	Regulation
Commencement and Citation	1
Revocation	2
Interpretation	3
Application and Exemptions	4 and 5

PART II.—REGULATIONS GOVERNING THE CONSTRUCTION, WEIGHT AND EQUIPMENT OF MOTOR VEHICLES AND TRAILERS

A. GENERAL

Construction	6
Overall length	7
Overall height of public service vehicles	8
Variation of wheel load	9
Springs	10
Parking brake	11
Vacuum or pressure braking systems	12
Speedometer	13
Diameter of wheels	14
Reversing	15
View to the front	16
Mirrors	17
Safety glass	18
Windscreen wiper	19
Audible warning instrument	20
Silencer	21
Emission of smoke or vapour	22 and 23
Emission of sparks or grit	24
Closets, urinals, lavatory basins and sinks	25
Maximum seating capacity of half-decked vehicles	26
Lighting equipment and reflectors	27

B. DIRECTION INDICATORS AND STOP LIGHTS

Direction indicators	28
Stop lights	29

C. GAS CONTAINERS

Gas containers	30

	Regulation
D. Locomotives	
Overall width	31
Distribution of weight	32
Tyres	33
Brakes	34 and 35
E. Motor Tractors	
Overall width	36
Overhang	37
Brakes	38
Tyres	39
F. Heavy Motor Cars	
Overall width	40
Overhang	41
Brakes	42
Tyres	43
Wings	44
G. Motor Cars	
Overall width	45
Overhang	46
Brakes	47
Tyres	48
Wings	49
H. Motor Cycles	
Brakes	50
Tyres	51
Wings	52
I. Invalid Carriages	
Width	53
Brakes	54
Wings	55
J. Trailers	
Overall length	56
Overall width	57
Brakes	58
Tyres	59 and 60
Wings	61

Part III.—Regulations Governing the Use on Roads of Motor Vehicles and Trailers

Markings on locomotives, tractors and heavy motor cars	62
Markings on trailers	63
Trailer plate	64
Laden weight of locomotive	65
Weight of trailers drawn by a locomotive	66
Laden weight of heavy motor car or motor car	67 and 68
Laden weight of trailer	69
Laden weight of vehicle and trailer	70
Laden weight of articulated vehicle	71
Distribution of weight	72

	Regulation
Maintenance and use of vehicle so as not to be a danger	73
Maintenance of speedometer	74
Maintenance of glass	75
Maintenance of brakes, steering gear and windscreen wiper	76
Maintenance of lighting equipment and reflectors	77
Use and maintenance of silencer	78
Maintenance of tyres	79
Use of vehicles so as not to emit smoke, etc.	80 and 81
Contents of lavatories, etc.	82
Excessive noise	83 and 84
Stopping of engine when stationary	85
Use of audible warning instruments	86
Duties relating to driving and stopping	87 to 92
Opening of doors	93
Application of brakes of trailers	94 and 95
Restriction on distance between motor vehicles and trailers and marking of trailer connections	96
Restrictions on the use of vehicles to draw trailers and of trailers drawn	97 to 103
Passengers on motor bicycles	104
Restrictions on use of vehicles carrying wide or long loads or having fixed appliances or apparatus	105 and 106
Mascots	107
Television sets	108
Implements suspended from lifting appliances	109
Attendants on trailers	110

PART IV.—TESTING AND INSPECTION OF BRAKES, SILENCERS, STEERING GEAR, TYRES, LIGHTING EQUIPMENT AND REFLECTORS

Testing of brakes, etc.	111

SCHEDULES

	Page
1. Regulations Revoked	51
2. Direction Indicators	52
3. Gas Containers	60
4. Requirements with respect to the efficiency of the brakes of certain motor vehicles	63
5. Diagram of Trailer Plate	65
6. Conditions to be complied with in relation to the use of vehicles carrying wide or long loads or vehicles carrying loads or having fixed appliances or apparatus which project	65

The Minister of Transport, in exercise of his powers under section 64(1) of the Road Traffic Act 1960(a) as amended by section 51 of and Schedule 4 to the Road Traffic Act 1962(b) and under section 72(5) of the said Act of 1960 and of all other powers him enabling in that behalf, and after

(a) 8 & 9 Eliz. 2. c. 16 (b) 10 & 11 Eliz. 2. c. 59.

consultation with representative organisations in accordance with the provisions of section 260(2) of the said Act of 1960, hereby makes the following Regulations :—

PART I.—PRELIMINARY

Commencement and Citation

1. These Regulations shall come into operation on 1st November 1963 and may be cited as the Motor Vehicles (Construction and Use) Regulations 1963.

Revocation

2. The Regulations specified in Schedule 1 to these Regulations are hereby revoked.

Interpretation

3.—(1) In these Regulations, unless the context otherwise requires, the following expressions have the meanings hereby assigned to them respectively, that is to say,—

" the 1960 Act " means the Road Traffic Act 1960 ;

" agricultural trailer " means a trailer the property of a person engaged in agriculture which is not used on a road for the conveyance of any goods or burden other than agricultural produce or articles required for the purposes of agriculture ;

" articulated vehicle " means a heavy motor car or motor car with a trailer so attached to the drawing vehicle that part of the trailer is superimposed upon the drawing vehicle, and when the trailer is uniformly loaded not less than 20 per cent. of the weight of its load is borne by the drawing vehicle ;

" close-coupled ", in relation to a trailer, means that the wheels on the same side of the trailer are so fitted that at all times while it is in motion they remain parallel to the longitudinal axis of the trailer, and that the distance between the centres of their respective areas of contact with the road surface does not exceed 33 inches ;

" deck " means a floor or platform upon which seats are provided for the accommodation of passengers ;

" direction indicator " means a device fitted to a motor vehicle or trailer for the purpose of intimating the intention of the driver to change the direction of the vehicle to the right or to the left ;

" double-decked vehicle " means a vehicle having two decks one of which is wholly or partly above the other and each deck of which is provided with a gangway serving seats on that deck only ;

" dual-purpose vehicle " means a vehicle constructed or adapted for the carriage both of passengers and of goods or burden of any description, being a vehicle of which the unladen weight does not exceed 2 tons, and which either—

(1) is so constructed or adapted that the driving power of the engine is, or by the appropriate use of the controls of the vehicle can be, transmitted to all the wheels of the vehicle, or

(2) satisfies the following conditions as to construction, namely :—

(*a*) the vehicle must be permanently fitted with a rigid roof, with or without a sliding panel ;

(*b*) the area of the vehicle to the rear of the driver's seat must—

(i) be permanently fitted with at least one row of transverse seats (fixed or folding) for two or more passengers and those seats must be properly sprung or cushioned and provided with upholstered back-rests, attached either to the seats or to a side or the floor of the vehicle; and

(ii) be lit on each side and at the rear by a window or windows of glass or other transparent material having an area or aggregate area of not less than two square feet on each side and not less than one hundred and twenty square inches at the rear;

(*c*) the distance between the rearmost part of the steering wheel and the backrests of the row of transverse seats satisfying the requirements specified in head (i) of the foregoing sub-paragraph (or, if there is more than one such row of seats, the distance between the rearmost part of the steering wheel and the backrests of the rearmost such row) must, when the seats are ready for use, be not less than one-third of the distance between the rearmost part of the steering wheel and the rearmost part of the floor of the vehicle;

"gangway" means the space provided for obtaining access from any entrance to the passengers' seats or from any such seat to an exit other than an emergency exit but does not include a staircase or any space in front of a seat which is required only for the use of passengers occupying that seat;

"gas" means any fuel that is wholly gaseous at 60° Fahrenheit under a pressure of 30 inches of mercury;

"gas equipment" means a container or containers for holding, or plant and materials for producing, gas;

"gas trailer" means a trailer used solely for the carriage of gas equipment for the purpose of the propulsion of the drawing vehicle;

"goods vehicle" means a vehicle constructed or adapted for use for the conveyance of goods or burden of any description;

"half-decked vehicle" means any vehicle not being a single-decked vehicle or a double-decked vehicle;

"hours of darkness" means the time between half-an-hour after sunset and half-an-hour before sunrise;

"indivisible load" means a load which cannot without undue expense or risk of damage be divided into two or more loads for the purpose of conveyance on a road;

"land implement" means any implement or machinery used with a land locomotive or a land tractor in connection with agriculture, grass cutting, forestry, land levelling, dredging or similar operations and includes a living van and any trailer which for the time being carries only the necessary gear or equipment of the land locomotive or land tractor which draws it;

"land implement conveyor" means a trailer, having an unladen weight not exceeding 10 hundredweight, which is specially designed and constructed for the conveyance of not more than one land implement and which is marked with its unladen weight, has each of its wheels fitted with a pneumatic tyre and is drawn by a land locomotive or a land tractor;

"land locomotive" means a locomotive designed and used primarily for work on the land in connection with agriculture, forestry, land levelling, dredging or similar operations, which is driven on a road only when proceeding to and from the site of such work and which when so driven hauls nothing other than land implements or land implement conveyors;

"land tractor" means a tractor, having an unladen weight not exceeding 7¼ tons, designed and used primarily for work on the land in connection with agriculture, grass cutting, forestry, land levelling, dredging or similar operations, which is—

(*a*) the property of a person engaged in agriculture or forestry or of a contractor engaged in the business of carrying out on farms or forestry estates any such operations as aforesaid; and

(*b*) not constructed or adapted for the conveyance of a load other than—

(i) water, fuel, accumulators and other equipment used for the purpose of propulsion, loose tools and loose equipment,

(ii) a load (consisting of goods or burden of a description referred to in paragraph 5(3) of Schedule 4 to the Vehicles (Excise) Act 1962(a)) in or on any appliance which satisfies the conditions whereby the vehicle to which the said appliance is fitted does not, by virtue of the said paragraph 5 and of any regulations made from time to time under paragraph 6 of the said Schedule 4, become chargeable with duty as a goods vehicle, and

(iii) an implement fitted to the tractor and used for work on the land on farms or forestry estates in connection with any such operations as aforesaid;

"locomotive" means a heavy locomotive or a light locomotive;

"overall length" means the length of a vehicle measured between vertical planes at right angles to the longitudinal axis of the vehicle and passing through the extreme projecting points thereof exclusive of—

(*a*) any driving mirror;

(*b*) any starting handle;

(*c*) any hood when down;

(*d*) any expanding or extensible contrivance forming part of a turntable fire escape fixed to a vehicle;

(*e*) any telescopic fog lamp when extended;

(*f*) any snow-plough fixed in front of a vehicle;

(*g*) any post office letter box the length of which measured parallel to the longitudinal axis of the vehicle does not exceed 12 inches; and

(*h*) any container specially designed to hold and keep secure a seal issued for the purposes of custom's clearance,

and, except for the purposes of Regulation 105 of these Regulations, exclusive of any front corner marker lamp or side marker lamp within the meaning of the Road Vehicles Lighting (Long Vehicles and Trailers) Regulations 1962(b) carried on the vehicle in accordance with those Regulations;

"overall width" means the width of a vehicle measured between vertical planes parallel to the longitudinal axis of the vehicle and passing through the extreme projecting points thereof exclusive of—

(*a*) any driving mirror;

(a) 10 & 11 Eliz. 2. c. 13. (b) S.I. 1962/1583 (1962 II, p. 1783).

(*b*) any direction indicator;

(*c*) any snow-plough fixed in front of the vehicle;

(*d*) so much of the distortion of any tyre as is caused by the weight of the vehicle;

(*e*) in the case of vehicles registered before 2nd January 1939 so much of a swivelling window designed to allow the driver to give hand signals as projects when opened not more than 4 inches beyond the side of the vehicle; and

(*f*) any container specially designed to hold and keep secure a seal issued for the purposes of custom's clearance,

and, except for the purposes of Regulation 105 of these Regulations, exclusive of any such front corner marker lamp or side marker lamp as aforesaid;

"overhang" means the distance measured horizontally and parallel to the longitudinal axis of a vehicle between two vertical planes at right angles to that axis passing through the two points respectively specified in paragraphs (*a*) and (*b*) of this definition,

(*a*) the rearmost point of the vehicle exclusive of—

(i) any hood when down,

(ii) any post office letter box the length of which measured parallel to the longitudinal axis of the vehicle does not exceed 12 inches,

(iii) any expanding or extensible contrivance forming part of a turntable fire escape fixed to a vehicle, and

(iv) in the case of a motor car constructed solely for the carriage of passengers and their effects and adapted to carry not more than seven passengers exclusive of the driver, any luggage carrier fitted to the vehicle; and

(*b*) (i) in the case of a motor vehicle having not more than three axles of which only one is not a steering axle, through the centre point of that axle,

(ii) in the case of a motor vehicle having three axles of which the front axle is the only steering axle and of a motor vehicle having four axles of which the two foremost are the only steering axles, through a point 4 inches in rear of the centre of a straight line joining the centre points of the two rearmost axles, and

(iii) in any other case through a point situated on the longitudinal axis of the vehicle and such that a line drawn from it at right angles to that axis will pass through the centre of the minimum turning circle of the vehicle;

"passenger vehicle" means a vehicle constructed solely for the carriage of passengers and their effects;

"pedestrian controlled vehicle" means a motor vehicle which is controlled by a pedestrian and not constructed or adapted for use or used for the carriage of a driver or passenger;

"pneumatic tyre" means a tyre which complies in all respects with the following requirements:—

(*a*) it shall be provided with, or together with the wheel upon which it is mounted shall form, a continuous closed chamber inflated to a pressure substantially exceeding atmospheric pressure when the tyre is in the condition in which it is normally used, but is not subjected to any load;

(*b*) it shall be capable of being inflated and deflated without removal from the wheel or vehicle;

(*c*) it shall be such that, when it is deflated and is subjected to a normal load, the sides of the tyre collapse;

"registered" means—

(*a*) in the case of a vehicle which was registered at any time under the Roads Act 1920(a), the date on which it was first so registered; and

(*b*) in the case of any other vehicle, the date on which it was first registered under the Vehicles (Excise) Act 1949(b) or the Vehicles (Excise) Act 1962;

"safety glass" means glass so constructed or treated that if fractured it does not fly into fragments likely to cause severe cuts;

"single-decked vehicle" means a vehicle upon which no part of a deck or gangway is vertically above another deck or gangway;

"stop light" means a device fitted to a motor vehicle or to a trailer drawn by a motor vehicle for the purpose of intimating the intention of the driver of the motor vehicle to stop or slow down;

"straddle carrier" means a motor vehicle constructed to straddle and lift its load for the purpose of transportation;

"statutory power of removal" means a power conferred by or under any enactment to remove or move a vehicle from any road or from any part of a road;

"towing implement" means any device on wheels designed for the purpose of enabling a motor vehicle to draw another vehicle by the attachment of that device to that other vehicle in such a manner that part of that other vehicle rests on the device and some but not all of the wheels on which that other vehicle normally runs are raised off the ground;

"track laying" in relation to a vehicle means that the vehicle is so designed and constructed that the weight thereof is transmitted to the road surface either by means of continuous tracks or by a combination of wheels and continuous tracks in such circumstances that the weight transmitted to the road surface by the tracks is not less than half the weight of the vehicle;

"vehicle in the service of a visiting force" means a vehicle belonging to the service authorities of such a force and used for the purposes of such a force, and any other vehicle when used as aforesaid by a person subject to the orders of any member of such a force;

"visiting force" means any such body, contingent or detachment of the forces of any country as is a visiting force for the purposes of the provisions of the Visiting Forces Act 1952(c)—

(*a*) which apply to that country by virtue of section 1(1)(*a*) of that Act; or

(*b*) which from time to time apply to that country by virtue of section 1(1)(*b*) of that Act and of any Order in Council made or hereafter to be made under the said section 1 designating that country for the

(a) 10 & 11 Geo. 5. c. 72. (b) 12, 13 & 14 Geo. 6. c. 89.
(c) 15 & 16 Geo. 6 & 1 Eliz. 2. c. 67.

purposes of all the provisions of that Act following subsection (2) of the said section 1 ;

and " member " and " service authorities " have the same meanings respectively as they have in the Visiting Forces Act 1952 ;

" wheel " in the case of a motor vehicle or trailer means a wheel the tyre or rim of which when the vehicle is in motion on a road is in contact with the ground ;

" wheeled " in relation to a vehicle means that the whole weight of the vehicle is transmitted to the road surface by means of wheels ;

" works trailer " means a trailer designed for use in private premises and used on a road only in delivering goods from such premises to a vehicle on a road in the immediate neighbourhood, or in passing from one part of any such premises to another or to other private premises in the immediate neighbourhood or in connection with road works while at or in the immediate neighbourhood of the site of such works ;

" works truck " means a motor vehicle (other than a straddle carrier) designed for use in private premises and used on a road only in delivering goods from such premises to a vehicle on a road in the immediate neighbourhood, or in passing from one part of any such premises to another or to other private premises in the immediate neighbourhood or in connection with road works while at or in the immediate neighbourhood of the site of such works.

(2) Except where otherwise provided in these Regulations a tyre shall not be deemed to be of soft or elastic material unless the said material is either—

(*a*) continuous round the circumference of the wheel ; or

(*b*) fitted in sections so that so far as reasonably practicable no space is left between the ends thereof,

and is of such thickness and design as to minimise, so far as reasonably possible, vibration when the vehicle is in motion and so constructed as to be free from any defect which might in any way cause damage to the surface of a road.

(3) For the purpose of these Regulations a brake drum shall be deemed to form part of the wheel and not of the braking system.

(4) For the purpose of these Regulations any two wheels of a motor vehicle or trailer shall be regarded as one wheel if the distance between the centres of the areas of contact between such wheels and the road surface is less than 18 inches.

(5) Any reference in these Regulations to any enactment shall be construed as a reference to that enactment as amended by any subsequent enactment.

(6) The Interpretation Act 1889(a) shall apply for the interpretation of these Regulations as it applies for the interpretation of an Act of Parliament, and as if for the purposes of section 38 of that Act these Regulations were an Act of Parliament and the Regulations revoked by Regulation 2 of these Regulations were Acts of Parliament thereby repealed.

(7) In so far as any consent, notice, direction or dispensation given or any other thing done under a provision of the Regulations revoked by these Regulations could have been given or done under a corresponding provision of these Regulations it shall not be invalidated by the revocation effected by Regulation 2 of these Regulations but shall have effect as if given or done under that corresponding provision.

(a) 52 & 53 Vict. c. 63.

Application and Exemptions

4.—(1) Except where the context otherwise requires these Regulations shall apply to wheeled vehicles only.

(2) Regulations 9, 10, 17, 20, 32, 33 and 39 of these Regulations shall not apply to road rollers.

(3) Regulations 7 to 10 inclusive, 12 to 15 inclusive, 17, 18, 21 to 63 inclusive and 74 of these Regulations shall not apply to vehicles proceeding to a port for export.

(4) Regulations 9, 10, 14, 33, 39, 43, 48, 59, 60, 62, 63 and 65 to 72 inclusive of these Regulations shall apply only to motor vehicles and trailers used on highways.

(5) Every motor vehicle registered before the expiration of one year from the making of any Regulation hereof by which the requirements as regards the construction or weight of any class or description of vehicles are varied shall be exempt from the requirements of that Regulation for a period of five years from the making thereof provided that it complies with the requirements of the Regulations to which it would have been subject immediately prior to the making of that Regulation.

(6) Part II of these Regulations, except Regulations 7, 30 to 32 inclusive, 36, 40, 45, 53, 56 and 57, shall not apply to any motor vehicle or trailer brought temporarily into Great Britain by a person resident abroad, provided that such motor vehicle or trailer respectively complies in every respect with the requirements relating to motor vehicles or trailers contained in :—

(*a*) Article 21 and paragraph (1) of Article 22 of the Convention on Road Traffic concluded at Geneva on 19th September 1949(a), and Part III (except paragraph (*e*)) of, and paragraph (*a*) of Part V of, Annex 6 to that Convention ; or

(*b*) paragraphs I, III and VIII of Article 3 of the International Convention relative to Motor Traffic concluded at Paris on 24th April 1926(b).

(7) Regulations 7 to 10 inclusive, 12 to 14 inclusive, 16 to 21 inclusive, 25 to 72 inclusive, and 105 of these Regulations shall not apply to any vehicle in the service of a visiting force.

(8) Part II of these Regulations and Regulations 62 to 83 inclusive and Regulation 107 of these Regulations shall not apply to a motor vehicle which has been submitted for an examination under section 65 of the 1960 Act while it is being used on a road in connection with the carrying out of that examination and is being so used by a person who is empowered under the said section 65 to carry out that examination, or by a person acting under the direction of a person so empowered.

(9) The provisions of these Regulations applicable to trailers contained in Part II (except paragraph (2) of Regulation 6) and Regulations 64 and 94 of these Regulations shall not apply—

(*a*) to any towing implement which is being drawn by a motor vehicle while it is not attached to any vehicle except the one drawing it if the following conditions are satisfied, that is to say,—

(i) the towing implement is not being so drawn during the hours of darkness, and

(a) Cmd. 7997. (b) Treaty Series, No. 11 (1930).

(ii) the vehicle by which it is being so drawn is not driven at a speed exceeding 20 miles per hour; or

(*b*) to any vehicle which is being drawn by a motor vehicle in the exercise of a statutory power of removal.

(10) Any reference in these Regulations to a vehicle which is being drawn by a motor vehicle in the exercise of a statutory power of removal or to a broken down vehicle shall include a reference to any towing implement which is being used for the drawing of any such vehicle.

5.—(1) In relation to a land tractor which complies with the conditions specified in paragraph (3) of this Regulation—

(*a*) Regulations 10, 13, 20 and 40 to 49 inclusive of these Regulations shall not apply;

(*b*) Regulation 17 shall apply as it applies in relation to a works truck; and

(*c*) Regulation 62 shall not apply if its unladen weight does not exceed 3 tons.

(2) Regulations 36 to 39 inclusive shall apply in relation to a land tractor which is a heavy motor car or motor car as they apply in relation to a land tractor which is a motor tractor.

(3) The conditions referred to in paragraph (1) of this Regulation are that while a land tractor is used on a road—

(*a*) it does not haul any object except—

(i) a land implement which is being hauled to or from the site of agricultural, grass cutting, forestry, land levelling, dredging or similar operations or from one part of a farm or forestry estate to another part of that farm or forestry estate,

(ii) a land implement conveyor which is being hauled as aforesaid, or

(iii) an agricultural trailer;

(*b*) it does not carry any load except any such load as it is constructed or adapted to carry;

(*c*) if it is a three-wheeled vehicle fitted with a removable appliance, it does not carry any load;

(*d*) if it is a land tractor fitted with a removable appliance in or on which any such load as aforesaid could be carried, it does not carry any load in or on such appliance unless there is a distance of at least 4 feet between the centre of the area of contact with the road surface of—

(i) a rear wheel, in a case where only one appliance is being used for the carriage of a load, and is fitted to the back of the vehicle,

(ii) any wheel on one side of the vehicle, in any other case,

and that of the nearest wheel on the other side;

(*e*) if it is a land tractor carrying a load in or on a removable appliance in conformity with the foregoing conditions, it does not draw a trailer and not more than one such appliance is fitted to it at any one time or, in a case where one such appliance is a specified appliance for the purposes of paragraph 6(2) of Schedule 4 to the Vehicles (Excise) Act 1962, not more than two of such appliances fitted at opposite ends of the land tractor; and

(*f*) it is not driven at a speed exceeding 20 miles per hour.

PART II

REGULATIONS GOVERNING THE CONSTRUCTION, WEIGHT AND EQUIPMENT OF MOTOR VEHICLES AND TRAILERS

A.—GENERAL

Construction

6.—(1) Every motor cycle and invalid carriage shall be so constructed that it is a wheeled vehicle.

(2) Save as aforesaid every motor vehicle and trailer shall be so constructed that it is either a wheeled vehicle or a track laying vehicle.

Overall length

7.—(1) The overall length of an articulated vehicle shall not exceed 35 feet:

Provided that—

(*a*) the total overall length of any eight-wheeled articulated vehicle registered before 1st January 1931 may equal but shall not exceed 36 feet;

(*b*) this paragraph shall not apply in the case of an articulated vehicle constructed and normally used for the conveyance of indivisible loads of exceptional length—

(i) if each wheel of the vehicle is fitted with a pneumatic tyre, or

(ii) if each wheel of the vehicle is not so fitted but the vehicle is not driven at a speed exceeding 12 miles per hour.

(2) The overall length of a public service vehicle or a vehicle which is constructed or adapted for use as such a vehicle or a chassis which is constructed for such a vehicle shall not exceed 36 feet.

(3) The overall length of a motor vehicle other than one falling within either of the two foregoing paragraphs shall not exceed 30 feet.

Overall height of public service vehicles

8. The overall height of a public service vehicle shall not exceed 15 feet.

Variation of wheel load

9. Every motor vehicle or trailer with more than four wheels and every trailer having more than two wheels being part of an articulated vehicle shall be provided with such compensating arrangement as will ensure that all the wheels will remain in contact with the road surface and under the most adverse conditions will not be subjected to abnormal variations of load:

Provided that this Regulation shall not apply to any steerable wheel of a motor vehicle if the load on such wheel does not exceed 2½ tons.

Springs

10. Every motor vehicle and every trailer drawn thereby shall be equipped with suitable and sufficient springs between each wheel and the frame of the vehicle:

Provided that this Regulation shall not apply—

(*a*) to any vehicle registered on or before 1st January 1932;

(*b*) to any motor tractor not exceeding 4 tons in weight unladen if each unsprung wheel of the vehicle is fitted with a pneumatic tyre;

(*c*) to any land locomotive, land implement, land implement conveyor, agricultural trailer or trailer used solely for the haulage of felled trees;

(*d*) to any motor tractor not exceeding 4 tons in weight unladen used in connection with railway shunting operations which is only used on a road when passing from one portion of the railway track to another for the purpose of such operations;

(*e*) to motor cycles;

(*f*) to mobile cranes;

(*g*) to works trucks and works trailers;

(*h*) to any vehicle not exceeding 4 tons in weight unladen specially designed for and mainly used in operations which necessitate working on rough ground or unmade roads if each wheel of the vehicle is fitted with a pneumatic tyre and if the vehicle is not driven or drawn at a speed exceeding 20 miles per hour;

(*i*) to any vehicle not exceeding 4 tons in weight unladen constructed or adapted for use and used solely for road sweeping if each wheel of the vehicle is fitted with a pneumatic tyre or a tyre of soft or elastic material and if the vehicle is not driven or drawn at a speed exceeding 20 miles per hour;

(*j*) to any pedestrian controlled vehicle, all the wheels of which are equipped with pneumatic tyres; or

(*k*) to any broken down vehicle which is being drawn by a motor vehicle in consequence of the breakdown.

Parking brake

11. Every motor vehicle shall be equipped with a braking system (which may be one of the braking systems hereinafter prescribed) so designed and constructed that it can at all times be set so as effectually to prevent two at least, or in the case of a vehicle with only three wheels one, of the wheels from revolving when the vehicle is not being driven or is left unattended:

Provided that this Regulation shall not apply—

(*a*) to a motor bicycle with or without a sidecar attached;

(*b*) to an invalid carriage; or

(*c*) to a land locomotive registered on or before 1st January 1932.

Vacuum or pressure braking systems

12. Every motor vehicle registered on or after 1st October 1937 which is equipped with a braking system which embodies a vacuum or pressure reservoir or reservoirs shall be provided with a warning device so placed as to be readily visible to the driver of the vehicle when in the driving seat in order to indicate any impending failure or deficiency in the vacuum or pressure system:

Provided that in the case of a vehicle the unladen weight of which does not exceed 3 tons and which is propelled by an internal combustion engine and equipped with a braking system embodying a vacuum reservoir or reservoirs, the vacuum therein being derived directly from the induction system of the engine, it shall not be necessary to provide such a warning device if, in the event of a failure or deficiency in the vacuum system, the brakes of that braking system are sufficient under the most adverse conditions to bring the vehicle to rest within a reasonable distance.

Speedometer

13. To every motor vehicle registered on or after 1st October 1937 and to every public service vehicle which is for the time being used as an

express carriage there shall be fitted an instrument so constructed and in such a position as at all times readily to indicate to the driver of the vehicle the speed thereof within a margin of accuracy of plus or minus 10 per cent. if and when he is driving at a speed in excess of 10 miles per hour :

Provided that this Regulation shall not apply—

(*a*) to an invalid carriage ;

(*b*) to a motor cycle, the cylinder capacity of the engine of which does not exceed 100 c.c. ;

(*c*) to a motor cycle neither constructed or adapted for use nor used for the carriage of a driver or passenger ;

(*d*) to a vehicle which it is at all times unlawful to drive at a speed exceeding 12 miles per hour ;

(*e*) to a vehicle which is incapable by reason of its construction of exceeding a speed of 12 miles per hour on the level under its own power ; or

(*f*) to a works truck.

Diameter of wheels

14. All wheels of a motor vehicle and all wheels of a trailer which are fitted with tyres other than pneumatic tyres shall have a rim diameter of not less than 670 mm. :

Provided that this Regulation shall not apply—

(*a*) to any motor vehicle registered on or before 2nd January 1933 ;

(*b*) to any trailer constructed before 1st January 1933 ;

(*c*) to any wheel fitted to a motor car registered on or before 1st July 1936, if the diameter of the wheel inclusive of the tyre is not less than 670 mm. ;

(*d*) to any works truck or works trailer ;

(*e*) to any motor vehicle or trailer designed for use and used solely in connection with street cleansing, the collection or disposal of refuse or the collection or disposal of the contents of gullies or cesspools ;

(*f*) to any pedestrian controlled vehicle ;

(*g*) to any mobile crane ;

(*h*) to any land implement ; or

(*i*) to any broken down vehicle which is being drawn by a motor vehicle in consequence of the breakdown.

Reversing

15. Every motor vehicle which exceeds 8 hundredweight in weight unladen shall be capable of being so worked that it may travel either forwards or backwards.

View to the front

16. Every motor vehicle shall be so designed and constructed that the driver thereof while controlling the vehicle can at all times have a full view of the road and traffic ahead of the motor vehicle.

Mirrors

17.—(1) Save as provided in paragraph (2) of this Regulation—

(*a*) the following motor vehicles, that is to say, every passenger vehicle adapted to carry more than seven passengers exclusive of the driver and every goods vehicle, including every dual-purpose vehicle, shall

be equipped with at least two mirrors one of which shall be fitted externally on the off-side of the vehicle and the other either internally or on the nearside externally and the mirrors shall be so constructed and fitted to the motor vehicle as to assist the driver, if he so desires, to become aware of traffic to the rear and on both sides rearwards; and

(*b*) subject to the provisions of the foregoing sub-paragraph, every motor vehicle shall be equipped either internally or externally with a mirror so constructed and fitted to the motor vehicle as to assist the driver, if he so desires, to become aware of traffic to the rear of the vehicle.

(2) Paragraph (1) of this Regulation shall not apply—

(*a*) to a two-wheeled motor cycle with or without a sidecar attached;

(*b*) to a land locomotive;

(*c*) to a motor vehicle when drawing a trailer if a person is carried on the trailer in a position which affords an uninterrupted view to the rear and such a person is provided with efficient means of communicating to the driver the effect of signals given by the drivers of other vehicles to the rear thereof;

(*d*) to a works truck if the driver can easily obtain a clear view of traffic to the rear; or

(*e*) to a pedestrian controlled vehicle.

Safety glass

18.—(1) In the case of motor vehicles registered on or after 1st January 1959—

(*a*) being passenger vehicles or dual-purpose vehicles, the glass of windscreens and all windows on the outside,

(*b*) being goods vehicles other than dual-purpose vehicles, the glass of windscreens and all windows in front and on either side of the driver's seat,

shall be safety glass.

(2) Save as provided in the foregoing paragraph, the glass of windscreens and windows facing to the front on the outside of any motor vehicle, except glass fitted to the upper deck of a double-decked vehicle, shall be safety glass.

For the purposes of this paragraph any windscreen or window at the front of the vehicle the inner surface of which is at an angle exceeding 30 degrees to the longitudinal axis of the vehicle shall be deemed to face to the front.

Windscreen wiper

19. An efficient automatic windscreen wiper shall be fitted to every motor vehicle which is so constructed that the driver cannot, by opening the windscreen or otherwise, obtain an adequate view to the front of the vehicle without looking through the windscreen.

Audible warning instrument

20.—(1) Subject to the provisions of this Regulation, every motor vehicle shall be fitted with an instrument capable of giving audible and sufficient warning of its approach or position.

(2) Paragraph (1) of this Regulation shall not apply to a works truck, a pedestrian controlled vehicle or a locomotive which is restricted by virtue of the provisions of Schedule 1 to the 1960 Act to a speed of 12 miles per hour or less.

(3) Except as provided in paragraphs (4) and (5) of this Regulation, no motor vehicle shall be fitted with a gong, bell or siren.

(4) A motor vehicle used solely for fire brigade, ambulance, salvage corps or police purposes, and a vehicle owned by the Forestry Commission and used from time to time for the purpose of fighting fires, may be fitted with a gong, bell or siren.

(5) A motor vehicle used for the conveyance of goods for sale from the vehicle may, if it is also fitted with an instrument or apparatus for the purpose of complying with paragraph (1) of this Regulation, be fitted with an instrument or apparatus designed to emit a sound for the purpose of informing members of the public that goods are on the vehicle for sale.

(6) References in paragraphs (3) and (4) of this Regulation to a gong, bell or siren include references to any instrument or apparatus capable of emitting a sound similar to that emitted by a gong, bell or siren.

Silencer

21. Every vehicle propelled by an internal combustion engine shall be fitted with a silencer, expansion chamber or other contrivance suitable and sufficient for reducing as far as may be reasonable the noise caused by the escape of the exhaust gases from the engine.

Emission of smoke or vapour

22. Every motor vehicle shall be so constructed that no avoidable smoke or visible vapour is emitted therefrom.

23.—(1) This Regulation shall apply to every motor vehicle (other than a works truck) propelled by a compression ignition engine.

(2) Where a motor vehicle to which this Regulation applies is equipped with a device designed to facilitate the starting of the engine by causing it to be supplied with excess fuel the device and any apparatus by means of which it is operated shall be fitted in such a position, or such other provision shall be made, as to ensure that the device cannot readily be operated by a person while he is being carried by the vehicle:

Provided that this Regulation shall not apply in the case of a vehicle fitted with such a device as aforesaid if the device is so designed that—

(i) its use after the engine has been started cannot cause the engine to be supplied with excess fuel, or

(ii) it does not cause any increase in the smoke or visible vapour emitted from the vehicle.

Emission of sparks or grit

24. Every motor vehicle using solid fuel shall be fitted—

(*a*) with an efficient appliance for the purpose of preventing the emission of sparks or grit; and

(*b*) with a tray or shield to prevent ashes and cinders from falling on to the road.

Closets, urinals, lavatory basins and sinks

25. No motor vehicle registered on or after 15th January 1931 or trailer shall be equipped with any closet, urinal, lavatory basin or sink, unless the following requirements are complied with, that is to say,—

(*a*) no vehicle shall be equipped with a closet or urinal the contents of which can be discharged directly on to a road and, except in the case

of a living van, every closet pan or urinal pan shall empty into a tank carried by the vehicle, such tank being efficiently ventilated by means of a pipe the outlet of which is outside the vehicle;

(*b*) every tank into which a closet pan or urinal pan empties and, where no such tank is fitted, every closet and urinal, shall contain non-inflammable and non-irritant chemicals of such character and in such quantity as to form at all times an efficient deodorant and germicide in respect of the contents of the tank, closet or urinal as the case may be; and

(*c*) no lavatory basin or sink shall drain into any closet or urinal or into any tank into which a closet or urinal empties.

Maximum seating capacity of half-decked vehicles

26. A half-decked vehicle shall not be provided with seating capacity for more than fifty passengers exclusive of the driver and conductor if carried.

For the purposes of this Regulation the seating capacity of a half-decked vehicle shall be taken to be the seating capacity which the vehicle would have for the purposes of paragraph 2 of Schedule 2 to the Vehicles (Excise) Act 1962 if it were a vehicle other than a tramcar.

Lighting equipment and reflectors

27.—(1) Every motor vehicle shall be equipped with such lighting equipment and reflectors as to render the vehicle capable of being driven on a road during the hours of darkness without contravention of any of the statutory provisions relating to obligatory lamps or reflectors which are applicable to that vehicle:

Provided that this paragraph shall not apply to a motor vehicle which is not provided with any front lamp or rear lamp.

(2) Where a motor vehicle is provided with a head lamp that lamp shall be so constructed and fitted to the vehicle that if that lamp were to be used to show a light to the front while the vehicle was driven on a road during the hours of darkness such use would not be in contravention of the provisions of Regulation 9 of the Road Vehicles Lighting Regulations 1959(**a**).

(3) For the purposes of the foregoing provisions of this Regulation, a vehicle shall not be treated as provided with any such lamp as is mentioned in those provisions by reason of its carrying such a lamp if—

(*a*) that lamp is so painted over or fitted with a mask that it is not capable of being immediately used, or readily put to use, to show, in the case of a front lamp, a light to the front or, in the case of a rear lamp, a light to the rear; or

(*b*) where the lamp is a lamp constructed to show a light derived from an electric bulb or bulbs, the vehicle is not provided with any system of wiring by means of which that lamp is, or can readily be, connected with a source of electricity.

(4) In this Regulation—

(*a*) the expressions "front lamp" and "rear lamp" in relation to a vehicle, mean respectively—

(i) a lamp carried by that vehicle which faces, or is capable of being readily moved so as to face, to the front, and

(ii) a lamp carried by that vehicle which faces, or is capable of being readily moved so as to face, to the rear,

whether (in either case) that lamp does or does not contain a burner or an electric bulb by means of which it can be used to show a light:

(**a**) S.I. 1959/1869 (1959 II, p. 2381).

Provided that neither of the said expressions shall include any lamp carried by a vehicle for any one or more of the following purposes only, that is to say,—

(i) for use as, or to illuminate, a direction indicator,

(ii) for intimating the intention of the driver of the vehicle to stop or slow down,

(iii) for showing a light to the rear when reversing the vehicle, and

(iv) for the internal illumination of the vehicle,

or any lamp carried by a vehicle which is a land locomotive, a land tractor, a mobile crane, a straddle carrier, a works truck or a vehicle which is movable plant or equipment specially designed or constructed for the purposes of engineering operations, if the lamp is carried by the vehicle for the purpose of providing illumination so as to enable the vehicle to be used at night otherwise than on a road for the particular operations for which it is designed or constructed;

(*b*) the expression "statutory provisions relating to obligatory lamps or reflectors" means the provisions contained in the Road Transport Lighting Act 1957(a), or in any regulations made thereunder with respect to the lamps or reflectors which are thereby required to be carried on vehicles while they are on a road during the hours of darkness, not being provisions which apply to such vehicles only when they are carrying a load overhanging laterally or projecting to the rear or are drawing or being drawn by another vehicle; and

(*c*) the expression "head lamp", in relation to a vehicle, means a front lamp fitted to that vehicle and constructed for the purpose of showing a light derived from an acetylene burner or from an electric bulb the power of which, or from electric bulbs the total power of which, exceeds 7 watts, whether the lamp does or does not contain any such burner or any such bulb or bulbs.

B.—Direction Indicators and Stop Lights

Direction Indicators

28.—(1) Save as provided in paragraph (3) of this Regulation, every motor vehicle registered on or after 1st January 1936 which is fitted with a direction indicator shall—

(*a*) if it is a vehicle fitted with electric lighting equipment, comply with the provisions relating to direction indicators contained in either Part I or Part II or Part III of Schedule 2 to these Regulations; or

(*b*) if it is a vehicle not so fitted, comply with the provisions relating to direction indicators contained in Part V of the said Schedule.

(2) Save as provided in paragraph (3) of this Regulation, every trailer constructed after 1st July 1955 which is fitted with a direction indicator shall comply with the provisions relating to direction indicators contained in either Part III or Part VI of Schedule 2 to these Regulations.

(3) Every motor vehicle registered on or after 1st September 1965 which is fitted with a direction indicator shall comply with the provisions relating to direction indicators contained in Part III of Schedule 2 to these Regulations, and any trailer drawn by such a motor vehicle, or by a motor vehicle registered before that date and fitted with direction indicators in accordance with those provisions, shall be fitted with direction indicators in accordance with those provisions.

(a) 5 & 6 Eliz. 2. c. 51.

Stop Lights

29.—(1) Every stop light fitted to a motor vehicle registered on or after 1st January 1936 or to a trailer shall be fitted at the rear of the vehicle and not to the left of the centre thereof and when in operation shall show a red or amber light:

Provided that nothing in this paragraph shall prevent the fitting of a duplicate stop light on the left or near side of the vehicle which (except when the stop light fitted on the right or offside of the vehicle is showing a flashing light as a direction indicator) comes into operation at the same time as the stop light fitted at the centre or on the right or offside of the vehicle.

(2) Every light shown by a stop light shall be diffused by means of frosted glass or other adequate means and shall be a steady light.

C.—Gas Containers

Gas Containers

30.—(1) The provisions of Schedule 3 to these Regulations shall be complied with in the case of every motor vehicle or trailer to which there is fitted a container intended for the storage of gaseous fuel for the purpose of the propulsion of the vehicle or the drawing vehicle as the case may be.

(2) The requirements of this Regulation shall be in addition to and not in derogation of any of the requirements of Regulations made by the Secretary of State under powers conferred upon him by the Petroleum (Consolidation) Act 1928(a) or by any other Act.

D.—Locomotives

Overall width

31. The overall width of a locomotive shall not exceed 9 feet.

Distribution of weight

32.—(1) This Regulation shall apply to every locomotive having not more than four wheels and registered before 1st June 1955.

(2) Not more than three quarters of the total weight of a locomotive to which this Regulation applies shall be transmitted to the road surface by any two wheels.

Tyres

33.—(1) Save as provided in paragraph (2) of this Regulation, every wheel of a locomotive shall be fitted with a pneumatic tyre or a tyre of soft or elastic material which either—

(*a*) extends continuously round the circumference of the wheel; or

(*b*) is fitted in sections in such manner that—

(i) at no point is any section separated by more than $\frac{3}{4}$ inch from any adjacent section, and

(ii) the aggregate extent of all spaces between the sections measured along any line taken round the outer surface of the tyre and parallel to its edge does not exceed 6 inches.

(2) Paragraph (1) of this Regulation shall not apply to a land locomotive if—

(*a*) the tyre of every steering wheel is smooth-soled and where the tyre touches the surface of the road it is not less than 5 inches in width, and

(a) 18 & 19 Geo. 5. c. 32.

(*b*) the tyre of every driving wheel is not less than 12 inches in width and is either—

(i) smooth-soled,

(ii) shod with diagonal cross bars of not less than 3 inches in width nor more than $\frac{3}{4}$ inch in thickness, extending the full breadth of the tyre and so arranged that the space intervening between adjacent cross bars is not more than 3 inches, or

(iii) shod with diagonal cross bars of soft or elastic material of not less than $2\frac{1}{2}$ inches in width, extending the full breadth of the tyre and so arranged that the space between adjacent cross bars is not more than 3 inches.

Brakes

34. Every locomotive registered before 1st June 1955 shall be equipped with an efficient braking system, the brakes of which act upon all the wheels of the vehicle other than the steering wheels, and so designed and constructed that the application of the brakes will bring the vehicle to rest within a reasonable distance:

Provided that this Regulation shall not apply to a locomotive registered on or before 2nd January 1933 if the locomotive is propelled by steam and the engine thereof is capable of being reversed.

35.—(1) This Regulation shall apply to every locomotive registered on or after 1st June 1955.

(2) Every locomotive to which this Regulation applies shall be equipped with an efficient braking system or efficient braking systems in either case having two means of operation, so designed and constructed that notwithstanding the failure of any part (other than a fixed member or a brake shoe anchor pin) through or by means of which the force necessary to apply the brakes is transmitted, there shall still be available for application by the driver to not less than half the number of the wheels of the vehicle brakes sufficient under the most adverse conditions to bring the vehicle to rest within a reasonable distance:

Provided that this paragraph shall not apply in the case of a road roller if the vehicle is equipped with one braking system with one means of operation.

(3) The application of one means of operation shall not affect or operate the pedal or hand lever of the other means of operation.

(4) No braking system shall be rendered ineffective by the non-rotation of the engine.

(5) All the brakes which are operated by one of the means of operation shall be capable of being applied by direct mechanical action without the intervention of any hydraulic, electric or pneumatic device.

(6) Where any brake shoe is capable of being applied by more than one means of operation, all the wheels of a locomotive to which this Regulation applies shall be fitted with brakes all of which are operated by one of the means of operation:

Provided that—

(*a*) where a vehicle has more than six wheels, at least four of which are steering wheels, it shall be a sufficient compliance with this paragraph if brakes are fitted to all the wheels, other than two steering wheels which are situated on opposite sides of the vehicle, and if all such brakes are operated by one of the means of operation;

(*b*) where a vehicle has more than four wheels and the drive is transmitted to all wheels other than the steering wheels without the interposition of a differential driving gear or similar mechanism between the axles carrying the driving wheels, it shall be deemed to be a sufficient compliance with this paragraph if one means of operation operates the brakes on two driving wheels situated on opposite sides of the vehicle and the other means of operation operates brakes on all the other wheels required to be fitted with brakes by this paragraph ; and

(*c*) where means of operation are provided in addition to those prescribed by this Regulation such additional means of operation may be disregarded for the purposes of this paragraph.

(7) One at least of the means of operation shall be capable of causing brakes to be applied directly, and not through the transmission gear, to not less than half the number of the wheels of the vehicle:

Provided that where a locomotive to which this Regulation applies has more than four wheels and the drive is transmitted to all wheels other than the steering wheels without the interposition of a differential driving gear or similar mechanism between the axles carrying the driving wheels, it shall be deemed to be a sufficient compliance with this paragraph if the brakes applied by one means of operation act directly on two driving wheels on opposite sides of the vehicle and the brakes applied by the other means of operation act directly on all other driving wheels.

(8) For the purpose of this Regulation—

(*a*) not more than one front wheel shall be included in half the number of the wheels of the vehicle for the purposes aforesaid except that this provision shall not apply to a locomotive with more than three wheels, whether or not any brake shoe is capable of being applied by more than one means of operation, if as respects the fitting of its wheels with brakes and the operation of those brakes the provisions of paragraph (6) of this Regulation relating to such matters are complied with ; and

(*b*) every moving shaft to which any part of a braking system or any means of operation thereof is connected or by which it is supported shall be deemed to be part of that system.

E.—Motor Tractors

Overall width

36. The overall width of a motor tractor shall not exceed 7 feet 6 inches.

Overhang

37. The overhang of a motor tractor shall not exceed 6 feet.

Brakes

38.—(1) Every motor tractor shall be equipped with an efficient braking system or efficient braking systems in either case having two means of operation, so designed and constructed that, notwithstanding the failure of any part (other than a fixed member or a brake shoe anchor pin) through or by means of which the force necessary to apply the brakes is transmitted, there shall still be available for application by the driver to not less than half the number of the wheels of the vehicle brakes sufficient under the most adverse conditions to bring the vehicle to rest within a reasonable distance :

Provided that this paragraph shall not apply in the case of a road roller or a land tractor, not propelled by steam, if the vehicle is equipped with one braking system with one means of operation.

(2) The application of one means of operation shall not affect or operate the pedal or hand lever of the other means of operation.

(3) In the case of vehicles registered on or after 1st April 1938 no braking system shall be rendered ineffective by the non-rotation of the engine:

Provided that this paragraph shall not apply in the case of any vehicle referred to in sub-paragraph (*b*) of paragraph (7) of this Regulation.

(4) In the case of a motor tractor registered on or after 1st April 1938 all the brakes which are operated by one of the means of operation shall be capable of being applied by direct mechanical action without the intervention of any hydraulic, electric or pneumatic device.

(5) Where any brake shoe is capable of being applied by more than one means of operation, all the wheels of the motor tractor shall be fitted with brakes all of which are operated by one of the means of operation:

Provided that where means of operation are provided in addition to those prescribed by this Regulation such additional means of operation may be disregarded for the purposes of this paragraph.

(6) In the case of a motor tractor registered after 14th January 1931 other than a land tractor, one at least of the means of operation shall be capable of causing brakes to be applied directly, and not through the transmission gear, to not less than half the number of the wheels of the vehicle:

Provided that where a motor tractor has more than four wheels and the drive is transmitted to all wheels other than the steering wheels without the interposition of a differential driving gear or similar mechanism between the axles carrying the driving wheels, it shall be deemed to be a sufficient compliance with this paragraph if the brakes applied by one means of operation act directly on two driving wheels on opposite sides of the vehicle and the brakes applied by the other means of operation act directly on all other driving wheels.

(7) For the purpose of this Regulation—

(*a*) in the case of a motor tractor registered on or after 1st October 1938—

(i) not more than one front wheel shall be included in half the number of the wheels of the vehicle for the purposes aforesaid except that this provision shall not apply to a motor tractor with more than three wheels, whether or not any brake shoe is capable of being applied by more than one means of operation, if as respects the fitting of its wheels with brakes and the operation of those brakes the provisions of paragraph (5) of this Regulation relating to such matters are complied with, and

(ii) every moving shaft to which any part of a braking system or any means of operation thereof is connected or by which it is supported shall be deemed to be part of that system; and

(*b*) in the case of a motor tractor propelled by steam the engine shall be deemed to be an efficient braking system with one means of operation if the engine is capable of being reversed and, in the case of a motor tractor registered on or after 1st October 1943, is incapable of being disconnected from any of the driving wheels of the vehicle except by the sustained effort of the driver.

Tyres

39. Every wheel of a motor tractor shall be fitted with a pneumatic tyre or a tyre of soft or elastic material:

Provided that this Regulation shall not apply to a land tractor if—

(*a*) the tyre of every steering wheel is smooth-soled and where the tyre touches the surface of the road it is not less than 2½ inches in width; and

(*b*) the tyre of every driving wheel, in the case of vehicles exceeding 3 tons in weight unladen, is not less than 6 inches in width and, in the case of vehicles not exceeding 3 tons in weight unladen, is not less than 3 inches in width and is either—

(i) smooth-soled,

(ii) shod with diagonal cross bars of not less than 3 inches in width nor more than ¾ inch in thickness, extending the full breadth of the tyre and so arranged that the space between adjacent cross bars is not more than 3 inches, or

(iii) shod with diagonal cross bars of soft or elastic material of not less than 2½ inches in width, extending the full breadth of the tyre and so arranged that the space between adjacent cross bars is not more than 3 inches.

F.—Heavy Motor Cars

Overall width

40. The overall width of a heavy motor car shall not exceed 7 feet 6 inches:

Provided that the said width may be exceeded—

(*a*) by not more than 3 inches in the case of a vehicle propelled by steam, using solid fuel and registered before 1st January 1939, if the excess width is due solely to the projection of the wheels or tyres beyond the sides of the vehicle;

(*b*) by not more than 6 inches in the case of—

(i) a vehicle registered on or before 1st July 1932, if the excess width has been necessarily caused by the conversion of the vehicle from use with solid tyres to use with pneumatic tyres,

(ii) a vehicle constructed or adapted for use and used solely for road sweeping, and

(iii) a vehicle the unladen weight of which is 4 tons or more, every wheel of which is fitted with a pneumatic tyre and which is either a goods vehicle or a vehicle so constructed or adapted as to form part of an articulated vehicle; and

(*c*) by not more than 8½ inches in the case of a public service vehicle or a vehicle which is constructed or adapted for use as such a vehicle or a chassis which is constructed for such a vehicle.

Overhang

41. The overhang of a heavy motor car shall not exceed 50 per cent. of the distance between the plane perpendicular to the longitudinal axis of the vehicle which passes through the centre or centres of the front wheel or wheels and the foremost vertical plane from which the overhang is to be measured as defined in Regulation 3 of these Regulations:

Provided that—

(*a*) in the case of a heavy motor car registered before 1st October 1938, it shall be a sufficient compliance with this Regulation if the overhang does not exceed 7/24ths of the overall length of the vehicle;

(*b*) in the case of a heavy motor car not exceeding 20 feet in overall length, the overhang may be increased by not more than 9 inches but not so as to exceed 7/24ths of the overall length of the vehicle;

(*c*) in the case of a heavy motor car exceeding 20 feet in overall length the overhang may be increased by not more than 15 inches but not so as to exceed 7/24ths of the overall length of the vehicle;

(*d*) in the case of a vehicle designed for use and mainly used for the purpose of heating a road or other like surface in the process of construction, repair or maintenance, no part of the heating plant shall be taken into account when calculating the overhang; and

(*e*) this Regulation shall not apply in the case of—

(i) a heavy motor car registered before 15th August 1928,

(ii) a heavy motor car designed for use and used solely in connection with street cleansing, the collection or disposal of refuse or the collection or disposal of the contents of gullies or cesspools,

(iii) a works truck, or

(iv) a heavy motor car designed so that it can dispose of its load by tipping to the rear, if the overhang does not exceed 45 inches.

Brakes

42.—(1) Every heavy motor car shall be equipped either with an efficient braking system having two means of operation or with two efficient braking systems each having a separate means of operation.

(2) The braking system or braking systems of every heavy motor car registered after 15th August 1928 shall be so designed and constructed that, notwithstanding the failure of any part (other than a fixed member or a brake shoe anchor pin) through or by means of which the force necessary to apply the brakes is transmitted, there shall still be available for application by the driver to not less than half the number of the wheels of the vehicle brakes sufficient under the most adverse conditions to bring the vehicle to rest within a reasonable distance.

(3) The braking system or braking systems of every heavy motor car to which Schedule 4 to these Regulations applies shall comply with the requirements of that Schedule relating to the efficiency of the brakes of such heavy motor cars.

(4) The braking system or braking systems of every heavy motor car registered on or before 15th August 1928, not being a heavy motor car to which the said Schedule 4 applies, shall be sufficient under the most adverse conditions to bring the vehicle to rest within a reasonable distance.

(5) Paragraphs (1) and (2) of this Regulation shall not apply in the case of a works truck if it is equipped with one braking system having one means of operation.

(6) The application of one means of operation shall not affect or operate the pedal or hand lever of the other means of operation.

(7) In the case of vehicles registered on or after 1st April 1938 no braking system shall be rendered ineffective by the non-rotation of the engine:

Provided that this paragraph shall not apply in the case of any vehicle referred to in sub-paragraph (*b*) of paragraph (12) of this Regulation.

(8) All the brakes of a heavy motor car which are operated by one means of operation shall be capable of being applied by direct mechanical action without the intervention of any hydraulic, electric or pneumatic device.

(9) Where any brake shoe is capable of being applied by more than one means of operation all the wheels of the heavy motor car shall be fitted with brakes all of which are operated by one of the means of operation:

Provided that—

(*a*) where a heavy motor car has more than six wheels, at least four of which are steering wheels, it shall be a sufficient compliance with this paragraph if brakes are fitted to all the wheels, other than two steering wheels which are situated on opposite sides of the vehicle, and all such brakes are operated by one of the means of operation;

(*b*) where a heavy motor car has more than four wheels and the drive is transmitted to all wheels other than the steering wheels without the interposition of a differential driving gear or similar mechanism between the axles carrying the driving wheels, it shall be deemed to be a sufficient compliance with this paragraph if one means of operation operates the brakes on two driving wheels situated on opposite sides of the vehicle and the other means of operation operates brakes on all the other wheels required to be fitted with brakes by this paragraph; and

(*c*) where means of operation are provided in addition to those prescribed by this Regulation such additional means of operation may be disregarded for the purposes of this paragraph.

(10) One at least of the means of operation shall be capable of causing brakes to be applied directly, and not through the transmission gear, to not less than half the number of the wheels of the vehicle:

Provided that where a heavy motor car has more than four wheels and the drive is transmitted to all wheels other than the steering wheels without the interposition of a differential driving gear or similar mechanism between the axles carrying the driving wheels, it shall be deemed to be a sufficient compliance with this paragraph if the brakes applied by one means of operation act directly on two driving wheels on opposite sides of the vehicle and the brakes applied by the other means of operation act directly on all other driving wheels.

(11) Paragraphs (6) to (10) inclusive of this Regulation shall not apply to a heavy motor car registered on or before 15th August 1928.

(12) For the purpose of this Regulation—

(*a*) in the case of any motor vehicle—

(i) not more than one front wheel shall be included in half the number of the wheels of the vehicle for the purposes aforesaid except that this provision shall not apply either to a heavy motor car with more than three wheels, whether or not any brake shoe is capable of being applied by more than one means of operation, if as respects the fitting of its wheels with brakes and the operation of those brakes the provisions of paragraph (9) of this Regulation relating to such matters are complied with, or to a works truck, and

(ii) every moving shaft to which any part of a braking system or any means of operation thereof is connected or by which it is supported shall be deemed to be part of that system; and

(*b*) in the case of a heavy motor car propelled by steam and not used as a public service vehicle the engine shall be deemed to be an efficient braking system with one means of operation if the engine is capable of being reversed and, in the case of a heavy motor car registered on or after 1st January 1927, is incapable of being disconnected from any of the driving wheels of the vehicle except by the sustained effort of the driver.

Tyres

43.—(1) Save as provided in paragraph (2) of this Regulation every wheel of a heavy motor car shall be fitted with a pneumatic tyre.

(2) In the case of any of the following vehicles every wheel shall be fitted with a pneumatic tyre or a tyre of soft or elastic material: —

(*a*) heavy motor cars registered on or before 2nd January 1933 ;

(*b*) heavy motor cars exceeding 4 tons in weight unladen mainly used in operations which necessitate working on rough ground or unmade roads ;

(*c*) vehicles designed for use and used solely in connection with street cleansing, the collection or disposal of refuse or the collection or disposal of the contents of gullies or cesspools ;

(*d*) turntable fire escapes ;

(*e*) tower wagons ; and

(*f*) works trucks.

Wings

44. A heavy motor car shall be equipped with wings or other similar fittings to catch, so far as practicable, mud or water thrown up by the rotation of the wheels, unless adequate protection is afforded by the body of the vehicle:

Provided that this Regulation shall not apply—

(*a*) in relation to the rear wheels of any heavy motor car for the time being forming part of an articulated vehicle if the trailer forming the remaining part of the articulated vehicle is used only for or, when empty, in connection with the carriage of round timber ;

(*b*) in the case of a vehicle in an unfinished condition proceeding to a works for completion ; or

(*c*) in the case of a works truck.

G.—Motor Cars

Overall width

45. The overall width of a motor car shall not exceed 7 feet 6 inches :

Provided that the said width may be exceeded by—

(*a*) not more than 6 inches in the case of a vehicle constructed or adapted for use and used solely for road sweeping ; and

(*b*) not more than 8½ inches in the case of a public service vehicle or a vehicle which is constructed or adapted for use as such a vehicle or a chassis which is constructed for such a vehicle.

Overhang

46. The overhang of a motor car shall not exceed 50 per cent. of the distance between the plane perpendicular to the longitudinal axis of the vehicle which passes through the centre or centres of the front wheel or wheels and the foremost vertical plane from which the overhang is to be measured as defined in Regulation 3 of these Regulations :

Provided that—

(*a*) in the case of a motor car registered before 1st October 1938, it shall be sufficient compliance with this Regulation if the overhang does not exceed 7/24ths of the overall length of the vehicle;

(*b*) in the case of a motor car not exceeding 20 feet in overall length, the overhang may be increased by not more than 9 inches but not so as to exceed 7/24ths of the overall length of the vehicle;

(*c*) in the case of a motor car exceeding 20 feet in overall length, the overhang may be increased by not more than 15 inches but not so as to exceed 7/24ths of the overall length of the vehicle; and

(*d*) this Regulation shall not apply in the case of—

(i) a motor car registered on or before 2nd January 1933;

(ii) a motor car designed for use and used solely in connection with street cleansing, the collection or disposal of refuse or the collection or disposal of the contents of gullies or cesspools or as an ambulance; or

(iii) a works truck.

Brakes

47.—(1) Every motor car shall be equipped either with an efficient braking system having two means of operation or with two efficient braking systems each having a separate means of operation.

(2) The braking system or braking systems of every motor car shall be so designed and constructed that notwithstanding the failure of any part (other than a fixed member or a brake shoe anchor pin) through or by means of which the force necessary to apply the brakes is transmitted there shall still be available for application by the driver to not less than half the number of the wheels of the vehicle brakes sufficient under the most adverse conditions to bring the vehicle to rest within a reasonable distance:

Provided that in the event of such failure as aforesaid it shall not be necessary for brakes to be available for application by the driver—

(*a*) in the case of a motor car registered before 1st October 1938, to more than two wheels;

(*b*) in the case of a vehicle having less than four wheels, to more than one wheel.

(3) The braking system or braking systems of every motor car to which Schedule 4 to these Regulations applies shall comply with the requirements of that Schedule relating to the efficiency of the brakes of such motor cars.

(4) Paragraphs (1) and (2) of this Regulation shall not apply in the case of a motor car first registered under the Motor Car Act 1903(a) before 1st January 1915 but—

(*a*) such a motor car shall be equipped with an efficient braking system;

(*b*) that system shall be so designed and constructed that brakes shall be available for application by the driver, in the case of a vehicle with not less than four wheels, to two wheels of the vehicle, and in the case of a vehicle with less than four wheels, to one wheel of the vehicle; and

(*c*) if such a motor car is not one to which the said Schedule 4 applies, the brakes required by the foregoing sub-paragraph to be available for application shall be brakes sufficient under the most adverse conditions to bring the vehicle to rest within a reasonable distance.

(a) 3 Edw. 7. c. 36.

(5) The foregoing paragraphs of this Regulation shall not apply in the case of a works truck if it is equipped with one braking system with one means of operation.

(6) The application of one means of operation shall not affect or operate the pedal or hand lever of the other means of operation.

(7) In the case of vehicles registered on or after 1st April 1938, no braking system shall be rendered ineffective by the non-rotation of the engine:

Provided that this paragraph shall not apply in the case of any vehicle referred to in sub-paragraph (*b*) of paragraph (11) of this Regulation.

(8) All the brakes of a motor car which are operated by one of the means of operation shall be capable of being applied by direct mechanical action without the intervention of any hydraulic, electric or pneumatic device.

(9) In the case of a motor car with more than three wheels where any brake shoe is capable of being applied by more than one means of operation all the wheels shall be fitted with brakes all of which are operated by one of the means of operation:

Provided that—

(*a*) where a motor car has more than six wheels, at least four of which are steering wheels, it shall be a sufficient compliance with this paragraph if brakes are fitted to all the wheels, other than two steering wheels which are situated on opposite sides of the vehicle, and all such brakes are operated by one of the means of operation;

(*b*) where a motor car has more than four wheels and the drive is transmitted to all wheels other than the steering wheels without the interposition of a differential driving gear or similar mechanism between the axles carrying the driving wheels, it shall be deemed to be a sufficient compliance with this paragraph if one means of operation operates the brakes on two driving wheels situated on opposite sides of the vehicle and the other means of operation operates brakes on all the other wheels required to be fitted with brakes by this paragraph;

(*c*) where means of operation are provided in addition to those prescribed by this Regulation such additional means of operation may be disregarded for the purposes of this paragraph;

(*d*) this paragraph shall not apply to a pedestrian controlled vehicle not exceeding 8 hundredweight in weight unladen; and

(*e*) in the case of a motor car the unladen weight of which does not exceed 2 tons or which is constructed solely for the carriage of passengers and their effects and adapted to carry not more than seven passengers exclusive of the driver, it shall be deemed to be a sufficient compliance with this paragraph if one means of operation operates brakes fitted to all but two of the wheels and, as respects each of those two wheels, operates a brake on the shaft leading thereto and no gearing is interposed between the brake and the wheel.

(10) One at least of the means of operation shall be capable of causing brakes to be applied directly and not through the transmission gear to not less than half the number of the wheels of the vehicle:

Provided that—

(*a*) in the case of a motor car having more than four wheels and registered before 1st October 1938, it shall be deemed to be a sufficient

compliance with this paragraph if one of the means of operation applies brakes directly and not through the transmission gear to not less than two of the wheels of the vehicle; and

(*b*) where a motor car has more than four wheels and the drive is transmitted to all wheels other than the steering wheels without the interposition of a differential driving gear or similar mechanism between the axles carrying the driving wheels, it shall be deemed to be a sufficient compliance with this paragraph if the brakes applied by one means of operation act directly on two driving wheels on opposite sides of the vehicle and the brakes applied by the other means of operation act directly on all other driving wheels.

(11) For the purpose of this Regulation—

(*a*) in the case of a motor car registered on or after 1st October 1938—

(i) not more than one front wheel shall be included in half the number of the wheels of the vehicle for the purposes aforesaid:

Provided that this provision shall not apply—

(1) to a motor car the unladen weight of which does not exceed 1 ton,

(2) to a motor car which is a passenger vehicle constructed or adapted to carry not more than seven passengers exclusive of the driver,

(3) to a works truck, or

(4) to a motor car with more than three wheels, whether or not any brake shoe is capable of being applied by more than one means of operation, if as respects the fitting of its wheels with brakes and the operation of those brakes the provisions of paragraph (9) of this Regulation relating to such matters are complied with, and

(ii) every moving shaft to which any part of a braking system or any means of operation thereof is connected or by which it is supported shall be deemed to be part of that system; and

(*b*) in the case of a motor car propelled by steam and not used as a public service vehicle, the engine shall be deemed to be an efficient braking system with one means of operation if the engine is capable of being reversed and is incapable of being disconnected from any of the driving wheels of the vehicle except by the sustained effort of the driver.

Tyres

48.—(1) Save as provided in paragraph (2) of this Regulation every wheel of a motor car the unladen weight of which exceeds 1 ton shall be fitted with a pneumatic tyre.

(2) In the case of any of the following vehicles every wheel shall, if the unladen weight of the vehicle exceeds 1 ton, be fitted with a pneumatic tyre or a tyre of soft or elastic material:—

(*a*) motor cars registered on or before 2nd January 1933;

(*b*) works trucks; and

(*c*) motor cars designed for use and used solely in connection with street cleansing, the collection or disposal of refuse or the collection or disposal of the contents of gullies or cesspools.

Wings

49. A motor car shall be equipped with wings or other similar fittings to catch, so far as practicable, mud or water thrown up by the rotation of the wheels unless adequate protection is afforded by the body of the vehicle:

Provided that this Regulation shall not apply—

(*a*) in relation to the rear wheels of any motor car for the time being forming part of an articulated vehicle if the trailer forming the remaining part of the articulated vehicle is used only for or, when empty, in connection with the carriage of round timber;

(*b*) in the case of a vehicle in an unfinished condition proceeding to a works for completion; or

(*c*) in the case of a works truck.

H.—Motor Cycles

Brakes

50.—(1) Every motor cycle shall be equipped either with an efficient braking system having two means of operation or with two efficient braking systems each having a separate means of operation.

(2) The braking system or braking systems with which a motor cycle is required to be equipped shall be so designed and constructed that notwithstanding the failure of any part (other than a fixed member or a brake shoe anchor pin) through or by means of which the force necessary to apply the brakes is transmitted there shall still be available for application by the driver to at least one wheel of the vehicle brakes sufficient under the most adverse conditions to bring the vehicle to rest within a reasonable distance.

(3) The braking system or braking systems of every motor cycle to which Schedule 4 to these Regulations applies shall comply with the requirements of that Schedule relating to the efficiency of the brakes of such motor cycles.

(4) Paragraphs (1) and (2) of this Regulation shall not apply in the case of a motor cycle first registered under the Motor Car Act 1903 or the Roads Act 1920 before 1st January 1927 but—

(*a*) such a motor cycle shall be equipped with an efficient braking system, and

(*b*) that system shall be so designed and constructed that brakes shall be available for application by the driver to at least one wheel of the vehicle.

(5) The foregoing paragraphs of this Regulation shall not apply in the case of a works truck if it is equipped with one braking system having one means of operation.

(6) In the case of a motor cycle required to have two means of operating brakes, the application of one means of operation shall not affect or operate the pedal or hand lever of the other means of operation.

Tyres

51. Every wheel of a motor cycle shall be fitted with a pneumatic tyre:

Provided that this Regulation shall not apply to a works truck or a pedestrian controlled vehicle if, in either case, every wheel of the vehicle is fitted with a tyre of soft or elastic material.

Wings

52. Every motor cycle other than a works truck shall be equipped with wings or other similar fittings to catch, so far as practicable, mud or water thrown up by the rotation of the wheels.

I.—Invalid Carriages

Width

53. The overall width of an invalid carriage shall not exceed 7 feet 2 inches.

Brakes

54. Every invalid carriage shall be equipped with an efficient braking system, the brakes of which act on at least two wheels of the vehicle, so designed and constructed that the application of the brakes shall bring the vehicle to rest within a reasonable distance.

Wings

55. Every invalid carriage shall be equipped with wings or other similar fittings to catch, so far as practicable, mud or water thrown up by the rotation of the wheels.

J.—Trailers

Overall length

56.—(1) The overall length of a trailer shall not exceed 22 feet:

Provided that this Regulation shall not apply—

(*a*) to a trailer constructed and normally used for the conveyance of indivisible loads of exceptional length;

(*b*) to a land implement;

(*c*) to a trailer forming part of an articulated vehicle;

(*d*) to any broken down vehicle which is being drawn by a motor vehicle in consequence of the breakdown;

(*e*) to a trailer which is a trolley vehicle in course of construction or delivery; or

(*f*) to any trailer which is drying or mixing plant designed for the production of asphalt or of bituminous or tar macadam and used mainly for the construction, repair or maintenance of roads or which is a road planing machine used as aforesaid if, in any such case, the overall length of the trailer together with that of the motor vehicle by which it is drawn does not exceed 60 feet.

(2) For the purposes of the foregoing paragraph, the overall length of a trailer shall be treated as excluding any part of the trailer designed primarily for use as a means of attaching it to another vehicle and any fitting designed for use in connection with any such part.

Overall width

57.—(1) Save as provided in paragraph (2) of this Regulation the overall width of a trailer shall not exceed 7 feet 6 inches:

Provided that the said width may be exceeded—

(*a*) by not more than 6 inches in the case of a trailer every wheel of which is fitted with a pneumatic tyre and which is drawn by a vehicle the overall width of which exceeds 7 feet 6 inches and which is a locomotive, or a heavy motor car as mentioned in item (iii) of proviso (*b*) to Regulation 40;

(*b*) by not more than 15 inches in the case of a trailer which is in use by a travelling showman in connection with his business and was in such use before 15th January 1931 ; and

(*c*) by not more than 6 inches in the case of a trailer constructed before 1st January 1933 which has been converted from use with solid tyres to use with pneumatic tyres if the width of no part of the vehicle exceeds 7 feet 6 inches except in so far as such increase is rendered necessary by the conversion.

(2) This Regulation shall not apply to a land implement, to a trailer which is a trolley vehicle in course of construction or delivery or to a broken down vehicle which is being drawn by a motor vehicle in consequence of the breakdown.

Brakes

58.—(1) Save as provided in paragraph (2) of this Regulation every trailer exceeding 2 hundredweight in weight unladen shall be equipped with an efficient braking system the brakes of which are capable of being applied when it is being drawn—

(*a*) to at least two wheels in the case of a trailer having not more than four wheels ;

(*b*) to at least four wheels in the case of a trailer having more than four wheels ; and

(*c*) in the case of trailers constructed after 1st April 1938, to at least half the number of wheels of the trailer,

and so constructed that—

(i) the brakes can be applied either by the driver of the drawing vehicle or by some other person on such vehicle or the trailer,

(ii) in the case of a trailer forming part of an articulated vehicle and being permanently attached to the drawing vehicle, the brakes are capable of being set so as effectively to prevent two at least of the wheels from revolving when the trailer is not being drawn, and

(iii) in the case of any other trailer, the brakes are capable of being set so as effectively to prevent two at least of the wheels from revolving when the trailer, whether it is attached to the drawing vehicle or not, is not being drawn :

Provided that the provisions of item (i) of this paragraph shall not apply in the case of a trailer not exceeding 1 ton in weight unladen or in the case of a trailer not constructed or adapted to carry any load, other than plant or other special appliance or apparatus which is a permanent or essentially permanent fixture, and not exceeding 45 hundredweight in total weight, or in the case of a living van not exceeding 2 tons in weight unladen and fitted with pneumatic tyres, if in any such case the brakes of the trailer automatically come into operation on the overrun of the trailer.

In this paragraph the expression " permanently attached " means that the trailer can only be detached from the drawing vehicle by an operation involving the use of facilities which are normally found only in a workshop.

(2) Paragraph (1) of this Regulation shall not apply—

(*a*) to any land implement or land implement conveyor drawn by a motor vehicle ;

(*b*) to any trailer designed for use and used for street cleansing which does not carry any load other than its necessary gear and equipment;

(*c*) to any broken down vehicle which is being drawn by a motor vehicle in consequence of the breakdown;

(*d*) to any agricultural trailer constructed before 1st July 1947 when drawn by a motor tractor or a land tractor which is not a motor tractor if—

(i) its laden weight does not exceed 4 tons,

(ii) it is the only trailer so drawn, and

(iii) it is not drawn at a speed exceeding 10 miles per hour; or

(*e*) to any trailer used only for the carriage of plant and materials for producing gas for the propulsion of the drawing vehicle if the drawing vehicle is either a goods vehicle weighing not less than 2 tons in weight unladen or a public service vehicle.

(3) In the case of trailers constructed on or after 1st April 1938, the braking system shall be so constructed that it is not rendered ineffective by the non-rotation of the engine of the drawing vehicle.

Tyres

59. Subject to the provisions of the following Regulation every wheel of a trailer when the trailer is being drawn on a road shall be fitted with a pneumatic tyre or a tyre of soft or elastic material:

Provided that this Regulation shall not apply—

(*a*) to any land implement or agricultural trailer;

(*b*) to any trailer constructed before 15th January 1931 which is specially designed for the conveyance of horses and cattle and is used either for that purpose or for some other purpose connected with agriculture.

(*c*) to any trailer constructed before 15th January 1931 which is specially designed and used for the conveyance of furniture and other similar household effects; or

(*d*) to any trailer used for the purpose of carrying water for a road roller which is being used in connection with the construction, maintenance or repair of roads.

60. Every wheel of a trailer constructed after 1st January 1933 when drawn by a heavy motor car or a motor car shall be fitted with a pneumatic tyre:

Provided that this Regulation shall not apply to any trailer—

(*a*) which is a works trailer;

(*b*) which is designed for use and used solely in connection with street cleansing, the collection or disposal of refuse or the collection or disposal of the contents of gullies or cesspools;

(*c*) when drawn by a heavy motor car every wheel of which is not required to be fitted with a pneumatic tyre;

(*d*) when used for the purpose of carrying water for a road roller which is being used in connection with the construction, maintenance or repair of roads;

(*e*) which is a land implement or an agricultural trailer drawn by a land tractor; or

(*f*) which is a broken down vehicle and is being drawn by a motor vehicle in consequence of the breakdown.

Wings

61. The rear wheels of every trailer or, in the case of a two-wheeled trailer both its wheels, shall be equipped with wings or other similar fittings to catch, so far as practicable, mud or water thrown up by the rotation of the wheels, unless adequate protection is afforded by the body of the trailer:

Provided that this Regulation shall not apply—

(*a*) to trailers in an unfinished condition proceeding to a works for completion;

(*b*) to land implements;

(*c*) to land implement conveyors;

(*d*) to living vans;

(*e*) to watercarts;

(*f*) to trailers used only for or, when empty, in connection with the carriage of round timber;

(*g*) to trailer pumps used for fire brigade purposes;

(*h*) to trailers drawn by a vehicle the maximum speed of which is restricted by virtue of the provisions of Schedule 1 to the 1960 Act to 12 miles per hour or less; or

(*i*) to any broken down vehicle which is being drawn in consequence of the breakdown.

PART III

REGULATIONS GOVERNING THE USE ON ROADS OF MOTOR VEHICLES AND TRAILERS

Markings on locomotives, tractors and heavy motor cars

62. The owner of a locomotive, motor tractor or heavy motor car shall cause the unladen weight of the vehicle to be painted or otherwise plainly marked upon some conspicuous place on the left or near side of the vehicle:

Provided that this Regulation shall not apply to a heavy motor car not registered under the Roads Act 1920, the Vehicles (Excise) Act 1949 or the Vehicles (Excise) Act 1962.

Markings on trailers

63. The owner of a trailer which, in compliance with Regulation 58 of these Regulations, is fitted with overrun brakes shall cause the unladen weight of the trailer or, in the case of a trailer not constructed or adapted to carry any load other than plant or other special appliance or apparatus which is a permanent or essentially permanent fixture, the total weight of the trailer to be painted or otherwise plainly marked upon some conspicuous place on the left or near side of it.

Trailer plate

64.—(1) Save as provided in paragraph (4) of this Regulation, when a motor vehicle is drawing a trailer or trailers on a road there shall be exhibited in a conspicuous position on the back of the trailer (or when more than one trailer is being drawn on the back of the rearmost trailer) a distinguishing mark in the form and complying with the provisions set out in the diagram contained in Schedule 5 to these Regulations.

(2) The reflex lenses indicated in the said diagram shall be not less than 19 mm. in diameter and the colour thereof shall be red.

(3) The mark shall be so fixed to the trailer that—

(*a*) it is vertical and easily distinguishable from behind the trailer;

(*b*) it is either on the centre line or to the offside of the trailer; and

(*c*) no part of it is at a height exceeding 4 feet from the ground,

and in all cases it shall be kept clean and unobscured.

(4) This Regulation shall not apply—

(*a*) to any trailer forming part of an articulated vehicle;

(*b*) to any broken down vehicle while being drawn in consequence of the breakdown;

(*c*) to any trailer drawn by a motor cycle being a passenger vehicle or by a motor car being either a passenger vehicle or a dual-purpose vehicle and in each case adapted to carry not more than seven passengers exclusive of the driver;

(*d*) to any trailer specially constructed for the carriage of round timber;

(*e*) to any land implement (other than a living van) and any land implement conveyor or any agricultural trailer; or

(*f*) to any water cart drawn by, and used for carrying water for, a road roller.

Laden weight of locomotive

65.—(1) Save as provided in paragraph (2) of this Regulation, the laden weight of a locomotive shall not exceed 20½ tons.

(2) The laden weight of a locomotive which is equipped with suitable and sufficient springs between each wheel and the frame of the vehicle and every wheel of which is fitted with a pneumatic tyre or a tyre of soft or elastic material shall not exceed—

(*a*) in the case of a vehicle with less than six wheels, 22 tons;

(*b*) in the case of a vehicle with six wheels, 26 tons; or

(*c*) in the case of a vehicle with more than six wheels, 30 tons.

(3) The total weight transmitted to the road surface by any two wheels of a locomotive in line transversely shall not exceed 11 tons:

Provided that this paragraph shall not apply to a road roller or to a vehicle with not more than four wheels registered before 1st June 1955.

Weight of trailers drawn by a locomotive

66. The maximum total weight of all trailers, whether wheeled or track laying and whether laden or unladen, drawn by a locomotive whether wheeled or track laying shall not exceed 40 tons.

Laden weight of heavy motor car or motor car

67.—(1) In the case of a heavy motor car or motor car which is a public service vehicle the total weight transmitted to the road surface by any two wheels in line transversely shall not exceed 9 tons and the sum of the weights so transmitted by all the wheels shall not exceed 14 tons.

(2) For the purpose of this Regulation the weight transmitted to the road surface by a vehicle shall be taken to be the weight so transmitted by the vehicle when it is complete and fully equipped for service with a full supply of water, oil and fuel and loaded with weights of 140 lbs. per person placed

in the correct relative positions for each passenger for whom a seat is provided and for the driver and conductor (if carried) and, in the case of a public service vehicle registered after 31st December 1954 in which by or under any enactment more than eight standing passengers may be carried, with additional weights of 140 lbs. per person for each standing passenger in excess of eight reasonably distributed in the space in which any such passengers may be so carried.

68. In the case of a heavy motor car or motor car which is not a public service vehicle, the weight transmitted to the road surface by any one wheel where no other wheel is in the same line transversely shall not exceed 4½ tons, the total weight so transmitted by any two wheels in line transversely shall not exceed 9 tons and the sum of the weights so transmitted by all the wheels shall not exceed—

(*a*) in the case of a vehicle with not more than four wheels, 14 tons;

(*b*) in the case of a vehicle with more than four but not more than six wheels, 20 tons; and

(*c*) in the case of a vehicle with more than six wheels, 24 tons.

Laden weight of trailer

69.—(1) The total weight transmitted to the road surface by any two wheels of a trailer in line transversely shall not exceed 9 tons.

(2) The total laden weight of a trailer with less than six wheels and not forming part of an articulated vehicle shall not exceed 14 tons.

Laden weight of vehicle and trailer

70.—(1) The total laden weight of a trailer, whether wheeled or track laying, together with that of any motor tractor, heavy motor car or motor car drawing such trailer, in each case whether wheeled or track laying, shall not exceed 22 tons:

Provided that—

(*a*) in the case of a wheeled trailer drawn by a wheeled motor tractor, wheeled heavy motor car or wheeled motor car, the total laden weight of the trailer together with that of the drawing vehicle may equal, but shall not exceed, 24 tons; and

(*b*) where the trailer is fitted with power-assisted brakes which can be operated by the driver of the drawing vehicle and are not rendered ineffective by the non-rotation of the engine of the drawing vehicle, the total laden weight of the trailer together with that of the drawing vehicle, if the drawing vehicle is equipped with a warning device so placed as to be readily visible to the driver when in the driving seat in order to indicate an impending failure or deficiency in the vacuum or pressure system, may equal, but not exceed, 32 tons.

(2) This Regulation shall not apply to any trailer forming part of an articulated vehicle.

Laden weight of articulated vehicle

71. The total laden weight of an articulated vehicle shall not exceed—

(*a*) if the trailer forming part thereof has less than four wheels, 20 tons; and

(*b*) if the trailer forming part thereof has four wheels or more, 24 tons.

Distribution of weight

72. In the case of a heavy motor car, motor car or trailer whether laden or unladen the weight transmitted to any strip of the surface upon which the vehicle rests contained between any two parallel lines drawn 2 feet apart on that surface at right angles to the longitudinal axis of the vehicle shall not exceed 11 tons.

Maintenance and use of vehicle so as not to be a danger

73.—(1) A motor vehicle, every trailer drawn thereby and all parts and accessories of such vehicle and trailer shall at all times be in such condition, and the number of passengers carried by such vehicle or trailer, the manner in which any passengers are carried in or on such vehicle or trailer, and the weight, distribution, packing and adjustment of the load of such vehicle or trailer shall at all times be such that no danger is caused or is likely to be caused to any person in or on the vehicle or trailer or on a road:

Provided that in the case of a public service vehicle the provisions of this Regulation with regard to the number of passengers carried shall be deemed to be complied with if the number does not exceed that for the time being permitted by regulations made by the Minister of Transport with regard to the carrying capacity of public service vehicles.

(2) The load carried by a motor vehicle or trailer shall at all times be so secured or be in such a position that danger is not likely to be caused to any person by reason of the load or any part thereof falling from the vehicle or by reason of any other movement of the load or any part thereof in relation to the vehicle.

(3) No motor vehicle or trailer shall be used for any purpose for which it is so unsuitable as to cause or be likely to cause danger to any person in or on the vehicle or trailer or on a road.

Maintenance of speedometer

74. Every instrument for indicating speed fitted in compliance with the requirements of Regulation 13 of these Regulations shall—

(*a*) at all material times be maintained in good working order; and

(*b*) be kept free from any obstruction which might prevent its being easily read:

Provided that it shall be a good defence to proceedings taken in respect of a contravention of paragraph (*a*) of this Regulation to prove that—

(i) the defect occurred in the course of the journey during which the contravention was detected, or

(ii) at the time when the contravention was detected steps had already been taken to have the defect remedied with all reasonable expedition.

Maintenance of glass

75. All glass or other transparent material fitted to motor vehicles shall be maintained in such condition that it does not obscure the vision of the driver while the vehicle is being driven on a road.

Maintenance of brakes, steering gear and windscreen wiper

76.—(1) Every part of every braking system and of the means of operation thereof fitted to a motor vehicle or trailer shall at all times while the vehicle or trailer is used on a road—

(*a*) be maintained in good and efficient working order and be properly adjusted; and

(*b*) in the case of motor vehicles to which Schedule 4 to these Regulations applies, be so maintained that the brakes forming part of the system comply with the requirements as to the efficiency of brakes which are applicable to such a vehicle by virtue of the provisions contained in paragraph (3) of Regulation 42, paragraph (3) of Regulation 47 and paragraph (3) of Regulation 50 of these Regulations.

(2) All steering gear fitted to a motor vehicle shall at all times while the vehicle is used on a road be maintained in good and efficient working order and be properly adjusted.

(3) Every windscreen wiper required by these Regulations to be fitted to a motor vehicle shall at all times while the vehicle is used on a road be maintained in good and efficient working order and be properly adjusted.

Maintenance of lighting equipment and reflectors

77.—(1) Subject to the following provisions of this Regulation, every lamp and reflector and all other equipment with which a motor vehicle is required by paragraph (1) of Regulation 27 of these Regulations to be equipped shall at all times while the vehicle is used on a road be maintained in such a condition as to render the vehicle capable of being driven on a road during the hours of darkness without contravention of any of the statutory provisions relating to obligatory lamps or reflectors which are applicable to that vehicle.

(2) Subject to the following provisions of this Regulation, every head lamp carried by a vehicle which, by virtue of paragraph (2) of the said Regulation 27, is required to be constructed and fitted to that vehicle in accordance with the provisions of the said paragraph (2) shall at all times while the vehicle is used on a road be maintained in such a condition that if that lamp were to be used to show a light to the front while the vehicle was driven on a road during the hours of darkness such use would not be in contravention of the provisions of Regulation 9 of the Road Vehicles Lighting Regulations 1959.

(3) Where a person is charged with a contravention of any provision of this Regulation in respect of the use of a vehicle on a road otherwise than during the hours of darkness, it shall be a defence for that person to prove—

(*a*) that the contravention arose from a defect in the lighting equipment of, or in a reflector carried by, the vehicle which occurred in the course of the journey during which the contravention occurred; or

(*b*) that the contravention arose from a defect in the lighting equipment of, or in a reflector carried by, the vehicle and that before the contravention occurred steps had been taken to have the defect remedied with all reasonable expedition.

(4) In this Regulation, the expressions "statutory provisions relating to obligatory lamps or reflectors" and "head lamp" have the same meanings as in Regulation 27 of these Regulations.

Use and maintenance of silencer

78.—(1) No person shall use or cause or permit to be used on a road any vehicle propelled by an internal combustion engine so that the exhaust gases from the engine escape into the atmosphere without first passing through the silencer, expansion chamber or other contrivance required by these Regulations to be fitted.

(2) Every such silencer, expansion chamber or other contrivance shall at all times while the vehicle is used on a road be maintained in good and

efficient working order and shall not have been altered in such a way that the noise caused by the escape of the exhaust gases is made greater by the alteration.

Maintenance of tyres

79. All the tyres of a motor vehicle or trailer shall at all times while the vehicle or trailer is used on a road be maintained in such condition as to be free from any defect which might in any way cause damage to the surface of the road or danger to persons on or in the vehicle or to other persons using the road.

Use of vehicles so as not to emit smoke, etc.

80. No person shall use or cause or permit to be used on a road any motor vehicle from which any smoke, visible vapour, grit, sparks, ashes, cinders, or oily substance is emitted if the emission thereof causes or is likely to cause damage to any property or injury to any person who is actually at the time or who reasonably may be expected on the road, or is likely to cause danger to any such person as aforesaid.

81. Where a motor vehicle, being a vehicle propelled by a compression ignition engine, is fitted with a device designed to facilitate the starting of the engine by causing it to be supplied with excess fuel—

(*a*) the device shall be maintained in such a condition that it does not cause the engine to be supplied with excess fuel while the vehicle is in motion on a road ; and

(*b*) no person shall use the device, or cause or permit it to be used, so as to cause it to supply the engine with excess fuel while the vehicle is in motion on a road :

Provided that paragraph (*b*) of this Regulation shall not apply as respects a device such as is mentioned in sub-paragraph (ii) of the proviso to Regulation 23(2) of these Regulations.

Contents of lavatories, etc.

82. No person shall cause or permit the contents of any closet, urinal, lavatory basin or sink carried by a motor vehicle or trailer or of any tank into which such closet, urinal, lavatory basin or sink drains to be discharged or to leak on to a road.

Excessive noise

83. No person shall use or cause or permit to be used on a road any motor vehicle or trailer which causes any excessive noise either directly or indirectly as a result of—

(*a*) any defect (including a defect in design or construction), lack of repair or faulty adjustment in the motor vehicle or trailer or any part or accessory of such motor vehicle or trailer ; or

(*b*) the faulty packing or adjustment of the load of such motor vehicle or trailer :

Provided that it shall be a good defence to proceedings taken in respect of a contravention of this Regulation—

(i) to prove that the noise or continuance of the noise in respect of which the proceedings are taken was due to some temporary or accidental cause and could not have been prevented by the exercise of due diligence and care on the part of the owner or driver of the motor vehicle, or

(ii) in the case of proceedings against the driver or person in charge of the motor vehicle who is not the owner thereof, to prove that the noise arose through a defect in design or construction of the motor vehicle or trailer or through the negligence or fault of some other person whose duty it was to keep the motor vehicle or trailer in proper condition or in a proper state of repair or adjustment or properly to pack or adjust the load of such motor vehicle or trailer as the case may be and could not have been prevented by the exercise of reasonable diligence and care on the part of such driver or other person in charge of the motor vehicle.

84. No motor vehicle shall be used on a road in such manner as to cause any excessive noise which could have been avoided by the exercise of reasonable care on the part of the driver.

Stopping of engine when stationary

85. The driver of every motor vehicle shall, when the vehicle is stationary otherwise than through enforced stoppage owing to the necessities of traffic, stop the action of any machinery attached to or forming part of such vehicle so far as may be necessary for the prevention of noise:

Provided that this Regulation shall not apply—

(*a*) so as to prevent the examination or working of the machinery attached to or forming part of a motor vehicle where any such examination or working is rendered necessary by any failure or derangement of the said machinery or where the machinery attached to or forming part of the vehicle is required to be worked for some ancillary purpose; or

(*b*) in the case of a motor vehicle which is propelled by gas produced in plant carried on the vehicle or on a trailer drawn by the vehicle.

Use of audible warning instruments

86.—(1) Subject to the provisions of this Regulation, no person shall—

(*a*) in the case of a vehicle which is stationary on a road, at any time; or

(*b*) in the case of a vehicle which is in motion on a restricted road, between the hours of 11.30 in the evening and 7 in the following morning,

sound or cause or permit to be sounded any instrument or apparatus fitted to or otherwise carried on the vehicle, being an instrument or apparatus capable of giving audible and sufficient warning of its approach or position.

(2) Subject to the provisions of this Regulation and without prejudice to the provisions of the foregoing paragraph, no person shall sound or cause or permit to be sounded a gong, bell or siren fitted to or otherwise carried on a vehicle (whether it is stationary or not) or any instrument or apparatus so fitted or so carried, being an instrument or apparatus which is capable of emitting a sound similar to that emitted by a gong, bell or siren.

(3) Nothing in paragraph (1) or (2) of this Regulation shall have effect to prevent the sounding of an instrument or apparatus fitted to or otherwise carried on a vehicle at a time when the vehicle is being used for fire brigade, ambulance, salvage corps or police purposes or an instrument or apparatus fitted to or otherwise carried on a vehicle owned by the Forestry Commission at a time when the vehicle is being used for the purpose of fighting fires, if compliance with any of the said provisions would be likely to hinder the use of the vehicle for the purpose for which it is being used at that time.

(4) Nothing in paragraph (1) of this Regulation shall have effect to prevent the sounding by the driver of a vehicle or by some other authorised person of an instrument or apparatus fitted to or otherwise carried on the vehicle at a time when the instrument or apparatus is sounded for the purpose of raising an alarm as to the theft or attempted theft of the vehicle or its contents.

(5) Nothing in paragraph (2) of this Regulation shall have effect to prevent the sounding of an instrument or apparatus fitted to or otherwise carried on a vehicle, being an instrument or apparatus designed to emit a sound for the purpose of informing members of the public that the vehicle is conveying goods for sale, if—

(*a*) when the instrument is sounded, it is sounded only for that purpose; and

(*b*) in a case where a vehicle is on a restricted road, the instrument is sounded otherwise than between the hours of 11.30 in the evening and 7 in the following morning.

(6) In this Regulation "restricted road" means a length of road—

(*a*) on which there is provided a system of street lighting furnished by means of lamps placed not more than 200 yards apart, or

(*b*) as respects which there is in force a direction under section 20(3) of the 1960 Act that the said length shall become a restricted road for the purposes of section 19 of that Act or a direction under section 1(4) of the Road Traffic Act 1934(a) which, by virtue of paragraphs 1 and 12 of Schedule 19 to the 1960 Act, has effect under that Act as such a direction as aforesaid.

Duties relating to driving and stopping

87. No person while actually driving a motor vehicle on a road shall be in such a position that he cannot have proper control of that vehicle or that he cannot retain a full view of the road and traffic ahead and no person shall cause or permit any other person while actually driving a motor vehicle on a road to be in such a position as aforesaid.

88. No person shall cause or permit a motor vehicle to travel backwards for a greater distance or time than may be requisite for the safety or reasonable convenience of the occupants of that vehicle or of other traffic on the road:

Provided that this Regulation shall not apply in the case of a road roller or other road plant while actually engaged in the construction, maintenance or repair of roads.

89. The driver of every vehicle propelled by steam (other than a motor car) shall, unless two persons are carried on it for the purpose of driving or attending to the vehicle, stop the vehicle whenever it is necessary to attend to the furnace.

90. No person in charge of a motor vehicle or trailer shall cause or permit the motor vehicle or trailer to stand on a road so as to cause any unnecessary obstruction thereof.

91.—(1) Save as provided in paragraph (2) of this Regulation no person shall, except with the permission of a police officer in uniform, cause or permit any motor vehicle to stand on any road during the hours of darkness otherwise than with the left or near side of the vehicle as close as may be to the edge of the carriageway.

(a) 24 & 25 Geo. 5. c. 50.

(2) This Regulation shall not apply—

(*a*) to any motor vehicle when it is being used for fire brigade, ambulance or police purposes or for defence purposes (including civil defence purposes) if compliance with this Regulation would hinder or be likely to hinder the use of the vehicle for the purpose for which it is being used on that occasion;

(*b*) to any motor vehicle standing on a part of a road specially set aside for the parking of vehicles or as a stand for hackney carriages or as a stand for public service vehicles or as a place at which such vehicles may stop for a longer time than is necessary for the taking up and setting down of passengers where compliance with this Regulation would conflict with the provisions of any order, regulations or byelaws governing the use of such part of a road for that purpose;

(*c*) to any motor vehicle waiting to set down or pick up passengers in accordance with regulations made or directions given by a chief officer of police in regard to such setting down or picking up;

(*d*) to any motor vehicle on any road in which vehicles are allowed to proceed in one direction only; or

(*e*) to any motor vehicle whilst it is being used in connection with—

(i) any building operation or demolition,

(ii) the repair of any other vehicle,

(iii) the removal of any obstruction to traffic,

(iv) the maintenance, repair or reconstruction of any road, or

(v) the laying, erection, alteration or repair in or near to any road of any sewer, of any main, pipe or apparatus for the supply of gas, water or electricity, of any telegraph or telephone wires, cables, posts or supports or of the apparatus of any electric transport undertaking if, in any such case, compliance with this Regulation would hinder or be likely to hinder the use of the vehicle for the purpose for which it is being used on that occasion.

92. No person shall cause or permit to be on a road any motor vehicle which is not attended by a person duly licensed to drive it unless the engine is stopped and, where the vehicle is fitted with a brake capable of being set, the brake is set so as effectually to prevent two at least or in the case of a vehicle with only three wheels one of the wheels, from revolving:

Provided that the requirements of this Regulation as to the stopping of the engine shall not apply in the case of—

(*a*) a fire brigade vehicle the engine of which is being used for any fire fighting purpose; or

(*b*) a vehicle which is propelled by gas produced in plant carried on the vehicle or on a trailer drawn by the vehicle.

Opening of doors

93. No person shall open or cause or permit to be opened any door of a motor vehicle or trailer on a road so as to cause injury or danger to any person.

Application of brakes of trailers

94. Where a trailer is drawn by a motor vehicle whether wheeled or track laying the driver (or in the case of a locomotive one of the persons employed in driving or tending the locomotive) shall be in a position readily to operate any brakes required by these Regulations to be fitted to the trailer as well as the brakes of the motor vehicle unless a person other than the driver is in a position and competent efficiently to apply the brakes of the trailer:

Provided that this Regulation shall not apply in the case of trailers which, in compliance with these Regulations, are fitted with brakes which automatically come into operation on the overrun of the trailer or where a motor vehicle is drawing a broken down vehicle, whether or not in consequence of a breakdown, in such a manner that the broken down vehicle cannot be steered by its own steering gear.

95. No person in charge of a motor vehicle, whether wheeled or track laying, or trailer drawn thereby shall cause or permit such trailer to stand when detached from the drawing vehicle unless one at least of the wheels of the trailer is prevented from revolving by the setting of the brake or the use of a chain.

Restriction on distance between motor vehicles and trailers and marking of trailer connections

96.—(1) Where a motor vehicle is drawing a trailer solely by means of a rope or chain or, in a case where more than one trailer is being drawn, where a trailer is attached to another trailer solely by such means, the length of the rope or chain shall be such that the distance between the nearest points of the trailer and the vehicle to which it is so attached cannot exceed 15 feet.

(2) Where a motor vehicle is drawing a trailer or trailers and the distance between the nearest points of the trailer or, as the case may be, of any trailer so drawn and the vehicle to which it is attached exceeds 5 feet, steps shall be taken to render the means whereby that trailer is attached to that vehicle clearly visible to other persons using the road within a reasonable distance from either side of either vehicle.

(3) For the purposes of this Regulation, in determining the nearest points of two vehicles any part of either vehicle designed primarily for use as a means of attaching the one vehicle to the other and of any fitting designed for use in connection with any such part shall be disregarded.

Restrictions on the use of vehicles to draw trailers and of trailers drawn

97. Every sidecar fitted to a motor cycle shall be so attached that the wheel thereof is not wholly outside perpendicular planes at right angles to the longitudinal axis of the motor cycle passing through the extreme projecting points in the front and in the rear of the motor cycle.

98. A motor cycle with not more than two wheels and without a sidecar shall not draw a trailer:

Provided that this Regulation shall not apply to prevent the towing of a broken down motor cycle which is being drawn by another motor cycle in consequence of the breakdown.

99. No motor cycle shall draw a trailer exceeding 5 hundredweight in weight unladen or 5 feet in overall width.

100. No straddle carrier or invalid carriage shall draw a trailer.

101. No trailer shall be used for the conveyance of passengers for hire or reward.

102. No trailer shall be drawn by a public service vehicle:

Provided that this Regulation shall not apply to the drawing of one empty public service vehicle by another empty public service vehicle in case of emergency or to the drawing of a gas trailer by a public service vehicle.

103.—(1) No motor vehicle shall draw a trailer or trailers where the overall length of the combination of vehicles exceeds 85 feet unless the conditions specified in paragraphs 1 and 2 of Schedule 6 to these Regulations have been complied with.

(2) For the purposes of this Regulation the reference to the combination of vehicles shall be construed in the same manner as provided in sub-paragraph (*g*) of Regulation 105(1) of these Regulations for the purposes of Regulation 106 thereof and the overall length of such a combination shall be measured in the manner provided in sub-paragraph (*h*) of the said Regulation 105(1).

Passengers on motor bicycles

104. If any person in addition to the driver is carried astride any two-wheeled motor cycle (whether a sidecar is attached thereto or not) suitable supports or rests for the feet shall be available on such cycle for that person.

Restrictions on use of vehicles carrying wide or long loads or having fixed appliances or apparatus

105.—(1) For the purposes of this and the following Regulation and of Schedule 6 to these Regulations—

(*a*) the expression "lateral projection", in relation to a load carried by a vehicle, means that part of the load which extends beyond a side of the vehicle;

(*b*) the width of any lateral projection shall be measured between vertical planes parallel to the longitudinal axis of the vehicle and passing through the extreme projecting point of the vehicle on that side on which the projection lies and that part of the projection furthest from that point;

(*c*) references to a special appliance or apparatus, in relation to a vehicle, are references to any crane or other special appliance or apparatus fitted to the vehicle which is a permanent or essentially permanent fixture;

(*d*) the expressions "forward projection" and "rearward projection"—

(i) in relation to a load carried in such a manner that its weight rests on only one vehicle, mean respectively that part of the load which extends beyond the foremost point of the vehicle and that part which extends beyond the rearmost point of the vehicle,

(ii) in relation to a load carried in such a manner that part of its weight rests on more than one vehicle, mean respectively that part of the load which extends beyond the foremost point of the foremost vehicle by which the load is carried and that part of the load which extends beyond the rearmost point of the rearmost vehicle by which the load is carried, and

(iii) in relation to any special appliance or apparatus, mean respectively that part of the appliance or apparatus which, if it were deemed to be a load carried by the vehicle, would be a part of

a load extending beyond the foremost point of the vehicle and that part which would be a part of a load extending beyond the rearmost point of the vehicle,

and references in the following Regulation and in Schedule 6 to these Regulations to a forward projection or to a rearward projection in relation to a vehicle shall be construed accordingly;

(*e*) the length of any forward projection or of any rearward projection shall be measured between vertical planes at right angles to the longitudinal axis of the vehicle and passing—

(i) in the case of a forward projection, through the foremost point of the vehicle and that part of the projection furthest from that point, and

(ii) in the case of a rearward projection, through the rearmost point of the vehicle and that part of the projection furthest from that point.

In this and the foregoing sub-paragraph the expression "vehicle" shall not include any special appliance or apparatus or any part thereof which is a forward projection or a rearward projection within the meaning of this Regulation;

(*f*) references to the distance between vehicles, in relation to vehicles carrying a load, are references to the distance between the nearest points of any two adjacent vehicles by which the load is carried, measured when the longitudinal axis of each vehicle lies in the same vertical plane.

For the purposes of this sub-paragraph, in determining the nearest point of two vehicles any part of either vehicle designed primarily for use as a means of attaching the one vehicle to the other and of any fitting designed for use in connection with any such part shall be disregarded;

(*g*) references to a combination of vehicles, in relation to a motor vehicle which is drawing one or more trailers, are references to the motor vehicle and the trailer or trailers drawn thereby, including any other motor vehicle which is used for the purpose of assisting in the propulsion of the trailer or the trailers on the road;

(*h*) the overall length of a combination of vehicles shall be taken as the distance between the foremost point of the drawing vehicle comprised in the combination and the rearmost point of the rearmost vehicle comprised therein, measured when the longitudinal axis of each vehicle comprised in the combination lies in the same vertical plane;

(*i*) the extreme projecting point of a vehicle shall be taken as excluding any part of, or part of the equipment of, a vehicle which, by virtue of sub-paragraphs (*a*) to (*f*) of the definition of the overall width of a vehicle contained in Regulation 3(1) of these Regulations, falls to be excluded in determining that overall width; and

(*j*) the foremost or, as the case may be, the rearmost points of a vehicle shall be taken as excluding any part of, or part of the equipment of, a vehicle which, by virtue of sub-paragraphs (*a*) to (*h*) of the definition of the overall length of a vehicle contained in Regulation 3(1) of these Regulations, falls to be excluded in determining that overall length.

(2) For the purposes of paragraphs (3) and (4)(*a*) of the following Regulation, a load carried by an articulated vehicle shall, notwithstanding that part of its weight is borne by the drawing vehicle, not be treated as carried in such a manner that part of its weight rests on more than one vehicle.

106.—(1) No load shall be carried on a vehicle where the overall width of the vehicle together with the width of any lateral projection or projections of its load exceeds 14 feet.

(2) Subject to the following provisions of this Regulation, no load shall be carried on a vehicle—

(*a*) where the load has a lateral projection exceeding 1 foot in width; or

(*b*) where the overall width of the vehicle together with the width of any lateral projection or projections of its load exceeds 9 feet 6 inches:

Provided that this paragraph shall not apply—

(i) to the carriage of an indivisible load if—

(*a*) it is not reasonably practicable to comply with the requirements of the said paragraph, and

(*b*) the conditions specified in paragraph 1 of Schedule 6 to these Regulations have been complied with, or

(ii) to the carriage of loose agricultural produce not baled or crated.

(3) No load shall be carried on a vehicle or in such a manner that part of its weight rests on more than one vehicle where the overall length of the vehicle together with the length of any forward projection and of any rearward projection of the load or, as the case may be, of the vehicles together with the distance between vehicles and the length of any forward projection and of any rearward projection of the load exceeds 90 feet.

(4) Subject to the following provisions of this Regulation—

(*a*) no load shall be carried on a vehicle or in such a manner that part of its weight rests on more than one vehicle where the overall length of the vehicle together with the length of any forward projection and of any rearward projection of the load or, as the case may be, of the vehicles, together with the distance between vehicles and the length of any forward projection and of any rearward projection of the load exceeds 60 feet; and

(*b*) without prejudice to the foregoing sub-paragraph, no load shall be carried on a trailer drawn by a motor vehicle or in such a manner that part of its weight rests on more than one trailer so drawn where the overall length of the combination of vehicles together with the length of any forward projection of the load extending beyond the foremost point of the drawing vehicle comprised in the combination and the length of any rearward projection of the load extending beyond the rearmost point of the rearmost vehicle comprised therein exceeds 85 feet

unless the conditions specified in paragraphs 1 and 2 of Schedule 6 to these Regulations have been complied with.

(5) Subject to the following provisions of this Regulation, no vehicle having a special appliance or apparatus which—

(*a*) has a forward projection exceeding 6 feet in length but not exceeding 10 feet in length, shall be used on a road unless the conditions specified in paragraphs 2 and 3 of Schedule 6 to these Regulations have been complied with;

(*b*) has a rearward projection exceeding 3 feet 6 inches in length but not exceeding 10 feet in length, shall be used on a road unless the condition specified in paragraph 4 of the said Schedule has been complied with; or

(*c*) has a forward or a rearward projection exceeding 10 feet in length, shall be used on a road unless the conditions specified in paragraphs 1, 2 and 3 of the said Schedule have been complied with.

(6) Subject to the following provisions of this Regulation, no load shall be carried on a vehicle—

(*a*) where the load has a forward projection exceeding 6 feet in length but not exceeding 10 feet in length, unless the conditions specified in paragraphs 2 and 3 of Schedule 6 to these Regulations have been complied with;

(*b*) where the load has a rearward projection exceeding 3 feet 6 inches in length but not exceeding 10 feet in length, unless the condition specified in paragraph 4 of the said Schedule has been complied with; and

(*c*) where the load has a forward or a rearward projection exceeding 10 feet in length, unless the conditions specified in paragraphs 1, 2 and 3 of the said Schedule have been complied with:

Provided that this paragraph shall not apply—

(i) to the carriage of a load which consists, whether wholly or partly, of a boat used for racing and propelled solely by oars if any provision of this paragraph would otherwise apply by reason only of the boat being so carried that it has a forward projection or, as the case may be, a rearward projection, or

(ii) to the carriage of a load by a straddle carrier.

(7) Subject to the following provisions of this Regulation, where the load or part of the load carried by a vehicle consists, whether wholly or partly, of a boat used for racing and propelled solely by oars, the boat shall not be so carried that it has a forward projection or a rearward projection—

(*a*) exceeding 3 feet 6 inches in length unless the condition specified in paragraph 4 of Schedule 6 to these Regulations has been complied with; or

(*b*) exceeding 10 feet in length unless the conditions specified in paragraphs 1 and 4 of the said Schedule have been complied with.

(8) Subject to the following provisions of this Regulation, no load shall be carried on a straddle carrier where the load has a rearward projection exceeding 3 feet 6 inches in length unless the condition specified in paragraph 4 of Schedule 6 to these Regulations has been complied with:

Provided that this paragraph shall not apply in the case of a vehicle used in passing from one part of any private premises to any other part thereof or to other private premises in the immediate neighbourhood.

(9) Subject to the following provisions of this Regulation, no load shall be carried on a straddle carrier—

(*a*) where the load has a forward projection exceeding 6 feet in length;

(*b*) where the load has a rearward projection exceeding 10 feet in length;

(*c*) where the overall length of the vehicle together with the length of any forward projection and of any rearward projection of its load exceeds 40 feet:

Provided that this paragraph shall not apply in the case of a vehicle used in passing from one part of any private premises to any other part thereof or to other private premises in the immediate neighbourhood if—

(i) the vehicle is not driven at a speed exceeding 12 miles per hour, and

(ii) where the overall length of the vehicle together with the length of any forward projection and of any rearward projection of its load exceeds 40 feet, the conditions specified in paragraphs 1 and 2 of Schedule 6 to these Regulations have been complied with.

(10) In a case where a vehicle has a special appliance or apparatus or is carrying a load or a boat used for racing as mentioned in paragraph (7) of this Regulation and the appliance or apparatus, the load or the said boat has, in relation to the vehicle, a forward projection or a rearward projection, and another vehicle is attached to that end of the vehicle from which the appliance or apparatus or, as the case may be, the load or the said boat projects and is attached to that vehicle in such manner that—

(*a*) in the case where there is a forward projection, the foremost point of that other vehicle extends beyond the foremost part of the projection or, in the case where there is a rearward projection, the rearmost point of that other vehicle extends beyond the rearmost part of the projection; or

(*b*) in the case where there is a forward projection, the foremost part of the projection extends beyond the foremost point of that other vehicle or, in the case where there is a rearward projection, the rearmost part of the projection extends beyond the rearmost point of that other vehicle, then—

(i) in either of the cases mentioned in sub-paragraph (*a*) of this paragraph, the provisions of paragraphs (5), (6) and (7) of this Regulation, in so far as they provide for compliance with paragraph 3 or 4 of Schedule 6 to these Regulations, shall not apply as respects any such projection, and

(ii) in either of the cases mentioned in sub-paragraph (*b*) of this paragraph, the provisions of the said paragraphs (5), (6) and (7), in so far as they provide for compliance with the said paragraph 3 or 4, shall apply as if each of the references in the said paragraphs (5), (6) and (7) to a forward projection and to a rearward projection were treated respectively as a reference to so much of a forward projection as extends beyond the foremost point of that other vehicle and to so much of a rearward projection as extends beyond the rearmost point of that other vehicle measured, in either case, when the longitudinal axis of each vehicle lies in the same vertical plane between vertical planes at right angles to the said longitudinal axis and passing, in the case of a forward projection, through the foremost point of the said other vehicle and that part of the projection furthest from that point or, in the case of a rearward projection, through the rearmost point of the said other vehicle and that part of the projection furthest from that point.

(11) This Regulation shall not apply to any motor vehicle or trailer being used—

(*a*) for fire brigade, ambulance or police purposes or for defence purposes (including civil defence purposes); or

(*b*) in connection with the removal of any obstruction to traffic

if, in any such case, compliance with any provision of this Regulation would hinder or be likely to hinder the use of the vehicle for the purpose for which it is being used on that occasion.

Mascots

107. No mascot shall be carried by a motor vehicle registered on or after 1st October 1937 in any position where it is likely to strike any person with whom the vehicle may collide unless the mascot is not liable to cause injury to such person by reason of any projection thereon.

Television sets

108.—(1) No person shall use or install for use in a motor vehicle a television receiving apparatus if the screen thereof is partly or wholly, and whether directly or in any reflection, visible to the driver whilst in the driving seat or if the controls thereof, other than the sound volume control and the main switch, are within reach of the driver whilst in the driving seat.

(2) No person shall use a television receiving apparatus in a motor vehicle under circumstances and in a position such that it might cause distraction to the driver of any other vehicle on the road.

Implements suspended from lifting appliances

109. Where a vehicle is fitted with any apparatus or appliance designed for lifting and part of the apparatus or appliance consists of an implement to facilitate lifting which is suspended from the apparatus or appliance, the implement shall at all times while the vehicle is in motion on a road and when the implement is not attached to any load supported by the appliance or apparatus be so secured either to the appliance or apparatus or to some part of the vehicle that no danger is caused or is likely to be caused to any person on the vehicle or on the road.

Attendants on trailers

110.—(1) The requirements of section 72 of the 1960 Act with regard to the employment of drivers and attendants shall not apply in the following cases, that is to say,—

(*a*) in the case of any articulated vehicle;

(*b*) where a land implement or land implement conveyor is drawn by a land locomotive or land tractor or where an agricultural trailer is drawn by a land tractor;

(*c*) where a trailer with not more than two wheels is drawn by a motor car or a motor cycle or where a four-wheeled trailer having two close-coupled wheels on each side is drawn by a motor car;

(*d*) where a motor tractor is drawing—

(i) any closed trailer specially constructed and used for the conveyance of meat between docks and railway stations or between wholesale markets and docks or railway stations,

(ii) any machine or implement used for the purpose of the maintenance, repair or cleansing of roads, or

(iii) any trailer designed for use and used solely in connection with street cleansing, the collection or disposal of refuse or the collection or disposal of the contents of gullies or cesspools;

(*e*) where a works truck is drawing any works trailer and the weight unladen of each vehicle does not exceed 30 hundredweight;

(*f*) where a gas trailer is drawn by a heavy motor car or a motor car;

(*g*) where a motor vehicle is drawing a trailer—

(i) not exceeding 1 ton in weight unladen;

(ii) not constructed to carry and not used for carrying a load other than plant or other special appliance or apparatus which is a permanent or essentially permanent fixture and not exceeding 45 hundredweight in total weight; or

(iii) which is a living van not exceeding 2 tons in weight unladen, every wheel of which is fitted with a pneumatic tyre;

if in any such case the brakes of the trailer automatically come into operation on the overrun of the trailer;

(*h*) in the case of any road roller;

(*j*) where a motor vehicle belonging to the Admiralty, the War Department or the Air Ministry and being used for naval, military or air force purposes is drawing a trailer fitted with brakes which can be applied by the driver of the drawing vehicle;

(*k*) where a motor vehicle is drawing a broken down vehicle, whether or not in consequence of a breakdown, in such a manner that the broken down vehicle cannot be steered by its own steering gear;

(*l*) where a vehicle is being drawn by a motor vehicle in the exercise of a statutory power of removal in such manner that the vehicle being so drawn cannot be steered by its own steering gear; or

(*m*) where a towing implement is being drawn by a motor vehicle while it is not attached to any vehicle except the one drawing it.

(2) The provisions of this Regulation shall not be treated as prejudicing the operation of any provision of Regulation 106 of these Regulations in so far as it provides, in relation to the use of a vehicle on a road, for compliance with the conditions specified in paragraph 2 of Schedule 6 to these Regulations (which relates to the employment of persons in attending to vehicles and their load).

PART IV

TESTING AND INSPECTION OF BRAKES, SILENCERS, STEERING GEAR, TYRES, LIGHTING EQUIPMENT AND REFLECTORS

Testing of brakes, etc.

111.—(1) Any police constable in uniform and any person for the time being appointed by the Minister of Transport as a certifying officer or public service vehicle examiner under Part III of the 1960 Act or under any enactment repealed by that Act or as an examiner appointed under Part IV of that Act or under any enactment so repealed or appointed by the commissioner of police of the metropolis to examine and inspect public carriages for the purposes of the Metropolitan Public Carriage Act 1869(a), who shall produce his authority if required, is hereby empowered to test and inspect the brakes, silencers, steering gear, tyres, lighting equipment and reflectors of any motor vehicle or trailer on any premises where that motor vehicle or trailer is, subject however to the consent of the owner of the premises.

(2) The power conferred by this Regulation to test and inspect the brakes, silencers, steering gear, tyres, lighting equipment and reflectors of a vehicle on any premises where the vehicle is shall not be exercised unless either the owner of the vehicle consents or notice of the date and time at which it is proposed to carry out the test and inspection has been given to him in accordance with the provisions of the following paragraph.

(a) 32 & 33 Vict. c. 115.

(3) The said notice shall be given to the owner of the vehicle personally or left at his address not less than 48 hours before the time of the proposed test and inspection or shall be sent to him not less than 72 hours before that time by recorded delivery service at his address.

(4) The provisions of paragraph (2) of this Regulation shall not apply in the case of a test and inspection made within 48 hours of an accident to which section 77 of the 1960 Act applies and in which the vehicle has been involved.

(5) For the purposes of this Regulation, the owner of the vehicle shall be deemed to be—

(*a*) in the case of a vehicle which is for the time being registered under the Vehicles (Excise) Act 1962 and is not being used under a trade licence under that Act the person appearing as the owner of the vehicle in the register kept by the appropriate council under that Act;

(*b*) in the case of a vehicle used under a trade licence, the holder of the licence; and

(*c*) in the case of a vehicle which is used under an international circulation permit, the person to whom the permit was issued;

and in cases (*a*) and (*b*) the address of the owner as shown on the register of the council by whom the vehicle is registered or, as the case may be, on the licence may be treated as his address.

Given under the Official Seal of the Minister of Transport the 26th September 1963.

(L.S.)

Ernest Marples,
The Minister of Transport.

SCHEDULE 1 (see Regulation 2)

REVOCATION

Column 1 (*Regulations revoked*)	*Column 2* (*S.I. numbers and volume references*)
The Motor Vehicles (Construction and Use) Regulations 1955;	S.I. 1955/482 (1955 II, p. 2242).
The Motor Vehicles (Construction and Use) (Amendment) Regulations 1956;	S.I. 1956/540 (1956 II, p. 2004).
The Motor Vehicles (Construction and Use) (Amendment) Regulations 1957;	S.I. 1957/359 (1957 II, p. 1976).
The Motor Vehicles (Construction and Use) (Amendment) (No. 2) Regulations 1957;	S.I. 1957/971 (1957 II, p. 1985).
The Motor Vehicles (Construction and Use) (Amendment) Regulations 1959;	S.I. 1959/1936 (1959 II, p. 2352).
The Motor Vehicles (Construction and Use) (Amendment) (No. 2) Regulations 1959;	S.I. 1959/2231 (1959 II, p. 2361).
The Motor Vehicles (Construction and Use) (Amendment) Regulations 1960;	S.I. 1960/1065 (1960 III, p. 2960).
The Motor Vehicles (Construction and Use) (Amendment) Regulations 1961;	S.I. 1961/1313 (1961 II, p. 2542).
The Motor Vehicles (Construction and Use) (Amendment) (No. 2) Regulations 1961;	S.I. 1961/1587 (1961 II, p. 3247).
The Motor Vehicles (Construction and Use) (Amendment) (No. 3) Regulations 1961;	S.I. 1961/1643 (1961 II, p. 3322).
The Motor Vehicles (Construction and Use) (Amendment) (No. 4) Regulations 1961;	S.I. 1961/2084 (1961 III, p. 3831).
The Motor Vehicles (Construction and Use) (Amendment) Regulations 1962;	S.I. 1962/1584 (1962 II, p. 1788).
The Motor Vehicles (Construction and Use) (Amendment) (No. 2) Regulations 1962.	S.I. 1962/2570 (1962 III, p. 3458).

SCHEDULE 2 (see Regulation 28)

DIRECTION INDICATORS

Alternative provisions in Part I or II as respects direction indicators on motor vehicles registered before 1st September 1965 fitted with electric lighting equipment

PART I

1. Every direction indicator fitted to a vehicle in compliance with this Part of this Schedule shall be, when in operation, in the form of an illuminated sign of a minimum illuminated length of 6 inches and a maximum illuminated breadth not exceeding one-fourth of the illuminated length, and shall show either a steady or a flashing light.

2. Save as provided in the next following paragraph as respects additional indicators, every direction indicator shall be so designed and fitted that—

(*a*) it is not more than 6 feet behind the base of the wind-screen; and

(*b*) when in operation—

(i) it temporarily alters the outline of the vehicle to the extent of at least 6 inches measured horizontally;

(ii) the outermost point of the direction indicator is at least 6 inches further from the longitudinal axis of the vehicle than is the outermost point of the driver's cab, or of the side of the body immediately behind the driver's seat;

(iii) the illuminated surface is visible at a reasonable distance both from the front and the rear of the vehicle; and

(iv) it remains steady:

Provided that sub-paragraph (*a*) of this paragraph shall not apply in the case of a pillarless saloon motor car if the direction indicator is not situated behind the widest part of the body. For the purposes of this proviso a pillarless saloon motor car means a motor car which has an enclosed body and four doors and no vertical pillar between the doors on either side and is a passenger vehicle adapted to carry not more than seven passengers exclusive of the driver.

3.—(1) An additional indicator may be fitted at the rear of any vehicle on any side to which there is fitted an indicator not being an additional indicator. Such additional indicator shall either—

(*a*) be in the form specified in paragraph 1 of this Part of this Schedule and shall, except when a trailer is being drawn, be visible at a reasonable distance from any point to the rear of the vehicle: or

(*b*) comply with the requirements of sub-paragraph (1) of paragraph 3 and of paragraph 5 of Part II of this Schedule as respects indicators showing a flashing light to the rear.

(2) An additional indicator may be fitted at the front of any vehicle on any side to which there is fitted an indicator not being an additional indicator. Such additional indicator shall comply with the requirements of sub-paragraph (1) of paragraph 3 and of paragraphs 4 and 5 of Part II of this Schedule as respects indicators showing a flashing light to the front.

4. Any direction indicator intended to indicate a right hand turn shall be fitted only to the right of the longitudinal axis of the vehicle and one intended to indicate a left hand turn shall be fitted only to the left of that axis:

Provided that this paragraph shall not apply to any direction indicator being an additional indicator fitted to a vehicle before the 1st April 1955.

5. Every direction indicator shall be at a height of not more than 7 feet 6 inches nor less than 1 foot 5 inches above the level of the ground.

6.—(1) The illuminated colour of every direction indicator shall—

(*a*) if it shows both to the front and to the rear, be amber;

(*b*) if it shows only to the front, be amber or white; and

(*c*) if it shows only to the rear, be amber or red.

(2) The light emitted by every direction indicator shall be diffused by frosted glass or other adequate means.

7. Every direction indicator showing a flashing light shall when in operation show a light which flashes constantly at the rate of not less than 60 nor more than 120 flashes per minute, each flash being of such duration as to permit the light to achieve its full brightness and to be fully observable to the eye at a reasonable distance. The light shall begin to flash not later than one second after the switch of the indicator is operated and between each flash there shall be an interval observable to the eye.

8. The following requirements shall be complied with as respects the direction indicators on a vehicle—

(*a*) not less than one indicator on each side to which indicators are fitted shall be so designed and fitted that the driver when in his seat can readily be aware when it is in operation; or

(*b*) the vehicle shall be equipped with a device or devices so designed and fitted that, when the switch actuating the indicator or indicators on one side of the vehicle is operated, the device or devices shall—

(i) if and so long as every indicator not being an additional indicator fitted on that side of the vehicle is in operation, together with the indicator on that side, if a trailer is drawn, of the trailer (or if more than one trailer is drawn, the rearmost trailer), give a warning readily visible or audible to the driver when in his seat; and

(ii) in any other case give no warning or a warning different from that given if the conditions of head (i) of this sub-paragraph are satisfied.

9. Every direction indicator shall be so fitted that when not in operation it will not be likely to mislead the driver of any other vehicle or any person controlling traffic.

10. Any reference in this Schedule to the side of a vehicle shall be taken to include that part of the front or the back of the vehicle which is on that side of the vehicle.

11. Every direction indicator fitted to either side of a vehicle together with every indicator on that side of any trailer drawn by the vehicle, while so drawn, shall be operated by one and the same switch and not otherwise.

In this Schedule the term "switch" includes any control or device by which a direction indicator can be operated or its operation cancelled.

PART II

1. Subject to the provisions of paragraph 3 of this Part of this Schedule, every direction indicator fitted to a vehicle in compliance with this Part of this Schedule shall be in the form of a lamp which, when in operation, shows a flashing light visible at a reasonable distance from both the front and rear of the vehicle.

2. Every such indicator shall be so designed and fitted that—

(*a*) it is not more than 6 feet behind the base of the wind-screen;

(*b*) both the minimum illuminated area showing to the front and the minimum illuminated area showing to the rear shall—

(i) be not less than 3½ square inches in extent in the case of either a vehicle the unladen weight of which does not exceed two tons or a passenger vehicle adapted to carry not more than twelve passengers, exclusive of the driver, if in either case the vehicle is not being used, except in a case of emergency, to draw a trailer other than one with less than four wheels or a four-wheeled trailer having two close-coupled wheels on each side;

(ii) be not less than 12 square inches in extent in any other case.

3.—(1) Subject to the provisions of sub-paragraph (2) of this paragraph, in lieu of a direction indicator in respect of which the provisions of paragraphs 1 and 2 of this Part of this Schedule are complied with, two indicators may be fitted to any side of a vehicle and shall be so designed and fitted that—

(*a*) when in operation one of the indicators on one side shall show a flashing light visible from a reasonable distance to the front of the vehicle and the other indicator on that side shall, except when a trailer is being drawn, show a flashing light visible from a reasonable distance to the rear of the vehicle;

(*b*) every such indicator shall be so placed that the centre of its illuminated area is not more than 16 inches nearer to the longitudinal axis of the vehicle than is the outermost part of the vehicle which is comprised in the overall width of the vehicle on the side on which the indicator is placed, except that in the case of a public service vehicle having combined rear and side entrances the near side indicator showing a flashing light to the rear of the vehicle may be so placed that the centre of its illuminated area is not more than 30 inches nearer to the longitudinal axis of the vehicle than the said outermost part of the vehicle; and

(*c*) the minimum illuminated area showing to the front or rear as the case may be shall be that prescribed in paragraph 2 of this Part of this Schedule.

(2) Whilst a vehicle is drawing a trailer or trailers the preceding provisions of this paragraph shall have effect subject to the following modifications:—

(*a*) there shall be carried on either side of the trailer or the rearmost trailer as the case may be an indicator so designed and fitted that when in operation it complies with the provisions of Part III or Part VI of this Schedule; and

(*b*) it shall not be necessary for an indicator showing a flashing light to the rear to be carried on either side of the vehicle.

This sub-paragraph shall not apply where the trailer or the rearmost trailer as the case may be is of an unladen weight not exceeding two hundredweight or was constructed before 1st January 1955, or is a broken down motor vehicle being drawn in consequence of the breakdown.

4.—(1) Save as provided in sub-paragraph (2) of this paragraph a direction indicator fitted in compliance with this Part of this Schedule and showing a flashing light to the front shall not be combined with nor obscure any lamp showing to the front a white light being a lamp required to be carried by or under any enactment.

(2) In the case of a vehicle on either side of which two direction indicators are fitted in accordance with the preceding paragraph an indicator showing a flashing light to the front may be combined with an electric lamp showing a white light to the front being a lamp required to be carried by or under any enactment provided that—

(*a*) the power of the lamp does not exceed 7 watts; and

(*b*) the indicator is fitted with a separate electric circuit and either a separate electric bulb or a separate electric filament.

5. The total rated wattage of the bulb or bulbs illuminating any indicator carried in compliance with this Part of this Schedule shall be not less than 15 watts nor more than 36 watts.

6.—(1) Where a vehicle is equipped on any side with a direction indicator in respect of which the provisions of paragraphs 1 and 2 of this Part of this Schedule are complied with, an additional indicator may be carried on that side provided that any such indicator complies with the provisions of paragraph 3 of Part I of this Schedule.

(2) Where a vehicle is equipped on any side with direction indicators in respect of which the provisions of paragraph 3 of this Part of this Schedule are complied with, an additional indicator may be carried on that side (excluding the front or rear of the vehicle). Any such indicator shall be in the form of a lamp which, when in operation, shows a flashing light visible at a reasonable distance to road users alongside the vehicle.

7. Every direction indicator shall be at a height of not more than 7 feet 6 inches nor less than 1 foot 5 inches above the level of the ground:

Provided that a direction indicator fitted to any side of a public service vehicle in accordance with the provisions of paragraphs 1 and 2 of this Part of this Schedule may be fitted at a height of not more than 8 feet 6 inches above the level of the ground if on the same side of the vehicle and at a height of not more than 6 feet 6 inches above the level of the ground there is also fitted an additional direction indicator which complies with the provisions of paragraph 3 of Part I of this Schedule.

8. The provisions of paragraphs 4, 6, 7, 8, 9, 10 and 11 of Part I of this Schedule shall apply as respects direction indicators fitted in compliance with this Part of this Schedule as they apply as respects direction indicators fitted in compliance with that Part.

Provisions as respects direction indicators on motor vehicles registered on or after the 1st September 1965 (which may be complied with by vehicles registered before that date) and on trailers drawn thereby

PART III

1.—(1) In this Part of this Schedule and in the diagrams set out in Part IV of this Schedule the following expressions have the meanings hereby respectively assigned to them:—

"inboard angle", in relation to a direction indicator, means an angle, within which light from the indicator is visible, measured horizontally inwards from a line parallel to the longitudinal axis of the vehicle and passing through the centre of the illuminated area of the indicator;

"outboard angle", in relation to a direction indicator, means an angle, within which light from the indicator is visible, measured horizontally outwards from a line parallel to the longitudinal axis of the vehicle and passing through the centre of the illuminated area of the indicator;

"blind angle", in relation to a direction indicator, means an angle, throughout which no light from the indicator need be visible, measured horizontally outwards from a line parallel to the longitudinal axis of the vehicle and passing through the centre of the illuminated area of the indicator.

(2) In this Part of this Schedule the expressions "front indicator", "shoulder indicator", "side indicator", "flank indicator" and "rear indicator" mean respectively a direction indicator to which diagram 1, 2, 3, 4 or 5 set out in Part IV of this Schedule applies and which being of a kind mentioned in column 1 of the following Table is when fitted to a vehicle in compliance with the provisions of this Part of this Schedule capable of being seen by an observer on the road standing in the position or, in turn, in each position in relation to that vehicle indicated in column 2 of that Table:—

TABLE

1. *Kind of direction indicator*	2. *Observer's position in relation to the vehicle*
Front	In front
Shoulder	In front and alongside
Side	In front, alongside and in rear
Flank	Alongside
Rear	In rear

2. Every direction indicator fitted to a vehicle in compliance with this Part of this Schedule shall be in the form of a lamp which, when in operation, shows a flashing amber light.

3.—(1) On each side of a motor vehicle there shall be fitted either—

(*a*) a single rear indicator and a single front indicator;

(*b*) a single rear indicator and at least one shoulder indicator; or

(*c*) at least one side indicator.

(2) A motor vehicle to which front indicators have been fitted in accordance with the preceding sub-paragraph shall in addition have fitted on each side of the vehicle at least one flank indicator, if the distance between the nearest part of the illuminated area of the front indicator and the nearest part of the illuminated area of the rear indicator on either side of the vehicle exceeds 19 feet 8 inches or if the motor vehicle is the drawing vehicle forming part of an articulated vehicle.

(3) Where one or more flank indicators are fitted on each side of a motor vehicle in accordance with the last preceding sub-paragraph, at least one shall be so fitted on that side that the distance between the foremost part of the motor vehicle which is comprised in the overall length of the vehicle and the rearmost part of the illuminated area of that indicator is not more than $\frac{1}{3}$ of the overall length of the motor vehicle or, where the motor vehicle is the drawing vehicle forming part of an articulated vehicle, not more than $\frac{1}{3}$ of the overall length of the articulated vehicle.

(4) Where in accordance with the foregoing provisions of this paragraph more than one kind of direction indicator is required to be fitted on a side of a motor vehicle, it shall be a sufficient compliance with those provisions if the vehicle is fitted on that side with either one direction indicator which satisfies or with two or more direction indicators which together satisfy the requirements of paragraph 8 of this Part of this Schedule in relation to each kind of direction indicator with which that vehicle would otherwise be required to be fitted on that side.

4.—(1) Subject to the provisions of the next sub-paragraph, in the case of a combination of a motor vehicle drawing one or more trailers and in the case of an articulated vehicle, where that motor vehicle or the motor vehicle forming part of the articulated vehicle is fitted with direction indicators in compliance with this Part of this Schedule, the rearmost trailer in that combination and the trailer forming part of that articulated vehicle shall be fitted on each side with a single rear indicator in compliance with this Part of this Schedule.

(2) No rear indicator shall be required to be fitted to a trailer which is being drawn by a motor vehicle to which are fitted direction indicators in compliance with this Part of this Schedule if—

(*a*) the trailer is a broken down motor vehicle or forms part of a broken down articulated vehicle and no vehicle apart from that motor vehicle or that articulated vehicle is being drawn;

(*b*) the trailer forms part of an articulated vehicle and was constructed before the 1st September 1965; or

(*c*) the trailer is one as respects which—

(i) its rearmost part comprised in its overall length is not more than 12 feet from the rearmost part comprised in the overall length of the motor vehicle by which it is being drawn, and

(ii) that motor vehicle is fitted with side indicators in compliance with this Part of this Schedule or with rear indicators which would comply with that Part if the inboard angle shown in diagram 5 were to be varied by the substitution of 5 degrees for 45 degrees.

5. No motor vehicle drawing a trailer, being a trailer to which is fitted on each side a rear indicator in compliance with this Part of this Schedule, need be fitted with any rear indicator under (*a*) or (*b*) of sub-paragraph (1) of paragraph 3 of this Part of this Schedule if—

(*a*) the motor vehicle forms part of an articulated vehicle; or

(*b*) the motor vehicle is owned by the Admiralty, the War Department, the Air Ministry or the Ministry of Aviation and is used for naval, military or air force purposes:

Provided that if the overall length of a motor vehicle owned and used as aforesaid exceeds 19 feet 8 inches it shall be fitted on each side with a flank indicator in compliance with this Part of this Schedule.

6.—(1) One or more additional indicators may be fitted on the side (excluding the front or rear) of any motor vehicle or trailer to which direction indicators have been fitted in accordance with the foregoing provisions of this Part of this Schedule.

(2) The requirements of paragraph 13 of this Part of this Schedule as respects the minimum total rated wattage of the bulb or bulbs illuminating any indicator shall not apply to an additional indicator.

7. Every direction indicator other than a flank indicator or an additional indicator shall be so designed and fitted to a vehicle that the minimum illuminated area showing to the front and the minimum illuminated area showing to the rear in accordance with the diagram relating to that indicator shall be—

(*a*) not less than 3½ square inches in extent in the case of either a motor vehicle the unladen weight of which does not exceed two tons or a passenger vehicle adapted to carry not more than twelve passengers, exclusive of the driver, if in either case the vehicle is not being used, except in a case of emergency, to draw a trailer other than one with less than four wheels or a four-wheeled trailer having two close-coupled wheels on each side;

(*b*) not less than 3½ square inches in extent in the case of a trailer which has less than four wheels or is a four-wheeled trailer having two close-coupled wheels on each side; and

(*c*) not less than 12 square inches in extent in any other case.

8. Every direction indicator of a kind to which a diagram in Part IV of this Schedule applies and which is fitted to a vehicle in compliance with this Part of this Schedule shall have an illuminated area of at least ¼ of a square inch visible within a reasonable distance at any point between not less than 15 degrees above and not less than 15 degrees below the horizontal throughout at least each inboard angle and at least each outboard angle (excluding any blind angle not exceeding 10 degrees) shown in the diagram relating to that kind of indicator:

Provided that in the case of any indicator fitted to a motor vehicle drawing one or more trailers the foregoing provisions of this paragraph shall be treated as being satisfied if the said illuminated area of the indicator would have been visible as aforesaid but for the presence of the trailer or trailers.

9. Every direction indicator shall be so placed that no part of its illuminated area is more than 16 inches nearer to the longitudinal axis of the vehicle than is the outermost part of the vehicle which is comprised in the overall width of the vehicle on the side on which the indicator is placed, except that in the case of a public service vehicle having combined rear and side entrances a nearside rear indicator may be so placed that no part of its illuminated area is more than 30 inches nearer to the longitudinal axis of the vehicle than the said outermost part of the vehicle.

10. No part of the illuminated area of any direction indicator fitted to either side of a vehicle shall be less than 12 inches from the longitudinal axis of the vehicle.

11.—(1) No part of the illuminated area of any direction indicator shall be at a height of more than 7 feet 6 inches above the level of the ground; except that in the case of a public service vehicle to which are fitted rear indicators in accordance with the provisions of paragraph 3 of this Part of this Schedule, if no part of the illuminated area of each of the rear indicators is at a height of more than 6 feet 6 inches above the level of the ground, then any shoulder indicator or flank indicator may be fitted to that vehicle so that no part of its illuminated area is at a height exceeding 8 feet 6 inches above the level of the ground.

(2) No part of the illuminated area of a front indicator or a rear indicator shall be below a height of 1 foot 3 inches above the level of the ground when the vehicle is unladen and no part of the illuminated area of any other indicator shall be below a height of 1 foot 8 inches above the level of the ground when the vehicle is unladen.

12. A direction indicator fitted to a vehicle in compliance with this Part of this Schedule shall be optically separated from any other lamp carried by the vehicle.

13. Save as provided in sub-paragraph (2) of paragraph 6 of this Part of this Schedule, the total rated wattage of the bulb or bulbs illuminating any direction indicator fitted to a vehicle in compliance with this Part of this Schedule shall not be less than 15 watts nor more than 36 watts and the rated wattage of each bulb shall be indelibly marked upon the glass or the metal cap thereof in a readily legible manner.

14. Any direction indicator intended to indicate a right hand turn shall be fitted only to the right of the longitudinal axis of the vehicle and one intended to indicate a left hand turn shall be fitted only to the left of that axis.

15. Where more than one direction indicator is fitted on the same side of a motor vehicle, an articulated vehicle or a combination of vehicles comprising a motor vehicle and one or more trailers they shall be so designed and fitted that the light emitted by such indicators flashes at the same time.

16. The provisions of paragraphs 7, 8, 9, 10 and 11 of Part I of this Schedule shall apply as respects direction indicators fitted in compliance with this Part of this Schedule as they apply as respects direction indicators fitted in compliance with that Part.

Diagrams applicable to Direction Indicators mentioned in Part III, paragraph 1

PART IV

Note. Positional requirements are set out in paragraphs 9, 10 and 11 of Part III.

Diagram 1. FRONT INDICATOR




Diagram 2. SHOULDER INDICATOR




Diagram 3. SIDE INDICATOR




Diagram 4. FLANK INDICATOR





Diagram 5. REAR INDICATOR



Provisions as respects direction indicators on motor vehicles registered before 1st September 1965 not fitted with electric lighting equipment

PART V

1. Subject to the provisions of the next following paragraph every direction indicator fitted to a vehicle in compliance with this Part of this Schedule shall be in the form of a hand not less than 6 inches in length, presenting a white surface visible both from the front and rear of the vehicle and shall comply with the requirements of paragraph 2 of Part I of this Schedule other than the requirements of sub-paragraph (*b*)(iii) of that paragraph.

2. Additional indicators may be fitted at the rear of a vehicle if they are in the form of a hand not less than 6 inches in length presenting a white surface visible at a reasonable distance from any point to the rear of the vehicle.

3. The provisions of paragraphs 4, 5, 8, 9, 10 and 11 of Part I of this Schedule shall apply as respects direction indicators fitted in compliance with this Part of this Schedule as they apply as respects direction indicators fitted in compliance with that Part.

Provisions as respects direction indicators on trailers drawn by certain motor vehicles registered before 1st September 1965

PART VI

1. Every direction indicator fitted to a trailer shall comply with the following provisions of this Part of this Schedule:

Provided that nothing in this Part of this Schedule shall apply to a broken down vehicle being drawn in consequence of the breakdown.

2. Every direction indicator shall either—

(*a*) when in operation be in the form of an illuminated sign of a minimum illuminated length of 6 inches and a maximum illuminated breadth not exceeding one fourth of the illuminated length, and shall show either a steady or a flashing light; or

(*b*) be such that—

(i) when in operation it shall show a flashing light,

(ii) the total rated wattage of the bulb or bulbs illuminating the indicator shall be not less than 15 watts nor more than 36 watts,

(iii) the minimum illuminated area shall be not less than 3½ square inches in extent if the trailer to which it is fitted has less than 4 wheels or is a four-wheeled trailer having two close-coupled wheels on each side and not less than 12 square inches in extent in any other case, and

(iv) the centre of the illuminated area shall be not more than 16 inches nearer to the longitudinal axis of the trailer than is the outermost part of the trailer on the same side.

3. Every direction indicator shall, when in operation, be visible at a reasonable distance from any point to the rear of the trailer:

Provided that, where two or more trailers are being drawn by the same motor vehicle, this paragraph shall apply only in relation to the rearmost trailer.

4. The provisions of paragraphs 4, 5, 6, 7, 9, 10 and 11 of Part I of this Schedule shall apply as respects direction indicators fitted in compliance with this Part of this Schedule as they apply as respects direction indicators fitted in compliance with that Part.

SCHEDULE 3 (See Regulation 30)

GAS CONTAINERS

PART I

Definitions relating to gas containers

1. In this Schedule, unless the context otherwise requires, the following expressions have the meanings hereby assigned to them respectively, that is to say,—

"gas container" means a container fitted to a motor vehicle or a trailer and intended for the storage of gaseous fuel for the purpose of the propulsion of the vehicle or the drawing vehicle as the case may be;

" gas cylinder " means a container fitted to a motor vehicle or a trailer and intended for the storage of compressed gas for the purpose of the propulsion of the vehicle or the drawing vehicle as the case may be ;

" compressed gas " means gaseous fuel under a pressure exceeding 15 lbs. per square inch above atmospheric pressure ;

" pipe line " means all pipes connecting a gas container or containers—

(*a*) to the engine or the mixing device for the supply of a mixture of gas and air to the engine ; and

(*b*) to the filling point on the vehicle ;

" pressure pipe line " means any part of a pipe line intended for the conveyance of compressed gas ; and

" reducing valve " means an apparatus which automatically reduces the pressure of the gas passing through it.

Gas containers

2. Every gas container shall—

(*a*) be securely attached to the vehicle in such manner as not to be liable to displacement or damage due to vibration or other cause ; and

(*b*) be so placed or insulated as not to be adversely affected by the heat from the exhaust system.

Pipe lines

3.—(1) Every pipe line shall be supported in such manner as to be protected from excessive vibration and strain.

(2) No part of a pipe line shall be in such a position that it may be subjected to undue heat from the exhaust system.

(3) Every pressure pipe line shall be made of steel solid drawn.

(4) The maximum unsupported length of a pressure pipe line shall not exceed 3 feet.

Unions

4.—(1) Every union shall be so constructed and fitted that it will—

(*a*) not be liable to work loose or develop leakage when in use ; and

(*b*) be readily accessible for inspection and adjustment.

(2) No union on a pressure pipe line or on a gas cylinder shall contain a joint other than a metal to metal joint.

Reducing valves

5. Every reducing valve shall be—

(*a*) so fitted as to be readily accessible ; and

(*b*) so constructed that there can be no escape of gas when the engine is not running.

Valves and cocks

6.—(1) Every valve or cock intended to be subjected to a pressure exceeding 100 lbs. per square inch shall be of forged steel or of brass or bronze complying with the specification contained in Part II of this Schedule.

(2) A valve or cock shall be fitted to the pipe line to enable the supply of gas from the container or containers to the mixing device to be shut off.

(3) (*a*) In the case of a pressure pipe line the valve or cock shall be placed between the reducing valve and the container or containers and shall be readily visible and accessible from the outside of the vehicle and a notice indicating its position and method of operation shall be affixed in a conspicuous position on the outside of the vehicle carrying the gas container or containers.

(*b*) In other cases, if the valve or cock is not so visible and accessible as aforesaid, a notice indicating its position shall be affixed in a conspicuous position on the outside of the vehicle carrying the container or containers.

Pressure gauges

7. Every pressure gauge connected to a pressure pipe line shall be so constructed as not to be liable to deterioration under the action of the particular gases employed and shall be so constructed and fitted that—

(*a*) in the event of failure of such pressure gauge no gas can escape into any part of the vehicle;

(*b*) it is not possible owing to leakage of gas into the casing of the pressure gauge for pressure to increase therein to such extent as to be liable to cause a breakage of the glass thereof; and

(*c*) in the event of failure of such pressure gauge the supply of gas thereto may be readily cut off.

Charging connections

8.—(1) Every connection for charging a gas container shall be outside the vehicle and in the case of a public service vehicle no such connection shall be within 2 feet of any entrance or exit.

(2) An efficient shut-off valve shall be fitted as near as practicable to the filling point:

Provided that in cases where compressed gas is not used a cock or an efficient non-return valve may be fitted in lieu thereof.

(3) Where compressed gas is used an additional emergency shut-off valve shall be fitted adjacent to the valve referred to in sub-paragraph (2) of this paragraph.

(4) A cap shall be fitted to the gas filling point on the vehicle and where compressed gas is used this cap shall be made of steel with a metal to metal joint.

Trailers

9.—(1) Where a trailer is used for the carriage of a gas cylinder, a reducing valve shall be fitted on the trailer.

(2) No pipe used for conveying gas from a trailer to the engine of a vehicle shall contain compressed gas.

Construction, etc., of system

10. Every part of a gas container propulsion system shall be—

(*a*) so placed or protected as not to be exposed to accidental damage and shall be soundly and properly constructed of suitable and well-finished materials capable of withstanding the loads and stresses likely to be met with in operation and shall be maintained in an efficient, safe and clean condition; and

(*b*) so designed and constructed that leakage of gas is not likely to occur under normal working conditions, whether or not the engine is running.

PART II

SPECIFICATION FOR BRASS OR BRONZE VALVES

Manufacture of valves

1. The stamping or pressing from which each valve is manufactured shall be made from bars produced by (*a*) extrusion, (*b*) rolling, (*c*) forging, (*d*) extrusion and drawing, or (*e*) rolling and drawing.

Heat treatment

2. Each stamping or pressing shall be heat treated so as to produce an equiaxed microstructure in the material.

Freedom from defects

3. All stampings or pressings and the bars from which they are made shall be free from cracks, laminations, hard spots, segregated materials and variations in composition.

Tensile test

4. Tensile tests shall be made on samples of stampings or pressings taken at random from any consignment. The result of the tensile test shall conform to the following conditions:—

Yield Stress.—Not less than 15 tons per square inch.

Ultimate Tensile Stress.—Not less than 30 tons per square inch.

Elongation on 2 inch gauge length.—Not less than 25 per cent.

Note.—When the gauge length is less than 2 inches the required elongation shall be proportionately reduced.

The fractured test piece shall be free from piping and other defects (see paragraph 3 of this Part of this Schedule).

SCHEDULE 4 (see Regulations 42, 47, 50 and 76)

REQUIREMENTS WITH RESPECT TO THE EFFICIENCY OF THE BRAKES OF CERTAIN MOTOR VEHICLES

1. This Schedule applies to a motor vehicle which is a heavy motor car, a motor car or a motor cycle and is not—

(*a*) a goods vehicle the unladen weight of which exceeds 30 hundredweight;

(*b*) a public service vehicle adapted to carry eight or more passengers;

(*c*) an articulated vehicle or a vehicle constructed or adapted for the purpose of forming part of an articulated vehicle;

(*d*) a works truck; or

(*e*) a pedestrian controlled vehicle;

and references to a motor vehicle in the following provisions of this Schedule shall be construed accordingly.

2. In this Schedule the expression "braking efficiency", in relation to the application of brakes to a motor vehicle at any time, means the maximum braking force capable of being developed by the application of those brakes, expressed as a percentage of the weight of the vehicle including any driver, passengers or load carried in the vehicle at that time.

3. For the purposes of this Schedule a two-wheeled motor cycle shall not, by reason that a sidecar is attached thereto, be treated as three-wheeled.

4. In the case of a motor vehicle having at least four wheels and required to have two means of operating brakes—

(*a*) if each means of operation applies brakes to at least four wheels, the brakes as applied by one of the means shall have a total braking efficiency of not less than 50 per cent. and the brakes as applied by the other means shall have a total braking efficiency of not less than 25 per cent.;

(*b*) if only one of the means of operation applies brakes to at least four wheels, the brakes as applied by that means shall have a total braking efficiency of not less than 50 per cent. and the brakes as applied by the other means shall have a total braking efficiency of not less than 25 per cent.; and

(*c*) if neither means of operation applies brakes to at least four wheels, the brakes as applied by one of the means shall have a total braking efficiency of not less than 30 per cent. and the brakes as applied by the other means shall have a total braking efficiency of not less than 25 per cent.

5. In the case of a three-wheeled motor vehicle required to have two means of operating brakes—

(*a*) if each means of operation applies brakes to all three wheels, the brakes as applied by one of the means shall have a total braking efficiency of not less than 40 per cent. and the brakes as applied by the other means shall have a total braking efficiency of not less than 25 per cent.;

(*b*) if only one of the means of operation applies brakes to all three wheels, the brakes as applied by that means shall have a total braking efficiency of not less than 40 per cent. and the brakes as applied by the other means shall have a total braking efficiency of not less than 25 per cent.; and

(*c*) if neither means of operation applies brakes to all three wheels, the brakes as applied by one of the means shall have a total braking efficiency of not less than 30 per cent. and the brakes as applied by the other means shall have a total braking efficiency of not less than 25 per cent.

6. In the case of a motor vehicle, being a two-wheeled motor cycle, required to have more than one means of operating brakes, the brakes as applied by one of the means shall have a total braking efficiency of not less than 30 per cent. and the brakes as applied by the other means shall have a total braking efficiency of not less than 25 per cent.

7. In the case of a motor vehicle not required to have two means of operating brakes—

(*a*) if the vehicle has at least four wheels and one or more means of operation applying brakes to at least four wheels, the brakes as applied by that means or one of those means shall have a total braking efficiency of not less than 50 per cent.;

(*b*) if the vehicle has at least four wheels and no means of operation applying brakes to at least four wheels, the brakes as applied by the means or one of the means of operation shall have a total braking efficiency of not less than 30 per cent.;

(*c*) if the vehicle is three-wheeled and has one or more means of operation applying brakes to all three wheels, the brakes as applied by that means or one of those means shall have a total braking efficiency of not less than 40 per cent.;


(*d*) if the vehicle is three-wheeled and has no means of operation applying brakes to all three wheels, the brakes as applied by the means or one of the means of operation shall have a total braking efficiency of not less than 30 per cent.; and

(*e*) if the vehicle is two-wheeled, the brakes as applied by the means or one of the means of operation shall have a total braking efficiency of not less than 30 per cent.

SCHEDULE 5

DIAGRAM OF TRAILER PLATE (See Regulation 64)

Red Reflex Lenses on White Ground



Note: The plate may be constructed without the central triangular space shown above.

SCHEDULE 6

PART I

Conditions to be complied with in relation to the use of vehicles carrying wide or long loads or vehicles carrying loads or having fixed appliances or apparatus which project (*See Regulations* 103 *and* 106)

1. The conditions referred to in Regulation 103 of these Regulations and in paragraphs (2), (4), (5), (6), (7) and (9) of Regulation 106 thereof as the conditions specified in paragraph 1 of this Schedule are as follows:—

(*a*) save in so far as the chief officer of police of any police area in which it is proposed that the vehicle or vehicles in question will be used dispenses, as respects the use of the vehicle or vehicles in that area, with any of the requirements contained in this and in the following sub-paragraph as to length of notice or particulars to be given, the owner of the vehicle or vehicles shall, before using the vehicle or, as the case may be, the vehicles on a road, give at least two clear days' notice of the intended use (excluding Sundays, any bank holiday, Christmas Day or Good Friday) to the chief officer of police of any such area as aforesaid.

In this sub-paragraph—

(i) the expression " police area " has the same meaning as in the Police Pensions Act 1921(a), and

(ii) the expression " bank holiday ", in relation to notice of the intended use of a vehicle on a road, means a day which is, or is to be observed as, a bank holiday, or a holiday, under the Bank Holidays Act 1871(b), or the Holidays Extension Act 1875(c), either generally or in the locality in which that road is situated;

(*b*) the notice referred to in the foregoing sub-paragraph shall contain particulars of the time, date and route of the journey and—

(i) in a case where this paragraph applies by virtue of paragraph (2) of Regulation 106 of these Regulations, particulars of the overall length and overall width of the vehicle by which the load is to be carried and of the width of any lateral projection or projections of its load,

(ii) in a case where this paragraph applies by virtue of paragraph (4)(*a*) of the said Regulation 106, particulars of the overall length and overall width of each vehicle by which the load is to be carried and of the length of any forward projection and of any rearward projection of the load and, where the load is to be carried by more than one vehicle, of the distance between vehicles,

(iii) in a case where this paragraph applies by virtue of the said Regulation 103 or paragraph (4)(*b*) of the said Regulation 106, particulars of the overall length of the combination of vehicles to be used and, in the second-mentioned case, particulars of the length of any forward projection and of any rearward projection of the load, being the projection or projections thereof as mentioned in the said paragraph (4)(*b*), and

(iv) in a case where this paragraph applies by virtue of paragraphs (5), (6), (7) or (9) of the said Regulation 106, particulars of the overall length of the vehicle to be used and of the length of any forward projection and of any rearward projection of its special appliance or apparatus or, as the case may be, of its load; and

(*c*) subject to any variations in the time, date or route of the journey which the owner of the vehicle or vehicles may be directed to make by any such chief officer of police as aforesaid, the vehicle or, as the case may be, the vehicles shall be used only in circumstances which accord with the particulars given in compliance with the foregoing sub-paragraph as to the time, date and route of the journey and only if any dimension or measurement relating to the vehicle or the vehicles (including that relating to a combination of vehicles), to a special appliance or apparatus or to a load, being a dimension or measurement of which particulars have been given as aforesaid, is not exceeded.

For the purposes of this sub-paragraph and of item (iv) of the foregoing sub-paragraph, the reference to a load shall, in a case where this paragraph applies by virtue of paragraph (7) of the said Regulation 106, be treated as a reference to a boat used for racing as mentioned in the said paragraph (7).

2. The conditions referred to in Regulation 103 of these Regulations and in paragraphs (4), (5), (6) and (9) of Regulation 106 thereof as the conditions specified in paragraph 2 of this Schedule are that at least one person in addition to the person or persons employed in driving the motor vehicle in question shall

(a) 11 & 12 Geo. 5. c. 31. (b) 34 & 35 Vict. c. 17. (c) 38 & 39 Vict. c. 13.

be employed in attending to that vehicle and its load and any other vehicle or vehicles drawn by that vehicle and the load or loads carried on the vehicle or vehicles so drawn and to give warning to the driver of the said motor vehicle and to any other person of any danger likely to be caused to any such other person by reason of the presence of the said vehicle or vehicles on the road.

For the purpose of this paragraph, in a case where a motor vehicle is drawing a trailer or trailers and another motor vehicle is used for the purpose of assisting in their propulsion on the road, the person or persons employed in driving that other motor vehicle shall not be treated as a person or persons employed in attending to the first-mentioned vehicle or any vehicle or vehicles drawn thereby.

3. The conditions referred to in paragraphs (5) and (6) of Regulation 106 of these Regulations as the conditions specified in paragraph 3 of this Schedule are as follows:—

(*a*) there shall be exhibited on every relevant projection such a number of plane unbroken surfaces as are required by the following provisions of this paragraph, the said surfaces to be of the size, shape and colour specified by those provisions and to be situated in accordance therewith.

In this sub-paragraph the expression "relevant projection" means any such forward or rearward projection as is mentioned in sub-paragraph (*a*) or (*c*) of the said paragraph (5) or of the said paragraph (6);

(*b*) subject to the provisions of sub-paragraph (*e*) of this paragraph, three surfaces shall be exhibited of which one (hereafter referred to as "the end projection surface") shall be of the shape and colour shown in the diagram first set out in Part II of this Schedule and shall conform with the dimensions there shown in relation to the size and colouring of that surface, and the other two, and any surface additional to those two required by the said sub-paragraph (*e*), (each hereafter referred to as a "side projection surface") shall be of the shape and colour shown in the diagram secondly set out in the said Part II and shall conform with the dimensions there shown in relation to the size and colouring of that surface;

(*c*) the end projection surface shall be exhibited so that it may be seen, in the case of a forward projection, from the front thereof or, in the case of a rearward projection, from the rear thereof and shall be situated—

(i) so that it lies, as near as practicable, in a vertical plane at right angles to the longitudinal axis of the vehicle and passing through a point not more than 2 feet from the extreme end of the projection,

(ii) so that the vertical distance between the carriageway of the road and the nearest point on the surface does not exceed 8 feet 6 inches,

(iii) so that the surface and any object or device by means of which it is exhibited impedes, as little as possible, the view of the driver to the front or, as the case may be, to the rear of the vehicle, and

(iv) so that every part of the surface is clearly visible to other persons using the road within a reasonable distance from that end of the projection from which the surface may be seen as provided by the foregoing provisions of this sub-paragraph;

(*d*) the two side projection surfaces shall be exhibited so that one may be seen from one side of the projection and the other may be seen from the other side thereof and each surface shall be situated—

(i) so that it lies, as near as practicable, in a vertical plane parallel to the longitudinal axis of the vehicle,

(ii) so that no part of it extends beyond the end of the projection,

(iii) so that the horizontal distance between it and the end projection surface does not exceed 3 feet,

(iv) so that the vertical distance between the carriageway of the road and any point on at least one side of the surface does not exceed 8 feet 6 inches, and

(v) so that every part of the surface is clearly visible to other persons using the road within a reasonable distance from that side of the projection from which the surface may be seen as provided by the foregoing provisions of this sub-paragraph ;

(*e*) in the case of a forward projection exceeding 15 feet in length or a rearward projection exceeding 17 feet in length such a number of side projection surfaces additional to the two side projection surfaces required by sub-paragraph (*b*) of this paragraph shall be exhibited on each side of the projection as to ensure that the horizontal distance between the foremost or, as the case may be, the rearmost point of the vehicle and that part of any side projection surface exhibited on the same side nearest that point, or between the nearest points of adjacent side projection surfaces exhibited on the same side, does not exceed, in the case of such surfaces exhibited on a forward projection, 8 feet or, in the case of such surfaces exhibited on a rearward projection, 12 feet.

For the purposes of this sub-paragraph the expression "the vehicle" shall not include any special appliance or apparatus or any part thereof which is a forward projection or a rearward projection within the meaning of Regulation 105 of these Regulations ;

(*f*) the provisions of items (i), (iv) and (v) of sub-paragraph (*d*) of this paragraph shall apply in relation to the additional side projection surfaces exhibited in accordance with the foregoing sub-paragraph as they apply in relation to the side projection surfaces referred to in the said sub-paragraph (*d*) ; and

(*g*) every surface exhibited in compliance with the foregoing provisions of this paragraph shall be kept clean and unobscured and during the hours of darkness shall be illuminated by means of lamps sufficient to render the surface readily distinguishable from a reasonable distance and so shielded that only light reflected from the surface is visible to other persons using the road.

4. The condition referred to in paragraphs (5), (6), (7) and (8) of Regulation 106 of these Regulations as the condition specified in paragraph 4 of this Schedule is that steps shall have been taken to render the relevant projection clearly visible to other persons using the road within a reasonable distance, in the case of a forward projection, from the front thereof or, in the case of a rearward projection, from the rear thereof and, in either case, from either side thereof.

In this paragraph the expression "relevant projection" means any such forward or rearward projection as is mentioned in sub-paragraph (*b*) of the said paragraph (5) or of the said paragraph (6) or in the said paragraph (7) or the said paragraph (8).

PART II

Projection markers (See paragraph 3(b) of this Schedule)

Diagram of end projection surface





Diagram of side projection surface



EXPLANATORY NOTE

(This Note is not part of the Regulations, but is intended to indicate their general purport.)

These Regulations consolidate with amendment the Motor Vehicles (Construction and Use) Regulations 1955 and the amending Regulations set out in Schedule 1 to these Regulations. The principal changes are those making provision as follows :—

1. Vehicles constructed for use and used solely as road sweepers, if they comply with certain conditions, are exempted from the requirements as to the springs with which vehicles must be equipped (Regulation 10(*i*));

2. Subject to certain exceptions, vehicles are required to be fitted with a speedometer instead of a speed indicator (Regulation 13);

3. Vehicles equipped with an excess fuel device designed to facilitate the starting of the engine by causing it to be supplied with excess fuel need not have the device fitted so that it cannot readily be operated by a person on the vehicle if the device does not cause any increase in the smoke or visible vapour emitted from the vehicle (proviso (ii) to Regulation 23(2));

4. Under Regulation 28 and Part III of Schedule 2 new provisions are introduced as respects direction indicators on motor vehicles and trailers. Motor vehicles first registered as from the 1st September 1965 and fitted with direction indicators must as respect those indicators comply with Part III of Schedule 2 (Regulation 28(3)). Motor vehicles registered before that date and fitted with direction indicators may comply with either such of the existing provisions relating to indicators reproduced in Part I, Part II or Part V of Schedule 2 as are applicable or with Part III (Regulation 28(1)).

   Trailers, drawn by motor vehicles which have been first registered whether before or after the 1st September 1965 and which are fitted with direction indicators complying with Part III, must also be fitted with indicators in accordance with that Part (Regulation 28(3)). In general, other trailers fitted with direction indicators may comply either with Part III or with the existing provisions reproduced in Part VI of Schedule 2 (Regulation 28(2)).

   The principal new requirements contained in Part III are as follows :—

   (1) All direction indicators must show a flashing amber light and be optically separated from other lamps (paragraphs 2 and 12);

   (2) A minimum number of indicators is required to be fitted on each side of a motor vehicle (paragraphs 3 and 5);

   (3) At least a ¼ square inch of the illuminated area of each indicator required to be fitted must be visible through prescribed minimum angles in the horizontal and vertical planes (paragraph 8);

   (4) All indicators on the same side of a motor vehicle or of a combination of vehicles must flash at the same time (paragraph 15).

Part IV of Schedule 2 sets out diagrams applicable to the main kinds of indicators mentioned in Part III ;

5. Passengers in a vehicle must be carried in such a manner that danger is not caused or likely to be caused to any person in the vehicle or on the road (Regulation 73) :

6. The opening of any door of a vehicle so as to cause injury or danger is prohibited (Regulation 93).